



HERB: A Home Exploring Robotic Butler

Siddhartha Srinivasa, Dave Ferguson, Casey Helfrich, Dmitry Berenson, Alvaro Collet, Rosen Diankov, Garratt Gallagher, Geoffrey Hollinger, James Kuffner, Michael Vande Weghe

Presentation by Elaine Short











- Motivation
- System Description
- Localization and Mapping
- Object Recognition and Pose Estimation
- Planning
- Demos
- Lessons Learned





Motivation

- System Description
- Localization and Mapping
- Object Recognition and Pose Estimation
- Planning
- Demos
- Lessons Learned





- Segway mobile base
- Barrett WAM arm
- 2 low-power computers
- Sensors
 - planar laser (on Segway)
 - 2 cameras on shoulder
 - camera on arm









 Minimal human input to sensing and planning





- Motivation
- System Description

• Localization and Mapping

- Object Recognition and Pose Estimation
- Planning
- Demos
- Lessons Learned



- 2 collocated maps:
 - Planar occupancy grid (full lab space)
 - 3D model of regions for manipulation (kitchen area)
- 2 localization modes
 - coarse: adaptive Monte Carlo localization
 - fine: vision-based localization

USC Viterbi School of Engineering Localization

- Checkerboard localization
 - area plastered with checkerboards
 - weird!!
 - take away checkerboards and sacrifice some accuracy for more natural environment







- Generalized Approach to Tracking Movable Objects (GATMO)
 - 2 parts:
 - Static map (background)
 - List of objects and positions
 - Keep track of the status of all objects and object types as they move.











- Motivation
- System Description
- Localization and Mapping
- Object Recognition and Pose Estimation
- Planning
- Demos
- Lessons Learned



Object Classification

- Objects are placed into a hierarchy
 - 2 meta-objects: "person" and "chair"
 - person: objects that actively move
 - chair: objects that rarely move
- GATMO and localizer work together to identify the robot location; this usually works well, but not always.



Object Recognition

• Goal: to detect textured free-formed objects in clutter against arbitrary backgrounds.



- Create an object model from natural features
 - Use SIFT with Best Bin First algorithm, and structure from motion to get a sparse 3D model.
 - "... proper alignment and scale for each model are optimized to match the real object dimensions."







- 1. Cluster SIFT features' 2D locations p using Mean Shift algorithm. Each cluster contains a subset of points p^k .
- 2. For each cluster of points p^k , choose a subset of *n* points and estimate a hypothesis with the best pose according to those points. If the amount of points consistent with the hypothesis is higher than a threshold ϵ , create a new object instance and refine the estimated pose using all consistent points in the optimization. Keep repeating this procedure until the amount of unallocated points is lower than a threshold, or the maximum number of iterations has been exceeded.
- 3. Merge all instances from different clusters whose estimated pose is similar. Those instances with the most consistent points survive.



Object

Recognition/Pose Estimation

- Accuracy:
 - Average translation error: 0.67cm
 - Average in-plane rotation error: 1.23 degrees
 - Average out-of-plane rotation error: 3.81 degrees
 - 91% success rate at grasping objects and lifting them 5cm off the table
- Speed
 - Average: 4fps
 - Variation: 1fps with 12 objects, 6fps with 1-2 objects.





- Motivation
- System Description
- Localization and Mapping
- Object Recognition and Pose Estimation
- Planning
- Demos
- Lessons Learned





- Input:
 - description of the robot
 - description of the parts of the environment with which the robot should not collide
 - kinematics of the environment
 - object IDs (most, automatically generated; some (doors), manually inputted)





- Output:
 - Kinematically feasible path for the robot
 - -OR- Failure, if no path found within time limit
- Features:
 - Generality
 - No physics
 - Work under uncertainty



Planning for Manipulation



- 3 configuration spaces: for robot, end-effector, and target object, each with a distance metric.
- Relax the task by giving each target a task frame rigidly attached to it, and grasps represented in that task frame
- Have a transform Tp relating the object configuration to the world reference frame. (allows grasps to be computed offline)
- Assume that the end-effector is within the set of grasps in relation to the task frame.
- This couples the motion of the object and robot, so we plan in a combined configuration space.
- Use Randomized A*





- Use of caging grasps can improve the feasibility region by 500%
- Extension to other kinds of grasps allows behavior such as opening doors by pulling then pushing.
- Qualitative analysis suggests that doors are particularly difficult; disregarding physics can result in failure.



- Introduce Workspace Goal Regions (WGRs), to allow goals located in the six-dimensional workspace of the end effector.
- These can be integrated into sampling-based planners, sampling both the goal space and the configuration space to improve efficiency.



- For many tasks, there will be constraints on the feasible movements for the robot (e.g. lifting a pitcher without spilling).
- Introduce Constraining BiDirectional Rapidly-exploring Random Tree (CBiRRT).



• HERB's strength: Fast, feasible manipulation planning in highly cluttered environments.





- Motivation
- System Description
- Localization and Mapping
- Object Recognition and Pose Estimation
- Planning
- Demos
- Lessons Learned



• <u>http://www.youtube.com/user/herbmugface</u>





- Motivation
- System Description
- Localization and Mapping
- Object Recognition and Pose Estimation
- Planning
- Demos
- Lessons Learned



- Failure modes:
 - Inaccuracy in robot joints
 - Robot localization errors
 - Segway positioning inaccuracy
- Not repeating errors is important for a live audience.
- Making sense of unexpected collisions is hard.





HERB for Discovery Channel Canada April 2, 2008

Personal Robotics Intel Labs Pittsburgh





