

# An Iterative Mixed Integer Linear Programming Approach to Pursuit Evasion Problems in Polygonal Environments

Max Pflueger  
Feb. 9, 2011

Paper by: Johan Thunberg and Petter  
Ogren

# Mixed Integer Linear Programming

- Linear Programming: optimize a linear equation subject to linear inequality constraints
  - parameters are continuous real values
- Mixed Integer Variant
  - some parameters may be integers
  - generally NP Hard
  - lots of standard tools are available
    - paper uses ILOG CPLEX 10.2

# Polygonal Environment




Fig. 3. The neighborhood that can be moved to,  $M_1$  (a) and the neighborhood that can be seen,  $N_1$  (b), from area  $F_1$ .

# Pursuit-Evasion

- Goal: Guarantee detection of an evader in the environment
  - evader is arbitrarily fast
- N Pursuers
- Free space  $F$ , composed of polygons  $F_i$
- $M_i$ : set of polygons that can be moved to from  $i$
- $N_i$ : set of polygons that can be seen from  $i$

# Pursuit-Evasion as MILP

*Problem 2 (MILP):* Given a  $T \in \mathbb{Z}^+$  solve the following integer linear program.

$$\max Z = \alpha \sum_{i \in J} \theta_{iT} + (1 - \alpha) \sum_{i \in J} \sigma_{iT} \quad (1)$$

subject to

$$\sum_{j \in N_i} \lambda_{jt} - \sigma_{it} \geq 0, \quad (2)$$

$$\sigma_{it} - \lambda_{jt} \geq 0 \quad \forall j \in N_i \quad (3)$$

$$\sum_{i \in J} \lambda_{it} - N = 0 \quad (4)$$

$$\sum_{j \in M_i} \lambda_{jt} - \lambda_{i(t-1)} \geq 0 \quad (5)$$

$$N - (N - 1)\lambda_{it} - \sum_{j \in M_i} \lambda_{jt} \geq 0 \quad (6)$$

$$2 - \sum_{j \in M_i} \lambda_{j(t-1)} - \lambda_{it} \geq 0 \quad (7)$$

$$2 - \sum_{j \in M_i} \lambda_{jt} \geq 0 \quad (8)$$

$$\sigma_{jt} + \theta_{jt} - \theta_{it} \geq 0, \quad \forall j \in M_i - \{i\}, (9)$$

$$\sigma_{i(t-1)} + \theta_{i(t-1)} - \theta_{it} \geq 0, \quad (10)$$

$$1 - \sigma_{it} - \theta_{it} \geq 0, \quad (11)$$

$$\theta_{i1} = 0, \quad (12)$$

# Receding Horizon Control

- solve with relatively short  $T$ 
  - if solved stop
  - if no progress, increase  $T$  (or  $N$ ) and repeat
- set terminal conditions to initial conditions and repeat

# Integer constraint relaxation

- relax the integer constraint on sigma and theta
  - running time is about 2x faster
  - both problem formulations have the same optimal solution

# Weaknesses

- No performance guarantees (particularly with the receding horizon)
- Linear programming constraints mean pursuers can never be adjacent or move to a cell that is also within movement range of another pursuer (constraints 6,7,8)



# Experiments




Fig. 6. The results of running the algorithm on a manhattan grid with four obstacles. The partition is shown in Figure 5, and the search problem is solved with 2 pursuers in three iterations where the results of iteration 1, 2 and 3 are shown in (a), (b) and (c) respectively. Note that 4 time steps were necessary in iteration 3, the result of the third iteration with 3 time steps is showed in (d). White regions are in state  $S_1$  and  $S_2$ , blue regions are in state  $S_3$ , whereas red regions are in state  $S_4$ .




Fig. 8. The results of running the algorithm on the environment in Figure 7. The search problem is solved with 3 pursuers in four iterations where the results of iteration 1, 2, 3 and 4 are shown in (a), (b), (c) and (d) respectively. After iteration 3, no improvement is achieved with 2 pursuers, thus one more pursuer is added in iteration 4. The number of time steps was also increased. White regions are in state  $S_1$  and  $S_2$ , blue regions are in state  $S_3$ , whereas red regions are in state  $S_4$ .