

A Formal Analysis and Taxonomy of Task Allocation in Multi-Robot Systems  
(B.Gerkey & M. Mataric)

Presented by Elaine.

Multi-Robot Task Allocation (MRTA). One of the first to look at MRTA formally.

Utility, Quality and Cost:

Utility - Maximizing Quality and Minimizing Cost

Framework being used to analyze the problem is Combinatorial Optimization.

Sets/Subset System (E,F).

Find a subset that maximizes Utility

Greedy Algorithm provides the optimal solution iff (E,F) is a matroid.

Single Task vs. Multi-Task, Single-Robot Tasks vs. Multi-robot tasks, Instantaneous Assignment (IA) vs. Time-extended Assignment (TA)

### **ST-SR-IA**

An Instance of the Optimal Assignment Problem

\* Centralized Hungarian method:  $O(mn^2)$

\* Distributed Auction Algorithm

### **Iterated Assignment**

Variant of ST-SR-IA; info coming in, need to reassign robots to tasks

Greedy algorithm, not a matroid; this is 2-competitive

Uses BLE( Broadcast Local Eligibility)

### **Online Assignment**

Murdoch Algorithm. Is 3-competitive. Is iterated ST-SR-IA, except robots already assigned cannot be reassigned. Best online assignment algorithm can do given information.

### **ST-SR-TA**

Time-extended model of robot assignments to minimize total cost.

NP-hard

Approximation Algorithm

\* Optimally solve initial  $m \times n$  assignment problem

\* Use Greedy to assign the remaining tasks in an online fashion as robots become available

Algorithm is 3-competitive.

### **ST-MR-IA**

Analogous to Set-Partitioning Problem  
Coalitions

### **ST-MR-TA**

Need to consider all schedules for all coalitions  
Instance of mutliprocessor scheduling problem  
Problem is strongly NP-hard

### **MT-SR-IA and MT-SR-TA**

Current robots are actuator-poor  
Directly analogous to ST-MR-IA and ST-MR-TA

### **MT-MR-IA**

Can be recast as an instance of set-cover. Strongly NP-hard.  
Useful if potential coalitions are limited.

### **MT-MR-TA**

Contains the strongly NP-hard problem.

Auction algorithms work well because they are known to be good at solving Optimizations.

## **Sequential Incremental-Value Auctions (Xiaoming Zheng and Sven Koenig)**

In Gerkey's terminology (**ST-SR-IA**)

Multi-robot routing

Number of robots, targets and want to visit all targets using our robots.

Previous algorithms use an auction method.

Intuition:

- \* Auctioneer releases the set of unassigned targets to the robots.
- \* Each robot calculates the cost for it to get to each target (given the previous targets it was assigned), submits that as a bid.
- \* The lowest-bid cost term wins bid.

### **SSI Auction algorithm.**

#### **SIV Auctions.**

- add another loop of rounds with an increasing bound  $b$ .
- Auctioneer releases the list of unassigned targets, bound.
- Eligible robots bid.
- Bid the number of targets the robot can reach in the bound.

## **Analysis**

Robots need to approximate the number of targets they can reach within the bound. Like a Hamiltonian path problem so its NP-hard.

Assume that we are doing this using an  $1/\alpha$  approximation. Similar to alpha-competitive

Discussion of Proofs. Mostly stated the theorems and corollaries. Proofs are in paper.

Nearest-neighbor algorithm will run fast, and is a good approximation

Constant-factor approximations for rooted k-MSTs are slow

Seems to be useful for multi-robot problems with many robots and fewer tasks. Nano-robot swarm?

## **Related Work:**

Tony Stentz's group also works on this.

Nidhi Kalra also worked on this.

Rob Zlot's work on auction.

-----

## **Data Gathering Tours for Mobile Robots**

Deepak Bhaduria and Volkan Isler

Presented by: Aninoy Mahapatra

**Motivation:** Consider the TSP

Wireless Sensor Networks

Authors are proposing Data-muling.

Planning routes for robotic mules, given N sensor locations, K-robots and need to compute routes of robots so that the time to download data from all sensors is minimized.

Resembles TSP but is not the same.

a) Time taken by a robot to download from a set of sources might be much more than that to travel to a given location.

b) using k-robots is different from a TSP

c) Non-zero communication range. no k-TSPN algorithms exist.

Previous work. differentiate themselves from other similar work.

Formal definition.

n sensors, base station B, k robots

Coverage of a sensor

## Assumptions

- Identical sensors, robots
- Communication range: disk of radius  $T_r$
- Download time:  $T_d$
- Constant speed  $v$
- Infinite buffer

## 1d DGP - 1d Data Gathering Problem

Prove by contradiction that there exists an optimal solution to cover  $n$  sensors with  $k$  robots in which every pair of robots is non-overlapping.

Solve using Dynamic programming to solve the 1d version.

Complexity  $O(n^2 k)$

## 2d DGP

TSP Neighborhood Tour (TSPN)

MIS

TSP tour from arbitrary disk

TSP k-SplitTour Algorithm

Split Tour based on cost threshold

## Algorithm for DGP in 2d

Combines the TSPN and TSP k-SplitTour Algorithms. Discussed in paper.

Algorithm for DGP in 2d Proof.

$$T_k/T^*_k < e^{2-1/k}$$

We discuss theorems from paper where a theoretical approximation for the algorithm is given.

Sparse Sensor Networks.

The one way TSPN tour algorithm

\* TSP tour twice as expensive.

\* Condition for sparsity is:  $T_r \leq C_l/4m$

## Experiments:

1. 600x600 environment with 100 sensors uniformly distributed.  $T_r$  chosen as 30.

2&3. Equal regions of 200x300. 100 sensor uniformly and randomly distributed. Compare between TSPN and Area-based partitioning. Report Histograms. TSPN does much better on random distributions.

