

Data Fusion (Christian)

Data fusion scenarios:

1. Centralized computers
2. Decentralized scenario (of interest)

Structure

Sensor gives input (measurements) to nodes.

Input from UI (making observations, see someone in the room)

Other nodes (interconnected nodes, tree structure, other structures also possible e.g. Star)

Sequence

Sensor gets measurement, computes likelihood of pose.

Likelihood sent to main node (treated as anonymous sender), combines all likelihoods (fuse likelihood).

Yellow color indicates all likelihoods gathered.

Decentralization

E.g. three robots going into building

No central hub where all robots send information and get replies (fails if one robot fails, others are affected).

Not one central computer

(if routing computer fails, entire network goes down)

Advantages:-

1. Scalability: all nodes are independent of the network structure.
2. Robustness
3. Modularity

Implemented this paper (not just theoretical)

Node Structure

Local filter

Channel filter: manages information flow between different nodes, filters out information that two nodes have in common.

Topology manager (in this paper they use tree structure, helps in message passing between robots)

Cycles avoided in their structure, don't need global topology information, undirected graphs.

Local Filter

Get the belief state of pose

Extract features out of those belief states

Prediction step (might be to make sure that all nodes are synced up, predicts m time steps ahead, $P(X_k | X_{k-m})$)

IF vs. KF

Diff. between them is that in IF, invert matrices to get canonical form of Gaussian)

Prediction step: $O(n^{2.4})$ vs. $O(n^2)$

Vice versa for measurement update

Control

Two types:

1. coordinated control: decides next move based on local observation
2. Cooperative control through negotiation: all robots have the same information, so they negotiate collectively which robot should go where for the next move.

Discussion about information sharing, coupling, how the different terms mean different things, etc.

Experiments

Don't compare different methods, graphs show that their method makes belief space much better).

They do implement at system level and it's very cool (fighter jets, autonomous vehicles, etc, find link to video)

Info Theoretic Control of Sensor Platforms

Presented by max

Optimal control using single agent.

1 robot, moves with constant velocity.

Sensor detects direction to its target.

Problem is formulated into matrix form minimize determinant of error covariance matrix.

Sensor platform trajectory

Moves laterally (bearings only sensor, with Gaussian error on sensor).

Tweaking the time horizon effect.

Care about the information gain only towards the end of the path.

Algorithm optimizes the info at the end.

Effect of prior information.

Based on the type of prior belief, the robot veers to the side very quickly in its path or very late, towards the end of the path.

Multi robot, multi sensor

Local utility and global utility concept.

Optimizing global utility

Case:

1. no coupling: cooperation not reqd. locally optimal action is also globally optimal
2. coupling: partial derivative of the coupled utility wrt to all the actions. Agents have local knowledge, and try to optimize it based on global stuff
3. full cooperation: coupled utility partial derivative is non zero and

Experiments

Two robots, const velocity, action u , sets bearing relative to location of feature, range only sensors, noise with known standard deviation, problem changes and falls into diff boxes on the flowchart, based on thresholds on vales of matrix Y .

Zone 1, zone 2 and zone 3 based on Y values.

7 cases explained in PDF, action space for both the robots plotted as contours and max and min plotted.