

1 Recursive-Greedy

1.1 Problem

- Find a path \mathbf{P} from a node s to a node t
- Have a path length budget B
- Want to maximize a monotonically increasing submodular function $f(P)$
- Assume:
 - Asymmetric triangle inequality
 - $f(P)$ evaluates to integer rewards

1.2 Algorithm

Algorithm: $\text{RG}(s, t, B, X, i)$

1. If $(\ell(s, t) > B)$ return **Infeasible**
2. $P \leftarrow s, t$
3. Base case: $i = 0$. return P
4. $m \leftarrow f_X(P)$
5. For each $v \in V$ do
 - (a) For $1 \leq B_1 \leq B$ do
 - i. $P_1 \leftarrow \text{RG}(s, v, B_1, X, i - 1)$
 - ii. $P_2 \leftarrow \text{RG}(v, t, B - B_1, X \cup V(P_1), i - 1)$
 - iii. If $(f_X(P_1 \cdot P_2) > m)$
 - $P \leftarrow P_1 \cdot P_2$
 - $m \leftarrow f_X(P)$
6. return P

- Approximation guarantee: $1 + \log k$
- Running time: $(2nB)^{\log k}$

1.3 RG-QP Algorithm

Algorithm: $\text{RG-QP}(s, t, B, X, i)$

1. If $(\ell(s, t) > B)$ return **Infeasible**
2. $P \leftarrow s, t$
3. Base case: $i = 0$. return P
4. $m \leftarrow f_X(P)$
5. For each $v \in V$ do
 - (a) For $1 \leq a \leq A$ do
 - i. $B_1 \leftarrow \min_b(\text{RG-QP}(s, v, b, X, i - 1) \geq a)$
 - ii. If $B_1 = \infty$, continue
 - iii. $P_1 \leftarrow \text{RG-QP}(s, v, B_1, X, i - 1)$
 - iv. $P_2 \leftarrow \text{RG-QP}(v, t, B - B_1, X \cup V(P_1), i - 1)$
 - v. If $(f_X(P_1 \cdot P_2) > m)$
 $P \leftarrow P_1 \cdot P_2$
 $m \leftarrow f_X(P)$
6. return P

- Where A is the maximum value of $f(P)$

1.4 Variants

- Can have time windows during which you are allowed to visit each node

2 Efficient Informative Sensing Using Multiple Robots

2.1 Informative Path Planning

Want to choose a path along which to sample that gives gives you the most “information” - often modeled as the reduction in entropy.

- Mutual Information - reduction in entropy for a set of random variables after getting measurements for another set of variable
- Mutual information is “Submodular”; it gives diminishing returns

2.2 Algorithm

- Uses Chekuri & Pal’s recursive-greedy algorithm
- For multiple robots, does “sequential allocation”. Plans a path for the first robot, adds those measurements to the pilot data, and then sequentially plans the path for the next robot.

2.3 Spatial Decomposition

SD-MIPP: Spatially decomposed multi-robot informative path planning.

- Split the area of interest up into large cells
- Use recursive greedy to plan a path over the cells
- Within each cell, use greedy subset selection to choose which locations to sample
- Connect up paths within each cell into one big path

3 Efficient Search

- Motivation: People in a burning building, want to send robots in to search for them
- Non-adversarial search: Have a rough model of how the target moves, want to maximize **average case** performance
- Multi-robot search is hard because the complexity scales exponentially with the number of robots.

3.1 Implicit Coordination

Each robot plans only its own path. It shares this path with other searchers, who can then plan knowledge of this path.

- Assume known environment, some localization, communication between robots.
- Represent environment by a discrete graph in which each node represents a convex region.

3.2 Reward

$$F_Y(A) = \gamma^t$$

- γ is the discount factor between 0 and 1
- Y is the target path
- t is the time til capture
- A is the set of sercher paths
- We don't actually know the target path, so we take the expectation over all possible target paths, using a distribution over the target's motion.

3.3 Algorithm

- Plan path for each robot over a finite horizon
- Plan paths for multiple robots using sequential allocation.