Rapidly-Exploring Random Trees and Motion Strategy Algorithms



Steven M. LaValle
Department of Computer Science
Iowa State University
Ames, IA 50011 USA
http://janowiec.cs.iastate.edu/∼lavalle

Acknowledgments

Collaborators:

- James Kuffner (University of Tokyo)
- Jeff Yakey
- Libo Yang

Funding:

- National Science Foundation (CAREER)
- Iowa State University (SPRIG)



Robotics



Virtual Prototyping

Virtual Humans



Computational Chemistry

Holonomic Path Planning

"Moving Pianos"







Holonomic Path Planning

"Moving Pianos"

GIVEN: $\mathcal{A}$ (robot), $\mathcal{C}$ (C-space), $f_i(q) \leq 0$ (obstacles), ...

FIND: Continuous path, τ, that satisfies $f_i(q)$ constraints

Stages of research:

1. IDENTIFICATION (1969-1982)

   Experimental mobile robotics, manipulators, etc.

2. HARDNESS (1979-1987)

   PSPACE-hardness

3. EXACT SOLUTIONS (1983-1987)

   Cylindrical algebraic decomposition, stratifications

4. PRACTICAL SOLUTIONS (1987-PRESENT)

   Randomized potential fields, probabilistic roadmaps

5. EXPLOSION OF APPLICATIONS (1994-PRESENT)

   Robotics, virtual prototyping, chemistry, architecture

Nonholonomic Path Planning

"Driving Cars"







Nonholonomic Path Planning

"Driving Cars"

ALSO GIVEN: $g_i(q, \dot{q}) \leq 0$, $g_i(q, \dot{q}) = 0$, ...

FIND: τ that satisfies $f_i(q)$, $g_i(q, \dot{q})$ constraints

Laumond, 1987; Murray, Sastry, 1990; Samson, 1990; Lafferierre, Sussman, 1990; Li, Canny, 1990; Jacobs, Rege, Laumond, 1991; Lafferriere, Sussmann, 1991; Mirtich, Canny, 1992; Boissonat, Cerezo, Leblond, 1992; Barraquand, Latombe, 1993; Murray, Sastry, 1993; Bui, Soueres, Boissonnat, Laumond, 1994; Bushnell, Tilbury, Sastry, 1995; Lynch, Mason, 1995; Soueres, Laumond, 1996; Ferbach, 1996; Lamiraux, Laumond, 1997; Sekhavat, Svestka, Laumond, Overmars, 1997; Venditelli, Laumond, 1997; Scheuer, Laugier, 1998; Duleba, 1998; Shkel, Lumelsky, 1998

- Cars, wheeled systems, pushing, rolling, hopping
- Control Lie Algebra
- The steering problem

Kinodynamic Planning

"Thrusting a Spacecraft"



Kinodynamic Planning

"Thrusting a Spacecraft"

ALSO GIVEN: $h_i(q, \dot{q}, \ddot{q}) \leq 0$, $h_i(q, \dot{q}, \ddot{q}) = 0$, ...

FIND: τ that satisfies $f_i(q)$, $g_i(q, \dot{q})$, $h_i(q, \dot{q}, \ddot{q})$

Canny, Donald, Reif, Xavier, 1988; Donald, Xavier, 1990; Canny, Rege, Reif, 1990; Fraichard, 1993; Donald, Xavier, Canny, Reif, 1993; Donald, Xavier, 1995; Connolly, Grupen, Souccar, 1995; Reif, Wang, 1997; Cherif, 1997; Lynch, 1998

Planning occurs directly in the state or phase space (tangent bundle of $\mathcal{C}$)

- Point mass, decoupled dynamics
- Approximately-optimal safe trajectories

State of the Art



Our goal is to develop practical algorithms for general nonholonomic and kinodynamic problems, hopefully leading to an explosion of applications.

Considering Dynamics Directly



State Space Formulation:

- $x = [q_1 \;\; q_2 \;\; \cdots \;\; q_n \;\; \frac{dq_1}{dt} \;\; \frac{dq_2}{dt} \;\; \cdots \;\; \frac{dq_n}{dt}]$
- n-D C-space becomes $2n$-D state space.
- $h_i(q, \dot{q}, \ddot{q}) = 0$ becomes $H_i(x, \dot{x}) = 0$

The Motion Strategy Problem



$\mathcal{W}$	$\rightarrow$	$\mathcal{C}$	$\rightarrow$	X	$\rightarrow$	$\mathcal{I}$
World or Workspace		Configuration Space		State Space		Information Space

Problem Formulation

State Space

$X = T(\mathcal{C})$, or $X = \mathcal{C}$, etc. $\quad (x = [q \ \ \dot{q}]$, or $x = q$, etc.)

Metric

$\rho : X \times X \rightarrow [0, \infty)$

State Transition Equation

$\dot{x} = f(x, u) \quad$ (solve h_i for $\dot{x}$; u is an input)

Initial and Goal Conditions

$x_{init} \in X$ and $X_{goal} \subset X$ or $x_{goal} \in X$

Collision Detection

Given $x \in X$, determine whether $x \in X_{obs}$

Incremental Simulator

$x(t + \Delta t) \approx x(t) + \Delta t \ f(x(t), u(t)) \quad$ (or Runge-Kutta)

A Randomized Approach is Needed

"Incomplete, but efficient and practical"

Existing approaches (for holonomic planning):

Randomized Potential Field

(e.g., Barraquand, Latombe, 1989)



- Artificial potential function
- Randomized gradient descent
- Random walks and backtracking

Probabilistic Roadmap

(e.g., Kavraki, Latombe, Overmars, Svestka, 1996)



- Uniform sampling of $\mathcal{C}_{free}$
- Local planner attempts connections
- Biased sampling

Adapting Existing Techniques?

Randomized potential field:

PLUS:	Gradient descent natural for incremental simulation
MINUS:	Difficult heuristics and local minima

Probabilistic roadmaps:

PLUS:	Uniform exploration
	Can be analyzed
MINUS:	Connection implies steering ability

Forward search method: (Barraquand, Latombe, 1993)

PLUS:	General nonholonomic planner
MINUS:	Limited to 3 or 4 dimensions (grid based)

A New Randomized Technique

Rapidly-exploring Random Trees (RRTs):

PLUS:	Little or no heuristics
	Steering ability not required
	Suited for high dimensions
MINUS:	Completeness sacrificed
	Metric issues

An RRT is a search tree:

- grown from an initial state
- expanded by performing incremental motions

A simple model

Bounded speed, planar motion

State Space

X is a convex, bounded subset of $\Re^2$

Denote $x \in X$ by (x_1, x_2)

Metric

$$\rho(x, x') = \sqrt{(x_1 - x_1')^2 + (x_2 - x_2')^2}$$

State Transition Equation

$$\dot{x}_1 = u_1 \cos u_2$$

$$\dot{x}_2 = u_1 \sin u_2$$

$u_1 \in [0, s]$ (s is a fixed, maximum speed)

$u_2 \in [0, 2\pi)$ (direction of motion)

Incremental Simulator

$$x_1(t + \Delta t) = x_1(t) + \Delta t \, u_1 \cos u_2$$

$$x_2(t + \Delta t) = x_2(t) + \Delta t \, u_1 \sin u_2$$

A Naive Random Tree

1. Pick a vertex at random
2. Move in a random direction to generate a new vertex
3. Repeat...



A Rapidly-Exploring Random Tree (RRT)



The RRT Construction Algorithm

```
GENERATE_RRT(x_init, K, Δt)
    T.init(x_init);
    for k = 1 to K do
        x_rand ← RANDOM_STATE();
        x_near ← NEAREST_NEIGHBOR(x_rand, T);
        u ← SELECT_INPUT(x_rand, x_near);
        x_new ← NEW_STATE(x_near, u, Δt);
        T.add_vertex(x_new);
        T.add_edge(x_near, x_new, u);
    Return T
```

The result is a tree, $\mathcal{T}$, rooted at x_{init}.



A Holonomic RRT in a Convex Region



Voronoi Interpretation



Rapidly-Exploring Property





The Limiting Distribution of RRT Vertices

Theoretical Limit

Eventually, the vertices of $\mathcal{T}$ will become uniformly distributed

If the random samples are sampled from a smooth p.d.f. $p(x)$, then the vertices of $\mathcal{T}$ will become distributed as $p(x)$

Experimental Validation with χ^2 Tests

For k degrees of freedom:

$$error = \sum_{i}^{k} \frac{(n_i - E[n_i])^2}{E[n_i]}$$



OPEN PROBLEM: Rate of convergence

OPEN PROBLEM: Relationship to optimal paths

RRT Advantages

Desirable Properties:

- Suited for high degrees of freedom
- Steering ability is not required
- Exploration biased toward unexplored free space
- Probabilistic completeness and uniform coverage
- Simplicity (few parameters or biases)
- Connected structure using minimal edges

Exploits Existing Algorithms:

- Incremental collision detection (Mirtich, 1997)
- Incremental dynamical simulation (Kuffner, Mirtich, 1998)
- Efficient nearest neighbors (Arya, Mount, 1997)

A Key Problem:

- Performance depends on metric

The Ideal (Pseudo)Metric

Cost:

$$L = \int_0^T l(x(t), u(t))dt + l_f(x(T))$$

Optimal cost to go from x to x':

$$\rho^*(x, x') = \min_{u(t)} \left\{ \int_0^T l(x(t), u(t))dt + l_f(x(T)) \right\}$$

Related concepts:

- Nonholonomic metric (e.g, Vershik, Gershkovich, Bui, Laumond)
- Value function (e.g., Sundar, Shiller)
- Global navigation function (e.g, Rimon, Koditschek)
- Cost-to-go function (e.g., Basar, Olsder)

PROBLEM: Computing ρ^* is at least as hard as the path planning problem!

Performance degrades as ρ and ρ^* diverge

RRT-Based Planning Algorithms

Single RRT Planners:

- Goal-biased sampling
- The Connect heuristic

Dual RRT Planners:

- Extend both trees toward samples (ICRA '99)
- Extend trees toward each other and samples



Experiments

Two implementations to date:

- Gnu C++ and LEDA on a 400Mhz PC/Linux
- C++ on a 200MHz SGI Indigo2 with 128MB

Types of experiments:

- Chi-square tests, optimality comparisons, convex hulls
- Holonomic planning for rigid bodies
- Holonomic planning for articulated bodies
- Holonomic planning for closed kinematic chains
- Manipulation planning for digital actors
- Nonholonomic planning for car-like robots
- Nonholonomic planning for cars with trailers
- Kinodynamic planning for automobiles
- Kinodynamic planning for hovercrafts and spacecrafts
- Kinodynamic planning for a submarine in a flow field

Up to 12D state spaces

A Rigid Robot in a 2D World

- 3D configuration space
- Holonomic motion



A Nonholonomic Car-Like Robot

- 3D configuration space
- Bounded turning radius



A Forward-Only Car-Like Robot

- 3D configuration space
- Bounded turning radius



A Right-Turn-Only and Forward-Only Car

- 3D configuration space
- Car-like constraints (bounded turning radius)
- Forward only, and right turn only



A Left-Turn-Only and Forward-Only Car

- 3D configuration space
- Car-like constraints (bounded turning radius)
- Forward only, and left turn only



A Kinodynamic Car

m = mass of car (100 slugs)
CAF = front cornering stiffness (17000 lbs/rad)
CAR = rear cornering stiffness (20000 lbs/rad)
a = distance from mass center to front axle (4 feet)
b = distance from mass center to rear axle (5 feet)
I_{zz} = is yaw moment of inertia (1600 slug ft^2)
s = forward speed (feet/sec)
u = steering angle (in radians)

$$\alpha_f = (v + ar)/s - u$$

$$\alpha_r = (v - br)/s$$

$$FYF = -\alpha_f CAF$$

$$FYR = -\alpha_r CAR$$

State transition equation:

$\dot{x} = s\cos\theta - v\sin\theta$
$\dot{y} = s\sin\theta + v\cos\theta$
$\dot{\theta} = r$
$\dot{r} = (FYF * a - FYR * b)/I_{zz}$
$\dot{v} = -sr + (FYF + FYR)/m$

A Kinodynamic Car

- 5D state space, 3D configuration space



A Translating Hovercraft in a 2D World

- 4D state space, 2D configuration space
- Two pairs of opposing thrusters
- Computation Time: 10 seconds



After 500 nodes



1000 nodes



1582 nodes



Solution

An Uncontrollable Hovercraft in a 2D World

- 6D state space, 3D configuration space
- Two unilateral thrusters (forward only)
- Computation Time: 4.2 minutes



An Uncontrollable Hovercraft in a 2D World



A Translating Satellite in a 3D World

- 6D state space, 3D configuration space
- Three opposing pairs of thrusters
- Computation Time: 4.1 minutes



A Translating Satellite in a 3D World



A Free Satellite in a 3D World

- 12D state space, 6D configuration space
- Momentum wheels and an opposing pair of thrusters
- Computation Time: 8.4 minutes



A Free Satellite in a 3D World



Closed Kinematic Chains







Automobile Virtual Prototyping

The Consumer Union Short Course

Linear tire model



Nonlinear tire model



Manipulation Planning for Virtual Humans



Conclusions

- Practical nonholonomic and kinodynamic methods can be developed for high-DOF problems
- RRTs appear to be a useful new tool for path planning
- Experimental results are encouraging
- Many variations and improvements are possible
- RRTs might even be faster than probabilistic roadmaps for holonomic planning
- Hope to open the doors for many interesting applications
- Fits well with the general motion strategy problem

Future Work

Theoretical

- Convergence rates
- General probabilistic completeness conditions
- Relationship to optimal solutions

Experimental

- Efficient nearest neighbors
- Biasing the sampling density
- Multiple trees and other planning variants
- Overcoming metric problems
- Variational optimization of solutions

Applications

- Mobile robotics
- Humanoid manipulation planning
- Automotive virtual prototyping
- Virtual humans (with James Kuffner)
- Satellite and spacecraft navigation
- Computational fluid dynamics

Random Neighborhood Graph



A quickly-reconfigurable navigation function



Polar Sampling