

Toward Precise Control of a Robotic Boat

Arvind Menezes Pereira, Jnaneshwar Das, Amit Dhariwal, Bin Zhang, Beth Stauffer, Xuemei Bai,
 Lindsay Darjany, Carl Oberg, David Caron & Gaurav Sukhatme
 Robotic Embedded Systems Lab, University of Southern California – <http://robotics.usc.edu/~namos>

Need for Precise Control


Introduction

Unmanned surface vehicles (USVs)

- Subjected to external forces
 - wind
 - water currents
 - waves
- § **challenging control problem.**
- Typical problems in USV control
 - navigation
 - trajectory tracking
 - station keeping.

Task	Requirements
<i>Vertical profiling</i> which involves dwell time and sampling rate at multiple depths.	Hold position for ~10mins in the presence of drift.
Efficient <i>bathymetry</i> with profiling sonar.	<ul style="list-style-type: none"> • Heading control for efficient scanning. • Regular and dense scan patterns involve planning of trajectory in position and velocity.
<i>Docking</i> to recharge for long term deployments.	Docking maneuver.
<i>Collaborative missions</i> involving multiple boats.	Multi-robot missions and formations.

Platform and Methodology



System Dynamics

$$M\dot{v} + C(v)v + D(v)v + g(\eta) = \begin{bmatrix} \tau \\ 0 \end{bmatrix}$$

$$\dot{\eta} = J(\eta)v$$

- M = inertia matrix
- C = coriolis and centripetal matrix
- D = hydrodynamic damping matrix
- G = gravitation and buoyancy vector
- v = velocity vector in body frame
- η = velocity vector in global frame
- J = kinematic transformation matrix

System Identification

- Identify the dynamics of the boat
- Empirically determine unknown parameters by observing response of the system to specific inputs.


State Estimator

Sensors are noisy. A good state estimator (location and orientation) is essential for precise control. We use an Extended Kalman filter.

Controller Design

- Feedback controllers for heading and speed.
- Feedforward controller for correcting the effect of wind.

Design Details and Preliminary Results



Station Keeping

Problem - Wind results in position drift.

Proposed solution

- Monitor wind direction and speed using an anemometer.
- Estimate effect of wind on the boat using a wind model
- Align boat to the wind direction.
- Compensate for wind using Feedforward control.
 - adjust heading and speed to hold position.
- Learn set of gains for robust position regulation.

Simulation Results

- A - initial position of the boat oriented at 0°.
- B - align with the wind.
- C - Minimize error to the target while maintaining alignment.

