

A Test Bed for Autonomous Formation Flying

David J. Naffin and Gaurav S. Sukhatme

dnaffin | gaurav@robotics.usc.edu

Robotic Embedded System Laboratory
Robotics Research Laboratory
Department of Computer Science
University of Southern California
Los Angeles California 90089-0781

?

Abstract—This paper outlines the design of an autonomous flying vehicle (AFV) for use in researching formation flying. Specifically, we have designed a small autonomous model helicopter as a reference vehicle. Once several more units have been constructed, these vehicles will form a test bed for formation experiments. In this paper various design decisions are presented as well as results from early testing of the reference design. A novel approach to relative localization within formations using just a single downward-pointing camera is discussed.

Index Terms -- Autonomous Flying Robots, Formations, Multiple Robot Coordination[?]

I. INTRODUCTION

Little research has been performed in the area of coordination of multiple Autonomous Flying Vehicles (AFVs). AFV systems tend to be expensive and complex and therefore just having one system is considered a major accomplishment.

Recent advancements in key technologies now allow for AFVs to be designed smaller and cheaper than ever before. Single chip micro-controllers now exist with a full suite of integrated peripherals. Today, Nickel-Metal Hydride (NiMH) batteries can source more than ten amperes of current for up to fifteen minutes yet weigh less than a pound. Inertial sensors that use to occupy hundreds of cubic centimeters of space can now be constructed on a single silicon substrate.

This paper outlines our reference design for an autonomous flying vehicle that will be the basis of a test bed for experimentation in formation flying. In particular, we plan on utilizing small electric-powered radio-controlled (R/C) model helicopters as a mechanical chassis for our design. This mechanical chassis coupled with state-of-the-art micro-controllers as well as Micro Electro-Mechanical based Sensors (MEMS) will provide the basic avionics necessary for rudimentary control.

Relative localization of each robot will be accomplished using only local sensing (CMOS camera). In contrast to global localization techniques (GPS), each robot will only have knowledge of its relative location with respect to one or more of its neighbors. This will be beneficial in environments where GPS is not available (i.e. indoors or between skyscrapers). Local sensing techniques tend to be more robust and scalable than global techniques

Why fly in formations? Besides the challenge of accurately controlling multiple robots, there is the added benefit of having the coordination of multiple sets of sensors. Nature favors animals that have the ability to form formations such as flocks of birds or schools of fish. Animals that can combine their sensing abilities have shown to better avoid predators and efficiently forage for food [6]. Both the Air Force and NASA have identified autonomous formation of spacecraft as key technological milestones for the 21st century [1]. Applications of spaced based autonomous vehicles range from ground surveillance to interferometry experiments.

II. RELATED WORK

There are three fundamental approaches to multi-robot coordination; leader-follower approaches, behavior based models and virtual structure techniques. The leader-follower approach [2] designates one or more robots as the leader and requires all other robots to track the leader's position while maintaining a fixed offset relative to the leader(s).

The behavior-based approach to multi-robot coordination integrates several goal-oriented behaviors that act simultaneously toward their respective goals. Examples of behaviors are avoiding obstacles, tracking nearest neighbors, maintaining a position in a formation, etc. Reynolds [3] performed pioneering work in behavior-based simulations of flocks of birds. His "Boids" model demonstrated how simple behaviors that utilize only local sensing could generate an "emergent" group behavior. Emergent group behavior was investigated in [4] where simple behaviors such as

[?]Index Terms--Autonomous Flying Robots, Formations, Multiple Robot Coordination

avoidance, aggregation and dispersion could be used to create a "flocking" global behavior in mobile robots.

Some of the earliest tests of formation following behaviors on actual mobile robots were reported in [6] using metrics to evaluate how well the robots maintained formations. Four different formations as well as three different techniques for determining each robot's relative positions were studied. The formation behaviors were implemented as motor schemas within their Autonomous Robot Architecture (AuRA) running onboard DARPA's Unmanned Ground Vehicles.

[7] reports a behavior-based approach to multi-robot control utilizing "Social Potentials". In this approach robots are drawn to particular attachment sites relative to other robots. This scheme was inspired by how molecules arrange themselves to form crystals. Simulated experiments were performed using groups of up to eight robots and three different formations.. Their results demonstrated that maintaining formations could be accomplished with only simple local sensing.

Formations using only local sensing and interaction are reported in [8]. A single robot was designated the conductor. As in typical leader-follower approaches, the conductor defines the heading for the entire formation. However, unlike the typical leader-follower scheme, each robot senses only a single *friend* (which is not necessarily the leader) and maintains a fixed orientation and distance from it.

Recently there has been a great deal of interest in formations of spacecraft. The use of multiple spacecraft is a much more practical approach to spaced-based interferometry than a single large monolithic craft. However, interferometry requires formations where the precision of the distances between the crafts are on the order of a wavelength of light [1]. In order to achieve this order of precision, control laws need to be proven reliable and stable. The virtual structure approach regards the entire formation as a single rigid structure. Control algorithms are derived in three steps. First, the desired global coordination for the entire formation is derived. Second, the motion of the structure is translated into the motion of the individual agents. Finally, control laws for each agent are derived. Examples include simple geometric arrangements [9], formation feedback control [10] and a virtual structure architecture [1] that has provable characteristics.

Formations of autonomous airships using GPS have been investigated by [11]. Experiments with two blimps equipped with multiple carrier-phase GPS (CP-GPS) receivers allowed them to determine both the position as well as attitude for each craft. Experiments demonstrated formations with positional errors on the order of less than a foot and attitude errors on the order of less than five degrees.

III. DESIGN CONSIDERATIONS

The overall design of any autonomous robotic system can be classified into the following major areas; mechanics, sensors, actuators, communications and control. This section discusses the various decisions that were made in designing a craft that is capable of autonomously maintaining its position in a formation.

A. Mechanical Chassis

The choice of mechanical chassis is a fundamental consideration that affects all other design choices. The dynamics of the mechanics directly affect the design of the controller as well as the choice of actuators and sensors. Although it is possible to design an entire mechanical system from scratch, we decided that all our designs would capitalize on the mature field of radio-controlled (R/C) models. Radio controlled models have been around for more than 40 years. They are readily available and reliable. Knowledgeable "experts" can be found on many Internet newsgroups as well as local hobby stores.

The general categories of R/C models that are capable of flight are airships (blimps), airplanes and helicopters. Each category has its own pros and cons as described in table 1. Our decision to select an R/C model helicopter as our mechanical chassis was due to several reasons. First, model helicopters exhibit a high number of degrees of freedom for controlling the model. Their ability to hover allows them to fly in constricted spaces. This is important since we plan on performing many experiments indoors. Unlike model blimps, model helicopter react very quickly (sometimes too quickly) to control inputs. Finally, we have extensive prior experience in designing control systems for model helicopters [12].

The choice of a model helicopter as the mechanical chassis does have some drawbacks. The flight dynamics of a model helicopter are quite complicated. This makes any realistic simulation




Figure 1. Electric LMH-110 Model Helicopter

Model Type	Advantages	Disadvantages
Airships	Flies in a confined area Statically Stable Lowest Onboard Power Requirements Simple Linear Control Systems	Slow reacting Only three controllable degrees of freedom
Airplanes	Statically Stable Simple Linear Control Five controllable degrees of freedom	Can not fly in a confined area
Helicopters	Flies in a confined area Full controllable six degrees of freedom	Statically Unstable Highest Onboard Power Requirements Non-linear Control System

Table 1. Tradeoff of various R/C model types

difficult. Unlike blimps or airplanes, helicopter dynamics are not statically stable and therefore require constant command inputs to maintain stability. For any helicopter, lift is generated exclusively through the rotation of the main rotor blades. This requires the helicopter's power plant to maintain a very high output level.

There are a variety of model helicopters available from the R/C hobby market. They differ in their size, type of power plant, and sophistication of their controls. Sizes range from 30 centimeters to two meters in length. The model's size directly affects the payload lifting capacity of the craft. We wanted a craft that was small enough to be operating in a confined area yet large enough to carry all of the necessary avionics. We decide upon a payload "weight budget" of approximately half a kilogram. Therefore, we limited our search to models that were capable of lifting at least that much.

Most R/C model helicopters utilize Internal Combustion (IC) engines. We decided to limit our selection to all electric models. There were several reasons for this decision. First, IC engines used in R/C models burn a fuel that is a mixture of alcohol, castor oil and Nitro-Methane additives. This produces a very nauseous exhaust when operating. This situation would preclude us from operating the vehicle indoors. Since electric power is necessary for the avionics, an all-electric system can be operated from a single battery pack. We decided we would need approximately ten minutes of flying time per experiment. This would necessitate the use of a very efficient brush-less electric motor as well as state-of-the-art batteries. Fortunately for us, there has been an increased demand for small all-electric model helicopters within the model R/C community. Several new models have been introduced recently by manufacturers.

Model helicopters are designed either with their main rotor blades set at a fixed pitch or with controllable-pitched blades. "Fixed Pitch" model helicopters are simpler to control. However they are less maneuverable than "Collective (variable) Pitch" models. There are four or five basic control inputs for any model

helicopter; two "cyclic" inputs on the main rotor's swash-plate that control the vehicle's attitude (roll and pitch). The tail rotor blade pitch is used to control the vehicle's heading (yaw). Finally, the vehicle's altitude is controlled by either the combination of the main rotor blades' pitch and speed (collective pitch models) or simply by the main rotor's speed (fixed pitch models). The model employs three or four servomotors (referred to as simply servos) to provide the actuation to these control inputs. R/C servomotors are actuated via a pulse width modulated (PWM) signal that has been a standard in the model industry for decades. In a standard configuration a transmitter held by a pilot encodes the pilot's commands into a sequence of PWM codes that are decoded by an onboard receiver and channeled to the proper actuator.

All electric powered models require a *motor controller* to regulate the speed of the model's motor. Typically this is a microprocessor-controlled device that takes signals from the onboard receiver and proportionately modulates the motor's drive current. These devices often provide a linear voltage regulator to supply power for all additional onboard electronics. To simplify the electronics they utilize the same PWM signal used by the servos.

After surveying many different models, we decided on the Lite Machine's LMH-110 as our chassis (figure 1). This small model helicopter is only 67 cm long. It has a 60 cm main rotor blade diameter and weighs approximately 800 grams without batteries or any additional avionics. Early tests demonstrated the model's ability to lift more than our half kilogram payload requirement. It is inexpensive, reliable and replacement parts are readily available from many mail order retailers and hobby shops.

An Aveox 1010/2Y DC brush-less electric motor was chosen as the power plant. This is a new generation brush-less motor that employs state of the art neodymium-iron-boron magnets. The motor has an 85 percent efficiency and can produce in excess of 400 watts of power. This motor coupled with a Castle-Creation's Dragon-35H motor controller and a seven cell

3000 milli-ampere-hour Nickel Metal Hydride (NiMH) battery pack provides approximately ten minutes of flight time.

B. Overall System Architecture

Our platform's avionics consists of several modules interconnected via a high-speed serial bus. The Inter-IC (I²C) Bus was selected as the mechanism by which each module would communicate to one another. Data is transferred on the I²C bus at data rates up to 400 kilobytes per second. Each module will have a dedicated micro-controller that provides the interface to the I²C bus. A standard messaging scheme will be built on top of the bus. This will allow us to design, construct and test each module independently. In the final design, the master control module will have the role of the I²C bus master. However, while testing, the communications module will often fill this role.

When selecting electronic components for these modules, there are three constraints that need to be taken into account. First, the overall size of the components must be kept as small as possible. Since we planned on using standard printed circuit boards that can be purchased at any Radio Shack store, we needed to "budget" the size of individual components to just those that would fit on these boards. Second, the components should be as light as possible. Third, each component should consume as little power as possible. High power consumption equates to more battery weight.

The choice of micro-controllers was an early key decision in our design phase. Ideally we wanted to use a single controller for all modules. Unfortunately, no single choice was perfect for all cases. Ultimately, we narrowed our choices to the Atmel's Mega163 AVR controller and Scenix's SX28 processor.

The Atmel Mega163 is a highly integrated controller from Atmel's Advanced RISC line of micro-controllers. It is a flash ROM based micro-controller that can be programmed without removing it from the system. The controller has 16 Kilobytes of Flash ROM, 512 bytes of EEPROM and 1024 bytes of static RAM. It can be clocked up to eight MHz and can execute one instruction per cycle. An important feature of this controller is the built-in peripherals such as a ten-bit by eight channel A/D converter, three programmable timers, three PWM channels and several serial interfaces (UART, SPI and I²C). At eight MHz, it uses only 25 milli-watts of power and has a sleep mode that draws less than one micro-amp. The controller is programmable using standard "C" and the development tools are freely available.

The Scenix SX28 is the fastest 8-bit micro-controller currently on the market. It can be clocked from four to 100 MHz! The architecture of these processors is a superset of the industry standard MicroChip PIC controller. Therefore, all of the PIC development tools and libraries can be used on the

SX28. Each controller has 2048 bytes of Flash ROM for program storage and 144 bytes of static RAM for data. Due to its high clock speed, this micro-controller can perform many tasks in software usually only possible with dedicated hardware. Scenix provides a library of "virtual peripherals" that includes options such as PWM channels, timers, serial interfaces and even an A/D converter. The controller is programmable using standard "C" and the development tools are freely available.

Our current list of modules includes communications, actuator interface, inertial sensors, camera-laser-sonar interface and a master controller. Figure 3 details the set of modules.

1) Communication Module

Our communication module consists of a Linx Technology's SC-PA transceiver combined with a SX28 micro-controller. Two identical modules provide both the communications for onboard as well as the ground station (see figure 2). The SC series of transceivers are 900 MHz Frequency Shift Keyed units in a 1-inch by 1½-inch by ½-inch package. They can operate over a range of 100 meters and have excellent noise rejection



Figure 2. A pair of communication modules

characteristics. While operating they use only 60 milli-watts of power and have a sleep mode that uses less than 0.25 milli-watts. These modules provide a half-duplex serial link between a transmitting module and all other modules operating in receiver mode. Data can be transferred up to 33,000 bits per second. Initially the link will be used for craft telemetry. Later it can be adapted for coordination tasks.

2) Actuator Interface

Actuator commands can originate from the pilot on the ground or the onboard controller. A mechanism is needed that will arbitrate between the two. At any point, a human pilot must be able to gain full control of the vehicle. This is necessary for both practical and safety

reasons. The actuator interface module provides this mechanism. It interfaces the actuators to the rest of the system. In addition, it has a direct interface to the standard R/C receiver. The module has two modes of operation. In the “Pilot Override” mode, the controller simply relays the pilot’s commands from the R/C receiver directly to the actuators. In the “Autonomous” mode of operation, commands are received from the master control module via the module’s interconnect bus.

3) Inertial Sensors

In order to control the system, there must be a means of sensing the vehicle’s attitude. The most common means for determining this type of information are by the use of inertial sensors. An Inertial Measurement Unit (IMU) is a set of inertial sensors capable of measuring changes in all six degrees of freedom (X, Y, Z, roll, pitch and yaw). Although there are several commercial IMU’s that we could have purchased, none were within our size, weight, and power budget. Therefore, we decided to design our own IMU module.

Our IMU consists of a set of three orthogonal

positioned accelerometers (Analog Devices’ AXDL202) and a set of three orthogonally positioned angular rate sensing gyroscopes (Tokin’s CG-16D). The accelerometers are MEMS-based devices that produce pulse width modulated digital signals in proportion to the acceleration that they are experiencing. Each axis is able to measure up to 2G’s of acceleration in either direction. The gyroscopes are piezoelectric ceramic devices that produce an analog signal in proportion to the angular velocity experienced about their primary axis. These signals are filter and amplified before digitized by A/D converters (see figure 4).

In theory, an accurate estimate of the IMU’s attitude could be calculated by integrating only the three gyro’s signals. Unfortunately, the integration of the gyro’s noise results in a drift that would accumulate indefinitely. However, when the IMU is not experiencing any linear acceleration, its three accelerators are measuring the earth’s gravity vector. In this situation, the IMU’s roll and pitch angles can be calculated directly from this measurement. Both measurements combined using a Kalman filter gives the best possible estimate of the IMU’s attitude.

The Mega163 micro-controller is best suited as the




Figure 3. Detailed System Architecture

controller for this module. The controller's built-in multi-channel A/D converter, multiple timers and I²C interface vastly reduces the required components. A freely available C compiler and floating point math library simplifies the design of the filter software.

4) Camera /Laser / Sonar Interface

Each platform will be equipped with a single CMOS digital camera. The camera will be affixed to the vehicle such that it is imaging the ground plane beneath the model (i.e. downward pointing). It will be used to detect the vehicle's lateral motion and the relative locations of




Figure 4. Inertial Measurement Unit

the other vehicles in the formation (see section IV). The Spectronix's Robo-CAM2 is a combination color CMOS camera (VLSI Vision's VV6404) and an integrated frame grabber. It has a 356 by 292 pixel-imaging array that can digitize up to 30 frames per second. Packaged on two printed circuit boards, the unit is only two-inch square and a half an inch deep. The entire package weighs less than 40 grams and uses approximately 500 milli-watts of power. The built-in frame grabber has 512 kilobytes of static RAM that can store up to four frames. It utilizes a simple 8-bit parallel interface that is easily attaches to just about any micro-controller.

A standard laser pointer projects the vehicle's detectable signature on the ground. It will be necessary for each vehicle to differentiate each other's signatures. This could be accomplished by using different projected images. However, we decided that the projected signature will be modulated. Since a CMOS camera onboard the other vehicles must maintain a visual fixation of this projected signature, the duty cycle will be biased toward the on state.

A Polaroid 6500 sonar range finder will sense the vehicle's altitude. This device is able to measure distances from 15 centimeters to over 10 meters. The unit consists of a transducer that produces ultrasonic pulses and a driver circuit that detects the returning echo.

. While waiting for the return echo, the module draws only 100 milli-amperes of current. However, the transducer can draw as much as two amperes while transmitting the pulses. The trade-off here is how often the vehicle's altitude will be sampled. A faster sampling rate will result in less flight time for the vehicle.

5) Master Controller

The master control module will provide global coordination for all the other modules. Low-level reactive control loops as well as high-level behaviors will execute on the master control. This module will consist of a single Mega163 micro-controller along with an additional 64 kilobytes of static RAM. A small Real-Time Operating System (uC/OS) that supports thread scheduling, messaging and thread synchronization will be used to create the overall behaviors for the systems.

IV. RELATIVE LOCALIZATION

In order to maintain a formation, each vehicle must know its position relative to some key location within the formation (usually the location of the leader craft). While GPS receivers and global communications are one solution to this problem, there are limitations to GPS. GPS requires a direct line of sight between the receiver and at least four NAVSTAR satellites. This precludes its use indoors as well as between tall buildings. GPS receivers require as much as ten watts of power and require an antenna that is considerably bulky for small vehicles. In contrast, CMOS cameras are extremely small, light weight and require only an illuminated area. However, a single camera is rarely able to ascertain a vehicle's absolute global position. Fortunately for us, we need only relative positions to maintain a formation.

Our approach to vehicle localization within a formation is vision-based. Each vehicle is equipped with a downward pointing camera with a large field of view. In addition, each vehicle is also equipped with an inexpensive laser pointer. Each laser pointer is attached to the vehicle in a manner such that it projects a signature (image) onto the surface below. The signature projected will be a plus (+) shape so that it can easily be distinguished from other features on the ground. Each laser pointer can be modulated to distinguish one vehicle's projection from another (see figure 5).

This approach has several important merits. First, the 3D sensing problem has been effectively reduced to a 2D problem. This greatly reduces the computation required for the vision detection system. Second, the number of sensors has been reduced to a single downward pointing camera.




Figure 5. Vision based relative localization

However, there are few issues in regard to this approach that need to be addressed. The signatures projected onto the ground plane must truthfully represent the relative location of each vehicle. In order for this situation to be true, there are several requirements. First, the ground plane must be parallel to the imaging plane of the camera. The projected signature must be perpendicular to the ground plane. When the model is hovering above a flat surface, these requirements are met. However in forward flight the vehicle must pitch its nose down to generate forward thrust. Additionally the image of the ground plane will skew in forward flight. Fortunately, this is never more than a few degrees for slow forward flight. Moreover, each craft knows its approximate pitch angle and altitude and can communicate this information to the other vehicles. Since only 2D relative information is projected, this approach does require planar formations.

V. RESULTS

Currently we have successfully constructed and test flown a single electric LMH-110 model. There was a considerable learning curve associated with piloting a model helicopter. Just to become proficient in basic maneuvers requires six months of daily practice. During this training period, we were also able to construct and test a few of the key avionics modules.

A. Communications

A pair of communication modules were constructed and tested. Tests were performed to establish the maximum reliable range for a given data rate. A particular configuration (i.e. data rate and distance) was considered reliable if no more than five percent of the data packets were lost or corrupt. The tests were performed with the base station module located approximately one meter above the ground and the helicopter hovering two meters above the ground. The results are summarized in table 2.

Data Rate (Bits Per Second)	Distance (meters)
2400	> 200
4800	187
9600	123
19200	68
33000	25

Table 2 Distances versus Data Rate Tests

B. Inertial Sensors

The inertial sensor module was tested by comparing its attitude estimates against a reference IMU. Our IMU was flown alongside a Boeing's Digital Quartz Inertial Measure Unit and Navigational Processor (DQI-NP). This unit is an integrated IMU and GPS system and is commonly found in commercial aircraft and guided missiles avionics. Both units were flown onboard USC's AVATAR Autonomous Helicopter [12]. Telemetry from both was transmitted to a ground station. Figure 6 shows attitude estimations for both the Boeing unit as well as our inertial sensors for a one second period while the craft was in hover. The roll and pitch estimates were calculated by integrating the roll and pitch gyros. The integration of the gyro's noise causes the drift seen in the graphs. However the vehicle occasionally stabilized (i.e. had no lateral accelerations). During these periods the accelerometers were used as a tilt sensor and re-initialized the gyro's current state. Unfortunately, there was no state re-initialization for the yaw estimate. Therefore, the yaw estimate continued to drift without bound. Although there is considerable drift associated with the gyros, no attempt was made to compensate for temperature variations, a common problem with ceramic-based gyros. Overall we believe an accurate enough state estimation exists for rudimentary control.

VI. FUTURE WORK

In the near future, the first onboard tests of the master control modules will be performed. Once this basic functionality has been tested, the first low-level control loops can be tested. All of this effort will lead up to a stable hover control algorithm. Camera tests will shortly follow with an early emphasis on determining ground plane motion and adding appropriate control loops to negate any motion other than what is commanded.

Once the fundamental control loops for hovering and slow forward flight have been tested, formation-maintaining behaviors will be written. Finally, formation feedback control algorithms will need to be tested.

VII. SUMMARY

We have designed a reference vehicle as an experimental test bed for autonomous formation flying research. A small electric radio-controlled model helicopter was selected as the mechanical chassis for our design. A modular architecture based on the I²C serial bus was outlined. The design of the major avionic sub-systems; communication, inertial sensors, actuator




Figure 6. Inertial Measurement Unit Tests

interface, camera-laser interface and the master control module were detailed. An innovative approach to relative localization was presented as well as results of early sub-system tests.

REFERENCES

[1] Randal W. Beard, Jonathan Lawton, Fred Y.

Hadaegh, "A Coordination Architecture for Spacecraft Formation Control," *IEEE Transactions on Control Systems Technology*, July 2000

[2] P.K.C. Wang, "Navigation strategies for multiple autonomous mobile robots moving in formation", *Journal of Robotic Systems*, vol. 8, no. 2, pp 177-195, 1991

[3] Craig Reynolds, "Flocks, herds and schools: A distributive behavioral model", *Computer Graphics*, 21(4): 25-34, 1987.

[4] Maja J Mataric, "Designing Emergent Behaviors: From Local Interactions to Collective Intelligence", in *Proceedings, From Animals to Animats 2, Second International Conference on Simulation of Adaptive Behavior (SAB-92)*, MIT Press, 432-441.

[5] Lynne E. Parker, Designing Control Laws for Cooperative Agent Teams, *Proceedings of the 1993 IEEE International Conference on Robotics and Automation*: pp 582-587.

[6] Balch, T. and Arkin, R.C., Behavior-based formation control for multi-robot teams, *IEEE Transactions on Robotics and Automation*, December 1998.

[7] Balch, T. and Hybinette, M Social potentials for scalable multi-robot formations, *IEEE International Conference on Robotics and Automation (ICRA-2000)*, San Francisco, 2000.

[8] Jakob Fredslund and Maja J Mataric, Robot Formations Using Only Local Sensing and Control, *Proceedings, IEEE International Symposium on computational Intelligence for Robotics and Automation (CIRA-2001)*, Banff, Canada, Jul 29-Aug 1 2001

[9] M. A. Lewis and K. H. Tan, "High precision formation control of mobile robots using virtual structures," *Autonomous Robots*, vol. 4, pp. 387-403, 1997.

[10] Brett J. Young, Randal W. Beard, and Jed M. Kesley, "A Control Scheme for Improving Multiple-Vehicle Formation Maneuvers,"

[11] Eric A. Olsen, Chan-Woo Park, Jonathan P. How, 3D Formation Flight using Differential Carrier-phase GPS Sensors, Institute of Navigation GPS Meeting, Nashville, TN, September 18, 1998.

[12] J. F. Montgomery, "Learning Helicopter Control Through 'Teaching by Showing'," Ph.D. Thesis, Department of Computer Science, University of Southern California, May, 1999