

Landing on a Moving Target using an Autonomous Helicopter

Srikanth Saripalli and Gaurav S. Sukhatme

*Robotic Embedded Systems Laboratory
Center for Robotics and Embedded Systems
University of Southern California
Los Angeles, California, USA
{srik,gaurav}@robotics.usc.edu*

Abstract

We present a vision-based algorithm designed to enable an autonomous helicopter to land on a moving target. The helicopter is required to identify a target, track it, and land on it while the target is in motion. We use Hu's moments of inertia for precise target recognition and a Kalman filter for target tracking. Based on the output of the tracker a simple trajectory controller is implemented which (within the given constraints) ensures that the helicopter is able to land on the target. We present results from data collected from manual flights which validate our tracking algorithm. Tests on actual landing with the helicopter UAV are ongoing.

1 Introduction

In recent years, considerable resources have been devoted to the design, development and operation of unmanned aerial vehicles. The applications of such unmanned aerial vehicles are diverse, ranging from scientific exploration and data collection, to provision of commercial services, and military reconnaissance and intelligence gathering [1]. Other areas include law enforcement, search and rescue and even entertainment.

Unmanned aerial vehicles, particularly ones with vertical takeoff and landing capabilities (VTOL), enable difficult tasks without endangering the life of human pilots. This potentially results in cost and size savings as well as increased operational capabilities, performance limits, and stealthiness. Currently the capabilities of such unmanned aerial vehicles are limited. A helicopter is a compact VTOL capable platform; it is also extremely maneuverable. Autonomous helicopters equipped with the ability to land on moving targets would be very useful for various tasks as search and rescue, law enforcement, and military scenarios where micro air vehicles (MAVs) may want to land on a

convoy of enemy trucks.

We have previously developed a system which was successful in landing a helicopter autonomously on a stationary target using vision and global positioning system [2]. In this paper we focus on the problem of tracking and landing on a moving target using an autonomous helicopter as a platform. We track a moving target using a downward looking camera mounted on a helicopter. Trajectory planning is performed to allow the helicopter to land on the target. Data from flight trials show that our tracking system works quite well. Based on the tracking information, our controller is able to generate appropriate control commands for the helicopter in order to land it on target.

2 Related Work

Classical visual target tracking has concentrated on object recognition using edge detection techniques followed by a velocity field estimator based on optical flow [3]. Edge detection may be bypassed altogether [4] using inter-temporal image deformation for heading prediction through feature matching. In related work [5] discuss the merits of "good" feature selection and offer a motion computation model based on dissimilarity measures of weighted feature windows. The idea of feature selection and point matching [6] has been used to track human motion. In [7] eigenfaces have been used to track human faces. They use a principal component analysis approach to store a set of known patterns in a compact subspace representation of the image space, where the subspace is spanned by the eigenvectors of the training image set. In [8], a single robot tracked multiple targets using a particle filter for object tracking and Joint Probabilistic Data Association Filters were used for measurement assignment. [9] described a Variable Structure Interacting Multiple Model (VS-IMM) estimator combined with an assignment algorithm for tracking multiple ground targets. Although con-

siderable research has been performed on tracking moving targets from both stationary as well as moving platforms for mobile autonomous systems [8], almost no work has been done on using autonomous helicopters for such a task. This is the first paper which focuses on actually tacking a moving target and landing on it using an autonomous aerial vehicle.

Several techniques have been implemented for vision based landing of an autonomous helicopter on stationary targets. The problem of landing as such is inherently difficult because of the instability of the helicopter near the ground [10]. In [11], a vision-based approach to landing is presented. Their landing pad had a unique shape which made the problem of identification of the landing pad much simpler. In [2], we use invariant moment descriptors for detection and landing on a stationary target. We do not impose any restriction on the shape of the landing pad except that it be planar.



Figure 1: AVATAR (Autonomous Vehicle Aerial Tracking And Reconnaissance) after landing on a stationary helipad

3 Problem Formulation and Approach

The problem of landing on a moving target can be broadly divided into four stages. The first stage consists of detecting the target. We use vision for this purpose. In our case, we assume the target shape is known and no distractor targets are present. The second stage is tracking the target. We formulate the tracking problem as a Bayesian estimation problem and under linear system and Gaussian white noise assumptions solve it using a Kalman filter. The third stage is motion planning which plans a desired landing trajectory for the autonomous helicopter to land on the moving target. The fourth and last stage is control, which

regulates the location of the helicopter over time, in accordance with the planner output.

The general problem is given a mechanical system (whose state is given by x) and initial and final conditions $x_0, x_f \in \mathbb{N}$ where \mathbb{N} is the state space of the mechanical system, we have to find a control signal $u : t \rightarrow u(t)$ such that at time t_f the system reaches x_f . The generalized problem is to find control inputs for a model helicopter for the entire range of a family of trajectories. Although such problems have been considered for general cases [12], to our knowledge, this is the first time that such a formalization is being applied to a combination of tracking a moving target and landing on it using an unmanned helicopter.

3.1 Assumptions

Real time target tracking for an autonomous mobile robot in a general dynamic environment is an unsolved problem. However with reasonable assumptions and proper constraints regarding the environment, the target tracking problem can be tractable. We make several assumptions which simplify the problem for our application but are not restrictive. These assumptions do not change the general nature of the problem but simplify the visual processing part.

- The most difficult aspect of tracking is the discrimination of the target from the background. We assume that the shape of the target is known (we use a helipad with the letter H painted on it). Also we ensure that there is a high contrast between the target and the background.
- It is assumed that the target moves slowly enough for the helicopter to track it. We also assume that the target is not evasive or malicious.
- The target is smaller than the size of the image plane, in relative terms. Thus the target feature points do not span an area larger than the pixel dimensions of the focal plane.
- We assume that the helicopter is oriented such that the focal plane of the camera mounted on it is parallel to the target plane and this attitude is maintained throughout the tracking and the landing process. This ensures that we do not have to consider image skew.
- The target is allowed to move in the x and y directions only. This allows us to employ an orthographic projection model for image acquisition. Also the lack of roll and pitch in both the target and the helicopter mean that we do not perform full 6 DOF pose estimation. Although this may seem quite restrictive, our algorithm can be enhanced to consider relative motions

of both the helicopter and the target, which we plan to implement in the future.




Figure 2: FlowChart describing the algorithm used for landing on a moving target

4 Target Detection using Vision

The vision algorithm is described below in three parts; preprocessing, geometric invariant extraction, object recognition and state estimation.

The goal of the preprocessing stage is to locate and extract the target, which is done by thresholding the intensity image and then segmenting and performing a connected component labeling of the image. The image is first converted to gray scale by eliminating the hue and saturation information while retaining the luminance. This is accomplished by the following equation [13].

$$Y = 0.299 * R + 0.596 * G + 0.211 * B \quad (1)$$

A 7×7 Median-filter is applied to the thresholded image for removing noise and to preserve the edge details effectively. Median-filters have low-pass characteristics and they remove additive white noise [13]. The image is scanned row-wise until the first pixel at a boundary is hit. All the pixels which belong to the 8-neighborhood of the current pixel are marked as belonging to the current object. This operation is continued recursively until all pixels belonging to the object are counted. A product of this process

is the area of the particular object in pixels. Objects whose area is less than a particular threshold area (≤ 80 pixels) are discarded. Similarly objects whose area is ≥ 700 pixels are discarded. The remaining objects are the regions of interest and are candidates for the target.

The next stage is to extract the target from the image which is performed by using Hu’s moments of inertia [14]. These are normalized set of moments of inertia which are invariant to rotation, translation and scaling. The reader is referred to [2, 15] for a complete discussion of the Hu’s moments of inertia and their application for landing using an autonomous helicopter on a stationary target. After the extraction of the target from the image, the coordinates of the target are transformed into helicopter coordinates by using the equations below.



Figure 3: An typical image obtained from the downward pointing camera on the helicopter during one of the trials.

The coordinates of the target so obtained are in the image coordinate frame. These coordinates are transformed into state estimates relative to the helicopter, based on the height of the helicopter above the ground. The height of the helicopter is obtained from the onboard differential GPS. The x-coordinate of the target in the helicopter frame of reference is given by

$$x_{heli} = \frac{height \times \tan \frac{\phi_h}{2} \times x_{image}}{resolution \text{ of the camera along the x axis}} \quad (2)$$

where ϕ_h is the field of view of the camera in the x direction, x_{image} is the x-coordinate of the target in the image plane. Similarly the y-coordinate of the target is given by

$$y_{heli} = \frac{height \times \tan \frac{\phi_v}{2} \times y_{image}}{resolution \text{ of the camera along the y axis}} \quad (3)$$

Since the helicopter is near hover at all instances we assume that the roll, pitch and yaw angles of the helicopter

are negligible for computing the world coordinates of the target with respect to the helicopter.

5 Target Tracking using a Kalman Filter

The output of the target detection (i.e. the measured x and y coordinates of the target on the ground) is the input to the tracker. Based on a second order kinematic model for the tracked object we can model the equations of the target as a linear system described by

$$X_{k+1} = AX_k + w_k \quad (4)$$

where w_k is the random process noise and the subscripts on the vectors represent the time step. X_k is the state vector describing the motion of the target (its position, velocity and acceleration). Since we measure the position p of the target (using the target detection) our measurement at time k is denoted by

$$Z_k = p_k + v_k \quad (5)$$

where v_k is a random measurement noise. The Kalman filter is formulated as follows. Suppose we assume that the process noise w_k is white, zero-mean, Gaussian noise with a covariance matrix Q . Further assume that the measurement noise is white, zero-mean, Gaussian noise with a covariance matrix R , and that it is not correlated with the process noise. The formulation for the kalman filter is given by

$$\begin{bmatrix} p_{k+1} \\ v_{k+1} \end{bmatrix} = \begin{bmatrix} 1 & T \\ 0 & 1 \end{bmatrix} \begin{bmatrix} p_k \\ v_k \end{bmatrix} + \begin{bmatrix} \frac{T^2}{2} \\ T \end{bmatrix} a_k$$

where a_k is a random time-varying acceleration and T is the time between the steps $k+1$ and k . The update equation for the kalman filter are given by

$$S_k = P_k + R \quad (6)$$

$$K_k = AP_k S_k^{-1} \quad (7)$$

$$P_{k+1} = AP_k A^T + Q - AP_k S_k^{-1} P_k A^T \quad (8)$$

$$\hat{X}_{k+1} = A\hat{X}_k + K_k(Z_{k+1} - A\hat{X}_k) \quad (9)$$

In the above equations, the superscript T indicates matrix transposition. S is the covariance of the innovation, K is the gain matrix, and P is the covariance of the prediction error.

6 Trajectory Planning

We approximate the desired trajectory to be followed by the helicopter for tracking and landing by a cubic polynomial where the altitude z varies with time t as follows:

$$z(t) = a_0 + a_1 \cdot t + a_2 \cdot t^2 + a_3 \cdot t^3 \quad (10)$$

with the following conditions

$$z(0) = z_o \quad z(t_f) = z_f \quad \dot{z}(0) = 0 \quad \dot{z}(t_f) = 0$$

where t_f is the final time. We restrict the class of trajectories by imposing these additional set of constraints:

$$\begin{aligned} \dot{z} &\leq 1m/s & x_h(0) &= 0 & \dot{x}_h(t_f) &= \dot{x}_{target}(t_f) \\ & & x_h(t_f) &= x_{target}(t_f) \end{aligned}$$

The above constraints provide a lower bound on the time of flight i.e, the time of flight for the helicopter can never be less than t_{min} where t_{min} is given by

$$t_{min} \geq \frac{-4a_2 + \sqrt{4a_2^2 - 12a_3a_1}}{6a_3} \quad (11)$$

Hence if the helicopter has to intercept and land on a target at say x meters from the origin then the target, if it moving with the same speed as the helicopter should at least take t_{min} seconds to reach x for the helicopter to actually land on it.. Hence the maximum velocity of the target is bounded to $\frac{x}{t_{min}}$. We assume that both the helicopter and the target start at relatively the same position.

7 Behavior-based Control

Our helicopter is controlled using a hierarchical behavior-based control architecture. The autonomous control has been discussed in detail in [16]. We used this controller for autonomous landing on a stationary target - this was discussed in detail in [2]. The reader is referred to them for the control and landing phase details. Here we recapitulate the controller briefly.

7.1 Control Architecture

The behavior-based control architecture used for the AVATAR is shown in Figure 4.

At the lowest level the robot has a set of reflex behaviors that maintain stability by holding the craft in hover.




Figure 4: AVATAR Behavior-Based Controller

The *heading control* behavior attempts to hold the desired heading by using data from the IMU to actuate the tail rotor. The *altitude control* behavior uses the sonar to control the collective and the throttle. The *pitch and roll control* behaviors maintain the desired roll and pitch angles received from the *lateral control* behavior. The *lateral motion* behavior generates desired pitch and roll values that are given to the *pitch and roll control* behaviors to move to a desired position. At the top level the *navigation control* behavior inputs a desired heading to the *heading control*, a desired altitude to the *altitude control* and a desired lateral velocity to the *lateral control* behavior. A key advantage of such a control algorithm is to build complex behaviors on top of the existing low level behaviors.

The *altitude control* behavior is further split into three sub-behaviors, *hover control*, *velocity control* and *laser control*. The *hover control* sub-behavior is activated when the helicopter is either flying to a goal or is hovering over the target. This sub-behavior is used during the object recognition and object tracking state when the helicopter should move laterally at a constant altitude. The hover controller is implemented as a proportional controller. It reads the desired GPS location and the current location and calculates the collective command to the helicopter.

Once the target has been tracked and a trajectory planned the *velocity control* sub-behavior runs in parallel with the *laser control* sub-behavior. It is implemented as a PI controller. An integral term is added to reduce the steady state error. The helicopter starts to descend (and move laterally) till touchdown. The *laser control* sub-behavior works in conjunction with the *velocity control* sub-behavior. It maintains the helicopter at a commanded altitude until touchdown. This is also implemented as a PI controller.

8 Experimental Results

In order to validate our algorithm, we performed experiments with the USC AVATAR shown in Figure 1

The helicopter was hovered manually at a height of 30 meters. The pilot controlled the helicopter to be in the hover position all the time, while the target (which was another robot in our experiments) was commanded to move in a straight line. The image data were processed offline. The goal position for the helicopter was 12 meters from the starting point, i.e, the helicopter should track the helipad for 12 meters and then land on it.

Figure 3 shows a typical image obtained from the downward pointing camera on the helicopter. The target is marked with an H and moves in the x-direction for a distance of 12m. Figure 5 shows three curves. The solid line is ground truth. It is the location of the target as measured on the ground by the odometry of the target robot. The dotted line is the location as measured by the camera without filtering. This is obtained by first detecting the target in the image, finding its image coordinates and then transforming them to the helicopter's reference plane as shown in Section 4. The dashed line is the location of the target deduced by the Kalman filter as explained in Section 5.




Figure 5: Kalman filter tracking performance

Figure 6 shows the trajectory followed by the helicopter while tracking the target. The plot shows the trajectory of the target (solid) and the trajectory of the helicopter (dashed). As can be seen the helicopter is able to track the target quite well.

Figure 7 shows the height of the helicopter with respect to time. During simulation it was found that updating the trajectory of the helicopter every time step the Kalman filter




Figure 6: The helicopter trajectory in the x -direction (dashed) and the target trajectory in the x -direction (solid) while tracking

made a new prediction was not necessary. Only a discrete number of modifications were made to the trajectory and a cubic spline trajectory as described in Section 6 was used. It may be noted that during the actual flight tests we will probably use a straight line interpolation of the cubic spline which is also shown in Figure 7




Figure 7: Height trajectory followed by the helicopter while tracking and landing

9 Conclusions

This paper describes the design of an algorithm for landing on a moving target using an autonomous helicopter. We

use a Kalman filter as an estimator to predict the position of the target and plan the trajectory of the helicopter such that it can land on it. Given conditions about the distance at which the helicopter should land on the target we perform discrete updates of the trajectory so that we can track and land on the target. We have performed experiments in manual control mode where a human pilot was controlling the helicopter and was holding it in hover while we collected data of a ground target moving in the field of view of the helicopter. The estimator and the trajectory planner were run offline to test the validity of the algorithm. Figures 5, 6, 7 show the results obtained by using the Kalman filter in conjunction with a object recognition algorithm.

9.1 Limitations, Discussion and Future Work

In the future we plan to test the algorithm on our autonomous helicopter. Several limitations exist with the current algorithm:

- We assume that the helicopter is in hover (zero roll, pitch and yaw values and zero movement in the northing and easting directions). This is almost impossible to achieve in an aerial vehicle. We plan to integrate the errors in GPS coordinates and attitude estimates into the Kalman filter so that we are able to track the target more precisely.
- The current estimator is able to track the target only in a single dimension. We will extend it so that it is able to track the target in all the six degrees of freedom and verify the validity of the algorithm.
- Currently we use an algorithm based on the intensity of the image for object detection. We also assume that the object is planar. This is quite restrictive in nature. We plan to integrate our algorithm with a better object detector and a camera calibration routine so that the coordinates of the tracked object obtained during the vision processing stage are much more accurate.
- We will extend the algorithm in the future such that we are able to track multiple targets and then land on any one of them. Also we intend to investigate algorithms to be able to pursue and land on evasive targets.

Acknowledgments

This work is supported in part by NASA under JPL/Caltech contract 1231521, by DARPA under grant DABT63-99-1-0015 as part of the Mobile Autonomous Robot Software (MARS) program, and by ONR grant N00014-00-1-0638 under the DURIP program. We thank Doug Wilson for support with flight trials.

References

- [1] Office of the Under Secretary of Defense, "Unmanned aerial vehicles annual report," Tech. Rep., Defense Airborne Reconnaissance Office, Pentagon, Washington DC, July 1998.
- [2] S. Saripalli, J. F. Montgomery, and G. S. Sukhatme, "Vision-based autonomous landing of an unmanned aerial vehicle," in *IEEE International Conference on Robotics and Automation*, Washington D.C., May 2002, pp. 2799–2804.
- [3] B. K. P. Horn and B. G. Schunk, "Determining optical flow," *Artificial Intelligence*, vol. 17, pp. 185–203, 1981.
- [4] Tomasi. C. and Shi. J, "Direction of heading from image deformations," in *IEEE Conference on Computer Vision and Pattern Recognition*, June 1993, pp. 4326–4333.
- [5] Shi. J and Tomasi. C, "Good frames to track," in *IEEE Conference on Computer Vision and Pattern Recognition*, June 1994, pp. 4326–4333.
- [6] Birchfield. S., "An elliptical head tracker," in *31 Asilomar Conference on Signals Systems and Computers*, November 1997, pp. 4326–4333.
- [7] Turk. M and Pentland. A., "Eigenfaces for recognition," in *Journal of Cognitive Neuroscience*, 1995, vol. 3, pp. 4326–4333.
- [8] D. Schultz, W. Burgard, D. Fox, and A. B. Cremers, "Tracking multiple moving targets with a mobile robot using particle filters and statistical data association," in *IEEE International Conference on Robotics and Automation*, 2001, pp. 1165–1170.
- [9] Y. Bar-Shalom and W. D. Blair, *Multitarget-Multisensor Tracking: Applications and Advances*, vol. 3, Artech House.
- [10] Bruno Sinopoli, Mario Micheli, Gianluca Donato, and T. John Koo, "Vision based navigation for an unmanned aerial vehicle," in *Proceedings of IEEE International Conference on Robotics and Automation*, 2001, pp. 1757–1765.
- [11] Omid Shakernia, Y. Ma, T. John Koo, and S. Shankar Sastry, "Landing an unmanned air vehicle: vision based motion estimation and non-linear control," in *Asian Journal of Control*, September 1999, vol. 1, pp. 128–145.
- [12] K. Ogata, *Modern Control Engineering*, Prentice Hall, 2nd ed., 1990.
- [13] R. Gonzalez and R. Woods, *Digital Image Processing*, Addison-Wesley, 1992.
- [14] M.K. Hu, "Visual pattern recognition by moment invariants," in *IRE Transactions on Information Theory*, 1962, vol. IT-8, pp. 179–187.
- [15] Papoulis. A, *Probability, Random Variables, and Stochastic Processes*, McGraw-Hill, New York, 1965.
- [16] J. F. Montgomery, *Learning Helicopter Control through 'Teaching by Showing'*, Ph.D. thesis, University of Southern California, May 1999.