

A UNIFYING FRAMEWORK FOR TUNABLE TOPOLOGY CONTROL IN SENSOR NETWORKS

Sameera Poduri¹, Sundeep Pattem², Bhaskar Krishnamachari^{1,2}, Gaurav Sukhatme¹

¹ Department of Computer Science, ² Department of Electrical Engineering,
University of Southern California,
Los Angeles, CA 90036, USA
{sameera, pattem, bkrishna, gaurav}@usc.edu

ABSTRACT

Topology control, primarily concerned with ensuring desired levels of coverage and connectivity, is a vital self-configuration operation in unattended sensor networks. We present a classification of sensor network topologies and discuss their implications for topology control. Our main contribution is a unifying framework that forms a basis for tunable topology control in all classes of topologies. It is based on a simple, local condition of ensuring a neighbor in every theta (θ) angle sector of each node's communication range. We present analysis to establish that varying this single parameter θ can indeed provide a wide range of coverage and connectivity tradeoffs. For specific values of θ , we show that the Neighbor-Every-Theta (NET) condition guarantees various proximity graphs such as the relative neighborhood graph. The problem of maximizing coverage given such a condition is also addressed. Algorithms for controlled deployment are presented to demonstrate how the NET condition can be integrated with positioning of nodes for tunable topology control.

1. INTRODUCTION

In view of their distributed and unattended operation, self-configuration of nodes is essential for deploying large scale sensor networks. Topology control is a key operation for enabling self-configuring capability in these networks. It consists of mechanisms designed to provide desired levels of coverage and connectivity and ensure power-efficient operation of the network. While power-efficiency is a basic requirement given the nature of sensor networks, coverage and connectivity are closely tied to application-specific requirements. For scalability, topology control mechanisms

that work well with local information and asynchronous node operations are desirable.

Most prior work on topology control has dealt with *uncontrolled* deployments, where there is no explicit control on positions of individual nodes [1]. The primary mechanisms proposed are power control and sleep scheduling. These methods involve pruning an already existing, well connected communication graph in order to save power while ensuring that the resultant sub-graph preserves connectivity. Given a network that is connected when all nodes are operating at maximum power, the aim of power control is to use the minimum power level at each node for which the network remains connected [2]. Given an over-deployed network, sleep scheduling seeks to activate a minimal subset of nodes to maintain connectivity and achieve other desired metrics [3].

In contrast, *controlled* deployments are feasible when positions of individual nodes can be altered. Such deployments are interesting for two reasons. First, network topology with wireless communication relates directly to proximity relations and hence, position of nodes. Second, there is increasing evidence that a large number of deployments are likely to involve careful, non-random placement of nodes [4, 5]. The positioning of nodes is controlled either by the nodes themselves or by external agents. Such networks present a different and interesting scenario for topology control since it is possible to exploit control of the motion and placement of the nodes to build efficient topologies.

Thus, sensor network topologies can be classified on the basis of node mobility (static or mobile) and the nature of their deployment (controlled or uncontrolled):

1. **Static nodes, uncontrolled deployment:** This is the assumption in a majority of work on sensor networks - resource-constrained, static nodes are randomly deployed in a given area. Power control (for sparse networks) and sleep scheduling (for over-deployed networks) are chiefly employed for topology control. It is plausible that these two mechanisms are used in conjunction.

2. **Mobile nodes, uncontrolled deployment:** Such sys-

This work is supported in part by the National Science Foundation (NSF) under grants 0347621, 0325875, 0325875, IIS-0133947, EIA-0121141 and grants CCR-0120778, ANI-00331481 (via subcontract). Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of the National Science Foundation.

Class	Example	Topology Control Mechanisms		
		Power Control	Sleep Scheduling	Position Control
Uncontrolled Static	29 Palms Experiment [6]	✓	✓	×
Uncontrolled Mobile	ZebraNet [7]	✓	⊕	×
Controlled Static	Structural Health Monitoring [5]	⊕	⊕	✓
Controlled Mobile	NIMS [4]	×	×	✓

✓ - primary mechanism, ⊕ - secondary mechanism, × - not applicable

Table 1. Classes of sensor network topologies and corresponding applicable topology control mechanisms

tems are studied as mobile ad-hoc networks (MANETS). The challenge is to ensure network operation in spite of the autonomous and mutually independent motion of the nodes. Power control is the suitable mechanism for topology control.

3. **Static nodes, controlled deployment:** In this class, static nodes are carefully positioned either by humans or by autonomous robots. Topology control is achieved by controlling the positions of nodes. Power-control and sleep scheduling might be employed, but largely as secondary mechanisms.

4. **Mobile nodes, controlled deployment:** This class involves mobile nodes which can position themselves with respect to each other. Topology control mechanisms are integrated with the motion and positioning strategy. Since motion is the dominant power consumer, power-efficiency of communication is not a major consideration. Sleep scheduling is also not relevant because mobile deployments are not likely to be dense.

The classification is summarized in Table 1.

We present a unifying framework for topology control in sensor networks. This framework is a basic building block for designing mechanisms for completely distributed and tunable topology control for all four classes of topologies. It is based on the following simple, local condition: ensure that each node has a neighbor in every theta angle sector of its communication range. This Neighbor-Every-Theta (NET) condition results from our analysis of local node positioning rules that guarantee global network properties.

The communication graph of a wireless network can be modeled as a proximity graph because high quality links typically exist only between proximate nodes. We analyze proximity graphs such as the relative neighborhood graph (RNG) which are known to have good coverage and connectivity properties and derive local conditions that guarantee formation of these graphs. The problem of maximizing sensing coverage under the NET condition is addressed. For certain values of the sector angle, it is possible to place the nodes such that the resultant communication graph is a symmetric tiling of the space. We show that such placement will achieve the maximum coverage. These results are combined to present a graph construction mechanism which has two key features:

- the required conditions are simple, local and geometric, and
- varying the single parameter θ provides a wide range of coverage and connectivity tradeoffs.

This general framework can support a number of existing power control and sleep scheduling schemes. Nodes can check for neighbors satisfying the NET condition, integrating it with the power adjustment and node activation policy respectively. It can also support controlled deployment of a static sensor network - the agent making a decision on the best location of the next node based on the geometry of the existing network. Self-deploying mobile nodes could use this condition to decide their motion strategy. In this paper, the focus is on establishing position control as a topology control mechanism. We present algorithms for controlled deployment of both static and mobile nodes to concretely demonstrate the use of the local geometric rules to implement coverage and connectivity tradeoffs. Simulations will study relaxations of some idealized assumptions made in the problem formulation for ease of analysis.

2. PROBLEM FORMULATION

Scalability is a major issue in deploying large scale sensor networks. As a design principle, the need is for network configuration mechanisms that depend solely on local information and interactions and yet are capable of achieving some global objective. In this work, we study this problem in the context of topology control by asking the following question:

Do there exist local, geometric conditions that can guarantee desired global topological properties?

If such conditions can indeed be found, it will be possible to devise a general framework on which topology control mechanisms can be based.

We analyze networks for the following desirable topological properties:

- **Coverage:** The total area lying within the sensing range of at least one node.




Fig. 1. Illustration of the NET condition. In a), node X has one sector greater than a given angle θ with no neighbor. It does not satisfy the NET condition. In b), the largest sector with no neighbors is smaller than θ , satisfying the NET condition

- **Connectivity:** A graph G is said to be k -(edge)-connected if there are at least k node disjoint paths between any two nodes $u, v \in V$. Connectivity is a measure of fault tolerance or path diversity in the network. 1-connectivity is a fundamental requirement for network operation.
- **Sparseness:** A graph is said to be sparse if the number of edges is $O(|V|)$ (linear in the number of nodes). A sparse topology is desired for power efficiency.
- **Degree:** The average number of neighbors across all nodes. A higher node degree can provide better sensing granularity. Bounded node degree leads to lower interference in wireless communication and hence increased throughput.
- **Spanning Ratio:** A graph G is called a c -spanner if for all $u, v \in V$ there exists a path $p = (u = v_0, v_1, v_2, \dots, v_l = v)$ from u to v in G with

$$|p| = \sum_{i=0}^{l-1} d(v_i, v_{i+1}) \leq c \cdot d(u, v),$$

where $d(u, v)$ is the Euclidean distance. If G is a c -spanner, c is called its spanning ratio. The spanning ratio is an indicator of the number of hops between two nodes given their separation.

In the next section, we present analysis of these desired properties.

In order to obtain analytically tractable models, two key idealized assumptions will be made - circular communication range (in Section 3) and availability of position (angle and distance) information (in Section 4). Justifications and explanations are provided at appropriate places. These assumptions will be relaxed in simulations (Sections 4.1 and 4.2).

3. NEIGHBOR EVERY THETA (NET) GRAPHS

We define the *Neighbor Every Theta* (NET) condition [figure 2] for a node as requiring at least one neighbor in every θ sector of the communication range. For finite networks, *boundary nodes* or nodes on the network edge cannot satisfy such a condition. For a given θ , we define boundary nodes as those which have no neighbor in at least a θ sector of *infinite radius*. A NET graph is one in which every node except the boundary nodes satisfies the NET constraint for a given θ .

An important feature of these graphs is that they can be constructed from purely local information - each node only needs to know the locations (distance and angle) of its neighbors relative to itself.

NET graphs form a family of graphs based on a single parameter θ . As θ becomes smaller, the graphs become denser with increasing level of connectivity and decreasing coverage. In this section we analyze the connectivity and coverage of these graphs as a function of θ .

3.1. Connectivity Analysis of NET Graphs

It has been shown that if every non-boundary node has at least one neighbor in each π sector around it, the network is guaranteed to be connected [8]. This implies that for $\theta \leq \pi$, NET graphs are guaranteed to be 1-connected.

We now derive values of θ for which NET graphs will be guaranteed to form each of three representative proximity graphs, namely the Relative Neighborhood Graph (RNG), Gabriel Graph (GG) and the Delaunay Graph (DelG). These graphs have been well studied and are known to be desirable global topologies for wireless communication networks.

The RNG, GG and DelG are all connected and are known to be sparse when defined over a *disk graph*. The sparseness of proximity graphs implies that the average node degree is




Fig. 2. RNG sector condition. a) The circle of radius $d(X, Y) > R_c$ subtends an angle of $\frac{2\pi}{3}$ at X . The lune contains an area larger than a $\frac{2\pi}{3}$ sector. b) The limiting case, when $d(X, Y) = R_c$.

bounded by a constant. The RNG displays desirable properties in terms of power consumption, average node degree and fault tolerance [9]. GPSR [10] is a greedy geographic routing protocol which derives its scalability from the RNG and GG as they allow routing decisions based on local state only. In [11], a restricted DelG is shown to improve GPSR performance by virtue of its bounded spanning ratio. In [12] a solution to the rendezvous problem of robotic networks is proposed that relies on forming proximity graphs like RNG, GG and DG.

We assume ideal, perfectly circular communication range. It is well known that the real communication range is very different from a circle [13]. However, using results in [14], it is possible to obtain a range in which the probability of packet receptions is close to 1. These results provide guidelines on how to leverage our analysis, which is based on idealized assumption of circular communication range, for real deployments. In power control, a minimal setting for the power and the corresponding circular region of high-quality communication links can be obtained. For sleep scheduling and deployment of static nodes using an external agent, a minimum density requirement based on node power settings can be arrived at. Finally, mobile nodes can be expected to have high-power radios for which there is a large circular neighborhood with high-quality links.

Let V be the set of nodes in a wireless communication network in \mathbb{R}^2 . For $u, v \in V$ let $d(u, v)$ denote the Euclidean distance from u to v . In what follows, the name and location of a node are used interchangeably.

The set of edges E for various proximity graphs is defined as follows [15].

Disk graph ($DG(V, E, r)$): The undirected graph containing all edges not longer than r .

$$E = \{(u, v) | u, v \in V \text{ and } d(u, v) \leq r\}$$

Given positive $r \in \mathbb{R}$, let $C(p, r)$ be the circle consisting of points whose distance from point p is strictly less than r . Define the lune, denoted $L(p, q)$, to be the intersection of two circles, both of radius $d(p, q)$, centered at these points, that is, $L(p, q) = C(p, d(p, q)) \cap C(q, d(p, q))$.

Relative Neighborhood Graph (RNG(V)): The undirected graph containing an edge (u, v) if there is no point $w \in V$ that is simultaneously closer to both u and v . Equivalently, (p, q) is an edge if $L(p, q) \cap V = \emptyset$.

$$E = \{(u, v) | u, v \in V \text{ and } \exists \text{ no } w \in V \ni$$

$$d(u, w) < d(u, v) \text{ and } d(v, w) < d(u, v)\}$$

Gabriel Graph (GG): The undirected graph containing an edge (u, v) if the disc whose diameter is edge (u, v) does not contain any other points of V , that is, if $C(\frac{u+v}{2}, \frac{d(u,v)}{2}) \cap V = \emptyset$.

$$E = \{(u, v) | u, v \in V \text{ and } C(\frac{u+v}{2}, \frac{d(u,v)}{2}) \cap V = \emptyset\}$$

Delaunay Graph (DelG): The undirected graph containing an edge (u, v) if the Voronoi regions of u and v have non-empty intersection. From the properties of Voronoi diagrams it follows that

1. edges of triangle (u, v, w) are in $DelG(V)$ if their circumcircle does not contain any other points of V
2. edge (u, v) is in $DelG(V)$ if the disc whose diameter is the line uv does not contain any other points of V

These graphs are hierarchically related:

$$RNG(V) \subseteq GG(V) \subseteq DelG(V).$$

In the proofs that follow, we assume that every node in the network has the same communication range R_c . This is not a requirement and we discuss how the proofs will hold even when each node has a different communication range. However, this assumption makes the proofs simpler. Now, the communication graph of a wireless network is a disk graph with all edges being smaller than or equal to the communication range R_c . Our next step is to find conditions under which the RNG of the network is contained in the communication graph. This is equivalent to finding conditions under which no edge of an RNG is longer than R_c . The following theorem presents this condition. Later, we prove similar results for the GG and DelG.

Theorem 1 *If each node $X \in V$ has at least one neighbor in every $\frac{2\pi}{3}$ sector of $C(X, R_c)$, the communication graph is a supergraph of $RNG(V)$. Moreover, $\frac{2\pi}{3}$ is the largest angle that satisfies this property.*

Proof: Consider any node $x \in V$. Suppose x has at least one neighbor in every $\frac{2\pi}{3}$ sector of $C(X, R_c)$. It is sufficient to show that for any node Y outside $C(Y, R_c)$, the edge $(X, Y) \notin RNG(V)$. The lune $L(X, Y)$ will contain a sector of at least $\frac{2\pi}{3}$ (figure 2). By premise, \exists a node Z that lies in $L(X, Y)$.

This implies that the RNG does not have any edge lengths greater than R_c and therefore $RNG(V) \subseteq DG(V, E, R_c)$.

Now suppose a node $X' \in V'$ has two neighbors with a sector angle of $\frac{2\pi}{3} + \delta$ ($\delta > 0$) between them (figure 3). We can place a node Y' outside $C(Y', R_c)$ such that the edge $(X', Y') \in RNG(V')$. Therefore, $\frac{2\pi}{3}$ is the largest angle for which $NET(V, \theta)$ contains $RNG(V)$. \square

Theorem 2 *If each node $X \in V$ has at least one neighbor in every $\theta = 2 \arccos(\frac{r}{R_c})$ sector of $C(X, r)$ ($r \leq R_c$), the communication graph is a supergraph of $GG(V)$.*

Proof: Consider a node X and a node Y outside $C(X, R_c)$. For any $r \leq R_c$, let β be the angle subtended by the intersection area $C(X, r) \cap C(\frac{x+y}{2}, \frac{d(X,Y)}{2})$ at X . From figure 4 we have,

$$\frac{r}{2} = \frac{d(X, Y)}{2} \cos\left(\frac{\beta}{2}\right) \Rightarrow \beta = 2 \arccos\left(\frac{r}{d(X, Y)}\right).$$

Since \arccos is strictly decreasing in $[0, 1]$ and $d(X, Y) \in (R_c, \infty)$, the smallest angle subtended is

$$\theta = \inf \beta = 2 \arccos\left(\frac{r}{R_c}\right). \quad (1)$$




Fig. 3. $\theta = \frac{2\pi}{3}$ bound for RNG - $L(X, Y)$ is empty




Fig. 4. Sector condition for GG

Suppose x has at least one neighbor in every

$$\theta = 2 \arccos\left(\frac{r}{R_c}\right)$$

sector of $C(X, r)$. By definition, the edge $(X, Y) \notin GG(V)$ if

$$C\left(\frac{d(X, Y)}{2}, \frac{d(X, Y)}{2}\right) \cap V \neq \emptyset. \quad (2)$$

(2) is satisfied for any choice of Y if there is a node $Z \in V$ in the θ sector of $C(X, r)$. By premise such a Z exists and hence the GG will not have any edge lengths greater than R_c . This implies that $GG(V) \subseteq DG(V, E, R_c)$. \square

Corollary: *If a node X has at least one neighbor in every $\theta = 2 \arccos(\frac{r}{R_c})$ sector of $C(X, r)$ ($r \leq R_c$), the communication graph is a supergraph of $DelG(V)$.*

Proof: Consider all circles passing through X and Y . The smallest is $C(\frac{X+Y}{2}, \frac{d(X, Y)}{2})$ and the largest are two circles of infinite radius of which the straight line through X and Y is an arc. From figure 5, it can be seen that the




Fig. 5. Sector condition for DelG

intersections of these circles with $C(X, r)$ subtend an angle which is at least θ at X , where

$$\theta = \inf \beta = 2 \arccos\left(\frac{r}{R_c}\right).$$

By premise, there is at least one node in every θ sector of $C(X, r)$. Therefore, every circle passing through X and Y will contain another node. So,

1. there is no $Z \in V$ such that the $\triangle XYZ \in DelG(V)$
2. trivially $C(\frac{X+Y}{2}, \frac{d(X,Y)}{2})$ also contains another node.

By 1,2 and definition of DelG, the edge $(X, Y) \notin DelG(V)$. Since the choice of Y is arbitrary, there are no edge lengths greater than R_c in the DelG. Hence $DelG \subseteq DG(V, E, R_c)$. \square

In all the proofs above, an arbitrary node X is considered. Now assume that such a node X has a communication range R_c^X , which is different from the other nodes. It is easy to see that the proofs can be slightly modified to show that the assertions hold even in this case. For the RNG, the $\frac{2\pi}{3}$ bound still holds. For the GG and DelG, each node X will need at least one neighbor in every $\theta = 2 \arccos(\frac{r}{R_c^X})$ sector of $C(X, r)$.

In real networks, it is not possible for the boundary nodes to satisfy the conditions required by the theorems. We show using simulated deployments (in section 4) that the assertions can be validated in spite of these exceptions.

3.2. Coverage Analysis of NET Graphs

Having listed the conditions that guarantee global connectivity properties, we now turn to the problem of maximizing coverage. Suppose that in order to satisfy the NET sector conditions, a node must have k neighbors. From the

node's local perspective, all neighbors must be located on the perimeter of the communication range to maximize coverage. Intuitively, the nodes must also be placed symmetrically on the perimeter. Assume a circular sensing range of radius R_s .

Theorem 3 For $R_s = R_c$, the area coverage is maximized when the $k \geq 3$ nodes are placed at the edges of k disjoint $\frac{2\pi}{k}$ sectors of $C(X, R_c)$.

Proof: Consider a node X and k nodes Y_1, Y_2, \dots, Y_k placed on the perimeter of $C(X, R_c)$. Let these nodes be placed in anticlockwise order at angles $\beta_1 = 0, \beta_2, \dots, \beta_k$ respectively. Define

$$\begin{aligned} \theta_i &= \beta_{i+1} - \beta_i, 1 \leq i \leq k-1 \\ \theta_k &= 2\pi - \beta_k \end{aligned} \quad (3)$$

We need to find θ_i such that the total area covered by these $k+1$ nodes is maximized. The open discs of all nodes lie within $C(2R_c, x)$ and are tangent to this disc at exactly one point (T_i) each. The discs of adjacent nodes i and $i+1$ intersect at point I_i (and at X). The total coverage lies between πR_c^2 and $4\pi R_c^2$ and is maximized when the area $\sum_{i=1}^k T_i I_i T_{i+1}$ is minimum (figure 6).

$$\begin{aligned} &T_i I_i T_{i+1} \\ &= T_i C T_{i+1} - I_i Y_i T_i - I_i Y_{i+1} T_{i+1} - I_i Y_i C Y_{i+1} \\ &= (2R_c)^2 \cdot \frac{\theta_i}{2} - 2R_c^2 \cdot \frac{\theta_i}{2} - \frac{1}{2}(2R_c \sin \frac{\theta_i}{2})(2R_c \cos \frac{\theta_i}{2}) \\ &= R_c^2(\theta_i - \sin \theta_i) \end{aligned}$$




Fig. 6. Coverage with k nodes placed on the communication perimeter of node X . The shaded area is the total coverage.

$$\begin{aligned} \sum_{i=1}^k T_i I_i T_{i+1} &= R_c^2 \left(\sum_{i=1}^k \theta - \sum_{i=1}^k \sin \theta_i \right) \\ &= R_c^2 \left(2\pi - \sum_{i=1}^k \sin \theta_i \right) \end{aligned} \quad (4)$$

The problem now reduces to finding $\max \sum_{i=1}^k \sin \theta_i$ subject to $\sum_{i=1}^k \theta_i = 2\pi$ and $0 \leq \theta_i \leq 2\pi$. Since \sin is non-negative and concave in $[0, \pi]$ and non-positive in $(\pi, 2\pi]$, it follows that the solution is $\theta_i = \frac{2\pi}{k}$, $1 \leq i \leq k$. \square

This result holds even for the case when $R_s \neq R_c$. This can be shown by considering 3 cases separately: 1) $R_c < R_s$ 2) $R_s < R_c < 2R_s$ and 3) $R_c > 2R_s$. The expressions obtained are involved and the proofs are not included here because of space constraints. This also implies that the result holds when the communication range of all nodes is not the same.

The result from Theorem 3 indicates how a node can locally maximize coverage while satisfying a sector condition. The symmetric nature of the locally optimal placement of neighbors has an interesting consequence. When $k = 3, 4, 6$, the symmetric arrangement of neighbors gives rise to tiling structures which are known to be globally optimal in terms of area coverage. The structures for $k = 3, 4, 6$ can be equivalently described in terms of the sector angle $\theta = \frac{2\pi}{3}, \frac{\pi}{2}, \frac{\pi}{3}$ respectively. It can be verified that the hexagonal tiling ($\theta = \frac{2\pi}{3}$) is an RNG and in this case, $GG \equiv RNG$. This holds for the square tiling ($\theta = \frac{\pi}{2}$) as well. The triangle tiling ($\theta = \frac{\pi}{3}$) is a DelG.

Theorems 1 and 2 provide sector conditions for supergraphs of the corresponding proximity graphs. These conditions however do not predicate sparseness. The tiling graphs have $O(|V|)$ edges and are therefore sparse. While the RNG and GG have spanning ratios of $O(|V|)$ and $O(\sqrt{|V|})$ in general, the spatial arrangement of nodes in the tilings result in constant spanning ratios. The exact ratios can be easily obtained by symmetry arguments and are shown in Table 2.

The analysis of coverage and connectivity was limited to certain values of θ . As a first step towards characterizing NET graphs for general values of θ , in the next section we study topologies resulting from deployment algorithms based on the NET condition.

4. TOPOLOGY CONTROL USING NET GRAPHS

We now describe the use of NET graphs and their properties for topology control. In general, based on the coverage and connectivity requirements of an application, nodes can either be pre-configured for a certain value of θ or they can tune it dynamically. In order to satisfy the NET condition, nodes can then employ power control, sleep scheduling, position control or a combination of these. For instance, each node can start with a low transmission power and increase its transmission power till it has at least one neighbor in every θ sector around it. Similarly, nodes can decide their sleep/wake schedules such that all the nodes that are awake satisfy the NET condition. Power control and sleep scheduling mechanisms have been studied extensively in prior work [1]. Relatively, there has been very little work on position control [16, 17]. Position control is relevant for situations in which deployment of static nodes by an external agent and for self-deployment of mobile nodes. In controlled deployment of a static sensor network, the agent can make a decision on the best location of the next node based on the geometry of the existing network. Self-deploying mobile nodes can use this condition to decide their motion strategy. In all these cases, the coverage can be maximized by choosing, activating or positioning neighbors within each θ sector which are as far apart from each other as possible (i.e., by trying to achieve a symmetric configuration).

It is evident that NET graphs naturally capture the features of all three primary topology control instruments: power level, sleep cycling and position. As illustrated in Table 1, combinations of these mechanisms can be employed to cover all classes of sensor network topologies. Thus, we have arrived at a **unifying framework** for designing mechanisms for completely distributed and tunable topology control for all classes of topologies.

A key requirement in constructing NET graphs is angular information of neighboring nodes. In case of mobile nodes, this is a reasonable assumption because they are usually equipped with ranging sensors for obstacle avoidance.

Name	Degree	K-Connectivity	Number of edges	Spanning Ratio	Proximity Relations
Line Tiling ($\theta = \pi$)	2	1	$O(n) \approx n$	1	RNG, GG
Hexagonal Tiling ($\theta = \frac{2\pi}{3}$)	3	3	$O(n) \approx \frac{3}{2}n$	$\frac{3}{2}$	RNG, GG
Square Tiling ($\theta = \frac{\pi}{2}$)	4	4	$O(n) \approx 2n$	$\sqrt{2}$	RNG, GG
Triangle Tiling ($\theta = \frac{\pi}{3}$)	6	6	$O(n) \approx 3n$	$\frac{2}{\sqrt{3}}$	RNG, GG, DelG

Table 2. Properties of Tiling Graphs

The same is true in case of a static network being deployed by a mobile agent. For uncontrolled static networks, this information can be obtained by estimating the angle-of-arrival of messages [18]. While constructing NET graphs does not require global location information, in cases when such information is available the angular information can be deduced easily.

We now focus on establishing position control as a topology control mechanism. To this end, we demonstrate how the NET condition can be integrated with the deployment algorithms. These algorithms were implemented in the Player/Stage software platform which simulates the behavior of real sensors and actuators with high fidelity [19].

4.1. Incremental Deployment of Static Nodes

Consider a naive incremental approach where a mobile robot deploys static nodes one at a time. The robot looks at a local snapshot of the already deployed nodes and examines them for the NET condition. For each node X , it identifies θ sectors that do not have a neighbor and deploys a new node in that sector. Using theorem 3 as a guideline, it deploys the new node at a distance equal to the communication range from X so that the coverage is maximized from X 's local perspective. The robot does not have any knowledge of its global location and deploys nodes relative to the positions of already deployed nodes. To sense the positions of these nodes, the robot uses a laser range finder which has a small error of $\pm 2^\circ$.

```

input :  $\theta$ 
output: Node Locations
place  $node_1$  at (0,0);
DeployLocations  $\leftarrow$  (NET locations of  $node_1$ );
for  $i=2$  to Num. of nodes do
   $l = \text{pop}(\text{DeployLocations})$ ;
  place  $node_i$  at  $l$ ;
  DeployLocations  $\leftarrow$  (NET locations of
   $node_i$ );
end

```

Algorithm 1: Incremental deployment

Figure 7a shows the topology obtained with $\theta = \frac{\pi}{3}$ for a deployment of 100 nodes. As expected, this topology is the triangle tiling discussed earlier where each (non-

boundary) node has exactly 6 ($= \frac{2\pi}{\theta}$) neighbors. On the other hand, a non-tiling angle like $\theta = \frac{2\pi}{5}$ (figure 8a) results in over-deployment and the average node degree (figure 9c) is greater than 5 ($= \frac{2\pi}{\theta}$). The average coverage (figure 9a) obtained in this case is lesser than the coverage for $\theta = \frac{\pi}{3}$. This is because, the algorithm follows the condition for locally optimizing coverage, which in case of $\theta = \frac{2\pi}{5}$ does not result in the best global coverage. For the tiling angles, the local condition results in globally optimal coverage, as discussed earlier. Increasing the global coverage for the non-tiling angles will involve avoiding over-deployment resulting from blindly following this local condition. Figure 9a also compares the coverage of the incremental deployment with the asymptotic upper bound obtained from theorem 3¹

Figure 9b shows the edge connectivity values for these graphs. By Menger's theorem, the edge-connectivity of a network equals the maximum number of edge-disjoint paths between any two nodes in the network. To avoid edge effects, we ignored all node pairs that contain a boundary node. Connectivity was computed using the network flow routines available in *Mathematica*. It is our conjecture that a NET graph for sector angle θ , the edge-connectivity will be bounded by $\lfloor \frac{2\pi}{\theta} \rfloor$. Figure 9c shows the number of sectors per node that violate the NET condition. These occur only at the boundary nodes.

Figure 10 shows a comparison of the communication graph obtained from deployment with $\theta = \frac{\pi}{3}$ with its corresponding RNG. In 10c, the dotted lines represent the edges in the RNG that are absent in the communication graph. It can be seen that the communication graph differs from the RNG in exactly 3 edges at the boundary of the network. This is because, the boundary nodes do not satisfy the NET condition for RNG, i.e., having at least one node in every $\theta = \frac{2\pi}{3}$ sector. In practice, every network will have boundary nodes that cannot satisfy the NET condition. However, this will only affect the edges incident on the boundary nodes and will not have a significant impact on the network properties.

We repeated the experiments with an additional error introduced in the angle and distance at which the robot de-

¹Consider a node X with neighbors placed symmetrically on its communication range. By accounting for the overlaps within the sensing radius of X , we can calculate the contribution of X to the total coverage of the network. This gives an upper bound on the per node coverage for an infinite network

ploy nodes. The error was modeled as zero-mean Gaussians with standard deviations of 3° in angle and 5% of R_c in position. The topologies obtained are shown in 7b and 8b. Note that in case of the static network, this error is equivalent to the error in angle and position information of neighbors. The topologies obtained are denser than those obtained without error. The coverage and connectivity performance is also close to the earlier deployment without the additional error (figure 9).

Comparison of the communication graph for $\theta = \frac{2\pi}{3}$ with the corresponding RNG (figure 11) shows that in addition to the edges on the boundary, there are only a few edges in the communication graph that are not in the RNG.

4.2. Distributed Deployment of Mobile Nodes

Potential field based algorithms have been widely used for the deployment of mobile networks [20, 21]. These algorithms involve constructing local virtual forces between neighboring robots to encode their desired motion and/or placement patterns. In our algorithm, we use two kinds of forces. The first, $\mathbf{F}_{\text{repel}}$, causes the nodes to repel each other to increase their coverage and the second, $\mathbf{F}_{\text{attract}}$ constrains neighboring nodes to stay connected. By using a combination of these mutually opposing forces, each node maximizes its coverage while maintaining the NET condition of having at least one neighbor in every θ sector.

In a typical mobile deployment scenario all the nodes start clustered together in random positions. In this initial state the network is highly well connected and the NET conditions are satisfied. Every node applies a force of $\mathbf{F}_{\text{repel}} + \mathbf{F}_{\text{attract}}$ on each its neighbors. These forces have inverse square law profiles - $\mathbf{F}_{\text{repel}}$ tends to infinity when the distance between the nodes decreases to zero and $\mathbf{F}_{\text{attract}}$ tends to infinity when the distance between nodes increases to R_c . As a result of these forces, each pair of nodes moves as far away from each other as possible without losing connectivity with each other. After every time step, each node evaluates the contribution of each of its edges towards satisfying the NET condition. An edge that is not necessary to satisfy the condition of either of the nodes it connects is broken by turning off $\mathbf{F}_{\text{attract}}$. As a result of these forces the nodes spread out as far as possible till no more edges can be broken.

```

input :  $\theta$ 
output: Velocity
while deployment not done do
  read locations of neighbors;
  for each edge do
    if edge is necessary for NET condition
      then
        |  $\mathbf{F}_{\text{net}} = \mathbf{F}_{\text{attract}} + \mathbf{F}_{\text{repel}}$ ;
      end
    else
      |  $\mathbf{F}_{\text{net}} = \mathbf{F}_{\text{repel}}$ ;
    end
     $acc+ = \frac{F_{\text{net}}}{mass}$ ;
  end
   $vel_{\text{new}}+ = acc * \Delta\text{Time} - v * vel_{\text{old}}$ ;
  if no significant change in velocity over
  time then
    | deployment done;
  end
end

```

Algorithm 2: Distributed deployment

In the simulator, each node is an omni-directional robot that uses laser range finders for obstacle avoidance. The laser range finders return the positions of neighboring nodes with an error of $\pm 2^\circ$ in the angle and negligible error in distance. In our experiments, communication between nodes was abstracted out using shared variables in the simulation program.

In all our experiments the distributed algorithm was significantly faster than the incremental approach and converged without any oscillations. Figures 7c and 8c show some example topologies. These topologies are significantly denser (figure 9c) than the topologies obtained in incremental deployment. This is expected because the algorithm is conservative - it trades off sparseness in order to guarantee that the NET condition is satisfied. In our experiments, the NET condition was satisfied at all the interior nodes. The distributed algorithm has a lower coverage but greater connectivity as compared to the incremental approach (figure 9a).

For $\theta = \frac{2\pi}{3}$, the communication graph contains the RNG (figure 12). In contrast to the incremental approach, we observe that there are no edges at the boundary that are present in the RNG and are not contained in the communication graph. This is because in the distributed approach, the boundary nodes are constrained in their movement in order to satisfy the NET condition.

Even in the presence of boundary nodes in real networks, these results validate the assertion in Theorem 1 that the communication graph will contain the RNG for $\theta \leq \frac{2\pi}{3}$. Also, the communication graph contains only a few non-boundary edges that are not in the RNG. Hence these graphs will inherit the sparseness properties of RNG.




Fig. 7. Topologies obtained for $\theta = \frac{\pi}{3}$ with 100 nodes and $R_s = R_c = 8m$ using a) Incremental deployment with small error b) Incremental deployment with large error and c) Distributed deployment







Fig. 8. Topologies obtained for $\theta = \frac{2\pi}{5}$ with 100 nodes and $R_s = R_c = 8m$ using a) Incremental deployment with small error b) Incremental deployment with more error and c) Distributed deployment




(a)



(b)



(c)



(d)

Fig. 9. Performance of the Incremental and Distributed deployment Algorithms for a deployment of 100 nodes in terms of (a) Coverage, (b) Edge Connectivity (c) Average Degree and (d) NET condition satisfaction




Fig. 10. Comparison of communication graph and corresponding RNG [**Incremental Deployment, 100 nodes, $\theta = \frac{2\pi}{3}$, small error**] a) communication graph b) RNG c) Dashed lines indicate edges in RNG that are not in communication graph. Dark lines indicate edges in communication graph that are not in RNG (none in this case).




Fig. 11. Comparison of communication graph and corresponding RNG [**Incremental Deployment, 100 nodes, $\theta = \frac{2\pi}{3}$, large error**] a) communication graph b) RNG c) Dashed lines indicate edges in RNG that are not in communication graph. Dark lines indicate edges in communication graph that are not in RNG.




Fig. 12. Comparison of communication graph and corresponding RNG [**Distributed Deployment, 100 nodes, $\theta = \frac{2\pi}{3}$**] a) communication graph b) RNG c) Dashed lines indicate edges in RNG that are not in communication graph. Dark lines indicate edges in communication graph that are not in RNG.

The algorithms presented serve the purpose of illustrating the use of NET graphs for tunable topology control. They do not optimize the coverage due to over-deployment. However, the insights gained can be used to design more sophisticated algorithms.

5. RELATED WORK

There has been a lot of work on topology control of static and ad-hoc mobile networks in the past [1, 22]. Our work is closest in spirit to the “bottom-up” approach to topology control discussed in [8]. Most earlier approaches begin with the assumption of a well connected graph and prune it to obtain a sparse, connected subgraph. In contrast, we prove that satisfying certain local conditions can guarantee global connectivity and coverage properties. In [8], it is shown that if each node has one neighbor in a every π sector around it, then the network is guaranteed to be 1-connected.

Power control techniques for topology control have been studied extensively for ad hoc wireless networks. Centralized algorithms to minimize the maximal power used per node while maintaining the (bi)connectivity of the network have been proposed in [23]. This work also introduced distributed heuristics for mobile networks. However, these heuristics cannot guarantee the preservation of network connectivity. In [24] a distributed algorithm for constructing an RNG has been proposed. Each node increases its transmit power till its neighbors cover the 2π region around it. We show that to obtain an RNG it is sufficient to have one neighbor in each $\frac{2\pi}{3}$ sector and present sector based conditions for other proximity graphs. Our work is similar to the CBTC algorithm [2]. In CBTC, every node divides the space around it into cones of angle α and increases its transmission power till in each cone it can reach a neighbor or till it reaches its maximum transmission power. It has been shown that, if the network is connected when all nodes operate at maximum transmission power, then for $\alpha \leq \frac{5\pi}{6}$, CBTC is guaranteed to result in a connected graph. The key difference is that CBTC assumes the existence of a connected graph and provides ways to prune it while retaining connectivity. On the other hand, the NET condition is a necessary condition that can guarantee global network properties. In such a scenario, a sector angle of π is sufficient to guarantee connectivity [8].

Sleep scheduling or on/off control is the principal topology control technique for over-deployed static networks. SPAN [3] is an energy efficient algorithm for topology maintenance, where nodes decide whether to sleep or join the backbone (a connected dominating set) based on connectivity information supplied by a routing protocol. In ASCENT [25], each node measures the number of neighbors and packet loss locally and makes a decision to join the network topology or to perform some form of adaptation

(e.g. reducing its duty cycle to save energy). In SPAN and ASCENT, the primary goal is to maintain connectivity in the network while we also seek to maintain a sparse topology and increase sensing coverage. CCP [26] is a sleep scheduling protocol to achieve tunable degrees of coverage and connectivity. The degree of coverage is defined as the minimum number of nodes that cover any point in network region. Therefore, achieving different degrees of coverage and connectivity are not opposing goals.

In the context of networks with controllable placement, the problem of topology control is closely linked to the problem of deployment. Several deployment strategies have also been proposed in the Robotics literature. An algorithm for incremental deployment team for mobile robots is presented in [27]. It maximizes the sensing coverage while simultaneously ensuring that the robots maintain line-of-sight connectivity. A potential field based self-deployment algorithm for a group of mobile nodes is presented in [21]. It maximizes coverage with the constraint that each node has at least k neighbors, where k is an input parameter to the algorithm. These algorithms maximize coverage but do not provide guarantees on connectivity.

In [16] a robot deploys a network with a simple grid topology using the deployed nodes as landmarks without using a map of the environment or localization. In [17] a static sensor network is deployed using an unmanned aerial vehicle (UAV). Typically, such algorithms have focussed on the control strategies of the robot rather than the properties of the network. By providing rules that can be easily combined with robot controllers, our work provides a means of integrating the two objectives.

6. CONCLUSION AND FUTURE WORK

We present a classification of sensor network topologies on the basis of the node mobility (static or mobile) and the nature of deployment (controlled or uncontrolled). The main contribution of this paper is a unifying framework for designing mechanisms for completely distributed and tunable topology control for all classes of topologies. It is based on a simple, local and geometric Neighbor-Every-Theta (NET) condition. We show that it is possible to obtain tunable coverage and connectivity tradeoffs by varying a single parameter - the sector angle θ . The NET condition results from our analysis of proximity graphs as representative of communication graphs of wireless networks. Proofs of local, geometric conditions that guarantee relative neighborhood, Gabriel and Delaunay graphs are presented. We also prove the symmetric placement condition for maximizing coverage under the NET condition. These findings could well be of independent interest. The NET based framework can support a number of existing power control and sleep scheduling schemes suitable for uncontrolled deployments. The use

of distributed algorithms for controlled deployment of both static and mobile nodes is simulated to concretely demonstrate use of the local geometric rules to implement global coverage and connectivity tradeoffs.

We are currently analyzing sparseness and spanner properties of the topologies resulting from the deployment algorithms. Proof of the conjecture on the k -connectivity of NET graphs is also of interest. Extensions of results for non-circular communication ranges will also be investigated.

Acknowledgements

The authors would like to thank Dr. Raissa D'Souza at Microsoft Research Labs for reading the manuscript and giving helpful feedback.

7. REFERENCES

- [1] P. Santi, "Topology control in wireless ad hoc and sensor networks," Technical Report IIT-TR-04/2003, Institute for Informatics and Telematics, Pisa, Italy, 2003.
- [2] R. Wattenhofer, L. Li, P. Bahl, and Y. M. Wang, "A cone-based distributed topology-control algorithm for wireless multi-hop networks," *IEEE/ACM Transactions on Networking*, Feb 2005.
- [3] B. Chen, K. Jamieson, H. Balkrishnan, and R. Morris, "Span: an energy-efficient coordination algorithm for topology maintenance in ad hoc wireless networks," *ACM Wireless Networks Journal*, vol. 8, no. 5, 2002.
- [4] W. Kaiser, G. Pottie, M. Srivastava, G. S. Sukhatme, J. Villaseñor, and D. Estrin, "Networked infomechanical systems (nims) for ambient intelligence," *Ambient Intelligence*, Springer-Verlag, 2004.
- [5] N. Xu, S. Rangwala, K. Chintalapudi, D. Ganesan, A. Broad, R. Govindan, and D. Estrin, "A wireless sensor network for structural monitoring," in *ACM Conference on Embedded Networked Sensor Systems (Sensys'04)*, November 2004, pp. 13–24.
- [6] UC Berkeley and MLB Co., "29 palms fixed/mobile experiment," <http://robotics.eecs.berkeley.edu/~pister/29Palms0103>, last visited Feb 2005.
- [7] P. Juang, H. Oki, Y. Wang, M. Martonosi, L. Peh, and D. Rubenstein, "Energy-efficient computing for wildlife tracking: Design tradeoffs and early experiences with zebrantet," in *Tenth International Conference on Architectural Support for Programming Languages and Operating Systems*, San Jose, CA, Oct 2002.
- [8] R. D'Souza, D. Galvin, C. Moore, and D. Randall, "A local topology control algorithm that guarantees global connectivity and geometric routing," submitted for publication, 2004.
- [9] E. H. Jennings and C. M. Okino, "Topology control for efficient information dissemination in ad-hoc networks," in *International Symposium on Performance Evaluation of Computer and Telecommunication Systems*, July 2002.
- [10] B. Karp and H.T. Kung, "Greedy perimeter stateless routing for wireless networks," in *6th Annual International Conference on Mobile Computing and Networking, MobiCom'00*, Boston, MA, August 2000, ACM/IEEE, pp. 243–254.
- [11] J. Gao, L. J. Guibas, J. E. Hershberger, L. Zhang, and A. Zhu, "Geometric spanner for routing in mobile networks," in *2nd ACM international symposium on Mobile ad hoc networking computing, MobiHoc'01*, Long Beach, CA, 2001, pp. 45–55.
- [12] J. Cortes, S. Martinez, and F. Bullo, "Robust rendezvous for mobile autonomous agents via proximity graphs in d dimensions," *IEEE Transactions on Automatic Control*, in submission.
- [13] J. Zhao and R. Govindan, "Understanding packet delivery performance in dense wireless sensor networks," in *The First ACM Conference on Embedded Networked Sensor Systems (Sensys'03)*, Nov 2003.
- [14] M. Zuniga and B. Krishnamachari, "Analyzing the transitional region in low power wireless links," in *First IEEE International Conference on Sensor and Ad hoc Communications and Networks (SECON)*, Santa Clara, CA, October 2004.
- [15] R. Diestel, *Graph Theory, Graduate Texts in Mathematics, second edition*, vol. 173, Springer Verlag, New York, NY, 2000.
- [16] M. Batalin and G. Sukhatme, "Coverage, exploration and deployment by a mobile robot and communication network," *In Telecommunication Systems Journal, Special Issue on Wireless Sensor Networks*, vol. 26, no. 2, pp. 181–196, 2004.
- [17] P. I. Corke, S. E. Hrabar, R. Peterson, D. Rus, S. Sarpalli, and G. S. Sukhatme, "Autonomous deployment and repair of a sensor network using an unmanned aerial vehicle," in *IEEE International Conference on Robotics and Automation*, April 2004, pp. 3602–3609.
- [18] K. Krizman, T. E. Biedka, and T. S. Rappaport, "Wireless position location: fundamentals, implementation

strategies and source of error,” in *IEEE 47th Vehicular Technology Conference*, 1997, pp. 919–923.

- [19] B. Gerkey, R. T. Vaughan, A. Howard, G. Sukhatme, and M. J. Mataric, “Most valuable player: A robot device server for distributed control,” in *IEEE/RSJ International Conference on Intelligent Robots and Systems, IROS’02*, 2002, pp. 299–308.
- [20] A. Howard, M. J. Mataric, and G. S. Sukhatme, “Mobile sensor network deployment using potential fields: A distributed, scalable solution to the area coverage problem,” in *Distributed Autonomous Robotic Systems*, 2002, pp. 299–308.
- [21] S. Poduri and G. Sukhatme, “Constrained coverage for mobile sensor networks,” in *IEEE International Conference on Robotics and Automation*, May 2004, pp. 165–172.
- [22] G. Srivastava, P. Boustead, and J. F. Chicharo, “A comparison of topology control algorithms for ad-hoc networks,” in *Australian Telecommunications Networks Applications Conference, ATNAC*, Melbourne, 2003.
- [23] R. Ramanathan and R. Rosales-Hain, “Topology control of multihop wireless networks using transmit power adjustment,” in *IEEE INFOCOM*, 2000, pp. 404–413.
- [24] S. A. Borbash and E. H. Jennings, “Distributed topology control algorithm for multihop wireless networks,” in *World Congress on Computational Intelligence*, May 2002.
- [25] A. Cerpa and D. Estrin, “Ascent: Adaptive self-configuring sensor networks topologies,” *IEEE Transactions Journal on Mobile Computing Special Issue on Mission-Oriented Sensor Networks*, vol. 3, no. 3, pp. 272–285, July-September 2004.
- [26] X. Wang, G. Xing, Y. Zhang, C. Lu, R. Pless, and C. Gill, “Integrated coverage and connectivity configuration in wireless sensor networks,” in *First ACM Conference on Embedded Networked Sensor Systems, Sensys’03*, Nov 2003.
- [27] A. Howard, M. J. Mataric, and G. S. Sukhatme, “An incremental self-deployment algorithm for mobile sensor networks,” *Autonomous Robots, Special Issue on Intelligent Embedded Systems*, vol. 13, no. 2, pp. 113–126, 2002.