

Toward Interactive Reaching in Static Environments for Humanoid Robots

Evan Drumwright
Interaction Lab/USC Robotics Research Labs
University of Southern California
Los Angeles, CA 90089-0781 USA
drumwrig@robotics.usc.edu

Victor Ng-Thow-Hing
Honda Research Institute USA
Mountain View, CA, 94041 USA
vng@honda-ri.com

Abstract—Reaching is a critical task for humanoid robots, requiring the application of state-of-the-art algorithms for motion planning and inverse kinematics. Practical algorithms for solving these subproblems are currently not complete, offering *resolution completeness* or *probabilistic completeness* instead. While this lesser provision of completeness is acceptable in many cases, naively combining state-of-the-art approaches in motion planning and inverse kinematics can lead to a method that provides no measure of completeness. We present a resolution complete solution to the reaching problem for humanoid robots in static environments, and evaluate it against two other methods using a kinematically simulated humanoid in a virtual environment.

I. INTRODUCTION

Reaching is a critical task for humanoid robots. There has been recent progress in inverse kinematics [1], [2] and motion-planning [3], [4], subproblems key to performing the reaching task. However, these subproblems have been studied in relative isolation. There has been relatively little work [5], [6], [7] attempting to address these problems in the context of the reaching task.

Although both inverse kinematics and motion planning are active areas of research, current approaches toward both problems are at best *probabilistically complete* or *resolution complete*. The former measure indicates that as the number of random samples tends to infinity, a solution will be found if it exists; similarly, a method is resolution complete if a solution will be found (again, assuming that there is a solution) as the number of samples selected deterministically (e.g., by covering the configuration space in a grid or *quasi-random* sequence) tends to infinity. Note the weaker concept of completeness implied by these definitions; in contrast to a complete method, probabilistically / resolution complete methods are unable to determine whether a solution exists.

Probabilistic completeness or resolution completeness is generally sufficient for solving inverse kinematics and motion planning problems in isolation. However, the combination of two incomplete methods in the context of the reaching task can yield a poor approach. The naive approach to the reaching task uses inverse kinematics to determine a valid joint-space goal configuration and motion planning to find a path from the current joint space configuration to the goal configuration. Unfortunately, this approach is unable to determine when there is no path to a given configuration; if the method is unable

to quickly find a solution, should it expend more time trying to find a valid path or should it try another IK solution? This difficulty is illustrated by Figure 1.

This paper presents an algorithm for reaching that is resolution complete. We compare this algorithm to two other methods: one based on a *lazy probabilistic roadmap* (Lazy PRM) [8] and another based on Ariadne’s Clew algorithm [7].

II. STATIC REACH IN STATIC ENVIRONMENT

This paper focuses on the Static Reach problem in a Static Environment (SRSE). SRSE focuses on attempting to reach to unmoving objects (the first *static* in SRSE) in environments that are essentially unchanging (the second *static* in SRSE). Though it would be desirable to handle moving objects and dynamic environments, addressing this ability would add considerable complexity. Indeed, Reif and Sharir proved that motion planning in the presence of moving obstacles is PSPACE-complete [9].

Given: an initial configuration of the robot $\mathbf{q}_{initial}$, a description of the valid configuration space of the robot \mathcal{C}_{free} , and a goal end-effector configuration \mathbf{x}_{goal} .

Find: a set of joint-space trajectories $\tau : [0, 1] \rightarrow \mathbb{R}^n$ such that $\tau(0) = \mathbf{q}_{initial}$, $f(\tau(1)) = \mathbf{x}_{goal}$ (where $f : \mathbb{R}^n \rightarrow \mathbb{R}^6$ is the direct kinematics function that transforms joint-space configurations to operational-space configurations). Also, each posture described by every point in time of the joint-space trajectories must be collision-free (i.e., $\forall \alpha \in [0, 1], \tau(\alpha) \in \mathcal{C}_{free}$).

III. BACKGROUND

A. Sample-based motion planning

The problem of planning a motion amongst static obstacles is called the Static Mover’s Problem [10] or the General Motion Planning Problem [11], and has been shown to be PSPACE-hard by Reif [10].

One well known solution to the general motion planning problem is Canny’s Roadmap Algorithm [12], which exhibits running time exponential in the degrees-of-freedom of the robot and polynomial in the number of polynomials and degree used to semi-algebraically represent the subset of configuration space populated by obstacles. Lindemann and LaValle [13] note that Canny’s algorithm, like most combinatorial motion

planning methods, employs techniques that are very difficult to implement correctly.

In contrast to correct motion planning algorithms, *sample-based* methods do not attempt to model the robot and the obstacles explicitly. Rather, these methods sample the configuration space, attempting to travel from the initial state to the goal state using collision-free samples (determined either randomly or deterministically) in the configuration space. Sample-based algorithms have proven to be successful in solving motion-planning problems within humanoid robotics [14], [15].

The seminal sample-based planning method is the probabilistic roadmap (PRM) [16], which generates random, collision-free samples and attempts to connect them. After the initial and goal samples are connected, a graph search algorithm is used to find a path between them. Our work utilizes one variant of the PRM, the *Lazy PRM*, which delays collision checking until a connected path is found, and then invalidates and augments the roadmap as necessary. This modification to the original PRM algorithm tends to work well in relatively uncluttered environments, as samples are not generated needlessly.

The most effective method for motion planning is currently the *rapidly-exploring dense tree* (RDT) [11], also known as the *rapidly-exploring random tree* (RRT) [17] when samples are randomly selected. RDTs exhibit *Voronoi bias*; as Lindemann and LaValle note [18], RDTs search incrementally biased toward those nodes with the largest Voronoi regions. Thus an RDT is biased to search in the largest unexplored volume of configuration space. This efficiency stands in stark contrast to unguided approaches like probabilistic roadmaps (PRMs) [19] that distribute samples uniformly across the configuration space.

B. Inverse kinematics

The state-of-the-art in inverse kinematics algorithms for robots with redundant manipulators is called *resolved motion rate control* (RMRC), and is performed using the Jacobian [20] of a manipulator’s end effector configuration with respect to its joint space configuration. The simplest method for performing inverse kinematics using RMRC for redundant manipulators is called the *Jacobian pseudo-inverse* method, and is computed using the pseudo-inverse of the manipulator Jacobian. It is possible to utilize the *nullspace* of the inverse kinematics solutions in order to utilize the redundant degrees-of-freedom. One possible use of the nullspace is obstacle avoidance: Sciavicco and Siciliano [21] present a simple method that avoids a single obstacle and Maciejewski and Klein [22] give a more involved method that avoids the closest obstacle, albeit at the expense of fairly significant computation.

The manipulator Jacobian can become rank-deficient in the presence of parametric singularities or workspace singularities. We utilize the *damped least-squares inverse* [23] to mitigate this problem. The three methods described in Section V use this numerically robust method, the Jacobian least-squares pseudoinverse, for inverse kinematics.

C. SRSE in robotics

Ahuactzin and Gupta [7] have previously attempted to approach the SRSE problem for redundant manipulators (though not robots with branching kinematic structures, like humanoids). However, their research was conducted prior to the development of the RRT algorithm, and is consequently based on a less efficient motion planning method (the Ariadne’s Clew algorithm [24]). Additionally, the authors utilize an iterative inverse kinematics method that attempts to minimize a cost function from the current operational-space configuration to the goal operational-space configuration. Ahuactzin and Gupta note that this gradient-descent method obviates computing a manipulator Jacobian; however, its convergence properties are not understood and it lacks a means to handle manipulator singularities.

Døring et al. [25] describe an algorithm based on the *Fuzzy Lazy PRM* (a modification to the method described in Section III-A) that utilizes inverse kinematics to reach operational-space goals with a redundant manipulator. Unfortunately, a detailed assessment of this method has not been undertaken, and the algorithm in Døring et al. is not presented sufficiently to allow for implementation here. We do utilize an idea from Døring et al. in the development of our RDT-IK algorithm, that of calling the inverse kinematics subroutine only when the operational-space configuration of a sample is sufficiently close to the goal.

Kagami et al. [15] have demonstrated a humanoid robot grasping a bottle utilizing stereo vision and the RRT algorithm. This work demonstrated the viability of motion planning algorithms in the domain of physical (rather than only simulated) humanoid robots. The humanoid used in Kagami et al. work utilized a “black box” inverse kinematics algorithm and made no claims on completeness; in contrast, our work provides a resolution-complete method for reaching on general, redundant humanoid robots.




Fig. 1. Pathological case of difficulty finding a valid plan due to numerous valid IK solutions. The robot is depicted by the red circle and uses a planar manipulator. It has four DOF: translation of the base in the plane and two revolute joints for the manipulator. The goal is to place the tip of the manipulator on the center of the red dot (making the robot’s manipulator redundant with respect to the task). This problem is difficult because there are many collision-free IK solutions, only a few of which can be used to find a collision-free plan from the robot’s initial configuration.

IV. APPROACH

Solving SRSE for robots with redundant manipulators is more challenging than solving the General Motion Planning problem because SRSE must find a collision-free goal (IK solution) configuration. Additionally, there may be multiple IK solutions, perhaps only one of which is reachable from the initial configuration of the robot.

It is natural to wonder whether multiple solutions might lead to a tractable solution using a complete method like Canny’s Roadmap Algorithm. Unfortunately, the computational expense of that algorithm (and others like it) lies not in trying to find a solution, but in performing a *cellular decomposition* of the configuration space. Once such a decomposition is performed, the cost of planning a motion from one point to another in the configuration space is cheap, requiring only a breadth-first or depth-first search of a sparse graph.

Complete methods also exhibit another difficulty with regard to this problem. IK solutions are rarely able to be represented using *semi-algebraic* sets (point sets composed of intersections between primitive shapes). Indeed, the topology of a space of IK solutions is typically very complex, requiring the testing of every IK solution as a possible solution to SRSE. It is currently unclear how to represent IK solutions for most redundant manipulators analytically, much less test a range of solutions for collision.

Sample-based methods are currently the most viable approach to solving SRSE. In fact, a sample-based method can be used to reach an operational-space goal with only a small modification. When a configuration-space sample $q \in \mathcal{C}_{free}$ is generated by this modified method, $f(q)$ is compared to the operational space goal; if $f(q)$ is sufficiently close, q is added to a list of goals. The algorithm continually attempts to connect to the goal configurations in this list. This method is resolution complete but is impractical, because it is analogous to attempting to perform inverse kinematics using sampling alone.

The RDT-IK algorithm was designed to be resolution complete, generate nodes in configuration space in an efficient manner, and provide a good balance between exploration and exploitation. It is a slightly modified version of the standard RRT algorithm, presented as Algorithm 1. This simple algorithm has proven empirically to be the fastest of multiple variants that we have tested, including several based on multiple trees (i.e., multidirectional search).

Algorithm 2 begins by initializing a single tree from the initial configuration of the robot (line 1) and initializing the set of goal states to the empty set (line 2). Next, a loop begins that is used to generate up to k IK solutions and up to k nodes in the tree.

Within the loop, a sample is selected from one of the set of goals (if available, lines 4–5) or drawn from a *quasi-random* sequence (e.g., Halton [26]) or random distribution (line 7). Lines 8–12 expand the tree toward the random sample or goal state. Line 13 checks whether a solution has been found. Line 15 check whether the new vertex in the tree is sufficiently

Algorithm 1 $\text{RRT}(q_{initial}, q_{goal}, k, v, \alpha)$ algorithm for motion planning. k is the maximum number of nodes to create. v is the connection frequency (i.e., the frequency of attempting a connection to the goal state). $\alpha : \mathbb{I} \rightarrow \mathbb{R}^n$ is a function that samples the configuration space of the robot. $\mathcal{B} : [0, 1] \rightarrow \{0, 1\}$ is a function that samples from a Bernoulli distribution, simulating tossing a biased coin.

```

1:  $T.\text{init}(q_{initial})$ 
2: for  $i = 1 \dots k$  do
3:   if  $\mathcal{B}(v) = 1$  then
4:      $\mathbf{x} = \mathbf{q}_{goal}$ 
5:   else
6:      $\mathbf{x} = \alpha(i)$ 
7:    $q_n \leftarrow \text{NEAREST}(T, \mathbf{x})$ 
8:    $q_s \leftarrow \text{STOPPING-CONFIGURATION}(q_n, \mathbf{x})$ 
9:   if  $q_s \neq q_n$  then
10:     $T.\text{add-vertex}(q_s)$ 
11:     $T.\text{add-edge}(q_n, q_s)$ 
12:    if  $q_s = \mathbf{q}_{goal}$  then
13:      return  $T$ 
14: return failure

```

close to the operational-space goal; if so, inverse kinematics using RMRC (line 16) is conducted from this vertex. If inverse kinematics converges to a collision-free solution, the generated configuration is added to the list of goals (line 17).




Fig. 2. A depiction of the NEAREST operation. The NEAREST operation finds the closest node in the *span* of a tree. The blue node is the sample, the black nodes are nodes in the tree, and the red node is that returned by NEAREST. In the figure on the left, the sample is nearest to a node in the tree. In the figure on the right, the sample is nearest a point on a line segment defined by two nodes in the tree; in that case, a new node is created (the red node).

V. EXPERIMENTS

A. Methods

The RDT-IK algorithm was tested against two alternate approaches: the method of Ahuactzin and Gupta [7] and a simple method based on the Lazy PRM [8]. These two methods are described briefly below.

1) *The Clew-IK method*: The method of Ahuactzin and Gupta, henceforth referred to as *Clew-IK*, is a probabilistically complete method for reaching to an operational-space target.




Fig. 3. A depiction of the STOPPING-CONFIGURATION operation. The STOPPING-CONFIGURATION operation determines the point between the sample and the node found by NEAREST closest to the sample while ensuring that the linear path between the node found by NEAREST and the aforementioned point is collision-free.

Algorithm 2 RDT-IK($\mathbf{x}_G, \mathbf{q}_{initial}, k, \epsilon, \nu, \alpha$). \mathbf{x}_G is the operational-space goal configuration. k is the maximum number of nodes to create. ϵ is the operational-space tolerance below which a connection is attempted from a state in configuration space. ν is the connection frequency (i.e., the frequency of attempting a connection to the goal state). $\alpha : \mathbb{I} \rightarrow \mathbb{R}^n$ is a function that samples the configuration space of the robot. $\mathcal{B} : [0, 1] \rightarrow 0, 1$ is a function that samples from a Bernoulli distribution, simulating tossing a biased coin. SELECT chooses the goal configuration that has had the fewest number of attempted connections.

```

1:  $T.\text{init}(\mathbf{q}_{initial})$ 
2:  $G \leftarrow \emptyset$ 
3: for  $i = 1 \dots k$  do
4:   if  $G \neq \emptyset$  and  $\mathcal{B}(\nu) = 1$  then
5:      $\mathbf{y} = \text{SELECT}(G)$ 
6:   else
7:      $\mathbf{y} = \alpha(i)$ 
8:    $\mathbf{q}_n \leftarrow \text{NEAREST}(T, \mathbf{y})$ 
9:    $\mathbf{q}_s \leftarrow \text{STOPPING-CONFIGURATION}(\mathbf{q}_n, \mathbf{y})$ 
10:  if  $\mathbf{q}_s \neq \mathbf{q}_n$  then
11:     $T.\text{add-vertex}(\mathbf{q}_s)$ 
12:     $T.\text{add-edge}(\mathbf{q}_n, \mathbf{q}_s)$ 
13:    if  $\mathbf{q}_s = \mathbf{y}$  and  $\mathbf{y} \in G$  then
14:      return success
15:    if  $\|f(\mathbf{q}_s) - \mathbf{x}_G\| < \epsilon$  then
16:       $\mathbf{q}_{new} \leftarrow f^{-1}(\mathbf{q}_s, \mathbf{x}_G)$ 
17:      if  $\mathbf{q}_{new} \neq \text{failure}$  then
18:         $G \leftarrow G \cup \mathbf{q}_{new}$ 
19:  return failure

```

It is based on Ariadne’s Clew algorithm [24], and functions by modifying a known collision-free sample (initially the starting configuration) in an incremental manner. An iterative inverse kinematics algorithm is performed from every new sample generated. The Clew-IK method is implemented as described in [7] with one exception. The iterative inverse kinematics method provided by Ahuactzin and Gupta exhibits poor convergence empirically. We replaced their IK method with the damped Jacobian pseudo-inverse algorithm described in Section III-B. Note that the Clew-IK method, unlike the Lazy PRM and RDT-IK methods, handles manipulators with




Fig. 4. The kinematically simulated humanoid used in our experiments

serial kinematic structures only; this requirement forced us to “lock” most of the degrees-of-freedom in our simulated robot when performing the empirical evaluation.

2) *The Lazy PRM + IK method:* The Lazy PRM + IK method is a simple, incomplete method that operates in two phases. The first phase attempts to find a collision-free inverse kinematics solution. The second attempts to connect to the IK solution using motion-planning. The Lazy PRM + IK method is incomplete due to its phased operation; if the IK solution generated in the first phase is unreachable by the motion planner, the method will fail even if a solution exists. The rationale behind evaluating this method is twofold: the IK method should steer toward a goal configuration rapidly and the Lazy PRM algorithm tends to perform well in relatively sparse environments (such as the ones utilized in the bulk of the experimental trials).

B. Experimental setup

All three methods were tested on the 51 DOF kinematically-simulated humanoid (six DOF base, seven DOF arms, five DOF legs, three DOF head, and 9 DOF back) shown in Figure 4; only a single arm, the base, and the back were employed in these experiments for a total of 22 DOF. Each method was given a maximum of one minute to find a solution; we wished to limit the time in order to gauge the applicability of the methods toward interactive applications (though one minute is at the upper limit of interactivity).

Each trial was executed under different conditions; the number, size, and position of obstacles as well as the initial humanoid configuration and goal task were variable. The initial configuration of the humanoid was confirmed to be collision-free; additionally, it was verified that there existed at least one collision-free joint-space configuration of the robot

TABLE I
RESULTS FOR THE THREE ALGORITHMS OVER 1670 TRIALS

Method	Successes
RDT-IK	730 (43.7%)
Clew-IK	550 (32.9%)
Lazy PRM+IK	101 (6.0%)

that could reach the operational-space goal. Note, however, that there was no guarantee that a viable path existed between the initial configuration and goal task; it is likely that in many scenarios, no solution existed.

Figure 5 depicts the humanoid within two environments. Unfortunately, the accuracy of simulating a human environment with floating obstacles is unknown. However, the number of obstacles in the experiments is uniformly distributed between zero and twenty-five. By varying the size, location, and number of obstacles in this manner, we hoped to extensively test the three methods under a wide range of conditions.

All experiments were run on a 2.2GHz AMD Athlon 64 machine.

C. Experimental results

Table I summarizes the experimental results over 1670 trials. As previously noted, a method was considered to be successful over a trial if it found a solution within one minute. The RDT-IK algorithm clearly performs the best, most likely due to the efficient sampling of the collision-free configuration space. Somewhat surprising is the dismal performance of the Lazy PRM + IK method; analysis indicates that this method expends the bulk of its effort on generating a collision-free IK solution, and is therefore allocated little time to perform motion planning.

The implication is that effective performance on the reaching task for humanoid robots is within a few generations of microprocessor technology. The most recent advances in CPU technology are in the area of multi-core design rather than accelerated clock speed. It is worth considering the future of the RDT-IK algorithm on anticipated platforms. The base RRT algorithm is challenging to parallelize; naive attempts result in inefficient trees. In contrast, it is relatively simple to make a parallel implementation of RDT-IK. Inverse kinematics can run in one process, RDT planning in another, and connection attempts to goals in a third. If more than three processors or cores are available, multiple IK and goal connection processes can run concurrently without concern of interference.

VI. CONCLUSION

We presented a probabilistically complete algorithm for reaching on a humanoid robot with degrees-of-freedom redundant to the task. We assume that the object to which we are reaching is not moving and the environment is unchanging. Given these constraints, we showed that our algorithm is capable of reaching to a target in a cluttered environment much faster than competing methods. Finally, we illustrated that this algorithm is nearly fast enough for interactive operation,




Fig. 6. A depiction of a run of the RDT-IK algorithm on a contrived problem. Obstacles are drawn using black rectangles, the inverse kinematics goals are depicted by the interior of the green circle in the lower right-hand corner, and the initial state is at the upper left-hand corner. The algorithm finds a path between the initial state and the set of goal states efficiently: the nodes in the tree are drawn in red.

and will truly become viable given short-term microprocessor trends.

REFERENCES

- [1] G. Tevatia and S. Schaal, "Inverse kinematics for humanoid robots," in *Proc. of IEEE Intl. Conf. on Robotics and Automation*, San Francisco, CA, 2000.
- [2] D. Tolani, A. Goswami, and N. Badler, "Real-time inverse kinematics techniques for anthropomorphic limbs," *Graphical Models*, vol. 62, no. 5, pp. 353–388, Sep 2000.
- [3] G. Varadhan and D. Manocha, "Star-shaped roadmaps – a deterministic sampling approach for complete motion planning," in *Proc. of Robotics: Science and Systems*, 2005.
- [4] B. Burns and O. Brock, "Toward optimal configuration space sampling," in *Proc. of Robotics: Science and Systems*, 2005.
- [5] T. Lozano-Pérez, J. L. Jones, E. Mazer, and P. A. O'Donnell, "Task-level planning of pick-and-place robot motions," *Computer*, vol. 22, no. 3, pp. 21–29, 1989.
- [6] C. Lück and S. Lee, "Global path planning of redundant manipulators based on self-motion topology," in *Proc. of the IEEE Intl. Conf. on Robotics and Automation (ICRA)*, 1994, pp. 372–377.
- [7] J. M. Ahuactzin and K. Gupta, "A motion planning based approach for inverse kinematics of redundant robots: The kinematic roadmap," in *Proc. IEEE Intl. Conf. on Robotics and Automation (ICRA)*, Albuquerque, NM, 1997, pp. 3609–3614.
- [8] R. Bohlin and L. Kavraki, "Path planning using lazy prm," in *Proc. of the IEEE Conf. on Robotics and Automation (ICRA)*, 2000.
- [9] J. H. Reif and M. Sharir, "Motion planning the presence of moving obstacles," *Journal of the Association of Computing Machinery*, vol. 41, pp. 764–790, 1994.
- [10] J. H. Reif, "Complexity of the mover's problem and generalizations," in *IEEE Symposium on Foundations of Computer Science*, San Juan, Puerto Rico, 1979, pp. 421–427.
- [11] S. LaValle, *Planning Algorithms*. Cambridge University Press, 2006.
- [12] J. F. Canny, *The Complexity of Robot Motion Planning*. Cambridge, MA: MIT Press, 1988.




Fig. 5. Depictions of the humanoid within two environments, one sparse and one highly cluttered. Each series of three figures depicts (from left to right), the initial humanoid configuration, the target (right) hand configuration, and the determined solution. The lines in the solution figures (c) and (f) depict the operational-space paths of the wrist and elbow, respectively, during the movement.

- [13] S. R. Lindemann and S. M. LaValle, "Current issues in sampling-based motion planning," in *Proc. of Intl. Symp. of Robotics Research*, Siena, Italy, Oct 2003.
- [14] J. Kuffner, K. Nishiwaki, S. Kagami, Y. Kuniyoshi, M. Inaba, and H. Inoue, "Self-collision detection and prevention for humanoid robots," in *Proceedings of IEEE Int. Conference on Robotics and Automation (ICRA)*, Washington, D.C., May 2002, pp. 2265–2270.
- [15] S. Kagami, J. J. Kuffner, K. Nishiwaki, M. Inaba, and H. Inoue, "Humanoid arm motion planning using stereo vision and rrt search," *Journal of Robotics and Mechatronics*, vol. 15, no. 2, pp. 200–207, April 2003.
- [16] L. E. Kavraki, P. Svestka, J.-C. Latombe, and M. Overmars, "Probabilistic roadmaps for path planning in high dimensional configuration spaces," *IEEE Transactions on Robotics and Automation*, vol. 12, no. 4, pp. 566–580, 1996.
- [17] J. J. J. Kuffner and S. M. L. Valle, "Rrt-connect: an efficient approach to single-query path planning," in *Proc. of the Intl. Conf. on Robotics and Automation (ICRA)*, San Francisco, USA, 2000, pp. 995–1001.
- [18] S. Lindemann and S. LaValle, "Incrementally reducing dispersion by increasing voronoi bias in rrts," in *Proc. of IEEE Intl. Conf. on Robotics and Automation*, 2004.
- [19] L. Kavraki, M. Kolountzakis, and J.-C. Latombe, "Analysis of probabilistic roadmaps for path planning," *IEEE Trans. on Robotics and Automation*, vol. 14, no. 1, pp. 166–171, 1998.
- [20] A. Ben-Israel, "A newton-raphson method for the solution of systems of equations," *Journal of Mathematical Analysis and Applications*, vol. 15, pp. 243–252, 1966.
- [21] L. Sciavicco and B. Siciliano, *Modeling and Control of Robot Manipulators, 2nd Ed.* London: Springer-Verlag, 2000.
- [22] A. A. Maciejewski and C. A. Klein, "Obstacle avoidance for kinematically redundant manipulators in dynamically varying environments," *Intl. Journal of Robotics Research*, vol. 4, no. 3, pp. 109–117, 1985.
- [23] Y. Nakamura and H. Hanafusa, "Inverse kinematics solutions with singularity robustness for robot manipulator control," *Journal of Dynamic Systems, Measurement, and Control*, vol. 108, pp. 163–171, Sept 1986.
- [24] E. Mazer, J. Ahuactzin, and P. Bessiere, "The ariadne's clew algorithm," *Journal of Artificial Intelligence Research (JAIR)*, vol. 9, pp. 295–316, 1998.
- [25] K. Döring, H. G. Peterson, and M. L. Peterson, "An integration of different motion planners," in *Proc. of Robotics and Applications*, 2003.
- [26] J. Halton, "On the efficiency of certain quasi-random sequences of points in evaluating multi-dimensional integrals," *Numerical Mathematics*, vol. 2, pp. 84–90, 1960.