

Distributed 1D-coverage control for a reconfigurable camera network

Sameera Poduri
Computer Science
University of Southern
California
sameera@usc.edu

Ajay Deshpande
Mechanical Engineering
Massachusetts Institute
of Technology
ajayd@mit.edu

Daniela Rus
Electrical Engineering
and Computer Science
Massachusetts Institute
of Technology
rus@csail.mit.edu

Gaurav Sukhatme
Computer Science
University of Southern
California
gaurav@usc.edu

Abstract

In this paper we address the problem of *covering* narrow indoor or outdoor pathways using a network of mobile Cyclops cameras. We propose and validate a 1D sensing-performance model for the detection behavior of the camera. Based on this, we formulate the covering problem as a new type of 1D *locational optimization problem* that explicitly accounts for the camera-location dependence of the sensing performance. We propose a distributed control law for reconfiguring camera locations based on the gradient descent approach to solve this problem and prove its convergence. We present simulation results on a *pseudo-real* data set constructed using indoor experiments.

1 Introduction

In this paper, we address the problem of *covering* indoor corridors or outdoor paths with a network of mobile Cyclops cameras [4]. We use the standard background-subtraction-based detection algorithm on Cyclops cameras to detect an intruder in the pathways. The covering problem involves finding a placement of cameras such that the overall detection-performance is maximized. We formulate this problem as a new type of *locational optimization problem* ([3], [1]) which accounts for a novel observation that the performance of an individual sensor can be a function of the sensor location itself. The work on the locational optimization problem so far, with the exception of [2], assumes that sensors have the same performance at every location in the domain [1], [5]. The detection performance of cameras, however, can vary drastically because of factors such as lighting conditions, luminance, background contrast, *etc.* that vary from location to location. We observed this in the following simple experiment. Figure 1(a) shows an aerial view of a botanical garden. We deployed two sets of Cyclops cameras along a pathway in the garden. The first deployment consisting of 11 cameras placed uniformly (Figure 2(a)) and the second deployment consisting of 9 cameras whose locations were chosen based on prior knowledge about lighting conditions (Figure 2(b)). We used the detection algorithm to test the number of times a person walking along the path was detected by each of these networks. The second deployment provided complete coverage using fewer cameras (Figure 2(d)) while the uniform deployment did not provide complete coverage (Figure 2(c)). These results motivate a sensing model that is a function of the sensor's loca-

tion which can then be used for coverage optimization.

Based on several indoor and outdoor experiments, we propose a 1D empirical model for the sensing performance function of a camera, which is based on the background-subtraction-based detection algorithm. The function is characterized by two parameters that vary with the location of the camera sensor thus capturing the location dependence of the sensing performance. Based on this, we formulate the problem of covering a single loop of indoor or outdoor pathways with a network of mobile Cyclops cameras as a locational optimization problem which includes location-dependent sensing performance function. We propose a distributed control algorithm for reconfiguring the locations of cameras to optimize the overall performance. We verify our results based on simulations on a 'pseudo-real' data set constructed using indoor experiments.



Figure 1. (a) An aerial view of the garden (b) Cyclops camera with an attached Mica2 Mote

2 Sensing Performance Function

The Cyclops camera sensor consists of a CMOS imager with CIF image capability and an internal image processor unit for image interpretation and analysis. It couples with a Mote and periodically captures images (figure 1(b)). Our choice of the sensing performance function of a camera is related to the performance of the object detection algorithm that is based on background subtraction. Foreground object detection using background subtraction has been used extensively and is well suited for low complexity camera sensor networks due to its low resource requirements in terms of memory and computation. According to this method, the cyclops camera periodically captures images and maintains a moving average background model of the environment. A foreground model is also constructed as the absolute difference of the instantaneous image and the constructed back-




Figure 2. Camera locations for (a) uniform deployment and (b) data-driven deployment and their corresponding detection results. The graphs in (c) and (d) illustrate detection events by camera IDs (y-axis) at a given time step (x-axis). The (green) circle is a correct detection and the (red) squares are false-positives.

ground. The resulting foreground images are then passed through a luminance and size filter, which identifies clusters of pixels that have a considerable change in illumination. See [4] for the details of the algorithm. Figure 4 shows images from a cyclops camera. Figure 4(a) and 4(b) show the background model and the instantaneous image obtained by placing a white board at some distance. The foreground images as the difference between the two images is shown in Figure 4(c). The *detectability* of the object depends on the number of pixels identified after passing the foreground model through the filter – larger the number of pixels, better the detection probability. We therefore use the number of pixels identified as the sensing performance function for each camera sensor. Note that the number of pixels detected is also a function of distance between the camera and the object. The further away the object is, the lower the number of pixels detected will be.




Figure 3. Perspective projection model

Suppose a rectangular object of dimension $h \times w$ placed at a distance d on the camera's central axis exactly facing the camera. Consider an ideal scenario in which every point on the object differs significantly in its illumination charac-

teristics from the background image. Then, according to a perspective projection camera model (Figure 3), the number of pixels, m , detected by the camera is approximately given by:

$$m \simeq \frac{f \cdot h \cdot w}{d^2} \cdot \frac{resolution}{sensor_area} = k \cdot \frac{h \cdot w}{d^2} \cdot resolution$$

where f is the focal length and k is a constant. Thus, the number of pixels detected is inversely proportional to square of the distance between the camera and the object. We indeed observed this relationship in practice when we experimented with a white board of dimension $3ft \times 2ft$ placed at different distances in front of a cyclops camera that was placed in a well-lit corridor. Figure 5.1(a) shows the experimental set-up and Figure 5.2(a) shows the number of pixels identified using the background subtraction algorithm as a function of distance between the camera and the white board. However these situations are rare in the environments where the lighting conditions and the object properties are far from the ideal situation. In practice, the number of pixels detected by the camera deviates from this ideal model because some pixels on the object have the same texture as that of the background and go undetected. This is illustrated in fig 4 where the target is a white rectangular board. In the foreground image, the pixels in white are the ones that are detected. Some of the pixels on the board have intensities close to their corresponding pixels in the background.

This indicates that the sensing performance function of camera depends not only on the distance but also on the location of the camera itself. This very behavior motivates the definition of the coverage problem we address. We restrict ourselves to coverage of narrow pathways reducing the problem to coverage of $1D$ loops. We conducted a series of experiments both indoors and outdoors to extract the sensing performance function of a camera. We placed a white/black rectangular board in front of a camera along its central axis at increments of 5 feet to obtain the number of pixels detected. Based on several data sets we observed that the following empirical model for the sensing performance function best fits the data.

$$f(\|x - q\|, x) = \frac{k_1(x)}{k_2(x) + \|x - q\|^2} \quad (1)$$

Here x denotes the location of the camera and q denote the sensing performance, *i.e.*, the number of pixels detected at location q . Note the dependence on the location of x via functions $k_1(x)$ and $k_2(x)$. Figure 5 shows the best fit for different values of k_1 and k_2 for indoor and an outdoor instances. Note that the sensing performance function is not exact; it corresponds to the best fit with the data.

3 Locational Optimization Problem Formulation

Let \mathcal{L} denote the $1D$ loop of the pathway we want to cover using mobile cameras. We assume that each camera is bi-directional (obtained by combining two cyclops camera modules aligned along the same axis). Thus each sensor can *see* on its *left* and *right* directions on the loop. The sensing performance function along each direction takes the




Figure 4. Illustration of pixels on target not detected. (a) background image (b) original image and (c) foreground image. In the foreground image, some of the pixels in the target board are black. These are the pixels that are similar to the background and are therefore not detected by the camera.

form of Equation 1 with possibly different parameter values. For now we assume that the pathway is a smooth curve that can be parameterized with a single parameter and does not contain any sharp corners, *i.e.*, at any location the curvature of the loop is very large compared with the local *detection range* of the camera assuming that the sensor is always aligned on the loop such that its central axis is always tangential to the loop. Let n be the number of cameras and let p_1, p_2, \dots, p_n denote their locations on the loop in the order such that p_i is *between* p_{i-1} and p_{i+1} . Further, let $p_{n+1} = p_1$. Let $f_l(\|p_i - q\|, p_i)$ and $f_r(\|p_i - q\|, p_i)$ be the left and the right sensing performance functions respectively of the i -th camera located at p_i . We assume that both f_l and f_r have the empirical form described in Equation 1:

$$f_l(\|p_i - q\|, p_i) = \frac{k_{1l}(p_i)}{k_{2l}(p_i) + \|p_i - q\|^2} \quad (2)$$

$$f_r(\|p_i - q\|, p_i) = \frac{k_{1r}(p_i)}{k_{2r}(p_i) + \|p_i - q\|^2} \quad (3)$$

The performance functions of the sensors induce a partition of \mathcal{L} into each sensor's *dominance region*, where its sensing performance is better than that for any other sensor. More formally, if W_i denotes the dominance region for the i -th sensor, then

$$W_i = \{q \in \mathcal{L} \mid \max\{f_l(\|q - p_i\|, p_i), f_r(\|q - p_i\|, p_i)\} \geq \max\{f_l(\|q - p_j\|, p_j), f_r(\|q - p_j\|, p_j)\}, \forall j \neq i\}.$$

Note that in higher dimensions, the dominance region is a *generalized Voronoi partition* [3]. We assume that the region of dominance of the i -sensor strictly belongs to the interval $[p_{i-1}, p_{i+1}]$. Let $[l_i, r_i]$ be the dominance range of the i -th sensor. Thus, $l_i \in [p_{i-1}, p_i]$ and $r_i \in [p_i, p_{i+1}]$. According to the definition of the dominance region,

$$f_l(\|p_i - l_i\|, p_i) = f_r(\|p_{i-1} - l_i\|, p_{i-1}) \text{ and,}$$

$$f_r(\|p_i - r_i\|, p_i) = f_l(\|p_{i+1} - r_i\|, p_{i+1}).$$

Now we define the *coverage metric* or *overall utility func-*

tion as follows:

$$\mathcal{H}(p_1, p_2, \dots, p_n) = \sum_{i=1}^n \left\{ \int_{l_i}^{p_i} f_l(\|p_i - q\|, p_i) dq + \int_{p_i}^{r_i} f_r(\|p_i - q\|, p_i) \right\} \quad (4)$$

We note that the result about the partial derivative of the net utility function based on the divergence theorem [1] generalizes easily to our case.

LEMMA 3.1. *The partial derivative of the net utility function with respect to the position of the i -th sensor is given by,*

$$\frac{\partial \mathcal{H}}{\partial p_i} = \int_{l_i}^{p_i} \frac{\partial f_l(\|q - p_i\|, p_i)}{\partial p_i} dq + \int_{p_i}^{r_i} \frac{\partial f_r(\|q - p_i\|, p_i)}{\partial p_i} dq \quad (5)$$

We refer readers to [1] for the proof of the lemma.

4 Distributed coverage control

We propose a distributed coverage control algorithm that is based on iterative local sub-gradient method.

4.1 Control Law for each sensor

Let $p_i(n)$ be the position of the i -th sensor after n updates. We state the control law for the position update of the i -th sensor to $p_i(n+1)$. During the time the i -th sensor updates its position, our coverage algorithm does not allow the simultaneous update at the dominance region neighbors (nodes whose dominance regions are adjacent) of the i -th sensor. The local control law involves searching for the local optimal solution. Given that the positions of the Voronoi neighbors are fixed, the net utility \mathcal{H} and the local gradient, $\frac{\partial \mathcal{H}}{\partial p_i}$ are just the functions of p_i . We state the control law as follows.

$$p_i(n+1) = p_i^*, \text{ where, } p_i^* = \arg \max_{p_i \in W_i} \mathcal{H}(\dots, p_i, \dots) \quad (6)$$

Essentially, the control law involves local search over the dominance region W_i for the optimal solution p_i^* by solving the constrained optimization problem. If p_i^* does not lie on the boundary of W_i , then it is the root of equation $g(p_i) = 0$. Since the search involves finding the optimal location just for one sensor, it is computationally tractable. We state the




Figure 5. Validation of the proposed model for pixels detected vs. distance for three different environments. 1(a) is a well-lit corridor and close to an ideal environment. 2(a) is an outdoor pathway with shadows of trees and buildings. 3(a) is inside a lab where the lighting conditions are not uniform. The solid blue line is the number of pixels detected from experiments and the red dashed line is the minimum least squares fit using the model in Equation 1

following lemma about the increase in the net utility after every pose update.

LEMMA 4.1. *The control law for an individual sensor in Equation 6 guarantees that the net utility increases after the position update of the sensor.*

Implementation of the above control law requires the exact knowledge of the sensing performance function $f(\|q - p_i\|, p_i)$ for each sensor i and the density function $\phi(q)$. These can either be known a priori or estimated on the fly using measurements [5].

Below is the coverage algorithm that runs at each node.

Algorithm 1 Coverage algorithm at the i -th sensor: Let p_i denote its position. Let W_i denote the set of its dominance region neighbors.

- t : Update W_i
 - t+1: Check if any $j \in W_i$ is updating its position
 - t+2: if yes, wait for random duration of time and repeat the above steps
 - t+2: if no, schedule position update at t+3 and broadcast over W_i
 - t+3: start moving to optimal p_i^* as obtained using Equation 6
 - t+k: After the move, wait for random duration before the next update
-

4.2 Convergence

THEOREM 4.2. *The distributed coverage algorithm at each sensor as described in Algorithm 1 converges, as the number of position updates tends to infinity.*

The proof follows from the fact that the net coverage utility is bounded and by lemma 4.1, it increases monotonically with each iteration of the algorithm.

5 Experimental Results

In this section, we discuss implementation issues and results of our coverage algorithm using Cyclops camera sensors. Our objective is to *cover* loopy environments such as indoor corridors such that an intruder object can be detected. Presently, we assume that the cameras have global knowledge of the sensing performance function. While this will not be feasible in a real setting, the cameras combine their local knowledge of the performance function with that of the neighboring sensors over a few hops to estimate the performance function. In our experiments, we first estimate the performance function over the entire domain by gathering data and use the estimated functions in simulations to test our algorithm.

We gathered images under controlled lighting conditions in a rectangular indoor corridor of which the central axis rectangle is of size $90ft \times 30ft$ and the corridor is $5ft$ wide. At every $20ft$ along the lengthwise central axis of the corridor, we placed a cyclops camera and captured on both sides the images of the corridor which serve as background models. We also captured images of a white or black board of dimension $3ft \times 2ft$ placed along the central line kept at every $5ft$ from the camera up to $25ft$. These images serve as foreground models. Since the width of the corridor is $30ft$, along the widthwise central axis, we placed a camera at the middle point and captured images on both sides in the similar fashion. We used these images to fit the sensing performance function to obtain the values of k_1 and k_2 at various locations. Along the entire corridor, we obtained 22 pairs of values of k_1 and k_2 . We interpolate spline functions through these values of k_1 and k_2 to estimate the *pseudo-real* global sensing performance function. Figure 6(a) shows $k_1(x)$ and




Figure 6. Performance of the distributed control law in an indoor rectangular corridor. The estimated values of (a) k_1 and (b) k_2 in the left and right directions along the entire length of the path. (c) The final positions of the cameras are not uniform. (d) The utility increases monotonically and converges after 20 iterations.

$k_2(x)$ along the entire length of the corridor. We use this form to test our coverage algorithm.

Sharp corners (and occlusions) cause an abrupt drop in the sensing performance function because cameras cannot see beyond corners (or occlusions). Equations 2, 3 can be modified as follows to account for occlusions.

$$f_l(\|p_i - q\|, p_i) = \begin{cases} \frac{k_{1l}(p_i)}{k_{2l}(p_i) + \|p_i - q\|^2} & \text{if } q \text{ is not occluded from } p_i \\ 0, & \text{otherwise} \end{cases} \quad (7)$$

$$f_r(\|p_i - q\|, p_i) = \begin{cases} \frac{k_{1r}(p_i)}{k_{2r}(p_i) + \|p_i - q\|^2} & \text{if } q \text{ is not occluded from } p_i \\ 0, & \text{otherwise} \end{cases} \quad (8)$$

Because the sensing function takes on a constant value for points beyond an occlusion, it is possible that the equations $f_l(\|p_i - l_i\|, p_i) = f_r(\|p_{i-1} - l_i\|, p_{i-1})$ and $f_r(\|p_i - r_i\|, p_i) = f_l(\|p_{i+1} - r_i\|, p_{i+1})$ that define the dominance region have many solutions. This will happen, for example, when adjacent cameras have two or more obstacles between them. For such cases, we define the dominance region boundary to be the position of its closest occlusion *i.e.*, if the value of the sensing function of a camera is zero at a point q then q is considered *not covered* by the camera and will not belong to its dominance region. Notice that with this definition, the dominance regions may not form a partition of the path and there could be segments of the path that do not belong to any camera's dominance region. However, since these segments have zero coverage utility for all the cameras, and the rest of the path is partitioned according to the Voronoi property, this definition of dominance regions is an optimal assignment of points on the path to cameras.

With these new definitions for performance function and dominance regions, we can apply the control law in equation 6 and Theorem 4.2 guarantees convergence. However, with this control law, cameras adjacent to occlusions will not cross the occlusions because they only pick new positions within their dominance regions. To further improve the coverage utility, we introduce an additional switching step where cameras can cross obstacles if the local utility gained by doing so is more than the utility gain of the optimal location within its dominance region. While computing the switching utility, we account for change in the dominance regions and the utility of the neighboring cameras. Note that the local utility of every other camera remains unchanged.

5.1 Simulation Environment

We simulated the rectangular corridor in MATLAB to test the convergence and resulting coverage of our distributed control law. The cameras start at randomly chosen initial positions and in each iteration of the algorithm, they update their position according to Equation 6 using a constrained optimization routine in MATLAB. We assume that cameras are localized and adjacent cameras on the path can communicate with each other. The simulation converges when the no camera changes its position.

Figure 6 shows the result of the algorithm on the rectangular corridor. The utility increases monotonically with each iteration and the algorithm converges. We can generalize this approach to deal with more complex pathways with multiple junctions so at a sensor adjacent to a junction reasons about the coverage gain in each of the branches that meet at the junction.

6 Conclusions and Future Work

We considered the problem of covering indoor and outdoor loopy pathways using Cyclops camera networks. Based on several measurements we proposed an empirical function for the sensing performance of the Cyclops camera. We presented simulation results for a pseudo-real data set based on indoor experiments and demonstrated that our algorithm converges. As a part of future work we plan to consider the case where the cameras do not have the global knowledge of functions k_1 and k_2 and will estimate these online. We also plan to extend the locational optimization problem formulation for the location-dependent sensing models in higher dimensions.

7 References

- [1] J. Cortes, S. Martinez, T. Karatas, and F. Bullo. Coverage control for mobile sensing networks. *IEEE Transactions on Robotics and Automation*, 20(2), 2004.
- [2] F. Lekien and N. E. Leonard. Non-uniform coverage and cartograms. *SIAM Journal on Control and Optimization*, in submission.
- [3] A. Okabe, B. Boots, and K. Sugihara. *Spatial Tessellations: Concepts and Applications of Voronoi Diagrams*. John Wiley & Sons Ltd., 1992.
- [4] M. Rahimi, R. Baer, O. Iroezzi, J. Garcia, J. Warrior, D. Estrin, and M. Srivastava. Cyclops: In situ image sensing and interpretation in wireless sensor networks. In *ACM Conference on Embedded Networked Sensor Systems (SenSys)*, 2005.
- [5] M. Schwager, J. Slotine, and D. Rus. Decentralized, adaptive control for coverage with networked robots. In *International Conference on Robotics and Automation*, Rome, April 2007.