

Constrained Interaction and Coordination in Proximity-Limited Multi-Agent Systems

Ryan K. Williams, *Student Member, IEEE*, and Gaurav S. Sukhatme, *Fellow, IEEE*

Abstract—In this paper, we consider the problem of controlling the interactions of a group of mobile agents, subject to a set of topological constraints. Assuming proximity-limited inter-agent communication, we leverage mobility, unlike prior work, to enable adjacent agents to interact discriminatively, that is, to actively retain or reject communication links on the basis of constraint satisfaction. Specifically, we propose a distributed scheme consisting of hybrid controllers with discrete switching for link discrimination, coupled with attractive and repulsive potentials fields for mobility control, where constraint violation predicates form the basis for discernment. We analyze the application of constrained interaction to two canonical coordination objectives, aggregation and dispersion, with maximum and minimum node degree constraints, respectively. For each task, we propose predicates and control potentials, and we examine the dynamical properties of the resulting hybrid systems. Simulation results demonstrate the correctness of our proposed methods and the ability of our framework to generate topology-aware coordinated behavior.

Index Terms—Distributed robot systems, dynamic networks, connectivity control.

I. INTRODUCTION

THE ubiquity of advanced communication technologies coupled with the continued scaling of processing capabilities has generated intense interest in the analysis and control of networked systems, and particularly in systems of mobile agents. Specifically, networks of cooperating intelligent agents have become a natural evolution of centralization, yielding gains in efficiency, scalability, and robustness when compared to classical solutions. Applications of mobile agent networks are multidisciplinary and highly varied; examples include formation control [1]–[3], adaptive sampling [4]–[6], and target tracking [7]–[9].

Central to the success of distributed systems is the modeling of coordinated objectives and the derivation of control schemes that rely only on limited local information. In this work, we consider a realistic model of interaction consisting of agents with proximity-limited communication and local sensing capabilities. When coupled with agent mobility, such interactions induce topological variations that can be modeled by the *dynamic network* (or *dynamic graph*) framework. In particular, we are concerned with controlling the topology of such a dynamic network of agents, while respecting a set of constraints relevant to system objectives or some performance metric. This goal is motivated by recent results indicating the profound effect network topology has on the performance and robustness of networked algorithms, for example in the analysis of formation stability [10], consensus seeking [11], and swarming behaviors

[12]. Consensus algorithms are particularly interesting as they underly many distributed processes including filtering [13]–[15], optimization [16]–[18], and estimation [19]–[21]. In [11], [22], [23] Olfati-Saber showed that network connectivity, expressed as the spectrum of the graph Laplacian matrix, fundamentally impacts the convergence rate, time-delay stability, and robustness of consensus, yielding a distinct tradeoff in network topology design. It is then natural to consider controlling topology in order to yield performance gains in networked processes like consensus, or to otherwise shape network information flow [10].

The connectivity (topology) control problem has been addressed primarily in two manners, by maintaining the connectivity of initially connected networks, or through the regulation of global and local connectivity measures. In [24] a robust local measure of connectivity is proposed along with connectivity-preserving controls for solving broadcast optimization and sensor coverage problems. Alternately, [25] takes a hybrid automata approach, incorporating market-based auctions and a local connectivity measure to define distributed controls for connectivity preserving link addition and deletion. In [26] centralized potential fields over the determinant of a reduced Laplacian are employed to guarantee connectivity. Distributed controls and algebraic connectivity estimation are considered in [27], while in [28] a distributed power iteration is formulated together with a distributed gradient controller for connectivity maximization.

As opposed to previous work that is centralized in nature [26], [29], solutions that limit connectivity control to link retention [30]–[32] or unconstrained maximization [27], [28], and approaches that regulate network links and not agent configuration [25], we propose a *distributed* control framework that modulates topology through agent *mobility*, and manages *discriminatively* the addition *and* deletion of network links in order to shape agent interaction under constraints¹. Specifically, we construct local controllers with discrete switching for link discrimination, whereby adjacent agents are classified as either candidates for constraint-aware link removal or addition, or as constraint violators requiring either the retention or denial of communication links. Attractive and repulsive potentials fields establish the local controls necessary for link discrimination and constraint violation predicates form the basis for discernment. We examine constrained interaction by considering two common coordination objectives, aggregation and dispersion, under two interaction constraints: maximum and minimum node degree. For each task, we propose predicates and continuity-preserving potential fields, we analyze the dynamical properties of the resulting hybrid system, and we present simulation results

The authors are with the Departments of Electrical Engineering and Computer Science at the University of Southern California, Los Angeles, CA 90089 USA (email: rkwillia@usc.edu; gaurav@usc.edu).

¹Previous work on constrained connectivity is relatively sparse, examples include [33]–[35].

demonstrating the correctness of our control formulation.

The outline of the paper is as follows. In Section II, we provide preliminary materials including agent and network models, a spatial model of interaction, and problem statements. A general framework for constrained agent interaction, including a switching model for discriminative connectivity and constraint-aware mobility control, is presented in Section III. Sections IV and V present an analysis of constrained aggregation and dispersion behaviors, respectively. Simulation results are provided in Section VI, and concluding remarks as well as directions for future work are stated in Section VII.

II. MODELING AND PROBLEM FORMULATION

Consider a system of n mobile agents operating in \mathbb{R}^m each capable of computation, inter-agent communication, and localized sensing. Denote by $x_i(t) \in \mathbb{R}^m$ the position of the i th agent at time $t \in \mathbb{R}_+$ and consider the single integrator agent dynamics

$$\dot{x}_i(t) = u_i(t) \quad (1)$$

where $u_i(t) \in \mathbb{R}^m$ is the control input for the i th agent. We can alternatively view the system in terms of the composite network dynamics given by

$$\dot{\mathbf{x}}(t) = \mathbf{u}(t) \quad (2)$$

where $\dot{\mathbf{x}}(t) = [\dot{x}_1(t), \dots, \dot{x}_n(t)]^T \in \mathbb{R}^{mn}$ and $\mathbf{u}(t) = [u_1(t), \dots, u_n(t)]^T \in \mathbb{R}^{mn}$ are formed by stacking vector components². It is assumed that the agents have some primary coordination objective (in this work, we consider aggregation and dispersion) together with interaction constraints that form the basis of the local control inputs.

The coordination of such a system lies in agent interaction and in the exchange of information, by means of passive sensing and explicit connectedness. The literature examines a broad range of dynamically interacting systems, from centralized scenarios to all-to-all communication assumptions. Here we adopt a realistic model of interaction that assumes the agents operate without contact to a centralized controller and that sensing and communication occurs only within limited proximities. Specifically, denoting the distance between agents i and j by $\|x_{ij}\| \triangleq \|x_i - x_j\|$, the threshold ρ_2 acts as the *interaction radius*, beyond which agent interaction becomes impossible. When $\|x_{ij}\| \leq \rho_2$ we assume the agents can sense displacement $\|x_{ij}\|$ and communicate over an established communication link, denoted (i, j) . The creation of communication links occurs within the *connection radius* $\|x_{ij}\| \leq \rho_1 < \rho_2$, generating a region of width $\rho_2 - \rho_1$ within which adjacent agents discern interactions (more on this in Section III). Finally, we require no collisions between agents³, thus we define the radius $\|x_{ij}\| \leq \rho_0 < \rho_1$, within which action is taken to avoid inter-agent collisions. Such a spatial partitioning reflects the reality of practical interacting systems: limited communication, finite range sensing, and discerned interaction. Figure 1 depicts the proposed interaction model, ignoring for now the details related to discernment.

²To simplify notation, in the sequel we drop explicit notation for time and state dependence when it is contextually apparent.

³For point agents this implies $\|x_{ij}\| > 0, \forall i \neq j$.

Agent mobility coupled with the described model of interaction induces a time-varying (or switching) element to the network topology, that is as the system evolves, agents may dynamically enter or exit the interaction radii of others and establish communication. As is common, we associate a dynamic graph object with the underlying topology of the network⁴:

$$\mathcal{G}(t) = (\mathcal{V}, \mathcal{E}(t)) \quad (3)$$

with vertices (nodes) $\mathcal{V} = \{1, \dots, n\}$ indexed by the set of agents and time-varying edge set $\mathcal{E} = \{(i, j) \mid i, j \in \mathcal{V}\}$ defined by

$$(i, j) \in \mathcal{E} \Leftrightarrow (\|x_{ij}\| \leq \rho_2) \wedge \sigma_{ij}(t) \quad (4)$$

with switching signals [25], [32], [38]

$$\sigma_{ij}(t^+) = \begin{cases} 0, & \sigma_{ij}(t^-) = 0 \wedge \|x_{ij}\| > \rho_1 \\ 1, & \text{otherwise} \end{cases} \quad (5)$$

where the notation t^- and t^+ refers to the state transitions of the switching signal and the symbol \wedge represents the boolean AND operation⁵. Switching signals (5) define our assumed mechanism of delayed link addition at the connection boundary and induce a lag in topology changes. The further implication is that agents detect potential collaborators within some region of sufficient communication, yet remain in a disconnected state. As discussed in [32], such a construction generates a hysteresis effect in link addition and loss, with a switching threshold⁶ modulated by $\rho_2 - \rho_1$. The hysteresis in topology switching is vital to properly formalizing controls for link discrimination as will be discussed in Section III.

The graph edges (4) take on the switched behavior of the mobile network topology, reflecting our assumed interaction model. We assume bidirectional communication and that there exists no self-loops⁷, implying that set \mathcal{E} will contain only undirected edges and that the induced graph \mathcal{G} will itself be undirected. Agents that are connected by a link are called *neighbors* and the set of neighbors of an agent i is given by as $\mathcal{N}_i = \{j \in \mathcal{V} \mid (i, j) \in \mathcal{E}\}$, which for an undirected graph induces the symmetry $j \in \mathcal{N}_i \Leftrightarrow i \in \mathcal{N}_j$. We can further define the notion of an *interaction set* for agent i , $\mathcal{I}_i = \{j \in \mathcal{V} \mid \|x_{ij}\| \leq \rho_2\}$, i.e. the set of agents within the interaction radius of i . The interaction set is also symmetric with $j \in \mathcal{I}_i \Leftrightarrow i \in \mathcal{I}_j$. Finally, the *connectedness* property of the underlying graph \mathcal{G} is of particular importance as it reflects a notion of global information flow over communicating agents:

Definition 2.1 (Graph Connectivity): The graph $\mathcal{G}(t)$ is connected at time t if for every pair of vertices $i, j \in \mathcal{V}$ there exists a path from i to j , that is a sequence of distinct, adjacent vertices. We denote by \mathbb{C}_n the set of connected graphs of n nodes.

We now come to our primary goal in this work, the constrained interaction of proximity-limited agents. Agent mobility coupled with communication, sensing, and processing capabilities motivates our desire to shape agent interaction, and thus information

⁴Also referred to as a proximity graph or disk graph [36], [37].

⁵In the sequel we will also use the symbols \vee and \neg representing the boolean OR and NOT operations, respectively.

⁶Specifically, a dwell time between topology switches is introduced which is fundamental to certain systematic stability proofs [25].

⁷That is, $(i, i) \notin \mathcal{E} \forall i \in \mathcal{V}$.




Fig. 1. Agent interaction model. Agents can sense one another and communicate within the interaction radius ρ_2 . In the discernment region, $\rho_1 < \|x_{ij}\| \leq \rho_2$, an agent (i) determines, relative to local constraints, whether adjacent agents are candidates for link addition (k) or removal, or should be attracted (j) or repelled (l) due to constraint violation. In the connection region with radius $\rho_1 < \rho_2$, agents establish communication, with collision avoidance being activated within a radius $\rho_0 < \rho_1$.

flow, through topological constraints. Though intuitive, it has been made clear in the literature that topology profoundly impacts the diffusion of information in networks, the stability of coordinated control processes, etc. [10]–[12]. Quite simply, the issue of interaction lies at the core of most dynamic network processes. In this work, we examine constrained interaction by considering two common coordination objectives, aggregation and dispersion, under two interaction constraints: maximum and minimum node degree, respectively. The specific problems considered in this paper are summarized as follows:

Problem 1 (Max degree aggregation): Assuming an initial topology $\mathcal{G}(0) \in \mathcal{C}_n$, design agent controls u_i such that inter-agent displacements are decreasing, i.e. aggregation occurs. Further, we require $\mathcal{G}(t) \in \mathcal{C}_n$ for all $t \geq 0$, while satisfying constraints $|\mathcal{N}_i| \leq \beta_i \forall i \in \mathcal{V}$.

Problem 2 (Min degree dispersion): Assuming an initial topology $\mathcal{G}(0) \in \mathcal{C}_n$, design agent controls u_i such that inter-agent displacements are increasing, i.e. dispersion occurs. Further, $\mathcal{G}(t)$ for all $t \geq 0$ must satisfy constraints $|\mathcal{N}_i| \geq \omega_i \forall i \in \mathcal{V}$ while establishing no new communication links.

In the sequel we will propose a general formulation for constraining the interactions of proximity-limited agents and the examination of methods and related proofs for solving the proposed constrained coordination problems.

III. CONSTRAINING AGENT INTERACTION

In a system comprising information sharing agents, interaction is fundamentally a matter of communication. The implication is then in order to constrain interaction one must control the underlying communication topology, that is discriminately create and delete links, and act to deny or retain new or established links, respectively. Our proposition is the notion of *discriminative connectivity* among agents in the system, leveraging a spatial model of interaction (Section II) and agent mobility to

generate an environment in which agents actively regulate their neighbors based on inter-agent constraints. Generally, the constraints may not be explicitly spatial in nature (e.g. a constraint on inter-agent mutual information), however we consider the satisfaction of constraints to be a spatial task; that is, unlike works that simply activate or deactivate links (e.g. [25]), we force link discrimination through spatial organization.

To achieve discriminative connectivity, we begin by describing further the spatial model of Section II. Specifically, consider the region of width $\rho_2 - \rho_1$ between the interaction and connection radii, which we deem the *discernment region*. Within this zone each agent discerns, relative to local constraints, between *candidates* for link addition (non-neighbors) or deletion (neighbors), and agents which must be either attracted (link retention) or repelled (link denial). The discernment region is an intuitive construction, as in a realistic interacting system communication does not occur at the instant of discovery, it is typical to determine or negotiate a connection. Our model is simply an analog of this notion applied to a proximity-limited mobile system, that is interactions should always be tempered. Figure 1 illustrates our proposed model and the varying scenarios that may occur during discernment⁸.

A. Switching Model for Discriminative Connectivity

We are now prepared to present a formal construction for the satisfaction of interaction constraints through agent mobility. First consider the following notion of a predicate [25]:

Definition 3.1 (Predicate): Let \mathcal{X} be a finite set of variables. A *predicate* over \mathcal{X} , denoted $P(\mathcal{X}): \mathcal{X} \rightarrow \{0, 1\}$, is a boolean-valued function defined as the finite conjunction of strict or non-strict inequalities over \mathcal{X} .

That is, $P(\mathcal{X})$ is a logical statement over the elements of \mathcal{X} . For example, a relevant predicate for this work is $P(\mathcal{X}) \triangleq |\mathcal{N}_i| \leq \beta_i$ over the set $\mathcal{X} \in \mathbb{Z}_+$, which returns 1 if agent i has a degree bounded above by β_i and 0 otherwise. The predicate forms the basis of discernment for each agent, where for brevity we omit the predicate domain notation in subsequent usage⁹.

Assume there exists some global constraint on agent interaction that is defined as the finite conjunction of local constraint predicates assigned to each agent. Specifically we have a global constraint predicate

$$\mathbb{P} \triangleq \bigwedge_{i=1}^n \bigwedge_{k=1}^{p_i} \mathcal{P}_i^k \quad (6)$$

that indicates the constraint satisfaction status of the system, where each agent possesses p_i local constraint predicates, denoted by \mathcal{P}_i^k and indexed by k . Thus, the global constraint is assumed to have a separability quality across the system or there exists an agreement mechanism in the local constraint formulation, e.g. consensus or an auction. The local predicates \mathcal{P}_i^k indicate the satisfaction of the k th local constraint and the conjunction $\bigwedge_{k=1}^{p_i} \mathcal{P}_i^k$ represents the constraint satisfaction status of

⁸The scenarios depicted by Figure 1 would occur for example if the agents were under maximum and minimum degree constraints (as will be examined in this work).

⁹Further, we use varying typefaces and subscripts/superscripts to distinguish global and local predicates and predicate purpose. We also use the notation $P(t)$ to indicate a predicate evaluated at some time t .

the i th agent. It is assumed that the predicates are well-posed and that they are topological in nature, i.e. they can be manipulated directly or indirectly through network link addition or removal.

In order to appropriately regulate topology, each agent is assigned predicates for link addition and deletion, P_{ij}^a and P_{ij}^d , that indicate *possible* constraint violations by the addition or deletion of link (i, j) . Necessitated by the hysteresis in topology switching, these *discernment predicates* enable the agents to properly determine constraint-aware topology changes and act through mobility. We then associate switching signals $\{\varphi_i\}_{i=1}^n$, $\{\gamma_i\}_{i=1}^n$, $\{\xi_i\}_{i=1}^n$, and $\{\zeta_i\}_{i=1}^n$ with addition candidacy, deletion candidacy, attraction, and repulsion, where $\varphi_i \in \{0, 1\}^n$, $\gamma_i \in \{0, 1\}^n$, $\xi_i \in \{0, 1\}^n$, and $\zeta_i \in \{0, 1\}^n$ are associated with agent i . We denote by φ_i^j , γ_i^j , ξ_i^j , and ζ_i^j the j th element of the respective signals, where we assume $\varphi_i^i = 0$, $\gamma_i^i = 0$, $\xi_i^i = 0$, and $\zeta_i^i = 0$. The signals indicate for the i th agent the membership of nearby agents j in link addition and deletion candidate sets

$$\mathcal{C}_i^a = \{j \in \mathcal{V} \mid \varphi_i^j = 1\} \quad \mathcal{C}_i^d = \{j \in \mathcal{V} \mid \gamma_i^j = 1\} \quad (7)$$

and attraction and repulsion sets

$$\mathcal{D}_i^a = \{j \in \mathcal{V} \mid \xi_i^j = 1\} \quad \mathcal{D}_i^r = \{j \in \mathcal{V} \mid \zeta_i^j = 1\} \quad (8)$$

dependent on constraint violation. Discriminative connectivity is then achieved by defining constraint dependent dynamics for the sets (7), (8) through their respective signals in order to regulate the system topology by attraction and repulsion. The proposed candidate signal updates (per element) are then

$$\varphi_i^j(t^+) = \underbrace{((\|x_{ij}\| \leq \rho_2) \wedge (j \notin \mathcal{N}_i))}_{\text{I}} \wedge \underbrace{(\varphi_i^j(t^-) \vee (\neg \zeta_i^j(t^-) \wedge \neg P_{ij}^a \wedge \neg P_{ji}^a))}_{\text{II}} \quad (9)$$

for link addition, and

$$\gamma_i^j(t^+) = \underbrace{((\|x_{ij}\| > \rho_1) \wedge (j \in \mathcal{N}_i))}_{\text{III}} \wedge \underbrace{(\gamma_i^j(t^-) \vee (\neg \xi_i^j(t^-) \wedge \neg P_{ij}^d \wedge \neg P_{ji}^d))}_{\text{IV}} \quad (10)$$

for link deletion. The attraction and repulsion signal updates take forms complimentary to (9), (10) given by

$$\xi_i^j(t^+) = ((\|x_{ij}\| > \rho_1) \wedge (j \in \mathcal{N}_i)) \wedge (\xi_i^j(t^-) \vee (\neg \gamma_i^j(t^-) \wedge (P_{ij}^d \vee P_{ji}^d))) \quad (11)$$

and

$$\zeta_i^j(t^+) = ((\|x_{ij}\| \leq \rho_2) \wedge (j \notin \mathcal{N}_i)) \wedge (\zeta_i^j(t^-) \vee (\neg \varphi_i^j(t^-) \wedge (P_{ij}^a \vee P_{ji}^a))) \quad (12)$$

respectively. Notice that the updates (9)-(12) take a straightforward form. Considering for illustration the candidate signals (9), (10), Terms I and III represent discernment management, that is, nearby agents are determined for candidacy only if they lie within the discernment region and have the appropriate neighbor status. Terms II and IV then operate to assign agents within the discernment region to the appropriate candidate set on the basis

of constraint violation. The dynamics of (9)-(12) are illustrated in Figure 2. The salient properties of the candidate, attraction, and repulsion sets are summarized in the following.

Proposition 3.1 (Discernment set properties): The sets (7), (8) under dynamics (9)-(12) possess the following properties:

- 1) *Symmetry:* The inclusion of P_{ji}^a and P_{ji}^d in the set dynamics of discerning agent i induces a symmetry in the discernment sets of the interacting agents:

$$\begin{aligned} j \in \mathcal{C}_i^a &\Leftrightarrow i \in \mathcal{C}_j^a & j \in \mathcal{C}_i^d &\Leftrightarrow i \in \mathcal{C}_j^d \\ j \in \mathcal{D}_i^a &\Leftrightarrow i \in \mathcal{D}_j^a & j \in \mathcal{D}_i^r &\Leftrightarrow i \in \mathcal{D}_j^r \end{aligned} \quad (13)$$

That is, there exists a notion of agreement or cooperation in interactions.

- 2) *Exclusivity:* For a discerning agent i , a nearby agent j with $\rho_1 < \|x_{ij}\| \leq \rho_2$ belongs to one and only one discernment set of i :

$$\begin{aligned} j \in \mathcal{C}_i^a &\Rightarrow j \notin (\mathcal{C}_i^d \cup \mathcal{D}_i^a \cup \mathcal{D}_i^r) \\ j \in \mathcal{C}_i^d &\Rightarrow j \notin (\mathcal{C}_i^a \cup \mathcal{D}_i^a \cup \mathcal{D}_i^r) \\ j \in \mathcal{D}_i^a &\Rightarrow j \notin (\mathcal{C}_i^a \cup \mathcal{C}_i^d \cup \mathcal{D}_i^r) \\ j \in \mathcal{D}_i^r &\Rightarrow j \notin (\mathcal{C}_i^a \cup \mathcal{C}_i^d \cup \mathcal{D}_i^a) \end{aligned} \quad (14)$$

- 3) *Persistence:* For a discerning agent i , a nearby agent j with $\rho_1 < \|x_{ij}\| \leq \rho_2$ that belongs to a discernment set of i remains a member of the set for all time until either $\|x_{ij}\| \leq \rho_1$ or $\|x_{ij}\| > \rho_2$, i.e. j leaves the discernment region. Together with the exclusivity property, it is implied that during this period of persistence agent j does not become a member of any other discernment set of i , i.e. switching between discernment sets does not occur.

We point out several important characteristics of the proposed constraint satisfaction formulation. In the construction of discernment set dynamics (9)-(12) we have forced the discrimination of links to occur on the boundaries of the discernment region, before the actual addition or deletion of a link. Specifically, switching in the elements of sets (7), (8) occurs only when displacement $\|x_{ij}\|$ transits the ρ_1 or ρ_2 radii. As will be shown in Section III-B, the constraint violation controls approach infinity at the boundaries of the discernment region and thus our *preemptive* policy ensures a hysteresis effect similar to the switching signal (5) for link addition. Further, without preemptively determining violators and applying appropriate mobility controls, a situation could arise where multiple agents reach the connection or interaction boundary simultaneously, generate a constraint violation, and experience infinite control force. Finally, in the vein of preemption we require the following general assumption on the construction of discernment predicates.

Assumption 1 (Preemption): As the invocation of P_{ij}^a and P_{ij}^d occurs on the boundaries of the discernment region, while possible link addition occurs at some future time relative to $\rho_2 - \rho_1$, we require the following assumption on predicate for-




Fig. 2. Model for discriminative connectivity, including signals and associated switching conditions for controlling: (a) link addition; (b) link deletion.

mulation to hold for all agents i :

$$\begin{aligned}
 & \{(\exists t_2 \mid j \in \mathcal{D}_i^r(t_2)) \Leftrightarrow (\exists t_1 \mid P_{ij}^a(t_1) \vee P_{ji}^a(t_1))\} \wedge \\
 & \{(j \in \mathcal{D}_i^r(t) \Rightarrow \exists \epsilon_r > 0 \mid \|x_{ij}(t)\| \geq \rho_1 + \epsilon_r) \wedge \\
 & \{(\exists t_2 \mid j \in \mathcal{D}_i^a(t_2)) \Leftrightarrow (\exists t_1 \mid P_{ij}^d(t_1) \vee P_{ji}^d(t_1))\} \wedge \\
 & \{(j \in \mathcal{D}_i^a(t) \Rightarrow \exists \epsilon_a > 0 \mid \|x_{ij}(t)\| \leq \rho_2 - \epsilon_a)\} \\
 & \Rightarrow \bigwedge_{k=1}^{p_i} \mathcal{P}_i^k
 \end{aligned} \quad (15)$$

where $t_1 \leq t_2$, and separate instances of t_1, t_2 are treated independently. In words, the discernment predicates must be constructed to be *preemptive* in nature, i.e. in tandem with appropriate link discrimination, they predict the potential for constraint violation upon link addition or deletion before it occurs, ensuring topological constraint satisfaction¹⁰.

B. Constraint-Aware Mobility Control

The discernment of interacting agents into either candidates or constraint violators allows us now to define attractive and repulsive controls between agents comprising a violating interaction (one or both agents violate a predicate). First, consider an attractive potential field $\psi_{ij}^a: \mathbb{R}_+ \rightarrow \mathbb{R}_+$ for the purpose of retaining established neighbors that present a constraint violation risk if lost. We consider here the case of an unbounded potential and require ψ_{ij}^a to be constructed with the following properties [31]:

- 1) ψ_{ij}^a is a function of the distance between adjacent agents i and j , i.e. $\psi_{ij}^a \triangleq \psi_{ij}^a(\|x_{ij}\|)$, ensuring that interactions require the knowledge of only local information.
- 2) $\psi_{ij}^a \rightarrow \infty$ as $\|x_{ij}\| \rightarrow \rho_2$, guaranteeing neighboring agents that present a constraint violation risk are retained.
- 3) The potential is continuously differentiable over $\|x_{ij}\| \in (\rho_1, \rho_2]$.
- 4) For $\|x_{ij}\| \leq \rho_1$, we have $\psi_{ij}^a = 0$ and $\partial\psi_{ij}^a/\partial x_i = 0$.

¹⁰An implication of the predicate formulation is that it will require the inclusion of candidate set state, as will be shown. We make no claims concerning a systematic way of constructing predicates, this is reserved for future work.

- 5) For $\|x_{ij}\| > \rho_1$ we have $\partial\psi_{ij}^a/\partial\|x_{ij}\|^2 > 0$, and for $\|x_{ij}\| \leq \rho_1$, we have $\partial\psi_{ij}^a/\partial\|x_{ij}\|^2 = 0$. That is, the potential is attractive within the discernment region and ineffectual otherwise.

The dependence of ψ_{ij}^a on $\|x_{ij}\|$ induces the symmetry properties $\psi_{ij}^a = \psi_{ji}^a$ and $\partial\psi_{ij}^a/\partial\|x_{ij}\|^2 = \partial\psi_{ji}^a/\partial\|x_{ji}\|^2$. An appropriate attractive potential which we adopt for this work takes the following form:

$$\psi_{ij}^a = \begin{cases} 0, & \|x_{ij}\| \in (0, \rho_1) \\ \frac{1}{\rho_2^2 - \|x_{ij}\|^2} + \Psi_a, & \|x_{ij}\| \in [\rho_1, \rho_2) \end{cases} \quad (16)$$

where $\Psi_a(\|x_{ij}\|) = a\|x_{ij}\|^2 + b\|x_{ij}\| + c$ is chosen such that (16) is smooth over the ρ_1 transition, i.e. $\Psi_a(\rho_1) = \partial\Psi_a/\partial\|x_{ij}\|(\rho_1) = 0$.

Now, consider a repulsive potential field $\psi_{ij}^r: \mathbb{R}_+ \rightarrow \mathbb{R}_+$ for the purpose of repelling non-neighbors that present a constraint violation risk upon link creation. We consider again the case of an unbounded potential and require ψ_{ij}^r possess the following properties:

- 1) ψ_{ij}^r is a function of the distance between adjacent agents i and j , i.e. $\psi_{ij}^r \triangleq \psi_{ij}^r(\|x_{ij}\|)$.
- 2) $\psi_{ij}^r \rightarrow \infty$ as $\|x_{ij}\| \rightarrow \rho_1$, guaranteeing that communication is not established with non-neighboring agents that present a constraint violation risk.
- 3) The potential is continuously differentiable over $\|x_{ij}\| \in [\rho_1, \rho_2)$.
- 4) For $\|x_{ij}\| > \rho_2$, we have $\psi_{ij}^r = 0$ and $\partial\psi_{ij}^r/\partial x_i = 0$.
- 5) For $\|x_{ij}\| \leq \rho_2$ we have $\partial\psi_{ij}^r/\partial\|x_{ij}\|^2 < 0$, and for $\|x_{ij}\| > \rho_2$, we have $\partial\psi_{ij}^r/\partial\|x_{ij}\|^2 = 0$. That is, the potential is repulsive within the discernment region and ineffectual otherwise.

Again, the dependence of ψ_{ij}^r on $\|x_{ij}\|$ induces the symmetry properties $\psi_{ij}^r = \psi_{ji}^r$ and $\partial\psi_{ij}^r/\partial\|x_{ij}\|^2 = \partial\psi_{ji}^r/\partial\|x_{ji}\|^2$. Similar to the attractive potential (16), the repulsive potential takes

the form

$$\psi_{ij}^r = \begin{cases} \frac{1}{\|x_{ij}\|^2 - \rho_1^2} + \Psi_r, & \|x_{ij}\| \in (\rho_1, \rho_2) \\ 0, & \|x_{ij}\| \in [\rho_2, \infty) \end{cases} \quad (17)$$

where Ψ_r is again a second order polynomial in $\|x_{ij}\|$ chosen to guarantee ψ_{ij}^r is smooth over the ρ_2 transition.

Finally, our proposed constraint-aware mobility controls are given by

$$\begin{aligned} u_i &= -\nabla_{x_i} \left(\sum_{j \in \mathcal{I}_i} \psi_{ij}^o + \sum_{j \in \mathcal{D}_i^a} \psi_{ij}^a + \sum_{j \in \mathcal{D}_i^r} \psi_{ij}^r \right) \\ &= -\nabla_{x_i} \psi(\|x_{ij}\|) \end{aligned} \quad (18)$$

where we consider for now a *generalized coordination objective* driven by potential field $\psi_{ij}^o: \mathbb{R}_+ \rightarrow \mathbb{R}_+$ over agents in the interaction set. We assume the coordination potential has the following properties:

- 1) ψ_{ij}^o is a function of the distance between adjacent agents i and j , $\psi_{ij}^o \triangleq \psi_{ij}^o(\|x_{ij}\|)$, i.e. it constitutes a distributed coordination protocol. This also guarantees the symmetry properties $\psi_{ij}^o = \psi_{ji}^o$ and $\partial \psi_{ij}^o / \partial \|x_{ij}\|^2 = \partial \psi_{ji}^o / \partial \|x_{ji}\|^2$.
- 2) The potential is continuously differentiable over $\|x_{ij}\| \in [0, \rho_2)$, specifically with respect to switches over the interaction set (or any further partitioning of the interaction set, as we will see).
- 3) The potential is collision avoiding, i.e. $\psi_{ij}^o \rightarrow \infty$ as $\|x_{ij}\| \rightarrow 0$.

The overall system consisting of proximity-limited agent dynamics (1), along with interaction constraints and objectives driven by potential field controls (18), can be treated as a *hybrid system*¹¹ in which discrete transitions occur at times when new network edges are added or removed, or when switches in the discernment sets occur. The analysis of such a system can be treated using the *common Lyapunov function* and an extension of LaSalle's invariance principle from hybrid system theory [39]–[41]. We begin our analysis by defining the set of feasible initial conditions

$$\begin{aligned} \mathcal{F} \triangleq & \{ \mathbf{x} \in \mathbb{R}^{mn} \mid \|x_{ij}\| \in [0, \rho_1), \forall (i, j) \in \mathcal{E} \} \cap \\ & \{ \mathbf{x} \in \mathbb{R}^{mn} \mid \|x_{ij}\| \in [\rho_2, \infty), \forall (i, j) \notin \mathcal{E} \} \cap \\ & \{ \mathbf{x} \in \mathbb{R}^{mn} \mid \mathbb{P} = 1 \} \end{aligned} \quad (19)$$

where we specifically denote the constraint satisfaction set by $\mathcal{F}_p \triangleq \{ \mathbf{x} \in \mathbb{R}^{mn} \mid \mathbb{P} = 1 \} \neq \emptyset$. Note that it is implied by (19) and dynamics (9)-(12) that in \mathcal{F} we have $\mathcal{C}_i^a = \mathcal{C}_i^d = \mathcal{D}_i^a = \mathcal{D}_i^r = \emptyset, \forall i \in \mathcal{V}$. The first result of this paper now follows.

Theorem 3.1: Consider the system (1) under the previously described interaction model, driven by local controls (18), and starting from feasible initial conditions (19). Then, the system converges to an equilibrium configuration where $u_i = 0, \forall i \in \mathcal{V}$.

¹¹In this work we have avoided the specific nomenclature and representations of formal hybrid automata. We reserve such a treatment for future work.

Proof: First, consider the Lyapunov function $V: \mathbb{R}^{mn} \rightarrow \mathbb{R}_+$ given by

$$V = \frac{1}{2} \sum_{i=1}^n \left(\sum_{j \in \mathcal{I}_i} \psi_{ij}^o + \sum_{j \in \mathcal{D}_i^a} \psi_{ij}^a + \sum_{j \in \mathcal{D}_i^r} \psi_{ij}^r \right) \quad (20)$$

and observe that at times where the system switches, V and controls \mathbf{u} are continuously differentiable by construction, with values that remain constant. Thus, V serves as a common Lyapunov function for the hybrid system and analysis can proceed in the standard manner. Now, for any $c > 0$, define the set $\Omega_V = \{ \mathbf{x} \in \mathbb{R}^{mn} \mid V \leq c \}$, noticing that Ω_V is compact due to the continuity of V and as a consequence of potential construction.

The time derivative of V in Ω_V is

$$\dot{V} = \frac{1}{2} \sum_{i=1}^n \left(\sum_{j \in \mathcal{I}_i} \dot{\psi}_{ij}^o + \sum_{j \in \mathcal{D}_i^a} \dot{\psi}_{ij}^a + \sum_{j \in \mathcal{D}_i^r} \dot{\psi}_{ij}^r \right) \quad (21)$$

where

$$\begin{aligned} \sum_{i=1}^n \sum_{j \in \mathcal{I}_i} \dot{\psi}_{ij}^o &= 2 \sum_{i=1}^n \sum_{j \in \mathcal{I}_i} \dot{x}_i^T \nabla_{x_i} \psi_{ij}^o \\ \sum_{i=1}^n \sum_{j \in \mathcal{D}_i^a} \dot{\psi}_{ij}^a &= 2 \sum_{i=1}^n \sum_{j \in \mathcal{D}_i^a} \dot{x}_i^T \nabla_{x_i} \psi_{ij}^a \\ \sum_{i=1}^n \sum_{j \in \mathcal{D}_i^r} \dot{\psi}_{ij}^r &= 2 \sum_{i=1}^n \sum_{j \in \mathcal{D}_i^r} \dot{x}_i^T \nabla_{x_i} \psi_{ij}^r \end{aligned} \quad (22)$$

due to symmetry of potentials ψ_{ij}^o, ψ_{ij}^a , and ψ_{ij}^r , and sets $\mathcal{I}_i, \mathcal{D}_i^a$ and \mathcal{D}_i^r . Thus

$$\begin{aligned} \dot{V} &= \sum_{i=1}^n \dot{x}_i^T \nabla_{x_i} \left(\sum_{j \in \mathcal{I}_i} \psi_{ij}^o + \sum_{j \in \mathcal{D}_i^a} \psi_{ij}^a + \sum_{j \in \mathcal{D}_i^r} \psi_{ij}^r \right) \\ &= - \sum_{i=1}^n \|\nabla_{x_i} \psi(\|x_{ij}\|)\|^2 \leq 0 \end{aligned} \quad (23)$$

which implies the positive invariance of the level sets Ω_V of V . The extension of LaSalle's invariance principle for hybrid systems¹² together with (23) and initial conditions (19) guarantees that the system converges to the largest invariant subset of $\{ \mathbf{x} \in \mathbb{R}^{mn} \mid \nabla_{x_i} \psi(\|x_{ij}\|) = 0 \}$. As $u_i = -\nabla_{x_i} \psi(\|x_{ij}\|)$ we must have at equilibrium $u_i = 0, \forall i \in \mathcal{V}$. ■

The collision avoidance and discernment set reachability properties are established in the following lemma.

Lemma 3.1: Assume the system (1) evolves according to control laws (18) and starts from initial conditions (19). Then, the sets $\mathcal{F}_c \triangleq \{ \mathbf{x} \in \mathbb{R}^{mn} \mid \|x_{ij}\| > 0, \forall i \in \mathcal{V}, j \in \mathcal{I}_i \}$, $\mathcal{F}_a \triangleq \{ \mathbf{x} \in \mathbb{R}^{mn} \mid \|x_{ij}\| \leq \rho_2 - \epsilon_a, \forall i \in \mathcal{V}, j \in \mathcal{D}_i^a \}$, and $\mathcal{F}_r \triangleq \{ \mathbf{x} \in \mathbb{R}^{mn} \mid \|x_{ij}\| \geq \rho_1 + \epsilon_r, \forall i \in \mathcal{V}, j \in \mathcal{D}_i^r \}$ are invariant for the trajectories of the closed-loop hybrid system.

Proof: It follows from (23) that the time derivative of V remains non-positive for every $\mathbf{x}(0) \in \mathcal{F}$ and for all $t \geq 0$. Since $V(\mathbf{x}(0)) < \infty$, we must have $V(\mathbf{x}(t)) < \infty, \forall t \geq 0$. As $\|x_{ij}\| \rightarrow 0^+$ for $j \in \mathcal{I}_i, \|x_{ij}\| \rightarrow \rho_2^-$ for $j \in \mathcal{D}_i^a$, and $\|x_{ij}\| \rightarrow \rho_1^+$ for $j \in \mathcal{D}_i^r$, we have $V \rightarrow \infty$. Thus, we can conclude that

¹²We can invoke this extension as the system exhibits no Zeno behavior.

there exists $\epsilon_a > 0$ and $\epsilon_r > 0$ such that $\mathbf{x}(t) \in \mathcal{F}_c \cap \mathcal{F}_a \cap \mathcal{F}_r$ for all $t \geq 0$. ■

We now come to our primary result concerning the constraint satisfaction properties of the system.

Theorem 3.2: Consider the multi-agent system (1) controlled by (18) and starting from initial conditions (19). Further, assume predicates P_{ij}^a and P_{ij}^d are constructed according to Assumption 1. Then the constraint satisfaction set \mathcal{F}_p is invariant for the trajectories of the closed-loop hybrid system.

Proof: By dynamics (11), initial condition $\mathcal{D}_i^a(0) = \emptyset$, $\forall i \in \mathcal{V}$, and the exclusivity and persistence properties of \mathcal{D}_i^a , we conclude that $j \in \mathcal{D}_i^a(t_2)$ at time t_2 for some agent i if and only if there exists a time $t_1 \leq t_2$ such that $P_{ij}^d(t_1) \vee P_{ji}^d(t_1) = 1$ with $\|x_{ij}(t_1)\| = \rho_1$ and $j \in \mathcal{N}_i(t_1)$, i.e. a link deletion predicate for established link (i, j) was violated on the transit of a neighboring agent j over the connection boundary ρ_1 . Similarly, by dynamics (12), initial condition $\mathcal{D}_i^r(0) = \emptyset$, $\forall i \in \mathcal{V}$, and the exclusivity and persistence properties of \mathcal{D}_i^r , we conclude that $j \in \mathcal{D}_i^r(t_2)$ at time t_2 for some agent i if and only if there exists a time $t_1 \leq t_2$ such that $P_{ij}^a(t_1) \vee P_{ji}^a(t_1) = 1$ with $\|x_{ij}(t_1)\| = \rho_2$ and $j \notin \mathcal{N}_i(t_1)$, i.e. a link addition predicate for potential link (i, j) was violated on the transit of a non-neighboring agent j over the interaction boundary ρ_2 . Now, invoking Lemma 3.1, we conclude proper link discrimination occurs, i.e. there exists no member $j \in \mathcal{D}_i^a$ that becomes disconnected from an agent i , and likewise there exists no member $j \in \mathcal{D}_i^r$ that becomes a neighbor of agent i . Finally, having satisfied the requirements of Assumption 1 concerning predicate formulation, we can conclude $\bigwedge_{k=1}^{P_i} \mathcal{P}_i^k(t) = 1$, $\forall i \in \mathcal{V}, t \geq 0$, and the result follows. ■

It is clear that the proper execution of the system rests primarily on the construction of the discernment predicates, specifically with respect to the requirements imposed by Assumption 1. We dedicate the remainder of this paper to the investigation of predicates for realistic multi-agent problems, related system analysis, and simulation.

IV. AGGREGATION UNDER MAX DEGREE CONSTRAINTS

Our first coordination objective calls for the distributed system of agents to *aggregate*¹³, that is, from some initial position the group of agents must enter asymptotically into a bounded region of \mathbb{R}^m . Further, in the spirit of this work, we require that the agents respect upper bounds on the degree of local connectivity, i.e. $|\mathcal{N}_i| \leq \beta_i$, $\forall i \in \mathcal{V}$, while maintaining overall network connectedness. We suggest that by constraining dynamically the connectivity of each agent, we yield realistic aggregation behaviors in terms of limiting local communication burden and bolstering the performance of information diffusion in the network¹⁴.

Consider first a potential field $\psi_{ij}^{\text{agg}}: \mathbb{R}_+ \rightarrow \mathbb{R}_+$ for achieving the aggregation objective:

$$\psi_{ij}^{\text{agg}} = K_1 \|x_{ij}\|^2 \quad (24)$$

¹³This behavior is also referred to as *swarming* and the agent collective as a *swarm*. Without some collision avoidance requirement, aggregation is typically treated as the common rendezvous problem.

¹⁴In [23] it is shown that large node degrees induce time-delay sensitivity in networked consensus processes.

where $K_1 > 0$ is a gain parameter. Our desire is to apply ψ_{ij}^{agg} over only $j \in \mathcal{N}_i$, however note that as $\psi_{ij}^{\text{agg}}(\rho_1) \neq 0$ a discontinuity occurs upon the network switch on link addition at ρ_1 . We thus require an additional potential field $\psi_{ij}^{\text{can}}: \mathbb{R}_+ \rightarrow \mathbb{R}_+$ that *stitches* together the aggregation potential for link addition candidates in order to preserve continuity over the topology switch at ρ_1 . That is, we define

$$\psi_{ij}^{\text{can}} = a\|x_{ij}\|^2 + b\|x_{ij}\| + c \quad (25)$$

with constants a, b, c chosen such that the following properties apply:

- 1) $\psi_{ij}^{\text{can}}(\rho_1) = \psi_{ij}^{\text{agg}}(\rho_1)$ and $\partial\psi_{ij}^{\text{can}}/\partial\|x_{ij}\|(\rho_1) = \partial\psi_{ij}^{\text{agg}}/\partial\|x_{ij}\|(\rho_1)$, ensuring the ρ_1 transition is sufficiently smooth.
- 2) $\partial\psi_{ij}^{\text{can}}/\partial\|x_{ij}\|(\rho_2) = 0$, ensuring continuity over switches in the ρ_2 transition.

For the purposes of collision avoidance, consider the potential field $\psi_{ij}^{\text{col}}: \mathbb{R}_+ \rightarrow \mathbb{R}_+$ defined as [31]:

$$\psi_{ij}^{\text{col}} = \begin{cases} K_2 \log\left(\frac{1}{\|x_{ij}\|^2}\right), & \|x_{ij}\| \in (0, z) \\ \Psi_{\text{col}}(\|x_{ij}\|), & \|x_{ij}\| \in [z, \rho_0] \end{cases} \quad (26)$$

where $0 < z < \rho_0$ and $\Psi_{\text{col}} = a\|x_{ij}\|^3 + b\|x_{ij}\|^2 + c\|x_{ij}\| + d$, with constants a, b, c, d chosen such that:

- 1) $\Psi_{\text{col}}(z) = K_2 \log(1/z^2)$ and $\partial\Psi_{\text{col}}/\partial\|x_{ij}\|(z) = -2K_2/z$, ensuring continuity over the potential transition at z .
- 2) $\Psi_{\text{col}}(\rho_0) = 0$ and $\partial\Psi_{\text{col}}/\partial\|x_{ij}\|(\rho_0) = 0$, ensuring continuity of the potential over switches in the ρ_0 transition.

As we will see in the sequel, this seemingly peculiar definition of ψ_{ij}^{col} allows us to bound the potential derivative and derive bounds on the swarm size of the system.

The final control laws are now given by

$$u_i = -\nabla_{x_i} \left(\sum_{j \in \mathcal{N}_i} \psi_{ij}^{\text{agg}} + \sum_{j \in \mathcal{C}_i^a} \psi_{ij}^{\text{can}} + \sum_{j \in \Pi_i} \psi_{ij}^{\text{col}} + \sum_{j \in \mathcal{D}_i^a} \psi_{ij}^a + \sum_{j \in \mathcal{D}_i^r} \psi_{ij}^r \right) \quad (27)$$

where $\Pi_i = \{j \in \mathcal{V} \mid \|x_{ij}\| \leq \rho_0\}$ is the collision avoidance set for agent i . A composite of the potentials comprising control laws (27) is depicted in Figure 3. It is important to note that the controls (27) are continuously differentiable over switches in the network topology and transitions in the discernment sets as required for analysis with a common Lyapunov function.

A. Predicate Formulation for Max Degree Constraints

Together with controls (27) we require predicates P_{ij}^a and P_{ij}^d to dictate the switching behavior of discernment sets \mathcal{D}_i^a and \mathcal{D}_i^r in order to satisfy the maximum degree constraints $|\mathcal{N}_i| \leq \beta_i$ of Problem 1. In particular we must choose predicates that meet the specifications of Assumption 1 to guarantee constraint satisfaction under the dynamic network topology. It is implied by the predicate formulation requirements that the agents possess the capability to either evaluate or predict the impact of a link




Fig. 3. Composite of inter-agent potentials for constrained aggregation, including aggregation, collision avoidance, and link retention (blue, $j \in \mathcal{N}_i$), link denial (green, $j \in \mathcal{D}_i^r$), and continuity-preserving attraction (red, $j \in \mathcal{C}_i^a$). The interaction model parameters ρ_2, ρ_1, ρ_0 are illustrated by dashed lines.

addition or deletion before it occurs and be able to appropriately temper that knowledge against local constraints. In the case of bounding node degree, the interaction constraint is explicit to the existence of the link itself, and thus we can formulate in a straightforward manner constraints that are compliant with Assumption 1. Specifically, we consider a *worst-case* network topology as it relates to the max degree constraints, yielding link addition predicate

$$P_{ij}^a \triangleq |\mathcal{N}_i| + |\mathcal{C}_i^a| \geq \beta_i \quad (28)$$

In terms of a maximal degree bound, predicate (28) evaluates a worst-case network topology by considering *all* candidates for connection, i.e. $j \in \mathcal{C}_i^a$, as virtual neighbors of discerning agent i . In this way, the preemptive property is guaranteed as discernments always evaluate over a worst-case degree bounded network topology.

Problem 1 also dictates that connectivity be preserved over the trajectories of the system. For this purpose, we define the link deletion predicate

$$P_{ij}^d = 1 \quad (29)$$

such that all links in the network are retained and initial connectivity implies dynamic connectedness. Although the maintenance of all established links for the purposes of guaranteeing connectivity is by nature conservative, we point out that in an aggregation objective the addition of links is of primary concern.

B. Stability Analysis of Constrained Aggregation

We are now prepared to analyze the behavior of dynamics (1) under controls (27) and predicates (28), (29), with initial conditions in $\mathcal{F} \cap \mathcal{F}_C$, where $\mathcal{F}_C \triangleq \{\mathbf{x} \in \mathbb{R}^{mn} \mid \mathcal{G} \in \mathbb{C}_n\}$ is the set of agent configurations that are connected. The equilibrium, collision avoidance, and discernment set reachability properties of the system can be determined by applying the results of Section III as follows.

Theorem 4.1: Assume that the agents (1) are subject to controls (27) starting from initial conditions $\mathbf{x}(0) \in \mathcal{F} \cap \mathcal{F}_C$. Then, the system converges to an equilibrium configuration where

$u_i = 0, \forall i \in \mathcal{V}$, and the sets \mathcal{F}_C and \mathcal{F}_d are invariant for the trajectories of the closed-loop hybrid system.

Proof: By construction the objective potential field

$$\sum_{j \in \mathcal{I}_i} \psi_{ij}^o \triangleq \sum_{j \in \mathcal{N}_i} \psi_{ij}^{\text{agg}} + \sum_{j \in \mathcal{C}_i^a} \psi_{ij}^{\text{can}} + \sum_{j \in \Pi_i} \psi_{ij}^{\text{col}} \quad (30)$$

meets the standards of a generalized coordination objective, i.e. (30) is continuously differentiable over $\|x_{ij}\| \in [0, \rho_2]$ with respect to switching in $\mathcal{N}_i, \mathcal{C}_i^a$, and Π_i . It is clear then that aggregation controls (27) are equivalent in nature to (18), and we can invoke Theorem 3.1 and Lemma 3.1, yielding our desired result. ■

Now, we establish the constraint satisfaction properties of the system in the following.

Theorem 4.2: Consider the system (1) under control laws (27) and discernment predicates (28), (29), with $\mathbf{x}(0) \in \mathcal{F} \cap \mathcal{F}_C$. Further, assume the local constraint predicates are $\mathcal{P}_i^1 \triangleq |\mathcal{N}_i| \leq \beta_i, \forall i \in \mathcal{V}$. Then the constraint satisfaction set \mathcal{F}_p is invariant for the trajectories of the closed-loop hybrid system and the network remains connected for all $t \geq 0$.

Proof: Following Theorem 3.2 with link addition predicate (28) we can conclude that non-neighboring agents i and j become mutual candidates for link addition only when $|\mathcal{N}_i| + |\mathcal{C}_i^a| < \beta_i$ and $|\mathcal{N}_j| + |\mathcal{C}_j^a| < \beta_j$ hold. In conjunction with proper discrimination of link additions (guaranteed by Theorems 4.1 and 3.2) and the fact that $|\mathcal{N}_i(0)| + |\mathcal{C}_i^a(0)| \leq \beta_i$, it follows that $|\mathcal{N}_i(t)| \leq \beta_i - |\mathcal{C}_i^a(t)|, \forall i \in \mathcal{V}, t \geq 0$. Further, considering link deletion predicate (29) it is clear that no $j \in \mathcal{N}_i$ becomes a candidate for link deletion, and all established links are maintained. Noting that link retention has no effect on \mathcal{P}_i^1 , we can finally conclude that $\bigwedge_{i=1}^n \mathcal{P}_i^1(t) = 1$ and $\mathbf{x}(t) \in \mathcal{F}_C$ (due to link maintenance over an initially connected network) for all $t \geq 0$, our desired result. ■

From the preceding analysis we can conclude that the system is convergent to a static state and that the desired collision avoidance and constraint satisfaction requirements are abided. However, it remains to determine whether the system behavior constitutes aggregation, that is, at equilibrium have the agents entered into a bounded region of the workspace. We begin our analysis of the coordination behavior by defining the center of the agent collective, known as the *swarm center*, given by $\bar{x} \triangleq \frac{1}{n} \sum_{i=1}^n x_i$. Notice that as $u_i = \sum_j f(x_i - x_j)$, and by construction anti-symmetry $f(x_i - x_j) = -f(x_j - x_i)$ holds, it follows that $\dot{\bar{x}} = 0$, that is the swarm center is invariant over the trajectories of the system [31], [32]. Therefore, without loss of generality, for the following analysis we choose \bar{x} as the origin of our coordinate system and define the swarm energy function

$$V_s = \frac{1}{2} \sum_{i=1}^n \|x_i\|^2 \quad (31)$$

Note that V_s is positive semi-definite and $V_s \rightarrow 0$ as $x_i \rightarrow \bar{x}, \forall i \in \mathcal{V}$, i.e. upon agent rendezvous. The time derivative of V_s is then

$$\dot{V}_s = \frac{1}{2} \sum_{i=1}^n \frac{\partial \|x_i\|^2}{\partial \|x_i\|} \left(\frac{\partial \|x_i\|}{\partial x_i} \right)^T \dot{x}_i = \sum_{i=1}^n x_i^T u_i \quad (32)$$

Applying the chain rule to controls (27), plugging into (32), and exploiting the potential and discernment set symmetry then

yields

$$\begin{aligned} \dot{V}_s = & - \sum_{i=1}^n \left(\sum_{j \in \mathcal{N}_i} \delta_{\text{agg}} \|x_{ij}\|^2 + \sum_{j \in \mathcal{C}_i^a} \delta_{\text{can}} \|x_{ij}\|^2 \right. \\ & - \sum_{j \in \Pi_i} |\delta_{\text{col}}| \|x_{ij}\|^2 + \sum_{j \in \mathcal{D}_i^a} \delta_a \|x_{ij}\|^2 \\ & \left. - \sum_{j \in \mathcal{D}_i^r} |\delta_r| \|x_{ij}\|^2 \right) \end{aligned} \quad (33)$$

where for clarity we let $\delta_{\square} \triangleq \partial \psi_{ij}^{\square} / \partial \|x_{ij}\|^2$, and we use the fact that $\delta_{\text{col}} \leq 0, \forall j \in \Pi_i$ and $\delta_r \leq 0, \forall j \in \mathcal{D}_i^r$. Now consider the derivative bounds, $\delta_{\text{agg}} = K_1, \delta_{\text{can}} \geq 0, \delta_a \geq 0, |\delta_{\text{col}}| \leq K_2 / \|x_{ij}\|^2$ and $|\delta_r| \leq \kappa$, and agent displacement bound $\|x_{ij}\| \leq \rho_2, \forall j \in \mathcal{D}_i^r$, which when applied to (33) gives the following bound on the time derivative of the swarm energy:

$$\dot{V}_s \leq -K_1 \sum_{i=1}^n \sum_{j \in \mathcal{N}_i} \|x_{ij}\|^2 + \sum_{i=1}^n (K_2 |\Pi_i| + \kappa \rho_2^2 |\mathcal{D}_i^r|) \quad (34)$$

Now, we can derive an upper bound on the swarm size by determining the conditions under which the swarm energy is decreasing, $\dot{V}_s < 0$. That is,

$$\sum_{i=1}^n \sum_{j \in \mathcal{N}_i} \|x_{ij}\|^2 > \frac{1}{K_1} \sum_{i=1}^n (K_2 |\Pi_i| + \kappa \rho_2^2 |\mathcal{D}_i^r|) \quad (35)$$

By Theorem 4.2 we know that for all time \mathcal{G} is connected and thus we can assume

$$\hat{\mathbf{x}} \triangleq \max_{i,j \in \mathcal{V}} \|x_{ij}\|^2 \leq \sum_{i=1}^n \sum_{j \in \mathcal{N}_i} \|x_{ij}\|^2 \quad (36)$$

where $\hat{\mathbf{x}}$ is the squared *swarm size*. We then have $\dot{V}_s < 0$ whenever

$$\hat{\mathbf{x}} > \frac{1}{K_1} \sum_{i=1}^n (K_2 |\Pi_i| + \kappa \rho_2^2 |\mathcal{D}_i^r|) \quad (37)$$

It is important to notice that the right-hand side of (37) switches with the dynamics of the network topology and discernment sets¹⁵. To obtain a bound over all possible network and discernment topologies, we consider the worst case of (37) yielding the final swarm bound

$$\hat{\mathbf{x}} \leq \frac{1}{K_1} \sum_{i=1}^n \max_{\mathcal{G}} (K_2 |\Pi_i| + \kappa \rho_2^2 |\mathcal{D}_i^r|) \quad (38)$$

As the terms of (38) are finite, we can conclude that the agents enter into a bounded region of the workspace, that is the desired aggregation behavior is achieved.

Remark 4.1 (Bounded repulsion): The bound κ on δ_r can be derived using the method proposed by Ji and Egerstedt in [32]. Briefly, we consider the Lyapunov function as in (20) and determine the maximum energy that can be generated over the possible network and discernment topologies. We then allocate

this maximal energy to $\psi_{ij}^r(d_{\min})$, where d_{\min} is the minimum distance from ρ_1 that can be achieved. That is, we solve

$$\max_{\mathcal{G}} (V) = \psi_{ij}^r(d_{\min}) \quad (39)$$

for d_{\min} , yielding bound $\kappa = \delta_r(d_{\min})$. Of course, one could also apply a bounded potential field for repulsion, however constraint satisfaction would no longer be guaranteed.

Remark 4.2 (Exact bound): To obtain an explicit form of bound (38), the problem $\max_{\mathcal{G}} (K_2 |\Pi_i| + \kappa \rho_2^2 |\mathcal{D}_i^r|)$ can be solved as follows. Notice first that as no links are lost by Theorem 4.2 we have $|\mathcal{N}_i(t)| \geq |\mathcal{N}_i(0)|, \forall i \in \mathcal{V}, t > 0$, requiring $|\mathcal{D}_i^r(t)| \leq n - |\mathcal{N}_i(0)| - 1, \forall i \in \mathcal{V}, t > 0$. We then have solution set

$$\begin{cases} K_2 \beta_i + \kappa \rho_2^2 (n - \beta_i - 1), & K_2 \geq \kappa \rho_2^2 \\ K_2 |\mathcal{N}_i(0)| + \kappa \rho_2^2 (n - |\mathcal{N}_i(0)| - 1), & K_2 < \kappa \rho_2^2 \end{cases} \quad (40)$$

dependent on parameter selection.

V. DISPERSION UNDER MIN DEGREE CONSTRAINTS

We now consider solving Problem 2 by defining local controls that ensure the agents *disperse*, while respecting lower bounds on the degree of local connectedness, $|\mathcal{N}_i| \geq \omega_i, \forall i \in \mathcal{V}$. Analogous to the aggregation behavior, realistic dispersive dynamics are generated by forcing a minimal level of agent connectivity, as information exchange processes are guaranteed a minimum level of performance¹⁶. More generally, we can also envision a system in which the agents act to maximize coverage area through dispersion (e.g. threat monitoring, environmental sampling, etc.), while maintaining certain critical links in the network as defined by some mission objective or metric.

The dispersion objective is achieved by defining potential field $\psi_{ij}^{\text{dis}}: \mathbb{R}_+ \rightarrow \mathbb{R}_+$ given by

$$\psi_{ij}^{\text{dis}} = \frac{K_3}{\|x_{ij}\|^2} + a \|x_{ij}\|^2 + b \|x_{ij}\| + c \quad (41)$$

where $K_3 > 0$ is a gain parameter and we choose constants a, b, c such that $\psi_{ij}^{\text{dis}}(\rho_2) = 0$ and $\partial \psi_{ij}^{\text{dis}} / \partial \|x_{ij}\|(\rho_2) = 0$, ensuring sufficient smoothness of the potential on link loss at ρ_2 . Notice that in this case, collision avoidance is implicit to the potential (41). Our control laws for constrained dispersion are then

$$u_i = -\nabla_{x_i} \left(\sum_{j \in \mathcal{N}_i} \psi_{ij}^{\text{dis}} + \sum_{j \in \mathcal{D}_i^a} \psi_{ij}^a + \sum_{j \in \mathcal{D}_i^r} \psi_{ij}^r \right) \quad (42)$$

Figure 4 depicts a composite of the potentials composing control laws (42).

Predicates for constraint satisfaction are derived in a manner similar to aggregation, by considering worst-case network topologies relative to the minimum degree constraint. Specifically, the link deletion predicate takes the form

$$P_{ij}^d \triangleq |\mathcal{N}_i| - |\mathcal{C}_i^d| \leq \omega_i \quad (43)$$

¹⁵The left-hand term clearly switches as well. However, as edges are never lost, and $\hat{\mathbf{x}}$ is non-decreasing on link additions, we conclude that condition (37) is valid for all network configurations over the system trajectories.

¹⁶In [11] it is shown that increased connectedness is correlated with improved consensus in networked systems.




Fig. 4. Composite of inter-agent potentials for constrained dispersion, including dispersion (blue, $j \in \mathcal{N}_i$), link retention (red, $j \in \mathcal{D}_i^a$), and link denial (green, $j \in \mathcal{D}_i^r$). The interaction model parameters ρ_2, ρ_1, ρ_0 are illustrated by dashed lines.

By considering *all* candidates for deletion, i.e. $j \in \mathcal{C}_i^d$, as virtual non-neighbors, predicate (43) discerns link loss over a worst-case network topology with respect to the minimum degree constraint. Problem 2 also requires that no links are added during the system execution. For that purpose we define link addition predicate

$$P_{ij}^a = 1 \quad (44)$$

guaranteeing that all non-neighbor agents that enter the discernment region are repelled.

A. Stability Analysis of Constrained Dispersion

We now determine the behavior of dynamics (1) under controls (42) and predicates (43), (44). The equilibrium, collision avoidance, and discernment set reachability properties of the system can be determined by applying the results of Section III as follows.

Theorem 5.1: Assume that the agents (1) are subject to controls (42) starting from initial conditions $\mathbf{x}(0) \in \mathcal{F} \cap \mathcal{F}_C$. Then, the system converges to an equilibrium configuration where $u_i = 0, \forall i \in \mathcal{V}$, and the sets \mathcal{F}_c and \mathcal{F}_d are invariant for the trajectories of the closed-loop hybrid system.

Proof: By construction the objective potential field $\sum_{j \in \mathcal{I}_i} \psi_{ij}^o \triangleq \sum_{j \in \mathcal{N}_i} \psi_{ij}^{\text{dis}}$ meets the standards of a generalized coordination objective, i.e. ψ_{ij}^{dis} is continuously differentiable over $\|x_{ij}\| \in [0, \rho_2]$ with respect to switching in \mathcal{N}_i . It is clear then that dispersion controls (42) are equivalent in nature to (18), and invoking Theorem 3.1 and Lemma 3.1, the result follows. ■

Now, we establish the constraint satisfaction properties of the system in the following.

Theorem 5.2: Consider the system (1) under control laws (42) and discernment predicates (43), (44), with $\mathbf{x}(0) \in \mathcal{F} \cap \mathcal{F}_C$. Further, assume the goal constraint predicates are $\mathcal{P}_i^1 \triangleq |\mathcal{N}_i| \geq \omega_i, \forall i \in \mathcal{V}$. Then the constraint satisfaction set \mathcal{F}_p is invariant for the trajectories of the closed-loop hybrid system.

Proof: Following Theorem 3.2 with link deletion predicate (43) we can conclude that neighboring agents i and j become mutual candidates for link deletion only when $|\mathcal{N}_i| - |\mathcal{C}_i^d| > \omega_i$ and $|\mathcal{N}_j| - |\mathcal{C}_j^d| > \omega_j$ hold. In conjunction with proper

discrimination of link deletions (guaranteed by Theorems 5.1 and 3.2) and the fact that $|\mathcal{N}_i(0)| - |\mathcal{C}_i^d(0)| \geq \omega_i$, it follows that $|\mathcal{N}_i(t)| \geq \omega_i + |\mathcal{C}_i^d(t)|, \forall i \in \mathcal{V}, t \geq 0$. Further, considering link addition predicate (44) it is clear that no $j \notin \mathcal{N}_i$ becomes a candidate for link addition, and thus no new links are established. Noting that link denial has no effect on \mathcal{P}_i^1 , we can finally conclude that $\bigwedge_{i=1}^n \mathcal{P}_i^1(t) = 1$ for all $t \geq 0$, our desired result. ■

With knowledge that the system is convergent and respects our desired collision avoidance and constraint satisfaction requirements, we now determine whether the induced coordination behavior is indeed dispersive. Consider once again the swarm energy V_s , in this context having time derivative

$$\begin{aligned} \dot{V}_s = \sum_{i=1}^n \left(\sum_{j \in \mathcal{D}_i^a} (|\delta_{\text{dis}}| - \delta_a) \|x_{ij}\|^2 + \sum_{j \in \Delta_i} |\delta_{\text{dis}}| \|x_{ij}\|^2 \right. \\ \left. + \sum_{j \in \Theta_i} |\delta_{\text{dis}}| \|x_{ij}\|^2 + \sum_{j \in \mathcal{D}_i^r} |\delta_r| \|x_{ij}\|^2 \right) \end{aligned} \quad (45)$$

where we further partition the interaction region by defining sets

$$\begin{aligned} \Delta_i &= \{j \in \mathcal{V} \mid j \in \mathcal{N}_i, \|x_{ij}\| \leq \rho_1\} \\ \Theta_i &= \{j \in \mathcal{V} \mid j \in \mathcal{N}_i \cap \overline{\mathcal{D}_i^a}, \|x_{ij}\| > \rho_1\} \end{aligned} \quad (46)$$

with $\overline{\mathcal{D}_i^a}$ denoting the complement of \mathcal{D}_i^a . Now consider derivative bounds, $|\delta_{\text{dis}}| \geq 0, \delta_a \leq \tau, \forall j \in \mathcal{D}_i^a, |\delta_{\text{dis}}| \geq |\delta_{\text{dis}}(\rho_1)|, \forall j \in \Delta_i, |\delta_{\text{dis}}| \geq 0, \forall j \in \Theta_i$, and $|\delta_r| \geq 0, \forall j \in \mathcal{D}_i^r$, together with agent displacement bound $\|x_{ij}\| \leq \rho_2, \forall j \in \mathcal{D}_i^a$, yielding

$$\dot{V}_s \geq -\tau \rho_2^2 \sum_{i=1}^n |\mathcal{D}_i^a| + |\delta_{\text{dis}}(\rho_1)| \sum_{i=1}^n \sum_{j \in \Delta_i} \|x_{ij}\|^2 \quad (47)$$

Thus, for dispersive action, i.e. $\dot{V}_s > 0$, we require

$$\sum_{i=1}^n \sum_{j \in \Delta_i} \|x_{ij}\|^2 > \frac{\tau \rho_2^2}{|\delta_{\text{dis}}(\rho_1)|} \sum_{i=1}^n |\mathcal{D}_i^a| \quad (48)$$

As the network is assumed to be initially connected with $|\mathcal{D}_i^a|(0) = 0, \forall i \in \mathcal{V}$ and $0 < \|x_{ij}(0)\| \leq \rho_1, \forall i, j \in \mathcal{V}$, we have $\dot{V}_s > 0$ if

$$\sum_{i=1}^n \sum_{j \in \Delta_i} \|x_{ij}\|^2 > 0 \quad (49)$$

which always holds. We therefore have the following intuitive result. For any valid initial configuration $\mathbf{x} \in \mathcal{F} \cap \mathcal{F}_C$, the agents are guaranteed to disperse until a point when some agent j becomes a member of a set \mathcal{D}_i^a , an occurrence that results from j being a minimum degree violation risk.

Remark 5.1 (Bounded attraction): The bound τ on δ_a can be derived using the steps described in Remark 4.1, that is by applying the method proposed by Ji and Egerstedt in [32]. In this case however, we would determine a maximal distance d_{max} achievable between an agent i and a neighbor j under attractive potential ψ_{ij}^a .




Fig. 5. Aggregation simulations of an $n = 10$ agent system with interaction model $\rho_2 = 10$, $\rho_1 = 7$, and $\rho_0 = 2$, under maximum degree constraints $|\mathcal{N}_i| \leq 6$ [(a)-(c)] and $|\mathcal{N}_i| \leq 5$ [(d)-(f)]: (a) random initial configuration; (b) intermediate configuration $|\mathcal{N}_i| \leq 6$; (c) final converged configuration $|\mathcal{N}_i| \leq 6$; (d) initial ring network configuration; (e) final converged configuration $|\mathcal{N}_i| \leq 4$; and (f) final converged configuration $|\mathcal{N}_i| \leq 5$.

VI. SIMULATION RESULTS

In this section, we present simulation results of our proposed control scheme for the constrained interaction of proximity-limited mobile agents, and show that the desired interactivity constraints, collision avoidance and connectivity properties hold. In particular, we consider the coordination scenarios of aggregation and dispersion analyzed in Sections IV and V, subject to maximum and minimum degree constraints, respectively. For all simulations we consider $n = 10$ agents operating in a bounded workspace over \mathbb{R}^2 , with interaction model parameters $\rho_2 = 10$, $\rho_1 = 7$, and $\rho_0 = 2$. First, we consider the agents driven by constrained aggregation controls (27) and subject to discernment predicates (28), (29). Two initial agent configurations are considered, a random placement of agents in the workspace (Fig. 5a), and a *ring network* of radius 10 (Fig. 5d), each satisfying initial condition requirement $\mathbf{x} \in \mathcal{F} \cap \mathcal{F}_C$. To the randomly placed network we apply maximal degree bound $\beta_i = 6$, $\forall i \in \mathcal{V}$, yielding intermediate configuration (Fig. 5b) and final configuration (Fig. 5c). For the ring network, we assume the cases of $\beta_i = 4$, $\forall i \in \mathcal{V}$ and $\beta_i = 5$, $\forall i \in \mathcal{V}$, yielding final configurations (Fig. 5e) and (Fig. 5f), respectively. As illustrated by the maximum node degree and swarm size over the simulations (Fig. 7a), the switching discernment controls satisfy the desired interaction constraints, avoid collisions, and maintain the con-

nectedness of the resulting network, while driving the agents to perform a coordinated aggregation objective.

Now, we consider the agents driven by constrained dispersion controls (42) and subject to discernment predicates (43), (44). In this case, a fully connected ring network of radius 2.5 is considered for the initial agent configuration (Fig. 6a), again satisfying initial condition $\mathbf{x} \in \mathcal{F} \cap \mathcal{F}_C$. We assume the cases of minimal degree bounds $\omega_i = 5$, $\forall i \in \mathcal{V}$ and $\omega_i = 3$, $\forall i \in \mathcal{V}$, yielding final configurations (Fig. 6b) and (Fig. 6c), respectively. From the minimum node degree and swarm size over the simulations (Fig. 7b), we see that the controls satisfy our desired interaction constraints while avoiding collisions, resulting in a topology-aware, coordinated dispersion objective.

VII. CONCLUSIONS AND FUTURE WORK

In this paper, we considered the problem of controlling the interactions of a group of mobile agents, such that a set of topological constraints were satisfied. Assuming proximity-limited communication between agents, we leveraged mobility to enable adjacent agents to achieve discriminative connectivity, that is, to actively retain established links or reject link creation on the basis of constraint satisfaction. Specifically, we proposed a distributed scheme consisting of controllers with discrete switching for link discrimination, whereby adjacent agents were classi-




Fig. 6. Dispersion simulations of an $n = 10$ agent system with interaction model $\rho_2 = 10$, $\rho_1 = 7$, and $\rho_0 = 2$, under minimum degree constraints $|\mathcal{N}_i| \geq 5$ [(b)] and $|\mathcal{N}_i| \geq 3$ [(c)]: (a) initial fully connected ring network configuration; (b) final converged configuration $|\mathcal{N}_i| \geq 5$; and (c) final converged configuration $|\mathcal{N}_i| \geq 3$.

fied as either candidates for constraint-aware link removal or addition, or as constraint violators requiring either link retention through attraction or link denial through repulsion. Attractive and repulsive potentials fields established the local controls necessary for link discrimination and constraint violation predicates formed the basis for discernment. We analyzed the application of constrained interaction to two canonical coordination objectives in distributed multi-agent systems: aggregation and dispersion behaviors, with maximum and minimum node degree constraints, respectively. For each task, we proposed predicates and continuity-preserving potential fields and proved the dynamical and constraint satisfaction properties of the resulting hybrid system. Simulation results demonstrated the correctness of our proposed methods and the ability of our framework to generate topology-aware self organization.

Directions for future work include investigating the satisfaction of non-local topological constraints (e.g. k -hop connectivity) through local discernment and inter-agent communication, determining existential guarantees for predicate formulations that solve certain classes of constraint problems, and exploring constraints that are not explicitly topological in nature (e.g. mutual information, agent similarity or compatibility measures, etc.).

REFERENCES

- [1] R. Sepulchre, D. A. Paley, and N. E. Leonard, "Stabilization of Planar Collective Motion With Limited Communication," *IEEE Transactions on Automatic Control*, 2008.
- [2] M. De Gennaro and A. Jadbabaie, "Formation control for a cooperative multi-agent system using decentralized navigation functions," in *American Control Conference*, 2006.
- [3] M. Porfiri, D. G. Roberson, and D. J. Stilwell, "Tracking and formation control of multiple autonomous agents: A two-level consensus approach," *Automatica*, 2007.
- [4] R. K. Williams and G. S. Sukhatme, "Probabilistic Spatial Mapping and Curve Tracking in Distributed Multi-Agent Systems," in *IEEE International Conference on Robotics and Automation*, 2012.
- [5] —, "Cooperative Multi-Agent Inference Over Grid-Structured Markov Random Fields," in *IEEE/RSJ International Conference on Intelligent Robots and Systems*, 2011.
- [6] F. Zhang and N. E. Leonard, "Cooperative Kalman filters for cooperative exploration," in *American Control Conference*, 2008.
- [7] R. Olfati-Saber and N. Sandell, "Distributed tracking in sensor networks with limited sensing range," in *American Control Conference*, 2008.
- [8] R. Olfati-Saber, "Distributed Tracking for Mobile Sensor Networks with Information-Driven Mobility," in *American Control Conference*, 2007.
- [9] S. Martínez and F. Bullo, "Optimal sensor placement and motion coordination for target tracking," *Automatica*, 2006.
- [10] J. Fax and R. M. Murray, "Information flow and cooperative control of vehicle formations," *IEEE Transactions on Automatic Control*, 2004.
- [11] R. Olfati-Saber, J. Fax, and R. M. Murray, "Consensus and Cooperation in Networked Multi-Agent Systems," *Proceedings of the IEEE*, 2007.
- [12] Y. Liu, K. Passino, and M. Polycarpou, "Stability analysis of M-dimensional asynchronous swarms with a fixed communication topology," *IEEE Transactions on Automatic Control*, 2003.
- [13] R. Olfati-Saber, "Distributed Kalman filtering for sensor networks," in *IEEE Conference on Decision and Control*, 2007.
- [14] R. Olfati-Saber and J. Shamma, "Consensus Filters for Sensor Networks and Distributed Sensor Fusion," in *IEEE Conference on Decision and Control and European Control Conference*, 2005.
- [15] E. Franco, R. Olfati-Saber, T. Parisini, and M. Polycarpou, "Distributed Fault Diagnosis using Sensor Networks and Consensus-based Filters," in *IEEE Conference on Decision and Control*, 2006.
- [16] A. Nedic, A. E. Ozdaglar, and P. A. Parrilo, "Constrained Consensus and Optimization in Multi-Agent Networks," *IEEE Transactions on Automatic Control*, 2010.
- [17] A. Nedic and A. E. Ozdaglar, "Distributed Subgradient Methods for Multi-Agent Optimization," *IEEE Transactions on Automatic Control*, 2009.
- [18] M. Zhu and S. Martínez, "On distributed optimization under inequality constraints via Lagrangian primal-dual methods," in *American Control Conference*, 2010.
- [19] I. Schizas, A. Ribeiro, and G. Giannakis, "Consensus-Based Distributed Parameter Estimation in Ad Hoc Wireless Sensor Networks with Noisy Links," in *IEEE International Conference on Acoustics, Speech and Signal Processing*, 2007.
- [20] I. Schizas, A. Ribeiro, and G. Giannakis, "Consensus in Ad Hoc WSNs With Noisy Links - Part I: Distributed Estimation of Deterministic Signals," *IEEE Transactions on Signal Processing*, 2008.
- [21] S. Barbarossa and G. Scutari, "Decentralized Maximum-Likelihood Estimation for Sensor Networks Composed of Nonlinearly Coupled Dynamical Systems," *IEEE Transactions on Signal Processing*, 2007.
- [22] R. Olfati-Saber and R. M. Murray, "Consensus protocols for networks of dynamic agents," in *American Control Conference*, 2003.
- [23] —, "Consensus problems in networks of agents with switching topology and time-delays," *IEEE Transactions on Automatic Control*, 2004.
- [24] D. Spanos and R. M. Murray, "Robust connectivity of networked vehicles," in *IEEE Conference on Decision and Control*, 2004.
- [25] M. M. Zavlanos and G. J. Pappas, "Distributed Connectivity Control of Mobile Networks," *IEEE Transactions on Robotics*, 2008.
- [26] —, "Potential Fields for Maintaining Connectivity of Mobile Networks," *IEEE Transactions on Robotics*, 2007.
- [27] M. De Gennaro and A. Jadbabaie, "Decentralized Control of Connectivity for Multi-Agent Systems," in *IEEE Conference on Decision and Control*, 2006.




Fig. 7. Node degree bounds and swarm size for aggregation and dispersion simulations depicted in Figs. 5 and 6: (a) maximum node degree (top) and swarm size (bottom) for $|\mathcal{N}_i| \leq 6$ (blue, [Fig. 5c]), $|\mathcal{N}_i| \leq 4$ (red, [Fig. 5e]), and $|\mathcal{N}_i| \leq 5$ (green, [Fig. 5f]); and (b) minimum node degree (top) and swarm size (bottom) for $|\mathcal{N}_i| \geq 3$ (blue, [Fig. 6c]) and $|\mathcal{N}_i| \geq 5$ (red, [Fig. 6b]).

- [36] J. Cortes, S. Martínez, and F. Bullo, "Robust rendezvous for mobile autonomous agents via proximity graphs in arbitrary dimensions," *IEEE Transactions on Automatic Control*, 2006.
- [37] S. Martínez, J. Cortes, and F. Bullo, "Motion Coordination with Distributed Information," *Control Systems Magazine, IEEE*, 2007.
- [38] M. M. Zavlanos, M. Egerstedt, and G. J. Pappas, "Graph-Theoretic Connectivity Control of Mobile Robot Networks," in *Proceedings of the IEEE*, 2011.
- [39] J. Lygeros, K. H. Johansson, S. N. Simic, J. Zhang, and S. S. Sastry, "Dynamical properties of hybrid automata," *IEEE Transactions on Automatic Control*, 2003.
- [40] R. Decarlo, M. Branicky, S. Pettersson, and B. Lennartson, "Perspectives and results on the stability and stabilizability of hybrid systems," *Proceedings of the IEEE*, 2000.
- [41] K. H. Johansson, M. Egerstedt, J. Lygeros, and S. Sastry, "On the regularization of Zeno hybrid automata," *Systems & control letters*, 1999.



Ryan K. Williams received the B.S. degree in computer engineering from Virginia Polytechnic Institute and State University, Blacksburg, Virginia in 2005. As a Viterbi fellowship recipient, he is currently working toward the Ph.D. degree in electrical engineering at the University of Southern California, Los Angeles.

His current research interests include control, cooperation, and intelligence in distributed multi-agent systems, consensus methods for modeling distributed cooperative phenomena, and distributed algorithms for optimization, estimation, inference, and learning.

He also has a patent pending for his work on high-speed autonomous underwater vehicles.



Gaurav S. Sukhatme is a Professor of Computer Science (joint appointment in Electrical Engineering) at the University of Southern California (USC). He received his undergraduate education at IIT Bombay in Computer Science and Engineering, and M.S. and Ph.D. degrees in Computer Science from USC. He is the co-director of the USC Robotics Research Laboratory and the director of the USC Robotic Embedded Systems Laboratory which he founded in 2000. His research interests are in robot networks with applications to environmental monitoring. He has published extensively in these and related areas. Sukhatme has served as PI on numerous NSF, DARPA and NASA grants. He is a Co-PI on the Center for Embedded Networked Sensing (CENS), an NSF Science and Technology Center. He is a fellow of the IEEE and a recipient of the NSF CAREER award and the Okawa foundation research award. He is one of the founders of the Robotics: Science and Systems conference. He was program chair of the 2008 IEEE International Conference on Robotics and Automation and is program chair of the 2011 IEEE/RSJ International Conference on Intelligent Robots and Systems. He is the Editor-in-Chief of *Autonomous Robots* and has served as Associate Editor of the *IEEE Transactions on Robotics and Automation*, the *IEEE Transactions on Mobile Computing*, and on the editorial board of *IEEE Pervasive Computing*.

- [28] P. Yang, R. A. Freeman, G. J. Gordon, K. M. Lynch, S. S. Srinivasa, and R. Sukthankar, "Decentralized estimation and control of graph connectivity for mobile sensor networks," *Automatica*, 2010.
- [29] M. M. Zavlanos and G. J. Pappas, "Controlling Connectivity of Dynamic Graphs," in *IEEE Conference on Decision and Control*, 2005.
- [30] D. Dimarogonas and K. Johansson, "Decentralized connectivity maintenance in mobile networks with bounded inputs," in *IEEE International Conference on Robotics and Automation*, 2008.
- [31] D. Dimarogonas and K. Kyriakopoulos, "Connectedness Preserving Distributed Swarm Aggregation for Multiple Kinematic Robots," *IEEE Transactions on Robotics*, 2008.
- [32] M. Ji and M. Egerstedt, "Distributed Coordination Control of Multiagent Systems While Preserving Connectedness," *IEEE Transactions on Robotics*, 2007.
- [33] S. Poduri and G. S. Sukhatme, "Constrained coverage for mobile sensor networks," in *IEEE International Conference on Robotics and Automation*, 2004.
- [34] J.-M. McNew and E. Klavins, "Locally Interacting Hybrid Systems with Embedded Graph Grammars," in *IEEE Conference on Decision and Control*, 2006.
- [35] R. K. Williams and G. S. Sukhatme, "Distributed Connectivity Control in Mobile Networks Under Local Topology Constraints," in *IEEE Conference on Decision and Control (submitted)*, 2012.