

Expanding the Computational Model of Graded Cueing: Robots Encouraging Health Behavior Change

Jillian Greczek and Maja Matarić

University of Southern California
[greczek, mataric]@usc.edu

Abstract

These late breaking results present a study extending the implementation of a computational model of graded cueing feedback from our previous work (Greczek et al., 2014). The model was extended to a nutrition education task with two sub-goals. Graded cueing helped 92.3% of participants to reach the correct answer, providing further evidence for the potential of the graded cueing model to promote user autonomy in health behavior tasks.

Introduction

As robot hardware, software, and affordability improve, studies involving socially assistive robots (SARs) will grow in scale, both in duration and the number of participants. Consequently, we will be able to examine how human-robot relationships can be built, sustained, and used to educate and train users in new health behaviors and self-management techniques. However, not all robot-mediated interventions can go on indefinitely. Finite interventions should encourage user autonomy, so the user can remain effective in the new behavior after the intervention has ended and the robot is gone.

Treating a patient as an *apprentice* rather than a *dependent* has been shown to result in greater proficiency at self-management (Moore 2012). This philosophy of patient-centered care respects the humanity of individuals with chronic conditions and other persistent healthcare problems. Importantly, this perspective must be incorporated into the design and implementation of robot-mediated healthcare interventions in order for them to be accepted by real-world users.

Our initial approach toward encouraging user autonomy and promoting generalized skill learning through robot-mediated intervention was to model the occupational

therapy technique of *graded cueing* (Bottari 2010). Graded cueing involves giving therapy patients the minimum required feedback while guiding them through a task. The goal of this process is to empower patients with autonomy to perform health behaviors outside of therapist intervention. The key challenge in giving graded cueing feedback is to strike a balance between promoting autonomy and preventing monotony or frustration.

Methods

Our computational model of graded cueing is a probabilistic model of first prompt choice. The model consists of all possible levels of feedback as a list of states, ordered by increasing specificity. P0 in Figure 1 represents the success state. The goal of the model is to select the *first* prompt to give the user depending on the user's ability level.




Figure 1: A one-goal, one-step task with N levels of specificity.

Ideally, this first prompt is adequately matched to the user's ability level, and this is all that is required for the user to correctly complete the task. If not, any subsequent prompt required is the next most specific prompt on the list. To achieve rapid adaptation over a short interaction period, a probabilistic model was used, wherein the model maintains a distribution over the states, is updated based on user responses, and selects actions by sampling from the distribution.

The graded cueing model was previously implemented in a study with children with autism spectrum disorders (ASDs) we conducted. In that study, using graded cueing

feedback was found to be beneficial to task performance compared to maximally specific feedback (Greczek et al. 2014). The model was implemented for an imitation game played between a Nao robot and a child with an ASD. The implementation consisted of one step (copy the robot) and one goal (imitation accuracy above a threshold). For the presented study, graded cueing was implemented for a task with one step and multiple goals.

This study of the graded cueing model was part of a larger, multi-session study to examine child-robot relationship-building across six interaction sessions over three weeks. The basis for interaction was the robot character teaching children about healthy food choices through a nutrition education game. During the second session of each week, the goal of the game was for the child to find all the healthy (prop) foods and place them on the plate. This resulted in two sub-goals: one for getting all the healthy foods on the plate, and one for not having any unhealthy foods on the plate (shown in Figure 2). These sub-goals were implemented with ranked levels of feedback for each individual food item.




Figure 2: A one-goal, one-step task with N levels of specificity.

Feedback to remove unhealthy foods was first priority; then, if there were no unhealthy foods left, feedback to add more healthy foods was given. More details about the experimental design can be found in the full study publication by Short et al. (2014).

Results

Overall, 92.3% of sessions saw the participant reach the correct answer, and 91.7% of sessions required at least one prompt from the robot. 204 prompts were given during the “lunch” lesson (Day 2), 93 during the “snacks” lesson (Day 4), and 59 during the “dinner” lesson (Day 6), for a total of 356 total prompts. The per-day breakdown of the average number of prompts required by all participants is shown in Figure 3.

Because most of the participants chose the correct foods by the end of each interaction, the graded cueing feedback likely did not hinder the participants’ progress. While the type of prompts were different during each lesson, the




Figure 3: The average number of prompts required per session.

number of prompts required during each lesson decreased over time, which suggests that participants improved on the task over time. However, there is still a question of how much the skills learned *during these intervention* will persist after the robot is gone.

Conclusion

This work aims to address HRI research problems related to building human-robot relationships and promoting user autonomy. When a social bond is likely to develop during a robot-mediated intervention, it can also be used to influence user behavior for the better. However, robot-mediated interventions have a finite duration, at least for the foreseeable future. Thus, the question of promoting user autonomy is especially important, given that the robot will not always be present/active, or stay with the user forever. Our goal is to develop methods that will enable a socially assistive robot to enter someone’s life, facilitate desired behavior changes, but also leave lasting benefits that continue beyond the intervention.

References

- Bottari, C. L., Dassa, C., Rainville, C. M., & Dutil, É. (2010). The IADL Profile: Development, content validity, intra- and interrater agreement. *Canadian Journal of Occupational Therapy*, 77(2), 90–100.
- Greczek, J., Kaszubski, E., Atrash, A. and M. J. Matarić. "Graded Cueing Feedback in Robot-Mediated Imitation Practice for Children with Autism Spectrum Disorders". In *23rd IEEE Symposium on Robot and Human Interactive Communication (RO-MAN '14)*, Edinburgh, Scotland, UK, Aug 2014.
- Moore, J. (2012). A New Wave of Patient-Centered Care: Apprenticeship in the Management of Chronic Disease. *JCOM*, 19(7), 293–300.
- Short, E., Swift-Spong, K., Greczek, J., Ramachandran, A., Litoiu, A., Grigore, E. C., Feil-Seifer, D.... (others), Ragusa, G., Spruijt-Metz, D., Matarić, M. J. and B. Scassellati. "How to Train Your DragonBot: Socially Assistive Robots for Teaching Children About Nutrition Through Play". In *23rd IEEE Symposium on Robot and Human Interactive Communication (RO-MAN '14)*, Aug 2014.