

# DC Behavior of Conductive Fabric Networks with Application to Wearable Sensor Nodes

Eric Wade, H. Harry Asada  
Massachusetts Institute of Technology  
d'Arbeloff Laboratory for Information Systems and Technology  
Mechanical Engineering Department  
Cambridge, MA, USA  
[erwade@mit.edu](mailto:erwade@mit.edu), [asada@mit.edu](mailto:asada@mit.edu)

## Abstract

*Wearable monitoring networks are designed to augment and improve daily life. These systems require sensors and various electrical components to be mounted on the body. We propose a novel technique of using a DC powerline-carrier communication system to integrate the system components. This simplifies the wiring and the routing of connectors, and reduces the system weight and bulk. We use conductive fabrics as the transmission medium of the system. A method of predicting the DC behavior of such a garment is presented, and its utility in the design of such garments is discussed.*


## 1 Introduction

Wearable computing applications are becoming more and more pervasive. The creation of more powerful computational devices and sensors allows us to place intelligent components on the human body for purposes such as entertainment, rehabilitation, and monitoring. In the particular area of wearable sensing devices, there is a trend towards smaller sensors and components. As sensor size decreases, and the number of body-mounted sensor nodes increases, more intelligent methods for sensor integration will be required. This integration includes physical attachments, as well as the data and power transfer methods between various nodes. The physical interconnections of sensor nodes should not impede the user's day-to-day activity. Bulky, rigid metal cables are physically constrictive, as well as heavy and unnatural to the touch.

To replace these cables, the authors propose the use of a woven conductive fabric garment as a power and data transmission bus. This idea was first presented by the authors in [1]. The resulting apparatus consists of a shirt-like garment made of conductive fabrics, with sensors embedded at various locations. In addition, there is a centralized set of

components consisting of a battery, a microprocessor, and a wireless transceiver. Physiological data is collected by the various sensor nodes, transmitted over the conductive fabric data bus to the centralized components, and transmitted wirelessly to a local PC. The same bus is used by the centralized components to distribute power to the various nodes in the system. By centralizing the transmission and power components, the number (and thus, the weight) of batteries is decoupled from the number of sensors in the system. Further, the routing presents no impediment to motion and is much lighter than metal cabling.

For such a system to be useful, care must be taken in the design and fabrication. The electrical characteristics must be conducive to transmission, and predictable by the designer. To this end, the authors propose a method of characterizing the DC resistance of such a garment, and indicate how it can be used in designing such garments for general use.



**Figure 1. Schematic of System Components Proposed by the Authors**

## 2 Relevant Technology: Conductive Fabrics and Power-line Carrier Communication

A schematic representing the system described by the authors is depicted in Figure 1. The system relies

on two specific technologies; conductive fabrics, and DC Power-line Carrier (DC-PLC) communication.

## 2.1 Conductive Fabrics

The use of conductive fabrics as body-based communication media has been discussed in the work of the authors, as well as others [1],[2]. Conductive fabrics are typically fabricated in one of two ways; the base fabric can be coated with conductive material, and then woven into a garment, or the garment can be woven from normal fabric, and then sprayed with a conductive material. Typical base fabrics include nylon and polyester, with silver, nickel, or aluminum coating.

While individual strands of conductive fabrics may have extremely large resistivities, which preclude power and data transmission, the authors showed that this does not impede the system functionality [1]. The two-dimensional nature of the garment ensures that there are in fact a multitude of paths between any two given points, and that the resulting DC resistance is conducive to transmission.

## 2.2 DC Power-line Carrier Communication

Simultaneous transmission of power and information over a single medium is commonly known as power-line carrier communication, or simply as power-line communication (PLC). This technology has been in development for quite a while for in-home networks. However, we propose to use PLC in a local, body-area network. We must take into account the safety of the user in addition to satisfying design simplicity.

The authors' unique direct current (DC) PLC system is pictured in Figure 2. In [3], the authors described a possible implementation for such a system that relies on transmission-line transformer (TLT) theory to minimize insertion losses associated with PLC transformers. The DC PLC system consists of three components; the transmission medium, a central command node, and the sensor nodes. The system we have developed requires only two conductors; a supply line, termed the consolidated power-signal (CPS) line, and a ground line for return. The CPS is used to transmit both DC power and data between the central node and the sensor nodes within the system.

The central node acts as the command node by sending commands to and reading data from the sensors located throughout the network. It also contains a battery which serves as the power source for the system.




Figure 2. DC PLC System Diagram

The sensor nodes rely on a modem developed by the authors specifically for a high-fanout DC PLC system. The modem, which contains a DC / DC converter, an analog-to-digital converter, a TLT, and a phased-lock loop, can be interfaced with a multitude of sensor types. It can read both analog and digital data, then digitize (if necessary), encode, and modulate the signal for transmission over the CPS to the central node. Frequency-shift keying (FSK) is used to modulate the signals, and frequency separation is used to minimize the number of collisions between sensor node transmissions. Using FSK ensures that we can maintain a high transmission bandwidth with carrier frequencies in the low mega-Hertz range, and bit transmission rates above 100kbps.

This DC PLC system is optimal for our wearable network as it consists of a minimum of components, does not require bulky sensors or routing, and has a very simple design.

In designing such systems for wearable applications, the practical issue becomes how to best model the transmission properties. Such shared-bus mediums are often treated as star topologies, as depicted in Figure 3. In such networks, we have a central node coordinating each remote node. The system functionality depends on the impedance match between the central node and the remote nodes. When designing such systems for varying body shapes and sizes, a physically inspired analytical tool is necessary.





Figure 3. Star Topology

### 3 Prediction Method

In order to use such a communication method, the resistive characteristics of the transmission medium must be ascertained. For our test apparatus, we have constructed the garment using silver-coated nylon, as pictured in Figure 4. In order to gain some initial insight into the behavior of such a garment, DC resistance measurements were taken with a milli-Ohm meter. With one probe connected to the lower back, the second probe was connected to various locations. The measured resistances at the corresponding locations are depicted in Figure 5.



**Figure 4. Conductive Fabric Garment**



**Figure 5. Resistance Measurements**

Despite the manufacturer-supplied rating of  $0.2\Omega/\text{cm}$  for silver-coated nylon, the results are not predictable. One problem is the rating itself. That is, ratings in  $\Omega/\text{cm}$  imply that probes used for

measurement or transmission are rectangular of length  $l$ , and that the material under measurement is a square of area  $l^2$ . Neither assumption is true in this case. Thus, we seek a method to predict the actual resistance characteristic as a function of length for the complex, 3-dimensional (3D) garment. Due to the 3D nature of the garment, an exact analytical solution cannot be derived from Maxwell's equations. However, the authors have created an approximation method based on simpler geometries; specifically, the 1D and 2D resistance characteristic. It can be shown that the 1D resistance characteristic is of the form;

$$R_{1d}(h) = k_{1d} \cdot h \quad (1)$$

The 2D resistance characteristic is of the form;

$$R_{2d}(h) = c \cdot \ln(k_{2d} \cdot h) \quad (2)$$

where  $h$  is the measurement distance between two points.

In order to predict the DC resistance, the authors took note of the fact that the garment can be decomposed into cylindrical sections. The trunk is primarily cylindrical, as are the arms. These cylinders are connected by the shoulders and neck of a garment.

In separate experiments, the authors constructed cylindrical sections of conductive fabrics. The sections had the same length (90cm), but different diameters. The authors were able to determine a relationship between the diameter-to-length ( $D/L$ ) ratio and the resulting resistance behavior. That is, for certain  $D/L$  ratios, the resistance of a section along its axis varies according to (1), whereas for other  $D/L$  ratios, the behavior is best described by (2). The constant  $c$  is based on material properties of the garment, and can be determined empirically. The constants  $k_{1d}$  and  $k_{2d}$  must also be determined experimentally for a given  $D/L$  ratio.

Once the constants are found for a given ratio, the method used to predict the resistance between two points is as follows; first, the points  $P_1$  and  $P_2$  are determined (See Figure 6). Next, the distances between them, along the garment, must be measured. The distance on the trunk section is termed  $h_t$ , and the distance along the arm is termed  $h_a$ . To determine total resistance between the points, we sum the resistances along the trunk,  $R_t$ , and the arm,  $R_a$ . The result can be computed as follows;


$$R_{total} = R_t + R_a \quad (3)$$

In this case, it has been determined that the trunk resistance varies according to (2), and the arm resistance according to (1). So, combining (1) – (3), we can write;


$$R_{total} = c \cdot \ln(k_{2d} \cdot h_t) + k_{1d} \cdot h_a \quad (4)$$

This prediction method allows us to estimate the resistances of the garment, and compare them with the results shown in Figure 5. The resulting predictions are depicted in Figure 7, where the measured values are shown in plain-text, and the predictions in bold.

We see that there is close agreement between the measured and predicted value. For points of primary interest, such as the upper arms and wrists, the error is under %11. This is acceptable for data and power transmission. The largest error (~%30) seems to occur at locations where the geometry is poorly approximated by cylindrical sections – the under-arm area. This result is to be expected, as the shoulder and under-arm section are complex 3D intersections. Despite the fact that the measurement points are not aligned directly along the cylinder axis, as assumed for our simplified model, there is satisfactory agreement between measured and predicted results.



**Figure 6. Model for Predicting DC Resistance**



**Figure 7. Results of DC Resistance Prediction**

Thus, what we have presented is an analytical relationship that can be used to predict DC resistance between two points. While this analytical method is based on a asset of empirical measurements, we are now equipped to characterize the behavior for garments of various sizes and shapes for users of varying body types, based only on the distance between the nodes, and the section diameters.

## 4 Conclusion

The authors have presented a method of estimating the DC resistance for complex, 3D garments based on simplified geometries. Such analysis is necessary in order to perform impedance matching, determine fan-out and power consumption, and other power and data transmission techniques for such garments. This now allows for the general design of such garments for various body shapes and sizes.

This method can also be applied to pants-like sections. Further work will involve characterization of the behavior when motion artifact is introduced, as well as characterization of the AC transmission properties. The applications of such a garment go beyond wearable health monitoring. Introduction of actuators, for instance, would allow for rehabilitation applications or assisting in the user's physical tasks.

## 5 References

- [1] Wade, E.; Asada, H.H. "Cable-Free Wearable Sensor System Using a DC Powerline Body Network in a Conductive Fabric Vest" Proceedings. EMBS '04. 2004 IEEE International Conference on .
- [2] K. Van Laerhoven, N. Villar & H.-W. Gellersen. "A Layered Approach to Wearable Textile Networks". In Proceedings of the IEE Euroearable 2003; ISBN: 0-85296-282-7; IEE Press. Birmingham, UK, pp. 61-67.
- [3] Wade, E.; Asada, H.H. "Wearable DC powerline communication network using conductive fabrics" Robotics and Automation, 2004. Proceedings. ICRA '04. 2004 IEEE International Conference on , Volume: 4 , April 26-May 1, 2004 Pages:4085 - 4090 Vol.4