

A Succinct Analysis of Von Neumann's Hackendot

Here I provide a brief analysis of the game, Hackendot, through the scope of the game theory article titled "A Complete Analysis of Von Neumann's Hackendot" written by J. Olehla. The purpose of the paper is to provide the first player winning strategy of Von Neumann's game titled *Hackendot*. The game is very similar to *Hackenbush*, as indicated by the name. The game's initial position, like *Hackenbush*, is a "forest" of "trees". A tree is a series of connected nodes, one node which is distinguished as a root, the lowest point in a tree, and the rest which are edges directed upwards, away from the root. In order to play, the first player selects any node within the tree. The first player then deletes all the nodes on the path from the root to the node, including all adjacently connected nodes. The second player then performs a similar move. The game continues as the players alternate turns until the board is empty. The last player to delete nodes from the board is the winner. Thus, the game is normal as well as impartial and a game of complete information.

The first main idea introduced in the paper is the proof that the first player has the winning strategy. This proof is provided by Neumann, who uses reduction ad absurdum to prove, specifically by a proof by contradiction, the first player has the winning strategy. This proof concerns the fact that if the second player was assumed to have a winning strategy such that this player were to delete a certain path of nodes, the first player would've been able to reach this same game state before the second player and would have been able to employ this winning strategy.

The next main idea is provided by the author of the article, who uses the Sprague Grundy function to determine what he calls nodes, or positions, of the N and P classes. He states that a node a has an $f(a)$ value of 0 if it is a terminal node, or one without followers which are nodes

connected to that specific node by directed flow. The value $f(a)$ of other nodes is then recursively defined to be the least number which is different from the $f(a)$ values of all the direct followers of these nodes. Then he classifies nodes with $f(a)$ value of 0 as P nodes and nodes of all other $f(a)$ values as N nodes. This strategy is not used to determine P and N positions, but rather is used as a classification of nodes which is useful in determining values of the strategy-solving function components introduced later on. After demonstrating this use of the Sprague Grundy theorem, the author goes on to discuss boards of multiple trees. He briefly explains that the entire game board is a disjunctive sum of all the trees within the board. Each tree can be seen as an individual game. However, they can also be collected and represented as one tree via the application of the nim-sum function. This is useful for especially large forests of trees.

The author then introduces the root-impurity function along with other mathematical entities in order to provide a general strategy-solving method. This function is said to have a value of zero if the number of P-class roots in an initial forest is even and a value of one if the number of N-class roots in a n initial forest is odd. Next, the LF forest series is introduced. An LF forest is basically a collection of the N-nodes of an original forest. An LF forest can be such a collection of another LF forest. Thus, there is a series of LF forests, starting from the original forest, L^0F , up to L^nF . The largest value n takes on before LF becomes an empty forest is called \mathbf{m} which is defined as the L-length of the initial forest F .

Finally, all previous mathematical entities are collected to solve for a function called the Main Theorem, $f(F) = \sum_{n=0}^m (2^n) Rip(L^n F)$. This function returns the nim-function value of a specific game board of forests. This nim-function is useful because if it isn't evaluated as zero, it tells the current player that he or she can make a move such that the function does evaluate to zero and they have the winning strategy. Thus, a good move from a forest F with $f(F) > 0$

consists in choosing \mathbf{a} such that $f(F^{\mathbf{a}}) = 0$, where $F^{\mathbf{a}}$ denotes a forest chopped from its root to a node \mathbf{a} .