

Homework I: Installing Linux on the iPaq

CS 546 - Spring 2006

The goal of this assignment is to install the GPE Palmtop Environment on the iPaqs. This assignment is a warmup for you to get familiar with the Linux environment and install Linux on an embedded system (the iPaq). The reference section has links to various pieces of information that are useful (directly or indirectly) for this assignment and for the class generally. Please take some time to read them. This will help you better understand what you are doing for this homework. It is also useful preparation for your project.

Administrivia

iPaqs

You will form teams of two people each. Each team will get an iPaq alongwith a cradle, power cord etc. Please check out the equipment Wednesday (Jan 18th) morning between 10-11 AM in the lab (KAP 103). Only one team member needs to come by to check out the equipment. If neither team member can come to KAP 103 at that time, email Karthik and we'll setup another time. You will need to return everything you checked out intact, so please be careful with it. Break it, and you buy it.

Submission

The assignment is due Tuesday, Jan 24th. No extensions will be given. You will need to demo the correct version of Linux running on the iPaq. Each team has been assigned a slot (see Table 1). Be there on time for your demo. There will be a large number of groups so please be on time. The demo will be in the lab (KAP 103).

Q&A Policy

As already mentioned, the preferred form of contact is email.

Class mailing list - cs546@robotics.usc.edu

Karthik Dantu - dantu@usc.edu

Vinay Malekal - malekal@usc.edu

Gaurav Sukhatme - gaurav@usc.edu

As Gaurav mentioned earlier, all of us are on the class mailing list. Direct all your questions to the list, and not to our personal emails. This will help the class benefit from any similar problems others are facing. It will also give a chance for everyone to respond, not just Gaurav, Vinay and myself.

We will try our best to respond to you in 24 hours. Please do not expect us to be faster than that. What this implies is that you will need to start your assignments early. We will not be responsible for unanswered questions the day before or on the day of the submission.

Office Hours

Karthik Dantu
Monday - 11-12 Noon
Thursday - 4-5PM

Vinay Malekal
Thursday - 4-5 PM

Please stop by during office hours. You should spend the first few weeks catching up on whatever you lack, from the questionnaire. Once the project starts, it will be hard to catch up otherwise. We are here to assist you in anyway possible.

Miscellaneous

This is a warmup assignment and is fairly easy, so take some time to familiarize yourself with the lab and the Linux environment.

All of you will have superuser privileges on the lab machines. Please do not abuse this. The lab is mainly for the class. **DO NOT** use the machines for other activities like illegal download/uploads, watching movies, playing computer games etc. Please do not use the lab for other classes. We have a limited number of machines and they are meant to be used for CS 546 only.

Table 1: Homework 1 Demo Schedule: Jan 24, 2006 in KAP 103

Time	Vinay	Karthik
10:00-10:10	Team 1	Team 2
10:10-10:20	Team 3	Team 4
10:20-10:30	Team 5	Team 6
10:30-10:40	Team 7	Team 8
10:40-10:50	Team 9	Team 10
11:50-11:00	Team 11	Team 12
11:00-11:10	Team 13	Team 14
11:10-11:20	Team 15	Team 16
11:20-11:30	Team 17	Team 18
11:30-11:40	Team 19	Team 20
11:40-11:50	Team 21	Team 22
11:50-12:00	Team 23	Team 24

Assignment

We will be loosely following instructions from <http://familiar.handhelds.org/releases/v0.8.2/install/>

Some things to note -

- You will be installing stable version 0.8.2 of GPE
- You are given a H3870 iPaq which falls under the H3800 series iPaqs
- Depending on whether you have Linux already running on your iPaq or not, you will install/upgrade your installation

Step 1: Download the files from <http://familiar.handhelds.org/releases/v0.8.2/install/download.html>
You should have downloaded a tar file with

```
h3600/BootBlaster_1.19.exe
h3600/bootldr-sa-2.21.12.bin
h3600/bootldr-sa-2.21.12.bin.gz
h3600/gpe-image-h3600-20050407124742.rootfs.jffs2
h3600/md5sums
h3600/reflash.ct1
```

Step 2: We will upload the needed files over serial using Synce([4]). Please make sure that the following packages are installed on your machine - synce-serial, synce-dccm, libsynce0, librapi2. All the lab machines have ubuntu Linux and you can use the Synaptic Package Manager to check which packages are installed.

Also make sure you have plugged in the serial cable to the machine and make a note of whether it is the first (ttyS0) or second (ttyS1) serial port on the machine.

Step 3: Install bootldr following the instructions at <http://familiar.handhelds.org/releases/v0.8.2/install/bootldr-synce.html>
Potential points of failure:

- The serial port you are using is not the one to which the iPaq is attached (ttyS0 or ttyS1)

Step 4: Check if your machine has minicom installed. Also familiarize yourself with minicom by reading its man page. Run minicom as superuser. Now, configure the serial line to *115200 8N1, no flow control, no hardware handshaking* ([5]). Install the gpe root image by following instructions at <http://familiar.handhelds.org/releases/v0.8.2/install/install-serial.html>

Step 5: Once you have booted into Linux, please use the touchpad to configure GPE and give it a root password. This is needed before we can remotely access the iPaq again.

Step 6: To connect the iPaq to the Internet, we will use PPP. As superuser, type the following command, **all in one line** -

```
~# /usr/sbin/pppd /dev/ttyS0 115200 192.168.10.1:192.168.10.2
  nodetach local noauth nocrtscts lock user ppp connect
  ‘‘/usr/sbin/chat -v -t3 ogin--ogin: ppp’’ &
~#
```

For details on the setup, take a look at ([3]). The output should look like this:

```
Serial connection established.
Using interface ppp0
Connect: ppp0 <--> /dev/ttyS1
found interface eth1 for proxy arp
local IP address 192.168.10.1
remote IP address 192.168.10.2
```

This creates a point-point link between the computer and the iPaq. You can now ssh into the iPaq by giving the following command -

```
$ ssh root@192.168.10.2
<enter password>
```

To enable the iPaq to access the Internet via the desktop[2], we will need to enable masquerading([1]) on the desktop. This can be done by issuing the following commands as superuser on the desktop:

```
~# iptables -t nat -I POSTROUTING -j MASQUERADE -s 192.168.10.2
~# iptables -I FORWARD -s
~# 192.168.10.2 -j ACCEPT
~# iptables -I FORWARD -d
~# 192.168.10.2 -j ACCEPT
~# echo 1 > /proc/sys/net/ipv4/ip_forward
```

Lastly, to be able to resolve DNS, we will need to provide nameservers to the iPaq. This can be done by adding the following two entries to `/etc/resolv.conf` on the iPaq.

```
nameserver 128.125.253.194
nameserver 128.125.7.23
```

Step 7: Now that you can connect to the Internet using the iPaq, we will update `gpe` and synchronize the time on the iPaq. Follow instructions at <http://familiar.handhelds.org/releases/v0.8.2/install/post-install.html>

References

- [1] "IP Masquerading Howto", <http://www.tldp.org/HOWTO/IP-Masquerade-HOWTO/>
- [2] "Enabling Networking on iPaq", <http://handhelds.org/moin/moin.cgi/HPiPaqH2200ssh>
- [3] "iPaq PPP Howto", <http://handhelds.org/moin/moin.cgi/PPPHowto>
- [4] "Synce HOWTO", <http://synce.sourceforge.net/synce/howto.php>
- [5] "Text Terminal HOWTO", <http://www.tldp.org/HOWTO/Text-Terminal-HOWTO.html>