

CS 547: Sensing and Planning in Robotics

Gaurav S. Sukhatme

Computer Science
Robotic Embedded Systems Laboratory
University of Southern California

gaurav@usc.edu
<http://robotics.usc.edu/~gaurav>

(Slides adapted from Thrun, Burgard, Fox book slides)

Bayes Filters: Framework

- **Given:**

- Stream of observations z and action data u :

$$d_t = \{u_1, z_1 \dots, u_t, z_t\}$$

- Sensor model $P(z|x)$.
- Action model $P(x|u, x')$.
- Prior probability of the system state $P(x)$.

- **Wanted:**

- Estimate of the state X of a **dynamical system**.
- The posterior of the state is also called **Belief**:

$$Bel(x_t) = P(x_t | u_1, z_1 \dots, u_t, z_t)$$

$$Bel(x_t) = \eta P(z_t | x_t) \int P(x_t | u_t, x_{t-1}) Bel(x_{t-1}) dx_{t-1}$$

1. Algorithm **Bayes_filter**($Bel(x), d$):
2. $\eta=0$
3. If d is a **perceptual** data item z then
4. For all x do
5. $Bel'(x) = P(z | x)Bel(x)$
6. $\eta = \eta + Bel'(x)$
7. For all x do
8. $Bel'(x) = \eta^{-1}Bel'(x)$
9. Else if d is an **action** data item u then
10. For all x do
11. $Bel'(x) = \int P(x | u, x') Bel(x') dx'$
12. Return $Bel'(x)$

Discrete Bayes Filter Algorithm

1. Algorithm **Discrete_Bayes_filter**($Bel(x), d$):
2. $\eta=0$
3. If d is a **perceptual** data item z then
4. For all x do
5. $Bel'(x) = P(z | x)Bel(x)$
6. $\eta = \eta + Bel'(x)$
7. For all x do
8. $Bel'(x) = \eta^{-1}Bel'(x)$
9. Else if d is an **action** data item u then
10. For all x do
11. $Bel'(x) = \sum_{x'} P(x | u, x') Bel(x')$
12. Return $Bel'(x)$

Bayes Filters

z = observation
 u = action
 x = state

$$\boxed{Bel(x_t)} = P(x_t | u_1, z_1, \dots, u_t, z_t)$$

Bayes $= \eta P(z_t | x_t, u_1, z_1, \dots, u_t) P(x_t | u_1, z_1, \dots, u_t)$

Markov $= \eta P(z_t | x_t) P(x_t | u_1, z_1, \dots, u_t)$


Total prob. $= \eta P(z_t | x_t) \int P(x_t | u_1, z_1, \dots, u_t, x_{t-1})$
 $P(x_{t-1} | u_1, z_1, \dots, u_t) dx_{t-1}$

Markov $= \eta P(z_t | x_t) \int P(x_t | u_t, x_{t-1}) P(x_{t-1} | u_1, z_1, \dots, u_t) dx_{t-1}$

Markov $= \eta P(z_t | x_t) \int P(x_t | u_t, x_{t-1}) P(x_{t-1} | u_1, z_1, \dots, z_{t-1}) dx_{t-1}$

$$\boxed{= \eta P(z_t | x_t) \int P(x_t | u_t, x_{t-1}) Bel(x_{t-1}) dx_{t-1}}$$

Sensor model



$$\begin{aligned}
 P(\text{detect_wall} | x) &= 0.5 & |x - x_{wall}| = 0 \\
 &= 0.25 & |x - x_{wall}| = 1 \\
 &= 0 & |x - x_{wall}| > 1
 \end{aligned}$$

Motion model

Two commands $u=R$ & $u=L$

$$\begin{array}{l|l}
 P(x+1 | x, u=R) = 0.5 & P(x-1 | x, u=L) = 0.5 \\
 P(x | x, u=R) = 0.5 & P(x | x, u=L) = 0.5
 \end{array}$$

exceptions ~~w/~~ ~~out~~, ~~about~~ exceptions for $x=0, x=5$

Start with uniform prior

$t=0$	x	0	1	2	3	4	5
	$Bel_0(x)$	$1/6$	$1/6$	$1/6$	$1/6$	$1/6$	$1/6$

Now the wall is detected

$t=1$	x	0	1	2	3	4	5
	$Bel_1(x)$	0	0	0	0	$1/6 \cdot 1/4 = 1/24$	$1/6 \cdot 1/2 = 1/12$
	$Bel'_1(x)$	0	0	0	0	$1/3$	$2/3$



Now a command $u = L$ is given

$$P(0 \mid x=0, u=L) = 1 \quad P(1 \mid x=0, u=R) = 1$$

$$P(5 \mid x=5, u=R) = 1 \quad P(4 \mid x=5, u=L) = 1$$

x	0	1	2	3	4	5
$Bel_2(z)$	0	0	0	$\frac{1}{3}$	$\frac{1}{6} = \frac{1}{2} \cdot \frac{1}{3} + 1 \cdot \frac{2}{3}$	0
$Bel_2(z)$	0	0	0	$\frac{2}{7}$	$\frac{5}{7}$	0

Now the wall is detected

x	0	1	2	3	4	5
$Bel_3(z)$	0	0	0	0	$\frac{1}{4} \cdot \frac{5}{7}$	0
$Bel_3(z)$	0	0	0	0	1	0

②

What if we redo this for the case where there is no special action model for the boundaries?

$t=0$	x	0	1	2	3	4	5
	$B_0(x)$	$1/6$	$1/6$	$1/6$	$1/6$	$1/6$	$1/6$

Now wall is detected

$t=1$	x	0	1	2	3	4	5
	$B_1(x)$	0	0	0	0	$1/3$	$2/3$

Now command $u = L$ is given

	x	0	1	2	3	4	5
	$B_2(x)$	0	0	0	$1/6$	$1/2(1/3)$ $+1/2(2/3)$	$1/2(2/3)$
	$B_2(x)$	0	0	0	$1/6$	$1/2$	$1/3$

Now the wall is detected (say)

3

	x	0	1	2	3	4	5
	$B_3(x)$	0	0	0	0	$1/8$	$1/6$
	$B_3(x)$	0	0	0	0	$3/8$	$4/6$

What if you started with a non-uniform prior?

$t=0$	x	0	1	2	3	4	5
	$B_0(x)$	1	0	0	0	0	0

DEPLETION EXAMPLE
Now wall is detected

$t=1$	x	0	1	2	3	4	5	
	$B_1(x)$	0	0	0	0	0	0	..

What if you started with a non-uniform prior but not zero everywhere

$t=0$	x	0	1	2	3	4	5
	$B_0(x)$	$19/20$	$1/100$	$1/100$	$1/100$	$1/100$	$1/100$

Now wall is detected

$t=1$	x	0	1	2	3	4	5
	$B_1(x)$	0	0	0	0	$1/400$	$1/200$
	$B_1(x)$	0	0	0	0	$1/3$	$2/3$



Today

- What is a perceptual model ?
- Physics-inspired beam-based models for range finders
- Scan-based models for range finders

Sensor Models: Notation and Assumptions

- $P(o|s)$ is a perceptual model. Could also be $P(o|s, m)$
- We will focus on range finders as the primary sensor (laser range finders, sonar, IR etc.)
- As usual the pose of the robot in the plane is given by $s = \langle x, y, \theta \rangle$
- Range finder produces a set of distances $o = \{o_1, o_2 \dots o_K\}$
- Assume $P(o|s, m) = \prod P(o_k|s, m)$

Beam-based Models

- Basic idea: Add noise to an expected 'ideal' measurement, to account for typical measurement errors
- Four kinds of measurement errors
 - Measurement noise
 - Unexpected objects (*e.g.* objects not in the map)
 - Failures (*e.g.* max range readings)
 - Random measurements (*e.g.* crosstalk)

Measurement Noise

Intuition: Measurements near the actual value are more likely

Model using a Gaussian distribution

$$P_{hit}(o_k | s, m) = \frac{\eta}{\sqrt{2\pi}\sigma_{hit}} e^{-\frac{(o_k - o_{exp})^2}{2\sigma_{hit}^2}} \quad 0 \leq o_k \leq o_{max} \quad (0 \text{ otherwise})$$

$$\eta = \left(\int_0^{o_{max}} \frac{e^{-\frac{(x - o_{exp})^2}{2\sigma_{hit}^2}}}{\sqrt{2\pi}\sigma_{hit}} dx \right)^{-1}$$

Unexpected Objects

Intuition: Nearer objects are detected with higher probability by a range sensor

Model using an exponential distribution

$$P_{unexp}(o_k | s, m) = \eta \lambda e^{-\lambda o_k} \quad 0 \leq o_k \leq o_{max} \text{ (0 otherwise)}$$

$$\eta = \frac{1}{\int_0^{o_{max}} \lambda e^{-\lambda x} dx} = \frac{1}{1 - e^{-\lambda o_{max}}}$$

Failures

Intuition: All the probability mass should be at O_{max}

Model using a very narrow uniform distribution

$$P_{max}(o_k | s, m) = \frac{1}{o_{small}} \text{ if } o_{max} - o_{small} \leq o_k \leq o_{max} \text{ (0 otherwise)}$$

o_{max} is a small number

Random Measurements

Intuition: Unexplained, phantom reading, crosstalk *etc.* Equally likely at all ranges (upto o_{max})

Model using a wide uniform distribution

$$P_{rand}(o_k | s, m) = \frac{1}{o_{max}} \text{ if } 0 \leq o_k \leq o_{max} \text{ (0 otherwise)}$$

Combining Distributions

Simple solution: a linear combination of the four distributions

$$P(o_k|s, m) = z_{hit}P_{hit}(o_k|s, m) + z_{unexp}P_{unexp}(o_k|s, m) + z_{max}P_{max}(o_k|s, m) + z_{rand}P_{rand}(o_k|s, m)$$

Computing the likelihood of a range finder scan

Input: o, s, m Output: $P(o|s, m)$

$q = 1$

for all $o_k \in o$ do

 compute o_{exp} for o_k using s and m

$$p = z_{hit}P_{hit}(o_k|s, m) + z_{unexp}P_{unexp}(o_k|s, m) + z_{max}P_{max}(o_k|s, m) + z_{rand}P_{rand}(o_k|s, m)$$

$q = qp$

return q

Finding the Values of the Coefficients

- Use the sensor to measure a set of n range values for a given o_{exp}
- For a given o_{exp} compute $P(o_k|o_{exp})$ ($0 \leq o_k < o_{max}$)
$$P(o_k|o_{exp}) = \frac{\#[o_k - \delta, o_k]}{n}$$
- Using least mean square error minimization compute values of z_{hit} , z_{unexp} , z_{max} and z_{rand} which minimize the difference between $P(o_k|o_{exp})$ and $P(o_k|s, m)$
- Repeat this for several values of o_{exp}
- Again use least mean square error minimization to infer z_{hit} , z_{unexp} , z_{max} and z_{rand} as functions of o_{exp}

Problems with the Beam-based Approach

- Lack of smoothness
 - *e.g.* environment with many small obstacles
 - small changes in s (particularly θ) lead to large changes in $P(o|s, m)$
- Computational complexity

The Scan-based Approach

- Project sensor reading o_k into x, y space
- Use map to compute likelihood function in x, y space
- Intersect sensor reading with likelihood
- Add other sources of noise

Projecting a Scan into the Plane

o_k is the sensor scan

$s = (x, y, \theta)$ is the robot pose

x_k, y_k, θ_k is the relative offset of the sensor to the robot

The measured obstacle coordinates x_{o_k}, y_{o_k} are

$$x_{o_k} = x + (x_k \cos \theta - y_k \sin \theta) + o_k \cos(\theta + \theta_k)$$

$$y_{o_k} = y + (x_k \sin \theta + y_k \cos \theta) + o_k \sin(\theta + \theta_k)$$

Adding Noise

- Measurement noise: Gaussian
- Failures: Narrow uniform distribution at o_{max}
- Random measurements: Wide uniform distribution

The Likelihood Function

Input: A grid map of the environment

Output: The likelihood of an obstacle being detected at every point in the environment

For every point (x, y) in the environment compute d - the distance to the closest obstacle

The likelihood at point (x, y) is given by

$$L(x, y) = \frac{1}{\sqrt{2\pi}\sigma_{hit}} e^{-\frac{d^2}{2\sigma_{hit}^2}}$$

Adding Noise

- Measurement noise
 - Given the pose of the robot, a sensor reading o_k and a likelihood function L
 - Intersect and normalize the likelihood field with the sensor ray to obtain $P_{hit}(o_k|s, m)$
- Failures: P_{max} is obtained as before
- Random measurements: P_{rand} is obtained as before

$$P(o_k|s, m) = P_{max}(o_k|s, m) \text{ if } o_{max} - o_{small} \leq o_k$$

$$P(o_k|s, m) = zP_{hit}(o_k|s, m) + (1 - z)P_{rand}(o_k|s, m) \text{ otherwise}$$

The Algorithm

Input: o, s, m Output: $P(o|s, m)$

$q = 1$

for all $o_k \in o$ do

 if $o_{max} - o_{small} \leq o_k$

$q = q / o_{small}$

 else

$x_{o_k} = x + (x_k \cos\theta - y_k \sin\theta) + o_k \cos(\theta + \theta_k)$

$y_{o_k} = y + (x_k \sin\theta + y_k \cos\theta) + o_k \sin(\theta + \theta_k)$

$d^2 = \min_{x', y'} [(x_{o_k} - x)^2 + (y_{o_k} - y)^2 | (x', y') \text{ occupied}]$

$q = q \left(\frac{z}{\sqrt{2\pi}\sigma_{hit}} e^{-\frac{d^2}{2\sigma_{hit}^2}} + \frac{1-z}{o_{max}} \right)$

return q

Advantages and Disadvantages

- Advantages
 - Smoothness
 - Pre-computation in 2D
- Disadvantages
 - Does not treat dynamic obstacles (people)
 - Sensor 'see through' walls
 - Does not account for map uncertainty

Multi-scan Models

- Use a sensor scan to build a local map m_{local}
- Match m_{local} to the map m (*i.e.* compute the correlation between the two)
- The more similar m_{local} is to the map m , the larger the values of $P(o|s, m)$