

Probabilistic Robotics

Bayes Filter Implementations


Particle filters

(Modified version of notes from
Thrun/Burgard/Fox book)

Particle Filters

- Represent belief by random **samples**
- Estimation of **non-Gaussian, nonlinear** processes
- Monte Carlo filter, Survival of the fittest, Condensation, Bootstrap filter, Particle filter
- Filtering: [Rubin, 88], [Gordon et al., 93], [Kitagawa 96]
- Computer vision: [Isard and Blake 96, 98]
- Dynamic Bayesian Networks: [Kanazawa et al., 95]d

Importance Sampling








Weight samples: $w = f/g$


Importance Sampling with Resampling: Landmark Detection Example







Distributions



Distributions






Wanted: samples distributed according to $p(x | z_1, z_2, z_3)$



This is Easy!

We can draw samples from $p(x|z_l)$ by adding noise to the detection parameters.




Importance Sampling with Resampling

$$\text{Target distribution } f : p(x | z_1, z_2, \dots, z_n) = \frac{\prod_k p(z_k | x) p(x)}{p(z_1, z_2, \dots, z_n)}$$

$$\text{Sampling distribution } g : p(x | z_l) = \frac{p(z_l | x) p(x)}{p(z_l)}$$

$$\text{Importance weights } w : \frac{f}{g} = \frac{p(x | z_1, z_2, \dots, z_n)}{p(x | z_l)} = \frac{p(z_l) \prod_{k \neq l} p(z_k | x)}{p(z_1, z_2, \dots, z_n)}$$

Importance Sampling with Resampling




Weighted samples




After resampling

Particle Filters





Sensor Information: Importance Sampling

$$\begin{aligned} Bel(x) &\leftarrow \alpha p(z|x) Bel^-(x) \\ w &\leftarrow \frac{\alpha p(z|x) Bel^-(x)}{Bel^-(x)} = \alpha p(z|x) \end{aligned}$$




Robot Motion

$$Bel^-(x) \leftarrow \int p(x|u, x') Bel(x') dx'$$





Sensor Information: Importance Sampling

$$\begin{aligned}
 Bel(x) &\leftarrow \alpha p(z|x) Bel^-(x) \\
 w &\leftarrow \frac{\alpha p(z|x) Bel^-(x)}{Bel^-(x)} = \alpha p(z|x)
 \end{aligned}$$



Robot Motion

$$Bel^-(x) \leftarrow \int p(x|u, x') Bel(x') dx'$$




Particle Filter Algorithm

1. Algorithm **particle_filter**(S_{t-1}, u_{t-1}, z_t):
2. $S_t = \emptyset, \eta = 0$
3. **For** $i = 1 \dots n$ *Generate new samples*
4. Sample index $j(i)$ from the discrete distribution given by w_{t-1}
5. Sample from $p(x_t | x_{t-1}, u_{t-1})$ using $x_{t-1}^{j(i)}$ and u_{t-1}
6. $w_t^i = p(z_t | x_t^i)$ *Compute importance weight*
7. $\eta = \eta + w_t^i$ *Update normalization factor*
8. $S_t = S_t \cup \{ \langle x_t^i, w_t^i \rangle \}$ *Insert*
9. **For** $i = 1 \dots n$
10. $w_t^i = w_t^i / \eta$ *Normalize weights*

Particle Filter Algorithm

$$Bel(x_t) = \eta p(z_t | x_t) \int p(x_t | x_{t-1}, u_{t-1}) Bel(x_{t-1}) dx_{t-1}$$




$$\begin{aligned} w_t^i &= \frac{\text{target distribution}}{\text{proposal distribution}} \\ &= \frac{\eta p(z_t | x_t) p(x_t | x_{t-1}, u_{t-1}) Bel(x_{t-1})}{p(x_t | x_{t-1}, u_{t-1}) Bel(x_{t-1})} \\ &\propto p(z_t | x_t) \end{aligned}$$


Resampling

- **Given**: Set S of weighted samples.
- **Wanted** : Random sample, where the probability of drawing x_i is given by w_i .
- Typically done n times with replacement to generate new sample set S' .

Resampling



- Roulette wheel
- Binary search, $n \log n$




- Stochastic universal sampling
- Systematic resampling
- Linear time complexity
- Easy to implement, low variance

Resampling Algorithm


1. Algorithm **systematic_resampling**(S, n):
2. $S' = \emptyset, c_1 = w^1$
3. **For** $i = 2 \dots n$ *Generate cdf*
4. $c_i = c_{i-1} + w^i$
5. $u_1 \sim U]0, n^{-1}]$, $i = 1$ *Initialize threshold*
6. **For** $j = 1 \dots n$ *Draw samples ...*
7. **While** ($u_j > c_i$) *Skip until next threshold reached*
8. $i = i + 1$
9. $S' = S' \cup \left\{ \left\langle x^i, n^{-1} \right\rangle \right\}$ *Insert*
10. $u_{j+1} = u_j + n^{-1}$ *Increment threshold*
11. **Return** S'

Also called **stochastic universal sampling**


Motion Model Reminder




Proximity Sensor Model Reminder





Laser sensor





Sonar sensor



















































Sample-based Localization (sonar)



Initial Distribution




After Incorporating Ten Ultrasound Scans




After Incorporating 65 Ultrasound Scans



Using Ceiling Maps for Localization




Vision-based Localization




Under a Light

Measurement z :




$P(z|x)$:




Next to a Light

Measurement z :



$P(z|x)$:




Elsewhere


Measurement z :



$P(z|x)$:



Global Localization Using Vision



Summary

- Particle filters are an implementation of recursive Bayesian filtering
- They represent the posterior by a set of weighted samples.
- In the context of localization, the particles are propagated according to the motion model.
- They are then weighted according to the likelihood of the observations.
- In a re-sampling step, new particles are drawn with a probability proportional to the likelihood of the observation.