Proposed Approach for Combining Distributed Sensing, Robotic Sampling, and Offline Analysis for in situ Marine Monitoring

Gaurav S. Sukhatme[1], Deborah Estrin[2], David Caron[3], Maja J. Matarić[1] and Aristides Requicha[1]

[1]Department of Computer Science
University of Southern California

[2]Department of Computer Science
University of California at Los Angeles

[3]Department of Biological Sciences
University of Southern California

ABSTRACT

An approach for coordinated, distributed, in situ sensing is proposed. An example application is chosen (offshore marine monitoring) and the approach is described in the context of the example. Three major research challenges are discussed, (1) coordinated sensing and triggering, (2) localization and time synchronization, and (3) micro mobility.

Keywords: In situ sampling, Coordinated sensing, Robotic sensing, Sensor networks

1. INTRODUCTION

The ability to acquire environmental data at very high spatial and temporal resolution, and to correlate those data with organism abundance and response would open new vistas in marine research. It would also have a major impact on how we detect and respond to pathogens and other harmful organisms in the coastal environment.

This paper describes a **proposed approach** to distributed, robotic sampling, and offline analysis for *in situ* marine monitoring. As an example, we consider the specific problem of monitoring ocean water in the vicinity of a major metropolitan area as a means to detect contamination. In particular, we are interested in the path of a fresh water plume which is ejected into the ocean from a river. For instance, in the Los Angeles basin, the Los Angeles river flows into the Pacific Ocean and the subsequent path of the fresh water (carrying harmful pollutants) is poorly known at the present time. We envisage a series of monitoring stations along the coast of the Los Angeles basin. Each station would be approximately 100 - 500 m offshore and would be tethered to a fixed buoy. Each station will make measurements and communicate them to the other stations via a radio link on the buoy. The buoy would also have a GPS receiver for exact geolocation. While the scientific applications of a such a monitoring network are vast, the practical applications are no less interesting. Just as California beaches now have regularly spaced lifeguard stations, these offshore robotic buoys could serve as water-safety stations. Each could be equipped with a light, green to signal that the local water was safe and red for potentially unsafe conditions.

The proposed experimental testbed is composed of three parts. The first (described above) is a system of sensors spread across the ocean front. The second is a system of tethered robots for laboratory testing in a tank, and the third is a Scanning Probe Microscope for offline analysis.

We will construct a laboratory set up consisting of robots at the 10 cm scale which will be deployed in a 1 cubic meter tank environment. We will imbue these robots with the capabilities we can expect in their smaller counterparts that are likely to be available in a few years. Thus, they will use low power, and have limited ability to move and communicate. Some of these robots will be able to collect water samples for offline analysis, because *in situ* analysis techniques for organism identification, for example, are not feasible yet. The tank work will serve to develop the

Further author information: (Send correspondence to GSS)
GSS: gaurav@usc.edu DE: destrin@cs.ucla.edu DC: dcaron@usc.edu MJM: mataric@cs.usc.edu AR: requicha@cs.usc.edu

necessary coordination strategies in preparation for the ocean deployment, and will provide a wealth of environmental data such as temperature, light, salinity and concentration of nutrients. Coordination concepts will first be tested in the tank environment and then in the ocean testbed.

A third approach will employ a liquid cell of a Scanning Probe Microscope (SPM), with a volume on the order of one cubic cm. (For basic concepts of nanorobotics using SPMs see [Requicha 1999a].) Both the tank and the liquid cell environments permit controlled lab experiments, and selectively avoid the complexity of natural marine environments, while still providing a realistic setting, involving thousands or millions of microorganisms.

The liquid cell environment finesses coordination issues because the SPM tip is essentially a single robot. (Note, however, that multi-tip SPMs are expected to emerge from research labs in the next couple of years, and these will require coordination, although possibly centralized.) On the other hand, the SPM generates data at a much higher (molecular-scale) spatial resolution than the cm-scale robots, and can thus provide, albeit offline, the results we could expect from future micro or nanorobots. We believe that the SPM can also be used to identify microorganisms, and that the techniques we intend to develop will be applicable in situ, when smaller robots become available.

SPM organism identification methods are at an embryonic stage. Our proposed merger of this technology with established cell biology techniques will constitute a major advancement in the application of this technology to cell detection and identification. Extant molecular techniques for the identification of microorganisms, while powerful, have significant drawbacks for some applications: they are laborious and time consuming, destroy the organisms, and, importantly, are very difficult or impossible to adapt to in situ operation, even with the most optimistic predictions of future micro or nanorobot capabilities. The successful union of these technologies will provide a suite of tools for in situ sensing more powerful than the two approaches separately.

Finally, we will correlate the environmental and organism data acquired in our experimental environments, to demonstrate the feasibility and potential of our approach. For example, a correlation between physical quantities such as salinity, temperature with the presence of specific microorganisms.

2. PROPOSED SYSTEM HARDWARE DESCRIPTION

Ocean Experiments

Each node in this network (composed of buoyed coastal nodes) will consist of a processor, power supply, network connection, GPS, and some sensors. A candidate hardware design of one such node is described here. We propose to use off-the-shelf PC-104-based products. PC-104 is a well accepted standard and compatible with desktop PCs. PC-104 based architectures have been designed for various robotic applications and can be designed for low power applications and equipped with processors ranging from 386 to Pentium II and from memory ranging from 0MB RAM to 64MB and more. A full range of PC-104 peripheral devices are supported and commercially available including digital I/O, sensors and actuators. Our group has considerable experience with these from extensive past and ongoing robot experiments.

Tank Experiments

The second testbed is a system of tethered robots attached to vertical strands (see Figure 1). Each strand will have multiple robots attached to it via tethers. We envisage two arrangements for the tethers. The first is a rigid tethering system in which each tether will be a 2 degree of freedom arm with two actuators and rigid links. Our preliminary estimate is that there will be 10 strands and 10 tethers per strand leading to a total of 100 submerged robots. The second arrangement (actually shown in Figure 1) uses the same strand stand but with flexible tethers. The number of robots remains the same.

The robots themselves will be very simple. In the first phase of testbed development we will focus on packaging the robot controller (PC/104+ or smaller form factors) so it is waterproof. We will also equip the robots with communication and sensing. It is likely that communication will be a wired serial line. Candidate sensors on the robot are a thermometer, an infrared opacity sensor, etc. In addition to sensing, each robot will be equipped with a simple mechanism to take a fluid sample. This will be a spring-loaded, binary actuator-driven trap door which can be retracted to expose a small cavity to the surrounding fluid. Sampling will consist of opening and closing this trapdoor in succession. Once a sample has been taken the robots will be brought to the surface manually and the



Figure 1. The Tank Experimental Testbed

sample will be transferred to the lab bench for analysis. When the tethers become flexible we will also equip each robot with actuators that allow it to position and orient itself (i.e. to swim).

Scanning Probe Microscope Experiments

The third testbed is a scanning probe microscope (SPM) which will be used offline to analyze samples collected by the robots. The samples collected by the robots will be analyzed by lab-based and SPM methods. These are explained in the following sections.

3. RESEARCH CHALLENGES

The use of distributed microsensor and actuator networks for *in situ* biological monitoring presents many fundamental technical challenges. We plan to focus on 1) Coordinated sensing and triggering, 2) Localization and time synchronization, and 3) Micro-mobility.

1. **Coordinated sensing and triggering:** Consider a network of small, low-power sensors, each with a low-bandwidth communication channel. Our objective is for the nodes to cooperate in collectively identifying local and, together, global, environmental conditions. Such a sensor network must be fully distributed; that is, there is no central controlling unit, and no individual sensor within the network has global knowledge of the entire system. Centralized knowledge is not achievable for large numbers of sensors and at fine granularities, both critical for many future applications. To cope with the inevitable implosion of data that could come from continuous monitoring at high spatial resolution, we must execute local correlation and aggregation of data inside the network. We will explore simple localized algorithms to execute data collection and processing in each node, such as generating alerts and aggregating measurements. These requirements pose unprecedented challenges for scalable, robust, distributed system design.

   In the proposed research we will explore a number of approaches to such self-configuring, energy-aware, distributed coordination. One of these approaches will be directed diffusion [Estrin et al. 1999, Intanagonwiwat et al. 2000], a newly proposed model for designing localized algorithms for sensor network applications; in this context applied to a network of both sensors and actuators. In a diffusion network, dynamic gradients influence the flow of information toward nodes that need that information. Importantly, these gradients are established in a completely decentralized manner, without use of any global information. Diffusion is best described with an example; in this case we will describe diffusion in the context of a marine monitoring application.

   Consider the tank environment of Figure 1 equipped with 10 strands of tethered sensors and actuators, with 10 sensors tethered to each strand. Assume that some of the sensors are able to evaluate salinity, while others are measuring temperature, still others water currents, and yet others have indicators of nutrient levels. We can pose an example hypothesis that algal blooms are associated with certain nutrient concentrations, which are in turn promoted by certain temperature and salinity conditions. In this case the nutrient-sensing nodes would use diffusion to obtain information from temperature and salinity sensors about significant changes in conditions. Only when the conditions change, would the nutrient sensors expend resources doing a detection. Similarly, only when the nutrient detection was positive and above threshold, the sample-collecting actuators would receive these indications and would move toward the detection point to collect a sample. The sample collection actuators would collect information from the sensors closest to the collection point to obtain as detailed information as possible about the local conditions. Moreover, the actuators could use information collected about current strength and direction to influence which actuator self-selects to take a particular action at a particular location.

2. **Localization and Time Synchronization:** Key to coordinated action in many contexts is the ability to localize the position and time of events in the network (e.g., in our application, events would be sensor readings and sample collections). Nodes collaborating on tasks such as sensing can then use localization information as a common basis for coordination and for correlation of their findings. Yet localization and time synchronization within distributed networks are themselves open research problems. On the scales of interest in this proposal, GPS is of limited utility. The size of the antenna is larger than our device and some applications will be operating underwater or soil; although in eventual deployed sensor networks some elements in the system might provide GPS as a point of reference to other systems and data (e.g., remote sensing). In fact, it is not quite critical that all objects are localized in terms of global Cartesian space. In many contexts, relative positioning and a basis for common identification of a position or orientation (e.g. everyone knows which way is North) within the system are all that is needed. Similarly, it might not be necessary that extremely precise time synchronization be maintained with an external clock. Rather, very precise synchronization is needed with elements inside the network as the basis for correlating detections and actions.

   Time-stamping of the sensory readings in the network, as near as possible to the original sensor event, is of critical importance. The ability to do so dramatically reduces the variable delay introduced by message transmission latencies. Time-stamping in the network also allows tracking data to be later post-processed into motion data, aggregated, and summarized inside of the network, thus requiring a greatly reduced number of bits to be sent outside and back to the user. All of these advantages, however, do come with a price: sensors in the network must share a common time-base in order to ensure the consistency of readings taken at multiple sensors. We need to solve this problem of maintaining distributed time synchronization in a sensor network where power constraints are paramount.

   Time synchronization in networks and distributed systems is not a new problem. However, the resource constraints on a sensor network make the problem unique in this context. The necessity of a minimum-power design makes existing solutions for achieving time synchronization potentially inapplicable to our framework. Along with other approaches we will consider a peer-to-peer time distribution strategy such as that employed by NTP, the Network Time Protocol [Mills 1991]. NTP can be used to establish a federation of synchronized systems, even if the federation has no external time source. An NTP-like algorithm operates over the existing communications infrastructure of nodes; peers repeatedly poll each other for their current time in an effort to establish their relative bias and skew. Hybrid time distribution algorithms are also possible. For example, if a small number of selected nodes have additional hardware for receiving universal time, they might then also participate in a peer-to-peer time distribution strategy, allowing the time-synced federation to also be synced to universal time; this could allow correlation with remotely sensed data.

   One approach to localization is to leverage the radio-frequency communication capabilities of the nodes for localization. As part of an NSF-funded ongoing pilot study, we have investigated two approaches toward this end. In the first approach, a few nodes in the network (e.g. these could be anchored rigidly to the sides of tank) serve as reference points (beacons) and transmit periodic signals. Nodes use a simple connectivity metric (percentage of transmitted beacon signals that are actually received) to infer proximity to a given subset of these beacons, and then localize themselves to the centroid of the selected (proximate) beacons. The second approach we investigated is to localize the nodes based on the communication signal strength. Preliminary investigation shows that this is not a viable method with low power receivers and transmitters that exhibit high variance and poor accuracy.

3. **Micro-mobility:** Locomotion and other forms of actuation will be needed to achieve the desired spatial coverage, collect samples, and automatically maneuver scarce resources to phenomena of interest. Unlike networking, robotics has always focused on interacting with the physical world. However, our proposed work calls for miniaturization and energy efficiency of individual components, in combination with coordination techniques that can scale to very large numbers of elements. Since the individual robots at those scales must be very simple, a robust strategy for the appropriate global behavior in our target applications depends crucially on a decentralized, bottom-up approach to the coordination of robot motion with limited and carefully chosen reliance on coordinated communication.

   Autonomous control of position and orientation are the basic problems of mobile robotics. However, in our context, they are made more challenging by the fluid environment and the small size and simple nature of the vehicles. Our previous work has addressed precisely the two fundamental problems involved here: 1) robust and accurate navigation and 2) group coordination of multiple autonomously mobile robots. Our previous work focused on ground mobile vehicles; in the proposed project, we will apply our expertise to the novel challenges of the domain of underwater monitoring, working within the constraints of tethered, constrained motion and strict energy conservation.

   We have considerable previous expertise in robot control and navigation. We have developed an integrated technique [Roumeliotis 1999a, 1999b, Goel 1999] based on a variant of the Kalman filter to accurately estimate position and orientation of robots. This technique allows us to fuse different sensor information at varying frequencies in order to obtain the best possible estimate of position and orientation for control. For autonomous robots on rugged terrain we have developed an approach that combines local and global information which is optimal under certain noise assumptions. We plan to adapt the same technique to the localization problem in the underwater system. We have also demonstrated decoupled low-level control for complex dynamics [Sukhatme 1999] which is directly relevant to the problem at hand. The system we have studied in the past is an aerial helicopter robot, subject to some constraints that are similar to underwater systems (lift is analogous to buoyancy, aerodynamic drag exists in both air and water). We have identified trim conditions [Jun 1999] for which relatively simple, decoupled PD control loops effectively stabilize the robot. We plan to use a similar approach to the low level control of individual underwater robots, while the coordination problem (addressed below) will use a behavior-based control approach outlined below.

   Our previous work has demonstrated how behavior-based control (BBC) can be effectively applied to the problem of multiple robot coordination, in order to minimize local interference and maximize local as well as global task-level synergy among the robots [Mataric 1992, Mataric 1995a, Mataric 1997a]. Behavior-based control is structured in the form of collections of real-time behaviors, processes that tightly couple sensory-motor interactions [Arkin 1998, Mataric 1997a]. This inherently distributed approach to control is a natural choice for coordinating a distributed system; the system as a whole can be viewed as a collection of interacting behaviors, resulting in robustness to individual failures and sensory and effector uncertainty and noise. In the context of this project, we will apply BBC to the problem of locally constrained motion of tethered fluid-suspended robots, an entirely new and as-yet unexplored domain. As in our previous work, individual robots will utilize only local sensing and action, controlled with rules aimed at globally consistent effects. We have studied the problem of such control in the context of distributed navigation, formations, mapping, and object collection [Mataric 1995a, Mataric 1995b, Mataric 1997a, Mataric 1997b], with robust results. In this project, the same ideas will be applied, but with two key differences: constrained motion and energy usage, discussed next.

   The problem of constrained motion presents different challenges depending on the kinds of physical constraints (such as tether geometry, elasticity etc.). Formally speaking, a tether is a non-holonomic constraint on the motion of an individual node. Rigid tethers (which we plan to use first) make the localization problem rather easy (at least at the accuracy we desire). However they do not allow for the same degree of spatial coverage as flexible tethers. Flexible tethers present a significant challenge for actuation and control but allow better spatial coverage.

4. EXPERIMENTAL APPROACH

As described, our goal is to investigate local techniques for data acquisition and interpretation that will scale to large domains. The lab test-beds for the proposed work are modest in size; a cylinder approximately 1 meter in diameter and 1 meter in depth and the liquid cell of a SPM. Since our broad goal is to achieve a reasonable spatial density over larger domains (as with the ocean experiments), we will ultimately be interested in problems where large numbers of sensor/actuators are deployed. We intend the algorithms we will develop during the course of the work to scale to much larger domains involving the coordination of massively distributed systems.

With larger scales in mind, we will deliberately investigate strategies whose payoff is in the massively distributed regime. However, we are committed to implementing strategies that are, in some sense, practical. By this we mean that our strategies will cope with the uncertainty in sensing and actuation (in some cases even exploit it) without making unrealistic assumptions about the capabilities of the individual sensors and robots.

Robot control and multi-robot coordination are difficult problems under the best of circumstances. With underwater robots there are numerous additional challenges such as seals, buoyancy control, sensing, etc. While the key to making effective progress is to dive in and begin experimentation in order to gain insights into the practical realities of the problem, we believe that simplifying the robots involved will greatly benefit the overall progress of the proposed research. Further, a minimalist approach to the mechanics and control of the robots is in line with the philosophy of our group. Finally, it allows us to perform more realistic simulations with more relevant predictions.

Therefore, we will work with tethered robots attached to vertical strands, as described in our example scenario in Figure 1. Each strand will have multiple robots attached to it via tethers. This arrangement will allow robots to stay localized (bounded by the tether length) and will minimize spatial interference, a challenging problem in multiple mobile robot systems. Furthermore, this constraint allows exploration of constrained mobility, in order to address the key problems of localization in a bounded context and of energy conservation. Similarly, we will exploit the tethered structure for low bit rate communications among tethered sensors and sample collectors, while the surface end of the strands may communicate with one another using low power RF.

4.1. THE FIRST EXPERIMENTS

As a first step, we will address the problem of detecting a plume of fresh water in a ocean-like environment. This will require a single sensor, which measures salinity. Commercial salinity sensors have sufficient accuracy for our purpose. We will experiment with fresh water plume detection in the tank environment by introducing fresh water into the tank and attempting to detect its trajectory by locally correlating the sensors which detect the presence of the plume.

Initial attempts at correlating these simple physical data with biological data in real time and space in the tank environment and subsequently in the ocean testbed will be accomplished using extant biological indicators. Real-time measurements of specific microbial populations are not yet feasible (as noted above), but "proof of concept" and networking/correlative issues can be addressed using a proxy for biology. For example, in-situ fluorescence (indicative of photosynthetic pigment concentration) can be used as an indicator of microalgal biomass. Measurements of salinity and pigment fluorescence at sub-second time scales can be made using off-the-shelf technology, so adapting these technologies to appropriate time scales (minutes-to-hours) for examining freshwater intrusion into the coastal ocean should be straightforward.

Ultimately, substituting real-time analyses of microbial species of interest (e.g. specific human pathogens) for the biological proxies employed during the initial trials will allow studies examining the relationship between freshwater intrusions and potential threats to public health in the coastal ocean. Such measurements will involve different space and time scales than employed in the tank environment (as indicated in the introductory paragraphs), but will be highly analogous in their overall application and collation.

5. APPLICATION TO MARINE SAMPLING AND MONITORING

5.1. Correlation of Environmental and Organismal Data

Early descriptions of the ocean cast it as a homogeneous environment. This description persisted for many years, despite the contradiction posed by the presence of a myriad of microbial species that should have outcompeted each other in a truly homogeneous ecosystem. Indeed, one of the landmark publications in the field drew attention to the presence of far too many planktonic species given the homogeneous nature of the environment [Hutchinson 1961].

It is now generally accepted that the ocean is an extremely heterogeneous environment at the microscale, and that these unique microhabitats support the huge diversity of microorganisms that exist in the ocean. Studies applying chemical detectors with high spatial resolution have indicated an enormous amount of microscale physical/chemical structure in planktonic ecosystems formerly believed to be homogeneous [Donaghay et al. 1992]. Similarly, the use of microelectrodes in sediment biogeochemistry has dramatically changed our understanding of benthic ecosystems. Investigations have demonstrated enormous microscale structure in these environments [Revsbech and Jorgensen 1986]. Examinations of the microbial populations within these microenvironments (both planktonic and benthic) have indicated distinct distributions of these populations with respect to chemical/physical zonation. Unfortunately, up to the present time high-resolution in situ measurements of chemistry and physics have been difficult, and in situ, real-time microbial species identification has been completely lacking. Yet, linking these two features together is fundamental for understanding the factors controlling the biogeography of these species.

The previous sections on networking and robotics describe our approach for environmental data acquisition at the centimeter scale. In the next section we discuss molecular biology techniques for microorganism identification, which are needed to correlate environmental and organismal data. Finally, we present basic concepts of nanorobotics, and explain how nanorobotics may be used to collect environmental data at an even finer resolution (millimeter or micrometer scale), and to apply cell biology identification techniques to in situ analysis of microorganisms.

5.2. Offline Organism Identification

The last 10-15 years has witnessed an explosion of new approaches for detecting and identifying microorganisms in natural aquatic communities as the molecular revolution within the biomedical field has expanded into other fields of study. In particular, genetic and immunological-based methodologies have appeared for identifying and enumerating a myriad of microbial types. Not surprisingly, these approaches have included protocols for the detection of many societally-relevant species of viruses, bacteria and protists [Anderson et al. 1989, Shapiro et al. 1989, Scholin et al. 1996, Noble and Fuhrman 1997, Caron et al. 1999]. While the appearance of these techniques has improved our ability to detect target species, they have not yet been adapted in a way that can provide the high-resolution real-time data required to understand the determinants of species distribution. That is, they are not yet applicable in situ.

Successful development and application of methodology for in situ identification of microbial species is dependent on the identification of specific signatures (e.g. genetic, immunological) that can be used to develop probes of high sensitivity and specificity towards those organisms. Today, this is a relatively straightforward matter. In addition, however, there must be a strategy for applying these probes, and a means of detecting the probe-target complexes efficiently and quantifiably. Unfortunately, techniques that are presently available to accomplish this latter task are lab-based and require considerable sample preparation and/or manipulation. For example, DNA arrays designed to determine the expression of genes typically require the extraction and purification of messenger RNA, the production of detectable (labeled) cDNA from the mRNA, and then the survey of those libraries against the arrays [Duggan et al. 1999]. Similarly, present immunological applications such as the ELISA (enzyme-linked immuno-sorbent assay) rely on the detection of antibody-antigen complexes using conditions that are not appropriate for in situ applications.

The development of in situ probing protocols is predicated on resolving the issues of forming and detecting highly specific probe-target complexes at very low concentration in an aqueous environment. These issues constitute a major research effort. We will address them via the use of genetic and immunological methods for microbial species identification both in a conventional lab setting and by nanorobotic techniques (see below). Both genetic and immunological approaches to the identification of microbial species have merit, and both will be pursued at least initially. A major advantage of this research program is that we have experience with both approaches, and excellent model systems for analyzing them.

Genetic-based methodology will focus on the use of oligonucleotide probes for detecting small (<10 m) microorganisms. We have recently completed a program to develop and apply ribosomal RNA-targeted oligonucleotide probes for an ecologically-important species of chrysomonad [Caron et al. 1999, Lim et al. 1999]. While there are significant technical issues involved with the application of RNA-targeted probes, their application is advancing rapidly as a consequence of their wide use in DNA arrays (DNA chips). We will test the feasibility of this technology, again in the biology lab and through nanorobotics. Immunologically-based approaches have greater immediate merit as a means of detecting and identifying microorganisms because antibodies for antigenic features of the cell surface can be developed. This possibility obviates the need to enter or disrupt the cell (which would be necessary if one is targeting RNA). We have recently developed a monoclonal antibody against the harmful alga *Aureococcus anophagefferens*, a 2-3 μm pelagophyte alga that is the cause of massive noxious algal blooms known as brown tides in coastal waters of the northeastern U.S. The antibody is very highly specific, and we have successfully adapted it to an ELISA format for assaying the abundance of this alga in natural water samples. While this constitutes a considerable improvement over previously used methods, we have not yet attempted to develop a truly in situ method based on its application. This research program will afford that opportunity.

Both approaches (genetic or immunological) raise difficult but not intractable issues in transitioning to an in situ method. Major considerations include temperature (both types of approaches are temperature-sensitive), effects of seawater ionic composition, pH, etc., and of course signal transduction. Reporter systems (mechanisms for detecting probe-target binding) include fluorescent, radioactive or electrical detection. Current research on the latter mechanism has proven to be particularly interesting (again, spearheaded by research on DNA arrays).

5.3. Nanorobotics

We now introduce some basic concepts of nanorobotics using Scanning Probe Microscopes (SPMs), and then focus on SPM applications in environmental data acquisition and organism identification. Invented in the 1980s, the SPM has had a major impact on science and technology, and is one of the primary forces behind the rapid development of nanotechnology that is presently taking place. There are many types on SPMs. We will focus here on the Atomic Force Microscope (AFM).

The forces between atoms in the tip of the AFM and the sample cause a deflection of the cantilever that carries the tip. The amount of deflection typically is measured by bouncing a laser beam off the top of the cantilever. (Other approaches, e.g., by using piezoresistive cantilevers, are also in use and are more amenable to miniaturization.) The tip can be moved vertically with respect to the sample, in the -z or +z directions in the figure, by means of piezoelectric actuators. If the tip of the AFM is brought very close to the sample, at distances below 1 nm, the tip/sample forces are repulsive, and oppose sample penetration by the tip. This mode of operation is called contact mode. The force is kept constant by a feedback circuit that controls the piezoelectric actuators. Because the force depends on the tip/sample gap, the distance is also kept constant. Additional piezo motors drive the tip (or, equivalently, the sample) in a xy scanning motion. Since the tip/sample gap is constant, the scanning tip traverses a surface parallel to the sample surface. The result of a scan is a z(x,y) terrain map that follows closely the topography of the sample, as indicated diagrammatically in the figure.

Alternatively, the AFM tip can be placed at distances on the order of several nm or tens of nm above the surface, where the interatomic forces between tip and sample are attractive. The cantilever is vibrated at a frequency near its resonance frequency, in the tens or hundreds of kHz range. The tip/sample force causes a change in the cantilever resonance frequency. In turn, the frequency shift in the resonance curve causes a change in the amplitude of the tips vibration. This amplitude change can be used as the error signal in the feedback circuit that controls the tip. This mode of operation is called non-contact mode. A third mode of operation, called intermittent contact (or tapping) mode, lies betweeen the other two. In this mode the cantilever vibration is such that the tip touches the sample briefly in each cycle. Typically, non-contact or intermittent contact (both are also known as Dynamic Force Microscopy or DFM) are used for biological samples, which cannot withstand the higher forces associated with contact mode. AFMs can be used in air, and, importantly, in liquid environments by (partially) immersing the cantilever in the liquid contained in a liquid cell, which typically is a cylinder of radius $\sim$ 1 cm and height $\sim$ 0.5 cm.

Modern SPM tips have radii in the range of tens of nm, and even smaller tips based on carbon nanotubes are being developed [Wong et al. 1998b]. Therefore, the tip is essentially a nanorobot, although it is tethered by a micrometer-scale cantilever to a centimeter-scale body, which in turn is connected to meter-scale electronic systems, computers and displays. For the past few years USCs molecular robotics lab has been successfully developing strategies and software for controlling the SPM tip as a nanorobot, so as to both sense and act at the nanoscale. The AFM senses primarily forces, but these can be converted into topography, as explained above, and also into chemical information, if the tip is functionalized with suitable molecules. Thus, for example, forces between complementary DNA strands can be measured [Lee et al. 1994], and more general chemical probing can be done [Wong et al. 1998a]. Lateral, or frictional forces as the tip travels over the sample can be measured in another mode of operation, called Lateral Force Microscopy (LFM). Friction often provides information that suffices to determine the chemical nature of the samples features [Papastavrou and Akari 1999]. Furthermore, chemical sensitivity has also been demonstrated by yet another technique called phase imaging [Wong et al. 1998a]. Temperature sensing with an SPM has also been achieved

[Nakabeppu et al. 1995]. In short, SPM technology offers a plethora of methods that can be used to investigate biological materials, and even single living cells see e.g. [Vi et al. 2000, Lehenkari et al. 2000]

Autonomous nanorobots capable of moving in a liquid do not yet exist. However, sensing and manipulation techniques developed for a tethered nanorobotic SPM tip are likely to extend to the more capable nanorobots of the future, unlike the cell biology methods described in the previous section. Since the tip is computer controlled, SPM methods are also likely to be easier to automate, and therefore may have advantages over their counterparts even in the short term.

We plan research with the dual goal of (i) acquiring data within an SPM liquid cell with extremely high resolution (micrometer or sub-micrometer) and (ii) developing methodology for the in-situ identification of aquatic microorganisms. The data acquisition work will supplement the environmental data obtained in the tank experiments with higher resolution information. The organism identification approach will be based on the same principles as the lab-based, molecular/immunological methodologies described in the previous section, but will seek to adapt these to real-time analysis in natural communities of microorganisms. The work will employ well-characterized probe-target models in the lab to validate the SPM approach.

6. SUMMARY

Sensor networks supporting detailed physical monitoring and manipulation offer enormous opportunities for many scientific disciplines. Moreover, these capabilities promise to revolutionize critical national priorities, from medicine to agriculture, to regulatory enforcement. This paper focused on Marine microbiology as the application domain. The ability to acquire environmental data at very high spatial and temporal resoultion, and to correlate those data with organism abudnance and resopnse would open new vistas in marine research. It would also have a major impact on how we detect and respond to pathogens and other harmful organisms in the coastal environment.

ACKNOWLEDGMENTS

This work is supported by NSF grants ANI-9979457 and ANI-0082498 under the Special Projects in Networking Program and ONR grant N00014-00-1-0638 under the DURIP equipment support program.

7. REFERENCES

[Arkin 1989] R. Arkin, "Behavior-Based Robotics", MIT Press, 1989.

[Caron et al. 1999a] Caron, D.A., R.J. Gast, E.L. Lim and M.R. Dennett. Protistan community structure: molecular approaches for answering ecological questions. 1999. Hydrobiologia. 401: 215-227.

[Caron et al. 1999b] Caron, D.A., E.L. Lim, M.R. Dennett, R.J. Gast, C. Kosman and E.F. DeLong. Molecular phylogenetic analysis of the heterotrophic chrysophyte genus Paraphysomonas and the design of rRNA-targeted oligonucleotide probes for two species. 1999. J. Phycol. 35: 824-837.

[Estrin et al. 1999] D. Estrin, R. Govindan, J. Heidemann and S. Kumar, "Next Century Challenges: Scalable Coordination in Sensor Networks", ACM MobiCom '99, August 1999, Seattle, USA.

[Goel 1999] Goel P., Roumeliotis S.I. and Sukhatme G.S.: "Robust Localization using Relative and Absolute Position Estimates", Proc. 1999 IEEE/RSJ International Conference on Robots and Systems (IROS 99).

[Intanagonwiwat et al. 2000] C. Intanagonwiwat, R. Govindan and D. Estrin "Directed Diffusion: A Scalable and Robust Communication Paradigm for Sensor Networks", submitted to ACM MobiCom 2000.

[Jun 1999] Jun M., Roumeliotis S.I. and Sukhatme G.S.: "State Estimation of an Autonomous Helicopter using Kalman Filtering", Proc. 1999 IEEE/RSJ International Conference on Robots and Systems (IROS 99).

[Lee et al. 1994] G. U. Lee, L. A. Chrisey and R. J. Colton, Direct measurement of the forces between complementary strands of DNA, Science, Vol. 266, pp. 771-773, 4 November 1994.

[Lehenkari et al. 2000] P. P. Lehenkari, G. T. Charras, A. Nyknen and M. A. Horton, Adapting atomic force microscopy for cell biology, Ultramicroscopy, Vol. 82, Nos. 1-4, pp. 289-295, February 2000.

[Lim et al. 1999] Lim, E.L., D.A. Caron and M.R. Dennett. 1999. The ecology of Paraphysomonas imperforata based on studies employing oligonucleotide probe identification in coastal water samples and enrichment culture. Limnol. Oceanogr. 44: 37-51.

[Mataric 1992] Mataric, M. J. (1992), Integration of representation into goal-driven behavior-based robots, IEEE Trans. Robotics & Automation, 8(3), pp. 304–312.

[Mataric 1995a] Maja J. Mataric, "Issues and Approaches in the Design of Collective Autonomous Agents", Robotics and Autonomous Systems, 16(2-4), Dec 1995, 321-331.

[Mataric 1995b] Maja J. Mataric, "Designing and Understanding Adaptive Group Behavior", Adaptive Behavior 4:1, Dec 1995, 51-80.

[Mataric 1997a] Maja J. Mataric, "Behavior-Based Control: Examples from Navigation, Learning, and Group Behavior", Journal of Experimental and Theoretical Artificial Intelligence, special issue on Software Architectures for Physical Agents, 9(2-3), H. Hexmoor, I. Horswill, and D. Kortenkamp, eds., 1997, 323-336.

[Mataric 1997b] Mataric, M. J. (1997), Learning social behavior, Robotics & Autonomous Systems, 20, pp. 191-204.

[Mills 1991] D. L. Mills, Internet time synchronization: the Network Time Protocol, IEEE Trans. Communications, Vol. COM-39, No. 10, pp. 1482-1493, October 1991.

[Papastavrou & Akari 1999] G. Papastavrou and S. Akari, "Specific detection of interactions between uncharged surfaces in different solvents: high-resolution imaging by chemical force microscopy", Nanotechnology, Vol. 10, No. 4, pp. 453-457, December 1999.

[Requicha 1999a] A. A. G. Requicha, Nanorobotics, in S. Nof, Ed., Handbook of Industrial Robotics. New York, NY: Wiley, 2nd. ed., pp. 199-210, 1999.

[Roumeliotis 1999a] Roumeliotis S.I., Sukhatme G.S., and Bekey G.A.: "Circumventing Dynamic Modeling: Evaluation of the Error-State Kalman Filter applied to Mobile Robot Localization", Proc. 1999 IEEE International Conference on Robotics and Automation, Detroit.

[Roumeliotis 1999b] Roumeliotis S.I., Sukhatme G.S., and Bekey G.A.: "Smoother based 3-D Attitude Estimation for Mobile Robot Localization", Proc. 1999 IEEE International Conference on Robotics and Automation, Detroit.

[Sukhatme 1999] Sukhatme G.S. and Montgomery J.F.: "Heterogeneous Robot Group Control and Applications", Proc. AUVS 99 Conference.

[Vi et al. 2000] V. Vi, M.-C. Giocondi, E. Lesniewska, E. Finot, J.-P. Goudonnet and C. Le Grimellec, Tapping-mode atomic force microscopy on intact cells: optimal adjustment of tapping conditions by using the deflection signal, Ultramicroscopy, Vol. 82, Nos. 1-4, pp. 279-288, February 2000.

[Wong et al. 1998a] S. S. Wong, E. Joselevitch, A.T. Woolley, C. L. Cheung and C. M. Lieber, Covalently functionalized nanotubes as nanometre-sized probes in chemistry and biology, Nature, Vol. 394, pp. 52-55, 2 July 1998.

[Wong et al. 1998b] S. S. Wong, J. D. Harper, P. T. Lansbury, Jr. and C. M. Lieber, Carbon nanotube tips: High resolution probes for imaging biological systems, J. Am. Chem. Soc., Vol. 120, No. 3, pp. 603-604, 1998.