

Distortion Metrics for Robotic Sensor Networks

Geoffrey A. Hollinger, Chiranjib Choudhuri, Urbashi Mitra, and Gaurav S. Sukhatme

Abstract—We examine the problem of planning the trajectory of a robotic vehicle to gather data from a deployment of stationary sensors. The robotic vehicle and the sensors are equipped with wireless modems (e.g., radio in terrestrial environments or acoustic in underwater environments), which provide noisy communication across limited distances. In such scenarios, the robotic vehicle can improve its efficiency by planning an informed data gathering trajectory. Prior work has proposed information theoretic performance metrics for these problems based on mutual information, but such metrics do not properly account for stochastic variations in the quantity being measured. We propose a novel performance metric for data gathering in robotic sensor networks based on the concept of squared error distortion. This metric provides a principled approach for modeling source variations and communication limitations during data collection. We analyze the formal properties of the distortion function, and we propose a sampling-based motion planning algorithm for optimizing data gathering tours for minimal distortion. We compare the proposed algorithms in simulation, and we show that distortion metrics provide significant improvements in data gathering efficiency.

I. INTRODUCTION

The accurate measurement and interpolation of large-scale spatio-temporal processes is becoming increasingly important for sciences such as biology, climatology, geology, and oceanography. In terrestrial environments, phenomena of interest include seismic activity [15], volcanic activity, and catastrophic weather patterns. In marine environments, harmful algal blooms [23], oil spills, and other oceanographic events are extremely challenging to monitor effectively with available technology (e.g., satellites, drifters, and human-operated surface craft). Recent advances in autonomous robotic vehicles and sensor networks have made it feasible to study and predict these phenomena across large spatial scales and long periods of time, but a number of challenges still remain. For example, many currently deployed sensors must be removed from the field to download their data. The ability to gather sensor data in situ would improve the cost-effectiveness and lifespan of the sensors and would make such deployments feasible across larger scales.

To improve the efficiency of spatio-temporal monitoring, we discuss the use of an autonomous robotic vehicle acting as a “data mule” to gather data from a large-scale sensor




Fig. 1. Visualization of an autonomous vehicle gathering data from a deployment of sensors monitoring a source signal. We propose a novel metric based on the squared error distortion to optimize the trajectory of the vehicle.

deployment. The vehicle and sensors are equipped with wireless modems (e.g., radio in terrestrial environments or acoustic in underwater environments), which allow communication across limited range. Such range constraints are apparent in all large-scale sensor deployments, and they are particularly prominent in underwater sensor networks, where communication is limited to low-bandwidth acoustic modems [8] or short-distance optical [28].

In this paper, we propose a novel metric for coordinating the actions of a robotic vehicle collecting data from a stationary sensor network. The objective of the robotic vehicle is to process the collected data in order to track the dynamic source sequence. Since the problem setting is inherently estimation theoretic in nature, the metric we propose to measure the fidelity of the source estimate is based on the idea of minimizing the squared error *distortion* along the trajectory of the vehicle, which captures the average error in estimating the stochastic source. The distortion metric is widely used in the wireless communications literature (see [25], [19], [11], [4], [5] for details) to study the problem of lossy reconstruction of source sequences, but to our knowledge is unknown in the robotics literature.

The distortion metric is related to the more commonly used metric of mutual information for arbitrary source sequences. In fact, both the metrics are equivalent for Gaussian sources with additive Gaussian measurement noise, which is the premise of this work. In this work, we also develop a

G. Hollinger and G. Sukhatme are with the Department of Computer Science, Viterbi School of Engineering, University of Southern California, Los Angeles, CA 90089 USA, {gahollin, gaurav}@usc.edu

C. Choudhuri and U. Mitra are with the Department of Electrical Engineering, Viterbi School of Engineering, University of Southern California, Los Angeles, CA 90089 USA, {cchoudhu, ubli}@usc.edu

This research has been funded in part by the following grants: ONR N00014-09-1-0700, ONR N00014-07-1-00738, ONR N00014-06-10043, NSF 0831728, NSF CCR-0120778 and NSF CNS-1035866.

communication strategy (encoding strategy at the sensors and decoding strategy at the vehicle), which quantifies the effective distortion along the trajectory of the vehicle. The communication strategy we propose here is suboptimal, since the optimal strategy that minimizes the distortion in our problem setting is an open problem in information theory (see [16], [18] for details).

It is straightforward to show that, in the general case, finding an optimal trajectory for a vehicle to minimize distortion is NP-hard. We also show that distortion does not possess the properties of monotonicity or submodularity, which are often associated with information gathering metrics. However, we demonstrate that sampling-based motion planning algorithms can be used to generate effective trajectories using limited computational resources. The resulting robotic data collection trajectories improve the efficiency of sensing and move towards tighter integration between motion planning and communication.

The novelties of this paper include the introduction of a principled metric for autonomous data gathering based on distortion, the formulation of motion planning algorithms to optimize this metric efficiently, and the empirical comparison of the proposed techniques. The remainder of this paper is organized as follows. We first highlight the need for principled data gathering metrics by discussing related work in the areas of robotic motion planning, wireless communication, and sensor networks (Section II). We then formulate the robotic data collection problem, we introduce the distortion metric, and we propose a communication strategy that evaluates this distortion metric along a trajectory (Section III). The properties of the proposed distortion metric is derived in Section IV. We then propose a number of approximate algorithms for optimizing the distortion metric efficiently (Section V). Finally, we validate our proposed approach through simulated experiments (Section VI), draw conclusions, and discuss future work (Section VII).

II. RELATED WORK

There has been increasing interest in the robotics community on the problem of coordinating robotic data mules for data collection tasks [21]. Recent research has often focused on ground robots constrained to download data from all deployed sensors. If the network is sparse, it can be efficient to partition the sensors into sub-networks and optimize the collection over each sub-network [29]. For denser networks, if the communication range of the sensors can be modeled as a fixed radius, it is possible to develop efficient motion planning methods based on the Traveling Salesperson (TSP) with Neighborhoods [30]. Such techniques have been implemented on robots operating in real-world environments, showing the feasibility of robotic data mules with current technology [2].

For many applications of robotic sensor networks, a fixed communication radius is not a valid assumption, due to gradual degradation of packet error rate over distance [20]. To provide more realistic communication modeling, two-ring communication models have been explored [26] as

well as methods that optimize based on expected network latency [27]. Similar approaches have also been applied to improving the placement of sensors to maximize communication efficiency [14]. While these prior works properly integrate network power consumption and latency, they utilize information metrics based on information gain, which are not fundamentally tied to the properties of the communication system.

Robotic data collection from sensor networks has also been applied to applications in underwater domains. In such domains, communication is limited to long-range and low-bandwidth acoustic communication [24] or shorter-range and higher-bandwidth optical communication [28]. In our prior work, we have integrated robotic motion planning techniques with realistic acoustic communication modeling for the problems of station-keeping [1] and underwater search [9]. In recent work, we explored the problem of robotic data collection in underwater sensor networks, and we proposed motion planning algorithms that optimize assuming a probabilistic communication model [8]. In the current paper, we introduce a new metric for such tasks that measures the integrity of sensed information that is communicated over a channel¹, which improves the performance of the data collection.

III. PROBLEM FORMULATION

In this section, we formulate the problem of mobile data collection from stationary sensors using an autonomous vehicle.² We consider a pre-deployed network of K sensors located in \mathbb{R}^d with $d \in \{2, 3\}$, which yields the 2D and 3D problems respectively. We assume that the location $l_s(:, k) \in \mathbb{R}^d$ is given for each sensor $k \in [1 : K]$, where K is the total number of deployed sensors.

The objective of this work is planning the trajectory of a robotic vehicle to gather data from a deployment of stationary sensors observing a dynamic source, which is modeled as a discrete time stochastic process $\{S_i\}_{i \geq 1}$, where i denotes the time index. The source is assumed to be located at $l \in \mathbb{R}^d$, and it evolves according to a zero mean i.i.d. Gaussian random variable $S_i \sim \mathcal{N}(0, \sigma^2)$. The i.i.d. assumption on the source distribution implies that the time domain sampling rate of the source is larger than the coherence time of the source (i.e., the time over which a time varying source may be considered constant). From a practical perspective, this assumption maps to the case wherein the sensors only sample the source when there is a change in the source; as such, innovative information is collected and can

¹This measure can be extended to the case where we wish to optimize between sending sensed information and additional signals. This is an avenue for future work.

²Throughout the paper, we closely follow the standard notations. In particular, a random variable is denoted by an upper case letter (e.g., X, Y, Z) and its realization is denoted by a lower case letter (e.g., x, y, z). The shorthand notation X^n is used to denote the tuple (or the column vector) of random variables (X_1, \dots, X_n) , and x^n is used to denote their realizations. The notation $X^n \sim p(x^n)$ means that $p(x^n)$ is the probability mass function (pmf) of the random vector X^n . Similarly, $Y^n | \{X^n = x^n\} \sim p(y^n | x^n)$ means that $p(y^n | x^n)$ is the conditional pmf of Y^n given $\{X^n = x^n\}$.

be thought to be statistically independent from the previous samples.

The sensors observe the source through a noisy communication channel. The observation of each sensor k , which we refer to as the state of the sensor k , can be modeled as a discrete time stochastic process $\{S_{ki}\}_{i \geq 1}$. The stochastic process $\{S_{ki}\}_{i \geq 1}$ for each $k \in [1 : K]$ is assumed to be i.i.d. over time, whereas the state of different sensors at any instant of time i can be arbitrarily correlated to each other, or in other words, $\{S_{ki}\}_{k=1}^K$ are jointly distributed random variables with joint density function $f_K(s_{1i}, \dots, s_{Ki})$ for each $i \geq 1$. For the purpose of this work, we will assume that $\{S_{ki}\}_{k=1}^K$ is a zero mean jointly Gaussian random variable with a given covariance matrix, i.e., $(S_{1i}, \dots, S_{Ki})^T \sim \mathcal{N}(0, \Sigma)$. The covariance matrix can be evaluated by assuming an additive white Gaussian noise channel between the source and each of the sensors, which is given by

$$S_{ki} = h(L(l, l_s(:, k)))S_i + Z_{ki},$$

where the receiver noise at the k -th sensor is $Z_{ki} \sim \mathcal{N}(0, 1)$, and $h(\cdot)$ is channel coefficient, which is some deterministic functions of the distance $L(\cdot)$ between the source and corresponding sensor. Note that the covariance matrix $\Sigma_{K \times K}$ is time invariant since the process is i.i.d.

We consider the problem of data collection from such a sensor network using a mobile autonomous vehicle equipped with a wireless modem. The moving vehicle can be thought of as a receiver that processes the received output to estimate the source sequence. The location $l_v \in \mathbb{R}^d$ of the vehicle is assumed to be known with reasonable fidelity (e.g., using an onboard localization system). The movement of the vehicle is controlled and may be subject to constraints, such as obstacles or vehicle kinematics. Based on these constraints, a traversal cost $C(l_1, l_2)$ is defined for all pairs of points $l_1, l_2 \in \mathbb{R}^d$.

Each of the stationary sensors k is capable of transmitting a function of its observation $x_{ki} = f(s_k^i)$ (note that x_{ki} is a causal function of the sensor state s_k) over a noisy state dependent Gaussian multiple access channel given by

$$Y_i = \sum_{k=1}^K h_k(L(l_v, l_{sk}))X_{ki}(S_k^i) + S_i + Z_i,$$

where the receiver noise $Z_i \sim \mathcal{N}(0, 1)$ and $\{h_k\}_{k=1}^K$ are channel coefficients, which are again functions of the distance between the vehicle and corresponding sensor. We would like to underscore the difference between our channel model and the standard communication channel, as in we consider that the channel output Y_i also depends on the dynamic source S_i in addition to the additive noise. A motivating example for this state-dependent channel setting would be to consider a dynamic acoustic source, which is to be estimated at the autonomous moving vehicle with the help of a pre-deployed sensor network.

The sensors send a function of their accumulated noisy observation of the source to the vehicle through a communication channel, which is not only influenced by the receiver

noise, but also by the presence of the acoustic source in the medium. We assume an expected average transmission power constraint at the sensors

$$\sum_{i=1}^n \mathbb{E}(x_{ki}^2(S_k^i)) \leq nP_k, \quad \forall 1 \leq k \leq K,$$

where the expectation is over the random source sequence S^n , and n is the number of samples taken by the vehicle at each location along its path. We also assume that the amount of time n the vehicle stays at a particular location is sufficient to invoke the law of large numbers.

The vehicle's goal is to move along a trajectory collecting data from the sensors to estimate the underlying sensor field with maximum fidelity. The fidelity of the field estimate at a particular location is measured by the *expected distortion*

$$D = \mathbb{E}(d(S^n, \hat{S}^n)) = \frac{1}{n} \sum_{i=1}^n \mathbb{E}(d(S_i, \hat{S}_i(Y^n))), \quad (1)$$

where $d : \mathcal{S} \times \hat{\mathcal{S}} \rightarrow [0, \infty)$ is a distortion measure between a state symbol $s \in \mathcal{S}$ and a reconstruction symbol $\hat{s} \in \hat{\mathcal{S}}$, which is a function of the observation y^n at a particular location l_v . Without loss of generality, we assume that for every symbol $s \in \mathcal{S}$ there exists a reconstruction symbol $\hat{s} \in \hat{\mathcal{S}}$ such that $d(s, \hat{s}) = 0$. In this work, we will consider squared error distortion $d(s, \hat{s}) = (s - \hat{s})^2$. The aim of the autonomous vehicle is to estimate the underlying field S^n in minimum mean squared error (MMSE); the estimate is made at each location and updated along the trajectory as the vehicle gathers more and more information.

A. Motion Planning

In the context of gathering data from pre-deployed sensor fields, the motion planning optimization problem is to generate a trajectory for an autonomous vehicle that retrieves data from the sensors and minimizes the traversal cost of the trajectory. The autonomous vehicle moves along a trajectory $\mathcal{P} = [l_v(:, 1), \dots, l_v(:, T)]$ (a trajectory is represented as a collection of points in \mathbb{R}^d) to gather data. As the vehicle receives more information from the sensors along its trajectory of travel, it updates the effective distortion $D_e(\mathcal{P}^t)$ in the estimation of the underlying field, which is given by

$$D_e(\mathcal{P}^t) = \frac{1}{2}(D_e(\mathcal{P}^{t-1}) + D(l_v(:, t))), \quad \forall t \in [1 : T],$$

where $D_e(\mathcal{P}^1) = D(l_v(:, 1))$, and $D(l_v(:, t))$ is given by (1). Given this problem formulation, we can state the following formal optimization problem:

Problem 1: Given a trajectory cost function $C(\mathcal{P}) = \sum_{t=1}^T c(\mathcal{P}(t-1), \mathcal{P}(t))$, and a set of possible trajectories $\mathcal{P} \in \Psi$, find

$$\mathcal{P}^* = \underset{f(\cdot), \mathcal{P} \in \Psi}{\operatorname{argmin}} D_e(\mathcal{P}) \quad \text{s.t.} \quad C(\mathcal{P}) \leq B,$$

where T is the index of the last point on the trajectory, B is a budget threshold on the cost of the trajectory (e.g., maximum mission time, battery life, or remaining fuel), and $f(\cdot)$ denote the encoding function at the sensors.

Remark 1: Instead of using the distortion metric as a fidelity criterion for the source estimate, the amount of information that the receiver retrieves about the source sequence can also be measured by the blockwise normalized mutual information, as is customary in measuring the security of the cipher systems in the literature of the Shannon theory (see [19] for an example). The blockwise normalized mutual information gain can be defined as

$$\mathcal{I} = \frac{1}{n} I(S^n; Y^n).$$

This measure guarantees that if there is coding involved at the sensors, then a large value of the associated mutual information implies reliable estimation at the receiver of the underlying source sequence. An alternative to minimizing the mean squared error of the estimate is to maximize the blockwise mutual information. For Gaussian sources with additive white Gaussian noises, which is the focus of our work, it can be shown that both metrics are equivalent, and the optimal strategy to maximize the mutual information also minimizes that distortion metric (see [19] for details). For any general source distribution, this mutual information measure would never be smaller than the rate–distortion function (see [6] for a detailed definition) of the source sequence, computed at the distortion given by the minimum value of D from Equation 1. Hence, minimizing the distortion remains a valid approach even for non-Gaussian source sequences.

B. Communication Strategy

If the vehicle were to know the sensor observations (s_{1i}, \dots, s_{Ki}) perfectly, then the optimal estimate of the underlying field S_i would be given by $\hat{S}_i = \mathbf{E}(S_i | S_{1i}, \dots, S_{Ki})$. Since the underlying field S_i is jointly Gaussian with (S_{1i}, \dots, S_{Ki}) , then the optimal estimate \hat{S}_i is a linear function of the sensor observations (S_{1i}, \dots, S_{Ki}) and is given by

$$\begin{aligned} \hat{S}_i &= [\mathbf{E}(S_i S_{1i}) \quad \dots \quad \mathbf{E}(S_i S_{Ki})] \Sigma^{-1}(S_{1i}, \dots, S_{Ki})^T \\ &= \Sigma_c \Sigma^{-1}(S_{1i}, \dots, S_{Ki})^T \\ &= \Lambda(S_{1i}, \dots, S_{Ki})^T = \sum_{k=1}^K \lambda_k S_{ki}. \end{aligned}$$

Thus, the aim of the vehicle (receiver in this case) is to estimate this linear function of the sensor observations at each location and update it along the path based on a strategy as given below.

As discussed in the introduction, the optimal encoding strategy at the sensors that achieve the minimum distortion is an open problem. We assume that the stationary sensors have limited capabilities and hence we choose the encoding function $X_{Ki} = f(S_k^i) = \alpha_k S_{Ki}$, where $\alpha_k = \sqrt{P_k / \Sigma(k, k)}$ is a constant chosen to satisfy the input power constraint of P_k at sensor k . Note that this simple amplification strategy at the sensors may be suboptimal, but with practical constraints of limited processing power at the sensors, amplify-and-forward is the most natural coding strategy to consider and offers good performance as seen in the sequel.

Now, let us compute the one-step effective distortion D_e for the proposed encoder and receiver as the data gathering vehicle moves from position $l_v(:, t)$ to $l_v(:, t+1)$. We assume that when the vehicle is at location $l_v(:, t)$, the effective distortion in estimating the observation S_k of sensor k from $T = 0$ to $T = t$ is given by $D_s(k, t)$, and the effective distortion in estimating the linear function of the sensor observations till time t is given by $D_e(\mathcal{P}^t)$. Then, the received output at the moving vehicle, when it is at location $l_v(:, t+1)$, is given by

$$\begin{aligned} Y_i &= \sum_{k=1}^K h_k(L(l_v(:, t+1), l_s(:, k))) X_{ki}(S_k^i) + S_i + Z_i, \\ &= \tilde{\Sigma}^T \underline{h} + S_i + Z_i, \end{aligned}$$

where $\tilde{\Sigma}^T$ and \underline{h} are K dimensional vectors with their j -th component given by $\underline{h}_j = h_j(L(l_v(:, t+1), l_s(:, 1))) \alpha_j$ and $\tilde{\Sigma}_j = S_{ji}$. If we choose $\hat{S}_{ki} = \mathbf{E}(S_{ki} | Y_i)$, then the distortion of the sensor observation S_{ki} at location $l_v(:, t+1)$ is

$$\begin{aligned} D(k) &= \Sigma(k, k) - \frac{\mathbf{E}(S_k Y)}{\mathbf{E}(Y^2)}, \\ &= \Sigma(k, k) - \frac{\mathbf{E}(S_k ([S_1 \quad \dots \quad S_K] \underline{h} + S + Z))}{\mathbf{E}([S_1 \quad \dots \quad S_K] \underline{h} + S + Z)^2}, \\ &= \Sigma(k, k) - \frac{\Sigma(k, :) \underline{h} + \Sigma_c(k)}{\underline{h}^T \Sigma \underline{h} + \underline{h}^T \Sigma_c^T + \Sigma_c \underline{h} + \mathbf{E}(S^2) + \mathbf{E}(Z^2)}. \end{aligned}$$

The total distortions of the sensor observations along the trajectory are then given by

$$D_s(:, t+1) = \frac{D_s(:, t) + D}{2}.$$

Hence, as the vehicle traverses from $l_v(:, t)$ to $l_v(:, t+1)$, the effective distortion $D_e(\mathcal{P}^{t+1})$ is given by

$$D_e(\mathcal{P}^{t+1}) = \sum_{k=1}^K |\lambda_k|^2 D_s(k, t+1).$$

Remark 2: The problem of online informative motion planning to estimate an underlying source for a network of sensing agents, each subject to some dynamic constraints and sensor limitations, has also been considered in [17], which focuses on a fixed vector source and quantifies the informativeness of a node given its measurement sequence as a function of the Fisher information metric for its connection to the Cramér–Rao lower bound (CRLB) on the error covariance of unbiased estimators [6]. Indeed, the Cramér–Rao matrix is exactly the inverse of the Fisher information matrix. However, the one caveat of this approach is that the Cramér–Rao lower bound is not always achievable, and hence the Fisher information metric is not a true measure of the actual information gain incurred in such settings.

In contrast, we consider an underlying stochastic source (as compared to a fixed vector source), and hence the Fisher information metric in its usual form (see [17]) is not the lower bound on the error covariance in estimating the dynamic source. The dynamic source in our problem setting

naturally suggests a stochastic version of the CRLB, wherein a further averaging the CRLB is needed to account for the stochastic nature of the source and this bound tends to be even looser if the CRLB for the fixed source is not tight. In contrast to prior work, we provide an encoding strategy at the sensors and a decoding strategy at the receiver, which quantifies the actual information gain at a node in terms of the effective mean squared error distortion. It can be easily shown that, conditioned on the encoding strategy of simple amplify-and-forward at the sensors (note that the encoding strategy we adopt may be suboptimal as we discussed above), the decoding strategy at the moving vehicle, this approach is optimal as it minimizes the mean squared error in estimating the source sequence.

Remark 3: The path planning algorithm can be easily extended to account for multiple sources present in the environment. We wish to plan the trajectory of the robotic vehicle gathering data from a set of K stationary sensors, which observes a set of N dynamic sources. The n -th source is modeled as a discrete time i.i.d. stochastic process $\{S_i^{(n)}\}_{i \geq 1}$, where i denotes the time index. The sources are assumed to be independent with each other for simplicity with $S_i^{(n)} \sim \mathcal{N}(0, (\sigma^{(n)})^2)$. Each sensor observe the sources through a noisy communication channel which is given by

$$S_{ki} = \sum_{n=1}^N h_n(L(l_n, l_s(:, k))) S_i^{(n)} + Z_{ki}, \quad \forall 1 \leq k \leq K.$$

The sensors amplify their observation to satisfy the power constraint (the amplify-and-forward is strictly suboptimal for multiple sources and a more sophisticated encoding strategy can be proposed) and send it to the moving autonomous vehicle, which receives an output that is given by

$$Y_i = \sum_{k=1}^K h_k(L(l_v(:, t+1), l_s(:, k))) \alpha_k S_{ki} + \sum_{n=1}^N S_i^{(n)} + Z_i.$$

With this communication strategy, we can evaluate the effective distortion along a trajectory of each of the sources separately based on an MMSE estimator discussed above. The path planning problem then reduces to minimizing the weighted effective distortion of the different sources, which is given by

$$\begin{aligned} \mathcal{P}^* &= \underset{f(\cdot), \mathcal{P} \in \Psi}{\operatorname{argmin}} \sum_{n=1}^N \beta_n D_e^{(n)}(\mathcal{P}) \\ \text{s.t. } &\beta_n \geq 0, \sum_{n=1}^N \beta_n = 1 \text{ and } C(\mathcal{P}) \leq B, \end{aligned}$$

where β_n are pre-established priors that signify the relative importance of the different sources.

IV. PROPERTIES OF THE DISTORTION METRIC

In this section, we show that the distortion metric defined in the previous section is neither monotonic nor submodular, two properties often associated with information optimization objectives [13]. These formal properties will provide

insight into the design of motion planning algorithms suitable for optimizing data gathering trajectories that minimize distortion.

Definition 1: Let Ω be the set of grid points of the sensor field. A function $f : 2^\Omega \rightarrow \mathbb{R}$ defined on the subsets of Ω , is said to be *monotonically decreasing* if for every $T \subseteq S \subseteq \Omega$, we have that $f(T) \geq f(S)$.

Definition 2: A function $f(\cdot)$ defined above, is said to be *submodular* iff for every $X \subseteq Y \subseteq \Omega$ and $x \in \Omega \setminus Y$ we have that $f(X \cup \{x\}) - f(X) \geq f(Y \cup \{x\}) - f(Y)$.

It is easy to see that the effective distortion function $D_e(\cdot)$ is *not monotonically decreasing* since it is inversely proportional to the channel qualities between the vehicle and the sensors (and thus proportional to the Euclidean distance between the sensors and the vehicle according to our channel model). Hence, along a randomly chosen trajectory \mathcal{P} , the effective distortion may increase or decrease depending on the varying channel qualities along the trajectory.

The effective distortion metric $D_e(\cdot)$ is also *not submodular*. To see this, let us consider a trajectory $\mathcal{P}_1 \subseteq \mathcal{P}_2$ and consider a new point $\{x\} \in \Omega \setminus \mathcal{P}_2$. The effective distortions along the trajectory are given by:

$$\begin{aligned} D_e(\mathcal{P}_1 \cup \{x\}) - D_e(\mathcal{P}_1) &= \sum_{k=1}^K |\lambda(k)|^2 \frac{D(k) - D_s(k, \mathcal{P}_1)}{2} \\ D_e(\mathcal{P}_2 \cup \{x\}) - D_e(\mathcal{P}_2) &= \sum_{k=1}^K |\lambda(k)|^2 \frac{D(k) - D_s(k, \mathcal{P}_2)}{2}, \end{aligned}$$

where $D(k)$ is the distortion of the sensor observation S_{ki} at location $x \in \Omega$. Since the effective distortions of the sensor observations $D_s(\cdot, \cdot)$ is not monotonic (varies randomly along a trajectory depending on the variation of channel quality along the path), there is no definite ordering between $D_e(\mathcal{P}_1 \cup \{x\}) - D_e(\mathcal{P}_1)$ and $D_e(\mathcal{P}_2 \cup \{x\}) - D_e(\mathcal{P}_2)$ for any randomly selected path in the sensor field. Thus the effective distortion metric $D_e(\cdot)$ is also not submodular.

V. MOTION PLANNING ALGORITHMS

We now discuss a sampling-based motion planning algorithm that efficiently generates trajectories to minimize the distortion metric while also maintaining the cost budget constraints. As discussed above, the distortion metric is neither monotone nor submodular, which excludes motion planning algorithms that rely on these assumptions [3], [22]. The distortion metric is also not convex, and it often contains a number of local minima. Thus, gradient-based methods are likely to perform poorly (see the simulations in the following section).

Our approach extends the RRT* [10] and Information-Rich RRT [17] algorithms to provide optimized distortion minimization. The key idea is to sample the configuration space of the vehicle (i.e., locations where the vehicle may visit) and to build up a tree of possible trajectories by incrementally extending candidate trajectories towards the

sampled points. The main challenges presented by the distortion metric are (1) calculating the distortion at each node on the tree in an efficient manner, and (2) focusing the tree generation such that candidate paths satisfy the budget requirements. We now discuss how we are able to handle these two challenges.

One desirable property of the distortion metric is that the distortion at time $t + 1$ is fully defined by the next segment of the vehicle’s trajectory, the locations of the sensors, the location of the information source, and the sensor distortion matrix $D_s(:, t)$ at time t along that trajectory. In the case where we know the locations of the sensors and the location of the information source, it is straightforward to build trajectories in an incremental fashion by storing the trajectory segments and the matrix $D_s(:, t)$ at each node. The memory requirements grow linearly in the number of nodes in the tree and quadratically in the number of sensors: $O(NK^2)$. For large deployments, the sparseness of $D_s(:, t)$ and/or local approximations can further reduce these memory requirements.

The problem of minimizing distortion subject to a budget constraint differs in several key ways from problems typically solved using sampling-based motion planners. In many problem domains, a vehicle must move from one point to another while minimizing the trajectory cost [10], [17]. For the problem of distortion minimization, there is no fixed goal point. Instead, there is a hard constraint on budget at which point the mission time has expired or the vehicle has run out of fuel. To apply sampling-based motion planners to these problems, we make the following modification: if a candidate trajectory would exceed the budget, it will never be extended towards a sampled point. We maintain a *closed list* of nodes on the tree that represent completed trajectories.³ As new points are generated, trajectories that are not completed will be extended and eventually lead to completed trajectories. This approach builds up a large number of completed trajectories that efficiently explore the space of trajectories and provide different levels of distortion minimization.

The final two optimizations that we make for the sampling-based motion planner are to rewire the tree if a new trajectory appears to provide lower distortion at a lower cost (see [10]) and to bias the sampling towards areas of lower distortion (generated by an initial coarse distortion estimate). We also store the locations of the nodes in a KD-tree, which allows for efficient retrieval of the nearest nodes. The full Budget-Constrained Distortion Minimization RRT (BCDM-RRT) algorithm is described in Algorithm 1. The general algorithm allows for constraints on the vehicle’s motion (e.g., non-holonomic constraints) and can also account for obstacles and “no-fly zones” in the environment.

We can also extend the proposed algorithm to multiple vehicles by sampling in the space generated by the cross product of the vehicle’s individual configuration spaces. In

³We note that this method can also be used in a receding-horizon manner by planning over a budget increment and then re-planning after the budget increment is expended.

Algorithm 1 Budget-Constrained Distortion Minimization RRT (BCDM-RRT)

```

1: Input: Step size  $\Delta$ , Budget  $B$ , Workspace  $\mathcal{X}_{all}$ ,
   Free space  $\mathcal{X}_{free}$ , Sensor/source specs  $\mathcal{S}_{sensors}$ ,
   Starting configuration  $\mathbf{x}_{start}$ 
2: % Calculate initial distortion
3:  $D_{init} \leftarrow InitialDistortion(\mathbf{x}_{start}, \mathcal{S}_{sensors})$ 
4:  $C_{init} \leftarrow 0$ ,  $n \leftarrow \langle \mathbf{x}_{start}, C_{init}, D_{init} \rangle$ 
5:  $\mathcal{T} \leftarrow \{n\}$ ,  $\mathcal{T}_{closed} \leftarrow \emptyset$ 
6: while processing time remains do
7:   % Sample configuration space of vehicle
8:    $\mathbf{x}_{samp} \leftarrow Sample(\mathcal{X}_{all})$ 
9:   % Find nearest point in tree that can be extended
10:   $n_{near} \leftarrow Nearest(\mathbf{x}_{samp}, \mathcal{T} \setminus \mathcal{T}_{closed})$ 
11:  % Extend towards nearest point
12:   $\mathbf{x}_{new} \leftarrow Steer(\mathbf{x}_{n_{near}}, \mathbf{x}_{samp}, \Delta)$ 
13:  if  $\mathbf{x}_{new} \in \mathcal{X}_{free}$  then
14:    % Update distortion and cost
15:     $D_{new} \leftarrow Distortion(D_{n_{near}}, \mathbf{x}_{new}, \mathcal{S}_{sensors})$ 
16:     $c(\mathbf{x}_{new}) \leftarrow EvaluateCost(\mathbf{x}_{n_{near}}, \mathbf{x}_{samp}, \Delta)$ 
17:     $C_{new} \leftarrow C_{n_{near}} + c(\mathbf{x}_{new})$ 
18:     $n_{new} \leftarrow \langle \mathbf{x}_{new}, C_{new}, D_{new} \rangle$ 
19:    % Set parent of new node
20:     $parent(n_{new}) \leftarrow n_{near}$ 
21:    % Add to closed list if budget exceeded
22:    if  $C_{new} > B - \Delta$  then
23:       $\mathcal{T}_{closed} \leftarrow \mathcal{T}_{closed} \cup \{n_{new}\}$ 
24:    end if
25:     $\mathcal{T} \leftarrow \mathcal{T} \cup \{n_{new}\}$ 
26:  end if
27:  % Get near nodes within pre-specified radius  $r$ 
28:   $N_{near} \leftarrow Near(\mathbf{x}_{n_{new}}, \mathcal{T} \setminus \mathcal{T}_{closed}, r)$ 
29:  % Rewire  $N_{near}$  if cost/distortion both smaller [10]
30:   $\mathcal{T} \leftarrow Rewire(\mathcal{T}, N_{near})$ 
31: end while
32:  $\mathcal{P} \leftarrow MinDistortionPath(\mathcal{T}_{closed})$ 

```

the multi-vehicle case, a large number of samples may be required to sufficiently cover the sampling space and generate desirable trajectories. We leave a detailed discussion of multi-vehicle data gathering for distortion metrics for future work.

VI. SIMULATED EXPERIMENTS

We now provide simulated experiments to test the proposed motion planning techniques and their effectiveness in minimizing the distortion metric. The simulations were performed in C++ on an Ubuntu Linux desktop with a 3.2 GHz Intel i7 processor with 9 GB of RAM. We first examine the performance of the proposed BCDM-RRT sampling-based motion planner in a 10 km \times 10 km 2D environment with 10 randomly placed sensors and a randomly placed source. The vehicle is capable of unconstrained motion with a maximum speed of 1 km/hr. The environment contains a varying number of circular obstacles generated with random radii up to 5 km.




Fig. 2. Comparison of the BCDM-RRT sampling-based motion planning algorithm to a gradient-based approach and two heuristic strategies in a $10 \text{ km} \times 10 \text{ km}$ environment with obstacles. The simulated vehicle is capable of unconstrained motion at a maximum speed of 1 km/hr . The proposed method provides improved estimation of the source signal for a given trajectory length. Each data point is averaged over 1000 random sensor deployments, and error bars are one SEM.

Figure 2 shows the results from data gathering tours in 1000 random deployments with an increasing number of obstacles for two mission times. In all cases, the BCDM-RRT outperforms the gradient-based method due to its ability to escape local-minima in the distortion function and find a more globally optimal path. The advantage of the BCDM-RRT is greater with increasing mission times and with fewer obstacles (due to fewer constraints on the vehicle’s motion). We also compare to two heuristics that are unaware of the underlying distortion: a random walk and a strategy that moves directly to the information source. The BCDM-RRT greatly outperforms these heuristics, which demonstrates the importance of considering distortion in the trajectory optimization.

We next apply our BCDM-RRT algorithm to an autonomous underwater vehicle (AUV) with dynamics. The BCDM-RRT was integrated into the Open Motion Planning Library (OMPL) [7]. The 3D position of the AUV is defined as $\mathbf{x} = (x, y, z)$, and the controls are modeled as $\mathbf{u} = (u_f, u_z, u_\theta)$. Simple vehicle dynamics are modeled using the following equations: $\dot{x} = u_f \cos \theta$, $\dot{y} = u_f \sin \theta$, $\dot{z} = u_z$,




Fig. 3. Trajectory generated for an autonomous underwater vehicle (AUV) with dynamics. The information source is shown as a square, and the sensors are shown as diamonds. The vehicle’s starting point is shown as a circle, and its trajectory is shown as a solid line. The proposed algorithm minimizes the expected distortion along the path and also incorporates general constraints on the vehicle’s trajectory. The vehicle moves in a trajectory that veers towards the bottom sensor before moving towards a location between the information source and its closest sensor.

and $\ddot{\theta} = u_\theta$. Figure 3 shows an example trajectory in a 3-sensor network where the vehicle veers towards one sensor before moving towards the source and its closest sensor. This sophisticated behavior is possible due to the generality of the BCDM-RRT motion planning algorithm. The demonstration of the proposed techniques to vehicles with motion constraints demonstrates the broad applicability of our approach across platforms and application environments.

VII. CONCLUSIONS AND FUTURE WORK

In this paper, we have examined the problem of cost-constrained motion planning of a robotic vehicle to gather data from a network of stationary sensors tracking a dynamic source. Since the underlying objective is to estimate a stochastic source sequence, we propose a performance metric based on the concept of minimizing the squared error distortion in communicating the sensed signal. We introduce a sampling-based motion planning algorithm for optimizing data gathering tours for minimal distortion, and we show that planning using distortion metrics provides significant improvements in data gathering efficiency versus naive methods.

We showed that a simple encoding and decoding strategy performs well in this domain, and we plan to explore the fundamental limit of the proposed distortion metric as future work. We also plan to extend our framework to study the trade-off between sending information about the sensed source and additional signals (which could be for example a preamble from each of the sensors to achieve synchronization at the receiver). In addition, the extension to correlated sources and moving sources would be of practical importance for many spatio-temporal monitoring applications. From the algorithmic point of view, one important area for future work is to examine the asymptotic optimality of the BCDM-RRT. Another area to consider is more informed sampling

techniques for biasing the tree generation towards areas of minimal distortion. These refinements will move towards improved estimation-theoretic planning for a wide variety of robotic data collection tasks.

REFERENCES

- [1] F. Arrichiello, D. N. Liu, S. Yerramalli, A. Pereira, J. Das, U. Mitra, and G. S. Sukhatme, "Effects of underwater communication constraints on the control of marine robot teams," in *Proc. Int. Conf. Robot Communication and Coordination*, 2009, pp. 1–8.
- [2] D. Bhadauria, O. Tekdas, and V. Isler, "Robotic data mules for collecting data over sparse sensor fields," *J. Field Robotics*, vol. 28, no. 3, pp. 388–404, 2011.
- [3] J. Binney and G. S. Sukhatme, "Branch and bound for informative path planning," in *Proc. IEEE Int. Conf. Robotics and Automation*, 2012, pp. 2147–2154.
- [4] C. Choudhuri, Y.-H. Kim, and U. Mitra, "Causal state amplification," in *Proc. IEEE Int. Symp. Inf. Theory*, 2011, pp. 2110–2114.
- [5] —, "Causal state communication," 2012, preprint available at <http://arxiv.org/pdf/1203.6027v1.pdf>.
- [6] T. M. Cover and J. A. Thomas, *Elements of Information Theory*, 2nd ed. New York: Wiley, 2006.
- [7] I. A. Şucan, M. Moll, and L. E. Kavraki, "The Open Motion Planning Library," *IEEE Robotics & Automation Mag.*, 2012, to appear. [Online]. Available: <http://ompl.kavrakilab.org>
- [8] G. Hollinger, S. Choudhary, P. Qarabaqi, C. Murphy, U. Mitra, G. Sukhatme, M. Stojanovic, H. Singh, and F. Hover, "Underwater data collection using robotic sensor networks," *IEEE J. Selected Areas in Communications*, vol. 30, no. 5, pp. 899–911, 2012.
- [9] G. Hollinger, S. Yerramalli, S. Singh, U. Mitra, and G. S. Sukhatme, "Distributed coordination and data fusion for underwater search," in *Proc. IEEE Conf. Robotics and Automation*, 2011, pp. 349–355.
- [10] S. Karaman and E. Frazzoli, "Sampling-based algorithms for optimal motion planning," *Int. J. Robotics Research*, vol. 30, no. 7, pp. 846–894, 2011.
- [11] Y.-H. Kim, A. Sutivong, and T. M. Cover, "State amplification," *IEEE Trans. Inf. Theory*, vol. 54, no. 5, pp. 1850–1859, 2008.
- [12] M. Kobilarov, "Cross-entropy motion planning," *Int. J. Robotics Research*, vol. 31, no. 7, pp. 855–871, 2012.
- [13] A. Krause and C. Guestrin, "Submodularity and its applications in optimized information gathering," *ACM Trans. Intelligent Systems and Technology*, vol. 2, no. 4, 2011.
- [14] A. Krause, C. Guestrin, A. Gupta, and J. Kleinberg, "Robust sensor placements at informative and communication-efficient locations," *ACM Trans. Sensor Networks*, vol. 7, no. 4, 2011.
- [15] A. Krishnan, E. Nissen, S. Saripalli, and R. Arrowsmith, "Change detection using airborne Lidar: application to earthquakes," in *Proc. Int. Symp. Experimental Robotics*, 2012.
- [16] A. Lapidoth and Y. Steinberg, "The multiple access channel with causal and strictly causal side information at the encoders," in *Proc. International Zurich Seminar on Communications*, 2010.
- [17] D. S. Levine, "Information-rich path planning under general constraints using rapidly-exploring random trees," Master's thesis, Massachusetts Institute of Technology, June 2010.
- [18] M. Li, O. Simeone, and A. Yener, "Multiple access channels with states causally known at transmitters," *arXiv:1011.6639*, 2011.
- [19] N. Merhav and S. Shamai, "Information rates subject to state masking," *IEEE Trans. Inf. Theory*, vol. 53, no. 6, pp. 2254–2261, 2007.
- [20] A. Molisch, *Wireless communications*. Wiley, 2011.
- [21] R. C. Shah, S. Roy, S. Jain, and W. Brunette, "Data mules: Modeling and analysis of a three-tier architecture for sparse sensor networks," *Ad Hoc Networks*, vol. 1, no. 2–3, pp. 215–233, 2003.
- [22] A. Singh, A. Krause, C. Guestrin, and W. Kaiser, "Efficient informative sensing using multiple robots," *J. Artificial Intelligence Research*, vol. 34, pp. 707–755, 2009.
- [23] R. N. Smith, Y. Chao, P. P. Li, D. A. Caron, B. H. Jones, and G. S. Sukhatme, "Planning and implementing trajectories for autonomous underwater vehicles to track evolving ocean processes based on predictions from a regional ocean model," *Int. J. Robotics Research*, vol. 29, no. 12, pp. 1475–1497, 2010.
- [24] M. Stojanovic, "On the relationship between capacity and distance in an underwater acoustic communication channel," *ACM SIGMOBILE Mobile Computing and Communications Review*, vol. 11, no. 4, pp. 34–43, 2007.
- [25] A. Sutivong, M. Chiang, T. M. Cover, and Y.-H. Kim, "Channel capacity and state estimation for state-dependent Gaussian channels," *IEEE Trans. Inf. Theory*, vol. 51, no. 4, pp. 1486–1495, 2005.
- [26] O. Tekdas, D. Bhadauria, and V. Isler, "Efficient data collection from wireless nodes under the two-ring communication model," *Int. J. Robotics Research*, vol. 31, no. 6, pp. 774–784, 2012.
- [27] Y. Tirta, Z. Li, Y.-H. Lu, and S. Bagchi, "Efficient collection of sensor data in remote fields using mobile collectors," in *Proc. Int. Conf. Computer Communications and Networks*, 2004, pp. 515–519.
- [28] I. Vasilescu, K. Kotay, D. Rus, M. Dunbabin, and P. Corke, "Data collection, storage, and retrieval with an underwater sensor network," in *Proc. Int. Conf. Embedded Networked Sensor Systems*, 2005, pp. 154–165.
- [29] F. Wu, C. Huang, and Y. Tseng, "Data gathering by mobile mules in a spatially separated wireless sensor network," in *Int. Conf. Mobile Data Management: Systems, Services and Middleware*, 2009, pp. 293–298.
- [30] B. Yuan, M. Orłowska, and S. Sadiq, "On the optimal robot routing problem in wireless sensor networks," *IEEE Trans. Knowledge and Data Engineering*, vol. 19, no. 9, pp. 1252–1261, 2007.