

# dragon\_sr

by Gregory Koch (gkoch09@austincollege.edu)

**Last revision:** *July 26, 2011*

The **dragon\_sr** program consists of a single ROS node that uses a TCP server to listen for microphone input data from **DragonClient**, then publishes that same data to ROS provided that the data is in a valid format.

## 1 General

- All of the necessary files for **dragon\_sr** can be found in the ROS package of the same name.
- By default, **dragon\_sr** listens on port 34264 for incoming connections. **DragonClient** is setup to use the same port to connect to **dragon\_sr**.
- The **dragon\_sr** package contains four files in the `src` directory: `DragonReceiver.cpp`, `DragonReceiver.h`, `TCPServer.cpp`, `TCPServer.h`. The former two files compose the main class, which is used to handle ROS functionality and run a TCP server on a single thread. The latter two files correspond to the actual TCP server logic itself on a second thread.

## 2 Approach

- The main function is located in `DragonReceiver.cpp`. It is responsible for starting up ROS, starting up the TCP server (in the constructor for `DragonReceiver`), then start listening for messages from that server in `initialize()` on its own thread.
- The thread's main loop can be found in the function `receiverMainLoop()`, which continues until the program is terminated.
- Once messages come into the server, the thread then gets that input from the server, removing it from the server's queue.
- The thread is subsequently responsible for making sure that the input received is valid microphone input. To make this check, it ensures the first character of the input string is a valid uppercase or lowercase letter.
- In `TCPServer.cpp`, the TCP code is implemented using the native Linux socket libraries. After setting up the server on a socket using a `sockaddr_in` and obtaining its file descriptor, we set up a blocking read on the socket in the main loop for the server's thread.
- Whenever the thread unblocks, new input has been read from the socket. This input is put into a queue of input strings consisting of new microphone data, then another blocking read is performed.

## 3 Compiling

- Open the Linux terminal and run the command `rosmake dragon_sr dragon_sr` from any directory on any computer containing the **dragon\_sr** package.