

USC Viterbi
School of Engineering

An Integrated Speech-to-Text Parser for a Humanoid Robot

Gregory Koch
USC Interaction Lab, REU 2011
with Juan Fasola, Ph.D. Student
Supervised by Prof Maja Matarić



This work was supported by the National Science Foundation (NSF) via
Research Experiences for Undergraduates (REU) Grant #0755534:
Coordination, Communication, Autonomy: Principles and Technologies


Bandit II

- Bandit II humanoid robot platform
- Human robot interaction (HRI)
- Willow Garage Robot Operating System (ROS)




Enhancing speech control system

- Provided flexibility to allow interaction to be more natural.
- Added **stop, restart, and resume** functionalities.



Integrating a speech-to-text engine

- Used commercially available Dragon NaturallySpeaking software on Windows for speech recognition
- With a good microphone, accuracy is quite high
- Easy to use for any robot platform



Stanford NLP Parser

- Natural language processing can allow us to identify parts of speech to (attempt to) intelligently handle conversations with a human
- Used Stanford NLP parser to process input data from microphone
- Created Java application to interface between SNLP parser and Bandit
- Wrapped applications in ROS nodes

Stanford NLP Parser (cont.)

- Sample of output data
- Implemented a program to take output data and put it into a usable data structure.

Your query

Bandit, go to the green table.

Tagging

Bandit/UH ,/, go/VB to/TO the/DT green/JJ table/NN ./.


Parse

```
(ROOT
  (S
    (INTJ (UH Bandit))
    (, ,)
    (VP (VB go)
      (PP (TO to)
        (NP (DT the) (JJ green) (NN table))))
    (. .)))
```

Typed dependencies

```
dep(go-3, Bandit-1)
prep(go-3, to-4)
det(table-7, the-5)
amod(table-7, green-6)
pobj(to-4, table-7)
```

Overview of system architecture



Learning Game

- Video introduction



Learning Game - Implementation

- Pulls data from Microphone class to do further processing.
- Objective: identify parts of speech and use that information.

Learning Game – Implementation (cont.)

- Maintain a **knowledge base of nouns, verbs, and adjectives.**

Bandit, go to the yellow table please.

VB ADJ NN

Nouns

Verbs

Adjectives

- When it is time to perform an action, Bandit applies an algorithm to ground a phrase with the base definitions from the knowledge base, then sends a message to Bandit's ROS controller to execute the action.

Learning Game – Full demo

- Further video showing a full demo (with Juan Fasola)
- Note: acquired knowledge can be used in new ways!



Future work

- Current demos use an effective, but simple and uninformed implementation.
- Use NLP data obtained from the Stanford parser to build an intelligent robot dialog system.
- Find intelligent ways to incorporate the microphone in human-robot interaction experiments.

Questions/comments?

A final thanks to Juan Fasola for his mentoring and support throughout the duration of the project, as well as to Prof Matarić for the opportunity to gain research experience in her lab this summer.

Notes:

- Images/diagrams were produced with the Gliffy software (www.gliffy.com) and Microsoft Office.
- Video was produced using the Sony Vixia HF M31 HD camera and is property of the USC Interaction Lab.
- All work presented in this report was supported by the National Science Foundation Research Experiences for Undergraduates (REU) program, 2011.