

On the Observability and Self-Calibration of Visual-Inertial Navigation Systems

Jonathan Kelly

November 30, 2008

Abstract

We examine the observability properties of visual-inertial navigation systems, with an emphasis on self-calibration of the six degrees-of-freedom rigid body transform between a camera and an inertial measurement unit (IMU). Our analysis depends on a differential geometric formulation of the calibration problem, and on an algebraic test for the ‘observability rank condition’, originally defined by Hermann and Krener.

We demonstrate that self-calibration of the camera-IMU transform is possible, under a variety of conditions. In contrast with previous work, we show that, in the presence of a known calibration target, both the local gravity vector and the IMU gyroscope and accelerometer biases are simultaneously observable (given sufficient excitation of the system). Further and more generally, we show that for a moving monocular camera and IMU, the absolute scene scale, gravity vector, and the IMU biases are all simultaneously observable. This result implies that full self-calibration is possible, without the need for any prior knowledge about the environment in which the system is operating.

1 Introduction

Accurate ego-motion estimation is critical for many navigation tasks. Recent work has shown that visual and inertial sensors can, in combination, provide very accurate motion estimates. This makes them ideal for use in environments where wide-area positioning information, from GPS for example, is either unavailable or unreliable.

Progress in the fabrication of micro-electrical mechanical systems has led to the development of reliable, low-cost strapdown Inertial Measurement Units (IMUs). A strapdown IMU usually contains three orthogonal, single-axis accelerometers and three orthogonal angular rate gyroscopes. The change in pose of the IMU can, in theory, be determined by double-integrating the accelerometer outputs over time, using rate information from the gyroscopes to determine orientation.

In reality, inertial sensors are subject to low frequency drift, and therefore some form of aiding is required to maintain the integrity of the pose information. The existence of




Figure 1: Global $\{G\}$, IMU $\{I\}$, and camera $\{C\}$ reference frames, for target-based calibration. The transform from the IMU frame to the global frame is defined by the $(\mathbf{p}^G, \boldsymbol{\xi}_I^G)$ translation and rotation pair. The transform from the camera frame to the IMU frame is defined by the $(\mathbf{p}^I, \boldsymbol{\xi}_C^I)$ translation and rotation pair. A version of this figure appeared previously in [1].

varying biases (i.e. drift terms) also implies that IMU measurements are correlated in time. The problem is further complicated by the fact that the IMU accelerometers sense the force of gravity, in addition to forces which accelerate the platform. Typically, the magnitude of the gravity vector (nominally 9.81 m/s^2) is much larger than the magnitude of the platform accelerations (i.e. for land vehicle applications). If the orientation of the IMU relative to gravity is unknown, or the orientation is misestimated, then the integrated pose will diverge rapidly from the true pose.

When a camera is used for aiding, it is also important that the relative transform between the sensors be accurately known, so that measurements can be properly fused. In [1], we formulated the camera-IMU relative pose calibration problem in a filtering framework; we estimated the transform between the sensors by recording measurements from the IMU and images from the camera while the camera viewed a known, planar calibration target.

In this technical report, we analyze the *observability* of visual-inertial navigation, which is a necessary property for any filtering or estimation algorithm to converge. Our analysis follows a differential geometric approach, based on the observability rank condition introduced by Hermann and Krener in [2]. We are interested primarily in the ability to self-calibrate the camera-IMU transform, while dealing with the problems of time-varying biases and inexact knowledge of the orientation and magnitude of the local gravity vector. In contrast with previous work, we show that the six degrees-of-freedom (6-DoF) camera-IMU transform, IMU biases, gravity vector, and the absolute scene scale are *all* observable and can be estimated simultaneously, given sufficiently ‘exciting’ motion of the platform.

In Part I we consider the situation in which the camera views a known planar calibration target. In Part II, we extend our analysis to the case where the positions of tracked feature

points are not a priori known, and must therefore also be estimated.

1.1 Modeling Overview

We use a standard model for aided inertial navigation [3], with additional calibration parameters and the gravity vector included as part of the system state. Our analysis involves three separate reference frames:

- the camera frame $\{C\}$, positioned at the optical center of the camera and with the z axis aligned with the optical axis of the lens,
- the IMU frame $\{I\}$, positioned at the center of the sensor body and with the z -axis pointed downwards when the IMU is horizontal, and
- the world, or global, frame $\{G\}$, which is a fixed, inertial frame that serves as an absolute reference for both the camera and the IMU.¹

Orientations in the state vector are parameterized by a minimal set of roll, pitch and yaw Euler angles. Although there are singularities in this representation, their existence does not unduly restrict our calibration algorithm in most cases (we discuss this issue in more detail in Sections 3 and 6). We also emphasize that the results presented herein are valid for other orientation parameterizations, such as quaternions.

1.2 Notation

Throughout this report, we use a notation that follows the general conventions outlined in Britting [4] and in Chatfield [3]. Vectors and matrices are denoted by boldface Greek or Roman letters, e.g. $\boldsymbol{\omega}$ and \mathbf{A} . To indicate that a vector is expressed in a specific reference frame, we append a superscript identifying the frame, e.g. \mathbf{p}^A for the vector \mathbf{p} expressed in frame $\{A\}$. In our analysis, we make frequent use of both the zero matrix $\mathbf{0}$, and the identity matrix \mathbf{I} . We indicate the size of these matrices using a subscript, e.g. $\mathbf{I}_{3 \times 3}$ for the 3×3 identity matrix.

The determinant of a matrix is denoted by a set of vertical bars, e.g. $|\mathbf{A}|$ for the determinant of matrix \mathbf{A} . We use curly braces, $\{$ and $\}$, to denote the submatrix formed from several rows of a larger matrix, e.g. $\mathbf{B}\{1, 2, 6\}$ for the submatrix formed from rows 1, 2 and 6 of matrix \mathbf{B} . Finally, we use the symbols \llbracket and \rrbracket to denote *vectorization*, which involves stacking the columns of a matrix to form a single column vector, e.g. for the $m \times n$ matrix \mathbf{D} , $\llbracket \mathbf{D} \rrbracket$ is a $mn \times 1$ column vector.

If a vector describes the relative orientation of two reference frames, we append a subscript identifying the rotated frame and a superscript identifying the fixed frame, e.g. $\boldsymbol{\xi}_B^A$ for the vector describing the orientation of frame $\{B\}$ with respect to frame $\{A\}$. In particular, we will use the notation $\boldsymbol{\xi}_B^A = [\phi_B^A \ \theta_B^A \ \psi_B^A]^T$ for the vector of roll, pitch and yaw Euler angles, respectively, which describe the orientation of frame $\{B\}$ with respect to frame $\{A\}$.²

¹In fact, the global frame is not strictly an inertial frame, since it is attached to the surface of the rotating Earth. The effects of the Earth’s rotation are very small over the calibration time interval, however, and we therefore ignore them in our analysis.

²We follow what is commonly known as the ‘aerospace convention’ for Euler angles, i.e. with the arbitrary frames $\{B\}$ and $\{A\}$ both aligned initially, we rotate by an angle ϕ about the x (roll) axis of frame $\{B\}$,

2 Nonlinear Observability

In this section, we review several concepts from nonlinear observability theory. A dynamical system is said to be *observable* if it is possible to recover the state $\mathbf{x}(t)$ from knowledge of the measured outputs $\mathbf{y}(t)$, the control inputs $\mathbf{u}(t)$, and a finite number of their time derivatives $d^i \mathbf{y}(t)/dt$ and $d^k \mathbf{u}(t)/dt$ [5]. Consider the system:

$$S \begin{cases} \dot{\mathbf{x}}(t) = \mathbf{f}_0(\mathbf{x}(t)) + \sum_{i=1}^p \mathbf{f}_i(\mathbf{x}(t)) u_i(t) \\ \mathbf{y}(t) = \mathbf{h}(\mathbf{x}(t)) \end{cases} \quad (1)$$

where $\mathbf{x} \in M \subseteq \mathbb{R}^m$ (see below) is the vector of system states, $\mathbf{y} \in \mathbb{R}^n$ is the vector of observed outputs, and $\mathbf{u} \in \mathbb{R}^p$, $\mathbf{u} = [u_1, \dots, u_p]^T$ is the vector of control inputs. Systems of this type, which are known as *input-linear* or *control-affine* [6], are significant in particular because their observability properties (in a specific sense, discussed below) can be determined using an algebraic test.

Our observability analysis follows the differential geometric approach described by Hermann and Krener in [2]. We consider the state space as a C^∞ (i.e. infinitely smooth) manifold M of dimension m , and introduce additional concepts and notation as follows. Given a smooth vector field $\mathbf{f} : M \rightarrow TM$, where TM is the tangent bundle of M , and a smooth scalar function $h : M \rightarrow \mathbb{R}$, the *Lie derivative* of h with respect to \mathbf{f} at a point $\mathbf{x} \in M$ is:

$$L_{\mathbf{f}} h(\mathbf{x}) = \nabla_{\mathbf{f}} h(\mathbf{x}) = \frac{\partial h(\mathbf{x})}{\partial \mathbf{x}} \mathbf{f}(\mathbf{x}) = \sum_{i=1}^m \frac{\partial h(\mathbf{x})}{\partial x_i} \mathbf{f}_i(\mathbf{x}) \quad (2)$$

where $\partial h(\mathbf{x})/\partial \mathbf{x}$ is a row vector. The Lie derivative is the directional derivative (rate of change) of h along \mathbf{f} , evaluated at \mathbf{x} . Lie differentiation can be defined recursively, so that if we, for example, differentiate along vector field \mathbf{f} and then along vector field \mathbf{g} , we obtain:

$$L_{\mathbf{g}} L_{\mathbf{f}} h(\mathbf{x}) = \frac{\partial L_{\mathbf{f}} h(\mathbf{x})}{\partial \mathbf{x}} \mathbf{g}(\mathbf{x}) \quad (3)$$

Note that, in general, the Lie derivative is not commutative. If the function h is differentiated k times along the vector field \mathbf{f} , we use the notation $L_{\mathbf{f}}^k h(\mathbf{x})$, according to the recurrence relation:

$$L_{\mathbf{f}}^k h(\mathbf{x}) = \frac{\partial (L_{\mathbf{f}}^{k-1} h(\mathbf{x}))}{\partial \mathbf{x}} \mathbf{f}(\mathbf{x}) \quad (4)$$

By definition, $L^0 h(\mathbf{x})$ is simply the function h itself:

$$L^0 h(\mathbf{x}) = h(\mathbf{x}) \quad (5)$$

We now describe the algebraic test for observability defined by Hermann and Krener [2]. Consider the system S above, and let Ω be the smallest vector subspace containing h_j , $j = 1, \dots, n$, which is closed with respect to Lie differentiation by \mathbf{f}_0 and by $\mathbf{f}_i u_i$, $i = 1, \dots, p$, for a fixed $\mathbf{u} \in \mathbb{R}^p$. Let $d\Omega$ be the space of the gradients of the elements of Ω . The system S is *locally weakly observable* at \mathbf{x}_0 if $d\Omega(\mathbf{x}_0)$ has rank m , and *locally weakly observable* if $d\Omega(\mathbf{x})$ has rank m for all $\mathbf{x} \in M$ [7].

then by an angle θ about the y (pitch) axis of the first intermediate frame, and then by an angle ψ about the z (yaw) axis of the second intermediate frame.

We can also define the *observability matrix* \mathcal{O} for S . This matrix is composed of the gradients of the Lie derivatives as above, and in general may have an infinite number of rows. The columns of \mathcal{O} span $d\Omega$, and so if \mathcal{O} has full column rank at \mathbf{x}_0 then the system is locally weakly observable at \mathbf{x}_0 ; we say that S satisfies the *observability rank condition at \mathbf{x}_0* . If \mathcal{O} has full column rank for all $\mathbf{x} \in M$, then S satisfies the *observability rank condition generally*.

Intuitively, the definition of local weak observability expresses the fact that it is possible to instantaneously distinguish one point in the state space from its neighbors, based on the observed output of the system – or, in summary, “if the states are different, the measurements are different.” In particular, the rank condition is sufficient for estimating the state of the system from the measured outputs.

Part I

Target-Based Calibration

3 Introduction: Target-Based Calibration

We begin with the problem of calibrating the relative transform between a single camera and an IMU, while the camera views a known planar calibration target. As an initial step, we must choose an origin for the global reference frame – we will select the upper leftmost corner point on the target as the origin of the global frame.

Since the global frame is defined with respect to the target itself, the relationship between the frame and the local gravity vector is arbitrary and depends entirely on how the target is positioned. It is possible to manually align the vertical axis of the target with the gravity vector, however this alignment will not usually be exact. Any errors in the alignment will introduce bias in the calibration. We noted in Section 1 that the large magnitude of the gravitational acceleration makes accurate knowledge of the gravity vector critical; an estimate of this relationship is therefore important.

In this part of the report, we show that the accelerometer and gyroscope biases *and* the gravity vector are observable, when added to the system state. Further, they are observable *independent* of the linear motion of the camera-IMU platform (as shown in [8] for the biases-only case). We are therefore able to account for the time-correlation of the IMU measurements *and* for inexact initial knowledge of the orientation and magnitude of the gravity vector as part of the calibration process.

Note that the existence of singularities in our representation of orientation does not adversely affect the calibration algorithm, because the target must remain visible throughout the calibration procedure. For the camera-to-IMU transform, the pitch singularities can be avoided simply through a proper choice of IMU axes.

4 System Modeling

We define the 24×1 state vector for the continuous time system model as:

$$\mathbf{x}(t) = [(\mathbf{p}^G(t))^T \quad (\boldsymbol{\xi}_I^G(t))^T \quad (\mathbf{v}^G(t))^T \quad (\mathbf{b}_g(t))^T \quad (\mathbf{b}_a(t))^T \quad (\mathbf{p}^I)^T \quad (\boldsymbol{\xi}_C^I)^T \quad (\mathbf{g}^G)^T]^T \quad (6)$$

where \mathbf{p}^G is the position of the IMU in the global frame, $\boldsymbol{\xi}_I^G$ is the orientation of the IMU frame relative to the global frame, and \mathbf{v}^G is the velocity of the IMU in the global frame. Vectors \mathbf{b}_g and \mathbf{b}_a are the gyroscope and accelerometer biases, respectively, while \mathbf{p}^I is the position of the camera in the IMU frame and $\boldsymbol{\xi}_C^I$ is the orientation of the camera frame relative to the IMU frame. Finally, \mathbf{g}^G is the gravity vector, expressed in the global frame. Note that the last three entries are *parameters*, or constants, whose values will be estimated during the calibration procedure.

4.1 Process Model

Our process model uses the IMU linear acceleration and angular velocity measurements as substitutes for control inputs in the system dynamics equations [3]. IMU gyroscope and accelerometer biases are modeled as Gaussian random walk processes, driven by the white noise vectors \mathbf{n}_{gw} and \mathbf{n}_{aw} . Gyroscope and accelerometer measurements are assumed to be corrupted by white, zero-mean Gaussian noise vectors \mathbf{n}_g and \mathbf{n}_a , respectively. The system

state evolves in continuous time according to:

$$\dot{\mathbf{p}}^G = \mathbf{v}^G \quad \dot{\boldsymbol{\xi}}_I^G = \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \boldsymbol{\omega}^I \quad \dot{\mathbf{v}}^G = \mathbf{a}^G \quad (7)$$

$$\dot{\mathbf{b}}_g = \mathbf{n}_{gw} \quad \dot{\mathbf{b}}_a = \mathbf{n}_{aw} \quad \dot{\mathbf{g}}^G = \mathbf{0}_{3 \times 1} \quad (8)$$

$$\dot{\mathbf{p}}^I = \mathbf{0}_{3 \times 1} \quad \dot{\boldsymbol{\xi}}_C^I = \mathbf{0}_{3 \times 1} \quad (9)$$

where we do not explicitly indicate the time dependence in order to simplify the notation. Here, $\boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)$ is the Euler kinematic matrix that relates the rate of change of the Euler angles to the IMU angular velocity; $\boldsymbol{\omega}^I$ is the angular velocity of the platform expressed in the IMU frame. The term \mathbf{a}^G is the IMU acceleration in the global frame. The *measured* IMU angular velocity and linear acceleration are:

$$\boldsymbol{\omega}_m = \boldsymbol{\omega}^I + \mathbf{b}_g + \mathbf{n}_g \quad (10)$$

$$\mathbf{a}_m = \mathbf{a}^I + \mathbf{b}_a + \mathbf{n}_a = \mathbf{C}(\boldsymbol{\xi}_I^G)^T (\mathbf{a}^G - \mathbf{g}^G) + \mathbf{b}_a + \mathbf{n}_a \quad (11)$$

where $\mathbf{C}(\boldsymbol{\xi}_I^G)$ is a 3×3 direction cosine (rotation) matrix. Taking expectations, we have:

$$\dot{\hat{\mathbf{p}}}^G = \hat{\mathbf{v}}^G \quad \dot{\hat{\boldsymbol{\xi}}}_I^G = \boldsymbol{\Gamma}(\hat{\boldsymbol{\xi}}_I^G) (\boldsymbol{\omega}_m - \hat{\mathbf{b}}_g) \quad \dot{\hat{\mathbf{v}}}^G = \mathbf{C}(\hat{\boldsymbol{\xi}}_I^G) (\mathbf{a}_m - \hat{\mathbf{b}}_a) + \hat{\mathbf{g}}^G \quad (12)$$

$$\dot{\hat{\mathbf{b}}}_g = \mathbf{0}_{3 \times 1} \quad \dot{\hat{\mathbf{b}}}_a = \mathbf{0}_{3 \times 1} \quad \dot{\hat{\mathbf{g}}}^G = \mathbf{0}_{3 \times 1} \quad (13)$$

$$\dot{\hat{\mathbf{p}}}^I = \mathbf{0}_{3 \times 1} \quad \dot{\hat{\boldsymbol{\xi}}}_C^I = \mathbf{0}_{3 \times 1} \quad (14)$$

The system process model can be described by the matrix differential equation:

$$\dot{\mathbf{x}} = \begin{bmatrix} \dot{\mathbf{p}}^G \\ \dot{\boldsymbol{\xi}}_I^G \\ \dot{\mathbf{v}}^G \\ \dot{\mathbf{b}}_g \\ \dot{\mathbf{b}}_a \\ \dot{\mathbf{p}}^I \\ \dot{\boldsymbol{\xi}}_C^I \\ \dot{\mathbf{g}}^G \end{bmatrix} = \begin{bmatrix} \mathbf{v}^G \\ -\boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \mathbf{b}_g \\ \mathbf{g}^G - \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{b}_a \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \end{bmatrix} + \begin{bmatrix} \mathbf{0}_{3 \times 3} \\ \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \end{bmatrix} \boldsymbol{\omega}_m + \begin{bmatrix} \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{C}(\boldsymbol{\xi}_I^G) \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \end{bmatrix} \mathbf{a}_m \quad (15)$$

where \mathbf{f}_1 and \mathbf{f}_2 are functions of the control inputs $\boldsymbol{\omega}_m$ and \mathbf{a}_m , respectively. Note that Equation 15 is in control-affine form. We slightly abuse our notation here, as \mathbf{f}_1 and \mathbf{f}_2 are actually matrices, composed of the individual columns $\mathbf{f}_{1,1}, \mathbf{f}_{1,2}, \mathbf{f}_{1,3}$ and $\mathbf{f}_{2,1}, \mathbf{f}_{2,2}, \mathbf{f}_{2,3}$ respectively.

4.2 Observation Model

It is well known that the pose of the camera in the global frame is observable, given measurements of at least three distinct, noncollinear points on the calibration target [9]. The

position of the camera can be directly specified by a 3×1 translation vector, and we are free to choose any convenient representation for the camera orientation. Since rotations in the state vector are parameterized by Euler angles (which we cannot add directly), we will represent the camera orientation using the elements of the 3×3 rotation matrix $\mathbf{C}(\boldsymbol{\xi}_C^G)$:

$$\mathbf{C}(\boldsymbol{\xi}_C^G) = \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{C}(\boldsymbol{\xi}_C^I) = [\bar{\mathbf{i}}^G \quad \bar{\mathbf{j}}^G \quad \bar{\mathbf{k}}^G] \quad (16)$$

where $\bar{\mathbf{i}}^G$, $\bar{\mathbf{j}}^G$ and $\bar{\mathbf{k}}^G$ are the 3×1 unit vectors that define the x , y and z axes, respectively, of the camera frame in the global frame. Note that $\bar{\mathbf{i}}^G$, $\bar{\mathbf{j}}^G$ and $\bar{\mathbf{k}}^G$ are vector-valued functions of the Euler angles $\boldsymbol{\xi}_I^G$ and $\boldsymbol{\xi}_C^I$. We stack the individual unit vectors to form the 9×1 orientation measurement vector $\boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$:

$$\boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) = \begin{bmatrix} \bar{\mathbf{i}}^G \\ \bar{\mathbf{j}}^G \\ \bar{\mathbf{k}}^G \end{bmatrix} \quad (17)$$

We can now define the following vector-valued observation functions for the camera pose:

$$\mathbf{h}_1 = \mathbf{p}^G + \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{p}^I \quad (18)$$

$$\mathbf{h}_2 = \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \quad (19)$$

5 Observability Analysis

We show in this section that the nonlinear system described by Equation 15 is observable, given measurements defined by Equations 18 and 19. First, we introduce additional notation as follows: let $\mathbf{D}_i(\cdot)$ and $\mathbf{U}_j(\cdot)$ be matrices whose individual elements are functions of the state vector \mathbf{x} , where i and j are arbitrary index variables. We will define matrices $\mathbf{D}_i(\cdot)$, $i = 1, \dots, 8$ below as part of the observability proof; matrices $\mathbf{U}_j(\cdot)$, $j = 1, \dots, 11$ appear in the full observability matrix \mathcal{O} , but are not required for the proof – we do not, therefore, derive them explicitly.³

To demonstrate that the system is locally weakly observable, as defined in [2], we must prove that the matrix formed from the gradients of the Lie derivatives of the measurement functions has full column rank. We begin by defining the zero-order Lie derivatives, which are simply the measurement functions themselves:

$$L^0 \mathbf{h}_1 = \mathbf{p}^G + \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{p}^I \quad (20)$$

$$L^0 \mathbf{h}_2 = \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \quad (21)$$

The gradients are:

$$\nabla L^0 \mathbf{h}_1 = [\mathbf{I}_{3 \times 3} \quad \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{0}_{3 \times 3} \quad \mathbf{0}_{3 \times 3} \quad \mathbf{0}_{3 \times 3} \quad \mathbf{C}(\boldsymbol{\xi}_I^G) \quad \mathbf{0}_{3 \times 3} \quad \mathbf{0}_{3 \times 3}] \quad (22)$$

$$\nabla L^0 \mathbf{h}_2 = [\mathbf{0}_{9 \times 3} \quad \mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \quad \mathbf{0}_{9 \times 3}] \quad (23)$$

³Here, we use the mnemonic that ‘D’ stands for *Derivative*, since these matrices are the Lie derivatives of the measurements with respect to specific state variables, while ‘U’ stands for *Unused*.

where:

$$\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \equiv \frac{\partial \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{p}^I}{\partial \boldsymbol{\xi}_I^G} \quad (24)$$

$$\mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \equiv \frac{\partial \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)}{\partial \boldsymbol{\xi}_I^G} \quad (25)$$

$$\mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \equiv \frac{\partial \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)}{\partial \boldsymbol{\xi}_C^I} \quad (26)$$

Continuing, the first-order Lie derivatives of \mathbf{h}_1 and \mathbf{h}_2 with respect to \mathbf{f}_0 are:

$$L_{\mathbf{f}_0}^1 \mathbf{h}_1 = \nabla L^0 \mathbf{h}_1 \cdot \mathbf{f}_0 = \mathbf{v}^G - \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \mathbf{b}_g \quad (27)$$

$$L_{\mathbf{f}_0}^1 \mathbf{h}_2 = \nabla L^0 \mathbf{h}_2 \cdot \mathbf{f}_0 = -\mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \mathbf{b}_g \quad (28)$$

The gradients are:

$$\nabla L_{\mathbf{f}_0}^1 \mathbf{h}_1 = [\mathbf{0}_{3 \times 3} \quad \mathbf{U}_1(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I) \quad \mathbf{I}_{3 \times 3} \quad \mathbf{U}_2(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{0}_{3 \times 3} \quad \mathbf{U}_3(\boldsymbol{\xi}_I^G, \mathbf{b}_g) \quad \mathbf{0}_{3 \times 3} \quad \mathbf{0}_{3 \times 3}] \quad (29)$$

$$\nabla L_{\mathbf{f}_0}^1 \mathbf{h}_2 = [\mathbf{0}_{9 \times 3} \quad \mathbf{U}_4(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \boldsymbol{\xi}_C^I) \quad \mathbf{0}_{9 \times 3} \quad -\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{U}_5(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \boldsymbol{\xi}_C^I) \quad \mathbf{0}_{9 \times 3}] \quad (30)$$

where:

$$\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) = \mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \quad (31)$$

The Lie derivatives above are computed with respect to \mathbf{f}_0 , which is a single column vector. We now consider the Lie derivatives of the measurement functions with respect to \mathbf{f}_1 , which is the product of a 24×3 matrix and a 3×1 vector $\boldsymbol{\omega}_m = [\omega_x \quad \omega_y \quad \omega_z]^T$ of control inputs. Note that each column of the 24×3 matrix will be multiplied by one element of $\boldsymbol{\omega}_m$; we can therefore compute the Lie derivative separately for each column, and stack the resulting gradients. The first-order Lie derivative of \mathbf{h}_1 with respect to \mathbf{f}_1 is:

$$\begin{aligned} L_{\mathbf{f}_1}^1 \mathbf{h}_1 &= \nabla L^0 \mathbf{h}_1 \cdot \mathbf{f}_1 = \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \\ &= [L_{\mathbf{f}_{1,1}}^1 \mathbf{h}_1 \quad L_{\mathbf{f}_{1,2}}^1 \mathbf{h}_1 \quad L_{\mathbf{f}_{1,3}}^1 \mathbf{h}_1] \end{aligned} \quad (32)$$

which is a 3×3 matrix. Computing the gradients of the individual Lie derivatives, we obtain:

$$\nabla L_{\mathbf{f}_1}^1 \mathbf{h}_1 = \begin{bmatrix} \nabla L_{\mathbf{f}_{1,1}}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_{1,2}}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_{1,3}}^1 \mathbf{h}_1 \end{bmatrix} = [\mathbf{0}_{9 \times 3} \quad \mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{D}_6(\boldsymbol{\xi}_I^G) \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3}] \quad (33)$$

where $\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I)$ and $\mathbf{D}_6(\boldsymbol{\xi}_I^G)$ are formed from the stacked partial derivatives of the columns of $\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)$:

$$\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \equiv \frac{\partial [\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)]}{\partial \boldsymbol{\xi}_I^G}, \quad \mathbf{D}_6(\boldsymbol{\xi}_I^G) \equiv \frac{\partial [\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)]}{\partial \mathbf{p}^I} \quad (34)$$

We also require the second-order Lie derivative of \mathbf{h}_1 with respect to \mathbf{f}_0 :

$$L_{\mathbf{f}_0}^2 \mathbf{h}_1 = \nabla L_{\mathbf{f}_0}^1 \mathbf{h}_1 \cdot \mathbf{f}_0 = -\mathbf{U}_1(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \mathbf{b}_g - \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{b}_a + \mathbf{g}^G \quad (35)$$

The gradient is:

$$\nabla L_{\mathbf{f}_0}^2 \mathbf{h}_1 = \begin{bmatrix} \mathbf{0}_{3 \times 3} & \mathbf{U}_6(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I) - \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) & \mathbf{0}_{3 \times 3} & \mathbf{U}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I) \dots \\ & & & -\mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{U}_8(\boldsymbol{\xi}_I^G, \mathbf{b}_g) & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} \end{bmatrix} \quad (36)$$

where:

$$\mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \equiv \frac{\partial \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{b}_a}{\partial \boldsymbol{\xi}_I^G} \quad (37)$$

Finally, we require a third-order Lie derivative – the second-order Lie derivative of \mathbf{h}_1 with respect \mathbf{f}_0 , taken with respect to \mathbf{f}_1 :

$$\begin{aligned} L_{\mathbf{f}_1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 &= \nabla L_{\mathbf{f}_0}^2 \mathbf{h}_1 \cdot \mathbf{f}_1 = \mathbf{U}_6(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) - \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \\ &= [L_{\mathbf{f}_{1,1}}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \quad L_{\mathbf{f}_{1,2}}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \quad L_{\mathbf{f}_{1,3}}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1] \end{aligned} \quad (38)$$

which is also a 3×3 matrix, so we proceed as before and stack the gradients of the individual columns:

$$\begin{aligned} \nabla L_{\mathbf{f}_1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 &= \begin{bmatrix} \nabla L_{\mathbf{f}_{1,1}}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_{1,2}}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_{1,3}}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \end{bmatrix} \\ &= \begin{bmatrix} \mathbf{0}_{9 \times 3} & \mathbf{U}_9(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{b}_a, \mathbf{p}^I) & \mathbf{0}_{9 \times 3} & \mathbf{U}_{10}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I) \dots \\ & & & -\mathbf{D}_8(\boldsymbol{\xi}_I^G) & \mathbf{U}_{11}(\boldsymbol{\xi}_I^G, \mathbf{b}_g) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} \end{bmatrix} \end{aligned} \quad (39)$$

where $\mathbf{D}_8(\boldsymbol{\xi}_I^G)$ is formed from stacked partial derivatives of the columns of $\mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)$:

$$\mathbf{D}_8(\boldsymbol{\xi}_I^G) \equiv \frac{\partial \llbracket \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \rrbracket}{\partial \mathbf{b}_a} \quad (40)$$

We form the complete observability matrix \mathcal{O} by stacking the matrices above:

$$\mathcal{O} = \begin{bmatrix} \nabla L^0 \mathbf{h}_1 \\ \nabla L^0 \mathbf{h}_2 \\ \nabla L_{\mathbf{f}_0}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_0}^1 \mathbf{h}_2 \\ \nabla L_{\mathbf{f}_1}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_0}^2 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \end{bmatrix} = \begin{bmatrix} \mathbf{I}_{3 \times 3} & \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{U}_1 & \mathbf{I}_{3 \times 3} & \mathbf{U}_2 & \mathbf{0}_{3 \times 3} & \mathbf{U}_3 & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{U}_4 & \mathbf{0}_{9 \times 3} & -\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_5 & \mathbf{0}_{9 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_6(\boldsymbol{\xi}_I^G) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{U}_6 - \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) & \mathbf{0}_{3 \times 3} & \mathbf{U}_7 & -\mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{U}_8 & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{U}_9 & \mathbf{0}_{9 \times 3} & \mathbf{U}_{10} & \mathbf{D}_8(\boldsymbol{\xi}_I^G) & \mathbf{U}_{11} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} \end{bmatrix} \quad (41)$$

We can now state the following theorem about the rank of \mathcal{O} .

Theorem 1. The observability matrix \mathcal{O} , defined by Equation 41, has full column rank whenever $\theta_I^G \neq \{\pi/2, -\pi/2\}$ and $\theta_C^I \neq \{\pi/2, -\pi/2\}$.

Proof. We use block Gaussian elimination to show that \mathcal{O} has full column rank when $\theta_I^G \neq \{\pi/2, -\pi/2\}$ and $\theta_C^I = \{\pi/2, -\pi/2\}$. Our strategy is as follows: we prove that the matrix $[\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{D}_6(\boldsymbol{\xi}_I^G)]$ has full column rank, and use this result to eliminate the remaining nonzero entries in column blocks 2 and 6; we then prove that matrix $\mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ has full column rank, and eliminate the remaining nonzero entry in column block 7. Next, we prove that $\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ has full column rank and eliminate the remaining nonzero entries in column block 4; finally, we prove that $\mathbf{D}_8(\boldsymbol{\xi}_I^G)$ has full column rank and eliminate the last remaining nonzero entry in column block 5. The details of these steps follow below.⁴

1. By Lemma 1, the matrix $[\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{D}_6(\boldsymbol{\xi}_I^G)]$ has full column rank when $\theta_I^G \neq \{\pi/2, -\pi/2\}$. Reducing the corresponding entries in \mathcal{O} to row echelon form, we obtain:

$$\mathcal{O} = \begin{bmatrix} \mathbf{I}_{3 \times 3} & \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{U}_1 & \mathbf{I}_{3 \times 3} & \mathbf{U}_2 & \mathbf{0}_{3 \times 3} & \mathbf{U}_3 & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{U}_4 & \mathbf{0}_{9 \times 3} & -\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_5 & \mathbf{0}_{9 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{U}_6 - \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) & \mathbf{0}_{3 \times 3} & \mathbf{U}_7 & -\mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{U}_8 & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{U}_9 & \mathbf{0}_{9 \times 3} & \mathbf{U}_{10} & \mathbf{D}_8(\boldsymbol{\xi}_I^G) & \mathbf{U}_{11} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} \end{bmatrix} \quad (42)$$

We proceed to eliminate the remaining nonzero entries in column blocks 2 and 6. The result is:

$$\mathcal{O} = \begin{bmatrix} \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{U}_2 & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & -\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_5 & \mathbf{0}_{9 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{U}_7 & -\mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} \\ \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_{10} & \mathbf{D}_8(\boldsymbol{\xi}_I^G) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} \end{bmatrix} \quad (43)$$

⁴We follow the general approach described in [8] for the initial steps in the proof, suitably extended to deal with the larger observability matrix. Later steps differ from [8], because the matrix \mathcal{O} contains an additional set of rows for the third-order Lie derivative.

and eliminate the only remaining nonzero entry, $-\mathbf{C}(\boldsymbol{\xi}_I^G)$, in column block 5:

$$\mathcal{O} = \begin{bmatrix} \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} & \mathbf{0}_{6 \times 3} \end{bmatrix} \quad (49)$$

As a last step, we express \mathcal{O} in reduced row echelon form:

$$\mathcal{O} = \begin{bmatrix} \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} \\ \mathbf{0}_{21 \times 3} & \mathbf{0}_{21 \times 3} & \mathbf{0}_{21 \times 3} & \mathbf{0}_{21 \times 3} & \mathbf{0}_{21 \times 3} & \mathbf{0}_{21 \times 3} & \mathbf{0}_{21 \times 3} & \mathbf{0}_{21 \times 3} \end{bmatrix} \quad (50)$$

which shows that the matrix has full column rank whenever $\theta_I^G \neq \{\pi/2, -\pi/2\}$ and $\theta_C^I \neq \{\pi/2, -\pi/2\}$. This completes the proof.

Note that the proof did not require any Lie derivatives with respect to \mathbf{f}_2 . It is therefore possible to perform target-based calibration *without* accelerating the IMU, i.e. using rotational motion only. \square

Lemma 1. The matrix $\mathbf{A} = [\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{D}_6(\boldsymbol{\xi}_I^G)]$ has full column rank when at least two components of $\boldsymbol{\omega}_m = [\omega_x \quad \omega_y \quad \omega_z]^T$ are nonzero and $\theta_I^G \neq \{\pi/2, -\pi/2\}$.

Proof. The complete \mathbf{A} matrix is 9×6 in size, and we will show that there are always six independent rows when $\theta_I^G \neq \{\pi/2, -\pi/2\}$. We represent the individual components of $\boldsymbol{\xi}_I^G$ as $[\phi \quad \theta \quad \psi]^T$ (omitting the frame identifiers) and \mathbf{p}^I as $[p_x \quad p_y \quad p_z]^T$. From Equation 33,

the columns of $\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I)$ are:

$$\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \equiv \frac{\partial [\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)]}{\partial \boldsymbol{\xi}_I^G} = [\mathbf{D}_{5,1}(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{D}_{5,2}(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \quad \mathbf{D}_{5,3}(\boldsymbol{\xi}_I^G, \mathbf{p}^I)] \quad (51)$$

$$\mathbf{D}_{5,1}(\boldsymbol{\xi}_I^G, \mathbf{p}^I) = \begin{bmatrix} \left. \begin{array}{l} (s\psi c\phi - c\psi s\theta s\phi) p_y - (s\psi s\phi + c\psi s\theta c\phi) p_z \\ (c\psi s\phi - s\psi s\theta c\phi) p_z - (c\psi c\phi + s\psi s\theta s\phi) p_y \\ -c\theta(s\phi p_y + c\phi p_z) \end{array} \right\} \omega_x \\ \left. \begin{array}{l} (c\psi s\theta s\phi - s\psi c\phi) p_x \\ (s\psi s\theta s\phi + c\psi c\phi) p_x \\ c\theta s\phi p_x \end{array} \right\} \omega_y \\ \left. \begin{array}{l} (c\psi s\theta c\phi + s\psi s\phi) p_x \\ (s\psi s\theta c\phi - c\psi s\phi) p_x \\ c\theta c\phi p_x \end{array} \right\} \omega_z \end{bmatrix} \quad (52)$$

$$\mathbf{D}_{5,2}(\boldsymbol{\xi}_I^G, \mathbf{p}^I) = \begin{bmatrix} \left. \begin{array}{l} c\psi c\theta(c\phi p_y - s\phi p_z) \\ s\psi c\theta(c\phi p_y - s\phi p_z) \\ -s\theta(c\phi p_y - s\phi p_z) \end{array} \right\} \omega_x \\ \left. \begin{array}{l} -c\psi(c\phi c\theta p_x + s\theta p_z) \\ -s\psi(c\phi c\theta p_x + s\theta p_z) \\ c\phi s\theta p_x - c\theta p_z \end{array} \right\} \omega_y \\ \left. \begin{array}{l} c\psi(s\phi c\theta p_x + s\theta p_y) \\ s\psi(s\phi c\theta p_x + s\theta p_y) \\ -s\phi s\theta p_x + c\theta p_y \end{array} \right\} \omega_z \end{bmatrix} \quad (53)$$

$$\mathbf{D}_{5,3}(\boldsymbol{\xi}_I^G, \mathbf{p}^I) = \begin{bmatrix} \left. \begin{array}{l} (c\psi s\phi - s\psi s\theta c\phi) p_y + (c\psi c\phi + s\psi s\theta s\phi) p_z \\ (s\psi s\phi + c\psi s\theta c\phi) p_y - (s\psi c\phi + c\psi s\theta s\phi) p_z \\ 0 \end{array} \right\} \omega_x \\ \left. \begin{array}{l} (c\phi s\psi s\theta - s\phi c\psi) p_x - s\psi c\theta p_z \\ -(c\phi c\psi s\theta - s\phi s\psi) p_x + c\psi c\theta p_z \\ 0 \end{array} \right\} \omega_y \\ \left. \begin{array}{l} -(s\psi s\phi s\theta - c\phi c\psi) p_x + s\psi c\theta p_y \\ (c\psi s\phi s\theta - c\phi s\psi) p_x - c\psi c\theta p_y \\ 0 \end{array} \right\} \omega_z \end{bmatrix} \quad (54)$$

Also from Equation 33, the matrix $\mathbf{D}_6(\boldsymbol{\xi}_I^G)$ is:

$$\mathbf{D}_6(\boldsymbol{\xi}_I^G) \equiv \frac{\partial [\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)]}{\partial \mathbf{p}^I} \quad (55)$$

$$= \begin{bmatrix} 0 & c\psi s\theta c\phi + s\psi s\phi & -c\psi s\theta s\phi + s\psi c\phi \\ 0 & s\psi s\theta c\phi - c\psi s\phi & -s\psi s\theta s\phi - c\psi c\phi \\ 0 & c\theta c\phi & -c\theta s\phi \\ -c\psi s\theta c\phi - s\psi s\phi & 0 & c\psi c\theta \\ -s\psi s\theta c\phi + c\psi s\phi & 0 & s\psi c\theta \\ -c\theta c\phi & 0 & -s\theta \\ c\psi s\theta s\phi - s\psi c\phi & -c\psi c\theta & 0 \\ s\psi s\theta s\phi + c\psi c\phi & -s\psi c\theta & 0 \\ c\theta s\phi & s\theta & 0 \end{bmatrix} \begin{array}{l} \left. \begin{array}{l} \\ \\ \end{array} \right\} \omega_x \\ \left. \begin{array}{l} \\ \\ \end{array} \right\} \omega_y \\ \left. \begin{array}{l} \\ \\ \end{array} \right\} \omega_z \end{array} \quad (56)$$

where we have abbreviated ‘sine’ as ‘s’ and ‘cosine’ as ‘c’ above. The series of braces to the right of each matrix indicate which components of the control input $\boldsymbol{\omega}_m$ must be nonzero in order to use the respective rows of $\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I)$ and $\mathbf{D}_6(\boldsymbol{\xi}_I^G)$.

We make two initial remarks. First, note that if all of the components of \mathbf{p}^I are zero, then every element of $\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I)$ will be zero, and the rank of \mathbf{A} will be at most three. It is therefore immediately clear that at least one component of \mathbf{p}^I must be nonzero. Second, observe that if any two control inputs are zero, a maximum of three rows of \mathbf{A} will be nonzero, and the rank of \mathbf{A} will again be at most three. So at least two of ω_x , ω_y and ω_z must be nonzero. With these requirements in mind, we consider the series of possible cases in turn.

Case 1: One component of \mathbf{p}^I is nonzero. Without loss of generality, let this component be p_x . We can choose rows $\{1, 3, 5, 7, 8, 9\}$ and $\{2, 3, 4, 7, 8, 9\}$ of \mathbf{A} , and compute the determinants of the submatrices containing these rows:

$$|\mathbf{A}\{1, 3, 5, 7, 8, 9\}| = p_x^3 (\sin \psi)^2 (\cos \theta)^3 \quad (57)$$

$$|\mathbf{A}\{2, 3, 4, 7, 8, 9\}| = -p_x^3 (\cos \psi)^2 (\cos \theta)^3 \quad (58)$$

We prove by contradiction that these determinants cannot be zero simultaneously. Assume that Equations 57 and 58 are both equal to zero and that $p_x \neq 0$, $\cos \theta \neq 0$. If we consider Equation 57, it must be the case that $\sin \psi = 0$, or $\psi = \{0, \pi\}$. Substituting $\psi = \{0, \pi\}$ into Equation 58, we obtain, $\pm p_x^3 (\cos \theta)^3 = 0$. But this violates our initial assumption that $p_x \neq 0$, $\cos \theta \neq 0$, and we have a contradiction.⁵ Note that for either determinant to be nonzero in this case, all three control inputs ω_x , ω_y and ω_z must be nonzero. We can derive the same result when p_y or p_z is nonzero, and we do not explicitly present those cases here.

Case 2: Two or more components of \mathbf{p}^I are nonzero. We can choose rows $\{1, 2, 3, 4, 5, 6\}$, $\{1, 2, 3, 7, 8, 9\}$ and $\{4, 5, 6, 7, 8, 9\}$ of \mathbf{A} , and compute the determinants of the respective

⁵We note the following as a result of using Euler angles to parameterize orientations: for all 6×6 submatrix of \mathbf{A} , any nonzero determinant will have $\cos \theta_I^G$ as a factor. The singularities at $\theta_I^G \neq \{\pi/2, -\pi/2\}$ are therefore unavoidable.

submatrices:

$$|\mathbf{A}\{1, 2, 3, 4, 5, 6\}| = -p_z \cos \theta (p_x^2 + p_y^2) \quad (59)$$

$$|\mathbf{A}\{1, 2, 3, 7, 8, 9\}| = p_y \cos \theta (p_x^2 + p_z^2) \quad (60)$$

$$|\mathbf{A}\{4, 5, 6, 7, 8, 9\}| = -p_x \cos \theta (p_y^2 + p_z^2) \quad (61)$$

It is clear that if any two or more components of \mathbf{p}^I are nonzero, at least one of the determinants above will be nonzero, assuming the appropriate control inputs are excited and $\theta \neq \{\pi/2, -\pi/2\}$. For example, if p_x and p_y are nonzero, then Equation 61 is nonzero, assuming control inputs ω_y and ω_z are nonzero.

This completes the proof. The MATLAB script used to compute the symbolic determinants is listed in Appendix B.1. \square

Lemma 2. The matrix $\mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ has full column rank when $\theta_C^I \neq \{\pi/2, -\pi/2\}$.

Proof. The complete matrix $\mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ is 9×3 in size, and is defined as:

$$\mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) = \frac{\partial \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)}{\partial \boldsymbol{\xi}_C^I} \quad (62)$$

We will show that there are always three independent rows when $\theta_C^I \neq \{\pi/2, -\pi/2\}$. We can choose rows $\{1, 2, 4\}$, $\{1, 2, 5\}$, $\{1, 2, 6\}$, $\{1, 2, 8\}$, $\{1, 2, 9\}$ and $\{1, 3, 4\}$ of \mathbf{D}_3 , and compute the determinants of the respective submatrices. The resulting expressions are large and combine various powers of sines and cosines of the Euler angles $\boldsymbol{\xi}_I^G$ and $\boldsymbol{\xi}_C^I$ – for the sake of brevity, we do not repeat the expressions here.

We use the symbolic/numerical solver provided by MATLAB[®] to prove that the determinants cannot be zero simultaneously. The script used for the complete proof is listed in Appendix B.2. \square

Lemma 3. The matrix $\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ has full column rank when $\theta_I^G \neq \{\pi/2, -\pi/2\}$.

Proof. The complete matrix $\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ is 9×3 in size, and is defined as:

$$\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) = \left(\frac{\partial \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)}{\partial \boldsymbol{\xi}_I^G} \right) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \quad (63)$$

We will show that there are always three independent rows when $\theta_I^G \neq \{\pi/2, -\pi/2\}$. We can choose rows $\{1, 2, 4\}$, $\{1, 2, 5\}$, $\{1, 2, 6\}$, $\{1, 2, 8\}$, $\{1, 2, 9\}$ and $\{1, 3, 4\}$ of \mathbf{D}_4 , and compute the determinants of the respective submatrices. The resulting expressions are large and combine various powers of sines and cosines of the Euler angles $\boldsymbol{\xi}_I^G$ and $\boldsymbol{\xi}_C^I$ – for the sake of brevity, we do not repeat the expressions here.

We use the symbolic/numerical solver provided by MATLAB[®] to prove that the determinants cannot be zero simultaneously. The script used for the complete proof is listed in Appendix B.3. \square

Lemma 4. The matrix $\mathbf{D}_s(\boldsymbol{\xi}_I^G)$ has full column rank when at least two components of $\boldsymbol{\omega}_m = [\omega_x \ \omega_y \ \omega_z]^T$ are nonzero.

Proof. Comparing Equation 33 and Equation 39, we note that matrices $\mathbf{D}_6(\boldsymbol{\xi}_I^G)$ and $\mathbf{D}_s(\boldsymbol{\xi}_I^G)$ are, in fact, identical. It follows immediately from Lemma 1 that $\mathbf{D}_s(\boldsymbol{\xi}_I^G)$ has full column rank when $\theta_I^G \neq \{\pi/2, -\pi/2\}$. We now show that $\mathbf{D}_s(\boldsymbol{\xi}_I^G)$ has full column rank in general.

$$\mathbf{D}_s(\boldsymbol{\xi}_I^G) \equiv \frac{\partial \llbracket \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \Gamma(\boldsymbol{\xi}_I^G) \rrbracket}{\partial \mathbf{b}_a} \quad (64)$$

$$= \begin{bmatrix} 0 & c\psi s\theta c\phi + s\psi s\phi & -c\psi s\theta s\phi + s\psi c\phi \\ 0 & s\psi s\theta c\phi - c\psi s\phi & -s\psi s\theta s\phi - c\psi c\phi \\ 0 & c\theta c\phi & -c\theta s\phi \\ -c\psi s\theta c\phi - s\psi s\phi & 0 & c\psi c\theta \\ -s\psi s\theta c\phi + c\psi s\phi & 0 & s\psi c\theta \\ -c\theta c\phi & 0 & -s\theta \\ c\psi s\theta s\phi - s\psi c\phi & -c\psi c\theta & 0 \\ s\psi s\theta s\phi + c\psi c\phi & -s\psi c\theta & 0 \\ c\theta s\phi & s\theta & 0 \end{bmatrix} \begin{array}{l} \left. \vphantom{\begin{matrix} 0 \\ 0 \\ 0 \end{matrix}} \right\} \omega_x \\ \left. \vphantom{\begin{matrix} -c\psi s\theta c\phi - s\psi s\phi \\ -s\psi s\theta c\phi + c\psi s\phi \\ -c\theta c\phi \end{matrix}} \right\} \omega_y \\ \left. \vphantom{\begin{matrix} c\psi s\theta s\phi - s\psi c\phi \\ s\psi s\theta s\phi + c\psi c\phi \\ c\theta s\phi \end{matrix}} \right\} \omega_z \end{array} \quad (65)$$

where we have abbreviated ‘sine’ as ‘s’ and ‘cosine’ as ‘c’ above. The series of braces to the right of each matrix indicate which components of the control input $\boldsymbol{\omega}_m$ must be nonzero in order to use the respective rows of $\mathbf{D}_s(\boldsymbol{\xi}_I^G)$.

Observe that if any two control inputs are zero, one entire column of \mathbf{D}_s will be zero and the matrix will be rank deficient. So at most one of ω_x , ω_y or ω_z may be zero. Without loss of generality, let control ω_z be zero; we can derive the same result when ω_x or ω_y is zero, and we do not explicitly present these cases here. We can choose rows $\{1, 2, 4\}$, $\{1, 2, 5\}$, $\{1, 3, 4\}$, $\{2, 4, 5\}$, $\{1, 3, 6\}$ and $\{2, 3, 6\}$ of \mathbf{D}_s , and compute the determinants of the respective submatrices:

$$|\mathbf{D}_s\{1, 2, 4\}| = (\cos \psi \sin \theta \cos \phi + \sin \psi \sin \phi) \sin \theta \quad (66)$$

$$|\mathbf{D}_s\{1, 2, 5\}| = (\sin \psi \sin \theta \cos \phi - \cos \psi \sin \phi) \sin \theta \quad (67)$$

$$|\mathbf{D}_s\{1, 3, 4\}| = (\cos \psi \sin \theta \cos \phi + \sin \psi \sin \phi) \sin \psi \cos \theta \quad (68)$$

$$|\mathbf{D}_s\{2, 4, 5\}| = (\sin \psi \sin \theta \cos \phi - \cos \psi \sin \phi) \cos \theta \sin \phi \quad (69)$$

$$|\mathbf{D}_s\{1, 3, 6\}| = \sin \psi (\cos \theta)^2 \cos \phi \quad (70)$$

$$|\mathbf{D}_s\{2, 3, 6\}| = -\cos \psi (\cos \theta)^2 \cos \phi \quad (71)$$

We prove by contradiction that these determinants cannot be zero simultaneously. Assume that the six equations above are all equal to zero. Then, from Equation 71, one or more of $\cos \psi$, $\cos \theta$ and $\cos \phi$ must be zero. We handle each possible case in turn.

Case 1: Assume that $\cos \psi$, $\cos \theta$ and $\cos \phi$ are all equal to zero. Substituting these values into Equation 66 we obtain:

$$\sin \psi \sin \theta \sin \phi = 0 \quad (72)$$

But $\sin \psi$, $\sin \theta$ and $\sin \phi$ must each be equal to ± 1 , so the above equation cannot hold, and we have a contradiction.

Case 2: Assume that $\cos \psi$ and $\cos \theta$ are equal to zero, and that $\cos \phi$ is nonzero. If we substitute these values into Equation 67 we obtain:

$$\sin \psi (\sin \theta)^2 \cos \phi = 0 \quad (73)$$

But $\sin \psi$ and $\sin \theta$ must each be equal to ± 1 , so the above equation violates our initial assumption that $\cos \phi \neq 0$, and we have a contradiction.

Case 3: Assume that $\cos \psi$ and $\cos \phi$ are equal to zero, and that $\cos \theta$ is nonzero. Substituting these values into Equation 68 we obtain:

$$(\sin \psi)^2 \cos \theta \sin \phi = 0 \quad (74)$$

But $\sin \psi$ and $\sin \phi$ must each be equal to ± 1 , so the above equation violates our initial assumption that $\cos \theta \neq 0$, and we have a contradiction.

Case 4: Assume that $\cos \theta$ and $\cos \phi$ are equal to zero, and that $\cos \psi$ is nonzero. Substituting these values into Equation 67 we obtain:

$$-\cos \psi \sin \theta \sin \phi = 0 \quad (75)$$

But $\sin \theta$ and $\sin \phi$ must each be equal to ± 1 , so the above equation violates our initial assumption that $\cos \psi \neq 0$, and we have a contradiction.

Case 5: Assume that $\cos \psi$ is equal to zero, and that $\cos \theta$ and $\cos \phi$ are nonzero. From Equation 70 we have:

$$\sin \psi (\cos \theta)^2 \cos \phi = 0 \quad (76)$$

But $\sin \psi$ must be equal to ± 1 , so the above equation violates our initial assumptions that $\cos \theta \neq 0$, $\cos \phi \neq 0$, and we have a contradiction.

Case 6: Assume that $\cos \theta$ is equal to zero, and that $\cos \psi$ and $\cos \phi$ are nonzero. It follows immediately that $\sin \theta = \pm 1$. Assuming $\sin \theta = 1$, and substituting these values into Equations 66 and 66, we obtain, respectively:

$$\cos \psi \cos \phi + \sin \psi \sin \phi = 0 \quad (77)$$

$$\sin \psi \cos \phi - \cos \psi \sin \phi = 0 \quad (78)$$

Given our assumption that $\cos \psi$ and $\cos \phi$ are nonzero, Equation 77 can only be zero if:

$$\cos \psi \cos \phi = -\sin \psi \sin \phi, \quad \text{or} \quad \sin \phi = -\cos \psi \cos \phi / \sin \psi \quad (79)$$

Substituting the result above into Equation 78, we obtain:

$$\sin \psi \cos \phi + (\cos \psi)^2 \cos \phi / \sin \psi = 0 \quad (80)$$

$$\sin \psi + (\cos \psi)^2 / \sin \psi = 0 \quad (81)$$

$$(\sin \psi)^2 + (\cos \psi)^2 = 0 \quad (82)$$

But $(\sin \psi)^2 + (\cos \psi)^2 = 1$ by definition, so the above equation violates our initial assumptions that $\cos \psi \neq 0$, $\cos \phi \neq 0$ and $\sin \theta = 1$, and we have a contradiction. The same result also holds for $\sin \theta = -1$

Case 7: Assume that $\cos \phi$ is equal to zero, and that $\cos \psi$ and $\cos \theta$ are nonzero. Substituting these values into Equation 69 we obtain:

$$-\cos \psi \cos \theta (\sin \phi)^2 = 0 \tag{83}$$

But $\sin \phi$ must be equal to ± 1 , so the above equation violates our initial assumption that $\cos \psi \neq 0$ and $\cos \theta \neq 0$, and we have a contradiction.

This completes the proof. The MATLAB script used to compute the symbolic determinants is listed in Appendix B.4. □

Part II

Target-Free Calibration

6 Introduction: Target-Free Calibration

We now consider the more complicated task of calibrating the relative transform between a single camera and an IMU when a known calibration target is *not* available (a situation we call *target-free calibration*). In this case, we can select a set of salient point features in one or more camera images, and use this set as a (static) reference for calibration. However, the 3-D positions of the world points corresponding to the image features will initially be unknown; these positions must therefore *also* be estimated along with the calibration parameters.

The problem of estimating both camera motion and scene structure has been extensively studied in computer vision (as monocular structure from motion (SFM)) and in robotics (as monocular simultaneous localization and mapping (SLAM)). Work by Chiuso et al. [10] has shown that monocular SFM is observable *up to an unknown similarity transform* from image measurements alone. If we select the initial (first) camera position as the origin of our global frame, and the initial camera orientation (relative to three or more world points) as the identity matrix, then, following [10, 11], scene structure is observable up to an unknown scale. Based on this result, we can modify our target-based calibration model for target-free calibration by introducing a *scale factor*, α , in the position observation function.

An additional difficulty in online monocular SFM is *scale drift*, which is induced by changes to the set of reference points used to estimate camera motion [10]. This problem can be avoided by employing stereo cameras, where the constant scale factor is defined by the stereo baseline (Zhang et al. [12], for example, gives an algorithm for stereo self-calibration up to scale). For the case of monocular camera-IMU calibration in particular, it is desirable to use the same set of image features (and world points) throughout the procedure.

We make a final comment regarding the pitch singularities that exist due to use of the Euler angles in the state vector. To avoid the singular orientations, the camera must not pitch up or down by 90 degrees relative to the initial reference points which define the global frame. This is not a significant issue, however, since it is important to keep (approximately) the same set of image features in the camera’s field of view at all times (see above).

7 System Modeling

We define the (expanded) 25×1 state vector for the continuous time system model as:

$$\mathbf{x}(t) = [(\mathbf{p}^G(t))^T \ (\boldsymbol{\xi}_t^G(t))^T \ (\mathbf{v}^G(t))^T \ (\mathbf{b}_g(t))^T \ (\mathbf{b}_a(t))^T \ (\mathbf{p}^I)^T \ (\boldsymbol{\xi}_c^I)^T \ (\mathbf{g}^G)^T \ \alpha]^T \quad (84)$$

where the first 24 states are identical to those described in Part I, Section 4, and the final state, α , is the *scale factor* used in the observation model.

7.1 Process Model

The process model used for the target-free case is essentially the same as the target-based model. We assume that the scene scale does not vary with time, i.e. that the time derivative of the expectation of the scale factor is zero. This is a reasonable choice for calibration, because the camera will usually move in a limited area where the same features are visible

at all times. Following Section 4.1, the expectations of the state propagation equations are:

$$\dot{\hat{\mathbf{p}}}^G = \hat{\mathbf{v}}^G \quad \dot{\hat{\boldsymbol{\xi}}}_I^G = \boldsymbol{\Gamma}(\hat{\boldsymbol{\xi}}_I^G) (\boldsymbol{\omega}_m - \hat{\mathbf{b}}_g) \quad \dot{\hat{\mathbf{v}}}^G = \mathbf{C}(\hat{\boldsymbol{\xi}}_I^G) (\mathbf{a}_m - \hat{\mathbf{b}}_a) + \hat{\mathbf{g}}^G \quad (85)$$

$$\dot{\hat{\mathbf{b}}}_g = \mathbf{0}_{3 \times 1} \quad \dot{\hat{\mathbf{b}}}_a = \mathbf{0}_{3 \times 1} \quad \dot{\hat{\mathbf{g}}}^G = \mathbf{0}_{3 \times 1} \quad (86)$$

$$\dot{\hat{\mathbf{p}}}^I = \mathbf{0}_{3 \times 1} \quad \dot{\hat{\boldsymbol{\xi}}}_C^I = \mathbf{0}_{3 \times 1} \quad \dot{\hat{\alpha}} = 0 \quad (87)$$

The system process model can be described by the matrix differential equation:

$$\dot{\mathbf{x}} = \begin{bmatrix} \dot{\mathbf{p}}^G \\ \dot{\boldsymbol{\xi}}_I^G \\ \dot{\mathbf{v}}^G \\ \dot{\mathbf{b}}_g \\ \dot{\mathbf{b}}_a \\ \dot{\mathbf{p}}^I \\ \dot{\boldsymbol{\xi}}_C^I \\ \dot{\mathbf{g}}^G \\ \dot{\alpha} \end{bmatrix} = \begin{bmatrix} \mathbf{v}^G \\ -\boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \mathbf{b}_g \\ \mathbf{g}^G - \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{b}_a \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{1 \times 1} \end{bmatrix} + \begin{bmatrix} \mathbf{0}_{3 \times 3} \\ \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{1 \times 1} \end{bmatrix} \boldsymbol{\omega}_m + \begin{bmatrix} \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{C}(\boldsymbol{\xi}_I^G) \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{3 \times 3} \\ \mathbf{0}_{1 \times 1} \end{bmatrix} \mathbf{a}_m \quad (88)$$

7.2 Observation Model

Given the assumptions that the initial camera position and orientation are $\mathbf{0}_{3 \times 3}$ and $\mathbf{I}_{3 \times 3}$ respectively, monocular structure from motion is able provide the metric camera pose up to an unknown scale. We therefore modify the first observation function, \mathbf{h}_1 , to include this scale factor, while leaving the second function, \mathbf{h}_2 , unchanged:

$$\mathbf{h}_1 = \alpha (\mathbf{p}^G + \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{p}^I) \quad (89)$$

$$\mathbf{h}_2 = \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \quad (90)$$

8 Observability Analysis

We now show that the nonlinear system described by Equation 88 is observable, given measurements defined by Equations 89 and 90. We must again prove that the matrix formed from the gradients of the Lie derivatives of the measurement functions has full column rank. We begin as before by defining the zero-order Lie derivatives, which are the measurement functions themselves:

$$L^0 \mathbf{h}_1 = \alpha (\mathbf{p}^G + \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{p}^I) \quad (91)$$

$$L^0 \mathbf{h}_2 = \boldsymbol{\Lambda}(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \quad (92)$$

The gradients are:

$$\nabla L^0 \mathbf{h}_1 = \begin{bmatrix} \alpha \mathbf{I}_{3 \times 3} & \alpha \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \dots \\ & & \mathbf{0}_{3 \times 3} & \alpha \mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{U}_1(\mathbf{p}^G, \boldsymbol{\xi}_I^G, \mathbf{p}^I) \end{bmatrix} \quad (93)$$

$$\nabla L^0 \mathbf{h}_2 = \begin{bmatrix} \mathbf{0}_{9 \times 3} & \mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \end{bmatrix} \quad (94)$$

where $\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I)$, $\mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ and $\mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ are the same matrices that we defined in Section 5.⁶ Continuing, the first-order Lie derivatives of \mathbf{h}_1 and \mathbf{h}_2 with respect to \mathbf{f}_0 are:

$$L_{\mathbf{f}_0}^1 \mathbf{h}_1 = \nabla L^0 \mathbf{h}_1 \cdot \mathbf{f}_0 = \alpha \mathbf{v}^G - \alpha \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \Gamma(\boldsymbol{\xi}_I^G) \mathbf{b}_g \quad (95)$$

$$L_{\mathbf{f}_0}^1 \mathbf{h}_2 = \nabla L^0 \mathbf{h}_2 \cdot \mathbf{f}_0 = -\mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) \Gamma(\boldsymbol{\xi}_I^G) \mathbf{b}_g \quad (96)$$

The gradients are:

$$\nabla L_{\mathbf{f}_0}^1 \mathbf{h}_1 = \begin{bmatrix} \mathbf{0}_{3 \times 3} & \mathbf{U}_2(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I, \alpha) & \alpha \mathbf{I}_{3 \times 3} & \mathbf{U}_3(\boldsymbol{\xi}_I^G, \mathbf{p}^I, \alpha) & \dots \\ & & \mathbf{0}_{3 \times 3} & \mathbf{U}_4(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \alpha) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{U}_5(\boldsymbol{\xi}_I^G, \mathbf{v}^G, \mathbf{b}_g, \mathbf{p}^I) \end{bmatrix} \quad (97)$$

$$\nabla L_{\mathbf{f}_0}^1 \mathbf{h}_2 = \begin{bmatrix} \mathbf{0}_{9 \times 3} & \mathbf{U}_6(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & -\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \dots \\ & & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \end{bmatrix} \quad (98)$$

The Lie derivatives above are computed with respect to \mathbf{f}_0 , which is a single column vector. We now consider the Lie derivatives with respect to \mathbf{f}_1 and \mathbf{f}_2 ; we will stack the gradients of the individual columns of the resulting matrices. The first-order Lie derivative of \mathbf{h}_1 with respect to \mathbf{f}_1 is:

$$\begin{aligned} L_{\mathbf{f}_1}^1 \mathbf{h}_1 &= \nabla L^0 \mathbf{h}_1 \cdot \mathbf{f}_1 = \alpha \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \Gamma(\boldsymbol{\xi}_I^G) \\ &= [L_{\mathbf{f}_{1,1}}^1 \mathbf{h}_1 \quad L_{\mathbf{f}_{1,2}}^1 \mathbf{h}_1 \quad L_{\mathbf{f}_{1,3}}^1 \mathbf{h}_1] \end{aligned} \quad (99)$$

which is a 3×3 matrix. Computing the gradients of the individual Lie derivatives, we obtain:

$$\begin{aligned} \nabla L_{\mathbf{f}_1}^1 \mathbf{h}_1 &= \begin{bmatrix} \nabla L_{\mathbf{f}_{1,1}}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_{1,2}}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_{1,3}}^1 \mathbf{h}_1 \end{bmatrix} \\ &= \begin{bmatrix} \mathbf{0}_{9 \times 3} & \alpha \mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \dots \\ & & \mathbf{0}_{9 \times 3} & \alpha \mathbf{D}_6(\boldsymbol{\xi}_I^G) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_8(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \end{bmatrix} \end{aligned} \quad (100)$$

where $\mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I)$ and $\mathbf{D}_6(\boldsymbol{\xi}_I^G)$ are formed from the stacked partial derivatives of the columns of $\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \Gamma(\boldsymbol{\xi}_I^G)$ with respect to $\boldsymbol{\xi}_I^G$ and \mathbf{p}^I . We also require the second-order Lie derivative of \mathbf{h}_1 with respect to \mathbf{f}_0 :

$$L_{\mathbf{f}_0}^2 \mathbf{h}_1 = \nabla L_{\mathbf{f}_0}^1 \mathbf{h}_1 \cdot \mathbf{f}_0 = -\mathbf{U}_2(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I, \alpha) \Gamma(\boldsymbol{\xi}_I^G) \mathbf{b}_g - \alpha \mathbf{C}(\boldsymbol{\xi}_I^G) \mathbf{b}_a + \alpha \mathbf{g}^G \quad (101)$$

⁶In this section, matrices $\mathbf{D}_i, i = 1 \dots 8$, are the same matrices that we defined in Section 5.

The gradient is:

$$\begin{aligned} \nabla L_{\mathbf{f}_0}^2 \mathbf{h}_1 = & \left[\mathbf{0}_{3 \times 3} \quad \mathbf{U}_9(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I, \alpha) - \alpha \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \quad \mathbf{0}_{3 \times 3} \quad \mathbf{U}_{10}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I, \alpha) \dots \right. \\ & \left. - \alpha \mathbf{C}(\boldsymbol{\xi}_I^G) \quad \mathbf{U}_{11}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \alpha) \quad \mathbf{0}_{3 \times 3} \quad \alpha \mathbf{I}_{3 \times 3} \quad \mathbf{U}_{12}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{b}_a, \mathbf{p}^I, \mathbf{g}^G) \right] \end{aligned} \quad (102)$$

Next, we require a third-order Lie derivative – the second-order Lie derivative of \mathbf{h}_1 with respect to \mathbf{f}_0 , taken with respect to \mathbf{f}_1 :

$$\begin{aligned} L_{\mathbf{f}_1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 = & \nabla L_{\mathbf{f}_0}^2 \mathbf{h}_1 \cdot \mathbf{f}_1 = \mathbf{U}_9(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I, \alpha) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) - \alpha \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G) \\ = & \left[L_{\mathbf{f}_1,1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \quad L_{\mathbf{f}_1,2}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \quad L_{\mathbf{f}_1,3}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \right] \end{aligned} \quad (103)$$

which is also a 3×3 matrix, so we proceed as before and stack the gradients of the individual columns:

$$\begin{aligned} \nabla L_{\mathbf{f}_1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 = & \begin{bmatrix} \nabla L_{\mathbf{f}_1,1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_1,2}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_1,3}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \end{bmatrix} \\ = & \left[\mathbf{0}_{9 \times 3} \quad \mathbf{U}_{13}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{b}_a, \mathbf{p}^I, \alpha) \quad \mathbf{0}_{9 \times 3} \quad \mathbf{U}_{14}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{p}^I, \alpha) \dots \right. \\ & \left. - \alpha \mathbf{D}_8(\boldsymbol{\xi}_I^G) \quad \mathbf{U}_{15}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \alpha) \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{U}_{16}(\boldsymbol{\xi}_I^G, \mathbf{b}_g, \mathbf{b}_a, \mathbf{p}^I) \right] \end{aligned} \quad (104)$$

where $\mathbf{D}_8(\boldsymbol{\xi}_I^G)$ is formed from stacked partial derivatives of the columns of $\mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)$ with respect to \mathbf{b}_a . Finally, we take the first-order Lie derivative of \mathbf{h}_1 with respect to \mathbf{f}_2 :

$$\begin{aligned} L_{\mathbf{f}_2}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 = & \nabla L_{\mathbf{f}_0}^1 \mathbf{h}_1 \cdot \mathbf{f}_2 = \alpha \mathbf{C}(\boldsymbol{\xi}_I^G) \\ = & \left[L_{\mathbf{f}_2,1}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 \quad L_{\mathbf{f}_2,2}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 \quad L_{\mathbf{f}_2,3}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 \right] \end{aligned} \quad (105)$$

and stacking the gradients of the individual columns, we obtain:

$$\begin{aligned} \nabla L_{\mathbf{f}_2}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 = & \begin{bmatrix} \nabla L_{\mathbf{f}_2,1}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_2,2}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_2,3}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 \end{bmatrix} \\ = & \left[\mathbf{0}_{9 \times 3} \quad \mathbf{D}_9(\boldsymbol{\xi}_I^G, \alpha) \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{0}_{9 \times 3} \quad \mathbf{D}_{10}(\boldsymbol{\xi}_I^G) \right] \end{aligned} \quad (106)$$

We form the complete observability matrix \mathcal{O} by stacking the matrices above:

$$\mathcal{O} = \begin{bmatrix} \nabla L^0 \mathbf{h}_1 \\ \nabla L^0 \mathbf{h}_2 \\ \nabla L_{\mathbf{f}_0}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_0}^1 \mathbf{h}_2 \\ \nabla L_{\mathbf{f}_1}^1 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_0}^2 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_1}^1 L_{\mathbf{f}_0}^2 \mathbf{h}_1 \\ \nabla L_{\mathbf{f}_2}^1 L_{\mathbf{f}_0}^1 \mathbf{h}_1 \end{bmatrix} = \begin{bmatrix} \alpha \mathbf{I}_{3 \times 3} & \alpha \mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \alpha \mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{U}_1 \\ \mathbf{0}_{9 \times 3} & \mathbf{D}_2(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \\ \mathbf{0}_{3 \times 3} & \mathbf{U}_2 & \alpha \mathbf{I}_{3 \times 3} & \mathbf{U}_3 & \mathbf{0}_{3 \times 3} & \mathbf{U}_4 & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{U}_5 \\ \mathbf{0}_{9 \times 3} & \mathbf{U}_6 & \mathbf{0}_{9 \times 3} & -\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_7 & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \\ \mathbf{0}_{9 \times 3} & \alpha \mathbf{D}_5(\boldsymbol{\xi}_I^G, \mathbf{p}^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \alpha \mathbf{D}_6(\boldsymbol{\xi}_I^G) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_8 \\ \mathbf{0}_{3 \times 3} & \mathbf{U}_9 - \alpha \mathbf{D}_7(\boldsymbol{\xi}_I^G, \mathbf{b}_a) & \mathbf{0}_{3 \times 3} & \mathbf{U}_{10} & -\alpha \mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{U}_{11} & \mathbf{0}_{3 \times 3} & \alpha \mathbf{I}_{3 \times 3} & \mathbf{U}_{12} \\ \mathbf{0}_{9 \times 3} & \mathbf{U}_{13} & \mathbf{0}_{9 \times 3} & \mathbf{U}_{14} & -\alpha \mathbf{D}_8(\boldsymbol{\xi}_I^G) & \mathbf{U}_{15} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_{16} \\ \mathbf{0}_{9 \times 3} & \mathbf{D}_9(\boldsymbol{\xi}_I^G, \alpha) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_{10}(\boldsymbol{\xi}_I^G) \end{bmatrix} \quad (107)$$

We can now state the following theorem about the rank of \mathcal{O} .

Theorem 2. The observability matrix \mathcal{O} , defined by Equation 107, has full column rank whenever $\theta_I^G \neq \{\pi/2, -\pi/2\}$, $\theta_C^I \neq \{\pi/2, -\pi/2\}$ and $\alpha \neq 0$.

Proof. We use block Gaussian elimination to show that \mathcal{O} has full column rank whenever $\theta_I^G \neq \{\pi/2, -\pi/2\}$, $\theta_C^I \neq \{\pi/2, -\pi/2\}$ and $\alpha \neq 0$. Our (revised) strategy is as follows: we prove that the matrix $[\mathbf{D}_9(\boldsymbol{\xi}_I^G, \alpha) \quad \mathbf{D}_{10}(\boldsymbol{\xi}_I^G)]$ has full column rank, and use this result to eliminate the remaining nonzero entries in column blocks 2 and 9; we then prove that matrix $\alpha \mathbf{D}_6(\boldsymbol{\xi}_I^G)$ has full column rank, and eliminate the remaining nonzero entries in column block 6. Next, we prove that $\mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ has full column rank and eliminate the remaining nonzero entry in column block 7. In the penultimate step, we prove that $\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I)$ has full column rank and eliminate the remaining nonzero entries in column block 4. Finally, we prove that $\alpha \mathbf{D}_8(\boldsymbol{\xi}_I^G)$ has full column rank and eliminate the last remaining nonzero entry in column block 5. The details of these steps follow below.

1. By Lemma 5, matrix $[\mathbf{D}_9(\boldsymbol{\xi}_I^G, \alpha) \quad \mathbf{D}_{10}(\boldsymbol{\xi}_I^G)]$ has full column rank when $\theta_I^G \neq \{\pi/2, -\pi/2\}$ and $\alpha \neq 0$. We reduce the corresponding submatrices in \mathcal{O} to row echelon form and eliminate the remaining nonzero entries in column blocks 2 and 9 (combining these intermediate steps here for brevity):

$$\mathcal{O} = \begin{bmatrix} \alpha \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \alpha \mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{D}_3(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \alpha \mathbf{I}_{3 \times 3} & \mathbf{U}_3 & \mathbf{0}_{3 \times 3} & \mathbf{U}_4 & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & -\mathbf{D}_4(\boldsymbol{\xi}_I^G, \boldsymbol{\xi}_C^I) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_7 & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \\ \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \alpha \mathbf{D}_6(\boldsymbol{\xi}_I^G) & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \\ \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{U}_{10} & -\alpha \mathbf{C}(\boldsymbol{\xi}_I^G) & \mathbf{U}_{11} & \mathbf{0}_{3 \times 3} & \alpha \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{U}_{14} & -\alpha \mathbf{D}_8(\boldsymbol{\xi}_I^G) & \mathbf{U}_{15} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 3} & \mathbf{0}_{9 \times 1} \\ \mathbf{0}_{3 \times 3} & \mathbf{I}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 3} & \mathbf{0}_{3 \times 1} \\ \mathbf{0}_{1 \times 1} & \mathbf{0}_{1 \times 1} & \mathbf{0}_{1 \times 1} & \mathbf{0}_{1 \times 1} & \mathbf{0}_{1 \times 1} & \mathbf{0}_{1 \times 1} & \mathbf{0}_{1 \times 1} & \mathbf{0}_{1 \times 1} & \mathbf{I}_{1 \times 1} \\ \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 3} & \mathbf{0}_{5 \times 1} \end{bmatrix} \quad (108)$$

control inputs are zero, a maximum of three rows of \mathbf{B} will be nonzero, and the rank of \mathbf{B} will be at most three. So at least two of a_x , a_y and a_z must be nonzero. With this requirement in mind, we consider the series of possible cases in turn.

Case 1: If a_x is zero, we can choose rows $\{4, 5, 7, 8\}$, and compute the determinant of the submatrix containing these rows:

$$|\mathbf{A}\{4, 5, 7, 8\}| = -\alpha^3(\cos \theta)^3 \quad (120)$$

which is nonzero unless $\alpha = 0$ or $\cos \theta = 0$, i.e. $\theta = \{\pi/2, -\pi/2\}$.

Case 2: If a_y is zero, we can choose rows $\{1, 2, 3, 9\}$ and $\{1, 2, 7, 8\}$, and compute the determinants of the respective submatrices:

$$|\mathbf{A}\{1, 2, 3, 9\}| = \alpha^3(\cos \theta)^2 \sin \phi \quad (121)$$

$$|\mathbf{A}\{1, 2, 7, 8\}| = -\alpha^3 \cos \theta (1 - (\cos \theta)^2 (\sin \phi)^2) \quad (122)$$

We prove by contradiction that the determinants above cannot be zero simultaneously. Assume that Equations 121 and 122 are both equal to zero and that $\alpha \neq 0$, $\cos \theta \neq 0$. If we consider Equation 121, it must be the case that $\sin \phi = 0$. Substituting $\sin \phi = 0$ into Equation 122, we obtain, $-\alpha^3 \cos \theta = 0$. But this violates our initial assumption that $\alpha \neq 0$, $\cos \theta \neq 0$, and we have a contradiction.

Case 3: If a_z is zero, we can choose rows $\{1, 2, 3, 6\}$ and $\{1, 2, 4, 5\}$, and compute the determinants of the respective submatrices:

$$|\mathbf{A}\{1, 2, 3, 6\}| = -\alpha^3(\cos \theta)^2 \cos \phi \quad (123)$$

$$|\mathbf{A}\{1, 2, 4, 5\}| = \alpha^3 \cos \theta ((\cos \theta)^2 (\cos \phi)^2 - 1) \quad (124)$$

We prove by contradiction that the determinants above cannot be zero simultaneously. Assume that Equations 123 and 124 are both equal to zero and that $\alpha \neq 0$, $\cos \theta \neq 0$. If we consider Equation 123, it must be the case that $\cos \phi = 0$. Substituting $\cos \phi = 0$ into Equation 124, we obtain, $-\alpha^3 \cos \theta = 0$. But this violates our initial assumption that $\alpha \neq 0$, $\cos \theta \neq 0$, and we have a contradiction.

This completes the proof. The MATLAB script used to compute the symbolic determinants is listed in Appendix B.5. \square

Lemma 6. The matrix $\alpha \mathbf{D}_6(\boldsymbol{\xi}_I^G)$ has full column rank when at least two components of $\boldsymbol{\omega}_m = [\omega_x \ \omega_y \ \omega_z]^T$ are nonzero and $\alpha \neq 0$.

Proof. Following Lemma 4, we note that matrices $\mathbf{D}_6(\boldsymbol{\xi}_I^G)$ and $\mathbf{D}_8(\boldsymbol{\xi}_I^G)$ are identical. We therefore compute the same derivatives, but include the scaling factor here, and show that $\alpha \mathbf{D}_6(\boldsymbol{\xi}_I^G)$ has full column rank when $\alpha \neq 0$.

$$\alpha \mathbf{D}_6(\boldsymbol{\xi}_I^G) \equiv \alpha \frac{\partial [\mathbf{D}_1(\boldsymbol{\xi}_I^G, \mathbf{p}^I) \boldsymbol{\Gamma}(\boldsymbol{\xi}_I^G)]}{\partial \mathbf{p}^I} \quad (125)$$

If any two control inputs are zero, one entire column of \mathbf{D}_6 will be zero and the matrix will be rank deficient. So at most one of ω_x, ω_y or ω_z may be zero. Without loss of generality, let control ω_z be zero; we can derive the same result when ω_x or ω_y is zero, and we do not explicitly present those cases here. We choose rows $\{1, 2, 4\}$, $\{1, 2, 5\}$, $\{1, 3, 4\}$, $\{2, 4, 5\}$, $\{1, 3, 6\}$ and $\{2, 3, 6\}$ of \mathbf{D}_6 , and compute the determinants of the respective submatrices:

$$|\alpha \mathbf{D}_6\{1, 2, 4\}| = \alpha^3 (\cos \psi \sin \theta \cos \phi + \sin \psi \sin \phi) \sin \theta \quad (126)$$

$$|\alpha \mathbf{D}_6\{1, 2, 5\}| = \alpha^3 (\sin \psi \sin \theta \cos \phi - \cos \psi \sin \phi) \sin \theta \quad (127)$$

$$|\alpha \mathbf{D}_6\{1, 3, 4\}| = \alpha^3 (\cos \psi \sin \theta \cos \phi + \sin \psi \sin \phi) \sin \psi \cos \theta \quad (128)$$

$$|\alpha \mathbf{D}_6\{2, 4, 5\}| = \alpha^3 (\sin \psi \sin \theta \cos \phi - \cos \psi \sin \phi) \cos \theta \sin \phi \quad (129)$$

$$|\alpha \mathbf{D}_6\{1, 3, 6\}| = \alpha^3 \sin \psi (\cos \theta)^2 \cos \phi \quad (130)$$

$$|\alpha \mathbf{D}_6\{2, 3, 6\}| = -\alpha^3 \cos \psi (\cos \theta)^2 \cos \phi \quad (131)$$

The determinants above are identical to those obtained in the proof of Lemma 4, except that each is multiplied by the additional factor of α^3 . Therefore, as long as α is nonzero, Lemma 4 can be applied directly (i.e. the six determinants cannot be zero simultaneously) and $\alpha \mathbf{D}_6(\xi_I^G)$ has full column rank. This completes the proof. \square

Lemma 7. The matrix $\alpha \mathbf{D}_8(\xi_I^G)$ has full column rank when $\alpha \neq 0$.

Proof. Following Lemma 4, we let control ω_z be zero, and choose rows $\{1, 2, 4\}$, $\{1, 2, 5\}$, $\{1, 3, 4\}$, $\{2, 4, 5\}$, $\{1, 3, 6\}$ and $\{2, 3, 6\}$ of $\alpha \mathbf{D}_8(\xi_I^G)$. Computing the determinants of the respective submatrices, we obtain:

$$|\alpha \mathbf{D}_8\{1, 2, 4\}| = \alpha^3 (\cos \psi \sin \theta \cos \phi + \sin \psi \sin \phi) \sin \theta \quad (132)$$

$$|\alpha \mathbf{D}_8\{1, 2, 5\}| = \alpha^3 (\sin \psi \sin \theta \cos \phi - \cos \psi \sin \phi) \sin \theta \quad (133)$$

$$|\alpha \mathbf{D}_8\{1, 3, 4\}| = \alpha^3 (\cos \psi \sin \theta \cos \phi + \sin \psi \sin \phi) \sin \psi \cos \theta \quad (134)$$

$$|\alpha \mathbf{D}_8\{2, 4, 5\}| = \alpha^3 (\sin \psi \sin \theta \cos \phi - \cos \psi \sin \phi) \cos \theta \sin \phi \quad (135)$$

$$|\alpha \mathbf{D}_8\{1, 3, 6\}| = \alpha^3 \sin \psi (\cos \theta)^2 \cos \phi \quad (136)$$

$$|\alpha \mathbf{D}_8\{2, 3, 6\}| = -\alpha^3 \cos \psi (\cos \theta)^2 \cos \phi \quad (137)$$

The determinants above are identical to those obtained in the proof of Lemma 4, except that each is multiplied by the additional factor of α^3 . Therefore, as long as α is nonzero, Lemma 4 can be applied directly (i.e. the six determinants cannot be zero simultaneously) and $\alpha \mathbf{D}_8(\xi_I^G)$ has full column rank. This completes the proof. \square

Part III
Appendices

Appendix A The Euler Kinematical Equation

The Euler kinematical equation relates the time derivatives of the yaw ψ , pitch θ , and roll ϕ Euler angles to the body frame angular velocity vector $\boldsymbol{\omega}^B$:

$$\dot{\boldsymbol{\xi}}_B^I = \begin{bmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\psi} \end{bmatrix} = \boldsymbol{\Gamma}(\boldsymbol{\xi}_B^I) \boldsymbol{\omega}^B \quad (138)$$

where:

$$\boldsymbol{\Gamma}(\boldsymbol{\xi}_B^I) = \begin{bmatrix} 1 & \tan \theta \sin \phi & \tan \theta \cos \phi \\ 0 & \cos \phi & -\sin \phi \\ 0 & \sin \phi / \cos \theta & \cos \phi / \cos \theta \end{bmatrix} \quad (139)$$

Note that $\boldsymbol{\Gamma}(\boldsymbol{\xi}_B^I)$ is undefined at $\theta = \{\pi/2, -\pi/2\}$, because of the division by $\cos \theta$. The determinant of $\boldsymbol{\Gamma}(\boldsymbol{\xi}_B^I)$ is:

$$|\boldsymbol{\Gamma}(\boldsymbol{\xi}_B^I)| = \frac{\cos^2 \phi + \sin^2 \phi}{\cos \theta} = \frac{1}{\cos \theta} \quad (140)$$

The matrix therefore has full rank for all values of ψ , θ and ϕ except $\theta = \{\pi/2, -\pi/2\}$.

Appendix B MATLAB Code

This appendix contains a series of MATLAB[®] scripts used for the various proofs in the report. The scripts rely on the Symbolic Math Toolbox[™] to manipulate symbolic expressions.

Appendix B.1 Proof of Lemma 1

```
% Script for proof of Lemma 1.
clear;

syms rgi pgi ygi;           % Euler angles.
syms px py pz;             % Translation vector.

Cgi = rotmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 rotation matrix.
Ggi = kinmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 kinematic matrix.
pic = [px; py; pz];        % Translation vector.

% Partial (intermediate) products.
P1 = Cgi*pic;
D1 = [diff(P1, rgi), diff(P1, pgi), diff(P1, ygi)];

P2 = reshape(D1*Ggi, 9, 1);
D5 = [diff(P2, rgi), diff(P2, pgi), diff(P2, ygi)];
D6 = [diff(P2, px), diff(P2, py), diff(P2, pz)];

A = [D5, D6];

%-----

% Angular rates - comment out to
% zero specific control inputs.
wmx = []; wmx = 1:3;
wmy = []; wmy = 4:6;
wmz = []; wmz = 7:9;

% Translation - uncomment to zero
% specific components.
% px = 0;
% py = 0;
% pz = 0;

% Rows to use.
r = [wmx, wmy, wmz]';
nr = nrows(r);

A = subs(A);
```

```

% Compute determinants.
for i = 1 : nr
    for j = i + 1 : nr
        for k = j + 1 : nr
            for l = k + 1 : nr
                for m = l + 1 : nr
                    for n = m + 1 : nr
                        d = det(A([r(i), r(j), r(k), r(l), r(m), r(n)], :)));
                        [d, how] = simplify_fully(d);

                        if d ~= 0
                            disp(d);
                            disp([r(i), r(j), r(k), r(l), r(m), r(n)]);
                        end
                    end
                end
            end
        end
    end
end
end
end
end
end
end
end

```

Appendix B.2 Proof of Lemma 2

```
% Script for proof of Lemma 2.
clear;

syms rgi pgi ygi; % Euler angles.
syms ric pic yic; % Euler angles.

Cgi = rotmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 rotation matrix.
Cic = rotmat_from_eulerRPY([ric; pic; yic]); % 3x3 rotation matrix.

h2 = reshape(Cgi*Cic, 9, 1);
D3 = [diff(h2, ric), diff(h2, pic), diff(h2, yic)];

%-----

% Compute determinants.
for i = 1 : 9
    for j = i + 1 : 9
        for k = j + 1 : 9
            d = det(D3([i, j, k], :));
            [d, how] = simplify_fully(d);

            if d ~= 0
                disp(d);
                disp([i, j, k]);
            end
        end
    end
end

% Choose series of determinants.
d(1) = det(D3([1, 2, 4], :));
d(2) = det(D3([1, 2, 5], :));
d(3) = det(D3([1, 2, 6], :));
d(4) = det(D3([1, 2, 8], :));
d(5) = det(D3([1, 2, 9], :));
d(6) = det(D3([1, 3, 4], :));

% Divide by cos(pic) (known zero).
d = simplify_fully(d/cos(pic));

maple(['d1 :=', char(d(1)), '= 0;']);
maple(['d2 :=', char(d(2)), '= 0;']);
maple(['d3 :=', char(d(3)), '= 0;']);
maple(['d4 :=', char(d(4)), '= 0;']);
maple(['d5 :=', char(d(5)), '= 0;']);
maple(['d6 :=', char(d(6)), '= 0;']);
```

```
% Equations and bounds for all variables.
eqns = ['{d1, d2, d3, d4, d5, d6}'];
bnds = ['{rgi = -Pi..Pi, pgi = -Pi..Pi, ygi = -Pi..Pi,', ...
        ' ric = -Pi..Pi, pic = -Pi..Pi, yic = -Pi..Pi}'];

[sol, result] = maple('fsolve', eqns, bnds);
```

Appendix B.3 Proof of Lemma 3

```
% Script for proof of Lemma 3.
clear;

syms rgi pgi ygi; % Euler angles.
syms ric pic yic; % Euler angles.

Cgi = rotmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 rotation matrix.
Cic = rotmat_from_eulerRPY([ric; pic; yic]); % 3x3 rotation matrix.
Ggi = kinmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 kinematic matrix.

h2 = reshape(Cgi*Cic, 9, 1);
D2 = [diff(h2, rgi), diff(h2, pgi), diff(h2, ygi)];
D4 = D2*Ggi;

%-----

% Compute determinants.
for i = 1 : 9
    for j = i + 1 : 9
        for k = j + 1 : 9
            d = det(D4([i, j, k], :));
            [d, how] = simplify_fully(d);

            if d ~= 0
                disp(d);
                disp([i, j, k]);
            end
        end
    end
end
end

% Choose series of determinants.
d(1) = det(D4([1, 2, 4], :));
d(2) = det(D4([1, 2, 5], :));
d(3) = det(D4([1, 2, 6], :));
d(4) = det(D4([1, 2, 8], :));
d(5) = det(D4([1, 2, 9], :));
d(6) = det(D4([1, 3, 4], :));

% Divide by cos(pgi) (known zero).
d = simplify_fully(d/cos(pgi));

maple(['d1 :=', char(d(1)), '= 0;']);
maple(['d2 :=', char(d(2)), '= 0;']);
maple(['d3 :=', char(d(3)), '= 0;']);
maple(['d4 :=', char(d(4)), '= 0;']);
maple(['d5 :=', char(d(5)), '= 0;']);
maple(['d6 :=', char(d(6)), '= 0;']);
```

```
% Equations and bounds for all variables.
eqns = ['{d1, d2, d3, d4, d5, d6}'];
bnds = ['{rgi = -Pi..Pi, pgi = -Pi..Pi, ygi = -Pi..Pi,', ...
        ' ric = -Pi..Pi, pic = -Pi..Pi, yic = -Pi..Pi}'];

[sol, result] = maple('fsolve', eqns, bnds);
```

Appendix B.4 Proof of Lemma 4

```
% Script for proof of Lemma 4.
clear;

syms rgi pgi ygi; % Euler angles.
syms bax bay baz; % Accelerometer biases.

Cgi = rotmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 rotation matrix.
Ggi = kinmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 kinematic matrix.
ba = [bax; bay; baz]; % 3x1 biases vector.

% Partial (intermediate) products.
P1 = Cgi*ba;
P2 = [diff(P1, rgi), diff(P1, pgi), diff(P1, ygi)];
P3 = reshape(P2*Ggi, 9, 1);

D8 = [diff(P3, bax), diff(P3, bay), diff(P3, baz)];

%-----

% Angular rates - comment out to
% zero specific control inputs.
wmx = []; wmx = 1:3;
wmy = []; wmy = 4:6;
wmz = []; wmz = 7:9;

% Rows to use.
r = [wmx, wmy, wmz]';
nr = nrows(r);

% Compute determinants.
for i = 1 : nr
    for j = i + 1 : nr
        for k = j + 1 : nr
            d = det(D7([r(i), r(j), r(k)], :));
            [d, how] = simplify_fully(d);

            if d ~= 0
                disp(d);
                disp([r(i), r(j), r(k)]);
            end
        end
    end
end
end
```

Appendix B.5 Proof of Lemma 5

```
% Script for proof of Lemma 5.
clear;

syms s; % Scale factor.
syms rgi pgi ygi; % Euler angles.

Cgi = rotmat_from_eulerRPY([rgi; pgi; ygi]); % 3x3 rotation matrix.

% Partial (intermediate) products.
P1 = reshape(s*Cgi, 9, 1);
D9 = [diff(P1, rgi), diff(P1, pgi), diff(P1, ygi)];
D10 = [diff(P1, s)];

B = [D9, D10];

%-----

% Accelerations - comment out to
% zero specific control inputs.
amx = []; amx = 1:3;
amy = []; amy = 4:6;
amz = []; amz = 7:9;

% Rows to use.
r = [amx, amy, amz]';
nr = nrows(r);

% Compute determinants.
for i = 1 : nr
    for j = i + 1 : nr
        for k = j + 1 : nr
            for l = k + 1 : nr
                d = det(B([r(i), r(j), r(k), r(l)], :)));
                [d, how] = simplify_fully(d);

                if d ~= 0
                    disp(d);
                    disp([r(i), r(j), r(k), r(l)]);
                end
            end
        end
    end
end
end
```

Appendix B.6 Simplify Fully

```
function [expr, how] = simplify_fully(expr)
% SIMPLIFY_FULLY Simplify symbolic expression fully.
%
% See also SIMPLE.

how_ = {};

[expr, last] = simple(expr);

if ~isempty(last);
    how_{end + 1} = last;

    [expr, last] = simple(expr);

    if ~isempty(last)
        how_{end + 1} = last;
    end
end

if nargin == 2
    how = how_;
end
```

References

- [1] J. Kelly and G. S. Sukhatme, “Fast Relative Pose Calibration for Visual and Inertial Sensors,” in *Proceedings of the 11th IFRR International Symposium on Experimental Robotics (ISER’08)*, Athens, Greece, July 2008.
- [2] R. Hermann and A. J. Krener, “Nonlinear Controllability and Observability,” *IEEE Transactions on Automatic Control*, vol. AC-22, no. 5, pp. 728–740, October 1977.
- [3] A. B. Chatfield, *Fundamentals of High Accuracy Inertial Navigation*, ser. Progress in Astronautics and Aeronautics, P. Zarchan, Ed. American Institute of Aeronautics and Astronautics, September 1997, vol. 174.
- [4] K. R. Britting, *Inertial Navigation Systems Analysis*. John Wiley & Sons, February 1971.
- [5] G. Conte, C. H. Moog, and A. M. Perdon, *Algebraic Methods for Nonlinear Control Systems*, 2nd ed. Springer, December 2006.
- [6] S. Sastry, *Nonlinear Systems: Analysis, Stability and Control*, ser. Interdisciplinary Applied Mathematics. Springer, June 1999, vol. 10.
- [7] A. Isidori, *Nonlinear Control Systems*, 3rd ed., ser. Communications and Control Engineering. Springer, August 1995.
- [8] F. M. Mirzaei and S. I. Roumeliotis, “IMU-Camera Calibration: Observability Analysis,” University of Minnesota, Minneapolis, Minnesota, USA, Tech. Rep. TR-2007-001, August 2007.
- [9] R. Hartley and A. Zisserman, *Multiple View Geometry in Computer Vision*, 2nd ed. Cambridge: Cambridge University Press, November 2003.
- [10] A. Chiuso, P. Favaro, H. Jin, and S. Soatto, “Structure from Motion Causally Integrated Over Time,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 24, no. 4, pp. 523–535, April 2002.
- [11] E. Jones, A. Vedaldi, and S. Soatto, “Inertial Structure From Motion with Autocalibration,” in *Proceedings of the IEEE International Conference on Computer Vision Workshop on Dynamical Vision*, Rio de Janeiro, Brazil, October 2007.
- [12] Z. Zhang, Q.-T. Luong, and O. Faugeras, “Motion of an Uncalibrated Stereo Rig: Self-Calibration and Metric Reconstruction,” in *Proceedings of the 12th IAPR International Conference on Pattern Recognition (ICPR’94)*, vol. 1, October 1994, pp. 695–697.