

The Android Programming Environment

Karthik Dantu
CS 546
University of Southern California

January 26, 2009

"I've always wished that my computer would be as easy to use as my telephone. My wish has come true. I no longer know how to use my telephone. "

-Bjarne Stroustrup

Android Overview

Hello Android Application

Nuts and Bolts Of An Android Application

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ **Application Framework**

- ▶ Dalvik VM

- ▶ Integrated browser

- ▶ Optimized graphics

- ▶ SQLite

- ▶ Media support

- ▶ GSM Telephony (hw dependent)

- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)

- ▶ Camera, GPS, compass and accelerometer (hw dependent)

- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.


- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

Introduction

Software stack for mobile devices with an OS, middleware and key applications.

- ▶ Application Framework
- ▶ Dalvik VM
- ▶ Integrated browser
- ▶ Optimized graphics
- ▶ SQLite
- ▶ Media support
- ▶ GSM Telephony (hw dependent)
- ▶ Bluetooth, EDGS, 3G and Wifi (hw dependent)
- ▶ Camera, GPS, compass and accelerometer (hw dependent)
- ▶ Development environment (Emulator, debugging tools, profiling tools and eclipse integration)

System Architecture



Linux Kernel

- ▶ Enhancements
 - ▶ Alarm driver for frequent standby and wakeup functionality
 - ▶ Low Memory Killer
 - ▶ Kernel Debugger
 - ▶ Logger
 - ▶ Power management policy implementation that is much more aggressive - shutdown any component that is not explicitly required to stay on
- ▶ ARM Embedded Application Binary Interface (EABI)
- ▶ OpenBinder IPC
- ▶ Emulator works on goldfish architecture using qemu. More details on the emulator internals are [here](#)
- ▶ Details and porting instructions [here](#)

Libraries

- ▶ **System C Library**
- ▶ Media libraries: PacketVideo's OpenCORE librarie suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizerx
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Libraries

- ▶ System C Library
- ▶ Media libraries: PacketVideo's OpenCORE librarie suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizerx
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Libraries

- ▶ System C Library
- ▶ Media libraries: PacketVideo's OpenCORE librarie suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizerx
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Libraries

- ▶ System C Library
- ▶ Media libraries: PacketVideo's OpenCORE librarie suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizerx
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Libraries

- ▶ System C Library
- ▶ Media libraries: PacketVideo's OpenCORE librarie suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizerx
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Libraries

- ▶ System C Library
- ▶ Media libraries: PacketVideo's OpenCORE librarie suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizerx
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Libraries

- ▶ System C Library
- ▶ Media libraries: PacketVideo's OpenCORE librarie suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizerx
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Libraries

- ▶ System C Library
- ▶ Media libraries: PacketVideo's OpenCORE library suite that supports playback and recording of many audio/video formats, as well as static image files including MPEG4, H.264, MP3, AAC, AMR, JPG and PNG
- ▶ Surface Manager: Manage access to display subsystem and seamlessly composites 2D and 3D graphic layers from multiple applications
- ▶ Webkit - modern web browser engine which powers both android browser and an embeddable web view
- ▶ SGL - Underlying 2D graphics engine
- ▶ 3D Libraries: An implementation of OpenGL ES 1.0; Uses either hardware acceleration (where available) or the highly optimized 3D software rasterizer
- ▶ FreeType bitmap and vector font rendering
- ▶ SQLite: A powerful and relational database engine available to all applications

Dalvik Virtual Machine

- ▶ Written by Dan Bornstein - named after the fishing village of Dalvik in Eyjafjorour, Iceland where his ancestors are from
- ▶ Register-based VM as opposed to Java VMs which are stack machines
- ▶ Correspondingly uses own bytecode
- ▶ Optimized for low memory requirements - no JIT compiler
- ▶ How Google routed around Sun's IP-based licensing restrictions on Java ME
- ▶ Dalvik VM Internals

Dalvik Virtual Machine

- ▶ Written by Dan Bornstein - named after the fishing village of Dalvik in Eyjafjorour, Iceland where his ancestors are from
- ▶ Register-based VM as opposed to Java VMs which are stack machines
- ▶ Correspondingly uses own bytecode
- ▶ Optimized for low memory requirements - no JIT compiler
- ▶ How Google routed around Sun's IP-based licensing restrictions on Java ME
- ▶ Dalvik VM Internals

Dalvik Virtual Machine

- ▶ Written by Dan Bornstein - named after the fishing village of Dalvik in Eyjafjorour, Iceland where his ancestors are from
- ▶ Register-based VM as opposed to Java VMs which are stack machines
- ▶ Correspondingly uses own bytecode
- ▶ Optimized for low memory requirements - no JIT compiler
- ▶ How Google routed around Sun's IP-based licensing restrictions on Java ME
- ▶ Dalvik VM Internals

Dalvik Virtual Machine

- ▶ Written by Dan Bornstein - named after the fishing village of Dalvik in Eyjafjorour, Iceland where his ancestors are from
- ▶ Register-based VM as opposed to Java VMs which are stack machines
- ▶ Correspondingly uses own bytecode
- ▶ Optimized for low memory requirements - no JIT compiler
- ▶ How Google routed around Sun's IP-based licensing restrictions on Java ME
- ▶ Dalvik VM Internals

Dalvik Virtual Machine


- ▶ Written by Dan Bornstein - named after the fishing village of Dalvik in Eyjafjorour, Iceland where his ancestors are from
- ▶ Register-based VM as opposed to Java VMs which are stack machines
- ▶ Correspondingly uses own bytecode
- ▶ Optimized for low memory requirements - no JIT compiler
- ▶ How Google routed around Sun's IP-based licensing restrictions on Java ME
- ▶ Dalvik VM Internals

Application Framework


- ▶ Linux kernel but not linux
 - ▶ No native windowing system
 - ▶ No glibc - system/bionic C not posix compliant
 - ▶ Very few commandline utilities
- ▶
- ▶ Inside the android application framework

Create A New Android Project - I

File -> New -> Project Menu Item



Create A New Android Project - II



- ▶ **Project Name:** Name of the folder on your computer that will contain this project (under workspace)
- ▶ **Package Name:** Package namespace
- ▶ **Activity Name:** name of the class stub generated by the plugin. Extends Activity class.
- ▶ **Application Name:** Human readable title for the application

Hello, Android!

```
package com.android.hello;


import android.app.Activity;
import android.os.Bundle;
import android.widget.TextView;

public class HelloAndroid extends Activity {
    /** Called when the activity is first created. */
    @Override
    public void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);

        TextView tv = new TextView(this);
        tv.setText("Hello, Android");
        setContentView(tv);
    }
}
```

10

Hello Android - Emulator Snapshot



XML-based Layout for UI

```
<?xml version="1.0" encoding="utf-8"?>
<TextView xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="fill_parent"
    android:layout_height="fill_parent"
    android:text="Hello, Android"/>
```

```
public class HelloAndroid extends Activity {
    /** Called when the activity is first created. */
    @Override
    public void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.main);
    }
}
```

Building Blocks

- ▶ Activity
- ▶ Intent and IntentFilters
- ▶ Broadcast Intent Receiver
- ▶ Service
- ▶ Content Provider

Activity

- ▶ Usually a single screen
- ▶ Extends Activity base class
- ▶ Applications consist of multiple activities
- ▶ Moving from one screen to another causes the former screen to be paused and put on a history stack
- ▶ Each application retains its history stack

Intent and Intent Filters

- ▶ Intent describes an action to be done
- ▶ Contains the action and the data to act upon
- ▶ Data is expressed as URIs
- ▶ IntentFilters are a list of intents an application is capable of
- ▶ Navigation from screen to screen is done by resolving intents
- ▶ **Reuse:** Activities can reuse functionality from other components simply by making a request in the form of an intent
- ▶ **Replace:** Activities can be replaced by a new Activity with an equivalent IntentFilter

Intent and Intent Filters

- ▶ Intent describes an action to be done
- ▶ Contains the action and the data to act upon
- ▶ Data is expressed as URIs
- ▶ IntentFilters are a list of intents an application is capable of
- ▶ Navigation from screen to screen is done by resolving intents
- ▶ **Reuse:** Activities can reuse functionality from other components simply by making a request in the form of an intent
- ▶ **Replace:** Activities can be replaced by a new Activity with an equivalent IntentFilter

Intent and Intent Filters

- ▶ Intent describes an action to be done
- ▶ Contains the action and the data to act upon
- ▶ Data is expressed as URIs
- ▶ IntentFilters are a list of intents an application is capable of
- ▶ Navigation from screen to screen is done by resolving intents
- ▶ **Reuse:** Activities can reuse functionality from other components simply by making a request in the form of an intent
- ▶ **Replace:** Activities can be replaced by a new Activity with an equivalent IntentFilter

Intent and Intent Filters

- ▶ Intent describes an action to be done
- ▶ Contains the action and the data to act upon
- ▶ Data is expressed as URIs
- ▶ IntentFilters are a list of intents an application is capable of
 - ▶ Navigation from screen to screen is done by resolving intents
 - ▶ **Reuse:** Activities can reuse functionality from other components simply by making a request in the form of an intent
 - ▶ **Replace:** Activities can be replaced by a new Activity with an equivalent IntentFilter

Intent and Intent Filters

- ▶ Intent describes an action to be done
- ▶ Contains the action and the data to act upon
- ▶ Data is expressed as URIs
- ▶ IntentFilters are a list of intents an application is capable of
- ▶ Navigation from screen to screen is done by resolving intents
- ▶ **Reuse:** Activities can reuse functionality from other components simply by making a request in the form of an intent
- ▶ **Replace:** Activities can be replaced by a new Activity with an equivalent IntentFilter

Intent and Intent Filters

- ▶ Intent describes an action to be done
- ▶ Contains the action and the data to act upon
- ▶ Data is expressed as URIs
- ▶ IntentFilters are a list of intents an application is capable of
- ▶ Navigation from screen to screen is done by resolving intents
- ▶ **Reuse:** Activities can reuse functionality from other components simply by making a request in the form of an intent
- ▶ **Replace:** Activities can be replaced by a new Activity with an equivalent IntentFilter

Intent and Intent Filters

- ▶ Intent describes an action to be done
- ▶ Contains the action and the data to act upon
- ▶ Data is expressed as URIs
- ▶ IntentFilters are a list of intents an application is capable of
- ▶ Navigation from screen to screen is done by resolving intents
- ▶ **Reuse:** Activities can reuse functionality from other components simply by making a request in the form of an intent
- ▶ **Replace:** Activities can be replaced by a new Activity with an equivalent IntentFilter

Broadcast Intent Receiver

- ▶ Used to execute in reaction to an external event
- ▶ Application need not be running with the BroadcastReceiver is called

Service

- ▶ Long-lived and mostly runs without a UI
- ▶ Communicating with a service is done by binding to it using *Context.bindService()*
- ▶ The service can be start using *Context.startService()*

Content Provider

- ▶ Data can be stored in files, SQLite or any other form
- ▶ Derives from *ContentProvider* class and implements a shared set of methods to let other applications access and store the type of data handled by this content provider