

# Proxemics and Performance: Subjective Human Evaluations of Autonomous Sociable Robot Distance and Social Signal Understanding

Ross Mead<sup>1</sup> and Maja J Matarić<sup>2</sup>

**Abstract**—An objective of an autonomous sociable robot is to meet the needs and preferences of a human user. However, this can sometimes be at the expense of the robot’s own ability to understand *social signals* produced by the user. In particular, human preferences of distance (*proxemics*) to the robot can have significant impact on the performance rates of its automated speech and gesture recognition systems. In this work, we investigated how people perceive a sociable robot based on its performance at different locations. We performed an experiment in which a robot’s ability to understand social signals was artificially attenuated across distance; robot maximum, minimum, and average performance rates were also varied. Participants ( $N = 160$ ) instructed a robot using speech and pointing gestures, and then responded to a questionnaire to provide their subjective evaluations of the robot. We identified significant relationships between robot performance and user perceptions of robot competence, anthropomorphism, engagement, likability, and technology adoption; we identified no relationship between human-robot distance and subjective measures, which contrasts related work. Our results have significant implications for autonomous sociable robot design.

## I. INTRODUCTION AND BACKGROUND

A sociable robot utilizes natural communication mechanisms, such as speech and gesture, to autonomously interact with humans to accomplish some individual or joint task [1]. Because the majority of human-robot interaction (HRI) contexts investigated to date involve one-on-one face-to-face interaction between the robot and the human user, how the robot understands and responds to user input through natural language is crucial to autonomous sociable robots [2].

One of the most fundamental social behaviors is *proxemics*, the social use of space in face-to-face social encounters [3]. A mobile sociable robot must position itself appropriately when interacting with the user. However, robot position has a significant impact on the robot’s *performance*—in this work, performance is measured by automated speech and gesture recognition rates. Just like electrical signals, human *social signals* (e.g., speech and gesture) are *attenuated* (lose signal strength) based on distance, which dramatically changes the way in which automated recognition systems detect and identify the signal; thus, a

proxemic control system that often varies its location and, subsequently, creates signal attenuation, can be a defining factor in the success or failure of a sociable robot [4].

The anthropologist Edward T. Hall [3] coined the term “proxemics”, and, in [5], proposed that proxemics lends itself well to being analyzed with performance (as measured through sensory experience) in mind. Proxemics has been studied in a variety of ways in HRI; here, we focus our scope of related work to the context of *autonomous* HRI.

The majority of proxemics work in HRI focuses on maximizing user subjective experiences (e.g., perceived safety [6], comfort/intimacy [6], [7], [8], and likability [6], [7]) during a face-to-face interaction. The results of many human-robot proxemics studies have been consolidated and normalized in [9], reporting mean distances of 0.49–0.71 meters using a variety of robots and conditions. Proxemic preferences between humans and the PR2 robot<sup>1</sup> were investigated in [8], reporting mean distances of 0.25–0.52 meters; in [4], we investigated the same preferences using the PR2 in a conversational context, reporting a mean distance of 0.94 meters. Farther proxemic preferences of 1.0–1.1 meters and 1.7–1.8 meters were measured in [7] and [10], respectively.

However, results in our previous work [4] suggest that autonomous speech and gesture recognition systems do not perform well using previously reported proxemic configurations. Speech recognition performed adequately at distances less than 2.5 meters, and face and hand gesture recognition performed adequately at distances of 1.5–2.5 meters; thus, given current technologies, distances for mutual recognition of these social signals is between 1.5 and 2.5 meters, at and beyond previously reported proxemic preferences.

In our previous work [4], we modeled sociable robot performance attenuated by distance, which was used to implement an autonomous robot proxemic controller that maximizes its performance during face-to-face HRI. In [11], we demonstrated that users naturally adapted their proxemic behavior to compensate for poor robot performance in at a variety of interaction conditions. We now investigate how people perceive (through subjective evaluations) the robot as its performance varies in different proxemic configurations. In Section II, we describe the overall setup in which our investigation took place. In Section III, we outline our experimental procedures, conditions, and participants.

\*This work is supported in part by an NSF Graduate Research Fellowship, the NSF National Robotics Initiative (IIS-1208500), and an NSF CNS-0709296 grant.

<sup>1</sup>Ross Mead is a PhD Candidate in Computer Science, University of Southern California, Los Angeles, CA 90089, USA rossmead@usc.edu

<sup>2</sup>Maja J Matarić is a Professor of Computer Science, Neuroscience, and Pediatrics, University of Southern California, Los Angeles, CA 90089, USA mataric@usc.edu

<sup>1</sup><https://www.willowgarage.com/pages/pr2/overview>



Fig. 1. The Bandit upper-body humanoid robot.

## II. EXPERIMENTAL SETUP

### A. Materials

The experimental robotic system used in this work was the Bandit upper-body humanoid robot<sup>2</sup> [Figure 1]. Bandit has 19 degrees of freedom: 7 in each arm (shoulder forward-and-backward, shoulder in-and-out, elbow tilt, elbow twist, wrist twist, wrist tilt, grabber open-and-close; left and right arms), 2 in the head (pan and tilt), 2 in the lips (upper and lower), and 1 in the eyebrows. These degrees of freedom allow Bandit to be expressive using individual and combined motions of the head, face, and arms. Mounted atop a Pioneer 3-AT mobile base<sup>3</sup>, the entire robot system is 1.3 meters tall.

A Bluetooth PlayStation 3 (PS3) controller served as a remote control interface with the robot. The controller was used by the experimenter (seated behind a one-way mirror [Figure 2]) to step the robot through each part of the experimental procedure (described in Section III-A)—the decisions and actions taken by the robot during the experiment were completely autonomous, but the timing of its actions were controlled by the press of a “next” button. The controller was also used to record distance measurements during the experiment, and to provide ground-truth information to the robot as to what the participant was communicating (however, the robot autonomously determined how to respond based on the experimental conditions described in Section III-C).

Four small boxes were placed in the room, located at 0.75 meters and 1.5 meters from the centerline on each side (left and right) of the participant [Figure 2]. During the experiment (described in Section III-A), the participant instructed the robot to look at these boxes. Each box was labeled with a unique shape and color; in this experiment, the shapes and colors matched the buttons on the PS3 controller: a green triangle, a red circle, a blue cross, and a purple square. This allowed the experimenter to easily indicate to the robot to which box the user was attending.




Fig. 2. The experimental setup.

A laser rangefinder on-board the robot measured the distance from the robot to the front of the participant’s legs.

### B. Robot Behaviors

The robot autonomously executed three primary behaviors throughout the experiment: 1) forward and backward base movement, 2) maintaining eye contact with the participant, and 3) responding to participant instructions with head movements and audio cues.

Robot base movement was along a straight-line path directly in front of the participant, and was limited to distances of 0.25 meters (referred to as the “near home” location) and 4.75 meters (referred to as the “far home” location); it returned repeatedly to these “home” locations throughout the experiment. Robot velocity was proportional to the distance to the goal location; the maximum robot speed was 0.3 m/s, based on user preferences [12].

As the robot moved, it maintained eye contact with the participant. The robot has eyes, but they are not actuated, so the robot’s head pitched up or down depending on the location of the participant’s head, which was determined by the distance to the participant (from the on-board laser) and the participant’s self-reported height. We note that prolonged eye contact from the robot often results in user preferences of increased distance in HRI [8], [7].

The robot provided head movement and audio cues to indicate whether or not it understood instructions provided by the participant (described in Section III-B). If the robot understood the instructions, it provided an *affirmative response* (looking at a box); if the robot did not understand the instructions, it provided a *negative response* (shaking its head). With each head movement, one of two affective sounds were also played to supplement the robot’s response; affective sounds were used because robot speech is known to influence proxemic preferences and would have introduced a confound in the experiment [13].

<sup>2</sup><http://robotics.usc.edu/interaction/?l=Laboratory:Robots#BanditII>

<sup>3</sup><http://www.mobilerobots.com/ResearchRobots/P3AT.aspx>

### III. EXPERIMENTAL DESIGN

With the described experimental setup, we performed a series of experiments to investigate user perceptions of the robot when its performance varied.

#### A. Experimental Procedure

Participants (described in Section III-E) were greeted at the door entering the private experimental space, and were informed of and agreed to the nature of the experiment and their rights as a participant, which included a statement that the experiment could be halted at any time.

Participants were then instructed to stand with their toes touching a line on the floor, and were asked to remain there for the duration of the experiment [Figure 2]. The experimenter then provided instructions about the task the participant would be performing.

Participants were introduced to the robot, and were informed that all of its actions were completely autonomous. Participants were told that the robot would be moving along a straight line throughout the duration of the experiment; a brief demonstration of robot motion was provided, in which the robot autonomously moved back and forth between distances of 3.0 meters and 4.5 meters from the participant, allowing them to familiarize themselves with the robot motion. Participants were told that they would be asked about some of their preferences regarding the robot’s location throughout the experiment.

Participants were then informed that they would be instructing the robot to look at any one of four boxes (of their choosing) located in the room [Figure 2], and that they could use speech (in English) and pointing gestures. A vocabulary for robot instructions was provided: for speech, participants were told they could say the words “look at” followed by the name of the shape or color of each box (e.g., “triangle”, “circle”, “blue”, “purple”, etc.); for pointing gestures, participants were asked to use their left arm to point to boxes located on their left, and their right arm to point to boxes on their right. This vocabulary was provided to minimize any perceptions the person might have that the robot simply did not understand the words or gestures that they used; thus, the use of the vocabulary attempted to maximize the perception that any failures of the robot were due to other factors.

Participants were told that they would repeat this instruction procedure to the robot many times, and that the robot would indicate whether or not it understood their instructions each time using the head movements and audio cues described in Section II-B.

Participants had an opportunity to ask the experimenter any clarifying questions. Once participant understanding was verified, the experimenter pressed a button to return the robot to the “far home” location and start the interaction scenario.

#### B. Interaction Scenario

The robot autonomously visited ten pre-determined locations [Figure 2]. At each location, the robot responded to instructions from the participant to look at one of four boxes

located in the room [Figure 2]. Five instruction-response interactions were performed at each location, after which the robot moved to the next location along its path; thus, each participant experienced a total of 50 instruction-responses interactions. Robot goal locations were in 0.5-meter intervals inclusively between the “near home” location (0.25 meters) and “far home” location (4.75 meters) along a straight-line path in front of the participant [Figure 2]. Locations were visited in a sequential order; for half of the participants, the robot approached from the “far home” location (i.e., farthest-to-nearest order), and, for the other half of participants, the robot backed away from “near home” location (i.e., nearest-to-farthest order); this was done to reduce any ordering effects [14].

To controllably simulate social signal attenuation at each location, robot performance was artificially manipulated as a function of the distance to the participant (described in Section III-C). After each instruction provided by the participant, the experimenter provided to the robot (via a remote control interface) the ground-truth of the instruction; the robot then determined whether or not it would have understood the instruction based on a prediction from a performance vs. distance curve (based on the assigned experimental condition in Section III-C), and provided either an *affirmative response* or a *negative response* to the participant indicating its successful or failed understanding of the instruction, respectively.

The entire interaction scenario lasted 10-15 minutes.

#### C. Experimental Conditions

During each interaction scenario, robot performance  $p(x)$  was artificially varied based on distance  $x$  in a between-subjects design. Performance values for  $p(x)$  were calculated *a priori* for each interaction, and were roughly proportional to a scaled Gaussian distribution parameterized by the following values:

- 1)  $\mu_x$ , the “**maximum performance distance**”—the *mean* (center) of the distribution;
- 2)  $p_{max}$ , the “**maximum performance value**”—the *maximum* likelihood of recognizing a user instruction;
- 3)  $p_{min}$ , the “**minimum performance value**”—the *minimum* likelihood of recognizing a user instruction; and
- 4)  $p_{avg}$ , the “**average performance value**”—the average likelihood of recognizing a user instruction, indicating how many affirmative and negative responses the robot produced during the interaction (e.g., if  $p_{avg} = 0.40$ , then the robot provided 20 affirmative responses and 30 negative responses distributed across 50 instructions).

Our experiments considered and systematically manipulated three of these parameters: 1)  $\mu_x$ , 2)  $p_{max}$ , and 3)  $p_{min}$ . These manipulations influenced the fourth parameter,  $p_{avg}$ , which, in turn, impacted the way in which robot responses were distributed across locations between conditions. The performance value  $p(\mu_x)$  at  $\mu_x$  was always  $p_{max}$  (e.g., the number of affirmative responses was 5 for  $p_{max} = 1.00$ ), and the number of affirmative responses at other distances was always less than that at  $\mu_x$  to ensure that participants were exposed to an actual singular maximum performance value.

1) *Maximum Performance Distance ( $\mu_x$ )*: To explore the space of human responses to robot performance differences at a variety of distances, we varied the maximum performance distance  $\mu_x$  by selecting the eight locations non-inclusively between the “near home” and “far home” locations [Figures 2 and 3]; the “near home” and “far home” locations were not included in the set of  $\mu_x$  to ensure that participants were always exposed to an actual *peak* in performance, rather than just a *trend*. The value of  $\mu_x$  was varied between participants. The number of affirmative responses was normalized to 20 (40%) to ensure a consistent user experience of average robot performance  $p_{avg} = 0.40$  for different values of  $\mu_x$ .

2) *Maximum Performance Value ( $p_{max}$ )*: To investigate how people responded to differences in robot maximum performance, we varied  $p_{max}$  at a constant location of maximum performance,  $\mu_x = 2.25$ . This value of  $\mu_x$  was chosen for four reasons: 1) it was the near center location between all locations explored, allowing for a balance in the number of affirmative robot responses on each side of the location of maximum performance; 2) it is at a location that is *not* where people initially preferred the robot to be (in [11], we found the preferred proxemic distance to our robot to be  $M = 1.14, SD = 0.49$  meters); 3) it is at a location at which the combined performance of actual automated speech and gesture recognition are acceptable and functional (as we reported in [4]), and 4) it allows for direct comparisons to other experimental conditions varying  $\mu_x$  and  $p_{min}$ . Values of  $p_{max}$  were 0.20, 0.40, 0.60, and 0.80; for our analysis, we also considered  $p_{max} = 1.00$  at  $u_x = 2.25$  ( $p_{avg} = 0.40$ ) collected in the condition varying  $\mu_x$  (Section III-C.1). Average performance values naturally varied in this condition, with  $p_{avg} = \{0.02, 0.20, 0.30, 0.40\}$ , respectively.

3) *Minimum Performance Value ( $p_{min}$ )*: We also investigated how people responded to differences in robot minimum performance. We varied  $p_{min}$  in a similar way that we varied  $p_{max}$  (Section III-C.2), with  $\mu_x = 2.25$ . Values of  $p_{min}$  were 0.20, 0.40, 0.60, and 0.80; for our analysis, we also considered  $p_{min} = 0.00$  at  $u_x = 2.25$  ( $p_{avg} = 0.40$ ) collected in the condition varying  $\mu_x$  (Section III-C.1). Average performance values naturally varied in this condition, with  $p_{avg} = \{0.50, 0.60, 0.70, 0.82\}$ , respectively.

An overview of the values for conditions varying  $\mu_x$ ,  $p_{max}$ , and  $p_{min}$  (and subsequently  $p_{avg}$ ), as well as the corresponding distribution of affirmative responses in each condition, is presented in Figure 6. In each condition, the number of affirmative responses was normalized to a desired average robot performance value  $p_{avg}$ . At each location, the order in which the five responses were provided was random.




Fig. 3. Experimental condition varying the **maximum performance distance**,  $\mu_x = \{0.75, 1.25, 1.75, 2.25, 2.75, 3.25, 3.75, 4.25\}$  meters.




Fig. 4. Experimental condition varying the **maximum performance value**,  $p_{max} = \{0.20, 0.40, 0.60, 0.80\}$ .




Fig. 5. Experimental condition varying the **minimum performance value**,  $p_{min} = \{0.20, 0.40, 0.60, 0.80\}$ .

		Performance Parameters				Distance, $x$ (meters)									
		$\mu_x$	$p_{max}$	$p_{min}$	$p_{avg}$	0.25	0.75	1.25	1.75	2.25	2.75	3.25	3.75	4.25	4.75
Experimental Condition	Vary $\mu_x$	<b>0.75</b>	1.00	0.00	0.40	4	<b>5</b>	4	3	1	1	1	1	0	0
		<b>1.25</b>	1.00	0.00	0.40	3	4	<b>5</b>	4	3	1	0	0	0	0
		<b>1.75</b>	1.00	0.00	0.40	1	3	4	<b>5</b>	4	3	0	0	0	0
		<b>2.25</b>	1.00	0.00	0.40	0	1	3	4	<b>5</b>	4	3	0	0	0
		<b>2.75</b>	1.00	0.00	0.40	0	0	0	3	4	<b>5</b>	4	3	1	0
		<b>3.25</b>	1.00	0.00	0.40	0	0	0	0	3	4	<b>5</b>	4	3	1
		<b>3.75</b>	1.00	0.00	0.40	0	0	0	0	1	3	4	<b>5</b>	4	3
		<b>4.25</b>	1.00	0.00	0.40	0	0	1	1	1	1	3	4	<b>5</b>	4
	Vary $p_{max}$	2.25	<b>0.20</b>	0.00	<b>0.02</b>	0	0	0	0	<b>1</b>	0	0	0	0	0
		2.25	<b>0.40</b>	0.00	<b>0.20</b>	1	1	1	1	<b>2</b>	1	1	1	1	0
		2.25	<b>0.60</b>	0.00	<b>0.30</b>	1	1	2	2	<b>3</b>	2	2	1	1	0
		2.25	<b>0.80</b>	0.00	<b>0.40</b>	1	1	3	3	<b>4</b>	3	3	1	1	0
	Vary $p_{min}$	2.25	1.00	<b>0.20</b>	<b>0.50</b>	<b>1</b>	<b>1</b>	3	4	5	4	3	2	<b>1</b>	<b>1</b>
		2.25	1.00	<b>0.40</b>	<b>0.60</b>	<b>2</b>	<b>2</b>	3	4	5	4	3	3	<b>2</b>	<b>2</b>
		2.25	1.00	<b>0.60</b>	<b>0.70</b>	<b>3</b>	<b>3</b>	3	4	5	4	4	3	<b>3</b>	<b>3</b>
		2.25	1.00	<b>0.80</b>	<b>0.80</b>	<b>4</b>	<b>4</b>	4	4	5	4	4	4	<b>4</b>	<b>4</b>

Fig. 6. The distribution of affirmative responses provided by the robot across conditions; note that average performance values  $p_{avg}$  vary as well. Values manipulated in each condition are highlighted in **bold italics**.

#### D. Measures

We developed behavioral and subjective measures to determine how people responded to differences in robot maximum performance and minimum performance ( $p_{max}$  and  $p_{min}$ , respectively) at different maximum performance distances ( $\mu_x$ ), as well as differences in average performance ( $p_{avg}$ ).

1) *Behavioral Measures*: Our behavioral measures considered how people adapted their proxemic preferences to perceived differences in robot performance at different locations. Using the robot’s on-board laser rangefinder, we considered changes between pre- and post-interaction proxemic preferences. Our detailed analysis of these changes is reported in [11], which focused on these behavioral measures; in summary, we found that people predictably underestimated (based on a Power Law) the distance to the *actual* maximum performance location, but consistently adapted their proxemic preferences to be at the *perceived* maximum performance location, suggesting that people are considerate of the needs of the robot [11]. The results reported here focus on participant subjective experiences across conditions.

2) *Subjective Measures*: Our subjective measures were collected via a multi-item questionnaire following the end of the experiment, and considered participant perceptions of the robot in terms of the Godspeed questionnaire metrics [15]—animacy (9 items; Cronbach’s  $\alpha = 0.88$ ), anthropomorphism (6 items; Cronbach’s  $\alpha = 0.82$ ), competence (6 items; Cronbach’s  $\alpha = 0.84$ ), likability (6 items; Cronbach’s  $\alpha = 0.85$ ), and safety (4 items; Cronbach’s  $\alpha = 0.55$ )—as well as engagement (6 items; Cronbach’s  $\alpha = 0.76$ ), comfort (6 items; Cronbach’s  $\alpha = 0.72$ ), and technology adoption (6 items; Cronbach’s  $\alpha = 0.65$ ). Participants responded to items for each measure on a seven-point Likert scale; items were randomly ordered prior to the study to reduce effects between them, and were consistent across participants.

#### E. Participants

We recruited 160 participants (80 male, 80 female) from our university campus community. Participant race was diverse (93 white/Caucasian, 51 Asian, 7 Latino/Latina, 6 black/African-American, and 3 mixed-race). All participants reported proficiency in English and had lived in the United States for at least two years (i.e., had acclimated to U.S. culture). The average age (in years) of participants was 21.57 ( $SD = 4.27$ ), ranging from 18 to 39. Based on a seven-point scale, participants reported moderate familiarity with technology ( $M = 4.03$ ,  $SD = 0.91$ ). Average participant height (in meters) was 1.73 ( $SD = 0.13$ ), ranging from 1.50 to 1.95. Related work reports how human-robot proxemics is influenced by participant gender and technology familiarity [8], culture [16], and height [17], [18].

The 160 participants were randomly assigned to a condition, with  $N_{\mu_x} = 80$ ,  $N_{p_{max}} = 40$ , and  $N_{p_{min}} = 40$  in the conditions varying maximum performance distance ( $\mu_x$ ), maximum performance value ( $p_{max}$ ), and minimum performance value ( $p_{min}$ ), respectively. Within each condition, the participants were randomly assigned to one of the subconditions (e.g., one of the eight maximum performance distances; described in Section III-C) with  $N = 10$  for each subcondition. Neither the participant nor the experimenter was aware of the assigned condition.

#### IV. ANALYSIS AND RESULTS

We utilized bidirectional stepwise multivariate linear regression to model and analyze the relationships between participant subjective experiences of the robot (described in Section III-D.2) and the four parameters of the distribution of robot responses (i.e.,  $\mu_x$ ,  $p_{max}$ ,  $p_{min}$ , and  $p_{avg}$ ; described in Section III-C) across all conditions.

Of the eight subjective factors considered, we found significant effects for five of them—competence, anthropomorphism, engagement, likability, and technology adoption.

Figure 7 illustrates the correlation coefficient ( $\beta$ ) and statistical significance ( $p$ ) of each predictor-measure pair represented in the resulting regression models. For our analyses,  $t$ -tests determined statistical significance ( $p$ ); adjusted  $R^2$  values ( $R_A^2$ ) indicate the explanatory power of the model based on the number of predictors.

A detailed summary of our results is provided below. Implications for autonomous sociable robot behavior and interaction design are discussed in Section V.




Fig. 7. The significant relationships modeled between our predictor variables and subjective measures. The correlation coefficient ( $\beta$ ) and statistical significance ( $p$ ) for each predictor-measure pair is presented along the connecting line; note that a dotted line indicates marginal significance.

### A. Competence

Values of average performance ( $p_{avg}$ ) and minimum performance ( $p_{min}$ ) were found to be significant predictors of perceived competence ( $R_A^2 = 0.425$ ,  $\beta_0 = 1.352$ ), with ( $\beta = 2.796$ ,  $p = 0.013$ ) and ( $\beta = 1.783$ ,  $p = 0.037$ ), respectively; furthermore, maximum performance ( $p_{max}$ ) was a marginal predictor of perceived competence ( $\beta = 0.860$ ,  $p = 0.088$ ). This indicates that robot performance factors should be strongly considered when deploying a sociable robot, as the perceptions of intelligence attributed by a co-present human user will dramatically vary based on how well the robot functions. Average performance should be as high as possible, as it is the deciding factor in perceptions of intelligence. Situations in which the robot fails should be avoided, as they hinder perceived robot competence. High robot maximum performance should be a tertiary objective, as it is only marginally predictive of perceived intelligence.

### B. Anthropomorphism

Values of average performance ( $p_{avg}$ ) and minimum performance ( $p_{min}$ ) were found to be significant predictors of perceived anthropomorphism ( $R_A^2 = 0.412$ ,  $\beta_0 = 1.679$ ), with ( $\beta = 2.727$ ,  $p = 0.044$ ) and ( $\beta = 1.537$ ,  $p = 0.038$ ), respectively. This suggests that a robot that is consistently performing well at many locations will receive the greatest attributions of agency and human-likeness; furthermore, reducing the number of times in which the robot fails will further increase these attributions.

### C. Engagement

Values of average performance ( $p_{avg}$ ) and minimum performance ( $p_{min}$ ) were found to be significant predictors of participant engagement ( $R_A^2 = 0.378$ ,  $\beta_0 = 2.878$ ), with ( $\beta = 2.206$ ,  $p = 0.011$ ) and ( $\beta = 1.386$ ,  $p = 0.043$ ), respectively. Thus, for increased user engagement, the robot should perform well on average and should avoid situations in which it would likely fail (using model predictions [4]).

In situations in which the robot was consistently failing (i.e., when both average and minimum performance were low), it was clear from experimenter observations that participants were significantly less engaged than when the robot was performing better. Interestingly, our observations of participants also suggested that participants appeared bored (i.e., less engaged) when minimum performance was at the highest level explored ( $p_{min} = 0.80$ ), as the robot performed very well at every location, though participant questionnaire responses did not support this observation. Related work [19] has shown that people are more engaged by a robot that produces imperfect or unexpected behaviors (in [19], the robot cheated during a game of rock-paper-scissors), which might offer insights into our observation.

### D. Likability

Values of minimum performance ( $p_{min}$ ), maximum performance ( $p_{max}$ ), and average performance ( $p_{avg}$ ) were found to be significant predictors of perceived likability ( $R_A^2 = 0.317$ ,  $\beta_0 = 1.634$ ), with ( $\beta = 1.656$ ,  $p = 0.026$ ), ( $\beta = 1.570$ ,  $p = 0.029$ ), and ( $\beta = 1.066$ ,  $p = 0.046$ ), respectively. People do not like when the robot consistently fails—this is intuitive, but has not been well quantified in the field. Increased average performance provided some support, and could be a deciding factor in a user’s liking of the robot.

### E. Technology Adoption

Values of minimum performance ( $p_{min}$ ) and average performance ( $p_{avg}$ ) were found to be significant predictors of participant technology adoption ( $R_A^2 = 0.322$ ,  $\beta_0 = 2.397$ ), with ( $\beta = 2.257$ ,  $p = 0.049$ ) and ( $\beta = 1.707$ ,  $p = 0.033$ ), respectively. Repetitive failures can dramatically reduce the possibility of a user adopting the technology, even if the robot performs well on average. Maximum performance is therefore not the most important factor in interaction design; instead, the avoidance of failure should be the objective.



## V. DISCUSSION AND IMPLICATIONS

The results reported in Section IV offer insights into behavior and interaction design of autonomous sociable robots.

The relationship between autonomous robot performance and participant subjective experiences should be strongly considered by developers if robots are to be successfully deployed. Overall, our results suggest that average performance across multiple interactions, rather than maximum performance in a select few interactions, should be a focus of robot developers, especially when considering human perceptions of robot competence, anthropomorphism, and engagement. Furthermore, in consideration of all reported significant effects, a robot developer should have the goal of minimizing the amount of user exposure to robot failure (as indicated by the effect of minimum performance values); if the robot can predict conditions in which it will most likely fail at recognizing user input (e.g., at certain physical locations, or based on the detected sound pressure level of speech or the regions of space occupied by gestures [4]), then the robot could autonomously determine how to react in the situation. One approach is to model the automated social signal (e.g., speech and gesture) recognition rates as a function of factors such as (but not limited to) distance, orientation, and environmental interference (as illustrated in [4]); the robot could then use this model to predict its performance and, combined with accumulated performance predictions at other locations in which it interacted, estimate how its performance might impact user subjective measures. Based on such predictions and possible alternatives, the robot could then autonomously decide whether or not to a) respond to user input that it predicts it will recognize poorly, or b) execute an error avoidance strategy (e.g., moving to a better location or requesting that the user repeat the instruction).

While we identified no statistically significant relationship between the location of maximum performance ( $\mu_x$ ) and participant subjective experiences along any measure, this might be the most important result to human-robot proxemics. Previous work in human-robot proxemics predicts changes in factors such as perceived safety [6], comfort/intimacy [6], [7], [8], and likability [6], [7]; similar changes are also predicted in human-human proxemics literature [20], [21]. This could be explained by the factors that govern proxemic behavior and how people perceive them. In [5], it is suggested that human-human proxemic behavior can be represented by the auditory, visual, kinesthetic, olfactory, and thermal sensory experiences of people at different distances, and that the four proxemic zones (public, social, personal, and intimate) identified by [20] are characterized by these sensory experiences. The implication then is that if certain sensory experiences are different or absent during a face-to-face interaction between two agents (human or robot), then perceptions of factors such as comfort or intimacy could not be predicted by distance alone—in short, sensory experience, rather than distance, is the significant variable in predicting these subjective measures (as further supported by our other results reported here).

This work adds further support for our representation of proxemic behavior reported in [22], [23], which proposed that the relationship between psychological and physical factors of proxemics [7] goes through a psychophysical layer of agent sensory experience. Modeling speech and gesture production and recognition parameters within this framework [22], [23] has been the focus of much of our work: in [11], we illustrated that people naturally adapt their proxemic behavior to improve the performance of the robot; in [24], we proposed methods to dynamically adapt the robot's models to differences in human social signal production and perception; and, in [4], we presented an autonomous proxemic controller that maximizes automated recognition rates of the robot.

## VI. LIMITATIONS AND FUTURE WORK

The experimental conditions were designed to be principled, rigorous, and extensive; however, there are limitations that will be addressed in future work, as follows.

The maximum and minimum performance values were varied in isolation (e.g.,  $p_{max} = 1.00$  when  $p_{min}$  was varied); however, in the real world, these recognition rates will likely vary together and in much more complex ways [4] (e.g., if  $p_{max} = 0.80$  and  $p_{min} = 0.40$ ), which might result in interaction effects between factors. Additionally, participants were exposed to more examples of the manipulated variable when  $p_{min}$  was varied vs. when  $p_{max}$  was varied; this choice was made to highlight the behavioral outcomes we reported in [11], but might have reduced the effects of  $p_{max}$  on subjective outcomes. Thus, the results presented here simply provide evidence to the effects of robot performance on human perceptions (upon which further studies could build), and aim to serve as guidelines rather than rigid rules about subjective experience in response to variability in robot performance.

We used coarse Gaussian approximations of robot automated recognition rates as a function of distance; however, our results from [4] indicate that these distributions are by no means normal and are often multimodal (when recognition rates of multiple social signals are combined) in the real world. In future work, we will investigate how people respond to a robot using real-time automated speech and gesture recognition in the same scenario.

## VII. CONCLUSIONS

This work formally identifies relationships between automated robot performance rates (maximum, minimum, and average) and user subjective measures of autonomous sociable robot competence, anthropomorphism, engagement, likability, and technology adoption. Our results provide quantitative evidence for what has to date been intuitive/anecdotal: objective robot performance (rather than superficial factors, such as robot appearance [25] and height [17], [18]) can be a determining factor in the efficacy of autonomous sociable robots. Contrary to related work, a lack of evidence was found to support the notion that human-robot proxemics is a significant predictor of commonly investigated factors, such as user-perceived safety, comfort, and likability [6], [7], [8].

Considerations and potential approaches for developers to integrate these results into autonomous robot control systems are provided in Section V, and aim to promote rich robot autonomy in human-robot interaction.

#### ACKNOWLEDGMENTS

We thank Aditya Bhattar, Kedar Prabhu, Jonathan Frey, Cherrie Wang, Lizhi Fan, Jeanelle Guardado, Akash Metawala, Tian Zhu, Divya Sharma, and Akanxa Padhi for their assistance in recruiting participants, conducting the experiment, and annotating the data.

#### REFERENCES

- [1] C. Breazeal, *Designing Sociable Robots*. Cambridge, Massachusetts: MIT Press, 2004.
- [2] —, “Social interactions in hri: The robot view,” *IEEE Transactions on Man, Cybernetics and Systems*, vol. 34, no. 2, pp. 181–186, 2003.
- [3] E. T. Hall, *The Silent Language*. New York, New York: Doubleday Company, 1959.
- [4] R. Mead and M. J. Matarić, “Perceptual models of human-robot proxemics,” in *14th International Symposium on Experimental Robotics*, ser. ISER’14, Marrakech/Essaouira, Morocco, 2014.
- [5] E. Hall, “A system for notation of proxemic behavior,” *American Anthropologist*, vol. 65, pp. 1003–1026, 1963.
- [6] Z. Henkel, R. Murphy, and C. Bethel, “Towards a computational method of scaling a robots behavior via proxemics,” in *7th ACM/IEEE International Conference on Human-Robot Interaction*, Boston, Massachusetts, 2012, pp. 145–146.
- [7] J. Mumm and B. Mutlu, “Human-robot proxemics: Physical and psychological distancing in human-robot interaction,” in *6th ACM/IEEE International Conference on Human-Robot Interaction*, ser. HRI-2011, Lausanne, 2011, pp. 331–338.
- [8] L. Takayama and C. Pantofaru, “Influences on proxemic behaviors in human-robot interaction,” in *IEEE/RSJ International Conference on Intelligent Robots and Systems*, ser. IROS’09, 2009, pp. 5495–5502.
- [9] M. Walters, K. Dautenhahn, R. Boekhorst, K. Koay, D. Syrdal, and C. Nehaniv, “An empirical framework for human-robot proxemics,” in *New Frontiers in Human-Robot Interaction*, Edinburgh, 2009, pp. 144–149.
- [10] E. Torta, R. H. Cuijpers, and J. F. Juola, “Design of a parametric model of personal space for robotic social navigation,” *International Journal of Social Robotics*, vol. 5, no. 3, pp. 357–365, 2013.
- [11] R. Mead and M. J. Matarić, “Robots have needs too: People adapt their proxemic behavior to improve autonomous robot recognition of human social signals,” in *4th International Symposium on New Frontiers in Human-Robot Interaction*, ser. NF-HRI’15, Canterbury, United Kingdom, 2015.
- [12] S. Satake, T. Kanda, D. F. Glas, M. Imai, H. Ishiguro, and N. Hagita, “How to approach humans?: Strategies for social robots to initiate interaction,” in *HRI*, 2009, pp. 109–116.
- [13] M. Walters, D. Syrdal, K. Koay, K. Dautenhahn, and R. te Boekhorst, “Human approach distances to a mechanical-looking robot with different robot voice styles,” in *The 17th IEEE International Symposium on Robot and Human Interactive Communication*, ser. RO-MAN 2008, 2008, pp. 707–712.
- [14] A. Murata, “Basic characteristics of human’s distance estimation,” in *1999 IEEE International Conference on Systems, Man, and Cybernetics*, ser. SMC’99, vol. 2, 1999, pp. 38–43.
- [15] C. Bartneck, E. Croft, D. Kulic, and S. Zoghbi, “Measurement instruments for the anthropomorphism, animacy, likeability, perceived intelligence, and perceived safety of robots,” *International Journal of Social Robotics*, vol. 1, no. 1, pp. 71–81, 2009.
- [16] G. Eresha, M. Haring, B. Endrass, E. Andre, and M. Obaid, “Investigating the influence of culture on proxemic behaviors for humanoid robots,” in *22nd IEEE International Symposium on Robot and Human Interactive Communication*, ser. RO-MAN 2013, 2013, pp. 430–435.
- [17] Y. Hiroi and A. Ito, *Influence of the Size Factor of a Mobile Robot Moving Toward a Human on Subjective Acceptable Distance*.
- [18] I. Rae, L. Takayama, and B. Mutlu, “The influence of height in robot-mediated communication,” in *8th ACM/IEEE International Conference on Human-Robot Interaction*, ser. HRI-2013, Tokyo, Japan, 2005, pp. 1–8.
- [19] E. Short, J. Hart, M. Vu, and B. Scassellati, “No fair!! an interaction with a cheating robot,” in *5th ACM/IEEE International Conference on Human-Robot Interaction*, Osaka, Japan, 2010, pp. 219–226.
- [20] E. T. Hall, *The Hidden Dimension*. Chicago, Illinois: Doubleday Company, 1966.
- [21] M. Argyle and J. Dean, “Eye-contact, distance, and affiliation,” *Sociometry*, vol. 28, pp. 289–304, 1965.
- [22] R. Mead, A. Atrash, and M. J. Matarić, “Automated proxemic feature extraction and behavior recognition: Applications in human-robot interaction,” *International Journal of Social Robotics*, vol. 5, no. 3, pp. 367–378, 2013.
- [23] —, “Representations of proxemic behavior for human-machine interaction,” in *NordiCHI 2012 Workshop on Proxemics in Human-Computer Interaction*, ser. NordiCHI’12, Copenhagen, Denmark, 2012.
- [24] R. Mead and M. J. Matarić, “Toward robot adaptation of human speech and gesture parameters in a unified framework of proxemics and multimodal communication,” in *2015 IEEE International Conference on Robotics and Automation Workshop on Machine Learning for Social Robots*, ser. ICRA’15, Seattle, Washington, 2015.
- [25] M. Walters, “The design space for robot appearance and behaviour for social robot companions.”