

Autonomous Human-Robot Proxemics: A Robot-Centered Approach

Ross Mead
Computer Science Department
University of Southern California
Los Angeles, California 90089-0781
Email: rossmead@usc.edu

Maja J Matarić
Computer Science Department
University of Southern California
Los Angeles, California 90089-0781
Email: mataric@usc.edu

I. INTRODUCTION

In this work, we consider how an autonomous sociable robot should understand and use proxemics in human-robot interaction (HRI). *Proxemics* is the study of distance and orientation in face-to-face social encounters [1]. The goal of this project is to determine appropriate human-robot proxemics—that is, where an autonomous robot should position during a face-to-face conversational interaction with a person.

II. RELATED WORK

During a dyadic (two-person) conversation, people tend stand between 0.5 meters and 3.5 meters apart from each other [1]. Many studies in human-robot proxemics have shown that people tend to stand closer to robots than to other people—often between 0.3 meters and 1.3 meters [2], [3], [4]. At these ranges, the robot is able to automatically recognize human speech; however, the robot is unable to recognize human gestures (face and arms) because its cameras cannot see the entire upper body of the person [5]. Thus, the robot often fails during an autonomous social interaction with a human user.

III. ROBOT-CENTERED APPROACH

Our approach considers how the robot recognizes both speech and gestures in a face-to-face social interaction. The robot first samples thousands of different locations in a room. At each location, it predicts how loudly the person will speak and in what region of space the person will gesture. The robot then predicts how loudly it will hear speech through its microphones and where it will see gestures using its camera. Based on this information, the robot predicts how well it will automatically recognize speech and gestures, and assigns a score (weight) to the location based on this prediction. Finally, the robot selects the location at which it predicts it will perform the best, and moves to that location. [5]

Using our approach with contemporary audio and visual sensor technology (e.g., the Microsoft Kinect¹), the robot predicts it will work well between 1.5 meters and 2.5 meters. In this work, the robot selects 1.7 meters as the optimal location to simultaneously recognize both human speech and gestures, and moves to this location. [5]

¹<https://dev.windows.com/en-us/kinect>

The robot maintains its position while the person is moving so that it continues to perform well during mobile interactions. This approach to autonomous human-robot proxemics yields combined automated speech and gesture recognition rates that are more than twice that of other proxemics systems [5].

IV. ADAPTATION IN COMPLEX ENVIRONMENTS

If the average background noise in a room increases over time, the robot will predict that its automated recognition systems will not perform as well, and will calculate a new location at which to interact. The robot will also select the best location to see and hear the person while moving in cluttered environments, which is crucial for natural HRI. [5]

V. SUMMARY AND CONCLUSIONS

Our approach enables the robot to execute proxemic behaviors that improve speech and gesture recognition for both the robot and the human, even in noisy and cluttered environments [5]. This work has been deployed on two different mobile robot platforms: (1) the PR2², and (2) the Bandit³ upper body humanoid atop an iRobot Ava⁴ mobile base. This demonstrates the portability of the approach.

ACKNOWLEDGMENTS

This work is supported in part by an NSF Graduate Research Fellowship, the NSF National Robotics Initiative (IIS-1208500), and NSF grants CNS-0709296 and CNS-1513275.

REFERENCES

- [1] E. T. Hall, *The Hidden Dimension*. Chicago, Illinois: Doubleday Company, 1966.
- [2] M. Walters, “The design space for robot appearance and behaviour for social robot companions.”
- [3] L. Takayama and C. Pantofaru, “Influences on proxemic behaviors in human-robot interaction,” in *2009 IEEE/RSJ International Conference on Intelligent Robots and Systems*, ser. IROS’09, 2009, pp. 5495–5502.
- [4] J. Mumm and B. Mutlu, “Human-robot proxemics: Physical and psychological distancing in human-robot interaction,” in *6th ACM/IEEE International Conference on Human-Robot Interaction*, ser. HRI-2011, Lausanne, 2011, pp. 331–338.
- [5] R. Mead and M. J. Matarić, “Perceptual models of human-robot proxemics,” in *Experimental Robotics*, ser. Springer Tracts in Advanced Robotics, 2016, vol. 109, pp. 261–276.

²<https://www.willowgarage.com/pages/pr2/overview>

³<http://robotics.usc.edu/interaction/?l=Laboratory:Robots#BanditIII>

⁴<http://www.irobot.com/For-Business/Platform-Opportunities.aspx>