

Reducing Actuator Switchings for Motion Control of Autonomous Underwater Vehicles

Monique Chyba, John Marriott
Dept. of Mathematics
Univ. of Hawai'i at Mānoa, Hawai'i
{mchyba,marriott}@math.hawaii.edu

Sergio Grammatico
Dept. of Energy and Systems Eng.
Univ. of Pisa, Italy
grammatico.sergio@gmail.com

Van T. Huynh, Ryan N. Smith
Electrical Eng. and Computer Science
Queensland Univ. of Tech., Australia
{tv.huynh,ryan.smith}@qut.edu.au

Abstract—A priority when designing control strategies for autonomous underwater vehicles is to emphasize their cost of implementation on a real vehicle, and at the same time to minimize a prescribed criterion, such as time, energy, payload or some combination of these. Indeed, the major issue is that due to the vehicles' design and the actuation modes usually under consideration for underwater platforms the number of actuator switchings must be kept to a small value to ensure feasibility and precision. This constraint is typically not verified by optimal trajectories which might not even be piecewise-constant. Our goal is to provide a feasible trajectory while maintaining some qualities of the desired trajectory, such as optimality with respect to a given criterion. The one-sided Lipschitz constant is used to derive theoretical error estimates of such a control. This theory is illustrated through two examples, one is a fully actuated underwater vehicle capable of motion in six-degrees-of freedom and one is minimally actuated with control motions constrained to the vertical plane. We show in both cases that we can achieve similar localization results in the same fixed time for the trajectory, but with significantly fewer actuator switchings.

I. INTRODUCTION

Investigating the control of mechanical systems becomes increasingly interesting when one considers systems that have unique methods of actuation and locomotion with specific constraints, or are underactuated, subject to dynamic external forces. Underwater vehicles are subjected to dynamic and unpredictable external forces (e.g., ocean currents), and are propelled in many different and novel ways (e.g., biomimetic [1], energy harvesting [2] and variable buoyancy [3]). In many cases they are also underactuated (e.g., torpedo-shaped vehicles). For these reasons, control theory for autonomous underwater vehicles (AUVs) is a heavily studied area with many open questions, practical applications and interesting problems.

With ever-increasing autonomy, AUVs are becoming a fundamental research tool for studying the ocean and conducting science underwater. These vehicles facilitate simultaneous and rapid measurements that capture the appropriate scale of spatiotemporal variability for many dynamic phenomena that we seek to understand in marine ecosystems. Intelligent implementations of AUVs can provide fine-scale data resolution far surpassing existing sampling methods, such as infrequent measurements from ships, or static measurements from buoys. Intelligent planning requires a path for the vehicle(s) to traverse, gathering samples in the right place at

the right time for maximal information gain. Based on the limited endurance of most AUVs, computing optimal controls (with respect to time or energy conservation) along these paths increases their abilities to gather data of high scientific importance. Additionally, a priority when computing control strategies is the implementation cost, indeed in some systems, such as AUVs, a large number of switchings is undesirable or unimplementable due to physical constraints on the actuators.

Our approach in this paper is to consider a desired trajectory that might not necessary be feasible by the vehicle, or such that its implementation cost is very high, e.g., in terms of energy expense. It is especially true, in optimal control for instance, that optimal trajectories often contain a singular arc, a large number of switchings or even chattering [4], [5]. A common solution is to develop a piecewise-constant (PWC) control to achieve the desired goal as well as possible. Based on practical constraints, these PWC strategies are designed to have a small number of switchings. In practice, these PWC controls are constructed through heuristics and extensive numerical simulations. The PWC controls can be designed in many different ways. For example, one technique is to fix the final configuration, and construct a sub-optimal path to reach it (see [6], [7] for applications of this approach to time and energy minimization for AUVs). There are also general strategies for development of PWC controls with popular software implementations [8], [9]. The outcome of these specific and general strategies often yield excellent results, but with little theoretical guidance in the form of error bounds. Moreover, some do not allow for features such as variable switching times or guidance from a known desired (non-PWC) control. Our approach allows, for instance, to preserve the duration of the given control (important in the case of time minimization), variable switching times, and we provide theoretical estimates on final state error with respect to the number of switchings.

In our first example, the desired trajectory for the fully actuated autonomous underwater vehicle is the time optimal one. Such trajectory is clearly unimplementable on a real vehicle due to its structure with singular arcs and between 15 and 30 switchings per thruster. The computed PWC control contains only two switchings for all thrusters combined, and is therefore ideal for implementation and is such that the vehicle reaches its final configuration within 2% displacement error while preserving the optimal time. The second example is a

profiling float for which the number of switchings is minimized to improve the endurance of the vehicle. We improve the given solution, obtained through a model predictive controller, by decreasing the number of switchings from 45 to 8 within the prescribed tolerance for the final configuration (0.7% error with respect to the final configuration of the given trajectory). Moreover, the duration of both paths is equal.

We also briefly address the question of construction of error bounds here. More precisely, we employ the one-sided Lipschitz constant to explicitly calculate an error bound (in terms of difference in final state vectors) of a PWC control with a fixed (small) number of switchings with respect to a desired control, with the same final time; we provide a construction of such a control. In particular, as seen above, if the desired trajectory is time-optimal, we produce a PWC control that preserves the optimal duration of the desired trajectory. We remark that an integral cost can be appended to the system as a state variable to expand to other costs to be minimized.

The paper is organized as follows. In Section II we introduce all necessary definitions and state the problem. Section III develops theoretical error estimates and describes an algorithm to develop a PWC control based on this. Finally, Section IV addresses the motion planning problem of an AUV via PWC controls. Results are presented for two different types of AUV, followed by concluding remarks on the application of our proposed methods.

II. PROBLEM STATEMENT

Consider a nonlinear, control-affine control system

$$\dot{x}(t) = f(x(t)) + g(x(t))u(t) \doteq \bar{f}(x(t), u(t)), \quad (1)$$

where $x(t) \in \mathbb{R}^n$ is the state variable, $u(t) \in \mathcal{U} \subset \mathbb{R}^m$ is a measurable bounded function called the control and assume the functions $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$, $g : \mathbb{R}^n \rightarrow \mathbb{R}^{n \times m}$ to be continuously differentiable. Let x_0 be an initial condition, and $u^*(\cdot)$ a reference control defined on $[0, T]$ such that its corresponding trajectory $x^*(\cdot)$ is the unique solution of (1) defined on $[0, T]$ as well.

Our goal is to construct a PWC control $\tilde{u}(\cdot)$ defined on $[0, T]$ with a fixed number of switchings σ such that its associated trajectory $\tilde{x}(\cdot)$ minimizes the difference of the final states $\|x^*(T) - \tilde{x}(T)\|$. We also provide an upper bound for the state error at the final time, which depends on the functions $f(\cdot), g(\cdot)$, on the given control signal $u^*(\cdot)$ and on the switching times of the PWC control.

III. ERROR ESTIMATION AND CONSTRUCTION OF A PWC CONTROL

The analysis of PWC controls has received some attention in the literature but the state of art is still incomplete. Some related work can be found in [10] in an optimal-control setting, in [11] for driftless control systems, and in [12], [13] for time-optimal syntheses of bang-bang controls. The major difficulty is to prove that the algorithms constructing PWC controls with a small number of switchings produce very efficient solutions

(either in terms of the cost or of the final configuration). In this paper we take a novel approach by considering the one-sided Lipschitz constant. It should actually be no surprise since it is known that the classical Lipschitz constant estimates only exponential growth even if the errors decay [14]. The details regarding the theoretical estimation bounds will be provided in a forthcoming work, here we limit the discussion to a few results without proofs since the emphasis is on the applicability of our techniques to AUVs.

Let us first introduce some basic definitions.

Definition 1 (Logarithmic norm [15]): Given a square matrix A , its logarithmic norm is defined as

$$\mu(A) \doteq \lim_{h \rightarrow 0^+} \frac{\|I + hA\| - 1}{h}. \quad (2)$$

where $\|\cdot\|$ is a given norm.

In [14] the reader can find formula for the logarithmic norm. For instance, for the Euclidean norm we have that $\mu(A) = \lambda_{max} =$ largest eigenvalue of $\frac{1}{2}(A^T + A)$.

Theorem 1: Assume that $(x(\cdot), u(\cdot))$ and $(\tilde{x}(\cdot), \tilde{u}(\cdot))$ are both solutions to the affine control system (1), and that the following estimates hold

- 1) $\mu\left(\frac{\partial \bar{f}}{\partial x}(\xi, u(t))\right) < l(t) \quad \forall \xi \in [x(t), \tilde{x}(t)];$
- 2) $\|\bar{f}(\tilde{x}(t), u(t)) - \bar{f}(\tilde{x}(t), \tilde{u}(t))\| \leq \delta(t);$
- 3) $\|x(0) - \tilde{x}(0)\| \leq \rho.$

Let $L(t) = \int_0^t l(\tau) d\tau$. Then the controlled trajectories satisfy

$$\|x(t) - \tilde{x}(t)\| \leq e^{L(t)} \left(\rho + \int_0^t e^{-L(\tau)} \delta(\tau) d\tau \right). \quad (3)$$

Proof: We here only sketch the proof since it closely follows the proof of Theorem 10.6 in [14], where a similar result in the framework of ordinary differential equations is presented. First, we introduce $\epsilon(t) \doteq \|x(t) - \tilde{x}(t)\|$. It is easy to see using triangle inequality and assumption 2 in the theorem that for small $h \in \mathbb{R}^+$,

$$\epsilon(t+h) \leq \|x(t) - \tilde{x}(t) + h(\bar{f}(x(t), u(t)) - \bar{f}(\tilde{x}(t), u(t)))\| + h\delta(t) + \mathcal{O}(h^2). \quad (4)$$

Applying the Mean Value Theorem on the compact interval $[x(t), \tilde{x}(t)]$ to the function $F(x(t)) = x + h\bar{f}(x, u(t))$ we obtain

$$\epsilon(t+h) \leq \epsilon(t) \max_{\xi \in [x(t), \tilde{x}(t)]} \left\{ \left\| I + h \frac{\partial \bar{f}}{\partial x}(\xi, u(t)) \right\| \right\} + h\delta(t) + \mathcal{O}(h^2). \quad (5)$$

Then

$$\frac{\epsilon(t+h) - \epsilon(t)}{h} \leq \epsilon(t) \max_{\xi \in [x(t), \bar{x}(t)]} \left\{ \frac{\|I + h \frac{\partial \bar{f}}{\partial x}(\xi, u(t))\| - 1}{h} \right\} + \delta(t) + \mathcal{O}(h) \quad (6)$$

and by taking the limit for $h \rightarrow 0^+$,

$$D_+ \epsilon(t) \leq \epsilon(t) \max_{\xi \in [x(t), \bar{x}(t)]} \mu \left(\frac{\partial \bar{f}}{\partial x}(\xi, u(t)) \right) + \delta(t), \quad (7)$$

where $\mu(\cdot)$ is defined as in (2).

Using the first inequality in the statement of the theorem, we obtain

$$D_+ \epsilon(t) < \epsilon(t) l(t) + \delta(t). \quad (8)$$

According to the definition of $L(t)$, the solution of the differential equation $\gamma'(t) = \gamma(t)l(t) + \delta(t)$ is

$$\gamma(t) = e^{L(t)} \left(\gamma(0) + \int_0^t e^{-L(\tau)} \delta(\tau) d\tau \right). \quad (9)$$

From the third assumption of the theorem, there exists ρ such that $\epsilon(0) \leq \rho$. We define $\gamma(0) = \rho$. Since $\epsilon(t)$ and $\gamma(t)$ are continuous, to complete the proof we simply have to show that $\epsilon(t) \leq \gamma(t) \quad \forall t \in [0, \Delta]$.

By contradiction, let t_2 be a point with $\epsilon(t_2) > \gamma(t_2)$ and consider the first point t_1 to the left of t_2 with $\epsilon(t_1) = \gamma(t_1)$. Then for small $h > 0$ we have

$$\frac{\epsilon(t_1+h) - \epsilon(t_1)}{h} > \frac{\gamma(t_1+h) - \gamma(t_1)}{h} \quad (10)$$

and, taking the limits, $D_+ \epsilon(t_1) \geq D_+ \gamma(t_1)$. This contradicts (8) as

$$D_+ \epsilon(t_1) < l(t_1) \epsilon(t_1) + \delta(t_1) = l(t_1) \gamma(t_1) + \delta(t_1) = D_+ \gamma(t_1). \quad (11)$$

A. An upper bound for the final error

It is important to provide an upper bound for the right-hand side of equality (3). This can be done as follows. Let σ be the number of fixed switchings for the new control and $t_0 < t_1 < \dots < t_\sigma$ be the switching times (including the initial and final time). We define $\Delta_0 = t_1 - t_0$ the first time interval and we define u_0 as

$$u_0 = \frac{1}{2} \max_{t, s \in [0, \Delta_0]} (u^*(t) - u^*(s)) \quad (12)$$

where $u^*(\cdot)$ is the reference trajectory. Using the fact that $\forall \tau \in [0, \Delta_0]$ there exists \bar{l}_τ such that

$$\int_\tau^{\Delta_0} l(t) dt = \bar{l}_\tau (\Delta_0 - \tau), \quad (13)$$

we have

$$e^{L(\Delta_0)} \int_0^{\Delta_0} e^{-L(\tau)} \|g(x(\tau))(u^*(\tau) - u_0)\| d\tau \leq \|\delta u_0\| \bar{e}(\Delta_0, \bar{l}_0) \quad (14)$$

where $\bar{l}_0 = \max_{\tau \in [0, \Delta_0]} \bar{l}_\tau$, $\|\delta u_0\| = \frac{k_g}{2} \max_{t, s \in [0, \Delta]} \|u^*(t) - u^*(s)\|$, k_g defined such that $\|g(x)\| \leq k_g \forall x$, and $\bar{e}(\Delta_0, \bar{l}_0) \doteq \frac{e^{\bar{l}_0 \Delta} - 1}{\bar{l}_0}$.

Theorem 1 applied with $x(0) = \tilde{x}(0)$ implies

$$\|x(t_1) - \tilde{x}(t_1)\| \leq \|\delta u_0\| \bar{e}(\Delta_0, \bar{l}_0). \quad (15)$$

Iterating this construction, we obtain

$$\|x(t) - \tilde{x}(t)\| \leq \sum_{k=0}^{\sigma-1} \left\{ \|\delta u_k\| \bar{e}(\Delta_k, \bar{l}_k) \prod_{i=k+1}^{\sigma-1} \{\bar{l}_i \Delta_i\} \right\}. \quad (16)$$

B. Construction of a PWC Control

In this section we provide a constructive algorithm to design a PWC control with a fixed number of switchings that minimizes the error on the final state of the system with respect to the desired one, with the same final time. The PWC controls with a fixed number of switchings are computed via general nonlinear programming with initial guess for the PWC control computed as follows¹. Notice that, as also outlined in [16], an accurate initial guess might play a central role in computing approximating PWC controls via nonlinear programming. For instance for our two examples, the fully actuated vehicle is very robust in terms of dependence with respect to initial guess while the minimally actuated vehicle is unstable.

We describe a numerical way to determine an initial guess for the PWC control. For a given time step Δ between two switchings, according to the result of Theorem 1, we have

$$\|x(\Delta) - \tilde{x}(\Delta)\| \leq e^{L(\Delta)} \rho + e^{L(\Delta)} \int_0^\Delta e^{-L(\tau)} \|g(\tilde{x}(\tau))(u^*(\tau) - \tilde{u})\| d\tau, \quad (17)$$

where u^* is the reference control and \tilde{u} is the value of the PWC control on this interval. Therefore the best choice for the constant value $\tilde{u} \in \mathbb{R}^m$ would be

$$\tilde{u} = \arg \min_{v \in \mathcal{U}} \int_0^\Delta e^{-L(\tau)} \|g(\tilde{x}(\tau))(u(\tau) - v)\| d\tau. \quad (18)$$

The main difficulty is that $\tilde{x}(t)$ is not known. To address this issue, a good initial guess can be obtained by assuming $g(\tilde{x}(t)) \simeq g(x(t))$ and solving the convex optimization problem:

$$\tilde{u} = \arg \min_{v \in \mathcal{U}} \sum_{k=0}^N e^{-L(t^k)} \|g(x^k)(u^k - v)\|^2 \quad (19)$$

where t^k are samples over the interval $[0, \Delta]$, divided in $N+1$ steps. Fixing the length of the time steps for the PWC control $\Delta_0, \Delta_1, \dots, \Delta_{\sigma-1}$, problem (19) can then be solved for each time step Δ_i , thus computing the values $\tilde{u}_0, \tilde{u}_1, \dots, \tilde{u}_{\sigma-1}$ of the initial-guess PWC control. Finally, after selection of an initial guess, general nonlinear minimization techniques are used to find the PWC control, i.e. a set of switching times and constant control values, which minimizes the final error $\|x(T) - \tilde{x}(T)\|$.

¹The code is available at <http://math.hawaii.edu/~marriott/pwc/>

| | | | |
|---------------|------------------------|--------------------------|------------------------|
| mass | 123.8 kg | $B = \rho g \mathcal{V}$ | 1215.8 N |
| diameter | 0.64 m | $W = mg$ | 1214.5 N |
| C_B | (0, 0, -7) mm | C_G | (0, 0, 0) mm |
| $M_f^{\nu_1}$ | 70 kg | $M_f^{\nu_2}$ | 70 kg |
| $M_f^{\nu_3}$ | 70 kg | I_{xx} | 5.46 kg m ² |
| I_{yy} | 5.29 kg m ² | I_{zz} | 5.72 kg m ² |

TABLE I
MAIN DIMENSIONS AND HYDRODYNAMIC PARAMETERS FOR ODIN.

IV. APPLICATION TO THE MOTION PLANNING FOR UNDERWATER VEHICLES

In this section, we examine the implementation of our methods on two types of underwater platforms: a fully actuated underwater vehicle capable of motion in all six degrees-of-freedom (DOF) and a profiling float which is a minimally actuated vehicle.

A. Application on a Fully-Actuated AUV

We first apply our analysis to the nonlinear, control-affine model for AUVs as seen in [17] or [18]. The reference control is taken as a time-optimal control to steer the fully actuated AUV from one configuration to another, with the motion starting and ending at rest (zero velocity). Time-optimal trajectories are formed by concatenations of bang arcs (corresponding to either maximal or minimal thrust) and singular arcs [6]. In [6], the authors develop a numerical algorithm to design control strategies to steer the AUVs to the exact configuration with a fixed number of switchings. It is shown that this method can produce control strategies with as few as two or three switchings and be within 10% of the optimal time. The approach taken here is different, as we fix the final time to the optimal time and minimize the error between the achievable final configuration and the desired final configuration.

The simulations are based on the AUV analyzed in [6]. The vehicle's main body is a 0.64 m diameter sphere, with eight thrusters evenly distributed around the sphere; four oriented vertically and four oriented horizontally. The numerical values of vehicle parameters, derived from estimations and experiments, see [6], are given in Table I. Based on these vehicle parameters, this fully actuated AUV is capable of unbiased movement in six DOF, and has acted as an excellent platform for the development, implementation and comparison of a wide-range of control strategies, e.g., [19]–[21].

For an underwater vehicle moving in six DOF, we consider the generalized position to be $\eta = (b^\top, \pi^\top)^\top = (b_1, b_2, b_3, \phi, \theta, \psi)^\top$, with respect to an inertial frame, and let $\nu = (v^\top, \omega^\top)^\top$ be the vehicle velocity in the body-fixed frame. Let $u = (u_1, \dots, u_6)$ represent the controls. Then the equations of motions are

$$\begin{aligned} \dot{\eta} &= J(\eta)\nu \\ M\dot{\nu} + C(\nu)\nu + D(\nu)\nu + g(\eta) &= u, \end{aligned} \quad (20)$$

where $J(\eta)$ maps a vector expressed in the body-fixed frame to the same vector expressed in the inertial frame, M is the




Fig. 1. Time-optimal control signals from [7]: u_1^* (solid blue), u_2^* (dashed red), u_3^* (dot-dashed green) in the top plot; u_4^* (solid blue), u_5^* (dashed red), u_6^* (dot-dashed green) in the bottom plot. In [7, Fig. 2], the corresponding signals for the eight thrusters are shown, where they are computed using a static control allocation.

mass and inertia matrix, $C(\cdot)$ the Coriolis matrix, $D(\cdot)$ the damping matrix and $g(\cdot)$ is the gravity vector (see [17] for details).

The initial and final states are taken respectively as the origin and $(\eta^\top, \nu^\top) = (5, 4, 1.3, 0_{1 \times 3}, 0_{1 \times 6})$. The time-optimal control signals have many discontinuities, see Fig. 1, and therefore are not implementable on physical actuators. Moreover there are singular arcs which require a continuous change in the actuation.

Applying our algorithm to this scenario, we can produce a PWC control with only two switchings, with an error with respect to the desired final state equals to (0.0414, 0.0474, 0.0171, 0.0112, 0.0104, 0.0273, -0.0137, -0.0132, -0.0010, -0.0289, -0.0226, -0.0085). This error corresponds to approximately 6 cm in position, 2 deg in orientation, 2 cm/s in translational velocity, and 2 deg/s in angular velocity.

Figures 2–4 show the simulation results. Note that the problem formulation is such that the control-vector components are allowed to jump all at the same time instants.

The precision of the algorithm is particularly relevant based on the fact that, unlike [6] and [7], the final time is fixed to be the optimal one of 17.39 s. The estimate (16) provides a reasonable theoretical bound even for two control switchings.

The gain here is significant. Indeed, the number of switchings were reduced from a large number (together with about 10 singular arcs) for the time-optimal control, to only 2 switchings, and reaching with good precision the final state. The advantage in reducing the number of control switchings has many practical reasons, for instance: less stress on the control actuators, and less onboard memory-storage requirements. From the computational-time point of view there is also a




Fig. 2. PWC control signals: u_1 (solid blue), u_2 (dashed red), u_3 (dot-dashed green) in the top plot; u_4 (solid blue), u_5 (dashed red), u_6 (dot-dashed green) in the bottom plot.




Fig. 3. State trajectories for the position vector: η_1 (blue), η_2 (red), η_3 (green). The solid line represents the trajectory obtained via the PWC control synthesis while the dashed line is the time-optimal trajectory.

significant gain by considering a small number of switchings. Solving the PWC control problem for a nonlinear system with 12 states and 6 inputs (including 2 switching times) required 36.943 s on a dual-core, 2.66 GHz processor. A computational time of 349.754 s was required for 10 switching times.

B. Application on a Minimally-Actuated AUV

Here, we consider applying our method to the control of profiling float. This vehicle is free-drifting, and can only actively control its depth. By intelligently altering its depth, the vehicle uses ocean currents to carry it to a desired destination. Apart from the hotel load, changes in depth (buoyancy) are the only source of energy consumption. Extending the endurance of this vehicle directly corresponds to minimizing the number of depth changes (switchings).

1) *System Model*: For the analysis here, we assume a simple model of a profiling float. The vehicle moves in \mathbb{R}^3 , and is invariant in roll (ϕ), pitch (θ), and yaw (ψ). The vertical position of the float ($b_3(t)$) can be controlled, and




Fig. 4. State trajectories for the orientation vector: η_4 (blue), η_5 (red), η_6 (green). The solid line represents the trajectory obtained via the PWC control synthesis while the dashed line is the time-optimal trajectory.

the horizontal velocities (\dot{b}_1, \dot{b}_2) are determined strictly by ocean currents. We assume that the float can be represented dynamically as a point mass. We can express the equations of motion in \mathbb{R}^3 by expressed by the equations

$$\dot{b}_1 = f(b_3, t), \quad \dot{b}_2 = g(b_3, t), \quad \dot{b}_3 = v_3(t) + h(b_3, t), \quad (21)$$

where $f(b_3, t), g(b_3, t)$ and $h(b_3, t)$ represent the horizontal (x, y) and vertical components of the ocean velocity, respectively. Note that this system is not control affine as in the previous example, however the system does fit into the flexible framework of the proposed algorithm.

Here, we will ignore vertical currents, i.e., $h(b_3, t) = 0$, and thus $\dot{b}_3 = v_3(t)$. As ocean currents are not constant functions with respect to depth, we can indirectly control the horizontal motion of the float by intelligently controlling the depth of the vehicle. Hence, rather than considering the ocean currents as drift to the system, we write them as a dependent input control, see [22]–[24] for a detailed treatment of this concept. Thus, for a given location, choosing a depth defines the direction of motion. Let $H(b_3, t) = (f(b_3, t), g(b_3, t), 0)^\top$, where $f, g : \mathbb{R}^+ \mapsto \mathbb{R}$ represent the north-south and east-west currents, respectively. Here, velocity is positive eastward and northward. Since we are interested in steering the float from one position on the sea surface to another position on the sea surface, the motion planning can actually be projected into \mathbb{R}^2 , with the depth (b_3) acting as the input control that defines the velocities in the plane. Thus, we express the system as

$$(\dot{b}_1, \dot{b}_2, b_3)^\top = (0, 0, 1)^\top u_3(t) + H(b_3, t). \quad (22)$$

The only direct control input is the depth of the vehicle, i.e., $b_3(t) = u_3(t)$, and $u \in [0, 2000]$ meters. Since $H(b_3)$ is a function of depth and time, we obtain indirect control on the vehicle velocity as we change the depth over time. For our analysis, $H(b_3)$ is obtained from an ocean model. Based on the time scale of the horizontal motion, we can assume that depth can be changed instantaneously. We remark that although the vehicle is moving in \mathbb{R}^3 the motion of interest only occurs in \mathbb{R}^2 . Since the depth is a control, the state variables are simply (b_1, b_2) , corresponding to longitude and latitude, respectively.

2) *Algorithm Results*: We compare the results of our algorithm to an existing control strategy for an ocean-science




Fig. 5. Reference depth control (dashed black line) and the computed PWC depth control (solid blue line).




Fig. 6. Reference trajectory projected to the sea surface (dashed black line) and the computed PWC trajectory (solid blue line) trajectory with eight switchings projected to the sea surface.

application, see [23], [24]. In [23], an A* algorithm is used to determine a set of waypoints, with a model predictive control algorithm determining the control necessary to navigate between these waypoints. We compare our result to the output of this lower-level algorithm. For a reference control, we take the initial point $(-118.4800^\circ E, 33.4600^\circ N)$ with a final point of $(-118.4600^\circ E, 33.4800^\circ N)$. The reference algorithm from [23] produces a control with a duration of 62 hours and 45 switchings, shown in Fig. 5. The final point reached is $(-118.4632^\circ E, 33.4800^\circ N)$, which lies within the destination tolerance (400 m) for the low-level actuator decision algorithm. A PWC control is found with only eight switchings. This computed PWC control reaches the point $(-118.4633^\circ E, 33.4801^\circ N)$, which is just more than 300 m from the desired destination. Hence, we achieve the goal location within the desired accuracy with only 18% of the switchings. This is a significant reduction in energy consumption. Note that the path executed with only eight switchings deviates more significantly from the desired, straight-line path connected the waypoints than the algorithm presented in [23], however this accuracy is application specific. In general, such deviations are acceptable given the significant energy savings, especially at the large spatiotemporal scales examined in ocean science.

In this application, we notice a particular sensitivity to the initial guess on the number of switchings. In many systems, an acceptable PWC control can be found without putting great effort into the initial guess. In the first system considered,

opposite initial guesses for the control, one with zero motor actuation and the other with constant full motor actuation, have a difference of only 9.3% in final state error of the optimized PWC control. However in this system, for a PWC control with ten switchings, if the initial guess is constructed by sampling the given control at evenly spaced switching times, the algorithm arrives at a control with a final state error of 9.79 km. On the other hand, we have given an instance of a control with only eight switchings with an error of just 300 m.

V. FUTURE WORK

Future publications will give further treatment to the theoretical framework and a wider range of applications. Most importantly, future work will focus on discussion of the most suitable norm to be used in the error estimate arguments, in particular allowing the flexibility of weighting individual state variables (of which the integral cost may be one) in the error estimates. The ultimate goal is to, given a prescribed tolerance on the final configuration and a possible cost, theoretically predict a number of switchings required to ensure this bound.

ACKNOWLEDGEMENTS

The authors thank Prof. Ernst Hairer for his suggestion of using the one-sided Lipschitz constant.

This work was supported by the National Science Foundation Division of Mathematical Sciences, award #1109937. This work relates to Department of the Navy Grant N62909-11-1-4046 issued by the Office of Naval Research Global. The United States Government has a royalty-free license throughout the world in all copyrightable material contained herein. This work was supported in part by the Early Career Academic Recruitment and Development (ECARD) Program of the Queensland University of Technology.

REFERENCES

- [1] K. A. Morgansen, B. I. Triplett, and D. J. Klein, "Geometric methods for modeling and control of free-swimming fin-actuated underwater vehicles," *IEEE Transactions on Robotics*, vol. 23, no. 6, pp. 1184–1199, December 2007.
- [2] J. Manley and S. Wilcox, "The wave glider, a persistent platform for ocean science," in *Proceedings of the MTS/IEEE OCEANS*, Sydney, Australia, May 2010.
- [3] D. Webb, P. Simonetti, and C. Jones, "SLOCUM: an underwater glider propelled by environmental energy," *IEEE Journal of Oceanic Engineering*, vol. 26, no. 4, 2001.
- [4] L. Pontryagin, V. Boltyanskii, R. Gamkrelidze, and E. Mishchenko, *The Mathematical Theory of Optimal Processes*, 1st ed. New York: Interscience, 1962.
- [5] B. Bonnard and M. Chyba, *Singular trajectories and their role in control theory*, 2nd ed. Berlin: Springer-Verlag, 2003.
- [6] M. Chyba, T. Haberkorn, R. N. Smith, and S. Choi, "Design and implementation of time efficient trajectories for autonomous underwater vehicles," *Ocean Engineering*, vol. 35, pp. 63–76, 2008.
- [7] M. Chyba, T. Haberkorn, S. B. Singh, R. N. Smith, and S. Choi, "Increasing underwater vehicle autonomy by reducing energy consumption," *Ocean Engineering*, vol. 9, no. 1, pp. 62–73, 2009.
- [8] L. Grüne, D. Nešić, and J. Pannek, "Model predictive control for nonlinear sampled-data systems," in *Assessment and future directions of nonlinear model predictive control*, ser. Lecture Notes in Control and Inform. Sci. Berlin: Springer, 2007, vol. 358, pp. 105–113. [Online]. Available: http://dx.doi.org/10.1007/978-3-540-72699-9_8

- [9] B. Houska, H. J. Ferreau, and M. Diehl, "ACADO toolkit—an open-source framework for automatic control and dynamic optimization," *Optimal Control Appl. Methods*, vol. 32, no. 3, pp. 298–312, 2011. [Online]. Available: <http://dx.doi.org/10.1002/oca.939>
- [10] K. Aida-Zadeh and A. Ragimov, "Solution of optimal control problems in class of piecewise-constant functions," *Automatic Control and Computer Sciences*, vol. 41, no. 1, pp. 18–24, 2007.
- [11] S. Monaco, D. Normand-Cyrot, and P. D. Giamberardino, "Input-state matching under piecewise constant control for systems on matrix lie groups," *Proc. of the IEEE Conf. on Decision and Control, Atlanta (Georgia, USA)*, pp. 7117–7122, 2010.
- [12] C. Kaya and J. Noakes, "Computational method for time-optimal switching control," *Journal of optimization theory and applications*, vol. 117 (1), pp. 69–92, 2003.
- [13] C. Kaya, S. Lucas, and S. Simakov, "Computations for bang-bang constrained optimal control using a mathematical programming formulation," *Optimal control applications and methods*, vol. 25 (6), pp. 295–308, 2004.
- [14] E. Hairer, S. Nørsett, and G. Wanner, *Solving ordinary differential equations I. Nonstiff problems*. Springer series in Computational Mathematics. Springer-Verlag, 2008.
- [15] M. Vidyasagar, *Nonlinear systems analysis*. SIAM Classics in Applied Mathematics, 2002.
- [16] C. Kaya and J. Noakes, "Computations and time-optimal controls," *Optimal control applications and methods*, vol. 17 (3), pp. 171–185, 1996.
- [17] T. Fossen, *Guidance and control of oceanic vehicles*. John Wiley and Sons, 1994.
- [18] G. Antonelli, *Underwater Robots*. Springer-Verlag, 2003.
- [19] J. Yuh, "A neural net controller for underwater robotic vehicles," *IEEE Journal of Oceanic Engineering*, vol. 15(3), pp. 161–166, 1990.
- [20] A. Hanai, H. Choi, S. Choi, and J. Yuh, "Minimum energy based fine motion control of underwater robots in the presence of thruster nonlinearity," in *Proceedings of IEEE/RSJ International Conference on Intelligent Robots and Systems*, Las Vegas, Nevada, USA, 2003, pp. 559–564.
- [21] M. Andonian, M. Chyba, D. Cazzaro, L. Invernizzi, and S. Grammatico, "Geometric control for autonomous underwater vehicles: overcoming a thruster failure," in *Proc. of the IEEE Conf. on Decision and Control*, Atlanta (Georgia, USA), 2010, pp. 7051–7056.
- [22] R. N. Smith and M. Dunbabin, "Controlled drift: An investigation into the controllability of underwater vehicles with minimal actuation," in *Proceedings of the Australasian Conference on Robotics and Automation*, July 2011.
- [23] R. N. Smith and V. T. Huynh, "Controlling minimally-actuated vehicles for applications in ocean observation," in *Proceedings of the IFAC Workshop on Navigation, Guidance and Control of Underwater Vehicles*, Porto, Portugal, April 2012.
- [24] —, "Control and application of minimally-actuated underwater vehicles," *IEEE Journal of Oceanic Engineering*, 2012, submitted.