

Controlling Minimally-Actuated Vehicles for Applications in Ocean Observation^{*}

Ryan N. Smith and Van T. Huynh

Electrical Engineering and Computer Science, Queensland University of Technology, Brisbane, QLD 4000, Australia
(e-mail: ryan.smith@qut.edu.au, thanhvan.huynh@student.qut.edu.au).

Abstract: Establishing a persistent presence in the ocean with an AUV to observe temporal variability of large-scale ocean processes requires a unique sensor platform. In this paper, we propose a strategy that utilizes ocean model predictions to increase the autonomy and control of Lagrangian or profiling floats for precisely this purpose. An A* planner is applied to a local controllability map generated from predictions of ocean currents to compute a path between prescribed waypoints that has the highest likelihood of successful execution. The control to follow the planned path is computed by use of a model predictive controller. This controller is designed to select the best depth for the vehicle to exploit ambient currents to reach the goal waypoint. Mission constraints are employed to simulate a practical data collection mission. Results are presented in simulation for a mission off the coast of Los Angeles, CA USA, and show surprising results in the ability of a Lagrangian float to reach a desired location.

Keywords: Autonomous Control, Path Planning, Marine Systems, Control Algorithms, Profiling Floats

1. INTRODUCTION

Enhancing our knowledge of large-scale ocean processes requires a persistent presence to understand the complex spatiotemporal interactions among the mechanisms driving these processes. Such persistent monitoring can help address a fundamental question in differentiating the processes that happen locally from those processes that happen remotely. Through the implementation of multiple and adaptable sensors, we can facilitate simultaneous and rapid measurements that capture the appropriate scale of spatiotemporal variability for many of these phenomena that we seek to understand. Autonomous Underwater Vehicles (AUVs) play a key role in this effective, efficient and adaptive data collection procedure to improve our overall understanding of our world's oceans. Such implementations can provide fine-scale resolution far surpassing previous sampling methods, such as infrequent measurements from ships, or static measurements from buoys.

A persistent presence is key to capturing the temporal variability of processes occurring over multiple scales (weeks to months, and possibly years). Currently, there are only a few types of AUVs able to achieve the necessary persistence; autonomous gliders Schofield et al. (2007); Griffiths et al. (2007), and profiling floats Roemmich et al. (2004). With reduced actuation, these vehicles save power, but are less able to achieve reliable trajectories, as their motion is dictated more by external forces (ocean currents) than by their own power (thrusters). There has been considerable research done on control of underwater gliders, e.g., Graver (2005); Paley et al. (2008); Leonard et al. (2010). Complementing this research, here we focus on the control and planning for profiling floats (see Fig. 1), and examine the application of these vehicles for ocean science. The most famous example of a profiling float is the ARGO float Bel-

bech (2010), with the mission to map out deep-ocean currents. However, based on the mode of operation, the primary region of operation for these floats is the deep ocean.

Recent research has seen profiling floats applied in multiple applications from physical oceanography to underwater imaging, see e.g., Schwitald and Roman (2009). This research has motivated interest in operating floats in highly-dynamic, coastal environments, or confined regions like embayments Smith and Dunbabin (2011); Jouffroy et al. (2011). Such environments can be extremely dangerous, as without proper control and actuation, the vehicles would run aground or travel away from the desired sensing location. However, with the proper control, a profiling float can provide an optimal sampling platform for multiple research scenarios.

A body of literature exists on path planning for actuated AUV in the presence of water currents, see e.g., Petres et al. (2007); Alvarez et al. (2004); Garau et al. (2005). These studies primarily relate to quasi steady-state ocean currents without consideration of vehicle actuation limits and often not identifying infeasible paths particularly in strong ocean currents. An alternate approach to minimum energy continuous path planning was proposed by Kruger et al. (2007). Here the authors considered vehicle actuation limits using a multi-dimensional cost function for generating energy and time optimum paths in estuarine environments. In an extension of this work a new optimal (time and energy) path planning approach was demon-



Fig. 1: Example of a profiling float manufactured by Teledyne Webb Research, Inc.

^{*} This work relates to Department of the Navy Grant N62909-11-1-4046 issued by the Office of Naval Research Global. The United States Government has a royalty-free license throughout the world in all copyrightable material contained herein.

strated with an actuated AUV in a highly dynamic embayment Witt and Dunbabin (2008). This work illustrated the potential to use currents for improving vehicle range and endurance as well as waypoint control in regions with tidally varying obstacles. However, there is little research examining the control of minimally-actuated vehicles; the horizontal motion is determined entirely by ocean currents.

Control of minimally actuated vehicles is an emerging area of study. In the last year, theoretical methods have been established for controlled Lagrangian particle tracking to analyse the offsets between physical positions of marine robots in the ocean and simulated positions of controlled particles in an ocean model Szwaykowska and Zhang (2011); design of an ocean-scale, sensor web was proposed via intelligent control of deployed ARGO floats Dahl et al. (2011); control strategies for coastal environments and embayments was presented in Smith and Dunbabin (2011); and a feedback controller for floats operating in tidally-forced regions is demonstrated in Jouffroy et al. (2011). Planning by use of ocean model predictions has been shown by the authors to be an effective method for reducing navigation error due to external disturbances and assist in planning for minimally actuated vehicles Smith et al. (2010b, 2012). Here, we extend the aforementioned results, specifically Smith and Dunbabin (2011) to demonstrate techniques for control of a profiling float in a practical, ocean-science application.

2. PROFILING FLOATS

Profiling floats are widely used to gather data throughout our world’s oceans in a cost-effective manner. In the history of oceanographic research, there have been many subsurface floats produced and implemented, see e.g., Rossby et al. (1985); Davis (1991); Davis et al. (1992); D’Asaro et al. (1996). We aim to extend the capabilities of a platform that has held a place in ocean science for multiple decades. These floats considered here are similar to Lagrangian floats in that they drift with the ambient currents, however the profiling float is able to change its buoyancy, hence its depth, throughout a mission. Alteration in buoyancy provides an important tool for analyzing specific processes occurring within discrete density layers, and provides a mechanism for the development of unique control for a minimally-actuated vehicle.

Recent developments in profiling floats and their associated autonomy McGilvray and Roman (2010) have provided a platform with accurate buoyancy control, and has the capability to be deployed for extended durations (depending on sensor payload). This platform motivates further study in the development of control methods and autonomy for such vehicles.

2.1 Assumed Float Characteristics

The characteristics of a float vary widely depending on the desired application. For the analysis presented here, we assume a simple profiling float. We assume that the vertical position of the float within the water column can be controlled, and the horizontal velocity is determined strictly by ocean currents. We will assume that the float can be represented dynamically as a point mass. We can express the equations of motion on \mathbb{R}^3 by

$$\dot{x}_1 = f(t), \quad \dot{x}_2 = g(t), \quad \dot{x}_3 = u^3(t) + h(t), \quad (1)$$

where $f(t)$, $g(t)$ and $h(t)$ represent the horizontal (x, y) and vertical components of the ocean velocity, respectively, and $\{x_1, x_2, x_3\}$ define a right-hand, inertial coordinate system with x_3 chosen positive in the direction of gravity. We




Fig. 2. An example vertical current profile prediction for a location off the coast of southern California, USA. This is a ROMS prediction of ocean depth versus current velocity for the zonal (blue) and meridional (red) components located at 33.5° N, -118° E.

initially ignore vertical currents, i.e., $h(z, t) = 0$, and thus $x_3 = u^3(t)$. As ocean currents are not constant functions with respect to depth (Fig. 2), we can indirectly control the horizontal motion of the float by varying the depth of the vehicle. Hence, rather than considering the ocean currents as drift to the system, we choose to write them as a dependent input control, see Smith and Dunbabin (2011). Thus, for a given location, choosing a depth defines the direction of motion. Let $H(z) = (f(z, t), g(z, t), 0)^t$, where $f, g : \mathbb{R}^+ \mapsto \mathbb{R}$ represent the zonal and meridional currents, respectively. Here, meridional velocity is positive eastward and zonal velocity is positive northward. The system is expressed on \mathbb{R}^3 as

$$(\dot{x}, \dot{y}, \dot{z})^t = (0, 0, 1)^t z(t) + H(z). \quad (2)$$

Here the control function $z(t)$ is the only input that we can directly control. Since $H(z)$ is a function of depth and time, we obtain indirect control on this velocity input as we control the depth over time. In this work, we obtain $H(z)$ from an ocean model to design the control for executing a prescribed motion.

3. OCEAN MODEL INPUT

The predictive tool that we utilize for general open ocean currents in the Pacific basin is the Regional Ocean Model System (ROMS) - a split-explicit, free-surface, topography-following-coordinate oceanic model. ROMS is an open-source, ocean model that is widely accepted and supported throughout the oceanographic and modelling communities. The model solves the primitive equations using the Boussinesq and hydrostatic approximations in vertical sigma (i.e., topography following) and horizontal orthogonal curvilinear coordinates. ROMS uses innovative algorithms for advection, mixing, pressure gradient, vertical-mode coupling, time stepping, and parallel efficiency. Detailed information on ROMS can be found in Shchepetkin and McWilliams (1998) and Shchepetkin and McWilliams (2005). Applications of this four-dimensional model implemented in AUV path planning can be found in Smith et al. (2010a, 2011) and the references contained therein. As with any model, there are inherent characteristics that cannot be modeled, and hence errors that exist in the outputs. An aim of this research is to provide information to assist in the reduction of prediction errors in regional ocean models. As we work closely with the developers of the ocean models, the intent of deployments

based on this method is to develop a continuous feedback between the vehicle and the ocean model. As the motion of the vehicle is purely based on currents, providing the model with position updates during a planned trajectory will increase the accuracy of predictions, in turn improving the controllability of the float.

4. PATH PLANNING

Based on the limited controllability provided by relying entirely on ocean currents, we accept that the floats may not be able to reach every position, and it is not guaranteed that a float will accurately reach a goal location. Here, we are only concerned in having the float arrive within a neighbourhood of the prescribed goal. Depending on the spatial scale of the process that is under consideration, the relative size of this neighbourhood will be different.

In this paper, we investigate the controllability of a profiling float off the coast of Los Angeles, CA USA. We utilize 16 days of ROMS predictions to provide a simulated ocean environment and demonstrate the effectiveness of our controller.

4.1 Conditions for Controllability

We are interested in verifying controllability for a float in \mathbb{R}^2 . This can be accomplished by examining the accessibility set; the set of all admissible motions from each configuration. As presented in Smith and Dunbabin (2011), the controllability of a float in \mathbb{R}^2 is given by the following proposition.


Proposition 1. A profiling float is controllable in \mathbb{R}^2 if and only if the convex hull of the accessibility set \mathcal{A} is compact and contains the origin.

The proof of Proposition 1 is a standard result from control theory, and in the interest of space, we omit the details here. See Smith and Dunbabin (2011) for further details.


Proposition 1 presents an analytic analysis of the control of a profiling float that can move vertically through the water column. In practice, the ocean is too dynamic and complex to formally incorporate and validate this analytic framework. However, we can utilise general trends and ocean models to assist in planning and control techniques.

4.2 Controllability Map

The key integration of the ocean model in this research is the ability to *predict* areas of full controllability, i.e., areas that satisfy Proposition 1. The result is a controllability *map* upon which we can plan. For each hour of available prediction, we project the velocity vector of each depth bin into a single plane for each location node in the model output. In the plane, we compute the convex hull of the set of velocity vectors at each location. For each location and each time step, we produce a binary output; 1 if the convex hull of the velocity vectors contains the origin (model node), and 0 if it does not. Then, we sum these outputs over all hours and compute the percentage that each location provides a *controllable* scenario, i.e., satisfies Proposition 1. A resultant heat map of controllability is presented in Fig. 3(a), with blue referring to areas of low controllability, and red the areas of high controllability. It is clear from Fig. ref that the northeastern portion of the figure is land, as seen in the Google Earth image of the same area in Fig. 3(b).



(a) Controllability map generated from ocean model predictions. Blue refers to areas of low controllability, and red are areas of high controllability.



(b) Google Earth image (right) of the same geographical area off the coast of southern California, USA.

Fig. 3. (a) The controllability heat map generated from ocean model predictions with the optimal A* path overlaid. (b) Google Earth image (right) of the same geographical area off the coast of southern California, USA.

4.3 Determining the Path

Given the controllability map described in Section 4.2, we can implement a path planner based on the desired level of predicted controllability. Given the graph structure of the ocean model output, we choose to implement a simple A* planner to compute a path from the start location to the goal. This method produces waypoints at discrete locations that correspond to nodes in the model output. The optimization constraint considered is to minimize the cost function $c(p) = 1 - p$ over the path between start and goal, where p is the percentage of controllability at a given node. The path planned by this method is shown in Fig.

3(a). For this example, we chose a start and end location that straddled an area of high probability of controllability. The start location is just off the tip of Catalina Island, CA and is depicted by a white dot in Fig. 3(a).

5. CONTROL STRATEGY

We chose the start and goal locations to emulate the float executing a transect crossing the channel between the US west coast and Catalina Island. This transect is of particular interest to study the flux of nutrients and phytoplankton transported into the region. The fundamental question is in differentiating the processes that happen locally from processes that happen remotely with the effects advected into San Pedro Bay. Given the start and goal locations, and the ocean science motivation, we incorporate the following operational constraints into the design of our proposed controller.

- ROMS provides 72-hour predictions each day, thus we fix a maximum of 70 hours between surfacings.
- For safety, we do not want to surface frequently. Or stay on the surface for extended periods of time, thus we set a minimum 6 hour limit between surfacings and only allow the float to remain on the surface for one hour.
- Based on the underlying science motivation, we require the float to perform periodic, full-depth, vertical profiles. This is implemented by requiring the float to go to the sea floor for the time-step immediately proceeding a scheduled surfacing.
- We do not constrain the float to follow a prescribed trajectory, but provide control such that each waypoint is achieved to within a user-defined tolerance.
- The interaction between the ocean model and float provides the opportunity to inform the model of the last executed path, and help to increase predictive capabilities.

To achieve the aforementioned control problem, we propose to implement a Robust Constraint Finite Horizon Model Predictive Controller (RCFMPC). We continue with the details of this controller.

We initially assume that there are no sudden changes in velocity of ocean the currents with respect to time. This allows us to consider the following Linear Time Varying (LTV) system,

$$\mathbf{X}(k+1) = \mathbf{A}(k)\mathbf{X}(k) + \mathbf{B}(k)\mathbf{U}(k) , \quad (3)$$

$$\mathbf{Y}(k) = \mathbf{C}(k)\mathbf{X}(k) , \quad (4)$$

where $\mathbf{U}(k) \in \mathbb{R}^{n_u}$ is the control input, $\mathbf{X}(k) \in \mathbb{R}^{n_x}$ is the state of the plant and $\mathbf{Y}(k) \in \mathbb{R}^{n_y}$ is the plant output. Also, $[\mathbf{A}(k) \ \mathbf{B}(k)] \in \Omega(k)$, which is a prescribed set at time k .

In Eq. (3), the control input is bang-bang, and given by $\mathbf{U}(k) = [u_1, \dots, u_{n_u}]^T$. Hence, $u_i \geq 0$, $u_i \in 0, 1$, and $\sum_{i=1}^{n_u} u_i \leq 1$. If the control is set to $u_1 = 1, u_2 = 0, \dots, u_{n_u} = 0$, the float will apply an alteration in buoyancy to move to the sea surface. Similarly, if $u_1 = 0, u_2 = 0, \dots, u_{n_u-1} = 0, u_{n_u} = 1$, the float will decrease its buoyancy and dive a depth slightly above the seabed. The size of the input vector \mathbf{U} depends on the maximum depth of the ocean at the current location of the float. The deeper the ocean, the larger n_u is allowed. In our case, $n_u \leq 20$, i.e., the maximum depth in the chosen region has a model index of 20, corresponding to an actual depth of 800 m.

The state $\mathbf{X}(k) = [x(k) \ y(k)]^T$, where $[x \ y]$ is the longitudinal and latitudinal coordinates of the profiler, respectively. The matrix \mathbf{A} is the identity matrix of size $n_x = 2$.

The matrix $\mathbf{B}(k) \in \mathbb{R}^{n_x \times n_u}$ is a matrix of time-varying elements, which are computed from the model prediction. Since the prediction data are updated each time the float surfaces, the matrix $\mathbf{B}(k)$ also changes, corresponding to the most recent model output. Finally, the output matrix \mathbf{C} is an identity matrix of size 2.

Equation (3) is the mathematical model for a float that is controlled horizontally by ocean currents. From this model, we now proceed to detail a RCFMPC. The desired controller has the objective,

$$\min_{\mathbf{U}(k+i|k), [\mathbf{A}(k)\mathbf{B}(k)] \in \Omega(k)} \max_{[\mathbf{A}(k)\mathbf{B}(k)] \in \Omega(k)} J_N(k) , \quad (5)$$

where

$$J_N(k) = \sum_{i=0}^N (\mathbf{X}(k+i|k)^T \mathbf{Q}_1 \mathbf{X}(k+i|k) + \mathbf{U}(k+i|k)^T \mathbf{R} \mathbf{U}(k+i|k))$$

with $\mathbf{Q}_1 > 0$ and $\mathbf{R} > 0$ being symmetric weighting matrices. The parameter m in the objective function is the number of prediction steps.

Since \mathbf{Q}_1 and \mathbf{R} are positive definite, we consider Eq. (5) equivalent to

$$\min_{\mathbf{U}(k+i|k), [\mathbf{A}_0\mathbf{B}_0] \in \Omega_0} \max_{[\mathbf{A}_0\mathbf{B}_0] \in \Omega_0} J_0 \max_{[\mathbf{A}_1\mathbf{B}_1] \in \Omega_1} J_1 \dots \max_{[\mathbf{A}_N\mathbf{B}_N] \in \Omega_N} J_N . \quad (6)$$

The desired RCFMPC is subject to the following constraints.

- Output:

$$\mathbf{Y}(0) \leq \mathbf{Y}(k) , \quad (7)$$

$$\mathbf{Y}(k+1) \leq [0, 0]^T . \quad (8)$$

Here, we choose the destination waypoint to be the origin, resulting in the inequality given in Eq. (8).

- Input:

$$\mathbf{U}(k) \in \mathbb{S} , \quad (9)$$

where \mathbb{S} is predetermined set values of inputs. Specifically,

$$\mathbb{S} = \{[0, 0, 0, \dots, 0]^T, [1, 0, 0, \dots, 0]^T, [0, 1, 0, \dots, 0]^T, \dots, \underbrace{[0, 0, 0, \dots, 1]^T}_{n_u \text{ elements}}\} . \quad (10)$$

- Guiding angle:

$$\boldsymbol{\tau}_1^T(k) \boldsymbol{\tau}_2(k) \leq \|\boldsymbol{\tau}_1(k)\| \|\boldsymbol{\tau}_2(k)\| , \quad (11)$$

$$\text{and } \boldsymbol{\tau}_1^T(k) \boldsymbol{\tau}_2(k) \geq \cos \gamma \|\boldsymbol{\tau}_1(k)\| \|\boldsymbol{\tau}_2(k)\| , \quad (12)$$

where γ is a Sector-of-Sight angle, which will be detailed later. Also, $\boldsymbol{\tau}_1(k) = \mathbf{X}(k+1) - \mathbf{X}(k)$ and $\boldsymbol{\tau}_2(k) = -\mathbf{X}(k)$.

- Terminal:

$$\mathbf{Y}(N) \subset \mathcal{B}_r , \quad (13)$$

where \mathcal{B}_r is a ball of radius r that is a user-defined parameter. We select \mathcal{B}_r to a desired tolerance, and this alerts the algorithm when a waypoint is successfully achieved.

We impose the guiding angle constraints (11)-(12) to ensure that the velocity vector at a chosen depth generally points towards the destination. This constraint reduces the number of depth choices to only those that provide a current that reduces the distance to the goal at each

time step. The implementation of this constraint was motivated by the work presented in Jouffroy et al. (2011), where an angle constraint is defined as a symmetric Sector-of-Sight about the line-of-sight between the actual position of the vehicle and the destination point. It is worth noting that the guiding angle constraints (11)-(12) imposed here exist only to speed up the convergence of the RCFMPC. This is in contrast to Jouffroy et al. (2011), where the conditions on the Sector-of-Sight must exist for the algorithm converge. The primary difference between the design of the controller in Jouffroy et al. (2011), and that presented here is the application domain. Here, we consider an open-ocean scenario where currents in many directions exist at most time steps. In Jouffroy et al. (2011), the authors consider a coastal region where the currents are tidally-driven. This, regardless of the depth chosen, currents only exist in a single direction at each time step.

Having presented the RCFMPC, we now continue with a discussion on the uncertainties and propose a solution to the presented problem.

- **Uncertainties:** We can see that the problem Eq. (3) is equivalent to

$$\mathbf{X}(k+1) = \bar{\mathbf{A}}(k)\mathbf{X}(k) + \bar{\mathbf{B}}(k)\mathbf{U}(k) + \mathbf{W}\boldsymbol{\omega}(k), \quad (14)$$

where $\bar{\mathbf{A}}(k)$ and $\bar{\mathbf{B}}(k)$ are nominal values of the pair $[\mathbf{A}(k), \mathbf{B}(k)]$ at time k , and $\boldsymbol{\omega}(k)$ is the uncertainty at time k . So, solving Eq. (3) is the same as providing solutions to the problem $\mathbf{X}(k+1) = \bar{\mathbf{A}}(k)\mathbf{X}(k) + \bar{\mathbf{B}}(k)\mathbf{U}(k)$ at vertices of $\Omega(k)$ for each point of time.

- **Solution:** Observing the objective Eq. (5) with constraints Eqs. (7), (8), (9), (11), (12) and (13), we state that the RCFMPC is a hybrid, nonlinear problem. There is no direct method to solve this problem explicitly. However, here we take advantage of the constraint Eq. (9), noting that \mathcal{S} is a finite set with deterministic values. As a result, the RCFMPC is feasible by only allowing a finite set of values for the control input. Additionally, we allow for the float to *sit* on the sea floor (experiencing near-zero currents) and wait for favorable currents to arise in the water column above.

6. CONCLUSION

We present the result of applying the proposed RCFMPC to a simulated scenario to steer a profiling float between the first two predetermined waypoints of the path computed in Section 4.3. We set the radius r of the ball \mathcal{B}_r to 350 m, and let $n_u = 20$. The plot in Fig. 4 shows the computed control for the float as a plot of prescribed depth with respect to time. Since we restrict the float to remain at a given depth for at least one hour, and changing depth can occur on the order of minutes, we express the changes in depth as occurring instantaneously. The next phase of this study is to move away from a point-mass model, and incorporate realistic buoyancy dynamics via a Kalman filter.

Given the predicted currents, and the mission constraints described earlier, it takes the float 52 hours to navigate from the start location to the first waypoint in the computed path shown in Fig. 3(a). Note that there were multiple instances when the currents on the sea surface were favourable to exploit to make progress toward the goal. In the time epoch before rising to the sea surface, the vehicle descends to the seabed; ensuring the float will

travel through the whole water column. This behavior is observed at $t = 10, 18, 27, 35,$ and 45 hours.




Fig. 4. A plot of the prescribed depth of the float versus time as computed by the RCFMPC.

Figure 5 presents the path executed by the profiling float, as projected up to the sea surface. The starting location is marked by a green circle, and the desired goal is given by a red star. The final destination achieved by the vehicle is denoted as a blue square. We remark that the final destination of the float and the goal location will rarely coincide due to the parameter r . Once the float is inside this ball, the waypoint is considered achieved. In practice, we must choose r sufficiently large to ensure convergence of the controller, but small enough to have the vehicle execute the basic path prescribed. We denote the executed path of the profiler by a dashed red line, and the prescribed path by a solid black line. It is evident from Fig. 5, that a profiling float is capable of utilizing ocean currents to broadly achieve a path that was computed by maximizing predicted controllability.




Fig. 5. The path followed by the profiling float (dashed red line) by executing the control presented in Fig. 4. The prescribed path is given by the solid blue line.

As the presented work was conducted on simulation, there are multiple areas for future work. We are investigating the design of an optimal controller that minimizes the switchings (depth changes), thus minimizing energy consumption, to achieve the same computed path. We cannot follow all of the previously mentioned constraints, but aim to increase persistence of the vehicle in the environment. The primary focus is to test our controller on a vehicle

during field trials. Research is currently being undertaken to deploy a profiling float in the considered ocean region, which implements the proposed controller.

7. ACKNOWLEDGEMENTS

This work was supported in part by the Early Career Academic Recruitment and Development (ECARD) Program of the Queensland University of Technology. The ROMS ocean modeling research described in this publication was carried out by the Jet Propulsion Laboratory (JPL), California Institute of Technology, under a contract with the National Aeronautics and Space Administration (NASA).

REFERENCES

- Alberto Alvarez, Andrea Caiti, and Reiner Onken. Evolutionary path planning for autonomous underwater vehicles in a variable ocean. *IEEE Journal of Oceanic Engineering*, 29(2):418–429, 2004.
- Mathieu Belbeoch. Argo - part of the integrated global observation strategy. <http://www.argo.ucsd.edu/index.html>, 2010. Last viewed March 2011.
- Kristen P. Dahl, David R. Thompson, David McLaren, Yi Chao, and Steve Chien. Current-sensitive path planning for an underactuated free-floating ocean sensorweb. In *IEEE/RSJ International Conference on Intelligent Robotic Systems*, pages 3140–3146, San Francisco, CA, September 2011.
- Eric A. D’Asaro, David M. Farmer, James T. Osse, and Geoffrey T. Dairiki. A lagrangian float. *Journal of Atmospheric and Oceanic Technology*, 13:1230 – 1246, 1996.
- R. E. Davis, D.C. Webb, L.A. Regier, and J. Dufour. The autonomous lagrangian circulation explorer (alace). *Journal of Atmospheric Ocean Technology*, 9:264–285, 1992.
- Russ E. Davis. Observing the general circulation with floats. *Deep-Sea Research*, 38(Suppl. 1):531–571, 1991.
- Barolome Garau, Alberto Alvarez, and Gabriel Oliver. Path planning of autonomous underwater vehicles in current fields with complex spatial variability: an A* approach. In *Proceedings of the IEEE International Conference on Robotics and Automation*, Barcelona, Spain, 2005.
- Joshua Grady Graver. *Underwater Gliders: Dynamics, Control and Design*. PhD thesis, Princeton University, 2005.
- Gwynn Griffiths, Clayton Jones, James Ferguson, and Neil Bose. Undersea gliders. *Journal of Ocean Technology*, 2(2):64–75, 2007.
- Jerome Jouffroy, Qiuyang Zhou, and Oliver Zielinski. Towards selective tidal-stream transport for lagrangian profilers. In *MTS/IEEE Oceans*, Kona, HI, September 2011.
- Dov Kruger, Rustam Stolkin, Aaron Blum, and Joseph Briganti. Optimal auv path planning for extended missions in complex, fast-flowing estuarine environments. In *Proceedings of the IEEE International Conference on Robotics and Automation*, Rome, Italy, 2007.
- Naomi E. Leonard, Derek A. Paley, Russ E. Davis, David M. Fratantoni, Francois Lekien, and Fumin Zhang. Coordinated control of an underwater glider fleet in an adaptive ocean sampling field experiment in monterey bay. *Journal of Field Robotics*, 27(6):718–740, 2010. ISSN 1556-4967.
- B. McGilvray and Chris Roman. Control system performance and efficiency for a mid-depth lagrangian profiling float. In *MTS/IEEE OCEANS 2010*, Sydney, Australia, May 2010.
- D.A. Paley, F. Zhang, and N.E. Leonard. Cooperative control for ocean sampling: The glider coordinated control system. *IEEE Transactions on Control Systems Technology*, 16(4):735–744, July 2008.
- C. Petres, Y. Pailhas, P. Patron, Y. Petillot, J. Evans, and D. Lane. Path planning for autonomous underwater vehicles. *IEEE Transactions on Robotics*, 23(2):331–341, 2007.
- Dean Roemmich, Stephen Riser, Russ Davis, and Yves Desaubies. Autonomous profiling floats: Workhorse for broad-scale ocean observations. *Marine Technology Society Journal*, 38:21–29, 2004.
- H.T. Rossby, E.R. Levine, and D.N. Connors. The isopycnal swallow float—a simple device for tracking water parcels in the ocean. *Progress In Oceanography*, 14:511 – 525, 1985. ISSN 0079-6611.
- O. Schofield, J. Kohut, D. Aragon, E.L. Creed, J.G. Graver, C. Haldman, J. Kerfoot, H. Roarty, C. Jones, D.C. Webb, and S. Glenn. Slocum gliders: Robust and ready. *Journal of Field Robotics*, 24(6):473–485, 2007.
- Alex Schwital and Chris Roman. Development of a new lagrangian float for studying coastal marine ecosystems. In *MTS/IEEE OCEANS 2009*, Bremen Germany, 2009.
- A.F. Shchepetkin and J.C. McWilliams. Quasi-monotone advection schemes based on explicit locally adaptive dissipation. *Monthly Weather Review*, 126:1541–1580, 1998.
- Alexander F. Shchepetkin and James C. McWilliams. The regional oceanic modeling system (ROMS): a split-explicit, free-surface, topography-following-coordinate oceanic model. *Ocean Modelling*, 9:347–404, 2005.
- Ryan N. Smith and Matthew Dunbabin. Controlled drift: An investigation into the controllability of underwater vehicles with minimal actuation. In *Proceedings of the Australasian Conference on Robotics and Automation*, July 2011. Submitted.
- Ryan N. Smith, Yi Chao, Peggy P. Li, David A. Caron, Burton H. Jones, and Gaurav S. Sukhatme. Planning and implementing trajectories for autonomous underwater vehicles to track evolving ocean processes based on predictions from a regional ocean model. *International Journal of Robotics Research*, 29(12):1475–1497, October 2010a.
- Ryan N. Smith, Jonathan Kelly, Yi Chao, Burton H. Jones, and Gaurav S. Sukhatme. Towards improvement of autonomous glider navigation accuracy through the use of regional ocean models. In *Proceedings of the 29th International Conference on Offshore Mechanics and Arctic Engineering*, pages 597–606, Shanghai, China, June 2010b.
- Ryan N. Smith, Mac Schwager, Stephen L. Smith, Burton H. Jones, Daniela Rus, and Gaurav S. Sukhatme. Persistent ocean monitoring with underwater gliders: Adapting sampling resolution. *Journal of Field Robotics*, 28(5):714 – 741, September/October 2011.
- Ryan N. Smith, Jonathan Kelly, and Gaurav S. Sukhatme. Towards improving mission execution for autonomous gliders with an ocean model and kalman filter. In *Proceedings of the IEEE International Conference on Robotics and Automation*, Minneapolis, MN, May 2012. Accepted, to appear.
- K. Szwajkowska and F. Zhang. A lower bound on navigation error for marine robots guided by ocean circulation models. In *Proc. 2011 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS 2011)*, pages 3583–3588, San Francisco, CA, 2011.
- Jonas Witt and Matthew Dunbabin. Go with the flow: Optimal path planning in coastal environments. In J. Kim and R. Mahony, editors, *Proceedings of the 2008 Australasian Conference on Robotics & Automation (ACRA 2008)*, Canberra, ACT, 2008. ISBN: 9780646506432.