

Design and Development of a Sampling Platform to Study Long Distance Seed Dispersal

Jonathan Ogle*, John Naglak*, Isaac Blue-Eyes*, Collin Miller*,
Aleph Baumbach*, Peter Prentis[†], York R. Smith[‡] and Ryan N. Smith*

*Department of Physics and Engineering, Fort Lewis College, Durango, CO 81301, USA

[†]School of Earth, Environmental and Biological Sciences,
Queensland University of Technology, Brisbane, 4001 Australia

[‡]Metallurgical Engineering Department,
University of Utah, Salt Lake City, UT 84112, USA

Corresponding Author Email: rnsmith@fortlewis.edu

Abstract—Recent theoretical research has shown that ocean currents and wind interact to disperse seeds over long distances among isolated landmasses. Dispersal of seeds among isolated oceanic islands, by birds, oceans and man, is a well-known phenomenon, and many widespread island plants have traits that facilitate this process. Crucially, however, there have been no mechanistic vector-based models of long-distance dispersal for seeds among isolated oceanic islands based on empirical data. Here, we propose an experimental methodology and present a novel sensor platform to circumvent these limitations and directly estimate a mechanistic, vector-based model of seed dispersal in the ocean.

We have developed seed analogues, or *pseudoseeds*, outfitted with wireless sensor technology that will enable high-fidelity tracking as they disperse across large distances in the ocean. The *pseudoseeds* are precisely designed to mimic actual seed buoyancy and morphology enabling realistic and accurate, vector-based dispersal models of ocean seed dispersal over vast geographic scales.

I. INTRODUCTION

The oceanographic community has an increasing desire for persistent observation platforms that are able to stay on deployment for long time periods (months to years). Propeller-driven vehicles are adequate for rapid data collection, but are limited in endurance and spatial coverage. Vehicles with minimal actuation have been developed, facilitating energy savings and offering increased endurance to study dynamic features, see e.g., [1]. Although such vehicles have a longer endurance, their motion is determined primarily by ocean currents rather than their own control.

Cain et al, has shown that ocean currents and wind interact to disperse seeds over long distances among isolated landmasses [2]. Seed migration between oceanic islands by birds, oceans, and humans are well-known dispersal phenomenon, and many island plant species have traits that facilitate these migrations [3]–[6]. For example, ocean dispersal is responsible for over 78% of plant colonists arriving on the volcanic island of Surtsey, highlighting the importance of this vector for island colonization. Although we know that buoyant seeds of many coastal plants have dispersed long distances to colonize isolated islands, remarkably little is known about the long distance dispersal (LDD) of seeds

in oceanic environments; there have been no mechanistic, vector-based models of oceanic LDD based on empirical data [2]–[4], [7], [8].



Fig. 1: An single image of actual coconut (left), and the associated 3D reconstruction (right) of the same coconut used to design the shell for the *pseudoseed*.

To gather the empirical data for the study of oceanic LDD, we propose to design a sensor platform as a seed analogue, that mimicks the morphology of a LDD seed candidate. The candidate chosen is *Cocos Nucifera*, as seen in Fig. 1. It has been shown that *Cocos Nucifera*, i.e., coconuts, can remain buoyant and fertile after long periods of time floating in the ocean [9]. Even coconuts that became water logged remained buoyant, but floated slightly below the sea surface. The authors are currently conducting a follow-on study to support these findings; seeds have been floating in salt and fresh water since 5 November 2013¹. The proposed *pseudoseed* must also be able to remain at sea for long periods (>1 year), while continually transmitting location data for tracking their LDD to build an empirical, vector-based model for the LDD process. In this paper, we present a detailed design of a long-duration sampling platform and an experimental procedure for the study of ocean currents as a vector for the LDD of seeds over vast geographic scales.

¹At the time of submission of this manuscript, the seeds have been floating for more than 4 months

II. BACKGROUND AND MOTIVATION

Until recently, LDD theory has been considered irrelevant due to the emergence of vicariance biogeography theory [8], which suggests that for island landmasses to have present a plant species, it must have been in extremely close proximity, or have directly broken off a landmass that was a natural carrier of the plant species [10]. Ancestral area reconstruction of certain phylogenies has shown that this is not true and that vicariance theory can not be the only means for plant migration [10]. Recent work has suggested that LDD largely affects invasion and migration rates [8]. It is currently only hypothesized that LDD in the ocean can be represented as a fat tailed dispersal kernel, see the representation in Fig. 2. Note that the a significant number ($> 80\%$) do not disperse a distance of more than 10 m, implying that only a small percentage of dropped seeds actually make it off of their original beach. Further, the fat tail of the dispersal kernel may only comprise 1% of the total dropped seeds, but this percentage remains constant after some threshold distance from shore. These data are difficult to obtain because 1) LDD is rare and stochastic in nature, and 2) reconstructing past patterns of LDD is difficult in most organisms.




Fig. 2: A representation of a fat tailed dispersal kernel for seeds of coastal plants that remain buoyant for long time periods immersed in the ocean.

Usually, biogeographical research is used only as a narrative addition to phylogenetic studies and lacks the scientific rigour other research fields are accustomed to [10]. In certain cases, including that of LDD, when the research questions can be formed as a hypothesis, the scenario can be tested [10]. In the case of LDD, there is currently no platform capable of carrying out this study. No empirical data has been presented to support LDD theory. Instead the hypothesis exists to explain facts formed from ancestral area reconstructions methods, and other biological methods [10].

Cocos nucifera, the coconut palm, is an ideal seed source for this study. The seed is large in size, and it has been found on the beaches of multiple continents. The coconut palm morphology is an ideal candidate platform for housing

significant battery storage, different sensors, and maintaining buoyancy. An example location for the observed effects of LDD is within the Pacific Ocean and Coral Sea between Fiji and Australia for *Cocos Nucifera* [5], as well as other plants [4], see Fig. 3. Here, plant geneticists have shown direct links between coconut trees in Fiji and those growing among islands within the Great Barrier Reef [5].




Fig. 3: The geographic location of Fiji relative to Australia representing the scale required for the study of oceanic LDD.

III. SYSTEM DESIGN

The primary design constraint for the *pseudoseed* is the ability to carry enough on-board power to track position and gather important oceanographic data over the course of a deployment lasting longer than one year. This system must be capable of identifying and transmitting location, along with other important science e.g., acceleration, heading, temperature and/or salinity data.

Salinity and temperature information are standard oceanographic measurements for any sensor platform. Accelerometer information, along with magnetic heading can be used to gather information about wave height, wave period and migration direction. These components can also be combined with ocean models to predict a coconut's path. The ability to monitor O_2 , pH, chlorophyll, and/or turbidity would also be ideal measurements contributing to ocean science. The major factor in sensor selection and implementation was cost. Proper LDD studies will require a large population of seeds (>100). Also, we must expect that some seeds will get lost during the study. Here, we propose a realistic budget that each seed costs less than \$1,000.

A. Shell Design

The *pseudoseed* shell must house electrical components, must be waterproof, accessed easily, and also must properly mimic the morphology of the coconut. The center of mass (C_G) of our system must also match that of our design. This means all electrical equipment placement must allow the *pseudoseed* to maintain the same center of buoyancy (C_B) as the natural coconut counterpart. A major focus in the shell design is cost. A cheaper design will allow for a larger number to be constructed and deployed. To facilitate cost effectiveness for the shell, we used a prefabricated watertight container to house the electronics and batteries.




Fig. 4: Exploded view of electronics, battery, polycarbonate housing, and *pseudoseed* shell.

As shown in (Fig 4), the prefabricated enclosure is secured inside the outer shell, formed from closed-cell epoxy expanding foam. This foam is very resilient to water absorption. For our design the foam expands in a plaster mold derived from a real coconut. A single longitudinal seam is secured with a band of glass-re-enforced-plastic. It is oriented such that the seal is above waterline under normal conditions. This design allows for reuse of materials with the removal of the seed material.

1) *Modeling Real Coconuts*: To understand how the physical characteristics of the coconut in the ocean would change with respect to time, a small population of 16 actual coconuts were used to conduct water adsorption studies. In Fig. 5, we show the change in mass over time of these coconuts in salt water (red), fresh water (blue), and ambient air (green). The coconuts masses are compared on a relative scale, comparing original mass (m_o) to the mass over time for each seed (m) as seen in Eqn. 1.

$$m_r = \frac{m}{m_o} \quad (1)$$

These data show that each coconut placed in water adsorbs water mass until it reached an absorption limit is reached (see Fig. 5. Comparing the absorption of mass differences between the fresh and salt water specimens, we see little difference between the absorption rates. There is some variance across all the coconuts. Most specimens had a large gain in mass initially slowing after approximately three weeks.




Fig. 5: Changes in relative mass over time for coconuts immersed in salt water (red), fresh water (blue), and ambient air (green) over time.

Three of the coconuts also began to absorb more water again after this initial three week gain. As expected, the results also show that the coconuts left out of the water lost mass. This study is still ongoing and results are only preliminary. The data gathered in this study support the findings presented in [9].

For our design it was necessary to determine the C_G and C_B of the coconut. The C_G was calculated using moments of inertia and basic inclining experiments as outlined in [11]. Due to the symmetric nature of the coconut, it was assumed




Fig. 6: Visual SFM sparse 3D reconstruction process.

that the vertical center of mass was through the beginning and end node of the coconut husk. The C_B of the *pseudoseed* was matched to the coconut that the design construction was based from and adjusted through model testing at a 1 : 1 scale.

2) *3D Coconut Reconstruction*: The primary objective for performing 3D reconstructions is to accurately capture the morphology of an actual coconut. Additionally, 3D reconstructions were used to determine an accurate volume of the coconuts throughout the absorption tests. The goal of creating a mechanistic, vector-based model of LDD, by oceanic surface currents relies heavily on having a *pseudoseed* resemble an actual coconut. Generating a 3D model successfully enabled the creation of an accurate coconut shell. A final 3D reconstruction of a representative coconut is shown in Fig 1, alongside the seed it was modeled after.

The technique of photogrammetry was chosen as the 3D reconstruction process. Photogrammetry uses non-contact imaging, such as photos by digital camera to collect optical information for 3D model generation [12]. Visual SFM software [13] was used to generate a photogrammetric coconut model from coconut photos [12]. Visual SFM is very robust, and requires no prior camera calibration. Internal calibration is done within the software using the camera/lens parameters from the EXIF tags in the jpeg photos. Figure 6 displays the Visual SFM interface, with the recorded camera images and associated poses.

Photogrammetry with monocular image data is a scale-less method, therefore it was crucial to incorporate a known dimension in the coconut photos. The represented range data in the Visual SFM [13] is presented in point cloud format, which contains no absolute scale. The point cloud format requires no specific order and presents the 3D points collected using a relative, 3D coordinate system. A line of length 5 cm

was marked on each coconut establishing an absolute scale and dimension. This reference line was used to appropriately scale each coconut model to the proper absolute dimensions [12].

Using 3D reconstruction techniques from image data, volumetric studies of two coconuts immersed in salt water were conducted to observe changes. This study provided insight on how the volume and surface area of the coconuts could change during the time at sea. It was found for coconut *A* (a larger coconut), that as the mass changed from 2,077.5 g to 2,260.1 g, its volume also changed from 5,520 cm³ to 5,283 cm³. It was found for coconut *5* (a smaller coconut), that as the mass changed from 848.3 g to 2,109.9 g, and the volume also changed from 2,690 cm³ to 2,800 cm³. Unexpectedly, coconut *A* actually lost 5% of its original volume. Both coconuts show that there is a significantly large gain in mass with a negligible change in volume.

B. Sensors

While the main directive of this design was to create a platform capable of monitoring the location of a device with the morphology of a LDD seed candidate, other information could also be collected. However, accommodation of sensors requires additional power. In our design, we chose to accommodate a temperature sensor, and accelerometer/magnetometer. Multiple sensors were evaluated for our initial design, but were eliminated from the final design based on cost and power constraints.

1) *Location*: For location, we chose to implement the SPOT Connect GPS module. The SPOT Connect transmission coverage map confirms that the SPOT Connect is a viable candidate for sending data from the *pseudoseeds* for most oceanic environments across the globe [14]. The accuracy of the SPOT Connect is reported as 10 m. This accuracy was experimentally validated through a series of experiments




Fig. 7: Distance from the actual location of the device to the recorded GPS reading. The different colors (red and green) represent data collected on separate days.



Fig. 8: Location information gathered along a path from the SPOT Connect device overlaid on a Google Maps image. The diamonds represent specific locations of the device, with the red pins the recorded GPS location.

relaying a GPS location multiple times and observing the group variance. Fig 7 shows that the accuracy of the GPS signal was 5 ± 3 meters radially. This variance is orders of magnitude smaller than the scale on which LDD dispersal is observed on ($> 3,000$ km). Figure 8 shows a proof of concept for the GPS, that was conducted by collecting a track. This information, along with the magnetometer reading allows for vector based heading and path observation.

To control the SPOT connect with a microcontroller, an open source design option from Sparkfun was implemented. SPOT Connect consists of a GPS receiver and Satellite transceiver with a micro-controller and Bluetooth module to allow it to receive custom text messages from the users smart phone. The layout of the device allows for the GPS/Satellite/Micro-controller portion to be separated and the power and Bluetooth elements to be discarded. Spark-

fun supplied the development for the implementation of an alternate power supply, and the control and communication protocol [15].

2) *Accelerometer*: A 6-axis magnetometer/accelerometer System-in-Package is utilized to gather motion data that can be used to get wave spectra. The System-in-Package includes ± 2 to 8 g scale-able, 3 degree-of-freedom acceleration and ± 1.3 to 8 Gauss magnetometer output at 12-bit resolution.

3) *Temperature*: The pseudoseed is equipped to measure ocean surface temperature with a silicon band-gap sensor. The 12-bit output of the sensor gives a precision of $0.0625^\circ C$ and the sensor has an accuracy of $0.5^\circ C$ [16]. In testing, the sensor measured an average water temperature of $22.1610 \pm 0.5^\circ C$ at 7.5 Hz sample rate. The temperature of the water was measured with three control methods, an Elmetron PT-105, a Comark C28 K-type thermocouple, and a General Instruments T656 non-contact thermometer. The controls measured $22.0 \pm 0.3^\circ C$, $22.1 \pm 0.2^\circ C$ and $22.4 \pm 2^\circ C$ respectively. These compared well with the measurement from the chosen silicon band-gap sensor.

C. Microcontroller

A central processor is necessary to collect data and manipulate it to suitable output formats. For this application, the Atmel ATmega328p 8-bit microcontroller provides the best balance of power efficiency, I/O features, computational ability and memory, low cost, and low weight. Some features of the ATmega328p include master/slave Serial-Peripheral Interface (SPI), Inter-Integrated Circuit (I^2C /TWI), USART, 8-bit Pulse-Width-Modulation(PWM), and 8-channel 10-bit analog-to-digital converter (ADC) hardware [17]. General purpose pins enable integration of all aforementioned sensors, as well as up to 3 additional sensors for future expansion or alternate applications. An entire system diagram is shown in Fig. 9.

The ATmega features five power save modes, with on-the-fly clock pre-scale adjustment and an internal 8 second watchdog timer. This allows the microcontroller to sleep for 8 seconds at $4.6 \mu A$ (3.3 V system voltage). The watchdog timer overflow interrupt triggers the microcontroller to iterate a count variable every 8 seconds. The cost of the ATmega328p is less than US\$2 in small quantities. An additional motivation for selecting this microcontroller is the extensive community and open-source support available because of its implementation in the popular Arduino platform.

D. Battery

Initial power source studies examined the idea of implementing an on-board power generation system along with power storage. While the idea of implementing a system that stores power from wave energy or solar energy is attractive, it would require additional circuitry, would introduce significant uncertainties in function, and the opportunity for potential error would compromise the stability of our design. For this reason, it was determined that the *pseudoseed* design would employ only batteries as the power source.




Fig. 9: *Pseudoseed* function block diagram at subsystem level.




Fig. 10: Estimated power discharge profile of a battery over the period of one week.




Fig. 11: Discharge profile of various battery designs. Note that the Alkaline battery profile is hidden underneath the Tadiran discharge line.

When active, the expected hourly power draw from the *pseudoseed* is 58 mAh, and while in sleep mode, the expected power draw is 180 pAh. For a 1-year deployment, this equates to 22 Ah. We analyzed multiple battery types taking into account self-discharge rate, duty cycles, and charge density. The discharge profile of a battery over a period of one week can be seen in Fig. 10. The Tadiran PulsesPlus Lithium Thionyl Chloride cell of bobbin construction with sealed hybrid layer capacitor was the best selection [18], as shown through a year-long discharge profile in Fig. 11. Accounting for internal self-discharge, the battery storage required is 26 Ah. A single D-cell battery with one integrated capacitor is necessary to maintain our system for approximately 1.5 years [19].

IV. DATA HANDLING

A. Processing

As previously mentioned, a microcontroller is used to collect information from each sensor in the *pseudoseed*.

To optimize operating time, the SPOT Connect is instructed to obtain a GPS coordinate fix while temperature and accelerometer/magnetometer information is simultaneously collected. The microcontroller then proceeds to process the accelerometer data. The basic process for each data recording cycle is presented in Algorithm 1. A standard full-size SDHC memory card is used to back up high resolution data throughout the duration of the mission. This provides external memory the micro-controller may access and allows for removal of a system log after the completion of the mission. The waveform information, magnetic heading, and average temperature data are then sent to the SPOT connect for transmission to shore.

B. Accelerometer

Accelerometer data in the heave direction (vertical) can be transformed and condensed using a Fast Fourier Transform (FFT). For the ATmega platform this is done using the

Algorithm 1: Microcontroller Processing

```
1 BEGIN: Initialize components
2 while Battery level is OK do
3   Collect GPS;
4   Collect accelerometer;
5   Read temperature;
6   Process accelerometer data;
7   Write raw data to SD card;
8   Compile 41 character data packet;
9   Transmit data packet and location via SPOT;
10  Low-power sleep to timer interrupt;
11 end
12 Enter long sleep mode
```

modified code FixFFT [20]. Since the microprocessor is 8-bit, to process the accelerometer as an FFT, the data need to be split into groups of 128 data points as shown in Alg. 2. The FFT, when coupled with time of collection, can be used to determine the intensity (amplitude) of each wave frequency. The significant wave height (H_s), defined as four times the standard deviation of the square root of the zeroth-order moment of the wave spectrum, can be determined from the FFT information. Further, the peak wave period (T_p) can be extracted from the accelerometer data.

Algorithm 2: Significant wave height analysis

```
1 Gather accelerometer data
2 Determine length of accelerometer data (L)
3 if  $L \nmid 128$  then
4   Concatenate with zeros so that  $L \mid 128$ ;
5 end
6 Let  $n = \frac{L}{128}$ ;
7 for  $j = 1, \dots, n$  do
8   Process FFTj;
9 end
10 Average(FFT)1n;
11 Compute major modes;
12 Compute  $H_s, T_p$ ;
```

This code will output the average FFT of multiple runs of data. Each FFT is saved directly to the microSD card where it can later be called during the data processing. With a character limitation for the SPOT connect system, the FFT is used to determine H_s and T_p so that only a few characters need to be transmitted back to shore.

C. Transmission

One of the largest obstacles given the *pseudoseed* design constraints was the need to transmit the collected data back to shore. The SPOT Connect satellite communicator allows for transmission of location along with a modifiable, 41-character message. For this to work within the scope of our design method, the SPOT Connect satellite communicator must be modified to communicate with our microcontroller,

so that the microcontroller can control when the SPOT device determines location via GPS, and can then package a message for transmission that includes the necessary data.

The SPOT device draws 33 mAh when active, and at most will require 10 minutes to determine location, and transmit data. Since data transmission is limited to 41 characters, to maximize data transmission, all information must be processed into its smallest form. The 41 character limitation does not include the GPS location [21]. For the current design, we are using 3 characters for H_s , 3 for T_p , 4 for temperature, 3 for battery state, and 18 for the three major waveforms computed from the FFT of accelerometry data. This leaves 10 additional characters for future sensor expansion, alternative applications, or the transmission of additional resolution of existing sensor data.

V. PROPOSED FIELD EXPERIMENTS

The motivation behind designing these *pseudoseeds* was to create a vehicle capable of collecting data for LDD theory. The study of LDD using *pseudoseeds* can be divided into two phases. The first phase determines the threshold distance that a seed must reach so that it is guaranteed not return to the original beach. The second phase is the actual dispersal of the seeds from this threshold distance across large expanses of ocean.

The first phase will involve high-resolution tracking of multiple coconuts' locations to understand the return patterns based off the distance each seed moves away from the beach. Data for this component of the study will include location, and wave spectrum information collected and transmitted approximately every 10 minutes. This tracking data can be directly compared to fat tailed dispersal kernel representations, similar to that presented in Fig. 2. This comparison can be used to directly identify the threshold at which seeds will continue to move away from their host beach. With a limited population of seeds used in testing, and more than 80% of the seeds returning to the original beach, returned seeds will be collected, recharged, and sent back out to dramatically increase the population size for this portion of the study.

The second phase will then release the full population of *pseudoseeds* at or beyond the identified threshold distance from the first phase. During this second phase, each seed will only collect and transmit data once each day. Each transmission will include the location, temperature, wave spectrum, and battery level information as detailed earlier. Upon the beaching of a seed, or nearing the extent of the battery life, the seed will then be collected. Automated detection of beaching is included in the accelerometer data analysis, with a *Come and get me* message sent when landfall is made.

If further data collection is necessary each seed can be recharged, and prepared for another release. With the vector-based data collected from these two phases, we will be able to produce an empirical, mechanistic, vector-based model of oceanic LDD. From this model we will be able to determine

whether or not LDD theory supports the actual oceanic migration patterns of coconuts and other seeds.

VI. CONCLUSIONS

Here we proposed a design for a *pseudoseed* vehicle. The design maintains the morphology of a *pseudoseed*, while also collecting and transmitting the data necessary to perform LDD theory studies. By modification to the SPOT transmitter, we show the successful integration of data observation mediums directly with transmission of that data on a global platform. 128-bit resolution of the FFT data has proven to provide excellent information on waveform intensity that could be used for predictive path modelling.

This design platform is also very modifiable to be used for different observation and analysis, with it's only limitation the fact that it's migration is directly dependent on wind and water currents. Other oceanic studies could easily be implemented using this platform so long as the sensor only needed to follow weather currents.

VII. FUTURE WORK

The major draw on duration of observation for this platform is in the efficiency of the electronics design. Further design efficiency can be reached by engineering a single board electronics design. Additionally a CT sensor capable of recording ocean salinity and temperature would be ideal for salinity studies, but is currently limited by price for resolution. One option is through StarODI [22]. Other interesting oceanic studies this platform could be used form might implement a Geiger counter to observe ocean surface radioactivity.

The hull design for this project is also somewhat function limited. With a sealing process being necessary each time the seed must be refitted for expedition. The design of a mold for the fabrication of polycarbonate injection shell form would be a fruitful venture for the large scale fabrication of a more reusable hull. This would include a new seal design that would be implemented above water, and would make any modification to the electronics significantly easier.

ACKNOWLEDGMENTS

This research was supported in part by a Fort Lewis College Natural and Behavioral Science student research grant, a contribution from The Colorado Alliance for Minority Participation, and a Fort Lewis College Dean's award for innovative research. P. Prentis is supported by the Queensland University of Technology Early Career Academic Recruitment and Development (ECARD) program.

The authors would additionally like to thank Kona Origins for supplying the coconuts utilized in this study.

REFERENCES

- [1] R. N. Smith, Y. Chao, P. P. Li, D. A. Caron, B. H. Jones, and G. S. Sukhatme, "Planning and Implementing Trajectories for Autonomous Underwater Vehicles to Track Evolving Ocean Processes Based on Predictions from a Regional Ocean Model," *The International Journal of Robotics Research*, vol. 29, no. 12, pp. 1475–1497, Oct. 2010. [Online]. Available: <http://ijr.sagepub.com/cgi/doi/10.1177/0278364910377243>
- [2] M. L. Cain, B. G. Milligan, and A. E. Strand, "Long-distance seed dispersal in plant populations," *American Journal of Botany*, vol. 87, no. 9, pp. 1217–1227, Sep. 2000. [Online]. Available: <http://www.amjbot.org/content/87/9/1217.full>
- [3] R. Nathan, F. M. Schurr, O. Spiegel, O. Steinitz, A. Trakhtenbrot, and A. Tsoar, "Mechanisms of long-distance seed dispersal," *Trends in Ecology & Evolution*, vol. 23, no. 11, pp. 638–647, Nov. 2008. [Online]. Available: <http://linkinghub.elsevier.com/retrieve/pii/S0169534708002723>
- [4] P. Prentis, "Seed dispersal, germination and fine-scale genetic structure in the stream lily, *helmholtzia glaberrima* (philydraceae)," Ph.D. dissertation, Queensland University of Technology, 2007.
- [5] J. Smith, "Drift disseminules on fijiian beaches," *New Zealand Journal of Botany*, vol. 28, no. 1, pp. 13–20, 1990. [Online]. Available: <http://www.tandfonline.com/doi/abs/10.1080/0028825X.1990.10412339>
- [6] R. N. Smith, P. Prentis, K. Langendoen, and P. Corke, "Pseudoseeds: Investigating long-distance, ocean seed dispersal with wireless sensors," in *IEEE/RSJ International Conference on Intelligent Robots and Systems, Workshop on Robotics for Environmental Monitoring*, 2011.
- [7] R. Nathan, "Long-distance dispersal of plants." *Science*, vol. 313, no. 5788, pp. 786–788, Aug. 2006. [Online]. Available: http://adsabs.harvard.edu/cgi-bin/nph-data_query?bibcode=2006Sci...313..786N&link_type=EJOURNAL
- [8] S. I. Higgins, R. Nathan, and M. L. Cain, "Are long-distance dispersal events in plants usually caused by nonstandard means of dispersal?" *Ecology*, vol. 84, no. 8, pp. 1945–1956, 2003. [Online]. Available: <http://www.esajournals.org/doi/abs/10.1890/01-0616>
- [9] C. H. Edmondson, "Viability of coconut after floating in sea," *Occasional Papers of Bernice P. Bishop Museum, Hawai'i*, vol. 16, no. 12, pp. 293 – 304, December 1941.
- [10] M. D. Crisp, S. A. Trewick, and L. G. Cook, "Hypothesis testing in biogeography," *Trends in Ecology & Evolution*, vol. 26, no. 2, pp. 66–72, Feb. 2011. [Online]. Available: <http://dx.doi.org/10.1016/j.tree.2010.11.005>
- [11] R. Bhattacharyya, *Dynamics of Marine Vehicles*. John Wiley & Sons, 1978.
- [12] P. L. Falkingham, "Generating a photogrammetric model using Visual SFM, and post-processing with meshlab," Brown University, Tech. Rep., 2013.
- [13] C. Wu, "VisualSFM : A visual structure from motion system," University of Washington, Tech. Rep., 2014.
- [14] SPOT. (2014) SPOT coverage map. <http://www.findmespot.ca/en/index.php?cid=109>. [Online]. Available: <http://www.findmespot.ca/en/index.php?cid=109>
- [15] SparkFun. (2012, April) <https://www.sparkfun.com/products/retired/11088>. [Online]. Available: <https://www.sparkfun.com/products/retired/11088>
- [16] Maxim Integrated, *DS18B20 Programmable Resolution 1-Wire Digital Thermometer*, 2008.
- [17] Atmel Corporation, *Atmel 8-bit Microcontroller with 4/8/16/32KBytes In-System Programmable Flash*, 2012.
- [18] Tardiran, "Pulses plus battery system for high energy high power applications," 2013. [Online]. Available: <http://www.tadiranbatteries.de/pdf/articles/pulses-plus-battery-high-power.pdf>
- [19] Tardiran Batteries, "Pulsesplusâ lithium ion batteries for high-current pulse applications," Tech. Rep., 2013. [Online]. Available: <http://www.tadiranbat.com/index.php/pulses-plus-lithium-cells>
- [20] Arduino. (2010) Modified 8bit FFT in C. [Online]. Available: <http://forum.arduino.cc/index.php/topic,38153.0.html>
- [21] SPOT. (2014, February) Find me spot. [Online]. Available: <http://www.findmespot.com/en/index.php?cid=116>
- [22] STAR ODDI. (2014) Logging life science. <http://www.star-oddi.com/>. [Online]. Available: <http://www.star-oddi.com/>