Localizing a Wireless Node in a Multi-Agent System Using Kalman Filtering

Puneet Goel and Gaurav S. Sukhatme

University of Southern California, Los Angeles CA 90089, USA
puneet|gaurav@robotics.usc.edu

1 Introduction and Problem Definition

In order to autonomously navigate and perform useful tasks, a mobile robot often needs to know its exact position and orientation. The objective of this work is to estimate the position of a mobile node (we will call it the receiver, Rx) based on signals from other moving/stationary nodes (transmitters, Tx). The measurements are the straight line distances between the receiver and the transmitters. Our aim is to calculate the (x, y) position of the receiver given the (x, y) positions of the transmitters. A baseline approach is to use triangulation. If there are more than 3 transmitters then averaging the estimates obtained from various triangles provides a quick estimate. The key problem is that naive averaging treats each estimate equally. We propose instead to use Kalman filtering because it explicitly uses the the variances in the measurements. Indeed, the Kalman filter provides an optimum estimate in minimum mean-square error sense.

2 Kalman Filter

Kalman filtering is a recursive estimation procedure that uses sequential sets of measurements. In the experiments reported here the measurement vector used in the filtering is composed of the position estimates x and y. We are using Kalman Filter in a scenario where we do not have any position estimates for the next step. Therefore the system matrix $\mathbf{\Phi}$ is the identity matrix. The system noise covariance matrix $\mathbf{Q}$ is determined empirically. The values of measurement noise matrix $\mathbf{R}$ are the most important in our experiments.

$$\mathbf{\Phi} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \; \mathbf{Q} = \begin{bmatrix} 0.01 & 0 \\ 0 & 0.01 \end{bmatrix} \; \mathbf{R} = \begin{bmatrix} var(x) & cov(x, y) \\ cov(x, y) & var(y) \end{bmatrix}$$

3 Experimental Results

Kalman filter (KF) is implemented in simulation. We assume that the position (x, y) of each transmitter is known. Further we assume that the straight line distance between the transmitter and receiver is also known but it is corrupted by Gaussian noise. The variance in the noise depends linearly on the distance between the transmitter and receiver. To improve the performance of the KF we provide a good initial estimate of the receiver position. The initial estimate had a Gaussian noise of standard deviation 0.5 units added to the actual position of the receiver. After the initial estimate, we take two transmitters at a time, calculate the two possible positions of the receiver using the straight line distance measurements and use the one closer to our current estimate as the new measurement to the KF. So if there are 'n' transmitters there will actually be ${}^{n}C_2 = \frac{n(n-1)}{2}$ such measurements.

Figure 1 shows the performance of the KF versus averaging when a good



Fig. 1. A random distribution of nodes and performance of KF and averaging on that distribution. Standard deviation in the measurements is 10% ($s = 10$).

initial estimate was provided to the KF. Notice the oscillation in error as the number of transmitters increases: a new placement of transmitter can actually increase the error instead of decreasing it due to its bad positioning.

4 Discussion and Conclusion

We presented the application of Kalman filtering to a scenario where the measurements do not come as a time series. We described a technique for position estimation of a wireless node (e.g. mobile robot or any portable device) while using only the line-of-sight distance estimates from the node to other nodes in its environment. In reality we do not expect to have an even distribution of transmitters. Thus if we use averaging we might see that the error rises as number of transmitters increases, instead of going down. We have shown that the KF performs well with larger noise and a good initial estimate. However if we continue to get poor measurements then KF will keep disregarding them and stay close to its first estimate. Therefore, the need for a good first estimate is apparent.

The major motivation of this work is in distributed tasks. If the receiver is a mobile robot then we can use odometry to estimate its position in the propagation step of the KF. In that case we do not need to rely only on measurements, thus improving the performance of the KF based technique.

Note: Full report is available at www-robotics.usc.edu/~puneet/research/research.html