Experiments in Imitation Using Perceptuo-Motor Primitives

Stefan Weber, Maja J Matarić, Odest Chadwicke Jenkins
Computer Science Department
University of Southern California
941 West 37th Place, SAL 228, MC 0781
Los Angeles, CA 90089-0781
stefanwe,mataric,cjenkins@usc.edu

1. INTRODUCTION

Imitation is a powerful mechanism for learning new skills. However, it involves an intricate interaction between perceptual and motor mechanisms, both of which are complex in themselves. Recently, findings from neuroscience have discovered so-called "mirror neurons", which directly couple the observation of a certain movements and their motor execution [6]. We combine the notions of perceptual and motor routines with the function of mirror neurons into *primitives*. The primitives are used as a basis set of motion, serving as a vocabulary for classifying and imitating observed movements. For a detailed discussion of the biological inspirations for our model, see [4].

2. PRIMITIVES IN IMITATION

In the imitation model we envisage (Figure 1) and are continually developing, perceptuo-motor primitives encode movements invariant to exact Cartesian position, rate of motion, size, and perspective. The primitives represent a basis set of motion that can be mapped to a set of parametric motor controllers. We postulate a small set of innate primitives and a composition mechanism, based on sequencing and superposition, that allows for learning new behaviors which can themselves be used as composable elements. In this sense, all complex motions and skills are represented as combinations of the basis set of primitives. In turn, these primitives were themselves either learned (future implementation) or innate (present implementation). In this approach, the issues of how to represent the primitives and which ones to choose are the most fundamental and most challenging. In the work described here, we apply three different motor primitives out of a very generic set of four introduced in [2]. The three primitives generate straight line, elliptical, and oscillatory endpoint movement. The fourth type, postural primitives, are omitted, since they are achieved in intrinsic, joint-space coordinates, and this work focuses on task-space, in the Cartesian endpoint coordinate frame.

3. IMPLEMENTATION

The first step in our implementation was the development of a basic human torso tracking system. The algorithm tracks human features from silhouettes in a presegmented image sequence. The tracking system is described in detail in [7]. The extracted motion is now ready to be classified into the primitive set, based on vector quantization [1] applied to the endpoint of each arm. A key issue is how to represent the primitives in a form that is invariant to the spatial and temporal dimension of the data for the most parsimonious encoding. We use a sliding horizon window of normalized gradients along a smoothed version of the endpoint motion. Each instance of the window is a high-dimensional vector that is classified into the set of perceptual primitives based on Euclidean distance (Figure 2). The results of each horizon window are then grouped to adjacent windows in time based on similarity of classification. This operation provides a segmentation of the motion. The classifier must also determine the appropriate parameter values for the trajectories performed in each segment. The result of these operations is a set of motor functions ordered in time to be traversed by the endpoint of an arm. From the classification of the recorded motion into primitives, a parameterized function for interpolating an arm endpoint over a desired trajectory is given. These endpoint functions are used to generate a sequence of Cartesian via points that represent the endpoint motion for traversal by the imitator. However, these must first be projected from the demonstrator in retinal coordinates (image pixel units) onto the egocentric frame of the imitator (meters). This transformation is determined with respect to a projection landmark, which is in our experiments chosen to be the midpoint between the shoulders, on both the demonstrator and the imitator.

In our experiments, the imitator is Adonis [5], a 20 DOF dynamically simulated humanoid, controlled using impedance [3]. This control strategy allows the movement of an endpoint to a desired target in Cartesian space. The endpoint trajectory is performed by providing the impedance controller with a sequence of via points along the reconstructed trajectory. Snapshots of Adonis performing a motion from the expimental set is shown in Figure 3.

4. RESULTS

The test data set, performed by a human, consists of seven different movements, each containing a circular path and an arc trajectory. The sizes of the patterns vary as does their order of appearance within the movement. Each of the movements was collected using our motion tracking system, presented to our classification algorithm, and then reconstructed.

5. SUMMARY AND CONTINUING WORK

We have described a primitives-based method for acquiring motor skills by imitation. This approach is based on neuroscience and cognitive science data on the organization of perceptual and motor systems, and our interpretation of those results for the specific purposes of imitation. The described model presents the current status of our on-going and continually developing efforts in imitation learning. Several extensions are being worked on, encompassing different components of the model. We are currently testing and evaluating two different methods for automatic derivation of primitives, as an alternative to the hand-coded "innate" ones we presented here. Our continuing work will also address the mapping between the perceptual and motor primitives. Further information about this and related ongoing work is available at *http://www-robotics.usc.edu/∼ agents/imitation.html*.

6. REFERENCES

[1] S. Arya and D. M. Mount. Algorithms for fast vector quantization. In *Proceedings of the Data Compression Conference*, pages 381–390. IEEE Press, 1993.

[2] J. Demiris and M. Matarić. Perceptuo-motor primitives in imitation. In *Proceedings of the Autonomous Agents 1998 Workshop on "Agents in Interaction: Acquiring Competence through Imitation"*, Minneapolis/St. Paul, USA, 1998.

[3] N. Hogan. Impedance control: An approach to manipulation. *Journal of Dynamic Systems, Measurement, and Control*, 107:1–24, 1985.

[4] M. J. Matarić. Sensory-motor primitives as a basis for imitation: Linking perception to action and biology to robotics. In *Imitation in Animals and Artifacts*. The MIT Press, 2000.

[5] M. J. Matarić, V. B. Zordan, and Z. Mason. Movement control methods for complex, dynamically simulated agents: Adonis dances the macarena. *Autonomous Agents*, pages 317–324, 1998.

[6] G. Rizzolatti, L. Gadiga, V. Gallese, and L. Fogassi. Premotor cortex and the recognition of motor actions. Cognitive Brain Research, 3:131–141, 1996.

[7] S. Weber. Simple human torso tracking from video. Technical Report IRIS-00-380, Institute for Robotics and Intelligent Systems, University of Southern California, 2000.

Acknowledgments

This work is supported by the Fulbright Foundation Grant to Stefan Weber, the NSF Career Grant IRI-9624237 to Maja Matarić, and the USC All-University Predoctoral Fellowship to Chad Jenkins.



Figure 1: *Our imitation model, consisting of motion extraction, matching to combinations of innate primitives, and reconstruction.*



Figure 2: *The results of classifying the original motion into primitives (top) and the reconstructed motion from those primitives (bottom).*



Figure 3: *An example motion after tracking (left) and actuation on Adonis (right).*