Localizing a Wireless Node in a Multi-Agent System Using Kalman Filtering

Puneet Goel and Gaurav S. Sukhatme*
puneet|gaurav@robotics.usc.edu
Department of Computer Science
Institute for Robotics and Intelligent Systems
University of Southern California
Los Angeles, CA 90089-0781

Abstract

Kalman Filtering has been successfully applied to various state estimation problems in mobile robotics. This paper presents the application of Kalman Filtering to a scenario where the measurements do not come as a time series. There is also no readily available estimation matrix for the system. The advantages and limitations of using Kalman Filtering in such a scenario are discussed. The work describes a strategy for position estimation of a wireless node (e.g. a mobile robot or any other portable device) while using only the line-of-sight distance estimates from the node to other nodes in its environment.
KeyWords: Kalman Filter, Wireless node, Signal Strength, Position Estimation, Distributed Agents.

1 Introduction

In order to autonomously navigate and perform useful tasks, a mobile robot often needs to know its exact position and orientation. *Robot localization* is thus a key problem in providing autonomous capabilities to a mobile robot. The different techniques that have been developed to tackle this problem can be classified into two main categories:
Relative localization: evaluating the position and orientation of the robot using information provided by various on-board sensors (e.g. encoders, gyroscopes, accelerometers etc). This family of algorithms uses local, on-board sensor information.

*contact author for correspondence

Absolute localization: obtaining the absolute position using beacons, landmarks or satellite-based signals (e.g. GPS). These algorithms rely on sensors external to the robot.

There has been substantial research in absolute localization. Leonard and Durrant-Whyte [11] developed a system in which the basic algorithm is formalized as a vehicle tracking problem, employing an Extended Kalman Filter (EKF) to match beacon observations to a navigation map to maintain an estimate of the position of the mobile robot. Thrun et.al.[14] have developed a learning algorithm that enables a mobile robot to learn what features/landmarks are best suited for localization. They also show a map matching technique [15],[5] using information from wheel encoders and wall orientation to localize the robot.

Several groups have also proposed improved odometry for robot localization. Borenstein and Feng [3] presented a calibration technique called the UMBmark test. The dominant systematic error sources were identified as the difference in wheel diameter and the uncertainty about the effective wheelbase. In another paper [4] the same authors introduce the term 'gyrodometry' where the localization algorithm relies on odometry most of the time while substituting gyro data only during those brief instances during which gyro and odometry data differ substantially.

In this work we target an indoor environment where various agents can perform tasks independently and still know the whereabouts of other agents in the system. Systems based on Global Positioning system (GPS), while very useful outdoors, are ineffective indoors. On the other hand, all the approaches for indoor localization stated above either use high cost, high powered sensors or rely on odometry. Odometry indeed is a good prospect for low cost localization but our focus is to build a system where a mobile node can estimate its position even when it is being carried by another (possibly human) agent. Since we are in a multi-agent networked environment we want to take advantage of each node's network connection with other nodes and use the line-of-sight distance measurements to estimate position. If the mobile node is a robot moving autonomously we could use odometry in conjunction with the approach developed here. Kato et. al [10] developed an approach to localize robots in a multi-robot system using omnidirectional vision sensors. They used triangulation to get the position estimates. The drawback is the use of high cost, bulky omnidirectional cameras. Also they were not able to produce real time results for more than 6 robot environment. We propose a low cost strategy that works for a large number of robots (e.g we show our results for an environment with 13 robots).

We explore the possibility of localizing the node based on its wireless connection so that we can get rid of high powered sensors to have extended battery life. Various groups have tried to use radio frequency and infrared sensors for position estimation in indoor environments. In the Active Badge System [16], [7] the mobile host emitted Infrared (IR) signals periodically which were picked up by sensors placed at fixed positions. This system scales poorly and suffers from significant installation and maintenance costs. [1] describes a similar system based on IR technology where transmitters are attached to the ceiling at known positions. The obvious drawback is that transmitters cannot be mobile robots. In the Dedalus Project [8] base stations transmit beacons augmented with their physical co-ordinates. A mobile host estimates its location to be the same as that of the base station to which it is attached. This is a very rough estimate of the position. We explore the case where a node listens to multiple transmitters and uses this information for better position estimation. Bahl et.al. [2] described a radio-frequency based system for locating and tracking users inside buildings. The authors used WaveLAN NIC which is a very costly and power consuming device. Most of the current state of the art either provides poor location estimates or uses stationary base stations. All of them need a lot of time for setting up the system *a priori*. The major missing element is a technique that can provide good location estimates for the mobile host without constraining transmitters to be stationary and evenly distributed. We would also like to use cheap and low powered transceivers instead of costly network interface cards. If there is an alternative system (like odometry) for providing position estimates, the transmitters should be able to reorganize themselves when their estimates are poor.

The rest of the paper is organized as follows. In Section 2, the problem is defined and the complexity involved is discussed. Section 3 describes the structure of the Kalman Filter. Section 4 presents the experimental results. Section 5 provides a discussion on the work and its possible applications. Section 6 concludes with a summary and a discussion of ongoing and future research.

2 Problem Definition

The objective of the work is to estimate the position of a mobile node (we will call it receiver, Rx) based on signals from other moving/stationary nodes (transmitters Tx). The measurements are the straight line distances between the receiver and the transmitters. Our aim is to calculate the (x, y) position of the receiver given the (x, y) positions of the transmitters. A baseline approach is to use triangulation. If there are more than 3 transmitters then averaging the estimates obtained from various triangles provides a quick estimate. The key problem is that naive averaging treats each estimate equally, as shown below.

$$\mathbf{x} = \frac{\sum_{i=1}^{p}(\mathbf{x}_i)}{p} \tag{1}$$

$$var(\mathbf{x}) = \frac{\sum_{i=1}^{p} var(\mathbf{x}_i)}{p^2} \tag{2}$$



Figure 1: Left hand side shows two special cases. The arcs show the error bounds for a transmitter. Figure 'a' shows the best case as variance in both 'x' and 'y' position of Rx is small. Figure 'b' shows a pathological case where it is possible to get a good estimate of 'y' but not of 'x'. Right hand graph shows a random distribution of nodes. Tx denotes transmitter and Rx denotes receiver.

Consider a random distribution of receiver and transmitters as shown in right hand graph of figure 1. Suppose we have 'p' position estimates for the receiver through triangulation, the final estimate using naive averaging is given by equation (1). As one can see from equation (2) if we have a measurement that is very poor it can increase the variance of the estimate $\mathbf{x}$ enormously. This is shown pictorially on left hand side in figure 1. The error bounds are shown by circular arcs. The case (a) shows a pair of transmitters placed evenly. If we estimate the position of the receiver using this pair the variance in the estimate will be small. Consider the pair of transmitters shown in case (b). Here one obtains a good bound on variance in the y estimate but the variance is extremely high for the x estimate. Therefore we cannot treat these two measurements equally. A technique that incorporates the variances in x and y emanating from the poor measurements of straight line distances between receiver and transmitter is needed. That is why naive averaging is not a good technique here. We propose to use Kalman Filtering because it explicitly uses the the variances in the measurements. Indeed, the Kalman Filter provides an optimum estimate in minimum mean-square error sense.

3 Kalman Filter

Kalman filtering [9] is a well known technique for state and parameter estimation. It is a recursive estimation procedure that uses sequential sets of measurements. Prior knowledge of the state (expressed by the covariance matrix) is improved at each step by taking the prior state estimates and new data for the subsequent state estimation. In recent years Kalman filter based localization has become common practice [13],[6] in the robotics literature.

Leonard et. al. [12] used Extended Kalman Filtering to localize the robot while mapping the environment through cross-map updates for better accuracy in vehicle estimates.

In the experiments reported here the measurement vector used in the Kalman Filtering is composed of the position estimates x and y. The state estimate is denoted by $\hat{\mathbf{x}}$, $\mathbf{z}$ is the measurement vector, $\mathbf{r}$ is the residual vector and $\hat{\mathbf{z}}$ is the measurement estimate.

$$\mathbf{z} = [x \; y]^T \quad \hat{\mathbf{z}} = \hat{\mathbf{x}} = [\hat{x} \; \hat{y}]^T \quad \mathbf{r} = \mathbf{z} - \hat{\mathbf{z}} \tag{3}$$

The Kalman filter consists of two different steps **propagation** and **update**. The equations for the propagation step are:

$$\hat{\mathbf{x}}_{k+1/k} = \mathbf{\Phi} \; \hat{\mathbf{x}}_{k/k} \tag{4}$$

$$\mathbf{P}_{k+1/k} = \mathbf{\Phi} \; \mathbf{P}_{k/k} \; \mathbf{\Phi}^T \; + \; \mathbf{Q} \tag{5}$$

We are using Kalman Filter in a scenario where we do not have any position estimates for the next step. Therefore the system matrix $\mathbf{\Phi}$ is the identity matrix:

$$\mathbf{\Phi} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

The equations for update are

$$\mathbf{K} = \mathbf{P}_{k+1/k} \; (\mathbf{P}_{k+1/k} + \mathbf{R})^{-1} \tag{6}$$

$$\hat{\mathbf{x}}_{k+1/k+1} = \hat{\mathbf{x}}_{k+1/k} + \mathbf{K} \; \mathbf{r} \tag{7}$$

$$\mathbf{P}_{k+1/k+1} = (\mathbf{I} - \mathbf{K}) \; \mathbf{P}_{k+1/k} \tag{8}$$

where $\mathbf{P}$ is the error covariance matrix, $\mathbf{Q}$ is the system noise covariance matrix, $\mathbf{K}$ is the Kalman gain matrix and $\mathbf{R}$ is the measurement noise covariance matrix.

The system noise covariance matrix $\mathbf{Q}$ is determined empirically. Different sets of experimental data were processed to calculate the system driving noise. The values of measurement noise matrix $\mathbf{R}$ are the most important in our experiments.

$$\mathbf{Q} = \begin{bmatrix} 0.01 & 0 \\ 0 & 0.01 \end{bmatrix} \quad \mathbf{R} = \begin{bmatrix} var(x) & cov(x,y) \\ cov(x,y) & var(y) \end{bmatrix}$$

The values in the matrix $\mathbf{R}$ are calculated as shown below. We can represent x as a non-linear function $\mathbf{f}$ of straight line distances r_i and r_j measured from a pair of transmitters T_i and T_j. Therefore $var(x)$ can be calculated as shown in equations (9) to (13). Similar calculations are used to calculate $var(y)$ and $cov(x,y)$.

$$x = \mathbf{f}(r_i, r_j) \tag{9}$$



Figure 2: A random distribution of nodes and performance of KF and Averaging on that distribution. Standard deviation in the measurements is 5% ($s = 5$).

$$var(x) = \mathbf{E}(X^2) \; - \; \mathbf{E}^2(X) \tag{10}$$

$$\mathbf{E}(X) = \sum_j \sum_i \mathbf{f}(r_i, r_j)\mathbf{P}(r_i, r_j)\delta r_i \delta r_j \tag{11}$$

$$\mathbf{E}(X^2) = \sum_j \sum_i \mathbf{f}^2(r_i, r_j)\mathbf{P}(r_i, r_j)\delta r_i \delta r_j \tag{12}$$

$$\mathbf{P}(r_i, r_j) = \mathbf{P}(r_i)\mathbf{P}(r_j) \tag{13}$$

$\mathbf{P}$ denotes the probability distribution of r_i, r_j. Since r_i and r_j are independent we get equation (13).

4 Experimental Results

The Kalman Filter (KF) was implemented in simulation. In this section we present some results. We assume that the position (x, y) of each transmitter is known. Further we assume there is a device that gives us the straight line distance between the transmitter and receiver. This straight line measurement is corrupted by Gaussian noise. The variance in the noise depends linearly on the distance between the transmitter and receiver. The farther the transmitter from the receiver, the greater the noise in its measurement. If the actual distance between the transmitter and receiver is r then the measurement provided to the KF, $\bar{r}$, is calculated as shown in equations (14) and (15) where η represents the noise added, G is a Gaussian function of zero mean and unit variance while s is the percentage deviation.

$$\eta = \frac{s}{100} \; r \; G(0, 1) \tag{14}$$



Figure 3: A random distribution of nodes and performance of KF and averaging on that distribution. Standard deviation in the measurements is 5% ($s = 5$). It seems averaging performs better but see the oscillations in mean squared error while the number of transmitters increase due to the incoming bad measurements. No initial estimate was given to KF.

$$\bar{r} = r + \eta \tag{15}$$

To start the process we pick any three transmitters and provide an initial estimate $\hat{x}, \hat{y}$ to the Kalman Filter through triangulation. Notice that since the triangulation is performed using noisy measurements and transmitters are picked randomly, the initial estimate can be very poor. After the initial estimate, we take two transmitters at a time, calculate the two possible positions of the receiver using the straight line distance measurements and use the one closer to our current estimate as the new measurement to the KF. So if there are 'n' transmitters there will actually be ${}^{n}C_2 = \frac{n(n-1)}{2}$ such measurements. For each measurement, the $\mathbf{R}$ matrix is calculated using the equations (9) to (13). If $\mathbf{R}$ is large, the KF will have small Kalman Gain matrix $\mathbf{K}$ (see equation (6)) and hence the measurement will be disregarded.

In figure 2, the graph on the right hand side shows the performance of KF and averaging method as the number of transmitters is increased from 7 to 12. The graph on the left shows the final distribution of 12 transmitters and one receiver. The standard deviation in the straight line distance measurements was 5% ($s = 5$) of the actual distance between the transmitter and receiver. The simulation is done in a 50X50 unit square arena. As we can see the KF performs better than averaging. But on the other hand if we look at figure 3 we see that averaging does a better job. If we examine the distribution of transmitters we see the explanation. In figure 3, the transmitters are very near (hence less noisy measurements) the receiver and also very well distributed. If the initial estimate to KF is poor and the distribution of transmitters is even, the KF cannot perform better than averaging. But this is not what we expect in reality. We discuss this in the next section.



Figure 4: A random distribution of nodes and performance of KF and Averaging on that distribution. Standard deviation in the measurements is 5% ($s = 5$). KF outperforms averaging with good initial estimate.

To improve the performance of the KF we decided to provide a good initial estimate of the receiver position. The initial estimate had a Gaussian noise of standard deviation 0.5 units added to the actual position of the receiver. Figure 4 shows the performance of the KF versus averaging when a good initial estimate was provided to the KF. It can be seen that the KF just outperforms averaging. Also notice the oscillation in error as the number of transmitters increase. This is exactly what we expect: a new placement of transmitter can actually increase the error instead of decreasing it due to its bad positioning. In this experiment the standard deviation in the measurement was 5% ($s = 5$) of the actual distance between transmitter and receiver. Figure 5 shows the same graphs but here the standard deviation of the noise was 10% ($s = 10$) of the actual distance.

5 Discussion

In reality we do not expect to have an even distribution of transmitters. Thus if we use averaging we might see that the error rises as number of transmitters increases, instead of going down. Also averaging cannot perform well if the noise in the measurement is large, say 10% ($s = 10$) of the actual distance. We have seen that the KF performs well with larger noise and a good initial estimate. In this section we will point out the weakness of the KF in such scenarios. Recall from section 3 that the system matrix for KF is just a 2X2 identity matrix. This means that the KF does nothing useful in the *propagation* step and just returns the previous estimate. If we continue to get poor measurements the KF will keep disregarding them and stay close to its first estimate. If the first estimate is also poor there is no way that the



Figure 5: A random distribution of nodes and performance of KF and averaging on that distribution. Standard deviation in the measurements is 10% ($s = 10$). KF outperforms averaging with good initial estimate.

KF can perform well. The need for a good first estimate is apparent.

Our experiments have shown that if a good initial estimate is provided to the KF it outperforms averaging. Also we point out that since we are running experiments in simulation and are adding normally distributed noise to the absolute measurements, it might happen that the errors in various measurements cancel each other, leading to good averaged estimates. But in the real world we cannot hope to be lucky enough for this to hold true.

Further, the major motivation of this work is in distributed tasks. If the receiver is a mobile robot then we can use odometry to estimate its position in the propagation step of the KF. In that case we do not need to rely only on measurements, thus improving the performance of the KF based technique.

6 Conclusions and Future Work

In this work we presented a technique to localize a node based on a network connection. We have been able to provide good location estimates for the mobile host even when transmitters are randomly distributed. We have also shown that if the node is a mobile robot we can do better. We outlined the limitations of using Kalman Filtering in the kind of scenario where a system matrix is not available. Generally the **R** matrix in KF is provided at the outset and is not changed throughout an experiment. However we have in this work pointed out the importance of the **R** matrix and it changes with each measurement to the KF. This work will be useful when we experiment with distributed tasks with multiple robots. Then, not only will we need to localize the robots but we will also need to reorganize them in order to maintain connectivity. This is what we will work on in the future.

Acknowledgments

The authors thank N. Bulusu and L. Girod for providing various useful insights. The authors also thank Dr. A. Goel for providing information on calculation of variance matrix. This research is sponsored in part by NSF grant #ANI-9979457, contract #DAAE07-98-C-L028 from DARPA and DARPA grant #DABT63-99-1-0015.

References

[1] R. Azuma. Tracking requirements for augmented reality. In *Communications of the ACM*, volume 36, July 1993.

[2] P. Bahl and V. N. Padmanabhan. Radar: An in-building rf-based user location and tracking system. In *Proceedings of IEEE Infocom 2000*, March 2000.

[3] J. Borenstein and L. Feng. Correction of systematic concurrency errors in mobile robots. In *Proceedings of the 1995 IEEE International Conference on Robotics and Automation*, pages 569–574, 1995.

[4] J. Borenstein and L. Feng. Gyrodometry: A new method for combinig data from gyros and odometry in mobile robots. In *Proceedings of the 1996 IEEE International Conference on Robotics and Automation*, pages 423–428, 1996.

[5] A. Elfes. Sonar-based real world mapping and navigation. *IEEE Journal of Robotics and Automation*, RA-3(3):249–265, June 1987.

[6] Puneet Goel, S.I. Roumeliotis, and G.S. Sukhatme. Robust localization using relative and absolute position estimates. In *Proceedings of the 1999 IEEE/RSJ International Conference on Intelligent Robots and Systems*, October 1999.

[7] A. Harter and A. Hopper. A distributed location system for the active office. In *IEEE Network*, January 1994.

[8] T.D. Hodes, R.H. Katz, E.S. Schreiber, and L. Rowe. Composable ad hoc mobile services for universal interaction. In *MobiCom '97 Proceedings*, September 1997.

[9] R.E. Kalman. A new approach to linear filtering and prediction problems. *ASME Journal of Basic Engineering*, 86:35–45, 1960.

[10] K. Kato, H. Ishiguro, and M. Barth. Identifying and localizing robots in a multi-robot system environment. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, volume 2, October 1999.

[11] J. J. Leonard and H. F. Durrant-Whyte. Mobile robot localization by tracking geometric beacons. *IEEE Transactions on Robotics and Automation*, 7(3):376–382, June 1991.

[12] J. J. Leonard and H. J. S. Feder. A computationally efficient method for large-scale concurrent mapping and localization. In *Proceedings of IEEE Infocom 2000Robotics Research: the Ninth International Symposium*, 2000.

[13] S.I. Roumeliotis, G.S. Sukhatme, and G.A. Bekey. Circumventing dynamic modeling: Evaluation of the error-state kalman filter applied to mobile robot localization. In *Proceedings of the 1999 IEEE International Conference in Robotics and Automation*, May 1999.

[14] S. Thrun. Bayesian landmark learning for mobile robot localization. *Machine Learning*, 33(1), 1998.

[15] S. Thrun. Learning maps for indoor mobile robot navigation. *Artificial Intelligence*, 1999.

[16] R. Want, A. Hopper, V. Falcao, and J. Gibbons. The active badge location estimation. In *ACM Transactions on Information Systems*, volume 40, January 1992.