The USC Autonomous Flying Vehicle (AFV) Project: Year 2000 Status

James F. Montgomery
monty@robotics.usc.edu
Robotic Embedded Systems Laboratory
Robotics Research Laboratories
Computer Science Department
University of Southern California
Los Angeles, CA 90089-0781

September 20, 2000

Robot helicopter research at the University of Southern California began in 1991 with the formation of the Autonomous Flying Vehicle (AFV) Project and continues to the present day. During this time our lab has designed, built and conducted research with three robot helicopters. A brief project history and background is given, followed by a more detailed description of the current state and accomplishments of the project. We conclude with a discussion of future research plans.

1 Project History and Background

In 1991, our research in robotic helicopters began with creation of the project namesake, the AFV (Autonomous Flying Vehicle) [1]. We transitioned to our second robot, the AVATAR (Autonomous Vehicle Aerial Tracking And Retrieval), in 1994 and to our current robot, the second generation AVATAR (Autonomous Vehicle Aerial Tracking And Reconnassaince), in 1997. The "R" in AVATAR has changed to reflect a change in robot capabilities.

Since the beginning of the project, a guiding design philosophy has been to create robots with high levels of autonomy. For example, to increase autonomy we require minimal robot dependence upon external resources. Therefore, we locate system power, sensors and computers onboard the robots themselves. Choices made for each are driven by factors such as weight, power consumption and cost. These choices consequently affect the robot control system design.

We use a behavior-based control approach for all three robots. In this approach, the control problem is partitioned into a set of loosely coupled computing modules. Each module, or behavior, is responsible for achieving a specific task. These behaviors interact to achieve the robots' overall goals. The modules are organized hierarchially, with low-level, reflexive behaviors responsible for robot survival and higher-level behaviors performing tasks such as navigation and object location.

As our experience and financial resources have increased over the years, so have the capabilities of our robots. Our first two robots had limited payload, computing and sensing capabilities as compared to our current robot. This in turn reduced the missions that they were capable of performing as compared to our current robot. For example, our earlier robots did not have GPS, while the current robot does, making them unable to navigate as precisely as our current robot.

2 AVATAR Hardware

The current AVATAR, shown in Figure 1, is based upon the Bergen Industrial Helicopter, a radio controlled (RC) model helicopter. It has a two meter diameter main rotor, is powered by a 6.0 horsepower twin cylinder gas engine and has a payload capability of approximately 10 kilograms. The helicopter has five degrees of control: main rotor lateral and longitudinal cyclic pitch, tail rotor pitch, main rotor collective pitch and engine throttle. The first three control the roll, pitch and yaw of the helicopter while the last two control its thrust. The helicopter can be controlled by a human pilot using a hand held transmitter which relays pilot control inputs to an onboard radio receiver using the 72 MHz frequency band. The receiver is connected to five actuators, one for each degree of control on the helicopter. For autonomous operation, these pilot control inputs are replaced by computer generated control inputs.

A block diagram of the AVATAR system; including sensors, onboard and offboard computing resources, wireless communication links and electrical power sources, is given in Figure 2. Refer to this diagram during the following discussion.

A variety of sensors are mounted on the AVATAR that provide information about the state of the helicopter as well as the environment in which it operates. An integrated Global Positioning System/Inertial Navigation System (GPS/INS) device, consisting of a GPS receiver and an Inertial Measurement Unit (IMU), is the primary sensor used for low-level control of the helicopter. The GPS/INS provides position (latitude, longitude and altitude), velocity (horizontal and vertical), attitude (roll and pitch), heading (yaw), delta theta and delta velocity information. This particular GPS receiver can only track 4 satellites at once and consequently provides a relatively poor estimate of current latitude and longitude as compared to other available receivers. So, a second stand alone GPS receiver is used that can track up to 12 satellites at once. This improves the standard deviations of the estimates of latitude and longitude from 4.5 meters for the 4 channel GPS unit down to 20 centimeters for the 12 channel unit. This GPS receiver is used for the high-level (guidance and navigation) control of the helicopter. A downward facing ultrasonic (sonar) transducer provides altitude information and an RPM sensor mounted on the main rotor mast measures engine speed. (Note: Neither the sonar or RPM sensor are currently mounted on the AVATAR, jfm 2/27/00). A downward looking color CCD camera provides visual information of the area

Figure 1: The Autonomous Vehicle Aerial Tracking And Reconnaissance (AVATAR)

below the AVATAR.

Onboard computing needs are met using a number of commercial off the shelf (COTS) PC/104 boards and one additional custom built PC/104 board. PC/104 boards stack together via a header that doubles as a communication and power bus and are useful for embedded applications. The main processor board contains a 486DX4 CPU which runs at 133 MHz, has 4 Mbytes of RAM and 8 Mbytes of solid state disk on chip (DOC). The DOC contains both the realtime operating system (RTOS) and flight software. The 486DX4 boots up the RTOS at system powerup, executes all flight control and image processing software and provides an interface to other PC/104 boards.

These boards include a timer/counter board used both to generate actuator commands and read pilot commands, a custom built PC/104 board that allows switching between human generated and robot generated commands on an actuator by actuator basis, a serial port board for interfacing to the GPS/INS and stand alone GPS, a color video frame grabber for the CCD camera (note: not currently on the AVATAR, jfm 2/27/00) and a PC/104 to PCMCIA interface board to allow the use of PCMCIA cards onboard the AVATAR. A 2.4 GHz wireless Ethernet system provides a multiway 1.2 Mbps communication link between the AVATAR, other robots and a human using an operator control unit (OCU). (The OCU comprises the offboard computing resources and will be described in detail later). The human receives telemetry from the AVATAR and sends high-level tasking commands to the AVATAR via this link. In addition, differential GPS corrections are sent from the OCU to the GPS receivers onboard the AVATAR through the wireless Ethernet to improve the GPS



Figure 2: AVATAR System Block Diagram

performance. A live video feed, provided by a one way 1.3 GHz wireless video link from the CCD camera, is displayed on a monitor for viewing by a human.

Nickel-metal hydride (NiMH) and lithium-ion (Li-Ion) batteries supply power to the electronics. Two 10.8 volt, 4.05 amp-hour Li-Ion batteries are connected to a 50 watt PC/104 power supply board that provides +5 volts and ±12 volts to the onboard electronics. A single Li-Ion battery provides power to the wireless Ethernet and wireless video links. The GPS/INS is relatively power hungry, requiring 0.8 amps at +24 volts and so a dedicated 12 volt, 3.5 amp-hour NiMH battery is connected to a DC/DC converter to produce +24 volt power. The electronics can operate for over an hour with this battery supply. Mission length is limited by the flight time of the helicopter on a single tank of gasoline which is approximately 20 minutes in duration.

3 AVATAR software

The RTOS used is QNX; a UNIX-like, hard realtime, multitasking, extensible POSIX OS with a small, robust microkernel ideal for embedded systems. The microkernel handles process creation, memory management, and timer control. The flight software encompasses all remaining software running onboard the AVATAR. This currently includes (or is planned to include):

- low-level software drivers for interfacing with sensors and actuators
- flight control software for guidance, navigation, and control
- self test software including built in test (BIT) and health checks software for increasing robot fault tolerance
- vision processing software running on the frame grabber

All software is written primarily in C/C++, with assembly used only when required for speed of execution. Custom drivers have been written for the timer/counter card, the GPS/INS and GPS units. All of the flight control software has been coded and tested except for the Altitude Control behavior. Our behavior-based control system is described in detail in Section 4 of this document. The BIT and health checks software has not yet been implemented. The vision processing software runs on a ground-based computer but has not yet been ported to execute onboard the AVATAR.

4 OCU hardware

The operator control unit (OCU) is implemented using a Toshiba Tecra 510CDT laptop PC based upon a 120 MHz Pentium CPU. It has 144 Mbytes of RAM, a 4.0 Gbyte hard drive, a 12.1 inch high-res color monitor, a CD-ROM and an Ethernet connection. The QNX operating system is installed as well as the Watcom C/C++ compiler. A docking station expands the capabilities of the laptop by providing two full-length expansion slots for standard ISA and 32-bit PC Expansion Cards and one half-length 32-bit PC expansion slot. It also has a selectable bay for installing additional hardware such as CD-ROM drives or floppy drives. A 1.44M byte floppy drive has been installed in the slot. The 510CDT has multiple functions and is used during all phases of the project; including development, integration and test.

The primary purpose of the laptop is to function as a wireless OCU for communication and tasking of the robots. A 2.4 GHz wireless Ethernet device is connected to the the Toshiba, providing a multiway connection between the human at the OCU and the wireless Ethernet onboard the robots. Additonal functions of the 510CDT include the following: First, it provides a software development environment through the use of the QNX operating system and the Watcom C/C++ Compiler. Using this environment code is developed and tested. Also, using RCS, a QNX software version control utility, software configuration management is implemented. Second, the 4.0 Gbyte hard drive provides long-term storage capability for mission data. Third, the docking station provides an ISA slot for a GPS receiver used to produce differential GPS corrections for use by the mobile robots.

5 AVATAR Flight Control System

The AVATAR (Autonomous Vehicle Aerial Tracking And Reconnaissance) control system is implemented using a hierarchical behavior-based control system architecture [2]. Briefly, a behavior-based control approach partitions the control problem into a set of loosely coupled computing modules (behaviors). Each behavior is responsible for a specific task and they act in parallel to achieve overall robot goals. Low-level behaviors in the hierarchy are responsible for robot functions requiring quick response while slower acting higher-level behaviors meet less time critical needs. The behavior-based control system architecture used for the AVATAR is shown in Figure 3.

At the lowest control level survival is the main priority. To this end the robot has a set of fast-acting reflex behaviors that attempt to maintain system stability by holding the craft in a hover condition. In a hover, the helicopter maintains a fixed heading and position above the ground. When the robot detects deviations the appropriate reflex returns the craft to its stable configuration. The *Heading Control* behavior attempts to hold a desired heading by using the IMU (Inertial Measurement Unit) heading data to drive the tail rotor actuator. The *Altitude Control* behavior uses the sonar (ultrasonic) data and RPM sensor data to control the collective and throttle actuators. This behavior is responsible for maintaining a desired altitude above the ground. The *Pitch Control* and *Roll Control* behaviors try to hold a desired pitch and roll angle using the IMU angular attitude data to control the longitudinal and lateral cyclic actuators.

At the next level in the hierarchy, behaviors try to achieve short-term goals of the AVATAR. The *Transition to Altitude* behavior inputs a **Desired Altitude** to Altitude Control to move the robot to a new altitude. *Lateral Velocity* generates **Desired Pitch** and **Desired Roll** commands that are given to Pitch Control and Roll Control, respectively, to maintain a desired lateral velocity.



Figure 3: The AVATAR Behavior-Based Control System Architecture

At the top level, *Navigation Control* inputs a **Desired Heading** to Heading Control, a **Desired Altitude** to Transition to Altitude and a **Desired Lateral Velocity** to Lateral Velocity to navigate the AVATAR to a new heading, altitude, latitude and longitude. Navigation Control produces these desired values using the current **Helicopter Configuration** and a **Desired Location** received from a human using a GUI-based control interface. The GUI runs on the OCU which has a wireless Ethernet link with the AVATAR.

A key advantage of the behavior-based approach is the ability to create greater capabilities for the robot by layering more complex behaviors on top of previously constructed behaviors. This addition is transparent to the lower level behaviors, modulating but not destroying their underlying functionality. This allows the building and testing of control systems incrementally.

References

[1] J. F. Montgomery A. H. Fagg, M. A. Lewis and G. A. Bekey. The USC Autonomous Flying Vehicle: an experiment in real-time behavior-based control. In *Proceedings of the 1993 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 1173–80, Yokohama, Japan, 1993.

[2] R. A. Brooks. A robust layered control system for a mobile robot. *IEEE Journal Robotics and Automation*, 2(1):14–23, March 1986.