Recursive Learning for Deformable Object Manipulation

by

Ayanna MacCalla Howard

A Dissertation Presented to the

FACULTY OF THE GRADUATE SCHOOL

UNIVERSITY OF SOUTHERN CALIFORNIA

In Partial Fulfillment of the

Requirements for the Degree

Doctor of Philosophy

(Electrical Engineering)

March 1999

Acknowledgements

I want to express my sincere thanks and appreciation to Professor George Bekey, my advisor and the chair of my Dissertation Committee. Your enthusiasm and interest in my research has been a constant source of inspiration. I thank you for your guidance and your support. To one day accomplish just a fragment of your achievements - that is my aspiration.

I also want to thank Professor Edmond Jonckheere, Professor Timothy Pinkston, Professor Wei-Min Shen, and Professor Geoffrey Shiflett for serving on my PhD Dissertation Committee. Your sincere interest in my research is truly appreciated.

Such amount of help and advice could never go unnoticed - thank you Kusum Shori.

To my parents, Dr. Eric and Dr. Johnetta MacCalla - without you, my success would not have even begun. I thank you for placing that first computer at my feet at the age of 9. I thank you for pushing me when I was young and knew nothing. I thank you for the knowledge and support you have provided throughout my entire life - that which has made me what I am today. My love and appreciation go out to you, always and forever.

To my wonderful husband, best friend, and companion, Donivan Howard - you have been there for the long haul. I thank you for providing the support that I needed, especially in those late night hours. I thank you for believing in me and loving me. I thank you for relieving the stress - and providing that listening ear whenever I needed. I love you and what you have given me in return.

And to God - from whom all was made possible. I praise Your name and give all glory and honor to You for without You, there would be nothing. Thank you.

Contents

List Of Tables

List Of Figures

Abstract

This research addresses the problem of robotic grasping of 3-D deformable objects. Specifically, we seek to develop a generalized approach for handling of 3-D deformable objects in which prior knowledge of object attributes is not required and thus can be applied to an infinite number of object types (e.g. asymmetric, nonhomogeneous, nonlinear object types). Our methodology relies on the implementation of two main tasks. Our first task is to calculate deformation characteristics for a non-rigid object represented by a physically-based model. This model is derived from discretizing the object into a network of interconnected particles, springs, and damping elements. Using nonlinear partial differential equations, we model the particle motion of the deformable object in order to calculate the deformation characteristics. For our second task, we must calculate the minimum force required to lift the deformable object. This lifting force consists of a combination of the base force required to lift a rigid object of the same weight plus an additional force term which successfully compensates for the deformation of the object. This minimum lifting force can be learned using a technique called iterative lifting. With this method, the robotic system learns the required lifting force by lifting the object with iterative measurements of force. Once the deformation characteristics and the associated lifting force term are determined, they are used to train a neural network for extracting the minimum force required for subsequent deformable object manipulation tasks. Our developed algorithm is validated with two sets of experiments. The first experimental results are derived from the implementation of the algorithm in a simulated environment. The second set involves a physical implementation of the technique whose outcome is compared with the simulation results to test the real world validity of the developed methodology. This real world implementation consists of a dual vision system and two cooperative manipulators, each possessing an end-effector constructed as a flat surface palm. Based on the simulation and real-world results, we are able to show

that our physical, simulation, and theoretical lifting forces differ from each other maximally by a 14% error level.

Chapter 1

Introduction

Most robotic systems currently in existence have been built under the assumption that manipulation of rigid objects remains the primary task. Geometry of the object is usually static, with very little variance between one instance of the object and another. The robot must have knowledge pertaining to the exact structure and location of objects in the environment and the precise actions to be performed. In reality though, many objects are non-rigid. Most are unsymmetrical, compliant, and have alterable shapes. Even solid objects can deform when the object's dimensions become extensive. Seemingly simple manipulations and actions can result in complex changes to the object due to the large deformation caused by external forces. In general, deformable objects may have one-,two-, or three-flexible degrees of freedom. In the real world, these classes of objects include such items as rubber balls, beams, hoses, cloth, and wire.

In this research, we seek to develop a generalized approach to handling of 3-D deformable objects. We define this as a 'generalized approach' since it does not assume prior knowledge of object characteristics and can thus be utilized for an extensive range of 3-D deformable objects. We define a '3-D deformable object' as an object whose three flexible degrees of freedom are characterized by viscoelastic interactions between molecules. Such an object, when an external force is applied, changes the volumetric space it occupies as well as its shape. This thus excludes such objects as cloth sheets, steel beams, and glass plates.

In order to manipulate a 3-D deformable object in the presence of gravity, we must determine the force required to successfully lift the object. We define the minimum force necessary for such an operation as the minimum object 'lifting force'.

Based on this classification, we define the basic problem as: Given a 3-D deformable object, calculate the object lifting force. Based on our methodology, we show that the attributes which the system needs to know for calculating the object lifting force can be learned off-line for a wide range of three dimensional deformable objects. The attributes learned can then be mapped such that, during run-time, enough relevant attributes can be retrieved to grasp any three dimensional deformable object presented to the system. The research described in this document addresses this issue.

1.1 Motivation

Manipulation of 3-D deformable objects is one of the least addressed research areas in robotics. Classical robotic systems assume only rigid objects will be manipulated by the system. Such systems assume that object geometry maintains a single, stable, configuration during the manipulation task. Many robotic systems which address manipulation of deformable objects focus on force control and stability in the presence of environments with compliant properties [Mandal and Payandeh, 1995], [Chiaverini et al., 1994]. With this focus, in-depth knowledge of the object deformation characteristics is usually incorporated directly into force calculation and force feedback is utilized to ensure grasp stability.

Some systems focus on deformation control versus force control. In these systems, the robot manipulator is designed to control the deformation of the object [Meer and Rock, 1994], [Patton et al., 1992]. Those systems which do not assume knowledge of object characteristics are limited in that they assume manipulation of an object with no more than two flexible degrees of freedom. Deformable objects also appear in the field of robotics in terms of grasping with soft fingers [Shimoga and Goldenberg, 1996a], [Tremblay and Cutkosky, 1993]. This type of research suffers from the same limitations as does rigid manipulation of compliant objects.

Dynamic modeling of deformability has been studied in the fields of computational solid mechanics and computer graphics [Chaudhuri and Chatterjee, 1991], [Provot, 1995], [Thalmann and Thalmann, 1995]. In solid mechanics, the focus is mainly on steady-state stress and strain distributions of a deformable body under external loads. In computer graphics, deformation is seen as a tool for producing realistic looking animations. Currently there are some efforts which focus on virtual control prototyping in which a user interacts with a virtual deformable object in the exact same way they would interact with the physical object [Reznik and Laugier, 1996], [Bradau, 1996]. The main limitation with these techniques are the same which face the robotic world. These systems assume in-depth knowledge of object characteristics is available for inclusion into the simulated environment.

The problems which arise in grasping of non-rigid objects have been inadequately addressed in previous research attempts. These limitations have motivated the development of a methodology which does not require prior in depth knowledge of object attributes for manipulation of 3-D deformable objects.

1.2 Main Contributions

In this thesis, we focus on the manipulation of three dimensional deformable objects. This research extends the field of robotic handling of real world objects by providing a way for future research efforts to drop the widely held assumption that objects presented to a robotic system must be rigid, isotropic, and homogeneous. The main contribution of this work is in the development of a learning methodology which allows a robotic device to successfully grasp a 3-D deformable object. The model used for representing the object is adopted from other research efforts and, thus, we must impose a few restrictions on our system. By using this model, we assume that our system is quasi-static. Thus, the system exhibits very low acceleration and any velocity inherent to the system is almost constant, both when the object is deformed, as well as when it is grasped. Based on these assumptions, we have developed a learning methodology for:

- On-line determination of deformable object characteristics
    - Allows a robotic system the ability to handle a multitude of three dimensional objects belonging to the class of deformable objects without prior in depth knowledge of object attributes.

- Off-line learning of the minimum deformable object lifting force
  - We introduce the "Iterative Lifting" process which allows for the determination of the minimum force required to manipulate a deformable object.
- On-line determination of the minimum deformable object lifting force
  - We present a technique which allows for the retrieval of the minimum object lifting force after learning.
- Manipulation of Nonlinear/Nonhomogeneous/Asymmetrical deformable objects
  - We show how our approach can expand to encompass the class of deformable objects which includes asymmetric, nonhomogeneous, and inelastically behaved deformable objects.

1.3 Overview of Methodology

Our main focus is to learn an adequate grasp for a deformable object. We choose to represent grasping as the act of pushing against an object from two opposite ends [Yun, 1993]. Our system, therefore, utilizes two cooperative manipulators, each possessing an end-effector constructed as a flat surface palm and possessing a force sensor able to detect and record any force applied to the palm's surface area.

For determination of an adequate grasp we must learn the minimum forces a multiple robotic mechanism must exert in order to lift a common deformable object cooperatively. If F_w is the force required to lift a rigid object of weight W with frictional coefficient μ, we define the minimum deformable object lifting force L_f as $F_w + F_d$ where F_d is the minimum additional force term required to compensate for the deformation of the object.

We shall begin the process of determining L_f by focusing on the physical changes of the deformable body. We show that once a representation for both the external and internal positional movements of the deformable object can be retrieved, the object lifting force can be determined. In effect, we show that a relationship between object deformation and force can be learned such that an adequate grasp with minimal force can be achieved. Once this relationship is learned, we can utilize these factors to maintain a firm grasp on any deformable body by comparing the current run-time object deformation with the learned relationship. When they are equivalent, we can retrieve the necessary object lifting force required for manipulation.

Deformable Object Model

At the submicroscopic scale, all solid material is composed of atoms. Adjacent atoms in a solid exhibit both attractive and repulsive forces which keep the atoms at an equilibrium distance from each other. When the spacing between atoms is increased, a pulling force is created which tends to pull the atoms toward each other. In an equivalent manner, if the spacing is decreased, a pushing force is created which pushes the atoms away from each other. The tendency to maintain this equilibrium spacing leads to an 'elastic' manifestation.

The grouping of atoms leads to the formation of solids. A solid can be classified as crystalline, amorphous, or a combination of both. A crystalline material is made up of crystals, an orderly array of atoms arranged in three dimensional rows such that each atom is at an equilibrium distance from each other. This structural arrangement is called a space lattice [Byars and Snyder, 1969] (Fig 1.1).



Figure 1.1: Space Lattice Arrangement

A crystalline material has an orderly arrangement and thus we shall utilize its atomic structural characteristics to approximate the modeling of an elastic solid. We shall utilize the space lattice characteristic to represent an object as a particle based system constructed from a discretized sampling of its volume. Let $\alpha > 0$ represent the object discretization constant. The particle based representation of the object is thus given by a set Ψ of particles where each particle $\psi_n \in \Psi$[1], has an associated Cartesian position vector

$$\bar{p}_n = (x_n, y_n, z_n) = x_n\hat{\imath} + y_n\hat{\jmath} + z_n\hat{k}$$

Deformation of a material is caused at the microscopic level by visco-elastic interactions between molecules. This visco-elastic interaction can be modeled by the Kelvin Model which is characterized by a spring and damper in parallel. We shall utilize this model and characterize a deformable object as a set of particles locally interconnected by damped springs (Fig 1.2).



Figure 1.2: Network of Interconnected Particles and Springs

Calculating Deformation Characteristics

Let us now extract a piece of the interconnected particle system as shown in Figure 1.2. Let $\bar{f}_n$ represent the external force

$$(f_x, f_y, f_z) = f_x\hat{\imath} + f_y\hat{\jmath} + f_z\hat{k}$$

applied to particle ψ_n . Let m_n represent the mass of particle ψ_n. Let S_n represent the number of damped springs connected to particle ψ_n. Based on the mathematical equations defining the Kelvin Model, the forces acting on the n^{th} particle are accumulation of external force, inertial force, damping force and spring force. Using Newton's law of motion, the partial differential equation for motion for the n^{th} particle can be written as:

[1]where $n \leq \alpha^3$

$$\sum_{i=1}^{S_n} m_n \frac{\partial^2 \Delta \bar{p}_{n,i}}{\partial t^2}(\bar{f}_n, t) + \sum_{i=1}^{S_n} \lambda_{n,i} \frac{\partial \Delta \bar{p}_{n,i}}{\partial t}(\bar{f}_n, t) + \sum_{i=1}^{S_n} D_{n,i} \Delta \bar{p}_{n,i}(\bar{f}_n, t) = \bar{f}_n \qquad (1.1)$$

where D_n, the deformability coefficient, is a function of the force and the change in spring length, λ_n, the damping coefficient, is a function of the force and the instantaneous change in spring length, $\Delta \bar{p}_{n,i}(\bar{f}_n, t)$ represents the change in spring length in each Cartesian direction, and $\frac{\partial \Delta \bar{p}_{n,i}}{\partial t}(\bar{f}_n, t)$ represents the instantaneous change in spring length. We shall designate the summation $\sum_{i=1}^{S_n} \Delta \bar{p}_{n,i}(\bar{f}_n, t)$ as the particle displacement vector $\bar{d}(\bar{f}_n, t)$ and the summation $\sum_{i=1}^{S_n} \frac{\partial \Delta \bar{p}_{n,i}}{\partial t}(\bar{f}_n, t)$ as the particle displacement velocity vector $\bar{d}'(\bar{f}_n, t)$.

From Eq 1.1, we see that the only parameters which are not directly defined as a function of time are the mass, deformability, and damping coefficients. If we assume that the mass of the object is given, then we can classify the overall deformation of the object in terms of the deformability function D and the damping function λ. The algorithm we implement for determining the deformability function is as follows:

- 1. Using both manipulators, apply a force against the object's surface. At time $t_m = t_0, t_1, \cdots, t_n$, record force $\bar{f}(t_m)$ felt by the manipulator.
  2. Calculate the particle displacement vector $\bar{d}(\bar{f}(t_m), t_m)$ for all $t_m \in t$
  3. The deformability function is $D(\bar{f}, \bar{d}) = \frac{\bar{f}(t_m)}{\bar{d}(\bar{f}(t_m), t_m)}$ for all $t_m \in t$

The technique we use for determining the damping function is as follows:

- 1. Using both manipulators, apply a force against the object surface. At time $t_m = t_0, t_1, \cdots, t_n$, record the force $\bar{f}(t_m)$ felt by the manipulator.
  2. Calculate the particle displacement velocity vector $\bar{d}'(\bar{f}_a(t_m), t_m)$ for all $t_m \in t$ where $\bar{f}_a(t_m) = \bar{f}(t_m) - D\bar{d}(\bar{f}(t_m), t_m)$ is the damping force.
  3. The damping function is $\lambda(\bar{f}_a, \bar{d}') = \frac{\bar{f}_a(t_m)}{\bar{d}'(\bar{f}_a(t_m), t_m)}$

Learning An Adequate Grasp

"Learning denotes changes in the system that are adaptive in the sense that they enable the system to do the same task or tasks drawn from the same population more efficiently and more effectively the next time" [Rich and Knight, 1991]. In this research, we wish to learn how to efficiently and effectively grasp a deformable object. To learn the characteristics of an adequate grasp, we must determine the relationship between mass, deformation, and force. Once this relationship is learned, we can utilize these factors to maintain a firm grasp on any deformable body by comparing the current run-time mass/deformation of the object with the learned relationship. When they are equivalent, we can retrieve the minimum force required for grasping a deformable object. The steps required to handle manipulation of 3-D deformable objects are as follows:

- Learn what forces a robotic system must exert in order to successfully grasp a deformable 3-D object
    1. Record dimensions of a known object
    2. Calculate the deformability and damping functions
    3. Determine the minimum force necessary to grasp known object by iteratively lifting object
    4. Link object attributes and grasping force into a index table

We assume that an object first presented to the system is initially in an equilibrium state. Thus the summation of all forces inherent to the object converges to zero. To begin the iterative lifting process we apply a force F_w to the object and lift the object until the object particles have stabilized their positions. If, at this time, the object has not slipped, the object is in equilibrium and a firm grasp on the object has been achieved. This then is the object lifting force L_f. We record its value at this time and terminate the lifting process. If the object has slipped from the manipulator grasp, we increase the applied manipulator force and repeat the lifting process. Eventually a minimum force will be reached which, when applied, will be able to lift the deformable object. The force required to lift a rigid object of weight W is F_w. Therefore we know that the object lifting force must be greater or equal to this force[2]: $L_f = F_w + F_d \geq F_w$.

[2]we define the deformable object lifting force L_f as $F_w + F_d$ where F_d is the minimum additional force required to compensate for the deformation of the object.

After learning values for the lifting force, we store this information into an index table where given the mass, deformability, and damping functions we can extract the object lifting force. The table constructed is only valid for the objects explicitly learned. We wish to determine the general relationship between mass, deformability, damping, and lifting force. To accomplish this, we utilize a neural network characterized by three inputs, one hidden layer, and one output node to learn the desired relationship (Fig 1.3).



Figure 1.3: Neural Network

A simple backpropagation algorithm [Rumelhart et al., 1990] is used for the training process.

1.4 Thesis Outline

An overview of the ensuing chapters is as follows: Chapter 2 reviews some of the existing literature most relevant to addressing 3-D deformable object manipulation. This includes a summary of techniques ranging from virtual cloth manipulation to soft robotic fingers. Chapter 3 presents, more precisely, the 3-D deformable object model and the approach we use to determine its characteristics. Chapter 4 describes the iterative lifting process in detail while Chapter 5 explains how we expand our methodology to encompass nonhomogeneous and inelastically behaved deformable objects. In Chapter 6, we describe the simulation and the real-world environment used to validate our methodology and in Chapter 7 we present the main results of our implementation. We conclude, in Chapter 8, with a summary of the main contributions of this research and possible future extensions.

Chapter 2

Related Past Work

In this chapter, we shall review previous research efforts closely related to the field of deformable object manipulation. In the first section, we shall review robotic manipulation of deformable objects. This type of manipulation is typically defined in terms of force and/or deformation control. To achieve force control, a robotic system utilizes a control strategy capable of achieving stable contact against a compliant environment by exerting a specified force on the environment. In the case of deformation control, the system controls the deformation of a compliant object. The deformable objects modeled range from those objects exhibiting 1-D deformation behavior (beams) to 2-D objects such as clothing. There currently does not exist a system which manipulates 3-D deformable objects.

To achieve compliance in robots, there are currently two approaches - control approaches and material approaches. The control approach applies software control to conventional robots with rigid links. This form of robotic compliance is achievable just by tuning parameters. We will discuss such compliant manipulator control in the second section. The material approach uses soft materials such as rubbers and elastomers for robot designs. The advantage of using soft material is it's simplicity and relative cheapness. The third section briefly discusses these types of manipulator devices - both compliant devices and manipulator devices for use with compliant objects.

In the area of computer vision and graphics, deformable objects are modeled in a simulated environment. This work is related to our research in terms of simulation and modeling, thus we will give a brief description of the most relevant work in the last section.

2.1 Robotic Manipulation of Deformable Objects

In the work presented by Naghdy and Esmaili [Naghdy and Esmaili, 1996], a robot was commanded to simulate fruit stiffness sensing as implemented by a human operator. In order to measure the firmness of fruit, a human operator grasps and slightly presses a piece of fruit and thus evaluates fruit maturity. In the same way, a robot was commanded to apply a controlled force to a piece of fruit and measure the response based on the motor armature current. The current's waveform was then fed into a pattern recognition routine which extracted the grade, and thus the maturity, of the fruit. This process required no pressure sensors, only an ampmeter, and no prior knowledge of fruit characteristics. The fruit was modeled as a 1-D deformable object (Fig. 2.1).



Figure 2.1: Fruit Model

Katic and Vukobratovic [Katic and Vukobratovic, 1998] developed a PD controller which allows a manipulator to apply a constant force to a deformable 1-D surface without having prior knowledge of the environment characteristics. They utilized a neural network whose inputs were the force values derived from the manipulator as it pressed against a deformable surface and whose output was a value representing the environment type. The network was trained on 5 different types of environments ranging from styrofoam to steel. After learning, the network's output was used to extrapolate values for the spring, damping, and mass parameters.

These values were then fed as control parameters into the PD controller. Although this approach makes no assumptions about environment parameters, it only models surface deformation in one dimension.

In the work of Al-Jarrah and Zheng [Al-Jarrah and Zheng, 1998], the stiffness of a sheet is modeled as a nonlinear function of the sheet's bending force and moment. Using an estimate of the environmental stiffness parameters, an initial controller is designed which commands the manipulator to bend the sheet into a desired configuration. As the manipulator's motion deviates from the desired response, the compliance felt by the manipulator is directly used to increase/decrease the gain on the original controller. With this approach, the controller does not need to have prior knowledge of the object's deformation characteristics and the deformation can exhibit nonlinear behavior. Unfortunately, the approach only applies to objects exhibiting one degree of deformation.

Tarokh and Bailey [Tarokh and Bailey, 1996] used an adaptive fuzzy controller for force control of a manipulator in contact with an unknown environment. A fuzzy adaptation and learning algorithm was used to learn the environmental parameters and modify the fuzzy controller accordingly. Initially, the fuzzy controller was designed with assumed environmental parameters. While in contact with the environment, the measured force was compared with the desired force output and a modification was made to the fuzzy controller to account for the difference. In this way, based on the measured force data, the controller could adapt to the environment. Although no knowledge of environmental characteristics was required, the system is only used for 1-D surface deformations.

In [Venkataraman et al., 1993], a neural network is used to address the problem of environment parameter identification. Given contact motion, force, and velocity values, the neural network identified values for stiffness, damping, spring hardness, and shock absorption parameters of the environment. The robotic system was trained on nonlinear 1-D deformation profiles and was successfully able to identify the nonlinear environment model at runtime. These values were then fed as parameters into an associated robotic force and position controller.

Mandal and Payandeh proposed a control strategy capable of achieving a stable contact against both stiff and compliant environments [Mandal and Payandeh, 1995].

The system utilized a PID controller which was able to estimate environmental stiffness on-line and tune gains accordingly. Stiffness was estimated based on the area under the force-time curve and the best gain parameters, given the stiffness parameters and the approach velocity stored in a table. The main limitation with the system is that only a coarse stiffness resolution could be achieved. ('very stiff', 'stiff', 'compliant'). In addition the environment is modeled with cantilever properties. This, in effect, made the environment deformable in only one dimension.

David W. Meer and Stephen M. Rock [Meer and Rock, 1994] researched the development of a controller which could explicitly control the deformation of a flexible object. The flexible object impedance controller required a model of the object's flexibility in order to regulate the deformation of the flexible degree of freedom. Although the project was successful in implementing an insertion task in which the object had to be deformed within certain specifications in order to perform the assembly operation, the proposed method possessed some limitations. The system only modeled a single flexible degree of freedom. It required an explicit initial model of the object which included mass/object dynamics and a model of the object's flexibility, and complex sensors were required to measure the position and force of the object.

In [Zheng et al., 1991] [Chen and Zheng, 1995], research on inserting a flexible beam into a hole was presented. The contributing factor of this paper is the discovery that the trajectory of the tool which handles the beam must comply with the deflected shape of the beam in order to maintain minimum tool motion. To accomplish this task, the beam deflection can be described by the stiffness of the material, length of the beam, and other parameters. In [Chen and Zheng, 1991] a vision system was used to calculate this deflection. From this deformation information, the trajectory of the end-effector was computed for insertion of the beam into a hole. Although this system was able to calculate beam deformation autonomously, only a 1-D flexible object was utilized for this research effort.

Kraus [Kraus and McCarragher, 1997] also presented an approach for controlling the position and force applied to a deformable beam. They used this approach to show the feasibility of bending a sheet of metal which they defined as two-dimensional bending of a flexible beam.

In [Hirai et al., 1995] the focus was on directing a robotic manipulator to mimic the actions of a human inserting a deformable hose onto a plug. As the human implemented the task, the position and orientation of the hose was measured by a 3-dimensional digitizer. The force and the moment acting on the hose was measured by a 6-axis force sensor and a video was recorded to examine the deformation of the hose. After task implementation, the stored inputs were used to direct the manipulator to 'mimic' the human motion. This motion is later refined in order to speed up the task process. Although this system was successfully able to manipulate a deformable object without prior knowledge of object attributes, the object utilized was not a 3-D deformable object.

In [Hopcroft et al., 1991], the robotic system described was a robot arm which could tie knots in a rope. At programming time, the exact form of the rope was unknown. The system was successfully able to tie knots in ropes of many different sizes, stiffness, and initial configurations. This system assumed that the rope laid flat at all times. It therefore only addressed a 2-D implementation and never discussed how this process could be expanded to relate to 3-D robotic rope manipulation.

Patton, Swern, Tricamo, and van der Veen [Patton et al., 1992] used an adaptive control loop to generate correct tension on a piece of cloth. The cloth stiffness is designated as the adaptive variable. The only assumption made was that cloth handling is a planar problem, and thus only 2-D control needs to be addressed. The adaptive controller was used to successfully control the straightening of a wrinkled piece of cloth. The disadvantages to this research effort were the system only modeled a 2 dimensional object and the system required explicit knowledge of the initial and desired cloth tension in terms of x, y, and θ.

In [Chiaverini et al., 1994] a force and position control scheme capable of regulating a manipulator in contact with an elastically compliant surface was proposed. The system utilized a position PD controller and a force PI controller. Although this system did not require exact knowledge of the stiffness matrix, it did need to determine suitable values for the force feedback gains (which are calculated by estimating the environment stiffness).

A.M. Annaswamy and D. Seto [Annaswamy and Seto, 1993] addressed the issue of manipulation of deformable objects using compliant finger pads. Both the fingers as well as the object were assumed to deform only in the horizontal direction. It was assumed that enough prior information was available about the object properties to ensure that the object always stayed in contact with the finger pads without getting crushed. These parameters included mass, viscosity and stiffness matrices representing both the finger pad and the object. The preliminary simulation results showed the system's ability to control the global motion of the object while keeping the deformation of the object at a constant. Unfortunately, the parameters which define an object as deformable must explicitly be provided to the system before successful completion of the task.

Yao and Tomizuka [Yao and Tomizuka, 1998] focused on controlling the force and motion of a manipulator as it applied a force against a 1-D nonlinear deformable surface. They utilized an adaptive robust controller which required no knowledge of object stiffness. The position, velocity, and interaction forces of the manipulator were fed as control parameters into the controller, which adapted the applied force based on their values.

Siciliano and Villani [Siciliano and Villani, 1997] developed a feedback regulator which only required force and position measurements to be fed into the control loop. The approach modeled the environment with 1 degree of deformation and required the parameters defining the surface elasticity to be provided.

In [Seraji et al., 1996], a dual-mode control scheme using compliance and force control was used to establish a desired force during non-contact to contact tasks. The deformation of the surface was modeled with 1 degree of freedom.

Luo and Ito [Luo and Ito, 1993] designed a controller which ensured a manipulator was able to maintain continuous contact against a 1-D compliant surface. The adaptive algorithm required no initial knowledge of the environment. To begin, the system estimated the mass, spring and damping parameters of the environment and used these values to design a robot force controller. Then the robot was commanded to manipulate the environment using the initial controller, at which time, position and force data was recorded. These data values were compared with the expected system outputs and, using a least squares method, the estimates for the mass, damping, and spring parameters were updated and the controller was redesigned to improve system performance.

In robotic exploration [Sinha et al., 1993], the ability to measure and sense the variation in material properties of a surface is highly desirable. This work therefore focused on designing exploratory procedures for calculating the penetrability, compliance, and roughness of a surface. The robotic system possessed a compliant wrist sensing mechanism. Material properties were retrieved by pressing the compliant wrist against a surface and measuring displacement and force values. In addition to retrieving material properties, the system utilized a hybrid position/force algorithm to control the robotic system. The only limitation was that the surface and the compliant wrist sensor had only 1 flexible degree of freedom.

2.2 Control of Compliant Manipulators

Shimoga and Goldenberg [Shimoga and Goldenberg, 1996a] modeled a soft finger using the Kelvin model in which a spring and damper are placed in parallel. The finger tip is made from soft material and modeled as a flexible one-dimensional object. The stiffness and damping coefficients were experimentally calculated. Using these coefficients in the Kelvin model, and given the desired impedance parameters, the researchers were able to successfully control the impedance of a soft fingertip. The main limitation is that the model was only valid for a fingertip with 1 flexible degree of freedom.

To ensure compliant force control, [Tisdall et al., 1994] placed a compliant device between the manipulator end tool and the surface being followed to compensate for tracking errors and disturbances. A back propagating neural network was then trained on real data sets in order to relate forces and manipulator positions. The robotic system utilized was a Puma with a complaint device and an attached force sensor located between the arm and the end tool. In order to train the neural network, the PUMA's position and resulting forces were recorded during movement. These force vectors were used as inputs into the neural network and the output was the position vector. This construct was compared with a simplified spring model with 3 dofs and its output error was significantly less. In order to approach the real behavior of the compliant device, "it would appear that a very highly complex [spring] model would be required to approach the real behavior, i.e. a finite element model." [Tisdall et al., 1994, pages 298].

To control contact forces when transitioning from free to constrained motion, Akella and Cutkosky [Akella and Cutkosky, 1995] used soft fingertips made from electrorheological fluid[1] The stiffness and the damping parameters of the finger were controlled as part of the control strategy.

In another work, Tremblay and Cutkosky [Tremblay and Cutkosky, 1993] used a deformable fingertip equipped with a dynamic tactile sensor able to detect localized slip. By detecting such slippage and measuring normal and tangential forces at the finger, the controller can compute the coefficient of friction at the contact. This then allows the controller to modify the grasp force necessary to prevent the object from slipping (Fig 2.2).



Figure 2.2: Slip Sensor

In [Kao et al., 1997], it is desired to study stiffness characteristics of human grasping as implemented in compliant robotic finger manipulation. The grasp stiffness associated with each finger was computed as a function of joint stiffness, finger compliance, and contact type. By applying a set of forces to the fingertips and measuring the deflections, a good fit of the stiffness matrix was obtained. In this research effort, data from a human grasping experiment was retrieved and used to calculate the stiffness matrix for different grasp types.

[1] An electrorheological fluid consists of a collection of particles suspended in a dielectric fluid. Its behavior changes from that of a viscous fluid to that of a plastic when a strong electric field is applied.

2.3 Manipulator Devices

There are many issues which arise through the utilization of hard fingers - 1. The impact which arises during the grasping of a rigid object can affect the functioning of force and tactile sensors located close to the fingertips. 2. Hands with hard fingers cannot securely grasp objects that have uneven surfaces due to poor conformability of fingers. 3. Strains which occur during the manipulation task may lead to jerky motion. In order to address these issues, soft robotic fingers are utilized. These fingers mainly consist of hard materials with soft covering. They closely relate to human fingers in that impact energy is dissipated so finger bones (rigid manipulator fingers) do not experience the impact.

2.3.1 Compliant Manipulators

[Shimoga and Goldenberg, 1996b] Shimoga discussed different material for use in constructing soft fingers. [Lorenz et al., 1990] Lorenz developed a compliant, four degree-of-freedom fingertip sensor able to sense normal force, shear force in two tangential directions, and the torque about the normal axis. The sensor was constructed of silicone rubber and a piezoelectric polymer used to detect strains in the rubber. When a force was applied to the fingertip sensor, the rubber deformed. This deformation was transferred to the piezoelectric film which was used to measure the applied forces.

Honda [Honda, 1997] developed a unique intelligent gripper (Fig 2.3) which utilized a dynamic vibration absorber to ensure an object did not slip. The system does not require any a prior information such as shape, size, weight, or object texture. The gripper was constructed with two parallel fingers. Each finger consists of a structural finger, a support spring, a grasping finger, an absorber spring, and a damping oscillator. The object was held by being sandwiched between both grasping fingers. The system was able to calculate the 'minimum' grasping force required to grasp the object without slipping.



Figure 2.3: Intelligent Gripper

2.3.2 Robot Grippers for Compliant Objects

[Taylor and Koudis, 1988] [Monkman, 1995] [Kemp et al., 1986]. These papers presented different types of robot gripping methods utilized in the garment cloth industry. These robotic devices range from grippers employing intrusive methods such as mechanical pinching to using electroadhesion. The most successful gripper utilized for cloth manipulation is a combination air jet/finger separation device. The air jets produce vibrations in the uppermost layer of a stack of material and the gripper is then used to grasp the upper layer and transport the garment to the workbench. These papers address 2-D cloth deformation by focusing on the grippers needed to handle the object rather than on the object itself.

In New Zealand [Tedford, 1990], the development of a range of robot end-effectors suitable for handling of soft fruit was undertaken. These end-effectors ranged from pneumatic cushioned fingertip grippers to a three-fingered electro-mechanical gripper which used conductive foam to detect the fruit contact pressure and adjust the gripping force accordingly.

2.4 Deformable Objects in Computer Vision and Graphics

There are two foci in the computer graphics world. One focus is on animation - the process of producing realistic looking motion. The other is on simulation - the process of utilizing realistic force interaction. Simulation techniques must decide between calculation time and accuracy of the final result. There are a variety of surface modeling techniques used to represent deformable surfaces, but they have little relevance to the physical objects they represent. Physically based deformable models [Terzopoulos et al., 1987] based on elastic and viscous properties of a material can produce realistic looking simulations of deformable bodies. Physically based models simulate physical laws to produce physically valid behavior. They include real world effects such as gravity, friction, and momentum. These models are based on elasticity theory and are able to represent the shape and motion of deformable material, especially when these objects interact with other objects. Such models can be utilized for such applications as virtual reality, haptic interfaces, force-feedback robotic teleoperation, remote surgery, and interactive solid modeling.

The mass-spring system is a physically based model in which an object is modeled as a collection of point masses connected by springs in a lattice structure. The motion of a single mass point in the structure is governed by Newton's law of motion. The main limitation with this model is that, although realistic looking dynamics can be generated relatively fast, it is often difficult to extrapolate the spring and damping constants directly from the material properties.

Reznik and Laugier [Reznik and Laugier, 1996] from UC Berkeley, address the issue of real-time dynamic simulation and control of a "virtual" deformable object using the mass-spring model. A geometric model of a deformable finger composed of a rigid rod and an external deformable tip is used to validate the virtual control process. A simulation program was successfully able to map the "virtual" deformation of a 3 dimensional finger as it pressed against a rigid surface. The only disadvantage to this system is that the object's volumetric dimensions, density, and elasticity must be known a priori.

Joukhadar, et al. [Joukhadar et al., 1997] presented an approach which does not assume knowledge of object deformation characteristics. In this work, dynamic simulation was used to study the interaction between rigid and deformable objects represented with the mass-spring model. Finding values for the deformation parameters (elasticity, viscosity) coincided with finding parameters for which the dynamics of the behavior matched that of the real object. Given the state of the object in terms of position, velocity, and deformation, the system used genetic algorithms to find the deformation parameters which would coincide with the given state. Thus, object dynamics matched real world behavior without having to explicitly define deformation parameter values. The only problem with this technique is that it is assumed object states are observable and definable.

The most relevant physically based 3-D deformable object model is the finite-element model. The finite-element model consists of discretizing an object using simple or complex volume elements. Each element is connected to each other by a finite number of nodes. The relationship between the nodal displacements and the force applied to its nodes follows Hooke's law and is defined as $[K]x = F$ where $[K]$ is the global stiffness matrix, x is the global displacement vector, and F is the global force vector. Although the FEM method describes object deformation in terms of elastic theory, the object discretization and stiffness matrix calculation are computationally intensive. Most computer graphic methods therefore focus on implementing FEM efficiently and quickly for graphical simulations.

Terzopoulos [Terzopoulos et al., 1987] developed the displacement model (Fig 2.4). In this formulation, internal structure is not modeled. This methodology relies on displacement vectors to define the object's shape, as defined from the reference frame of the undeformed object. Each point is linked to its neighbor by elastic elements. A deformable body is represented as the sum of a reference component r(u,t) and a deformation component e(u,t). The positions of mass elements in the body relative to a body frame ϕ is given by

$$q(u,t) = r(u,t) + e(u,t) \tag{2.1}$$

Elastic deformations are represented by an energy ϵ(e) which depends on the position of the body frame ϕ where ϵ(x) can be represented by K(x)*x.



Figure 2.4: Displacement Model

Metaxas [Metaxas and Koh, 1996] [Metaxas, 1996] focused on utilizing the displacement model and implementing the FEM methodology for calculating the deformation component.

The work in [Astley and Hayward, 1998] simulated the dynamics of deformable visco-elastic 3-D bodies for haptic interaction. The dynamics were based on a multi-layer FEM model in which each layer represented a different level of resolution, thus minimizing the computation time.

Provot [Provot, 1995] used a physically-based model for animating cloth objects. The system used a FEM implementation and a simple Euler integration method to extract position at iterative instances of time. In order for the system to effectively animate the cloth objects, values for all parameters (mass, viscosity, damping) were provided.

In [Kang and Kak, 1996], a deformable object is modeled using a hierarchy of coarser particle resolutions. This reduced the computational overhead of a FEM implementation. [Turner, 1995] used force-based constraints such as viscosity, elasticity, gravity, air pressure, and a non-penetration constraint to simulate an elastic surface model.

In surgery simulation, users touch and interact with objects such as organs and human tissue. The physical behavior of objects therefore needs to be modeled in real time. In [Bro-Nielsen and Cotin, 1996] the feasibility of surgery simulation using the FEM methodology was shown.

[Thalmann and Thalmann, 1995] addressed human grasping of a deformable object. This work thus modeled both the human flesh and the deformable object using a FEM implementation.

[Bradau, 1996] implemented virtual grasping of a deformable object. The stiffness matrix was reduced to including only the surface nodes. The complexity of the FEM computation was reduced by determining the stiffness matrix and a corresponding grasp configuration in an off-line, pre-processing stage. A complete database was then learned which could be retrieved during on-line manipulation.

Desbrun [Desbrun and Gascuel, 1994] [Cani-Gascuel and Desbrun, 1997] used a technique for animating inelastic objects which differs from the FEM and mass-spring model implementation. An object is represented by a base structure surrounded by an elastic layer. The base structure is modeled as a particle-based system and the elastic layer is constructed of any graphic primitive (points, lines, etc.). Object movement is based on the equations of motion for the internal particles. The external elastic layer allows for visual deformation during collision. Its deformation characteristics are expressed in terms of attractive and repulsive field functions. The system was able to successfully animate soft bodies compacting against a rigid surface.

Chaudhuri [Chaudhuri and Chatterjee, 1991] used a vision approach to determine an objects' deformation characteristics. An object's movement in 3-D space can be modeled by its deformation, rotation and translation terms. In this work, the system needed only subset correspondence between 3-D feature points on the object at two different time instances in order to determine an object's deformation and rotation parameter. Subset correspondence is when a given set of feature points can be classified into a number of subsets and the correspondence between such subsets at different time instances is known. The deformation parameters were obtained by utilizing the changes in the squared Euclidean distance between different points before and after object movement. One of the main limitations with this approach was the need for the subset correspondence. In order to ensure such a correspondence, the system must have the ability to uniquely mark points located on the object. In the robotic world, this is usually not feasible, especially when a system is dealing with a multitude of different objects.

2.5 Summary of the Literature

Manipulation of 3-D deformable objects is one of the least addressed research areas in robotics. Many robotic systems which address manipulation of deformable objects focus on robotic force and position control for environments possessing compliant properties. In many of the research works belonging to this category, deformation of the object is usually incorporated directly into force calculation and force feedback is utilized to ensure grasp stability. This manipulation process therefore becomes computationally expensive and requires in-depth knowledge of system characteristics in order to complete a task. These system characteristics can range from object dimensions to stiffness coefficients and density parameters. Normally, when an object is unexpectedly presented to the system, such information as this is not readily available. Some of the systems focused on deformation control versus force control. In these systems, the robot manipulator is designed to control the deformation of the object. Efforts in this category ranged from assuming all knowledge to assuming no knowledge about the object characteristics. Of the research reviewed, there were some novel techniques which used neural networks and genetic algorithms to detect the deformation characteristics of an object. In a fruit harvesting process, the robot determined the firmness of fruit by squeezing as a human operator does. Some processes even modeled the environment with nonlinear characteristics and incorporated this unknown nonlinearity directly into the controller. But even those systems which did not assume knowledge of object characteristics were limited in that they assumed manipulation of an object with no more than two flexible degrees of freedom.

Deformable objects also appear in the field of robotics in terms of grasping with soft fingers. In this category, the topics ranged from the utilization of software control strategies for ensuring robot compliancy to the development of specialized robotic sensing devices. This type of research suffers from the same limitations as does rigid manipulation of compliant objects. Robotic systems which address manipulation of deformable objects basically fall into two categories. On one hand, those which do not assume knowledge of deformable object attributes fail to address 3-D deformable object manipulation, with many researchers feeling that by addressing the simpler one-dimensional case, a generalized three dimensional solution can be easily found. Unfortunately, no one has, as of yet, developed a generalized solution to manipulation of 3-D deformable objects.

Dynamic modeling of deformability has been studied in the fields of computer graphics and vision. In computer graphics, deformation is seen as a tool for producing realistic looking animations. This differs from simulation in that the focus is on visually appealing behavior rather than producing physically valid behavior of an object based on physical laws. For simulating physically valid behavior, the computer graphics world uses physically based models. In this category, there are two main models used to describe the dynamics of a deformable object - the FEM model and the spring-mass model. The FEM model produces more realistic looking behavior but is a computationally intense process. The spring-mass model is easy to implement, but it is difficult to transplant the real world deformation attributes to the model itself. The main limitation with these techniques are that these systems are more concerned with the simulation of realistic looking animations and disregard the actual forces required to implement the desired deformation. Thus, the simulations can not easily be transplanted to a real world environment. Currently there are some efforts which focus on virtual control prototyping in which a user interacts with a virtual deformable object in the exact same way they would interact with the physical object. This is required especially for interfacing with haptic interfaces and for remote surgery applications. These efforts suffer from the same limitations as those facing the robotic world. These systems assume in-depth knowledge of object characteristics is available for inclusion into the simulated environment.

The problems which arise in grasping of non-rigid objects have been inadequately addressed in previous research attempts. In the following sections, we shall address these limitations and describe a technique which does not require prior in depth knowledge of object attributes for manipulation of 3-D deformable objects.

Chapter 3

Deformable Object Model

In this thesis, we will discuss the approach used to address the problem of manipulation of 3-D deformable objects. In order to address this issue, we must first answer the following questions:

- What physical representation is most appropriate for representing a non-rigid object?
- What parameters are necessary to describe the deformation of a non-rigid object?
- How do we calculate these deformation characteristics?

3.1 Deformable Object Representation

3.1.1 Constructing a Physically Based Model

At the submiscroscopic scale, all solid material is composed of atoms. Adjacent atoms in a solid exhibit both attractive and repulsive forces. These forces keep the atoms at an equilibrium distance from each other. When the spacing between atoms is increased, a pulling force is created which tends to pull the atoms toward each other. In an equivalent manner, if the spacing is decreased, a pushing force is created which pushes the atoms away from each other. The tendency to maintain this equilibrium spacing leads to an 'elastic' manifestation.

The grouping of atoms leads to the formation of solids. A solid can be classified as crystalline, amorphous or a combination of both. A crystalline material is made up of crystals, an orderly array of atoms arranged in three dimensional rows such that each atom is at an equilibrium distance from each other. This structural arrangement is called a space lattice [Byars and Snyder, 1969] (Fig 3.1). An amorphous material is made up of molecules, the arrangement of atoms into chains or sheets. In both types of classifications, elastic action consists of atomic distortions caused by an externally applied force in which relative distances between atoms is increased or decreased. When the externally applied force is removed, the atoms return to their original configuration. Since the atomic spacing is altered when a force is applied, an elastic action also results in volume change.



Figure 3.1: Space Lattice Arrangement

A crystalline material has an orderly atomic arrangement and thus we shall utilize its atomic structural characteristics to approximate the modeling of an elastic solid. We shall utilize the space lattice arrangement to represent an elastic object as a particle based system constructed from a discretized sampling of its volume. The particle based representation of the object consists of the set Ψ of particles. $\alpha > 0$ represents the object discretization constant and N represents the number of particles in Ψ. Each particle $\psi_n \in \Psi : (1 \leq n \leq N)$ has a mass m_n and an associated Cartesian position vector

$$\bar{p}_n = (x_n, y_n, z_n) = x_n\hat{i} + y_n\hat{j} + z_n\hat{k} \tag{3.1}$$

where $\hat{i}, \hat{j}$, and $\hat{k}$ are unit vectors. Let (x_0,y_0,z_0) represent the origin of the object coordinate system such that all particles $\psi_n \in \Psi$ are located in the positive quadrant. This means there exists no particle $\psi_n \in \Psi$ with a Cartesian position vector of $(x_n < 0, y_n < 0, z_n < 0)$. Given α, the discretization constant, the number of particles, N, is determined as follows:

$$N = \sum_{m=0}^{\frac{Z}{\alpha}} \sum_{n=0}^{\frac{Y_m}{\alpha}} \frac{X_{mn}}{\alpha} + 1 \tag{3.2}$$

where Z is the maximum diameter of the object in the $\hat{k}$ unit direction, Y_m is the maximum diameter of the object in the $\hat{j}$ unit direction on the $z = m\alpha$ plane, and X_{mn} is the maximum diameter of the object located on the line of intersection of the two planes, $y = n\alpha, z = m\alpha$.



Figure 3.2: Example of Determining N for a cubed object with volume D^3 and $\alpha = \frac{D}{2}$: $\Rightarrow$ N=27

Eq (3.2) allows us to 'count' the number of particles which comprise the object. But, it also allows us to determine the set Ψ of particles. We can thus represent ψ_n by the following:

$num_p = 0$
For m=0 to Z step α
  For n=0 to Y_m step α
    For p=0 to X_{mn} step α
      $z_c = m$
      $y_c = n$
      $x_c = p$
      $\Psi_{num_p} = (x_c, y_c, z_c)$

$num_p = num_p + 1$

Next

Next

Next

(3.3)

We now have a particle-based representation for the deformable object.

3.1.2 Modeling Object Deformation

Deformation of a material is caused at the microscopic level by visco-elastic interactions between molecules. This visco-elastic property is characterized by the time dependent nature between applied force and particle displacement. A prolonged applied force results in a greater particle displacement. This particle displacement describes the movement of a particle during the process of deformation. These displacements consist primarily of distortions of the atomic space lattice.

A viscoelastic material exhibits three basic characteristics: instantaneous elastic response, viscous damping, and delayed elastic response. Several simple models are used for modeling viscoelastic behavior: the Maxwell Model, the Kelvin Model, and the Standard Linear Model [Byars and Snyder, 1969]. We shall begin by focusing on a one-dimensional particle system located along the x-direction (Fig. 3.3). The Maxwell Model for this system is composed of a spring and dashpot in series. The mathematical equation defining the Maxwell Model can be written as: $\dot{x} = \frac{\dot{F}}{k} + \frac{F}{c}$. The Kelvin Model representing this system is composed of a spring and dashpot in parallel. Its relationship is defined as: $F = c\dot{x} + kx$. The last model is the Standard Linear Model as shown in Figure 3.3. It is governed by the linear differential equation $F + \frac{c}{k_2}\dot{F} = k_1 x + c\frac{k_1+k_2}{k_2}\dot{x}$. For all equations, c = damping coefficient; k, k_1, k_2 = spring constant; x = mass displacement from initial position; F = force.

Determining the parameters for both the Maxwell Model and the Standard Linear Model is difficult. Since viscoelasticity can be modeled by a spring and damper in parallel, we choose to use the Kelvin Model to represent the deformable object. In the Kelvin Model, deformation is directly proportional to the amount of load



Figure 3.3: One-dimensional particle systems

applied. Depending on the rate of loading, the dashpot acts as a damper to soak up deformation energy. In order to use this model to characterize a deformable object, we must ensure that there is enough connectivity between mass nodes within the object to adequately model its deformation. In addition, the system must remain as simple as possible by keeping the number of modeling elements to a minimum while still maintaining adequate deformation characteristic. The spring and dashpot model is uncomplicated and can be used to model deformable objects in real time applications. We shall thus utilize the Kelvin Model and characterize a deformable object as a set of particles locally interconnected by damped springs (Fig 3.4).



Figure 3.4: Network of Interconnected Particles and Springs

Let us examine a simple one-dimensional damped spring-mass model (Fig. 3.5). The mathematical equation defining this Kelvin Model can be written as:

$$\sum F_{applied} = F_{inertial} + F_{damped} + F_{spring} \tag{3.4}$$

$$\sum F_{applied} = m\ddot{x} + c\dot{x} + kx \tag{3.5}$$

where m = mass, c = damping coefficient, k = spring constant, x = mass displacement from initial position, and $\sum F_{applied}$ = summation of forces applied to the mass.



Figure 3.5: One-dimensional Damped Spring-Mass Model

Let us now extract a piece of the interconnected particle system as described above. Based on Eq (3.5), the forces acting on the n^{th} particle are accumulation of external force[1], inertial force, damping force and spring force. Using Newton's law of motion, the differential equation for motion for the n^{th} particle can be written as

$$m_n \frac{\partial^2 \Delta \bar{p}_n}{\partial t^2}(\bar{f}_n, t) + c_n \frac{\partial \Delta \bar{p}_n}{\partial t}(\bar{f}_n, t) + k_n \Delta \bar{p}_n(\bar{f}_n, t) = \bar{f}_n \tag{3.6}$$

where $\bar{f}_n$ is the summation of manipulator and weight force $(f_x, f_y, f_z) = f_x\hat{\imath} + f_y\hat{\jmath} + f_z\hat{k}$ applied to particle ψ_n, $\Delta\bar{p}_n(\bar{f}_n, t)$ is the change in the spring length of particle ψ_n given a force $\bar{f}_n$ applied for a prolonged time t, m is the mass of particle ψ_n, c_n is the damping constant and k_n is the spring constant.

3.1.3 Calculating Object Deformation

Equation (3.6) is valid for a particle $\psi_n \in \Psi$ with one damped spring connection. Real values for the inertial, damping, and elastic forces are derived from accumulation of all the interconnecting damped springs. Let $\bar{p}_n(\bar{f}_n, t)$ represent the Cartesian position of particle ψ_n given a force $\bar{f}_n$ applied for time t. Let $l_{n,i}$ represent the scalar length of the damped spring connecting particle ψ_n and ψ_i. Thus

$$l_{n,i}(t) = \parallel \bar{p}_i(\bar{f}_i, t) - \bar{p}_n(\bar{f}_n, t) \parallel \tag{3.7}$$

This gives us a designation of the spring's restlength as $l_{n,i}(0)$. If we let S_n represent the number of damped springs connected to particle ψ_n Equation (3.6) becomes:

[1]where external force is derived from the accumulation of weight and applied manipulator force

$$m_n \sum_{i=1}^{S_n} \frac{\partial^2 \Delta \bar{p}_{n,i}}{\partial t^2}(\bar{f}_n, t) + \sum_{i=1}^{S_n} \lambda_{n,i} \frac{\partial \Delta \bar{p}_{n,i}}{\partial t}(\bar{f}_n, t) + \sum_{i=1}^{S_n} D_{n,i} \Delta \bar{p}_{n,i}(\bar{f}_n, t) = \bar{f}_n \tag{3.8}$$

where

$$\Delta \bar{p}_{n,i}(\bar{f}_n, t) = [l_{n,i}(0) - l_{n,i}(t)] \frac{\bar{p}_i(\bar{f}_i, t) - \bar{p}_n(\bar{f}_n, t)}{l_{n,i}(t)} \tag{3.9}$$

m_n is the mass of particle ψ_n, $D_{n,i}$, the deformability coefficient, is a function of the force and the change in spring length, $\lambda_{n,i}$, the damping coefficient, is a function of the force and the instantaneous change in spring length, $[l_{n,i}(0) - l_{n,i}(t)]$ is the scalar change in spring length and $\frac{\bar{p}_i(\bar{f}_i,t) - \bar{p}_n(\bar{f}_n,t)}{l_{n,i}(t)}$ is the spring's unit vector $\hat{l}_{n,i}(t)$. The spring's unit vector changes with respect to time since the connected particles ψ_i and ψ_N may shift position as an external force is applied, thus resulting in a direction change. $\Delta \bar{p}_{n,i}(\bar{f}_n, t)$ therefore gives us the change in spring length in each Cartesian direction. We shall designate the particle displacement vector $\bar{d}(\bar{f}_n, t) = (d_x, d_y, d_z)$ as

$$\bar{d}(\bar{f}_n, t) = \sum_{i=1}^{S_n} \Delta \bar{p}_{n,i}(\bar{f}_n, t) \tag{3.10}$$

If we take the partial derivative of $\Delta \bar{p}_{n,i}(\bar{f}_n, t)$, we obtain the following equation

$$\frac{\partial \Delta \bar{p}_{n,i}(\bar{f}_n, t)}{\partial t} = \dot{l}_{n,i}(t) \hat{l}_{n,i}(t) \tag{3.11}$$

which represents the instantaneous change in spring length. We shall designate the particle displacement velocity vector $\bar{d}'(\bar{f}_n, t) = (d'_x, d'_y, d'_z)$ as

$$\bar{d}'(\bar{f}_n, t) = \sum_{i=1}^{S_n} \frac{\partial \Delta \bar{p}_{n,i}(\bar{f}_n, t)}{\partial t} \tag{3.12}$$

From Eq.(3.8), we see that the only parameters which are not directly defined as a function of time are the mass, deformability, and damping terms. If we assume that the mass of the object is given, we can classify object deformation in terms of the deformability coefficient $D_{n,i}$ and the damping coefficient $\lambda_{n,i}$.

Initially, we assume that the deformable object is homogeneous and exhibits linearly elastic behavior. Thus the deformability and damping coefficients maintain equivalent values for all springs such that

$$\sum_{i=1}^{S_n} D_{n,i} = S_n D \tag{3.13}$$

$$\sum_{i=1}^{S_n} \lambda_{n,i} = S_n \lambda \tag{3.14}$$

We shall thus classify the deformation characteristics in terms of D, the object deformability coefficient, and λ, the object damping coefficient. In Chapter 5, we will show how we expand our algorithm to include object nonhomogeneity and nonlinearity.

In "Tactual Discrimination of Softness" [Srinivasan and Lamotte, 1995], the ability of humans to tactually discriminate the softness of objects was investigated. Soft objects were classified as elastic objects constructed of rubber samples having different compliances. "A common mode of assessing the softness [compliance] of an object with the hand is to squeeze or indent it with the fingerpads. The resulting predominantly normal forces applied on the object cause corresponding deformations of both the object and the fingerpad" [Srinivasan and Lamotte, 1995, page 88]. Based on this physiological study, we propose using a similar procedure to determine D and λ as follows:

- 1. Using both manipulators, apply a manipulator force $\bar{F}_m = F_A \hat{i}$ against the object surface until the system is in equilibrium. Record the equilibrium time Δt. [2]
  2. Calculate the particle displacement vector $\bar{d}(F_A, \Delta t)$
  3. The deformability coefficient is $D = \frac{F_A}{d(F_A, \Delta t)}$
- 1. Using both manipulators, apply a force $F_A \hat{i}$ against the object surface. At a specific time t_m record the force $\bar{f}(t_m)$ felt by the manipulator.

[2] In equilibrium, the summation of all forces converges to zero. After the manipulator has completely stopped, we assume that the object is in equilibrium when the force measured by the force sensors is constant.

2. Calculate the particle displacement velocity vector $\bar{d}'(\bar{f}_a(t_m), t_m)$ where $\bar{f}_a(t_m) = \bar{f}(t_m) - D\bar{d}(\bar{f}(t_m), t_m)$ is the damping force.
3. The damping function is $\lambda = \frac{\bar{f}_a(t_m)}{\bar{d}'(\bar{f}_a(t_m), t_m)}$

3.1.3.1 Calculating External Object Force

Our system utilizes two cooperative manipulators, each possessing an end-effector constructed as a flat surface palm and possessing a force sensor able to detect and record any force applied to the palm's surface area. Our first task is to determine the manipulator force applied to one surface particle, ψ_N. Based on the algorithm, each manipulator applies a constant force $F_A\hat{i}$ against the object surface. We can therefore represent one manipulator face[3] by a non-negative function:

$$G(y, z) = y_0 \leq y \leq y_1; z_0 \leq z \leq z_1 \tag{3.15}$$

Let (x_c, y_c, z_c) represent the centroid of the manipulator surface after the force is applied and the object is in equilibrium. Thus every object particle located at the points where the manipulator has touched the object surface has the same i^{th} position component x_c. If the manipulator is commanded to move in the i^{th}-direction, the area of the manipulator surface is represented by the following equation:

$$A_{manipulator} = (z_1 - z_0)(y_1 - y_0) \tag{3.16}$$

Since $y_c > y_0, z_c > z_0$, this equation can be replaced by the following:

$$(z_1 - z_0)(y_1 - y_0) = (z_1 - z_c)(y_1 - y_0) + (z_c - z_0)(y_1 - y_0) \tag{3.17}$$

$$(z_1 - z_0)(y_1 - y_0) = (z_1 - z_0)(y_1 - y_c) + (z_1 - z_0)(y_c - y_0) \tag{3.18}$$

$$\tag{3.19}$$

Let $(x_p = x_c, y_p, z_p)$ represent the object surface at point p.
If

$$(z_p - z_c)(y_1 - y_0) \leq (z_1 - z_c)(y_1 - y_0) \tag{3.20}$$

[3]derived from the flat surface palm

And

$$(z_1 - z_0)(y_p - y_c) \leq (z_1 - z_0)(y_1 - y_c) \tag{3.21}$$

then the object particle located at point p is in the region encompassed by the manipulator surface. We now can associate with each particle an external applied force.

Let n_a represent the number of surface particles encompassed by the manipulator.
$\forall \psi_n \in$ object surface:
if Eq. (3.21,3.20), then $\bar{f}_n = (\frac{F_A}{n_a}, 0, 0)$
else $\bar{f}_n = (0, 0, 0)$

For all ψ_n with $\bar{f}_n \cdot \hat{i} = \frac{F_A}{n_a}$, we collapse ψ_n into one particle ψ_N (Figure 3.6) such that

$$\bar{f}_N \cdot \hat{i} = \sum_{\forall \psi_n \in surface} \bar{f}_n \cdot \hat{i} = F_A \tag{3.22}$$



Figure 3.6: Collapsing External Particle Force

3.1.3.2 Calculating Deformability from Knowledge of Object Discretization

Let ψ_N represent the particle(s) upon which the manipulator force $F_A \cdot \hat{i}$ is applied. This gives us a representation for the external force applied to particle ψ_N as $\bar{f}_N = F_A \hat{i}$. At equilibrium, all forces converge to zero. Object particles are at rest and particle velocity and acceleration equal zero. At this point, we record the equilibrium time Δt. This gives us the following relation from Equation 3.8 for the force in the i^{th} vector direction:

$$F_A = D\sum_{i=1}^{S_N}[l_{N,i}(0) - l_{N,i}(\Delta t)]\frac{\bar{p}_i(\bar{f}_i, \Delta t) - \bar{p}_N(F_A, \Delta t)}{l_{N,i}(\Delta t)} \cdot \hat{i} = D(\bar{d}(F_A, \Delta t) \cdot \hat{i}) = Dd_x \tag{3.23}$$

Based on the initial object discretization, we know the value of $l_{N,i}(0)$. We also assume that since ψ_N is a surface particle we know its Cartesian position value $\bar{p}_N(F_A, \Delta t)$ as well.[4] We therefore only need to determine the value of $l_{N,i}(\Delta t)$ and $\bar{p}_i(\bar{f}_i, \Delta t)$ for input into Equation 3.23. The values of $l_{N,i}(\Delta t)$ and $\bar{p}_i(\bar{f}_i, \Delta t)$ are based on the Cartesian position vectors of the internal particles. Since we can not determine the Cartesian position vectors without assuming knowledge of object characteristics, we shall calculate $l_{N,i}(\Delta t)$ and $\bar{p}_i(\bar{f}_i, \Delta t)$ based on the assumption that the internal object particles do not change their original positioning. The error derived from this assumption is minimal, as shown in the error analysis in Appendix A.1. This analysis tells us that if we model our deformable object with only 1 spring connected to an external particle and we assume the internal particles do not shift, then the upper bound error derived from our deformability calculations is 100%. Based on our discretization, there are 17 springs incident on an external particle. Therefore the error derived from calculating deformability for our system is upper bounded by 6%.

Based on this assumption, we calculate $\bar{d}(F_A, \Delta t)$ based on the following:

$$\bar{p}_i(\bar{f}_i, \Delta t) = \bar{p}_i(\bar{f}_i, 0) = (x_i(0), y_i(0), z_i(0)) \tag{3.24}$$

$$\bar{p}_N(F_A, \Delta t) = (x_N(0) + \Delta x, y_N(0), z_N(0)) \tag{3.25}$$

$$l_{N,i}(0) = \sqrt{(x_N(0) - x_i(0))^2 + (y_N(0) - y_i(0))^2 + (z_N(0) - z_i(0))^2} \tag{3.26}$$

$$l_{N,i}(\Delta t) = \sqrt{(x_N(0) + \Delta x - x_i(0))^2 + (y_N(0) - y_i(0))^2 + (z_N(0) - z_i(0))^2} \tag{3.27}$$

[4]equivalent to the amount the manipulator has moved against the object in the i^{th} direction

where, from Eq. 3.9,3.10

$$\bar{d}(F_A, \Delta t) = \sum_{i=1}^{S_N} \Delta \bar{p}_{N,i}(F_A, \Delta t) = [l_{N,i}(0) - l_{N,i}(\Delta t)] \frac{\bar{p}_i(\bar{f}_i, \Delta t) - \bar{p}_N(F_A, \Delta t)}{l_{N,i}(\Delta t)} \quad (3.28)$$

Using Equations 3.23 - 3.28, was can calculate deformability as:

$$D = \frac{F_A}{d_x} \quad (3.29)$$

3.1.3.3 Calculating Damping from Knowledge of Object Discretization

If we take the partial derivative of $\Delta \bar{p}_{N,i}(\bar{f}_i, \Delta t)$, we obtain the following equation

$$\frac{\partial \Delta \bar{p}_{N,i}(\bar{f}_i, \Delta t)}{\partial t} \approx \dot{l}_{N,i}(\Delta t) \hat{l}_{N,i}(\Delta t) \quad (3.30)$$

where $\dot{l}_{N,i}(\Delta t)$ is the instantaneous change in spring length and $\hat{l}_{N,i}$ is the spring unit vector. The rate of change in spring length is approximated by

$$\dot{l}_{N,i}(\Delta t) \approx \frac{l_{N,i}(\Delta t) - l_{N,i}(0)}{\Delta t} \quad (3.31)$$

We therefore obtain:

$$\dot{l}_{N,i}(\Delta t) \hat{l}_{N,i}(\Delta t) = \frac{l_{N,i}(\Delta t) - l_{N,i}(0)}{\Delta t} \hat{l}_{N,i}(\Delta t) \quad (3.32)$$

In the above defined procedure for calculating the damping coefficient, we assume Δt is the given time step and d_x is calculated as in Equations 3.23 - 3.28. The internal spring force, $\bar{F}_{spring}$, is thus determined by Dd_x. $\bar{F}_m$ represents the force measured by the manipulator. In calculating damping, we assume the manipulator force is applied at a constant rate of loading. We thus assume the object deforms with constant velocity and therefore the only acceleration inherent to the system is due to gravitational force. This gives us $\frac{\partial^2 \Delta \bar{p}_{N,i}(\bar{f}_N, t)}{\partial t^2} = g\hat{k}$ where g is the gravitational constant. From Newton's equation, the damping force in the i^{th}-direction is therefore calculated by subtracting the spring force from the total applied manipulator force:

$$F_A = (\bar{F}_m - \bar{F}_{spring}) \cdot \hat{i} = \lambda \sum_{i=1}^{S_n} \frac{l_{N,i}(\Delta t) - l_{N,i}(0)}{\Delta t} \hat{l}_{N,i}(\Delta t) \cdot \hat{i} = \lambda(\bar{d}'(F_A, \Delta t) \cdot \hat{i}) \quad (3.33)$$

If we assume that the system began at time t=0, then we only need to calculate $l_{N,i}(\Delta t)$ and $l_{N,i}(0)$ as we did in Equation 3.27.

This allows us to calculate the damping coefficient as:

$$\lambda = \frac{F_A}{\bar{d}'_x} \quad (3.34)$$

We have now defined a physical representation for the deformable object and have derived a technique for calculating the object deformation characteristics. Our next step is to find the minimum forces required for successfully manipulating the deformable object.

Chapter 4

Iterative Lifting

In this chapter, we shall discuss the approach used to successfully manipulate 3-D deformable objects. In order to address this issue, we must first answer the following questions:

- What minimal forces are necessary to grasp a deformable object?
- How do we calculate these force characteristics?
- How do we link force and deformation characteristics in order to enable future manipulation tasks?

4.1 Learning An Adequate Grasp

To learn the characteristics of an adequate grasp, we must determine the relationship between mass, deformability, damping, and force. Once this relationship is learned, we can utilize these factors to maintain a firm grasp on any deformable body by comparing the current run-time mass/deformability/damping of the object with the learned relationship. When they are equivalent, we can retrieve the minimum force required for grasping a deformable object. The steps required to handle manipulation of deformable objects are as follows:

- Learn what forces a robotic system must exert in order to successfully grasp a deformable 3-D object
    1. Determine position and dimensions of an object with known mass

2. Calculate the deformability and damping coefficients
3. Determine the minimum force necessary to grasp known object by iteratively lifting object
4. Link object attributes and grasping force into a learning table

- Retrieve the learned minimum forces required to grasp a deformable object

1. Determine position and dimensions of an object with known mass
2. Calculate the deformability and damping coefficients of the object
3. Map object attributes into the learning table to retrieve grasping force

4.1.1 Iterative Lifting

We assume that an object first presented to the system is initially in an equilibrium state. Thus the summation of all forces inherent to the object converges to zero. When an object rests on a surface, a reactive force, the surface normal is created. To ensure that the object is in equilibrium, this surface normal is equal and opposite to the given weight of the object. By discretizing an object, we must also discretize the forces such that a uniform force distribution is applied to all particles. This means that two equal and opposite external forces are initially applied to each particle when the object is in equilibrium.

$$F_w = -Mg \tag{4.1}$$

$$F_{normal} = Mg \tag{4.2}$$

$$\forall \psi_n : \bar{f}_n \cdot \hat{k} = \frac{F_w}{N} + \frac{F_{normal}}{N} = \frac{-Mg}{N} + \frac{Mg}{N} = 0 \tag{4.3}$$

$$\tag{4.4}$$

where N is the number of object particles (Eq. 3.2), M is the mass of the object, and g is the applied gravitational constant.

When the object is lifted, the surface ceases to apply a reactionary force. Therefore, the summation of external forces applied to each particle is no longer equal to zero.

$$\forall \psi_n : \bar{f}_n \cdot \hat{k} = \frac{F_w}{N} = \frac{-Mg}{N} \tag{4.5}$$



Figure 4.1: Reactionary Particle Forces Before and After Lifting

We have two manipulators, each applying an external force $F_A\hat{i}$ to the surface of an object. This force is applied until an equilibrium state is achieved and the surface particle displacement is recorded. We then proceed to lift the object. For all particles upon which the manipulator force is applied, a frictional force is added. The magnitude of this frictional force is proportional to the normal component F_A of the reaction of the manipulator.

Let μ represent the coefficient of friction (static and kinetic)
$\forall \psi_n \in$ surface particles satisfying Eq. (3.21)
if $\bar{f}_n \cdot \hat{k} < \mu F_A$ then $\bar{f}_n \cdot \hat{k} = 0$
else $\bar{f}_n \cdot \hat{k} = \frac{-Mg}{N} + D \sum \bar{d} \cdot \hat{k} + \lambda \sum \bar{d}' \cdot \hat{k} + \mu F_A$

For a 3 dimensional deformable object, slippage occurs when the system, centered around ψ_N, is underdamped. Let us look at Newton's equation for a one-particle system (Eq. 3.5). Depending on the magnitude of the damping ratio, there are three possible forms of the general solution:

- Underdamped: $\lambda < 2\sqrt{Dm} : x = \frac{mg}{D} + e^{\frac{-\lambda t}{2m}}[Acos(\mu t) + Bsin(\mu t)]$
- Critically Damped: $\lambda = 2\sqrt{Dm} : x = \frac{mg}{D} + e^{\frac{-\lambda t}{2m}}[A + Bt]$



Figure 4.2: Frictional Particle Force

- Overdamped: $\lambda > 2\sqrt{Dm} : x = \frac{mg}{D} + Ae^{r_1 t} + Be^{r_2 t}$

where $\mu = \frac{\sqrt{4Dm-\lambda^2}}{2m}$ and $r_{1,2} = \frac{-\lambda \pm \sqrt{\lambda^2-4Dm}}{2m}$

As shown in Figure 4.3, the underdamped case causes the spring displacement to overshoot its equilibrium point, thus causing slippage. The more oscillation the system undergoes, the more the spring is displaced. For this case, the dynamic stretch of the spring is defined as:

$$r_d(t) = e^{\frac{-\lambda t}{2m}}[Acos(\mu t) + Bsin(\mu t)] \tag{4.6}$$

where $\mu = \frac{\sqrt{4Dm-\lambda^2}}{2m}, A = \psi(0), B = \frac{\lambda\psi(0)+2\dot{\psi}^2}{\sqrt{4Dm-\lambda^2}}$.



Figure 4.3: Step Response of Damped-Spring Mass System

For this underdamped case, we need to find the maximum stretch of the spring past equilibirum. This maximum stretch will give us the maximum force felt by the system during oscillation since this stretch is equivalent to the spring displacement (x) in the spring force equation F=Kx. To find the maximum stretch, we take the derivative of the dynamic stretch spring equation (Eq. 4.6) and equate it to zero in order to find the time at which the maximum stretch occurs (Appendix B.1).

Based on this derivative calculation, we find that the maximum spring stretch occurs at time $t = 0, \frac{\pi}{\mu}, \frac{2\pi}{\mu}, ..., \frac{n\pi}{\mu}$. Since the system begins at time t=0, the maximum stretch of the spring past equilibrium occurs at $t = \frac{\pi}{\mu}$. The maximum force experienced by the system is therefore

$$F_{max} = D * [r_d(0) - r_d(\frac{\pi}{\mu})] \tag{4.7}$$

At equilibrium, the spring force balances the gravitational force such that

$$mg = Dr_d(t) \tag{4.8}$$

Thus, when the object is first lifted, the position of the particle away from equilibrium is $\frac{mg}{D}$. Therefore the initial value for $\psi(0)$ is $\frac{mg}{D}$. Substituting this value, along with the deformability and damping coefficients, into Equation 4.6 gives us values for $r_d(0)$ and $r_d(\frac{\pi}{\mu})$. We can thus add the weight of the particle itself and the spring stretch $r_d(0) - r_d(\frac{\pi}{\mu})$ for all attached particles in order to determine the maximum force for our S_N-dimensional system [1].

$$F = mg + D\sum_{i=1}^{S_N}[r_d^i(0) - r_d^i(\frac{\pi}{\mu})] \tag{4.9}$$

Based on this equation, we make an interesting observation that if damping = 0, the maximum force is not dependent on the deformation parameters (Appendix B.2). This means that with zero damping, the maximum force required to lift the deformable object is only dependent on object weight[2].

Although we can determine the maximum upper bound lifting force which the system can experience, in reality this will not be the desired minimum lifting force.

[1]where S_N is the number of springs connected to particle ψ_N

[2]In Appendix B.2, we show that the magnitude of the lifting force is equal to twice the object weight when damping is zero.

For the underdamped case, we must determine the minimum lifting force large enough to offset the additional spring force caused by the added spring displacement. We thus employ a process called iterative lifting.



Figure 4.4: Object slipping from Manipulator Grasp

We begin the iterative lifting process by applying a force $\bar{F}_m = F_w \hat{\imath}$ to the object and lifting the object until the object particles have stabilized position. If the object has not slipped the object is in equilibrium and a firm grasp on the object has been achieved. This then is the object lifting force L_f. We record its value at this time and terminate the lifting process. If the object has slipped from the manipulator grasp (Fig. 4.4), we increase the applied manipulator force and repeat the lifting process. Eventually a minimum force will be reached which, when applied, will be able to lift the deformable object. The force required to lift a rigid object of weight W is F_w. Therefore we know that the object lifting force must be greater or equal to this force[3]: $L_f = F_w + F_d \geq F_w$.

After learning values for the lifting force, we store this information into a index table (Fig 4.5) where given the mass, deformability, and damping coefficients we can extract the object lifting force. The table constructed is only valid for the objects explicitly learned. We wish to determine the general relationship between mass, deformability, damping, and lifting force. To accomplish this, we utilize a neural network characterized by three inputs, one hidden layer, and one output node to learn the desired relationship.

[3]we define the deformable object lifting force L_f as $F_w + F_d$ where F_d is the minimum additional force required to compensate for the linear deformation of the object.

	Deformability/Damping			
	F_0	F_{11}	F_6	F_9
Mass	F_4	F_1	F_7	F_3
	F_8	F_{10}	F_2	F_5

Figure 4.5: Lifting Force Index Table

A simple backpropagation algorithm [Rumelhart et al., 1990] is used for the training process.

4.2 Backpropagation Neural Network

An artificial neural network (ANN) is "a computational structure inspired by the study of biological neural processing" [Rao and Rao, 1995]. A neural network allows us to represent arbitrary input-output relationships without being limited to linearity. For our experiment, we wish to find a corresponding relationship between mass, deformability, damping and the lifting force output. There are different types of neural networks which can be constructed. We utilize a 3-layer feed-forward neural network which consists of: an input layer, a hidden layer, and an output layer (Figure 4.6). Each layer contains a set of processing elements, called nodes. These nodes individually compute an output value based upon a weighted sum of its inputs. In a feed-forward network, the outputs of one layer are fed as inputs into the next layer. In this way, given a set of input parameters, we can compute the corresponding output by passing the values from one layer to another. Of course, initially, we must train the network by finding a set of weights that will give us the desired output. We employ a training process called backpropagation, or the generalized delta rule. In this process, we present a set of corresponding input and output patterns to the network. Given an input pattern, the network will calculate the output, which is then compared with the desired output. The difference between the network output and the desired output is then used to change the network weights, thus minimizing the network's error. In this way, the network can learn the desired relationship.



Figure 4.6: Neural Network

Our network has three input nodes corresponding to the mass, deformability, and damping coefficients and one output node corresponding to the lifting force parameter. Our hidden layer has two processing elements. We use the sigmoidal activation function on the output value as follows:

$$f_{act}(x) = \frac{1}{1+e^{-x}} \tag{4.10}$$

where x is the weighted sum of the inputs.

We begin by randomly initializing the network weights. We then iterate through the following procedure:

Present a corresponding set of input values [4] and output values [5] to the network. For each layer, compute each node's output value net_{pj} as:

$$net_{pj} = f_{act}(\sum_i w_{ji} o_{pi}) \tag{4.11}$$

where p=0,1,2 for the input, hidden, and output layer respectively, i is the i^{th} input value, j is the j^{th} node belonging to layer p, $o_{pi} = i$, if p =0 else $o_{pi} = net_{pi}$, and w_{ji} is the weight of node j corresponding to input i . After passing inputs through the last layer, we compare the force computed by the network and the desired force L_f

[4] mass,deformability,damping
[5] lifting force

which corresponds to the given input values. Using this comparison, we change the network weights based on the following (where L_f is the desired lifting force output value):

$$\Delta w_{ji} = 0.01(\delta_{pj} o_{pi}) \tag{4.12}$$

where

$$\delta_{pj} = (L_f - o_{pj}) o_p (1 - o_{pj}) \tag{4.13}$$

for the output node and

$$\delta_{pj} = o_{pj}(1 - o_{pj}) \sum_k \delta_{pk} w_{kj} \tag{4.14}$$

for all other nodes. The network is thus trained to produce the desired lifting force output by using a gradient descent method to minimize the criterion function $J = \frac{(L_f - o_{pj})^2}{2}$

To fully train a neural network, we must divide our corresponding input-output pairs into two sets. The first set, called the training set, is used to change the network weights, as described above, until the error function is minimized. During training, each corresponding input-output pair is presented to the network one at a time. When the network weights are changed for the currently presented input-output pair, the previously learned input-output relationship may no longer correspond. We must therefore feed the entire training set to the network multiple times. The number of iterations, or epochs, required may vary depending on the relationship to be learned. The second set is called the testing set. If we train the network for too many epochs, the network becomes too specialized in that it is only able to correctly relate the input-output pairs it has trained on. The testing set is utilized to determine whether the relationship learned by the network is valid or not. We use the overall testing set error to stop training the network, thus ensuring that the network learns the correct relationship.

After training the network, we can now utilize it to extract the lifting force during run-time. In order to obtain an output from a set of input values which do not correspond to values used during the training process, the network interpolates using a process known as 'generalization'. At this time, we present the network with the given object mass, calculated deformability and calculated damping coefficients. The output of the network will give us the desired lifting force.

4.3 Grasp Stability

"A Grasped object is defined to be in equilibrium if the sum of all forces and moments acting on a body equals zero ... When a restrained (grasped) object is in a position of stable equilibrium, and is subjected to an arbitrary disturbance twist, it returns to its position of equilibrium" [Howard and Kumar, 1996]

This definition of a stable grasp leads us to three necessary conditions for maintaining a stable grasp on a homogeneous deformable object:

1. The summation of object forces and moments must equal 0.
2. Small externally applied disturbance forces do not cause the object to slip,
3. Any external force applied to the object must lie within its friction cone.

4.3.1 Equilibrium Forces

We represent a deformable object as a particle-based system constructed from a discretized sampling of its volume. The particle based representation of the object is given by a set Ψ of particles. Let N represent the number of particles in Ψ and M represent the mass of the object. Each particle $\psi_n \in \Psi$ has a mass m_n and an associated Cartesian position vector:

$$\bar{p}_n = (x_n, y_n, z_n) = x_n\hat{\imath} + y_n\hat{\jmath} + z_n\hat{k} \tag{4.15}$$

In evaluating grasp stability, we shall model the manipulator as a simple point contact with friction. With this assumption, the manipulator can apply normal and tangential forces to the object at the contact point. Finding a stable grasp with this limiting assumption guarantees that a stable grasp using the real manipulator is feasible. This is because, as the manipulator grows in size (until it corresponds to its real dimensions), more force is applied over a larger area of the object. Thus, a stable grasp achieved with one point of contact is just as stable when we add additional symmetric points of contact. To grasp the object, a manipulator force $\bar{f}_N = F_A\hat{\imath}$ is applied at position $\bar{p}_N = (x_N, y_N, z_N)$ and an opposing manipulator force $\bar{f}_K = -F_A\hat{\imath}$ is applied at position $\bar{p}_K = (x_K, y_K, z_K)$. When the object is lifted, a gravitational force is applied to each particle such that

$$\forall \psi_n \in \Psi : \bar{f}_n \cdot \hat{k} = m_n g \tag{4.16}$$

where g is the gravitational constant. In addition, a frictional force $\mu F_A \hat{k}$, known as the object lifting force, is applied at position $\bar{p}_N, \bar{p}_K$.

A deformable body is in equilibrium when the sum of the forces and the sum of the moments equals zero (Fig 4.7). This gives us the following equations:



Figure 4.7: Equilibrium Forces

$$\sum_{n=1}^{N} \bar{f}_n = 0 \tag{4.17}$$

$$\sum_{n=1}^{N} \bar{p}_n \times \bar{f}_n = 0 \tag{4.18}$$

Let $L_w = \mu F_A \hat{k} = Mg$ represent the minimum object lifting force required to successfully grasp a rigid object of weight W and coefficient of friction μ. Even though the minimum object lifting force for a deformable object $L_f \geq L_w$, we shall use this rigid object lifting force because in stable equilibrium, an increase in the disturbance force in the applied manipulator direction will not cause the contacts to slip or separate from the object. We can thus satisfy 4.17 for each vector direction.

$$\sum_{n=1}^{N} \bar{f}_n \cdot \hat{i} = \bar{f}_N \cdot \hat{i} + \bar{f}_K \cdot \hat{i} = F_A + -F_A = 0 \quad (4.19)$$

$$\sum_{n=1}^{N} \bar{f}_n \cdot \hat{j} = \bar{f}_N \cdot \hat{j} + \bar{f}_K \cdot \hat{j} = 0 \quad (4.20)$$

$$\sum_{n=1}^{N} \bar{f}_n \cdot \hat{k} = \bar{f}_N \cdot \hat{k} + \bar{f}_K \cdot \hat{k} + \sum_{n=1 \notin N,K}^{N} \bar{f}_n \cdot \hat{k} = 2\mu F_A + \sum_{n=1 \notin N,K}^{N} m_n g = 0 \quad (4.21)$$

In order to maintain our desired applied force $\bar{f}_N, \bar{f}_K$, we must fix the coordinate located along the axis which the applied manipulator force is directed. Since the manipulator force is applied in the i^{th} vector direction, we must fix the x-coordinate of $\bar{p}_N, \bar{p}_K$. Thus, in order to satisfy Equation 4.18 and maintain equilibrium, we must determine the (y,z) contact coordinate points at which to apply the manipulator force $\bar{f}_N, \bar{f}_K$.

$$\sum_{n=1}^{N} \bar{p}_n \times \bar{f}_n = 0 \quad (4.22)$$

$$\bar{p}_N \times \bar{f}_N + \bar{p}_K \times \bar{f}_n + \sum_{n=1 \notin N,K}^{N} \bar{p}_n \times \bar{f}_n = 0 \quad (4.23)$$

Summing all the components for each particle in each vector direction (Appendix C.1) gives us:

$$y_K \frac{\mu M g}{2} + y_N \frac{\mu M g}{2} - \sum_{i \notin N,K}^{N} y_n m_n g = 0 \quad (4.24)$$

$$(z_N \frac{Mg}{2} - x_N \frac{\mu M g}{2}) - (z_K \frac{Mg}{2} + x_K \frac{\mu M g}{2}) + \sum_{i \notin N,K}^{N} x_n m_n g = 0 \quad (4.25)$$

$$-y_N \frac{Mg}{2} + y_K \frac{Mg}{2} = 0 \quad (4.26)$$

The center of mass of an object is represented by the following:

$$\bar{c} = \frac{\sum m_n \bar{p}_n}{M} \quad (4.27)$$

$$c_x = \frac{\sum m_n x_n}{M} \tag{4.28}$$

$$c_y = \frac{\sum m_n y_n}{M} \tag{4.29}$$

$$c_z = \frac{\sum m_n z_n}{M} \tag{4.30}$$

Using the center of mass equations, we can simplify equations 4.24 - 4.26.

$$y_N = y_K \tag{4.31}$$

$$2y_N \frac{\mu M g}{2} = \sum_i^N y_n m_n g = gMc_y \tag{4.32}$$

$$(z_K - z_N)\frac{Mg}{2} = \sum_i^N x_n m_n g - (x_N + x_K)\frac{\mu M g}{2} = gMc_x - (x_N + x_K)\frac{\mu M g}{2} \tag{4.33}$$

Which gives us the necessary equations needed to satisfy the equilibrium criteria:

$$y_N = y_K \tag{4.34}$$

$$y_N = \frac{c_y}{\mu} \tag{4.35}$$

$$(z_K - z_N) = 2c_x - \mu(x_N + x_K) \tag{4.36}$$

Due to deformation, when the object is squeezed by the manipulators, the relative (x,y) coordinates of some of the particles may change. But, the manipulators apply a force along a line of action which intersects the center of mass. Thus, as the object is squeezed in a direction normal to the z-axis, the center of mass components in the x-y plane c_x, c_y will remain constant. Thus, we can use the object surface coordinates in the object's undeformed state to solve for the unknowns in the above equations. By satisfying these three equations, we can find an equilibrium grasp capable of grasping the deformable object.

4.3.2 Cone of Friction

The external applied manipulator force must lie within its respective friction cone (Fig. 4.8). Thus

$$\| \alpha \| < tan^{-1}\mu \tag{4.37}$$

where μ is the coefficient of friction and α is the angle between the applied force and the surface normal.



Figure 4.8: Equilibrium Forces

If the applied forces do not lie within their respective friction cones, any infinitesimal disturbance force in the direction of the applied force will result in slippage. Thus, such a grasp will be unstable. Since the applied manipulator forces are dependent on each other (colinear, with equal and opposite magnitude), the closer the sides are to parallel, the smaller the coefficient of friction needs to be in order to stably grasp the object.

The manipulator is commanded to apply a force against the surface of a deformable object. Due to the nature of its deformation, the deformable object will deform around the point of contact such that the surface normal will be parallel to the applied manipulator force. In effect, the region of contact will deform into the shape of the manipulator end-effector itself. Thus, the applied force will always be within the cone of friction. (Fig 4.9).



Figure 4.9: Equilibrium Forces

4.4 Rigid Object Lifting Force

In this section, we show that the minimum object lifting force derived from implementing our algorithm on a non-deformable object converges to the weight force F_w[6].

In Chapter 3, we show that the deformability and damping coefficients are calculated using the following two equations:

$$D = \frac{F_A}{d_x}$$
$$\lambda = \frac{F_A}{d'_x}$$

If a rigid object is presented to the system, the calculated particle displacement and particle displacement velocity vectors (Equation 3.27-3.28) will converge to zero[7]. This causes the calculated deformability coefficient D and damping coefficient λ to become very large, thus causing the damping ratio to converge to infinity. We show this in the following analysis.

As $D, \lambda >> 0$

$$D = \lambda = C \tag{4.38}$$
$$\xi = \frac{\lambda}{2\sqrt{mD}} = \frac{C}{2\sqrt{mC}} = \frac{\sqrt{C}}{2\sqrt{m}} \tag{4.39}$$
$$\lim_{C \to +\infty} \frac{\sqrt{C}}{2\sqrt{m}} = +\infty \tag{4.40}$$

Based on the general solution to the particle equations of motion (Equation 4.3), a damping ratio of infinity corresponds to the case when the springs are overdamped. Slippage only occurs when the object is underdamped. For the overdamped and critically damped cases, no additional force is required to compensate for object deformation. Thus, for the overdamped case, the required object lifting force $L_f = F_w + F_d$ becomes equal to the weight force F_w. Since a rigid object corresponds to

[6]where F_w is the minimum force neccessary to lift a rigid object of weight W

[7]Since the object does not deform, relative positioning of object particles does not change

the overdamped case, the derived minimum object lifting force extracted from our algorithm will be equal to the object weight force.

We have now defined a technique for determining the minimum forces necessary to successfully grasp a deformable object. In the next section, we will discuss how our approach can be expanded to include nonhomogeneity and nonlinearity in the grasping of deformable objects. Then, in Chapter 6, we will describe the experimental setup designed to validate these results.

Chapter 5

Methodology Expansion of Deformable Objects

5.1 Nonhomogeneous Deformable Objects

We represent a deformable object as a set of particles locally interconnected by damped springs. The particle based representation of the object is given by a set Ψ of particles. Let N represent the number of particles in Ψ. Each particle $\psi_n \in \Psi$ has a mass m_n and an associated Cartesian position vector. For each spring l_{nm} connecting particle ψ_n to particle ψ_m, there is an associated deformability coefficient D_{nm} and a damping coefficient λ_{nm}.

Thus far, we have assumed that a deformable object is homogeneous. As such, we have assumed deformability, damping, and mass characteristics are constant throughout the body. "Inhomogeneity relates to a whole composed of dissimilar or nonidentical elements or parts" [Maugin, 1993]. Inhomogeneity in a deformable object thus equates to regions of the body in which the density and deformation characteristics vary pointwise in the material.

We assume a deformable object is made up of regions of homogeneity amassed into one nonhomogeneous body. We can thus discretize an object such that a particle ψ_n and spring l_{nm} represents the smallest such region of homogeneity.

In order to manipulate a deformable object, a manipulator is first commanded to apply a given force to the surface of the object in a direction normal to the gravitational force. The manipulator is then commanded to lift the object in an upward direction. The frictional force derived from such lifting gives us the object lifting force. Let ψ_N represent the particle upon which the manipulator applies the object lifting force. Let S_N represent the number of springs connected to particle ψ_N.

For a 3 dimensional deformable object, slippage occurs when the system, centered around ψ_N, is underdamped. Let $\xi = \frac{\lambda}{2\sqrt{Dm}}$ represent the damping ratio of a one-particle damped spring system attached to particle ψ_N. Depending on the magnitude of the damping ratio, there are three possible forms of the general solution for the particle's equation of motion.

- Underdamped: $0 < \xi < 1$
- Critically Damped: $\xi = 1$
- Overdamped: $\xi > 1$



Figure 5.1: Step Response of Damped-Spring Mass System

As shown in Figure 5.1, the underdamped case causes the spring displacement to overshoot its equilibrium point, thus causing slippage. The more oscillation the system undergoes, the more the spring is displaced. Slippage of a deformable object occurs when the damping ratio $\xi < 1$. For this case, the dynamic stretch of the spring is defined as:

$$r_d(t) = e^{\frac{-\lambda t}{2m}}[Acos(\mu t) + Bsin(\mu t)] \tag{5.1}$$

where $\mu = \frac{\sqrt{4Dm-\lambda^2}}{2m}$, $A = \psi(0)$, $B = \frac{\lambda\psi(0)+2\dot{\psi}^2}{\sqrt{4Dm-\lambda^2}}$.

We can add the weight of the particle itself and the spring stretch $r_d(0) - r_d(\frac{\pi}{\mu})$ for all attached particles in order to determine the maximum force for our S_N-dimensional system [1].

$$F = mg + \sum_{i=1}^{S_N} D_{Ni} * [r_d^i(0) - r_d^i(\frac{\pi}{\mu})] \tag{5.2}$$

We make an interesting observation that if we had values for the deformability and damping coefficients for all springs connected to ψ_N, then we could run through the dynamic stretch spring equation (Eq. 5.1) and get an approximate upper bound on the object lifting force.

In order to calculate values for all connected deformability and damping coefficients, we need to incorporate multiple force/displacement tests. These tests are used to solve an under-determined system of equations for the deformation characteristics. If we apply a small enough force in the direction of the spring's unit vector, we can determine the deformability and damping coefficients for all attached springs (Appendix B.3).

In reality though, it is not an efficient practice to apply a force in all spring directions. We would then have to perform S_N force/displacement tests for each manipulator in order to determine the maximum force required to lift the nonhomogeneous deformable object.

If we take the average of the deformability coefficients of all connected springs, the average damping coefficient of these springs, and the average mass, we can get an upper bound on the spring force experienced by the system within a certain error (Appendix B.6). The average deformability coefficient is:

$$D^N_{AVG} = \frac{D_{N1} + \cdots + D_{NS_N}}{S_N} \tag{5.3}$$

And the average damping coefficient is:

$$\lambda^N_{AVG} = \frac{\lambda_{N1} + \cdots + \lambda_{NS_N}}{S_N} \tag{5.4}$$

[1] where S_N is the number of springs connected to particle ψ_N

The average mass of the system is calculated based on the weight value provided to the system. It equates to $\frac{W}{gN}$ where W is the given weight of the object, N is the number of particles in the object, and g is the gravitational constant.

An example comparison is shown in Figure 5.2 for a simplified spring system consisting of two springs (Figure 5.3). The spring force calculated when using the average deformability and damping coefficients is greater than the force calculated when using all spring deformation values within a certain error (Appendix B.6). This force comparison is depicted in the following equation:

$$ERR + F_N(D_{AVG}, \lambda_{AVG})|_1^{S_N} > F_{max}|_1^{S_N} \tag{5.5}$$

where

$$ERR = gM - (S_N - 1)\frac{gM}{S_N}exp(-\frac{\pi\sqrt{M\sum D}}{\mu M}) \tag{5.6}$$

$F_N(D_{AVG}, \lambda_{AVG})|_1^{S_N}$ is the force calculated using the average of the deformability coefficients and the average damping coefficient of the S_N springs connected to particle ψ_n and $F_{max}|_1^{S_N}$ is the force calculated using Equation 5.2.

In order to find the average deformability and average damping coefficients, we begin by using the deformability and damping coefficients as calculated previously for a nonhomogeneous object and perform multiple force/displacement tests until we find a value approaching the average deformability and average damping coefficients of the system. We begin by subdividing the connected spring space into 4 quadrants and perform a force/displacement test along the spring direction which bisects the quadrant. We will also perform a test along the spring direction which bisects all 4 quadrants. In effect, we are trying to find the average deformability by averaging the calculated deformability values for each quadrant. Thus we begin by initially performing 5 force/displacement tests. These tests are performed in the following order:

Apply Force in Spring Unit Direction:

- $(\frac{1}{\sqrt{3}}, \frac{-1}{\sqrt{3}}, \frac{-1}{\sqrt{3}})$
- $(\frac{1}{\sqrt{3}}, \frac{1}{\sqrt{3}}, \frac{-1}{\sqrt{3}})$
- $(\frac{1}{\sqrt{3}}, \frac{-1}{\sqrt{3}}, \frac{1}{\sqrt{3}})$

- $(\frac{1}{\sqrt{3}}, \frac{1}{\sqrt{3}}, \frac{1}{\sqrt{3}})$

- (1,0,0)

We then perform additional force/displacement tests until our stopping criteria is satisfied:

Perform Tests Until:

$$abs(\frac{\sum_n^T D_c^n}{T} - \frac{\sum_n^{T-1} D_c^n}{T-1}) < ERROR \tag{5.7}$$

where D_c^N is the deformability coefficient calculated for Test N (Appendix B.4), $T > 5$ is the number of force/displacement tests and ERROR is an acceptable error level (such as 1.0). On the average, we need to only perform 6 tests in total. Some example results are given in Table 5.1.

	Object A	Object B	Object C
Deformability Variation	1.0-30.0	1.0-30.0	5.0-55.0
Average Deformability	15.9	14.9	29.8
Test 1	18.5	14.3	25.4
Test 2	15.2	12.6	32.1
Test 3	13.2	9.5	29.0
Test 4	14.1	18.9	31.5
Test 5	12.8	17.0	24.8
Avg. Test	14.8	14.5	28.6
Addition Random Tests	1	1	1
Total Tests	6	6	6
Percent Error	7%	3%	4%

Table 5.1: Determination of Average Deformability

For damping, we want to find the average damping value. We use the same tests as before with our stopping criteria defined as:

Perform Tests Until:

$$abs(\frac{\sum_n^T \lambda_c^n}{T} - \frac{\sum_n^{T-1} \lambda_c^n}{T-1}) < ERROR \tag{5.8}$$

where λ_c^N is the damping coefficient calculated for Test N (Appendix B.5). Some example results are given in Table 5.2.

The error in the average damping coefficient is greater than that in calculating of the average deformability coefficient because in computing $\dot{\bar{d}}$ we use an approximation of velocity, thus increasing the error in the calculation of damping. This comparison is given in Column 4 of Fig 5.2 as an example. The force calculated using our average damping coefficient will therefore be greater than using the actual average damping coefficient because the smaller the damping, the more oscillation the spring undergoes. We are thus still ensuring that our calculated lifting force maintains an upper bound on the real object lifting force.

5.2 Inelastic Deformable Objects

Previously we have only dealt with objects characterized by linear viscoelastic behavior. The associated deformation characteristics of such an object are summarized as follows:

- Elasticity - the ability of a material to recover from deformation caused by an externally applied force. Characterized by the Deformability coefficient.
- Viscosity - the ability of a material to resist an applied force due to internal forces such as molecular attraction. Characterized by the Damping coefficient.
- Viscoelasticity - based on a combination of elastic and viscous behavior. The exhibition by a material of time-dependent, elastic deformation resulting from an applied force.

All deformable objects do not exhibit perfectly linear viscoelastic behavior. As such, we shall introduce some terms used to characterize other forms of deformation.

- Nonlinear deformation
  - Nonlinear Viscoelastic Deformation - the deformation of a material characterized by nonlinear deformability and/or nonlinear damping
  - Viscous Deformation - the deformation of a viscous liquid contained within an elastic membrane

- Nonelastic deformation
  - Plasticity - a deformable body which undergoes permanent deformation when an external force is applied.
  - Fragility - the point at which the felt object force does not increase even with increased object deformation.

5.2.1 Nonlinear Deformation

5.2.1.1 Nonlinear Viscoelastic Deformation

For a nonlinear spring ($F = K\Delta x$), the spring constant can be subdivided into two parts [FEMur, 1997].

$$K = K_l + K_{nl} \tag{5.9}$$

Where K_l is the linear spring constant portion and K_{nl} is a nonlinear function of Δx (Figure 5.4).

For a softening spring, the incremental force required to produce an additional incremental deformation decreases as the spring deformation increases. For a hardening spring, the incremental force required to produce an additional incremental deformation increases as the spring deformation increases.

In the same way, the damping constant ($F = \lambda v$) can be subdivided into two parts.

$$\lambda = \lambda_l + \lambda_{nl} \tag{5.10}$$

Where λ_l is the linear damping constant portion and λ_{nl} is a nonlinear damping function of v (Figure 5.5).

For increased damping, the incremental force required to produce an additional incremental velocity increases as the velocity increases. For decreased damping, the incremental force required to produce an additional incremental velocity decreases as the velocity increases.

Based on our previous analysis for nonhomogeneous deformable objects, the force required to lift a deformable object is upperbounded by the force calculated using the average damping and average deformability coefficients of all attached springs. We can extract a common relationship between nonlinear viscoelasticity and nonhomogeneous viscoelasticity by noting that a nonlinear object is actually nonhomogeneous with respect to deformation. Thus, instead of applying the same force in different directions (as for the nonhomogeneous case), we shall apply different forces in the same direction. By averaging the deformability and damping coefficients calculated when applying different forces, we can retrieve the average deformability and damping coefficients of all attached springs.

- Apply Manipulator Force $\bar{F}_m = F\hat{i}$ where $0 < F < W$ [2].
- Calculate Deformability and Damping Coefficients for each Force
- Calculate Average Deformability and Average Damping

5.2.1.2 Viscous Deformation

A viscous fluid, such as air, contained in a body with an elastic membrane can be characterized as a nonlinear deformable object. The percentage of viscous fluid encompassed within the elastic membrane has a direct influence on the deformability of the object. As the object is grasped, the viscous fluid is compressed. We shall define the compressibility factor as the ability of the object to affect a reactive force (called the compressibility force). This compressibility factor is a function of fluid viscosity and volume. The less fluid contained within the body and the higher the viscosity, the less the compressibility factor. Since the viscosity of water is about 37 times that of air [Houwink and de Decker, 1971], a water-filled object would have a lower compressibility factor than an air-filled object of the same percent volume.

$$Compressibility = G(\%volume, viscosity) \tag{5.11}$$

The compressibility factor results in a reactive force. The higher the compressiblity factor, the larger the reactive force. When a force is applied to a fluid-filled object, the object undergoes compression. The more compression an object undergoes, the less the object is able to deform. The viscous-filled elastic object thus

[2] Since an attached spring mass will not experience a force greater than the object's weight (W=Mg), we shall apply different forces in the range between $0 < F < W$.

exhibits a form of nonlinear elastic behavior. When the force is removed, the compressibility factor dictates whether the object will return to its original state. For example, the compressibility factor of an air-filled object of volume percent .95 is large enough to ensure that the object will return to its original state. [3]

We shall determine the deformability and damping of a viscous deformable object in the same manner as we determine nonlinear viscoelastic characteristics. We note that with a very low compressibility factor, a desired reactive force may be unachievable. For example, for a highly viscous fluid , such as water, of volume 20%, the compressibility factor will be minimum. Thus, the reactive force is minimum and thus, no matter how much we compress the object, the compressibility force may never result in the desired reactive force. For such objects as these, the deformability coefficient approaches zero, and thus we do not incorporate them into our research at this time.

5.2.2 Nonelastic Deformation

5.2.2.1 Plasticity

A plastic material deforms beyond its ability to recover its shape (Figure 5.6). In this case, an increase in force will still correspond with an increase in deformation. Thus, the desired lifting force may still be achievable. Since object shape contributes only to the force placement and not the actual required lifting force measurement, we can perform the same procedure used for calculating the deformability and damping coefficients for an elastically deformable object as for a plastically deformable object. The lifting force procedure will therefore remain the same.

5.2.2.2 Fragility

Fragility is the characteristic of an object in that with an increment in deformation, there is no additional increment in reactive force (Figure 5.7). The only means we have of detecting this phenomenon is to monitor the force as it is applied against the object. If we detect a non-increase in force coupled with an increase in deformation,

[3] At this point, we will not analytically evaluate the limits of the compressibility factor, nor derive its actual analytical expression.

we know that we have reached the object's "fragility" region. As such, the required grasping force needed to lift the object may be unachievable and thus, we do not incorporate them into our research at this time.



Figure 5.2: Spring Force Comparison of Simplified Spring System. As noted from the graph, the maximum error occurs when damping is minimum. This is because, at this point (damping near 0), the lifting force required is based on the object weight and not the deformation characteristics. Thus by adding in the ERR term, we are actually increasing the overall error



Figure 5.3: Simplified Spring System

	Object A	Object B	Object C	Object C using Velocity
Deformability Variation	5.0-55.0	0.0-50.0	0.0-40.0	
Damping Variation	0.0-10.0	0.0-20.0	0.0-15.0	
Average Damping	3.7	12.0	8.1	
Test 1	3.2	10.7	7.2	7.5
Test 2	3.2	8.2	6.0	6.1
Test 3	3.0	10.9	7.4	7.4
Test 4	3.7	10.3	8.4	9.1
Test 5	3.0	11.1	8.7	8.3
Avg. Test	3.2	10.2	7.5	7.7
Addition Random Tests	1	1	1	
Total Tests	6	6	6	
Percent Error	13%	15%	7%	5%

Table 5.2: Determination of Average Damping



Figure 5.4: Nonlinear Spring Constant Representation



Figure 5.5: Nonlinear Damping Representation



Figure 5.6: Plastic Force-Deformation Curve



Figure 5.7: Fragility Force-Deformation Curve

Chapter 6

Experimental Setup

In the previous chapters, we have discussed our methodology for the successful manipulation of 3-D deformable objects. In this chapter, we will describe two experimental setups used to validate the developed algorithm. The first setup consists of the implementation of the algorithm in a simulated environment. The second involves a physical implementation of the algorithm whose outcome is compared with the simulation results in order to test the real world validity of the developed methodology.

6.1 Simulation

In the literature section, we briefly discussed Reznik and Laugier's research on simulating the deformation of a "virtual" deformable finger as it was pressed against a rigid surface [Reznik and Laugier, 1996]. We shall utilize Reznik and Laugier's algorithm as a basis for simulating the deformation of a "virtual" deformable object as the rigid surface of the manipulators is pressed against it. Their modified algorithm will provide us with the necessary force and deformation feedback parameters required to model a 3-D deformable object in our simulated environment. Using this model, we will describe our 'iterative lifting' simulation program which calculates the deformation characteristics of 3-D deformable objects and learns the desired minimum object lifting force without assuming prior in-depth knowledge of object attributes.

6.1.1 Reznik and Laugier's Algorithm

A Particle System T is a tuple (P,S) made up of a set P of particles and a set S of springs. Each particle $p \in P$ is represented by $(m, \bar{x}, \bar{v}, \bar{f})$ where m is the particle's mass, $\bar{x}$ is the particle's vector position, $\bar{v}$ is the particle's vector velocity, and $\bar{f}$ is the vector force acting on the particle. Each spring $s \in S$ is represented by (i,j,k,μ,l_0) where $p_i, p_j \in P$ are connected by spring s, k is the spring's elastic constant, μ is the damping factor, and l_0 is the rest length. Let $\bar{u}_{ij}$ be the force spring s applies to its endpoint particles p_i and p_j. Let $\bar{u}_{ij} = (k(\parallel \bar{d} \parallel - l_0) + \mu \parallel \dot{\bar{d}} \parallel)\hat{d}$ where $k(\parallel \bar{d} \parallel - l_0)\hat{d}$ is the resultant of the tensions of the springs linking p_i to its neighbors and $\mu \parallel \dot{\bar{d}} \parallel \hat{d}$ is the viscous damping used to model in first approximation the dissipation of the mechanical energy of the model.

As we apply a force to the surface of a deformable object, the force acting on the particle at each instant of time consists of the summation of internal spring forces and any external force applied to the particle.

$$\bar{f}_i = \sum_{\forall p_i p_j \in P} \bar{u}_{ij} + \bar{F}_{external} \tag{6.1}$$

To determine particle displacement, the standard equations of motion are utilized.

$$\bar{a}_i(t) = \frac{\bar{f}_i(t)}{m} \tag{6.2}$$

$$\bar{v}_i(t) = \bar{v}_i(t - \Delta t) + \bar{a}_i(t)\Delta t \tag{6.3}$$

$$\bar{x}_i(t) = \bar{x}_i(t - \Delta t) + \bar{v}_i(t)\Delta t \tag{6.4}$$

In order to ensure spring convergence, a satisfactory time factor Δt must be chosen. The period of an oscillatory particle system is given by $T_0 = \sqrt{\frac{m}{k}}$. Thus the time factor is chosen such that $\Delta t << T_0$.

We discretize a deformable object into the set of particles P and the set of springs S using $\alpha = 1.0$ and the Procedure (3.3) as defined in Chapter 3. This gives us the initial Cartesian position vector $\bar{x}$ for each particle $p \in P$ and the rest length l_0 for each spring $s \in S$. In addition, we choose values for m, k, and μ for each spring such that

$$m = Mass$$
$$\mu = \mu_0 + \mu_1 v + \mu_2 v^2 + \mu_3 v^3$$
$$k = k_0 + k_1 \Delta x + k_2 \Delta x^2 + k_3 \Delta x^3$$

where Mass, $k_0, k_1, k_2, k_3, \mu_0, \mu_1, \mu_2$ and μ_3 are randomly determined based on the object type (perfectly elastic, nonlinear, nonhomogeneous, etc.) to be evaluated.

With these parameter values, we can model the deformation of a deformable object with Reznik and Laugier's algorithm. Once this model is constructed, we can implement the routines needed to calculate the deformation characteristics of the deformable object and calculate the minimum object lifting force.

Let p_N and p_M represent the object particles on opposing sides upon which we apply the manipulator force. Let W represent the weight of the deformable object. To calculate the deformation characteristics, we begin by applying an external force $\bar{F}_{external} = \frac{W}{2}$ to the surface of the object at particle locations N and M. We then iterate through Equations 6.1-6.4 until $\bar{f}_M = \bar{f}_N = 0$ (Eq. 6.1). At this point, we have achieved equilibrium. We call this procedure the 'squeezing operation'.

To determine object deformation characteristics, we use the values for $\bar{F}_{external}$ and $\bar{x}_M$ (Eq. 6.4) to determine the object deformability coefficient D from Equation 3.34 and the damping coefficient λ from Equation 3.29.

$$D = \frac{F_{external}}{d_x} \tag{6.5}$$
$$\lambda = \frac{F_{external}}{d'_x} \tag{6.6}$$

where d_x and d'_x are calculated as in Chapter 3. Depending on the object type, we use these coefficients to calculate the object deformation characteristics as described in Chapter 5.

After squeezing, we now need to simulate object lifting. We perform this lifting operation by applying an external vertical force to each particle $p \in P$ equal to the particle weight (Eq. 4.5). We then iterate through Reznik and Laugier's equation of motions (Eq. 6.1-6.4) until one of following two conditions are met -

Condition 1:

$$\bar{f}_N = \bar{f}_M = 0 \tag{6.7}$$

Condition 2:

$$\bar{x}_N(0) \neq \bar{x}_N(t) \tag{6.8}$$

$$\bar{x}_M(0) \neq \bar{x}_M(t) \tag{6.9}$$

where time t=0 is defined as the time at which the object is first lifted. If the first condition is satisfied, then the object has successfully been lifted. If the second condition is satisfied, then the object has slipped from the manipulator grasp.

To calculate the minimum object lifting force, we must loop through both the squeezing and lifting operations until Condition 1 is satisfied. We initially begin by applying a force equal to the object weight and then squeezing the object[1]. This initially applied force is the same force required to lift a non-deformable object of the same weight and thus acts as our starting point for the iterative lifting process (Chapter 4). After squeezing, we then lift the object[2]. If the object slips (Condition 2), the simulation program halts, the applied force $\bar{F}_{external}$ is incremented by 10% and we loop through the squeezing and lifting operations again. This process is continued until Condition 1 is satisfied and the minimum object lifting force has been retrieved. This process can be summarized as follows:

- Initialize $\bar{F}_{external} = F_{weight} \cdot \hat{i}$ for particles N and M
- While Condition 1 is not satisfied
  - Implement squeezing operation
  - Implement lifting operation
  - If Condition 2, $\bar{F}_{external} = \bar{F}_{external} + 0.1\bar{F}_{external}$
- End While

[1] Apply the squeezing operation as defined above

[2] Apply the lifting operation as defined above

In this manner, we are able to calculate the deformation characteristics of a 3-D deformable object and learn the minimum lifting force required to manipulate the object without assuming prior in-depth knowledge of object attributes. Results from our simulation program are documented in the next chapter.

6.2 Automation of Manipulator System

The physical test setup involves running our algorithm on an automated stereo-vision dual manipulator system (Figure 6.1). The dual robotic devices are used to perform the deformable object grasping routines. The vision system provides object dimension and position to the robotic manipulators for task initialization. In addition, the vision system provides feedback for determining object slippage in order to successfully accomplish the recursive learning process. In the following section, we shall describe this system in detail and give an overview of the entire recursive learning automation routine.



Figure 6.1: Dual Manipulator System

6.2.1 Vision System

In the real world, robotic systems must operate in uncertain, changing environments. The use of a vision sensor allows a robotic manipulator to perform manipulations on objects having unknown position and orientation. In addition, a vision sensor can replace costly position and force feedback devices required for manipulator error correction. Viewing a scene from two different viewpoints allows a system to make inferences about 3D structure, provided that the system can match up corresponding points in the two images. In order to use a stereo vision system for implementation of a robotic task, we must address two computational issues

- Camera Calibration
  - Deriving the relationship between camera image and real-world object position for a single camera
- Stereo Geometry
  - Matching the images attained from multiple cameras in order to retrieve 3D information

6.2.1.1 Camera Calibration using Tsai's Camera Model

Tsai's camera model [Tsai, 1987] is based on the pin hole model of perspective projection (Figure 6.2). Perspective projection describes the image process which occurs when the illumination from a 3D scene passes through a lens, converges to its focal point and then diverges onto the 2D image plane where the film is located. Due to this convergence effect, objects closer to the camera will appear larger than those further away. The pin-hole camera model is used to simplify the projection and imaging process by making the diameter of this lens infinitely small, thus requiring objects to always be in focus, regardless of their distance from the lens. Given the position of a point in the 3D world coordinate system, Tsai's camera model predicts the position of the reflected image point in 2D pixel coordinates. This model is defined using 11 parameters. Five parameters specify the internal geometric and optical characteristics (intrinsic parameters) of the camera. They are defined as:

- f - effective focal length of the pin hole camera,
- κ_1 - 1st order radial lens distortion coefficient,
- C_x, C_y - coordinates of the center of the radial lens distortion and the point at which the camera coordinate frame's Z axis intersects with the camera's sensor plane

- s_x - scale factor which accounts for any uncertainty due to framegrabber horizontal scanline resampling

The other parameters specify the 3D position and orientation of the camera frame relative to a world coordinate system (extrinsic parameters):

- R_x, R_y, R_z - rotation angles for the transformation between world and camera coordinate frames
- T_x, T_y, T_z - translational components for the transformation between world and camera coordinate frames.



Figure 6.2: Perspective Projection. (x_w, y_w, z_w): Origin of 3D Coordinate System; (x,y,z): 3D coordinate of point P; (X,Y): Origin of 2D Coordinate system; (X_u, Y_u): undistorted image coordinate of (x,y,z) if a perfect pin-hole lens is used;(X_d, Y_d): distorted image coordinate due to radial lens distortion

In order to solve for these parameters, we require a set of calibration data points consisting of 3D world coordinates of a feature point (in mm) and corresponding 2D image coordinates (in pixels). These calibration points are not required to lie in the same plane, so our calibration will be based on non-coplanar data. Using this set of calibration data points, Tsai's model is able to solve for the 11 parameters required to establish a mapping between 2D image coordinates and 3D world coordinates. Thus we can extract the 3D world coordinate position of a 2D image point. The details of Tsai's camera model are described in Appendix D.

6.2.1.2 Calibration Pattern and Centroid Extraction

The first step in Tsai's calibration routine requires that we provide a set of calibration points consisting of 3D world coordinates of a feature point (in mm) and corresponding 2D image coordinates (in pixels). We retrieve this calibration data set by imaging a calibration pattern consisting of known 3D world object points in the camera and computing the reflected image coordinates of these points.

We utilize two cameras which each provide us an image of 504x348 pixels in 256 grayscale colors. Our calibration pattern consists of 12 circles of 38.1mm diameter. Our calibration points are thus defined as the centroid location of each circle. Each circle is placed such that each centroid is located at a distance of 50.8mm from another (Figure 6.3). The origin of the camera image is located in the upper left hand corner of the image. For Camera A, the 3D Cartesian positions of the circle centroids are computed based on an origin and axis as shown in Figure 6.4. For Camera B, the Cartesian position of the circle centroids are computed based on an origin and axis as shown in Figure 6.5. Figure 6.6 shows the relative positioning of the cameras with respect to the workspace area.



Figure 6.3: Calibration Pattern



Figure 6.4: Camera A: Difference Between Real World Cartesian Coordinate System and that used for calculating the Cartesian Position of Image Points



Figure 6.5: Camera B: Difference Between Real World Cartesian Coordinate System and that used for calculating the Cartesian Position of Image Points



Figure 6.6: Camera Locations with Respect to Workspace Area



Figure 6.7: Calibration Patterns

In order to create a calibration data set consisting of non-coplanar data, we image the calibration pattern at different camera depths. Figure 6.7 shows the actual patterns as seen by each camera. To compute the centroids (and thus the calibration points), we implement the following procedure for each of our two cameras:

1. Threshold calibration pattern
2. Remove noise pixels
3. Loop through all pixels until all centroids calculated
4. Sort Centroids first by $centroid_y$ position, then $centroid_x$ position
5. Based on sorting output, link centroid's 3D world Cartesian position to image pixel position

Thresholding Since the calibration patterns are black circles on white paper, we threshold the image such that any pixels having a value below the threshold will equate to 0, and those above will equate to 255. This process ensures that the circles remain the only target items located in the scene, and classifies everything else as background. We thus equate pixels belonging to the circles as target pixels, and all else as background.

Remove Noise Pixels Noise pixels belong to those areas in the image which contain less than a given number of target pixels. This in effect removes any areas of pixels which can not belong to circle items based on a minimum size factor.

Calculate Centroids We loop through the entire calibration image to calculate the circle centroids.

- Initialize starting position at image pixel origin x=0,y=0
- Begin Loop
  - Traverse image in the +x,+y direction until we reach a non-visited target pixel [pixel(x,y) = 0]. Store starting y position ($start_y$)
  - Traverse target in the +y direction until we reach object border [$pixel(x, y) <> 0$]. Store ending y position (end_y)

- Calculate y coordinate of object center:

$$centroid_y = start_y + \frac{end_y - start_y}{2} \tag{6.10}$$

- Traverse target in the +x direction until we reach object border. Store ending x position (end_x)
- Traverse target in the -x direction until we reach object border. Store starting x position ($start_x$)
- Calculate x coordinate of object center:

$$centroid_x = start_x + \frac{end_x - start_x}{2} \tag{6.11}$$

- Save Centroid Information ($centroid_x, centroid_y$)
- Mark Target as Visited:

$$\forall start_x \leq x \leq end_x, start_y \leq y \leq end_y : pixel(x, y) <> 0 \tag{6.12}$$

- Let $x = 0, y = start_y$

• End Loop

Sorting The sorting algorithm sorts the circle centers such that the circle located closest to the image origin will be first and the one located furthest from the origin will be positioned last on the sorting list (Figure 6.8). Thus, since we know the 3D world coordinate position of each circle, and we know in which way the circles should be ordered, we can easily equate the 3D world coordinate positions to image pixel position in realtime. We perform this automatically using a lookup table (Table 6.1).

The above procedure will provide us with two files, one for each camera, containing 3D world coordinate position points and their associated 2D image points for use in the calibration routine (Appendix D).



Figure 6.8: Numbered Output of Sorting List

6.2.1.3 Stereo Geometry

Once we run through Tsai's camera model and extract the 11 parameters required for camera calibration (Appendix D), we can extract the 3D world Cartesian position (x_w, y_w, z_w) of a 2D image point (X_f, Y_f). In order to accomplish this, we first realize that there is not a unique mapping between image and real world object points[3]. We must therefore provide at least one of the relative 3D coordinates in order to extract the other two using Tsai's model. We can then implement the following procedure:

1. Convert the image point (X_f, Y_f) to undistorted sensor plane coordinates (X_u, Y_u) as shown in Appendix D

2. Given z_w, calculate x_w, y_w

$$x' = X_u - T_x \tag{6.13}$$

$$y' = Y_u - T_y \tag{6.14}$$

$$x_w = r_1 x' + r_4 y' + r_7 z_w \tag{6.15}$$

$$y_w = r_2 x' + r_5 y' + r_8 z_w \tag{6.16}$$

[3]In the real world, multiple 3D locations are mapped to the same 2D image location

where $T_x, T_y, r_1, r_2, r_4, r_5, r_7, r_8$ are derived from Tsai's camera model (Appendix D).

As seen from this procedure, in order to associate a 3D Cartesian position with a 2D image point for one camera, we need to provide the system with at least one of the relative 3D coordinates (x_w, y_w, or z_w) in order to extract the other corresponding two. We utilize the second camera in order to provide us with this additional required information.

Our cameras are located with respect to the work area as shown in Figure 6.9. Since the 3D Cartesian origin as specified with respect to the camera is different than the real world origin, we must relate the Cartesian position extracted from the calibration routine to the 3D real world Cartesian position. For Camera A, the 3D real world Cartesian position (x_r, y_r, z_r) is related to the 3D world coordinate position of the camera (x_w^A, y_w^A, z_w^A) as follows:

$$x_r = x_w^A \tag{6.17}$$

$$y_r = Y^d - y_w^A \tag{6.18}$$

$$z_r = z_w^A \tag{6.19}$$

where $Y^d = 215.9mm$ is the y-distance between the origin of the 3D real world coordinate system and the origin of the coordinate system used for calculating the Cartesian position of the 2D image points.



Figure 6.9: Camera Locations with Respect to Workspace Area

And for Camera B:

$$x_r = x_w^B \tag{6.20}$$

$$y_r = z_w^B \tag{6.21}$$

$$z_r = y_w^B \tag{6.22}$$

In order to find the 3D world coordinate position, we perform the following 'coordinate point approximation' routine:

1. Given a correlated image point from both cameras, extract a list of possible (x_r, y_r, z_r) 3D coordinate points from the above procedure for $0 \leq z_w \leq 254mm$ at iterations of z=2.54mm for each camera[4]. This will provide us with two lists of 100 possible 3D world coordinate positions related to the image point.

2. Pairwise compare each point contained in the two lists and extract the two points having the mean squared minimum distance.

3. Compute the average of the two points and denote as the selected 3D world coordinate point.

This routine will thus extract an approximate 3D world coordinate position of an image point given the correlated location of the point as seen in both cameras.

6.2.1.4 The Correspondence Problem

The problem of pairing up features in multiple images is known as the correspondence problem. For our system, we are utilizing a stereo vision system in order to extract object position and dimension. Therefore, we wish to extract the Cartesian position locations of the minimum and maximum points of the object's dimensions. We will utilize Camera A to provide our system with the x,y dimensions $(min_x^A, max_x^A, min_y^A, max_y^A)$ of the object and Camera B will provide our system with the x,z dimensions $(min_x^B, max_x^B, min_z^B, max_z^B)$ of the object. We thus only need to find correspondence between these minimum and maximum points in order

[4] $z_w = 254mm$ is the maximum dimension of any deformable object which can be presented to the robotic system.

to retrieve the correct x,y,z dimensions of the object. We shall utilize our x dimension, which can be seen by both cameras, to simply identify two correlation points. Based on the positioning of the cameras, the minimum x pixel and its associated minimum y pixel in Camera A will correspond to the maximum x pixel and its associated minimum y pixel (corresponding to the z dimension) in Camera B. In the same way, the maximum x pixel and its associated minimum y pixel in Camera A will correspond to the minimum x pixel and its associated minimum y pixel in Camera B (Figure 6.10). Thus, our correlation points will be:

- Correlation Point 0: Camera A-(min_x^A, min_y^A); Camera B-(max_x^B, min_y^B)
- Correlation Point 1: Camera A-(max_x^A, min_y^A); Camera B-(min_x^B, min_y^B)



Figure 6.10: Correlation Points

In order to find the min_x, max_x, and min_y pixel in the image attained from Camera A and the min_x, max_x, and min_y pixel in the image attained from Camera B, we perform the following steps (Figure 6.11):

1. Threshold Image
2. Remove Noise
3. Find Object Boundary

4. Follow Object Boundary

5. Store Boundary Values



Figure 6.11: Top: Initial Camera Image; Bottom Left: Image Result after Thresholding and Noise Removal; Bottom Right: Image Result after Boundary Following

Threshold Image The color of the background upon which the object is placed is higher in value than the object itself (equating to a lighter color). We thus begin by thresholding the camera image in order to distinguish background pixels from object pixels. Object pixels will thus equate to 0 and background pixels to 255. This process though does not ensure that all non-target pixels are removed from the image scene. This is mainly because the manipulators themselves can be seen by both cameras and are reflected in the camera images. Thus, pixels belonging to the manipulator will still be classified as target pixels.

Remove Noise Noise pixels belong to those areas in the image which contain less than a given number of target pixels. We thus remove any areas of pixels classified as objects which can not belong to the deformable object based on a minimum size factor. In addition, we remove outliers which are defined as those target pixels located near the image edge. This is because most of the outlier pixels actually belong to the manipulator itself, and thus, the deformable object can not be located in this space.

Find Object Boundary The target object is presented to the vision system in such a way that it is visible in both cameras. Thus, our first task it to find a point located within the interior of the object. We will utilize this pixel location as a starting point to find the object boundary.

In order to find an interior point, we divide the camera image space into R regions. Each region represents the smallest image area that an object can occupy. We then sum up the number of object type pixels in each region. The two adjacent regions with the largest number of pixels are designated as containing the object. We then average the center coordinates of both regions to determine an interior object point. To begin, we define the following:

- A = region with largest number of object pixels
- B = adjacent region with next largest number of object pixels
- (x_A, y_A) = center coordinate point of region A
- (x_B, y_B) = center coordinate point of region B
- P_A = number of pixels in region A
- P_B = number of pixels in region B
- $P = P_A + P_B$

Thus the coordinate point located within the object interior is evaluated as:

$$\frac{P_A}{P} * (x_A, y_A) + \frac{P_B}{P} * (x_B, y_B) \tag{6.23}$$

Beginning at this point, we traverse the object interior in the +y direction until we reach the object boundary.

Follow Object Boundary Beginning at the edge of the object's boundary, we follow the object's shape in order to extract the object dimensions. We begin by applying an edge detector filter that compares the relative brightness of adjacent pixels in order to extract all edges in the image. We then perform a line following routine.

- Initialize the direction in which to follow the boundary edge
- Traverse boundary, pixel by pixel, by locating the next edge pixel situated in the currently traversed direction. If no edge pixel exists in current direction, change direction in clockwise fashion. Loop until boundary is mapped and all edge pixels are visited. Store perimeters defining object boundary.

Store Boundary Values Once we've found the object boundary, we store the minimum x (and the corresponding minimum/maximum y) and maximum x (and the corresponding minimum/maximum y) of Boundary. These stored values will equate to the min_x^A,max_x^A,min_y^A, max_y^A of Camera A and the min_x^B, max_x^B, min_y^B, max_y^B of Camera B.

We now have 2 correlation points which we feed into Equations 6.13- 6.22 and use the coordinate point approximation routine to find the 3D world coordinate position of these points. This will provide us with the max_x,min_x,max_z of the object dimensions in 3D real world coordinates. To extract the y dimension of the object, we use the (min_x^A, min_y^A) and (min_x^A, max_y^A) points of the object border and the approximated Cartesian z-dimension max_z for z_w in Equations 6.13-6.22. Our object dimensions will thus be defined as:

$$Dim(x) : max_x - min_x \tag{6.24}$$

$$Dim(y) : max_y - min_y \tag{6.25}$$

$$Dim(z) : max_z \tag{6.26}$$

To retrieve position information, we use the center of the sides facing each Microbot. We thus get:

$$Position_A : (min_x, min_y + \frac{Dim(y)}{2}, \frac{Dim(z)}{2}) \tag{6.27}$$

$$Position_B : (max_x, min_y + \frac{Dim(y)}{2}, \frac{Dim(z)}{2}) \tag{6.28}$$

And thus we are able to calculate object dimension and position from utilization of our stereo vision system.

6.2.1.5 Determining Object Slippage

In addition to providing object dimension and position information for our automation task, we also utilize our vision system to determine object slip during the recursive lifting process. In order to detect object slippage, two steps are instituted. Before the object is lifted, the average grayscale color G_A of a small region of the object is calculated from the camera image.

$$Size(G_A) = 0.1 * (x_{max} - x_{min}) * (y_{max} - y_{min}) \tag{6.29}$$

After lifting, the average grayscale color G_B of the same region in the camera image is calculated (Figure 6.12).

If

$$\| G_A - G_B \| < ERR \tag{6.30}$$

Then we record object slippage else we say the object was successfully grasped.



Figure 6.12: Determining Slippage from Camera Images. The average grayscale value of the highlighted rectangle is the region used to determine slippage. Top: Camera Image Before Lifting; Bottom Left: Image from a Slipped Object; Bottom Right: Image from a Successfully Grasped Object

	3-D World Coordinate Points (in mm)			
	Camera A		Camera B	
	Image 1	Image 2	Image 1	Image 2
1	$(46, 165.1, 0)$	$(46, 165.1, 63.5)$	$(198.4, 152.4, 63.5)$	$(198.4, 152.4, 0)$
2	$(96.8, 165.1, 0)$	$(96.8, 165.1, 63.5)$	$(147.6, 152.4, 63.5)$	$(147.6, 152.4, 0)$
3	$(147.6, 165.1, 0)$	$(147.6, 165.1, 63.5)$	$(96.8, 152.4, 63.5)$	$(96.8, 152.4, 0)$
4	$(198.4, 165.1, 0)$	$(198.4, 165.1, 63.5)$	$(46, 152.4, 63.5)$	$(46, 152.4, 0)$
5	$(46, 114.3, 0)$	$(46, 114.3, 63.5)$	$(198.4, 101.6, 63.5)$	$(198.4, 101.6, 0)$
6	$(96.8, 114.3, 0)$	$(96.8, 114.3, 63.5)$	$(147.6, 101.6, 63.5)$	$(147.6, 101.6, 0)$
7	$(147.6, 114.3, 0)$	$(147.6, 114.3, 63.5)$	$(96.8, 101.6, 63.5)$	$(96.8, 101.6, 0)$
8	$(198.4, 114.3, 0)$	$(198.4, 114.3, 63.5)$	$(46, 101.6, 63.5)$	$(46, 101.6, 0)$
9	$(46, 63.5, 0)$	$(46, 63.5, 63.5)$	$(198.4, 50.8, 63.5)$	$(198.4, 50.8, 0)$
10	$(96.8, 63.5, 0)$	$(96.8, 63.5, 63.5)$	$(147.6, 50.8, 63.5)$	$(147.6, 50.8, 0)$
11	$(147.6, 63.5, 0)$	$(147.6, 63.5, 63.5)$	$(96.8, 50.8, 63.5)$	$(96.8, 50.8, 0)$
12	$(198.4, 63.5, 0)$	$(198.4, 63.5, 63.5)$	$(46, 50.8, 63.5)$	$(46, 50.8, 0)$

Table 6.1: Table Lookup Values for Calibration Points from Fig. 6.7

6.2.2 Automation Routine

The dual manipulator system (Figure 6.13) consists of two Microbots, each possessing a flat-plate end-effector. The surface of the flat-plate is constructed of sandpaper. We utilize sandpaper to ensure that our coefficient of friction is very close to 1.0. Each manipulator possesses a force sensor (Figure 6.14) able to read applied forces in the range ± 50N at a resolution of 0.5N.



Figure 6.13: Dual Manipulator System

The two manipulators are commanded using inverse kinematics (Appendix E). Thus, given a location x,y,z in 3D world coordinates, the system determines the necessary joint angles required to position the manipulator end-effector at the desired Cartesian location (Figure 6.16). The only difference between the joint angles required to control the two manipulators is that both the base and wrist joints must be equal and opposite in magnitude. This allows us to achieve the appearance of approximate parallelism. All other joint parameters will maintain equivalent values with respect to each manipulator.

For automation, the camera system determines object dimension and passes the center side position to the Microbots. Internally, we discretize the object using the calculated dimensions and a discretization constant equal to 1.0. The Microbots then move to each side of the object ensuring that the flat-plate end-effector is positioned normal to the object side (Figure 6.15). The Microbots then perform X squeezing operations[5]. After each such operation, the outputs from the force sensors are read. These force values, along with the amount the object was squeezed (Δx) are fed into Equations 3.34,3.29 for calculating the deformability and damping coefficients. The iterative lifting process is then begun. For the first iteration attempt, a force equivalent to the Weight Force is applied. The Microbots then attempt to lift the object until the manipulators have moved a distance of 0.5*object height. After "lifting", the cameras are used to determine whether the object has been successfully grasped. If the object is no longer in the grasp of the manipulator, the Microbots reposition themselves against the object's side, increment the lifting force by 20%, and begin the lifting process again. At some point, the object will be successfully grasped and the object lifting force is recorded.

And thus, our system autonomously determines the deformable object lifting force.

Results from the physical runs and comparison with the simulation results are documented in the next chapter.

[5]Each Microbot applies a force against the object, thus "squeezing" the object. We perform 3 such operations.



Figure 6.14: Robotic Gripper EndTool with Force Sensor



Figure 6.15: Orientation of Gripper with Respect to Object



Figure 6.16: Robotic Arm Structure

Chapter 7

Results

7.1 Simulation Results

A simulation program was written for implementation of the learning algorithm. For object representation, we assume that:

- Coefficient of friction equals 1.0
- At time t = 0, object is fixed in a stable position
- Weight of the object is provided during run time.

The object presented to the system is a six-sided convex object with each side possessing equivalent dimensions of 24 cm. The discretization constant α is defined as 1.0. The number of particles N (Eq. 3.2) sums to 27 particles. After discretization, the object is represented as below:



Figure 7.1: Set Ψ of Particles

7.1.1 Homogeneous, Perfectly Elastic Simulation Results

For this set of results, we assume:

- Object is isotropic and homogeneous
- Object displays perfectly linear elastic behavior

In order to calculate the deformability and damping coefficients (Eq 3.29,3.34), we need to extract a value for the external particle displacement Δx given an applied manipulator force $\bar{F}_{external}$. We utilize Reznik and Laugier's algorithm to provide the value of Δx. We input into their algorithm values for the particle weight, deformability coefficient, damping coefficient, and external applied manipulator force $\bar{F}_{external} = \frac{Mg}{2}\hat{i}$ applied to the surface particles. We then utilize Equations 6.1-6.4 to provide us with the external particle displacement value Δx. This extracted displacement value Δx and the external applied manipulator force $F_{external} = \frac{Mg}{2}$ is input into Eq. 3.29,3.34 for calculating D, the deformability coefficient, and λ, the damping coefficient. For a given deformability coefficient D, and damping coefficient λ, we begin to simulate the iterative lifting process by 'lifting' the object until we have achieved a successful grasp. At this point, we record the minimum object lifting force. Table 7.1 tabulates values for the actual parameters used as inputs to model the deformable object in Reznik and Laugier's algorithm, the resulting deformability and damping coefficients determined by our calculations, the learned minimum object lifting force and the theoretical lifting force calculated from Equation 5.2[1].

The theoretical lifting force as documented in Table 7.1 represents the maximum force required to lift a deformable object given the object's weight, deformability, and damping coefficients. This theoretical lifting force is computed based on the assumption that all springs attached to our external particle[2] are allowed to move independently of one another. This concept does not exactly represent the behavior of our model, since all particles attached to an external particle are also attached to other internal particles. Based on this dependency, we shall begin our analysis of the lifting force error by looking at the factors used to compute the theoretical lifting force.

[1] We only use this equation for the underdamped case

[2] The particle upon which we apply the manipulator force

We begin by examining, at what transition point, the object transforms from an underdamped to critically damped/overdamped system. If you recall, the maximum object lifting force required to lift an object that possesses critically damped or overdamped characteristics is equivalent to the force required to lift a non-deformable object of the same weight. For independently attached springs, this transition occurs when the damping ratio[3]≥ 1. Based on our simulation results, we conclude that, for our system, the transition occurs when the damping ratio ≈ 3.6. If $\xi < 3.6$, the interactions between particles causes an increase in the overall oscillation of the system, even though, individually, the springs are not underdamped. Using this boundary condition ($\xi < 3.6$) as the transition point between an underdamped and critically damped system, we get a maximum error of 18.8%. This comparison is shown in Table 7.2.

We shall now examine the situation which occurs when the damping ratio is very small and thus the springs, independently, exhibit maximum oscillation. Due to the spring interconnection within the object, a maximally underdamped spring (damping ratio = 0) can not actually experience its full range of oscillation. Each spring located within the deformable object is positioned such that its unit vector is at a 45 degree angle from the unit vector direction of its vertical neighbor (Figure 7.2). Based on this angular information, we extrapolate that the maximum range of vertical motion a spring can experience before 'colliding' with its neighbor is equivalent to 3/4 of its range[4]. For our system, we must now define the boundaries at which the maximum oscillation occurs. We already know that a damping ratio of 0 gives us maximum oscillation. Based on our simulation, we can also conclude that maximum oscillation occurs for all damping ratios < 0.1. This gives us a maximum error of 13.7% and is as shown in Table 7.3. These results are the theoretical results given in Table 7.1.

We now examine the error derived in calculating the deformability and damping coefficients (Table 7.4). We first note that the maximum error derived in our computation of the damping coefficient is greater than the deformability coefficient's maximum error value. In addition, the maximum damping error occurs when the

[3]The damping ratio is defined as $\xi = \frac{\lambda}{2\sqrt{Dm}}$

[4]Based on Eq. 5.2, the maximum range of oscillation occurs at 180 degrees into the cycle. Thus, $\frac{45}{180} degrees = 3/4$



Figure 7.2: Particle Unit Vector Relationship

damping coefficient is approximately 0 (when $\lambda < 1.0$). This maximum error mainly occurs because we approximate the velocity of the particle in order to calculate the damping coefficient. With such a small damping, the resulting damping force is so small that even with a minimal velocity error, our damping coefficient error becomes maximum. On the other hand, although we retrieve a maximum error of 14% in computing deformability and 27% for our damping computation, we note that the difference between the damping ratios is less than 0.3. Thus, the maximum difference between the damping ratios using the actual values and the damping ratios using the calculated values is minimal. Since the damping ratio defines the amount of spring oscillation inherent in the system and has the most influence on the calculation of the theoretical object lifting force, we can confidently state that our calculation of the deformability and damping coefficients is satisfactory.

Based on our results, we observe that our theoretically calculated lifting force is accurate to within 14% of our simulation lifting force. Depending on the time constant used, a typical lifting simulation can take anywhere from 3-20 minutes[5]. On the other hand, running through the theoretical equations gives us almost instantaneous results. Considering the amount of interaction that is inherent within the system and the complexity of the 3D model used, we accept the error level between the theoretical and simulation as acceptable and conclude that we can actually use the theoretical equations themselves to compute the object lifting force.

After learning the minimum force required to successfully grasp a multitude of deformable objects possessing different deformation characteristics, we can now train

[5]Time based on using Matlab on a 133Mhz processor

the neural network on the tabulated data. Our network possesses 3 input nodes representing the deformability coefficient, damping coefficient, and object weight, two hidden nodes, and 1 output node representing the minimum object lifting force. For our simulation, we incorporate 40 corresponding input-output pairs into the training set and 33 corresponding input-output pairs into the testing set. The minimum error derived from the testing set occurred when we trained the network for 1000 epochs. The neural network testing set output results are shown in Table 7.5.

The maximum error retrieved from the network is $< 14.8\%$. Based on this error calculation, we conclude that there is a derivable relationship between weight, deformability, damping and the object lifting force. In addition, since the neural network error is approximately the same as that derived from using the theoretical lifting force equations, we conclude that our theoretical equations definitely gives us acceptable results. In fact, we conclude that we could use the theoretical equations in place of the simulation and neural network and still achieve desirable results for the homogeneous, perfectly elastic case.

Simulation Input			Calculated		Learned	Theoretical	
Weight (N)	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Lifting Force (N)	Lifting Force(N)	Percent Error (%)
18.99	35.89	5.68	31.69	5.78	25.44	25.32	0.47
17.70	11.13	2.98	9.62	2.82	23.74	23.60	0.59
45.17	30.58	1.80	28.08	2.02	75.63	76.10	0.62
17.70	11.14	2.98	9.63	2.82	23.75	23.60	0.63
107.12	34.25	13.06	30.23	13.40	143.85	142.83	0.71
39.43	16.71	5.48	14.61	5.29	52.95	52.57	0.72
76.38	16.14	8.13	14.08	8.01	100.89	101.84	0.94
49.16	45.52	11.02	40.18	10.24	64.83	65.55	1.11
21.15	50.71	6.60	44.98	6.44	28.72	28.20	1.81
56.33	45.99	12.32	40.54	13.16	73.73	75.11	1.87
58.38	17.70	6.49	15.51	6.89	79.38	77.84	1.94
50.34	41.66	0.15	39.49	0.19	93.04	94.96	2.06
95.15	25.51	12.24	22.37	12.74	124.16	126.87	2.18
52.46	23.87	6.76	21.05	6.54	71.99	69.95	2.83
81.27	24.92	8.32	22.00	8.11	112.43	108.36	3.62
4.47	10.50	8.80	10.50	8.80	4.64	4.47	3.66
47.22	46.08	0.08	43.74	0.10	86.99	90.72	4.29
9.09	31.14	0.75	28.74	0.89	14.94	15.72	5.22
96.97	12.89	9.69	11.23	10.14	122.68	129.29	5.39
76.93	18.31	2.49	16.52	2.77	124.83	117.55	5.83
29.95	44.79	11.06	39.30	10.54	37.72	39.93	5.86
52.50	29.39	11.91	25.71	12.37	65.80	70.00	6.38
76.28	19.97	12.48	17.39	12.16	94.82	101.71	7.27
33.42	24.46	0.97	22.56	1.13	57.47	62.14	8.13
21.38	49.99	4.07	44.98	4.22	31.45	28.51	9.35
17.15	11.36	9.11	9.80	8.58	19.02	17.15	9.83
99.13	14.66	3.82	13.28	4.15	149.79	134.93	9.92
67.91	14.61	2.98	13.13	2.59	105.23	93.71	10.95
109.63	40.44	6.58	36.56	6.84	168.87	149.88	11.25
45.91	10.94	9.38	9.43	8.80	54.28	61.21	12.77
47.01	45.68	0.87	42.86	1.02	82.90	94.02	13.41
47.56	16.25	13.12	14.06	13.20	55.09	47.56	13.67

Table 7.1: Homogeneous, Perfectly Elastic Simulation Results

Simulation Input			Learned	Theoretical		Theoretical	
Weight (N)	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Lifting Force (N)	Initial Pass Lifting Force(N)	Percent Error (%)	1st Pass Lifting Force(N)	Percent Error (%)
21.38	49.99	4.07	31.45	21.38	32.02	28.51	9.35
95.58	43.68	8.90	139.37	95.58	31.42	127.44	8.56
72.91	50.15	8.29	105.96	72.91	31.19	97.21	8.26
78.60	28.33	6.67	114.19	78.60	31.17	104.80	8.22
57.00	36.47	6.43	82.50	57.00	30.91	76.00	7.88
35.60	10.48	2.90	51.14	35.60	30.39	47.47	7.18
51.77	23.09	5.30	74.05	51.77	30.09	69.03	6.78
72.35	41.90	9.90	100.26	72.35	27.84	96.47	3.78
81.27	24.92	8.32	112.43	81.27	27.72	108.36	3.62
52.46	23.87	6.76	71.99	52.46	27.13	69.95	2.83
58.38	17.70	6.49	79.38	58.38	26.46	77.84	1.94
21.15	50.71	6.60	28.72	21.15	26.36	28.20	1.81
39.63	15.49	5.12	53.61	39.63	26.08	52.84	1.44
50.21	47.67	10.25	67.55	50.21	25.67	66.95	0.89
107.12	34.25	13.06	143.85	107.12	25.53	142.83	0.71
39.43	16.71	5.48	52.95	39.43	25.53	52.57	0.72
17.70	11.14	2.98	23.75	17.70	25.47	23.60	0.63
17.70	11.13	2.98	23.74	17.70	25.44	23.60	0.59
18.99	35.89	5.68	25.44	18.99	25.35	25.32	0.47
70.73	19.52	8.63	93.55	70.73	24.39	94.31	0.81

Table 7.2: Comparison of Theoretical Results - 1st Pass

Simulation Input			Learned	Theoretical		Theoretical	
Weight (N)	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Lifting Force (N)	1st Pass Lifting Force(N)	Percent Error (%)	2nd Pass Lifting Force(N)	Percent Error (%)
81.90	19.79	0.15	137.88	163.80	18.80	153.75	11.51
47.56	16.25	13.12	55.09	47.56	13.67	47.56	13.67
19.51	10.56	6.34	22.89	26.01	13.63	26.01	13.63
47.01	45.68	0.87	82.90	94.02	13.41	94.02	13.41
24.21	15.94	9.92	27.83	24.21	13.01	24.21	13.01
4.35	38.34	6.68	5.00	4.35	13.00	4.35	13.00
45.91	10.94	9.38	54.28	61.21	12.77	61.21	12.77
27.00	42.91	0.29	47.99	54.00	12.52	48.01	0.04
15.82	45.56	0.00	28.19	31.64	12.24	31.06	10.18
15.77	23.54	10.74	17.90	15.77	11.90	15.77	11.90
19.29	34.78	10.49	23.06	25.72	11.54	25.72	11.54

Table 7.3: Comparison of Theoretical Results - 2nd Pass

Simulation Input				Calculated			Error		
Weight (N)	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Damping Ratio	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Damping Ratio	Deformability Error (%)	Damping Error (%)	Damping Ratio Difference
50.34	41.66	0.15	0.03	39.49	0.19	0.03	5.21	26.67	0.01
81.90	19.79	0.15	0.03	18.48	0.19	0.04	6.62	26.67	0.01
47.22	46.08	0.08	0.01	43.74	0.10	0.02	5.08	25.00	0.00
27.00	42.91	0.29	0.07	40.51	0.35	0.09	5.59	20.69	0.02
40.81	41.66	0.15	0.03	39.47	0.18	0.04	5.26	20.00	0.01
9.09	31.14	0.75	0.36	28.74	0.89	0.45	7.71	18.67	0.09
47.01	45.68	0.87	0.15	42.86	1.02	0.18	6.17	17.24	0.03
33.42	24.46	0.97	0.28	22.56	1.13	0.33	7.77	16.49	0.06
103.60	14.22	2.40	0.51	13.14	2.72	0.60	7.59	13.33	0.09
67.91	14.61	2.98	0.77	13.13	2.59	0.71	10.13	13.09	0.06
45.17	30.58	1.80	0.39	28.08	2.02	0.46	8.18	12.22	0.07
76.93	18.31	2.49	0.54	16.52	2.77	0.63	9.78	11.24	0.09
59.92	33.03	3.14	0.57	30.08	3.48	0.67	8.93	10.83	0.09
67.90	14.61	2.90	0.75	13.13	2.59	0.71	10.13	10.69	0.04
15.77	23.54	10.74	4.54	20.42	9.69	4.39	13.25	9.78	0.14
99.13	14.66	3.82	0.82	13.28	4.15	0.93	9.41	8.64	0.12
100.81	12.59	3.59	0.82	11.48	3.87	0.93	8.82	7.80	0.11
23.32	43.19	2.61	0.67	38.40	2.81	0.76	11.09	7.66	0.09
49.16	45.52	11.02	1.90	40.18	10.24	1.87	11.73	7.08	0.02
56.33	45.99	12.32	1.97	40.54	13.16	2.24	11.85	6.82	0.27
77.71	32.07	11.92	1.94	28.21	12.72	2.21	12.04	6.71	0.27
48.04	38.68	11.91	2.25	33.97	11.12	2.24	12.18	6.63	0.01
72.35	41.90	9.90	1.46	37.21	9.25	1.45	11.19	6.57	0.01
45.91	10.94	9.38	3.41	9.43	8.80	3.44	13.80	6.18	0.04

Table 7.4: Comparison of Deformation and Damping Ratio Differences

NN Input			Expected Output	NN Output	
Weight (N)	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Lifting Force (N)	Lifting Force (N)	Percent Error (%)
40.81	41.66	0.15	74.57	74.41	0.22
56.33	45.99	12.32	73.73	73.95	0.30
47.22	46.08	0.08	86.99	87.92	1.07
39.63	15.49	5.12	53.61	52.72	1.66
19.51	10.56	6.34	22.89	22.51	1.68
76.93	18.31	2.49	124.83	122.35	1.98
27.00	42.91	0.29	47.99	48.96	2.02
39.43	16.71	5.48	52.95	51.85	2.07
95.58	43.68	8.90	139.37	135.70	2.63
95.15	25.51	12.24	124.16	127.91	3.02
67.91	14.61	2.98	105.23	108.42	3.03
59.92	33.03	3.14	96.51	99.86	3.47
52.46	23.87	6.76	71.99	74.66	3.71
45.91	10.94	9.38	54.28	52.22	3.80
51.77	23.09	5.30	74.05	76.93	3.90
56.52	11.70	9.65	68.19	70.97	4.08
78.60	28.33	6.67	114.19	119.12	4.32
18.99	35.89	5.68	25.44	26.56	4.42
81.90	19.79	0.15	137.88	131.31	4.76
21.15	50.71	6.60	28.72	30.12	4.89
17.70	11.14	2.98	23.75	25.11	5.72
60.38	37.36	4.64	92.85	98.31	5.88
23.32	43.19	2.61	36.28	38.47	6.03
57.00	36.47	6.43	82.50	87.71	6.32
99.13	14.66	3.82	149.79	140.12	6.45
58.38	17.70	6.49	79.38	84.64	6.62
72.35	41.90	9.90	100.26	106.98	6.71
37.26	49.00	10.90	48.39	44.28	8.49
21.38	49.99	4.07	31.45	34.48	9.65
109.63	40.44	6.58	168.87	146.15	13.45
29.95	44.79	11.06	37.72	32.59	13.59
34.82	3.46	10.40	36.97	31.86	13.82
28.94	45.56	11.43	36.20	30.87	14.73

Table 7.5: Simulation Results: Neural Network Output

7.1.2 Nonhomogeneous Simulation Results

We document our nonhomogeneous deformable object results in Table 7.6. For this simulation run, we present an object possessing variable deformability, damping, and weight characteristics for each spring and object particle. We then calculate the average deformability and damping values using Equations 5.7-5.8 and compare it with the real averages as computed in Equations 5.3-5.4. We then perform the iterative lifting process and retrieve the minimum object lifting force. This value is compared with the theoretical lifting force as computed in Equation 5.5.

	Object A	Object B	Object C
Deformability Variation ($\frac{N}{cm}$)	1.0-20	1.0-30.0	1.0-50.0
Real Average Deformability	9.8	14.8	28.6
Calculated Deformability	9.6	15.9	29.8
Percent Difference	2.5%	7%	4%
Damping Variation ($\frac{Ns}{cm}$)	0.0-5.0	0.0-10.0	0.0-15.0
Real Average Damping	2.5	3.7	8.1
Calculated Average Damping	1.9	3.2	7.5
Percent Difference	23.6%	13%	7%
Weight Variation (N)	0.1-2.1	1.0-2.0	1.0-2.0
Average Particle Weight	1.08	1.53	1.34
Real Damping Ratio	0.38	0.39	0.65
Calculated Damping Ratio	0.30	0.32	0.59
Damping Ratio Difference	0.08	0.07	0.06
Simulation Lifting Force (N)	47.8	56.2	48.4
Theoretical Lifting Force + ERR	53.8	61.6	54.4
Percent Difference	12.7%	9.6%	12.4%

Table 7.6: Nonhomogeneous Simulation Results

For the nonhomogeneous case, we compute the theoretical lifting force by adding in an error term to compensate for the nonhomogeneity of the object. With this added term, we see that our theoretical lifting force is still accurate to within 13% of our simulation lifting force. As before, the error in calculating the average deformability is less than the error in computing the average damping. And yet the damping ratio differences are still < 0.3. Although the nonhomogeneous case possesses much more complexity than the homogeneous, perfectly elastic case, we conclude that we have successfully addressed the nonhomogeneity issue in determining the theoretical lifting force.

The main issue that remains is how do we determine whether an object is homogeneous or nonhomogeneous? This distinction is necessary so that we can autonomously determine whether to include the error term into the theoretical lifting force calculation (or not). If you recall, we compute the deformability and damping coefficients by performing a minimum of 6 force-displacement tests (Chapter 5). If, for all tests, the calculated deformability and damping coefficients remain constant, we can conclude that the object is homogeneous. This distinction will allow us to determine which set of equations to use for the theoretical lifting force and thus, still maintain our 13.7% error level for all homogeneous and nonhomogeneous object types.

7.1.3 Nonlinear Simulation Results

We document our nonlinear deformable object results in Table 7.7-7.8. For this simulation run, we present an object possessing deformability and damping characteristics which are functions of the particle displacement and velocity respectively. We then calculate the average deformability and damping values using Equations 5.7-5.8 and compare it with the real averages as computed in Equations 5.3-5.4. We then perform the iterative lifting process and retrieve the minimum object lifting force. This value is compared with the theoretical lifting force as computed in Equation 5.5.

From our nonlinear simulation results, we see that we get a maximum error of 18.8%. This error shows that our theoretical lifting force is not as accurate as we would like for the nonlinear case. We would therefore like to evaluate the reasons why our error is so high. The graphs representing the springs constructing Objects A,B, C, and D are as shown in Figure 7.3-7.6. If we examine the graph for Object A, we see that the damping function increases much more rapidly than the deformability function. This means that our damping ratio will increase as the object is deformed. For Object B, we see that the damping function increases while our deformability function decreases. This also accounts for an increase in the damping ratio as the object is deformed. An increase in the damping ratio corresponds to a decrease in the spring oscillation, and thus a decrease in the required object lifting force. On the other hand, Object C has a decreasing damping ratio while Object D's damping ratio remains fairly constant. Based on this observation, we conclude that we must increase the force range used to compute the average deformability and damping coefficients for those objects with an increased damping ratio. In determining the average damping and deformability coefficient, we apply a force in the range $0 < F < W$ (where W is the weight of the object). In actuality though, a particle can experience a force of up to twice its weight[6]. We therefore re-compute the average deformability and damping coefficients using a force in the range $0 < F < 2W$ for those objects with an increased damping ratio. This will ensure that we are incorporating a better approximation for the damping ratio.

[6]when attached to another particle with an undamped spring

Using this approach gives us the theoretical lifting forces as in Table 7.9. These results are acceptable as they give us a maximum error of $< 12.5\%$.

	Object A	Object B
Deformability Function ($\frac{N}{cm}$)	$30 + 50\Delta x + (20\Delta x)^3$(H)	$20 - 20\Delta x - (10\Delta x)^2$ (S)
Real Average Deformability	31.06	19.69
Calculated Avg. Deformability	26.56	25.96
Percent Difference	14.5%	31.8 %
Damping Function ($\frac{Ns}{cm}$)	$1 + v + v^2$ (I)	$3 + v + v^2$ (I)
Real Average Damping	1.56	3.34
Calculated Average Damping	2.63	3.53
Percent Difference	68.6 %	5.7%
Weight (N)	27	27
Simulation Lifting Force (N)	46.6	37.2
Theoretical Lifting Force + ERR	55.4	43.0
Percent Difference	18.5 %	15.7 %

Table 7.7: Nonlinear Simulation Results with (H):hardening deformability, (S):softening deformability, (I):increased damping

	Object C	Object D
Deformability Function ($\frac{N}{cm}$)	$40 - 20\Delta x - (10\Delta x)^2$ (S)	$25 + 50\Delta x + (20\Delta x)^3$ (H)
Real Average Deformability	39.84	25.34
Calculated Avg. Deformability	25.88	25.55
Percent Difference	35 %	.8%
Damping Function ($\frac{Ns}{cm}$)	$5 - v^2$ (D)	$7 - v^2$ (D)
Real Average Damping	4.94	6.95
Calculated Average Damping	5.29	6.76
Percent Difference	7.1%	6.8 %
Weight (N)	27	27
Simulation Lifting Force (N)	38.2	36.2
Theoretical Lifting Force + ERR	41.8	36.0
Percent Difference	9.6%	.6%

Table 7.8: Nonlinear Simulation Results with (H):hardening deformability, (S):softening deformability, (D):decreased damping

	Object A	Object B	Object C	Object D
Simulation Lifting Force (N)	46.6	37.2	38.2	36.2
Theoretical Lifting Force + ERR	52.4	40.9	41.8	36.0
Percent Difference	12.4 %	9.9 %	9.6 %	0.6 %

Table 7.9: Nonlinear Simulation Results



Figure 7.3: Comparison of Linear vs Nonlinear Functions for Object A Springs



Figure 7.4: Comparison of Linear vs Nonlinear Functions for Object B Springs



Figure 7.5: Comparison of Linear vs Nonlinear Functions for Object C Springs



Figure 7.6: Comparison of Linear vs Nonlinear Functions for Object D Springs

7.2 Physical Implementation Results

For this physical implementation, we utilize four deformable objects, each with different deformation characteristics and weights. The objects relative properties are given in Table 7.2.1.

The iterate lifting process is diagramed for the four objects as shown in Figures 7.7-7.10. The values used to calculate the object deformation parameters are given in Table 7.12. And our physical implementation results are tabulated in Table 7.14. Given these results, we now examine the differences in the physical object lifting force and the simulation/theoretical lifting force and give reasons for our error calculations as follows.

We first examine the simulation/theoretical lifting force derived for the cotton object. The force sensor that is utilized in our robotic system has a resolution of 0.05N. Based on this resolution, the actual damping force for the cotton object can not be determined accurately (Table 7.12, Row 2). If the damping force was equivalent to the sensor resolution ($= 0.05N$), the damping coefficient would be 5.55 and the associated Simulation Lifting Force would be 1.47N. This would give us a lifting force error of 14.5%.

We now address the sand object lifting force calculation. The sand object exhibits large nonlinearities in the damping force. As more force is applied to the object, the damping force decreases. This is due to the fact that the sand within the object body shifts downward as the object is held. Thus, the harder the object is held, the less movement of the sand is possible. Table 7.13 shows the damping force retrieved as the object is squeezed. We use the last row for our damping coefficient calculation. We note though, as the object is squeezed, the damping force converges to zero. This would give us a damping coefficient of 0 and an associated Simulation Lifting Force of 5.2N. Our lifting force error would then be 2.9%.

For the water and the sponge object, we achieve a 9.8% and 14% error value respectively. The sponge object error is mainly due to the fact that its weight is so small that it is difficult to achieve an accurately applied lifting force autonomously. This is because the feedback algorithm used to establish the manipulator applied force is not precise.

Overall, we conclude that we can achieve an error level of 14% with respect to the simulation/theoretical lifting force. This is actually equivalent to the maximum error derived from our simulation results. Even with our inaccurate sensor resolution and force feedback routine, we can achieve surprisingly good results. With more accurate equipment, we could decrease this error to an even lower level.

7.2.1 Results Overview

In this section, we validated our developed algorithm with two sets of experiments. The first experimental results were derived from the implementation of the algorithm in a simulated environment. The second set involved a physical implementation of the technique whose outcome was compared with the simulation/theoretical results to test the real world validity of the developed methodology. Based on the results, we are able to show that we can achieve both a physical, simulation, and theoretical lifting force for the same deformable object which only differs from each other by a maximum of 14%. In fact, with more accurate equipment, the results derived from our theoretical equations shows us that we could use our equations to get a measurement for the minimum lifting force required to lift a deformable object without having to physically perform the iterative lifting process. We could derive the required lifting force from the equations and input them into the robotic device for lifting. The iterative lifting process would then only need to be performed to incrementally compensate for the 14% error.



Figure 7.7: Physical Implementation: Lifting Diagram for Sponge Object



Figure 7.8: Physical Implementation: Lifting Diagram for Cotton Object



Figure 7.9: Physical Implementation: Lifting Diagram for Sand Object



Figure 7.10: Physical Implementation: Lifting Diagram for Water Object

Object	Interior	Weight (N)	Dimensions (x,y,z) - cm
A	Sponge	0.7	17.78 x 19.05 x 9.21
B	Cotton	1.4	19.05 x 19.69 x 19.05
C	Sand	2.9	11.43 x 11.43 x 9.53
D	Water	4.9	10.8 x 11.43 x 8.89

Table 7.10: Physical Implementation: Object Characteristics

	Dimensions (cm) Extracted from Vision Algorithm
Sponge	18.29 x 18.67 x 9.12
Cotton	19.66 x 21.67 x 17.70
Sand	12.52 x 11.94 x 9.39
Water	10.8 x 12.5 x 8.5

Table 7.11: Physical Implementation: Calculated Object Characteristics

	Amount Squeezed (cm)	Deformability Force (N)	Damping Force (N)	Squeezing Time (s)
Sponge	0.075	2.00	0.0070	3.80
Cotton	0.357	2.25	0.003	20.80
Sand	0.114	1.97	0.008	3.98
Water	0.452	2.85	0.000	13.04

Table 7.12: Values Used to Calculate Deformation Parameters

Amount Squeezed (cm)	Damping Force (N)
0.088	0.054
0.101	0.013
0.114	0.008

Table 7.13: Damping Force as Sand Object is Squeezed

	Calculated			Simulation	Theoretical
	Deformability ($\frac{N}{cm}$)	Damping ($\frac{Ns}{cm}$)	Lifting Force (N)	Lifting Force (N)	Lifting Force (N)
Sponge	49.18	6.47	0.84	0.7	0.7
Cotton	13.03	0.33	1.72	2.23	2.05
Sand	30.02	0.47	5.97	4.86	4.83
Water	10.52	0.00	10.23	11.13	9.8

Table 7.14: Physical Implementation Results

Chapter 8

Conclusions

8.1 Summary

In this dissertation, we developed a generalized algorithm capable of successfully manipulating 3-D deformable objects without assuming prior in-depth knowledge of object attributes. Our methodology was able to incorporate a wide variety of deformable object types including those possessing asymmetric, nonhomogeneous, and inelastic attributes. Our approach was subdivided into two main tasks. The first task involved calculating the deformation characteristics for a non-rigid object represented by a physically-based model. These deformation characteristics were defined using two parameters - Deformability and Damping. Using nonlinear partial differential equations, we modeled the particle motion of the deformable object in order to calculate these deformation characteristics. For our second task, we calculated the minimum force required to lift the deformable object. This lifting force consisted of a combination of the base force required to lift a rigid object of the same weight plus an additional force term which successfully compensated for the deformation of the object. This minimum lifting force was learned using a technique called iterative lifting in which the robotic system learns the required lifting force by lifting the object with iterative measurements of force. We showed that this minimum lifting force was upper bounded by the force retrieved from force summation of the internal object springs. Once the deformation characteristics and the associated lifting force term were determined, they were used to train a neural network for extracting the minimum force required for subsequent deformable object manipulation tasks. We validated our developed algorithm with two sets of experiments. The first experimental results were derived from the implementation of the algorithm in a simulated environment. The second set involved a physical implementation of the technique whose outcome was compared with the simulation results to test the real world validity of the developed methodology.

8.2 Future Work

The eventual goal of this research effort is to create a robotic system able to manipulate deformable objects without any human intervention. To this effect, there are many extensions necessary in order to develop a truly autonomous system.

In our system we assume that we are only manipulating 3-D deformable objects versus 1-D deformable objects such as beams or 2-D objects such as cloth sheets. In the real world, an automated robotic handling system must be robust when faced with any deformable object. Thus, an extension to the work would be to formalize the distinction between 1-D, 2-D, and 3-D deformable objects such that the system could successfully switch between deformable object manipulation techniques.

In our work, we assume that the coefficient of friction is constant. In reality, this is not a valid assumption. A manipulator grasping a greasy deformable object will not possess the same coefficient of friction as a non-greased object. An extension would be to incorporate a friction sensing algorithm into the system. Perhaps if the coefficient of friction is too low, a different manipulation scheme, such as 'scooping' the object, would need to be utilized. Another assumption made in the algorithm is that the object's weight is provided during runtime. For a truly robust system, we need to incorporate a way for the robotic system to extract weight information without external assistance.

In our research, we define the 'compressibility factor' as a term used to characterize the ability of a viscous-filled object to affect a reactive force (called the compressibility force). This compressibility factor was defined as a function of fluid viscosity and volume. For this research effort, we did not develop an analytical expression for the compressibility factor, nor did we evaluate its limits. A future research endeavor would be to formalize the compressibility factor relationship.

Currently, we do not incorporate fragile objects into our research. Such objecs as these exhibit a crushing characteristic[1]. For future research efforts, the developed algorithm should be modified to deal with these fragile deformable objects.

In our research, we model a deformable object as a set of particles locally interconnected by damped springs. Although the Kelvin model, by itself, is uncomplicated, the fact that we discretize a deformable object in order to calculate deformation characteristics causes our system to be computationally expensive. A future extension would be to investigate the usage of other models, which not only perform efficiently in real time applications, but can operate with non quasi-static systems.

One of the restrictions we placed on our system was that it exhibits quasi-static properties. Thus, the speed at which the manipulators are commanded to lift the deformable object is moderate. For systems with large accelerations, a force feedback technique must be developed which can maintain the same applied force, even when dealing with highly viscous objects in which the object shape and center of mass may change appreciably over time.

Such extensions as these would enable a robotic system to successfully manipulate deformable objects in a truly autonomous fashion.

[1]The characteristic of an object in that it deforms beyond its ability to recover its shape.

Bibliography

[Akella and Cutkosky, 1995] Akella, P. and Cutkosky, M. (1995). Contact transition control with semiactive soft fingertips. *IEEE Transactions on Robotics and Automation*, 11(6):859–867.

[Al-Jarrah and Zheng, 1998] Al-Jarrah, O. and Zheng, Y. (1998). Intelligent compliant motion control. *IEEE Transactions on Systems, Man, and Cybernetics*, 28(1):116–122.

[Annaswamy and Seto, 1993] Annaswamy, A. and Seto, D. (1993). Object manipulation using compliant fingerpads: Modeling and control. *Transactions of the ASME*, 115:638–648.

[Astley and Hayward, 1998] Astley, O. and Hayward, V. (1998). Multirate haptic simulation achieved by coupling finite element meshes through Norton equivalents. In *IEEE International Conference on Robotics and Automation*, pages 989–994.

[Atilgan and Hodges, 1991] Atilgan, A. and Hodges, D. (1991). Unified nonlinear analysis for nonhomogeneous anisotropic beams with closed cross sections. *AIAA Journal*, 29(11):1990–1999.

[Beer and Johnston, 1988] Beer, P. and Johnston, E. (1988). *Vector Mechanics for Engineers*. McGraw-Hill, New York.

[Bradau, 1996] Bradau, B. (1996). Deformability and force return for virtual objects grasping. In *Second ECPD International Conference on Advanced Robotics*, pages 510–515, Vienna.

[Bro-Nielsen and Cotin, 1996] Bro-Nielsen, M. and Cotin, S. (1996). Real-time volumetric deformable models for surgery simulation using finite elements and condensation. *Computer Graphics Forum*, 15(3):57–66.

[Burdea, 1996] Burdea, G., editor (1996). *Force and Touch Feedback for Virtual Reality*. John Wiley and Sons Inc., New York.

[Byars and Snyder, 1969] Byars, E. and Snyder, R. (1969). *Engineering Mechanics of Deformable Bodies*. International Textbook Company, Pennsylvania.

[Cani-Gascuel and Desbrun, 1997] Cani-Gascuel, M.-P. and Desbrun, M. (1997). Animation of deformable models using implicit surfaces. , *IEEE Transactions on Visualization and Computer Graphics*, 3(1):39–50.

[Chaudhuri and Chatterjee, 1991] Chaudhuri, S. and Chatterjee, S. (1991). Motion analysis of a homogeneously deformable object using subset correspondences. *Pattern Recognition*, 241(8):739–745.

[Chen and Zheng, 1991] Chen, M. and Zheng, Y. (1991). Deformation identification and estimation of one-dimensional objects by using vision sensors. In *International Conference on Robotics and Automation*, pages 2306–2311, Sacramento, CA.

[Chen and Zheng, 1995] Chen, M. and Zheng, Y. (1995). Vibration-free handling of deformable beams by robot end-effectors. *Journal of Robotic Systems*, 12(5):331–347.

[Chiaverini et al., 1994] Chiaverini, S., Siciliano, B., and Villani, L. (1994). Force/position regulation of compliant robot manipulators. *IEEE Transactions on Automatic Control*, 39(3):647–652.

[Crandall et al., 1978] Crandall, S., Dahl, N., and Lardner, T., editors (1978). *An Introduction to the Mechanics of Solids*. McGraw-Hill, New York.

[Cutkosky, 1985] Cutkosky, M., editor (1985). *Robotic Grasping and Fine Manipulation*. Kluwer Academic Publishers, Boston.

[Desbrun and Gascuel, 1994] Desbrun, M. and Gascuel, M.-P. (1994). Highly deformable material for animation and collision processing. In *Fifth Eurographics Workshop on Animation and Simulation*, Norway.

[Fearing, 1984] Fearing, R. (1984). Simplified grasping and manipulation with dexterous robot hands. *A.I. Memo 809 MIT*, pages 1–17.

[FEMur, 1997] FEMur (1997). Finite element method universal resource. *http://femur.wpi.edu*.

[Flander, 1985] Flander, H., editor (1985). *Calculus*. W.H. Freeman and Company, New York.

[Flugge, 1967] Flugge, W. (1967). *Viscoelasticity*. Blaisdell Publishing Company, Massachussetts.

[Flynn et al., 1998] Flynn, D., Peura, G., Grigg, P., and Hoffman, A. (1998). A finite element based method to determine the properties of planar soft tissues. *Journal of Biomechanical Engineering: Transactions of the ASME*, 120(2):202–210.

[Fowley and Horton, 1995] Fowley, D. and Horton, M., editors (1995). *MATLAB User's Guide*. Prentice Hall, New Jersey.

[Gibson and Mirtich,] Gibson, S. and Mirtich, S. A survey of deformable modeling in computer graphics. *http://www.merl.com*.

[Greenwood, 1965] Greenwood, D. (1965). *Principles of Dynamics*. Prentice-Hall, New Jersey.

[Gudukbay and Ozguc, 1994] Gudukbay, U. and Ozguc, B. (1994). Animation of deformable models. *Computer-Aided Design*, 26(12):251–262.

[Hirai et al., 1995] Hirai, S., Noguchi, H., and Iwata, K. (1995). Transplantation of human skillful motion to manipulators in insertion of deformable tubes. In *IEEE International Conference on Robotics and Automation*, pages 1900–1905, Japan.

[Honda, 1997] Honda, S. (1997). Development of an intelligent gripper with a dynamic vibration absorber. *International Journal Japan Soc. Precision Engineering*, 31(1):63–67.

[Hopcroft et al., 1991] Hopcroft, J., Kearney, J., and Krafft, D. (1991). A case study of flexible object manipulation. *International Journal of Robotics Research*, 10(1):41–50.

[Houwink and de Decker, 1971] Houwink, R. and de Decker, H., editors (1971). *Elasticity, Plasticity, and Structure of Matter*. Cambridge University Press, London.

[Howard and Kumar, 1996] Howard, W. and Kumar, V. (1996). On the stability of grasped objects. *IEEE Transactions on Robotics and Automation*, 12(6):904–917.

[Joukhadar et al., 1997] Joukhadar, A., Garat, F., and Laugier, C. (1997). Parameter identification for dynamic simulation. In *IEEE International Conference on Robotics and Automation*, pages 1928–1933.

[Kang and Kak, 1996] Kang, H. and Kak, A. (1996). Deforming virtual objects interactively in accordance with an elastic model. *Computer-Aided Design*, 28(4):251–262.

[Kao et al., 1997] Kao, I., Cutkosky, M., and Johansson, R. (1997). Robotic stiffness control and calibration as applied to human grasping tasks. *IEEE Transactions on Robotics and Automation*, 13(4):557–566.

[Katic and Vukobratovic, 1998] Katic, D. and Vukobratovic, M. (1998). A neural network based classification of environment dynamics models for compliant control of manipulation robots. *IEEE Transactions on Systems, Man, and Cybernetics*, 28(1):58–68.

[Kemp et al., 1986] Kemp, D., Taylor, G., Taylor, P., and Pugh, A. (1986). A sensory gripper for handling textiles. In *Robot Grippers*, pages 155–164. IFS Publications.

[Kraus and McCarragher, 1996a] Kraus, W. and McCarragher, B. (1996a). Control of flexible load deformations and environment contact forces in dual-arm manipulation. In *Proceedings of the 13th IFAC World Congress*, pages 61–66, San Francisco, CA.

[Kraus and McCarragher, 1996b] Kraus, W. and McCarragher, B. (1996b). Force fields in the manipulation of flexible materials. In *, Proceedings of the 1996 IEEE International Conference on Robotics and Automation*, pages 2352–2357, Minneapolis.

[Kraus and McCarragher, 1997] Kraus, W. and McCarragher, B. (1997). Case studies in the manipulation of flexible parts using a hybrid position/force approach. In *Proceedings International Conference on Robotics and Automation*, pages 367–372.

[Logan et al., 1994] Logan, I., Wills, D., and N.J., A. (1994). Deformable objects in virtual environments. In *Second UK VR-SIG Conference*, pages 88–103, U.K.

[Lorenz et al., 1990] Lorenz, R., Meyer, K., and Van De Riet, D. (1990). A novel, compliant, four degree-of-freedom robotic fingertip sensor. *IEEE Transactions on Industry Applications*, 26(4):613–619.

[Luo and Ito, 1993] Luo, Z. and Ito, M. (1993). Control design of robot for compliant manipulation on dynamic environments. *IEEE Transactions on Robotics and Automation*, 9(3):286–296.

[Mandal and Payandeh, 1995] Mandal, N. and Payandeh, S. (1995). Control strategies for robotic contact tasks: An experimental study. *Journal of Robotic Systems*, 12(1):67–92.

[Maugin, 1993] Maugin, G. (1993). *Material Inhomogeneities in Elasticity*. Chapman and Hall, London.

[Medguid and Zhu, 1995] Medguid, S. and Zhu, Z. (1995). A novel finite element for treating inhomogeneous solids. *Int. Journal for Numerical Methods in Engineering*, 38(9):1579–1592.

[Meer and Rock, 1994] Meer, D. and Rock, S. (1994). Experiments in object impedance control for flexible objects. In *Proceedings International Conference on Robotics and Automation*, pages 1222–1227.

[Metaxas, 1996] Metaxas, D., editor (1996). *Physics-Based Deformable Models: Applications to Computer Vision, Graphics, and Medical Imaging.* Kluwer Academic Publishers, Boston.

[Metaxas and Koh, 1996] Metaxas, D. and Koh, E. (1996). Flexible multibody dynamics and adaptive finite element techniques for model synthesis and estimation. *Computer methods in applied mechanics and engineering*, 136:1–25.

[Monkman, 1995] Monkman, G. (1995). Robot grippers for use with fibrous materials. *International Journal of Robotics Research*, 14(2):144–151.

[Naghdy and Esmaili, 1996] Naghdy, F. and Esmaili, M. (1996). Soft fruit grading using a robotics gripper. *International Journal of Robotics and Automation*, 11(3):93–100.

[Nemat-Nasser and Hori, 1995] Nemat-Nasser, S. and Hori, M. (1995). Universal bounds for overall properties of linear and nonlinear heterogeneous solids. *Journal of Engineering Materials and Technologies: ASME*, 117(4):412–432.

[Patton et al., 1992] Patton, R., Swern, F., Tricamo, S., and van der Veen, A. (1992). Automated cloth handling using adaptive force feedback. *Journal of Dynamic Systems Measurements and Control*, 114:731–733.

[Pollard, 1990] Pollard, N. (1990). The grasping problem: Toward task-level programming for an articulated hand. *MIT Technical Report 1214*, pages 1–93.

[Provot, 1995] Provot, X. (1995). Deformation constraints in a mass-spring model to describe rigid cloth behavior. In *Graphics Interface '95*, pages 147–154.

[Rao and Rao, 1995] Rao, V. and Rao, H. (1995). *C++ Neural Networks and Fuzzy Logic*. MIS:Press, New York.

[Reznik and Laugier, 1996] Reznik, D. and Laugier, C. (1996). Dynamic simulation and virtual control of a deformable fingertip. In *Proceedings of the 1996 IEEE International Conference on Robotics and Automation*, pages 669–674.

[Rich and Knight, 1991] Rich, E. and Knight, K., editors (1991). *Artificial Intelligence*. McGraw-Hill, New York.

[Rumelhart et al., 1990] Rumelhart, D., Hinton, G., and Williams, R. (1990). Learning internal representations by error propagation. In *Readings in Machine Learning*, pages 115–137. Morgan Kaufmann.

[Seraji et al., 1996] Seraji, H., Lim, D., and Steele, R. (1996). Experiments in contact control. *Journal of Robotic Systems*, 13(2):53–73.

[Shimoga and Goldenberg, 1996a] Shimoga, K. and Goldenberg, A. (1996a). Soft robotic fingertips part i: A comparison of construction material. *International Journal of Robotics Research*, 15(4):320–334.

[Shimoga and Goldenberg, 1996b] Shimoga, K. and Goldenberg, A. (1996b). Soft robotic fingertips part ii: Modeling and impedance regulation. *International Journal of Robotics Research*, 15(4):335–350.

[Siciliano and Villani, 1997] Siciliano, B. and Villani, L. (1997). An output feedback parallel force/position regulator for robot manipulator in contact with a compliant environment. *Systems and Control Letters*, 29:295–300.

[Sinha et al., 1993] Sinha, P., Xu, Y., Bajcsy, R., and Paul, R. (1993). Robotic exploration of surfaces with a compliant wrist sensor. *International Journal of Robotics Research*, 12(2):107–120.

[Srinivasan and Lamotte, 1995] Srinivasan, M. and Lamotte, R. (1995). Tactual discrimination of softness. *Journal of Neurophysiology*, 73(1):88–101.

[Tarokh and Bailey, 1996] Tarokh, M. and Bailey, S. (1996). Force tracking with unknown environment parameters using adaptive fuzzy controllers. In *Proceedings of the 1996 IEEE International Conference on Robotics and Automation*, pages 270–275, Minneapolis, MN.

[Taylor and Koudis, 1988] Taylor, P. and Koudis, S. (1988). The robotic assembly of garments with concealed seams. In *IEEE Conference on Robotics and Automation*, pages 1836–1838.

[Tedford, 1990] Tedford, J. (1990). Developments in robot grippers for soft fruit packing in New Zealand. *Robotica*, 8:279–283.

[Terzopoulos et al., 1987] Terzopoulos, D., Platt, J., Barr, A., and Fleischer, K. (1987). Elastically deformable models. *Computer Graphics*, 21(4):205–214.

[Thalmann and Thalmann, 1995] Thalmann, N. and Thalmann, D. (1995). Finite elements in task-level animation. *Finite Elements in Analysis and Design*, 19:115–137.

[Tisdall et al., 1994] Tisdall, J., Broome, D., and Greig, A. (1994). Neural network modelling of a compliant device to enhance and simplify compliant force control. *Robotics and Computer-Integrated Manufacturing*, 11(4):293–301.

[Tremblay and Cutkosky, 1993] Tremblay, M. and Cutkosky, M. (1993). Estimating friction using incipient slip sensing during a manipulation task. In *Proceedings of the 1993 IEEE International Conference on Robotics and Automation*, pages 363–368, Altanta, GA.

[Tsai, 1987] Tsai, R. (1987). A versatile camera calibration technique for high-accuracy 3d machine vision metrology using off-the-shelf tv cameras and lenses. *IEEE Journal of Robotics and Automation*, RA-3(4):323–344.

[Turner, 1995] Turner, R. (1995). Interactive sculpting of an elastic surface model using reaction constraints. In *Workshop on Simulation and Interaction in Virtual Environments*.

[Venkataraman et al., 1993] Venkataraman, S., Gulati, S., Barhen, J., and Toomarian, N. (1993). A neural network based identification of environment models for compliant control of space robots. *IEEE Transactions on Robotics and Automation*, 9(5):685–696.

[Willson,] Willson, R. Public domain implementation of Tsai camera calibration. *http://www.cs.cmu.edu/ rgw/TsaiCode.html*.

[Yao and Tomizuka, 1998] Yao, B. and Tomizuka, M. (1998). Adaptive robust motion and force tracking control of robot manipulators in contact with compliant surfaces with unknown stiffness. *Transactions of the ASME*, 120:232–240.

[Yun, 1993] Yun, X. (1993). Object handling using two arms without grasping. *International Journal of Robotics Research*, 12(1):99–106.

[Zheng et al., 1991] Zheng, Y., Pei, R., and Chen, C. (1991). Strategies for automatic assembly of deformable objects. In *International Conference on Robotics and Automation*, pages 2598–2603, Sacramento, CA.

Appendix A

Error Analysis

A.1 Error Analysis of Deformability

Let ψ_N represent the surface particle(s) upon which the squeezing force is applied. Let n_e represent the number of springs incident on particle ψ_N. Let n_i represent the number of springs connected to an inner particle where $n_e \leq n_i \leq n_e + 8$. We apply the squeezing force in a direction perpendicular to the y-z plane [1] for time Δt such that $\bar{f}_N = (F_A, 0, 0)$. Let t=0 represent the initial time at which the force is applied. Let $\bar{p}(\bar{f}, t)$ represent the position of a particle for which a force is applied for time t.
Let the following initial conditions hold for all ψ_j connected to ψ_N:

$$\bar{p}_N(\bar{f}_N, 0) = (x_N, y_N, z_N) \tag{A.1}$$

$$\bar{p}_j(\bar{f}_j, 0) = (x_j, y_j, z_j) \tag{A.2}$$

$$l_x = x_j - x_N \tag{A.3}$$

$$l_y = y_j - y_N \tag{A.4}$$

$$l_z = z_j - z_N \tag{A.5}$$

The original restlength of the spring connecting particle ψ_j and ψ_N is therefore computed by:

$$l_{N,j}(0) = l_{0j} = \sqrt{l_x^2 + l_y^2 + l_z^2} \tag{A.6}$$

After the force $F_A\hat{i}$ is applied, the estimated values[2] for all ψ_j connected to ψ_N are:

$$\bar{p}_N(\bar{f}_N, \Delta t) = (x_N + \Delta x, y_N, z_N) \tag{A.7}$$

[1] normal to the x-plane
[2] based on the assumption that the internal particles do not change position

$$\bar{p}_j(\bar{f}_j, \Delta t) = (x_j, y_j, z_j) \tag{A.8}$$

$$l_x^e(\Delta t) = x_j - (x_N + \Delta x) = l_x - \Delta x \tag{A.9}$$

$$l_y^e(\Delta t) = y_j - y_N = l_y \tag{A.10}$$

$$l_z^e(\Delta t) = z_j - z_N = l_z \tag{A.11}$$

$$l_{N,j}^e(\Delta t) = l_{0j}^e(\Delta t) = \sqrt{(l_x - \Delta x)^2 + l_y^2 + l_z^2} \tag{A.12}$$

$$\tag{A.13}$$

where Δx is the change in the i^{th} coordinate position of particle ψ_N at time t=Δt and $l_{N,j}^e(\Delta t)$ is the spring length based on the estimated values. This allows us to calculate the estimated deformability from Eq. 3.23 as:

$$D_e = \frac{F_A}{\sum_{j=1}^{n_e} \frac{l_{0j} - l_{0j}^e(\Delta t)}{l_{0j}^e(\Delta t)}(x_j - x_N - \Delta x)} \tag{A.14}$$

After $F_A\hat{i}$ is applied, the real values for all ψ_j connected to ψ_N are:

$$\bar{p}_N(\bar{f}_N, \Delta t) = (x_N(\Delta t), y_N(\Delta t), z_N(\Delta t)) = (x_N + \Delta x, y_N, z_N) \tag{A.15}$$

$$\bar{p}_j(\bar{f}_j, \Delta t) = (x_j + \Delta x_j, y_j + \Delta y_j, z_j + \Delta z_j)) \tag{A.16}$$

$$l_x(\Delta t) = (x_j + \Delta x_j) - (x_N + \Delta x) \tag{A.17}$$

$$l_y(\Delta t) = (y_j + \Delta y_j) - y_N \tag{A.18}$$

$$l_z(\Delta t) = (z_j + \Delta z_j) - z_N \tag{A.19}$$

$$l_{N,j}(\Delta t) = l_{0j}(\Delta t) = \sqrt{l_x^2(\Delta t) + l_y^2(\Delta t) + l_z^2(\Delta t)} \tag{A.20}$$

The real deformability is therefore computed by:

$$D_r = \frac{F_A}{\sum_{j=1}^{n_e} \frac{l_{0j} - l_{0j}(\Delta t)}{l_{0j}(\Delta t)}(x_j + \Delta x_j - x_N - \Delta x)} \tag{A.21}$$

Given D_r and D_e, the error is $\frac{D_r - D_e}{D_r}$

$$Error = \frac{\frac{F_A}{\sum_{j=1}^{n_e} \frac{l_{0j} - l_{0j}(\Delta t)}{l_{0j}(\Delta t)}(x_j + \Delta x_j - x_N - \Delta x)} - \frac{F_A}{\sum_{j=1}^{n_e} \frac{l_{0j} - l_{0j}^e(\Delta t)}{l_{0j}^e(\Delta t)}(x_j - x_N - \Delta x)}}{\frac{F_A}{\sum_{j=1}^{n_e} \frac{l_{0j} - l_{0j}(\Delta t)}{l_{0j}(\Delta t)}}(x_j + \Delta x_j - x_N - \Delta x)} \tag{A.22}$$

This equation simplifies to:

$$Error = 1 - \frac{\sum_{j=1}^{n_e} \frac{l_{0j} - l_{0j}(\Delta t)}{l_{0j}(\Delta t)}(x_j + \Delta x_j - x_N - \Delta x)}{\sum_{j=1}^{n_e} \frac{l_{0j} - l_{0j}^e(\Delta t)}{l_{0j}^e(\Delta t)}(x_j - x_N - \Delta x)} \tag{A.23}$$

Based on Eq. (A.23), a minimum value for

$$\frac{\sum_{j=1}^{n_e} \frac{l_{0j}-l_{0j}(\Delta t)}{l_{0j}(\Delta t)}(x_j + \Delta x_j - x_N - \Delta x)}{\sum_{j=1}^{n_e} \frac{l_{0j}-l_{0j}^e(\Delta t)}{l_{0j}^e(\Delta t)}(x_j - x_N - \Delta x)} \tag{A.24}$$

will give an upper bound on the Error. Substituting A.6 and A.12 into Eq. A.24 gives us:

$$\frac{\sum_{j=1}^{n_e} \frac{\sqrt{l_x^2+l_y^2+l_z^2}-\sqrt{l_x^2(\Delta t)+l_y^2(\Delta t)+l_z^2(\Delta t)}}{\sqrt{l_x^2(\Delta t)+l_y^2(\Delta t)+l_z^2(\Delta t)}}(x_j + \Delta x_j - x_N - \Delta x)}{\sum_{j=1}^{n_e} \frac{\sqrt{l_x^2+l_y^2+l_z^2}-\sqrt{(l_x^e(\Delta t))^2+(l_y^e(\Delta t))^2+(l_z^e(\Delta t))^2}}{\sqrt{(l_x^e(\Delta t))^2+(l_y^e(\Delta t))^2+(l_z^e(\Delta t))^2}}(x_j - x_N - \Delta x)} \tag{A.25}$$

Substituting Eq. A.3-A.5,A.9-A.11 into Eq. A.25 gives us:

$$\frac{\sum_{j=1}^{n_e} \frac{\sqrt{(x_j-x_N)^2+(y_j-y_N)^2+(z_j-z_N)^2}-\sqrt{(x_j+\Delta x_j-x_N-\Delta x)^2+(y_j+\Delta y_j-y_N)^2+(z_j+\Delta z_j-z_N)^2}}{\sqrt{(x_j+\Delta x_j-x_N-\Delta x)^2+(y_j+\Delta y_j-y_N)^2+(z_j+\Delta z_j-z_N)^2}}(x_j + \Delta x_j - x_N - \Delta x)}{\sum_{j=1}^{n_e} \frac{\sqrt{(x_j-x_N)^2+(y_j-y_N)^2+(z_j-z_N)^2}-\sqrt{(x_j-x_N-\Delta x)^2+(y_j-y_N)^2+(z_j-z_N)^2}}{\sqrt{(x_j-x_N-\Delta x)^2+(y_j-y_N)^2+(z_j-z_N)^2}}(x_j - x_N - \Delta x)} \tag{A.26}$$

Substituting $\Delta y_j = 0, \Delta z_j = 0, y_j - y_N = 0, z_j - z_N = 0$ into Eq. (A.26), will give us a minimum value for Eq. (A.24) based on the following analysis:

$$\frac{\sum_{j=1}^{n_e} \frac{(x_j-x_N)-(x_j+\Delta x_j-x_N-\Delta x)}{(x_j+\Delta x_j-x_N-\Delta x)}(x_j + \Delta x_j - x_N - \Delta x)}{\sum_{j=1}^{n_e} \frac{(x_j-x_N)-(x_j-x_N-\Delta x)}{(x_j-x_N-\Delta x)}(x_j - x_N - \Delta x)} \overset{?}{\leq} \frac{\sum_{j=1}^{n_e} \frac{l_{0j}-l_{0j}(\Delta t)}{l_{0j}(\Delta t)}(x_j + \Delta x_j - x_N - \Delta x)}{\sum_{j=1}^{n_e} \frac{l_{0j}-l_{0j}^e(\Delta t)}{l_{0j}^e(\Delta t)}(x_j - x_N - \Delta x)} \tag{A.27}$$

Let us focus on one spring interconnection:

$$\frac{\frac{(x_j-x_N)-(x_j+\Delta x_j-x_N-\Delta x)}{(x_j+\Delta x_j-x_N-\Delta x)}(x_j + \Delta x_j - x_N - \Delta x)}{\frac{(x_j-x_N)-(x_j-x_N-\Delta x)}{(x_j-x_N-\Delta x)}(x_j - x_N - \Delta x)} \overset{?}{\leq} \frac{\frac{l_{0j}-l_{0j}(\Delta t)}{l_{0j}(\Delta t)}(x_j + \Delta x_j - x_N - \Delta x)}{\frac{l_{0j}-l_{0j}^e(\Delta t)}{l_{0j}^e(\Delta t)}(x_j - x_N - \Delta x)} \tag{A.28}$$

$$\frac{\frac{x_j-x_N-x_j-\Delta x_j+x_N+\Delta x}{(x_j+\Delta x_j-x_N-\Delta x)}}{\frac{x_j-x_N-x_j+x_N+\Delta x}{(x_j-x_N-\Delta x)}} \overset{?}{\leq} \frac{\frac{l_{0j}-l_{0j}(\Delta t)}{l_{0j}(\Delta t)}}{\frac{l_{0j}-l_{0j}^e(\Delta t)}{l_{0j}^e(\Delta t)}} \tag{A.29}$$

$$\frac{\frac{\Delta x-\Delta x_j}{(x_j+\Delta x_j-x_N-\Delta x)}}{\frac{\Delta x}{(x_j-x_N-\Delta x)}} \overset{?}{\leq} \frac{(l_{0j} - l_{0j}(\Delta t))l_{0j}^e(\Delta t)}{l_{0j}(l_{0j}(\Delta t) - l_{0j}^e(\Delta t))} \tag{A.30}$$

$$\frac{(\Delta x - \Delta x_j)(x_j - x_N - \Delta x)}{(x_j + \Delta x_j - x_N - \Delta x)(\Delta x)} \overset{?}{\leq} \frac{(l_{0j} - l_{0j}(\Delta t))l_{0j}^e(\Delta t)}{l_{0j}(l_{0j}(\Delta t) - l_{0j}^e(\Delta t))} \tag{A.31}$$

$$\begin{aligned}&(\Delta x - \Delta x_j)(x_j - x_N - \Delta x)(l_{0j}l_{0j}(\Delta t) - l_{0j}(\Delta t)l_{0j}^e(\Delta t))\\ &\overset{?}{\leq} (x_j + \Delta x_j - x_N - \Delta x)\Delta x(l_{0j}^e(\Delta t)l_{0j} - l_{0j}(\Delta t)l_{0j}^e(\Delta t))\end{aligned} \tag{A.32}$$

$$(\Delta x x_j - \Delta x x_N - \Delta x^2 - \Delta x_j x_j + \Delta x_j x_N + \Delta x_j \Delta x)(l_{0j} l_{0j}(\Delta t) - l_{0j}(\Delta t) l_{0j}^e(\Delta t))$$
$$\stackrel{?}{\leq} (\Delta x x_j - \Delta x x_N - \Delta x^2 + \Delta x_j \Delta x)(l_{0j}^e(\Delta t) l_{0j} - l_{0j}(\Delta t) l_{0j}^e(\Delta t)) \tag{A.33}$$

From Eq. A.3, we get $l_x = x_j - x_N$. By adding $(\Delta x x_j - \Delta x x_N - \Delta x^2 + \Delta x_j \Delta x) l_{0j}(\Delta t) l_{0j}^e(\Delta t)$ to both sides, the above equation then becomes:

$$(\Delta x l_x - \Delta x_j l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j} l_{0j}(\Delta t) - \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t)$$
$$\stackrel{?}{\leq} (\Delta x l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j}^e(\Delta t) l_{0j} \tag{A.34}$$

$$(\Delta x l_x - \Delta x_j l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j} l_{0j}(\Delta t)$$
$$\stackrel{?}{\leq} (\Delta x l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j}^e(\Delta t) l_{0j} + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \tag{A.35}$$

Since $l_{0j}(\Delta t) \leq l_{0j}$ and $l_{0j}^e(\Delta t) \leq l_{0j}$, we get

$$\begin{aligned}(\Delta x l_x - \Delta x_j l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j} l_{0j}(\Delta t) &\leq (\Delta x l_x - \Delta x_j l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j} l_{0j} \\ &\stackrel{?}{\leq} (\Delta x l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j}^e(\Delta t) l_{0j}^e(\Delta t) + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \\ &\leq (\Delta x l_x + \Delta x(\Delta x_j - \Delta x)) l_{0j}^e(\Delta t) l_{0j} + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t)\end{aligned} \tag{A.36}$$

Substituting $l_{0j} = \sqrt{l_x^2 + l_y^2 + l_z^2}$ (A.6) and $l_{0j}^e(\Delta t) = \sqrt{(l_x - \Delta x)^2 + l_y^2 + l_z^2}$ (A.12) gives us

$$(\Delta x l_x - \Delta x_j l_x + \Delta x(\Delta x_j - \Delta x))(l_x^2 + l_y^2 + l_z^2)$$
$$\stackrel{?}{\leq} (\Delta x l_x + \Delta x(\Delta x_j - \Delta x))((l_x - \Delta x)^2 + l_y^2 + l_z^2) + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \tag{A.37}$$

By subtracting $(\Delta x l_x + \Delta x(\Delta x_j - \Delta x))(l_x^2 + l_y^2 + l_z^2)$ from both sides, we get

$$\Delta x_j l_x(l_x^2 + l_y^2 + l_z^2) \leq \Delta x_j l_x l_x^2 \stackrel{?}{\leq} (\Delta x l_x + \Delta x(\Delta x_j - \Delta x))(-2 l_x \Delta x + \Delta x^2) + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \tag{A.38}$$

Since $l_x^2 \leq l_x^2 + l_y^2 + l_z^2$, we can reduce the above equation to:

$$-\Delta x_j(l_x) l_x^2 \stackrel{?}{\leq} (\Delta x(l_x) + \Delta x(\Delta x_j - \Delta x))(-2 l_x \Delta x + \Delta x^2) + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \tag{A.39}$$

Adding $\Delta x_j l_x^3$ to both sides gives us

$$0 \stackrel{?}{\leq} \Delta x_j l_x^3 - 2\Delta x^2 l_x^2 + \Delta x^3 l_x - 2 l_x \Delta x^2 \Delta x_j + \Delta x^3 \Delta x_j + 2\Delta x^3 l_x - \Delta x^4 + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \tag{A.40}$$

Let us say $\Delta x \leq l_x$. We can therefore substitute $\Delta x = l_x$ into A.40, which then becomes

$$0 \stackrel{?}{\leq} \Delta x_j l_x^3 - 2l_x^2 l_x^2 + l_x^3 l_x - 2l_x l_x^2 \Delta x_j + l_x^3 \Delta x_j + 2l_x^3 l_x - l_x^4 + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t)$$
$$0 \stackrel{?}{\leq} 0 + \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \tag{A.41}$$

Since

$$0 \leq \Delta x_j l_x l_{0j}(\Delta t) l_{0j}^e(\Delta t) \tag{A.42}$$

we can substitute $\Delta y_j = 0, \Delta z_j = 0, y_j - y_N = 0, z_j - z_N = 0$ into Eq. (A.23) to give us an upper bound on the error (as long as we guarantee $\Delta x \leq l_x$). This gives us:

$$Error = 1 - \frac{\sum_{j=1}^{n_e}(x_j - x_N) - (x_j + \Delta x_j - x_N - \Delta x)}{\sum_{j=1}^{n_e}(x_j - x_N) - (x_j - x_N - \Delta x)} \tag{A.43}$$

$$Error = 1 - \frac{\sum_{j=1}^{n_e} \Delta x - \Delta x_j}{\sum_{j=1}^{n_e} \Delta x} \tag{A.44}$$

An externally applied force $\bar{F}_N = (F_A, 0, 0)$ gives rise to a particle displacement of Δx in the i^{th} direction. Based on Eq. (3.23), the accumulation of spring forces incident on particle ψ_N equals $F_A\hat{i}$. Since an applied force $\bar{F} = (F_A, 0, 0)$ gives rise to a displacement of Δx, the accumulation of spring forces equaling $F_A\hat{i}$ gives rise to an upper bound on the accumulation of inner particle x-displacement values.

$$\sum_{j=1}^{n_e} \Delta x_j \leq \Delta x \tag{A.45}$$

From Eq. A.44, this gives us an upper error bound on deformability (Fig A.1):

$$Error = 1 - \frac{n_e \Delta x - \Delta x}{n_e \Delta x} \tag{A.46}$$

$$Error = 1 - \frac{n_e - 1}{n_e} = \frac{1}{n_e} \tag{A.47}$$

Figure A.1 tells us that if we model our deformable object with only 1 spring connected to an external particle and we assume the internal particles do not shift, then the upper bound error derived from our deformability calculations is 100%. Based on our discretization, there are 17 springs incident on an external particle. Therefore the error derived from calculating deformability for our system is upper bounded by 6%.



Figure A.1: Deformability Upper Bound Error

Appendix B

Spring Analysis

B.1 Time of Maximum Spring Stretch

$$\frac{dr_d(t)}{dt} = \frac{-\lambda}{2m} e^{\frac{-\lambda t}{2m}} [Acos(\mu t) + Bsin(\mu t)] + e^{\frac{-\lambda t}{2m}} [-\mu Asin(\mu t) + \mu Bcos(\mu t)] \quad \text{(B.1)}$$

$$0 = e^{\frac{-\lambda t}{2m}} [\frac{-\lambda}{2m} Acos(\mu t) - \frac{\lambda}{2m} Bsin(\mu t) - \mu Asin(\mu t) + \mu Bcos(\mu t)] \quad \text{(B.2)}$$

$$0 = (-\frac{\lambda}{2m} A + \mu B) cos(\mu t) + (-\frac{\lambda}{2m} B - \mu A) sin(\ mut) \quad \text{(B.3)}$$

$$(\frac{\lambda}{2m} B + \mu A) sin(\mu t) = (\mu B - \frac{\lambda}{2m} A) cos(\mu t) \quad \frac{sin(\mu t)}{\cos(\mu t)} = \frac{\mu B - \frac{\lambda}{2m} A}{\frac{\lambda}{2m} B + \mu A} \quad \text{(B.4)}$$

$$tan(\mu t) = \frac{2m\mu B - \lambda A}{\lambda B + 2m\mu A} \quad \text{(B.5)}$$

$$t = \frac{1}{\mu} arctan(\frac{2m\mu B - \lambda A}{\lambda B + 2m\mu A}) \quad \text{(B.6)}$$

We assume that the initial velocity $\dot{\psi}(t) = 0$ since the object is initially at rest when first presented to the robotic system. Thus,

$$t = \frac{1}{\mu} arctan(\frac{2m\mu B - \lambda A}{\lambda B + 2m\mu A}) = \frac{1}{\mu} arctan(\frac{2m \frac{\sqrt{4Dm - \lambda^2}}{2m} \frac{\lambda \psi(0)}{\sqrt{4Dm - \lambda^2}} - \lambda \psi(0)}{\lambda B + 2m\mu A}) \quad \text{(B.7)}$$

$$t = \frac{1}{\mu} arctan(\frac{\lambda \psi(0) - \lambda \psi(0)}{\lambda B + 2m\mu A}) = \frac{1}{\mu} arctan(0) \quad \text{(B.8)}$$

$$t = \frac{1}{\mu} arctan(0) \quad \text{(B.9)}$$

B.2 Maximum Spring Force with Zero Damping

If damping = 0, then we have a cyclic relation and

$$r_d^i(\frac{\pi}{\mu}) = -r_d^i(0) \tag{B.10}$$

$$r_d^i(0) = \frac{m_i g}{D_{Ni}} \tag{B.11}$$

$$F_{max} = mg + \sum_{i=1}^{S_N} D_{Ni} * [r_d^i(0) - r_d^i(\frac{\pi}{\mu})] = mg + \sum D_{Ni} * 2r_d^i(0) \tag{B.12}$$

$$F_{max} = mg + \sum D_{Ni}(2 * \frac{m_i g}{D_{Ni}}) \tag{B.13}$$

$$F_{max} = mg + \sum_{i}^{S_N} 2m_i g \tag{B.14}$$

Thus, if damping equals zero, the maximum force is not dependent on the deformation parameters.

B.3 Determining Deformability and Damping for all attached Springs

Let l_{Nm} represent the spring connecting particle ψ_N to particle ψ_m where $1 \leq m \leq S_N$. Let $\Delta\bar{p}_{Nm}$ represent the particle displacement vector of spring l_{Nm}, $\frac{\partial \Delta\bar{p}_{Nm}}{\partial t}$ represent the particle displacement velocity vector and let $\hat{l}_{Nm}$ represent the spring's unit vector. $\bar{F} \cdot \hat{l}_{Nm}$ therefore represents the magnitude of the force applied in the direction of the spring 's unit vector.

$$\bar{F} \cdot \hat{l}_{N1} = D_{N1}\bar{d}_{N1} \cdot \hat{l}_{N1} + \cdots + D_{NS_N}\bar{d}_{NS_N} \cdot \hat{l}_{N1} \tag{B.15}$$

$$\bar{F} \cdot \hat{l}_{N2} = D_{N1}\bar{d}_{N1} \cdot \hat{l}_{N2} + \cdots + D_{NS_N}\bar{d}_{NS_N} \cdot \hat{l}_{N2} \tag{B.16}$$

$$\bar{F} \cdot \hat{l}_{NS_N} = D_{N1}\bar{d}_{N1} \cdot \hat{l}_{NS_N} + \cdots + D_{NS_N}\bar{d}_{NS_N} \cdot \hat{l}_{NS_N} \tag{B.17}$$

$$\begin{bmatrix} \bar{d}_{N1} \cdot \hat{l}_{N1} & \bar{d}_{N2} \cdot \hat{l}_{N1} & \cdots & \bar{d}_{NS_N} \cdot \hat{l}_{N1} \\ \bar{d}_{N1} \cdot \hat{l}_{N2} & \bar{d}_{N2} \cdot \hat{l}_{N2} & \cdots & \bar{d}_{NS_N} \cdot \hat{l}_{N2} \\ \bar{d}_{N1} \cdot \hat{l}_{NS_N} & \bar{d}_{N2} \cdot \hat{l}_{NS_N} & \cdots & \bar{d}_{NS_N} \cdot \hat{l}_{NS_N} \end{bmatrix} \begin{bmatrix} D_{N1} \\ D_{N2} \\ D_{NS_N} \end{bmatrix} = \begin{bmatrix} \bar{F} \cdot \hat{l}_{N1} \\ \bar{F} \cdot \hat{l}_{N2} \\ \bar{F} \cdot \hat{l}_{NS_N} \end{bmatrix}$$

$$[d][D] = [F]$$

Thus, the matrix equation needed to solve for the deformability coefficients of all connected springs.

$$[D] = [d]^{-1}[F]$$

In the same way, we can calculate the damping coefficients.

$$\bar{F} \cdot \hat{l}_{NS_N} = [D_{N1}\bar{d}_{N1} + \lambda_{N1}\dot{\bar{d}}_{N1}] \cdot \hat{l}_{NS_N} + \cdots + [D_{NS_N}\bar{d}_{NS_N} + \lambda_{NS_N}\dot{\bar{d}}_{NS_N}] \cdot \hat{l}_{NS_N} \tag{B.18}$$

$$[d]\,[D] + \begin{bmatrix} \dot{\bar{d}}_{N1} \cdot \hat{l}_{N1} & \cdots & \dot{\bar{d}}_{NS_N} \cdot \hat{l}_{N1} \\ \dot{\bar{d}}_{N1} \cdot \hat{l}_{N2} & \cdots & \dot{\bar{d}}_{NS_N} \cdot \hat{l}_{N2} \\ \dot{\bar{d}}_{N1} \cdot \hat{l}_{NS_N} & \cdots & \dot{\bar{d}}_{NS_N} \cdot \hat{l}_{NS_N} \end{bmatrix} \begin{bmatrix} \lambda_{N1} \\ \lambda_{N2} \\ \lambda_{NS_N} \end{bmatrix} = [F]$$

$$[d][D] + [\dot{d}][\lambda] = [F]$$

Thus, the matrix equation needed to solve for the damping coefficients of all connected springs.

$$[\lambda] = [\dot{d}]^{-1}([F] - [d][D])$$

This calculated deformability and damping coefficients allow us to derive an expression for the maximum force experienced by the system as:

$$F_{max} = mg + max[F_t] - min[F_t] \tag{B.19}$$

where

$$F_t = \sum_{i=1}^{S_N} D_{Ni} e^{\frac{-\lambda_i t}{2m}} [A_i cos(u_i t) + B_i sin(u_i t)] \tag{B.20}$$

B.4 Calculating Deformability From Multiple Tests

Based on our previous calculations, the calculated deformability coefficient equals:

$$\bar{F} \cdot \hat{l}_{N1} = D_c \sum_{i}^{S_N} \bar{d}_{Ni} \cdot \hat{l}_{N1} = D_{N1}\bar{d}_{N1} \cdot \hat{l}_{N1} + \cdots + D_{NS_N}\bar{d}_{NS_N} \cdot \hat{l}_{N1} \tag{B.21}$$

$$D_c = \frac{D_{N1}\bar{d}_{N1} \cdot \hat{l}_{N1} + \cdots + D_{NS_N}\bar{d}_{NS_N} \cdot \hat{l}_{N1}}{\bar{d}_{N1} \cdot \hat{l}_{N1} + \cdots + \bar{d}_{NS_N} \cdot \hat{l}_{N1}} \tag{B.22}$$

$$D_c = \frac{D_{N1} + \cdots + \frac{\bar{d}_{NS_N}}{\bar{d}_{N1}} D_{NS_N}}{1 + \cdots + \frac{\bar{d}_{NS_N}}{\bar{d}_{N1}}} \tag{B.23}$$

$$D_c = \frac{D_{N1} + \cdots + A_{S_N} D_{NS_N}}{1 + \cdots + A_{S_N}} \tag{B.24}$$

If the force is applied in the direction of the spring's unit vector $\hat{l}_{N1}$ then if D_{N1} is the maximum deformability of all connected springs, then $D_{AVG} < D_c < D_{N1}$ and D_c, the calculated deformability in Equation B.24, is maximum for all force/displacement tests. If D_{N1} is the minimum deformability of all connected springs, then $D_{AVG} > D_c > D_{N1}$ and D_c is minimum for all force/displacement tests. And if D_{N1} is the average deformability for all connected springs, then $D_{AVG} = D_c = D_{N1}$ and D_c will equate to the average deformability. In addition, A_i is maximum when the angle between spring's $\hat{l}_{Ni}$ and the spring's unit vector $\hat{l}_{N1}$ is smallest. Based on these observations, we shall subdivide the connected spring space into 4 quadrants and perform a force/displacement test along the spring direction which bisects the quadrant.

B.5 Calculating Damping from Multiple Tests

Based on our previous calculations, the calculated damping coefficient equals:

$$\bar{F} \cdot \hat{l}_{N1} = D_c \sum_i^{S_N} \bar{d}_{Ni} \cdot \hat{l}_{N1} + \lambda_c \sum_i^{S_N} \dot{\bar{d}}_{Ni} \cdot \hat{l}_{N1} \tag{B.25}$$

$$\bar{F} \cdot \hat{l}_{N1} = D_c \sum_i^{S_N} \bar{d}_{Ni} \cdot \hat{l}_{N1} + \lambda_{N1} \dot{\bar{d}}_{N1} \cdot \hat{l}_{N1} + \cdots + \lambda_{NS_N} \dot{\bar{d}}_{NS_N} \cdot \hat{l}_{N1} \tag{B.26}$$

$$\lambda_c = \frac{D_c \sum_i^{S_N} \bar{d}_{Ni} \cdot \hat{l}_{N1} + \lambda_{N1} \dot{\bar{d}}_{N1} \cdot \hat{l}_{N1} + \cdots + \lambda_{NS_N} \dot{\bar{d}}_{NS_N} \cdot \hat{l}_{N1}}{\dot{\bar{d}}_{N1} \cdot \hat{l}_{N1} + \cdots + \dot{\bar{d}}_{NS_N} \cdot \hat{l}_{N1}} \tag{B.27}$$

$$\lambda_c = \frac{\frac{D_c \sum_i^{S_N} \bar{d}_{Ni} \cdot \hat{l}_{N1}}{\dot{\bar{d}}_{N1}} + \lambda_{N1} + \cdots + \frac{\dot{\bar{d}}_{NS_N}}{\dot{\bar{d}}_{N1}} \lambda_{NS_N}}{1 + \cdots + \frac{\dot{\bar{d}}_{NS_N}}{dot \bar{d}_{N1}}} \tag{B.28}$$

$$\lambda_c = \frac{\frac{D_c \sum_i^{S_N} \bar{d}_{Ni} \cdot \hat{l}_{N1}}{\dot{\bar{d}}_{N1}} + \lambda_{N1} + \cdots + B_{S_N} \lambda_{NS_N}}{1 + \cdots + B_{S_N}} \tag{B.29}$$

B.6 Determination of Spring Force Error Value

From Equation 4.7, we know that:

$$F_{max} = D * [r_d(0) - r_d(\frac{\pi}{\mu})] \tag{B.30}$$

$$r_d(0) = A = \frac{mg}{D} \tag{B.31}$$

$$r_d(\frac{\pi}{\mu}) = -Aexp(\frac{-\lambda * \frac{\pi}{\mu}}{2m}) = \frac{mg}{D} exp(\frac{-\lambda * \frac{\pi}{\mu}}{2m}) \tag{B.32}$$

Thus, for all connected springs, the maximum force is:

$$\sum_{i=1}^{S_N} D_i \frac{m_i g}{D_i} (1 + exp(\frac{-\lambda_i * \frac{\pi}{\mu_i}}{2m_i}) = g \sum m_i + g \sum m_i exp(\frac{-\lambda_i * \frac{\pi}{\mu_i}}{2m_i}) \tag{B.33}$$

Using the average deformability, average damping, and average mass values we get:

$$S_N\frac{\sum D}{S_N}\frac{g\sum m}{S_N\frac{\sum D}{S_N}}(1+exp(\frac{-\pi\sum\lambda}{2S_N\mu\frac{\sum m}{S_N}}))=g(\sum m)(1+exp(\frac{-\pi\sum\lambda}{2\mu\sum m})) \tag{B.34}$$

The maximum spring force Equation 5.5 thus gives us:

$$g\sum m_i+g\sum m_i exp(\frac{-\lambda_i*\frac{\pi}{\mu_i}}{2m_i})<g(\sum m)(1+exp(\frac{-\pi\sum\lambda}{2\mu\sum m}))+ERR \tag{B.35}$$

$$(\sum m_i)exp(\frac{-\lambda_i*\frac{\pi}{\mu_i}}{2m_i})<(\sum m)exp(\frac{-\pi\sum\lambda}{2\mu\sum m})+\frac{ERR}{g} \tag{B.36}$$

The worse case ERR occurs when:

$$\lambda_j<\frac{\sum_i^{S_N}\lambda_i}{S_N} \tag{B.37}$$

$$D_j>\frac{\sum_i^{S_N}D_i}{S_N} \tag{B.38}$$

for S_N-1 springs.

Thus, for each spring force:

$$m_j exp(\frac{-\lambda_j*\frac{\pi}{\mu_j}}{2m_j})<\frac{\sum m}{S_N}exp(\frac{-\pi\sum\lambda}{2\mu\sum m})+\frac{ERR_j}{g} \tag{B.39}$$

$$gm_j exp(\frac{-\lambda_j*\frac{\pi}{\mu_j}}{2m_j})-\frac{g\sum m}{S_N}exp(\frac{-\pi\sum\lambda}{2\mu\sum m})<ERR_j \tag{B.40}$$

For the underdamped situation, we have $\xi<1$. Thus

$$\xi<1 \tag{B.41}$$

$$\frac{\frac{\sum\lambda}{S_N}}{2\sqrt{\frac{\sum D}{S_N}\frac{\sum m}{S_N}}}<1 \tag{B.42}$$

$$\frac{\sum\lambda}{2\sqrt{\sum D\sum m}}<1 \tag{B.43}$$

$$\frac{\sum\lambda}{2\sqrt{\sum D\sum m}}*\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}<\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m} \tag{B.44}$$

$$\frac{\pi\sum\lambda}{2\mu\sum m}<\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m} \tag{B.45}$$

$$-\frac{\pi\sum\lambda}{2\mu\sum m}>-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m} \tag{B.46}$$

$$exp(-\frac{\pi\sum\lambda}{2\mu\sum m}) > exp(-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}) \tag{B.47}$$

$$-exp(-\frac{\pi\sum\lambda}{2\mu\sum m}) < -exp(-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}) \tag{B.48}$$

$$-\frac{g\sum m}{S_N}exp(-\frac{\pi\sum\lambda}{2\mu\sum m}) < -\frac{g\sum m}{S_N}exp(-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}) \tag{B.49}$$

$$gm_j exp(\frac{-\lambda_j * \frac{\pi}{\mu_j}}{2m_j}) - \frac{g\sum m}{S_N}exp(-\frac{\pi\sum\lambda}{2\mu\sum m})gm_j exp(\frac{-\lambda_j * \frac{\pi}{\mu_j}}{2m_j}) - \frac{g\sum m}{S_N}exp(-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}) \tag{B.50}$$

Thus:

$$ERR_j = gm_j exp(\frac{-\lambda_j * \frac{\pi}{\mu_j}}{2m_j}) - \frac{g\sum m}{S_N}exp(-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}) \tag{B.51}$$

The worse case error occurs when:

$$exp(\frac{-\lambda_j * \frac{\pi}{\mu_j}}{2m_j}) = 1 \tag{B.52}$$

Thus:

$$ERR_j = gm_j - \frac{g\sum m}{S_N}exp(-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}) \tag{B.53}$$

And the overall error is:

$$ERR = (g\sum m) - (S_N - 1)\frac{g\sum m}{S_N}exp(-\frac{\pi\sqrt{\sum D\sum m}}{\mu\sum m}) \tag{B.54}$$

Appendix C

Grasp Stability

C.1 Momentum Vector Components

For particle ψ_N, we get

$$\begin{aligned}
\bar{p}_N \times \bar{f} &= (y_N f_z - z_N f_y)\hat{\imath} + (z_N f_x - x_N f_z)\hat{\jmath} + (x_N f_y - y_N f_x)\hat{k} && \text{(C.1)}\\
&= y_N f_z \hat{\imath} + (z_N f_x - x_N f_z)\hat{\jmath} - y_N f_x \hat{k} && \text{(C.2)}\\
&= y_N \mu F_A \hat{\imath} + (z_N F_A - x_N \mu F_A)\hat{\jmath} - y_N F_A \hat{k} && \text{(C.3)}\\
&= y_N \frac{\mu M g}{2}\hat{\imath} + (z_N \frac{Mg}{2} - x_N \frac{\mu M g}{2})\hat{\jmath} - y_N \frac{Mg}{2}\hat{k} && \text{(C.4)}
\end{aligned}$$

For particle ψ_K, we get

$$\begin{aligned}
\bar{p}_K \times \bar{f} &= (y_K f_z - z_K f_y)\hat{\imath} + (z_K f_x - x_K f_z)\hat{\jmath} + (x_K f_y - y_K f_x)\hat{k} && \text{(C.5)}\\
&= y_K f_z \hat{\imath} + (z_K f_x - x_K f_z)\hat{\jmath} - y_K f_x \hat{k} && \text{(C.6)}\\
&= y_K \mu F_A \hat{\imath} + (-z_K F_A - x_K \mu F_A)\hat{\jmath} + y_K F_A \hat{k} && \text{(C.7)}\\
&= y_K \frac{\mu M g}{2}\hat{\imath} + (-z_K \frac{Mg}{2} - x_K \frac{\mu M g}{2})\hat{\jmath} + y_K \frac{Mg}{2}\hat{k} && \text{(C.8)}
\end{aligned}$$

For all other particles, we get

$$\begin{aligned}
\forall \psi_n : \bar{p}_n \times \bar{f} &= (y_n f_z - z_n f_y)\hat{\imath} + (z_n f_x - x_n f_z)\hat{\jmath} + (x_n f_y - y_n f_x)\hat{k} && \text{(C.9)}\\
&= y_n f_z \hat{\imath} - x_n f_z \hat{\jmath} && \text{(C.10)}\\
&= -y_n m_n g \hat{\imath} + x_n m_n g \hat{\jmath} && \text{(C.11)}
\end{aligned}$$

Summing all the components for each particle in each vector direction gives us:

$$y_K \frac{\mu M g}{2} + y_N \frac{\mu M g}{2} - \sum_{i \notin N,K}^{N} y_n m_n g = 0 \qquad \text{(C.12)}$$

$$(z_N \frac{Mg}{2} - x_N \frac{\mu Mg}{2}) - (z_K \frac{Mg}{2} + x_K \frac{\mu Mg}{2}) + \sum_{i \notin N,K}^{N} x_n m_n g = 0 \tag{C.13}$$

$$-y_N \frac{Mg}{2} + y_K \frac{Mg}{2} = 0 \tag{C.14}$$

Placing the manipulator at these vector positions will satisfy the momentum force equation required for achieving grasp stability.

Appendix D

Tsai's Camera Model

D.1 Camera Calibration using Tsai's Camera Model

We define the following variables:

- (X_f, Y_f): 2D image coordinate in pixels
- (x_w, y_w, x_w): 3D world coordinate in mm
- (C_x, C_y): image coordinate of origin in image plane
- d_x: distance between adjacent sensor elements in X direction
- d_y: distance between adjacent sensor elements in Y direction
- N_{cx}: number of sensor elements in camera's X direction
- N_{fx}: number of pixels in frame grabber's X direction

Tsai's Model solves for the 11 extrinsic and intrinsic camera parameters required to establish the link between 3D world coordinate position and 2D image coordinate position using the following technique:

1. Compute the distorted image coordinates (X_d, Y_d)
   - Retrieve camera calibration pattern
   - Compute the coordinates (X_f^i, Y_f^i) of each calibration point i.
   - Obtain N_{cx}, N_{fx}, d_x, d_y from camera stats
   - Compute (X_d^i, Y_d^i) with $s_x = 1$ where

$$d'_x = \frac{d_x N_{cx}}{N_{fx}} \tag{D.1}$$

$$X_d^i = s_x^{-1} d'_x (X_f^i - C_x) \tag{D.2}$$

$$Y_d^i = d_y (Y_f^i - C_y) \tag{D.3}$$

2. Compute R, T_x, T_y using the following procedure

- Solve for a system of linear equations $x = A^{-1}b$ where

$$A = \left[\begin{array}{cccccc} Y_d^i x_w^i & Y_d^i y_w^i & Y_d^i & -X_d^i x_w^i & -X_d^i y_w^i & -X_d^i z_w^i \end{array}\right] \tag{D.4}$$

$$x = \left[\begin{array}{ccccccc} \frac{s_x r_1}{T_y} & \frac{s_x r_2}{T_y} & \frac{s_x r_3}{T_y} & \frac{s_x T_x}{T_y} & \frac{r_4}{T_y} & \frac{r_5}{T_y} & \frac{r_6}{T_y} \end{array}\right]^T \tag{D.5}$$

$$b = [X_d^i] \tag{D.6}$$

$$\tag{D.7}$$

- Let $a_1 = x[0], a_2 = x[1], a_3 = x[2], a_4 = x[3], a_5 = x[4], a_6 = x[5], a_7 = x[6]$
- Compute $\parallel T_y \parallel$:

$$\parallel T_y \parallel = \frac{1}{\sqrt{a_5^2 + a_6^2 + a_7^2}} \tag{D.8}$$

- Compute the sign of T_y :
  - Pick a calibration point (x_w^i, y_w^i, z_w^i) and it's corresponding image coordinate (X_f^i, Y_f^i)
  - Let the sign of $T_y = +1$
  - Compute the following:

$$r_1 = a_1 T_y \tag{D.9}$$

$$r_2 = a_2 T_y \tag{D.10}$$

$$r_3 = a_3 T_y \tag{D.11}$$

$$T_x = a_4 T_y \tag{D.12}$$

$$r_4 = a_5 T_y \tag{D.13}$$

$$r_5 = a_6 T_y \tag{D.14}$$

$$r_6 = a_7 T_y \tag{D.15}$$

$$x = r_1 x_w + r_2 y_w + r_3 z_w + T_x \tag{D.16}$$

$$y = r_4 x_w + r_5 y_w + r_6 z_w + T_y \tag{D.17}$$

  - If sign(x) = sign(X_f) and sign(y) = sign(Y_f) then sign(T_y)=+1 else sign(T_y)=-1
- Compute the real value of s_x:

$$s_x = (a_1^2 + a_2^2 + a_3^2)^{1/2} \parallel T_y \parallel \tag{D.18}$$

- Compute r_i, T_x:

$$r_1 = a_1 \frac{T_y}{s_x} \tag{D.19}$$

$$r_2 = a_2 \frac{T_y}{s_x} \tag{D.20}$$
$$r_3 = a_3 \frac{T_y}{s_x} \tag{D.21}$$
$$T_x = a_4 \frac{T_y}{s_x} \tag{D.22}$$
$$r_4 = a_5 T_y \tag{D.23}$$
$$r_5 = a_6 T_y \tag{D.24}$$
$$r_6 = a_7 T_y \tag{D.25}$$

- The rotation matrix R is:

$$R_x = \begin{bmatrix} r_1 & r_2 & r_3 \end{bmatrix} \tag{D.26}$$
$$R_y = \begin{bmatrix} r_4 & r_5 & r_6 \end{bmatrix} \tag{D.27}$$
$$R_z = R_x \times R_y \tag{D.28}$$

3. Compute f,κ_1, and T_z using the following procedure

   - Compute an approximation of f and T_z with N calibration points

$$\begin{bmatrix} f \\ T_z \end{bmatrix} = \begin{bmatrix} y_i & -d_y Y_i \end{bmatrix}^{-1} [w_i d_y Y_i] \tag{D.29}$$

     where $y_i = r_4 x_w^i + r_5 y_w^i + r_6 z_w^i$ and $w_i = r_7 x_w^i + r_8 y_w^i + r_9 z_w^i$

   - Compute the exact solution for f, T_z, κ_1 using steepest descent (nonlinear optimization scheme) with the initial estimated f, T_z, and $\kappa_1 = 0$.

Once we run through Tsai's Camera Model and extract the 11 parameters required for camera calibration, we can use the following procedure to extract the 3D world Cartesian position x_w, y_w, z_w of a 2D image point X_f, Y_f

1. Convert from (X_f, Y_f) to distorted sensor coordinates (X_d, Y_d):

$$d'_x = \frac{d_x N_{cx}}{N_{fx}} \tag{D.30}$$
$$X_d^i = s_x^{-1} d'_x (X_f^i - C_x) \tag{D.31}$$
$$Y_d^i = d_y (Y_f^i - C_y) \tag{D.32}$$

2. Convert from (X_d, Y_d) to undistorted sensor plane coordinates (X_u, Y_u):

$$r = \sqrt{X_d^2 + Y_d^2} \tag{D.33}$$
$$D_x = X_d(\kappa_1 r^2) \tag{D.34}$$

$$D_y = Y_d(\kappa_1 r^2) \tag{D.35}$$

$$X_u = X_d + D_x \tag{D.36}$$

$$Y_u = Y_d + D_y \tag{D.37}$$

3. Given z_w, calculate x_w, y_w

$$x' = X_u - T_x \tag{D.38}$$

$$y' = Y_u - T_y \tag{D.39}$$

$$x_w = r_1 x' + r_4 y' + r7 z_w \tag{D.40}$$

$$y_w = r_2 x' + r_5 y' + r8 z_w \tag{D.41}$$

D.2 Results from Calibration

Based on the given calibration patterns, the following calibration data set was retrieved. And based on the given calibration data set, the following parameter values were retrieved from Tsai's Camera Model.

Camera A - Image 1

3-D World Coordinate Point (in mm)	2D Image Point (in pixels)
(46 , 165.1 , 0)	(187 , 214)
(96.8 , 165.1 , 0)	(228 , 213)
(147.6 , 165.1 , 0)	(269 , 212)
(198.4 , 165.1 , 0)	(310 , 211)
(46 , 114.3 , 0)	(186 , 265)
(96.8 , 114.3 , 0)	(228 , 264)
(147.6 , 114.3 , 0)	(270 , 263)
(198.4 , 114.3 , 0)	(312 , 262)
(46 , 63.5 , 0)	(186 , 317)
(96.8 , 63.5 , 0)	(228 , 316)
(147.6 , 63.5 , 0)	(271 , 315)
(198.4 , 63.5 , 0)	(314 , 314)

Table D.1: Calibration Data Set Retrieved from Camera A/Image 1

Camera A - Image 2

3-D World Coordinate Point (mm)	2D Image Point (in pixels)
(46 , 165.1 , 63.5)	(182 , 188)
(96.8 , 165.1 , 63.5)	(226 , 188)
(147.6 , 165.1 , 63.5)	(272 , 187)
(198.4 , 165.1 , 63.5)	(316 , 186)
(46 , 114.3 , 63.5)	(180 , 243)
(96.8 , 114.3 , 63.5)	(226 , 242)
(147.6 , 114.3 , 63.5)	(272 , 242)
(198.4 , 114.3 , 63.5)	(318 , 241)
(46 , 63.5 , 63.5)	(179 , 300)
(96.8 , 63.5 , 63.5)	(226 , 299)
(147.6 , 63.5 , 63.5)	(273 , 299)
(198.4 , 63.5 , 63.5)	(320 , 297)

Table D.2: Calibration Data Set Retrieved from Camera A/Image 2

Camera B - Image 1

3-D World Coordinate Point (mm)	2D Image Point (in pixels)
(198.4 , 152.4 , 63.5)	(115 , 117)
(147.6 , 152.4 , 63.5)	(185 , 116)
(96.8 , 152.4 , 63.5)	(256 , 115)
(46 , 152.4 , 63.5)	(329 , 115)
(198.4 , 101.6 , 63.5)	(113 , 206)
(147.6 , 101.6 , 63.5)	(184 , 206)
(96.8 , 101.6 , 63.5)	(257 , 206)
(46 , 101.6 , 63.5)	(330 , 205)
(198.4 , 50.8 , 63.5)	(112 , 296)
(147.6 , 50.8 , 63.5)	(184 , 296)
(96.8 , 50.8 , 63.5)	(257 , 297)
(46 , 50.8 , 63.5)	(332 , 296)

Table D.3: Calibration Data Set Retrieved from Camera B/Image 1

Camera B - Image 2	
3-D World Coordinate Point (mm)	2D Image Point (in pixels)
(198.4 , 152.4 , 0)	(131 , 131)
(147.6 , 152.4 , 0)	(193 , 130)
(96.8 , 152.4 , 0)	(255 , 129)
(46 , 152.4 , 0)	(318 , 129)
(198.4 , 101.6 , 0)	(130 , 209)
(147.6 , 101.6 , 0)	(192 , 208)
(96.8 , 101.6 , 0)	(256 , 208)
(46 , 101.6 , 0)	(319 , 208)
(198.4 , 50.8 , 0)	(130 , 287)
(147.6 , 50.8 , 0)	(192 , 287)
(96.8 , 50.8 , 0)	(256 , 287)
(46 , 50.8 , 0)	(319 , 287)

Table D.4: Calibration Data Set Retrieved from Camera B/Image 2

Camera A	
512.0000	N_{cx}
504.0000	N_{fx}
0.0230	d_x
0.0230	d_y
252.0235	C_x
222.3861	C_y
0.4989	s_x
5607.1983	f
0.0000	κ_1
-123.9198	T_x
148.0380	T_y
5872.3416	T_z
2.8320	R_x
-0.0046	R_y
-0.0131	R_z

Table D.5: Calculated Calibration Parameters for Camera A

Camera B	
512.0000	N_{cx}
504.0000	N_{fx}
0.0230	d_x
0.0230	d_y
208.1043	C_x
153.7178	C_y
0.5095	S_x
653.2244	f
0.0000	κ_1
130.7497	T_x
129.3857	T_y
398.2870	T_z
0.0960	R_x
-0.0616	R_y
3.1351	R_z

Table D.6: Calculated Calibration Parameters for Camera B

Appendix E

Inverse Kinematics of Manipulator

E.1 Inverse Kinematics

We wish to determine the joint angles required to position the manipulator end point at a desired x,y,z position with a pitch angle of -90 degrees[1] and a roll of 0 degrees defined with respect to the Cartesian Frame (Figure E.2). The following procedure gives us our solution.

$$pitch = \frac{-\pi}{2} \tag{E.1}$$
$$roll = 0 \tag{E.2}$$
$$\theta_1 = atan(\frac{y}{x}) \tag{E.3}$$
$$rr = \sqrt{x^2 + y^2} \tag{E.4}$$
$$ro = rr - (HANDLENGTH * cos(pitch)) \tag{E.5}$$
$$zo = z - (HANDLENGTH * sin(pitch)) - SHOULDERHEIGHT \tag{E.6}$$
$$b = atan(zo/ro) \tag{E.7}$$
$$a = atan(\sqrt{(4.0 * ARMLENGTH^2)/(ro^2 + zo^2)) - 1.0} \tag{E.8}$$
$$\theta_2 = a + b \tag{E.9}$$
$$\theta_3 = b - a \tag{E.10}$$
$$\theta_4 = pitch - roll - \theta_1 \tag{E.11}$$
$$\theta_5 = pitch + roll + \theta_1 \tag{E.12}$$

where

θ_1 Base Swivel Angle (counter-clockwise)

θ_2 Shoulder Bend Angle (downwards)

[1] gripper pointing downward

θ_3 Elbow Bend Angle (downwards)

θ_4 Right Wrist Angle (downwards)

θ_5 Left Wrist Angle (downwards)

ShoulderLength - 195.0mm

HandLength - 96.5mm

ArmLength - 177.8mm



Figure E.1: Kinematic Model of Manipulator



Figure E.2: Roll with Respect to Cartesian Frame