Haptic Teleoperation of a Mobile Robot: A User Study

Sangyoon Lee[†] Gaurav S. Sukhatme[‡] Gerard Jounghyun Kim[†] Chan-Mo Park[†]

[†]*Virtual Reality Lab.*
Dept. of Computer Science & Engineering
Pohang University of Science and Technology(POSTECH)
Pohang, Kyoungbuk, 790-784 South Korea
sylee|gkim|parkcm@postech.ac.kr

[‡]*Robotic Embedded Systems Lab.*
Dept. of Computer Science
University of Southern California
Los Angeles, CA 90089-0781 USA
gaurav@usc.edu

Abstract

The problem of teleoperating a mobile robot using shared autonomy is addressed: an on-board controller performs close range obstacle avoidance while the operator uses the manipulandum of a haptic probe to designate the desired speed and rate of turn. Sensors on the robot are used to measure obstacle range information. A strategy to convert such range information into forces is described, which are reflected to the operator's hand via the haptic probe. This haptic information provides feedback to the operator in addition to imagery from a front-facing camera mounted on the mobile robot. Extensive experiments with a user population both in virtual and in real environments show that this added haptic feedback significantly improves operator performance, as well as presence, in several ways (reduced collisions, increased minimum distance between the robot and obstacles, etc.) without a significant increase in navigation time.

1 Introduction

Teleoperation is often employed to control mobile robots navigating in unknown and unstructured environments. This is largely because teleoperation benefits from the sophisticated cognitive capabilities of the human operator [1, 2].

However, for navigation in dynamic environments or at high-speeds, it is often desirable to provide a sensor-based collision avoidance scheme on-board the robot to guarantee safe navigation. Without such a collision avoidance scheme, it would be difficult for the (remote) operator to prevent the robot from colliding with obstacles, particularly when trying to accomplish a higher level task at the same time. This is primarily due to (1) limited information from the robot's sensors (such

as images within a restricted viewing angle without depth information) which is insufficient for the users' full perception of the environment in which the robot moves [3], and (2) the delay in the communication channel between the operator and the robot.

The implementation of a collision avoidance scheme on-board the robot can cause conflict between the user's actions and the movement of the robot. For example, consider a situation in which the operator directly controls a mobile robot moving forward in tandem with a joystick. Imagine that the robot is also programmed with a simple collision avoidance algorithm to avoid obstacles. While driving forward, if there is an object at an intermediate distance the robot may try to stop or turn in order to avoid a collision, although the operator is commanding it to move ahead (thinking that the obstacle is still sufficiently far away). In this example, the conflict may be less problematic if the user can at least clearly see the obstacles. If, however, the obstacles were invisible due to a restricted viewing angle, the user might become confused since the robot would not move or act according to the teleoperation commands.

It is hypothesized that the conflict can naturally be partly resolved by exploiting haptic information, that is, by providing the operator with force feedback. The utility of force feedback in a mobile robot teleoperation system for safe navigation while resolving the conflicting goals was measured. The experiments (conducted in both a virtual and real environments) measure the extent to which the haptic information helps an operator to safely navigate a mobile robot. Experimental results clearly show that the added haptic feedback significantly improves operator performance, as well as presence, in several ways (reduced collisions, increased minimum distance between the robot and obstacles, etc.) without a significant increase in navigation time.

This paper is structured as follows. In Section 2, Related work in the area of haptic information for navigation is described. In Sections 3 and 4, it is described how the haptic device in commanding the robot and the force rendering algorithm are used, respectively. Section 5 deals with the specifics of the implementation of the overall navigation system using a mobile robot. In Sections 6 and 7, the experiments in a virtual test environment and a real test environment, respectively, are described and their results are discussed. Finally, this paper is concluded with a summary and future work in Section 8.

2 Related Work

Force feedback has long been used for precise remote control in the teleoperation of manipulators [4, 5]. Recently, with the spread of commercial haptic devices such as the PHANToM [6, 7], the CyberGrasp [8], and various force-feedback joysticks [8, 9], haptic information is being used in

many areas of virtual reality, robotics, training and entertainment. Haptic feedback is usually used as a supplementary cue to help the user understand the virtual environment [10, 11, 12, 13, 14].

In [15], the authors used artificial force fields for "comfortable" navigation in virtual environments. Their work neither provided force feedback to users, nor was it applied to guiding mobile robots. However, they showed that force fields contributed to making navigation comfortable. In [16], the authors proposed an algorithm for haptic navigation within volumetric datasets. Although their aim was to understand the structure of the volumetric datasets (rather than effective navigation), their force-rendering method was similar to ours for rendering the environmental force, in that distance fields were used.

For mobile robot navigation, an event-based direct control with force feedback was proposed in [12, 17]. This approach reflected the difference between the actual velocity and the desired velocity of the mobile robot to the operator as force feedback. It was difficult to perform precise navigation in a cluttered environment with their method, as the turn rate was not considered for force rendering and collision avoidance was automatically performed, which compelled the robot to stop at the distance of 0.5 m (too far) from obstacles.

A full range of advanced interfaces for vehicle control has been investigated in [18]. In particular, the HapticDriver [3, 18] had the same aims as ours. They used the force cube primitives modeled from the range information obtained by infrared sensors attached to the vehicle in order to compute the force fed back to operators. It was informally shown that the HapticDriver had improved obstacle detection and collision avoidance in vehicle teleoperation. However, there was room for improvement in that the force computed from the penetration distance of the end-point of the haptic device into the force cube primitives could give wrong information to operators, because the positions of the primitives (in the local coordinate system of the vehicle) were directly related with that of the end-point of the device (not in the coordinate system) while the position of the end-point was mapped into the speed and turn rate of the vehicle.

A haptic interface using a force feedback joystick for the remote control of mobile robots has been implemented in [19]. They used force sensors attached in the front of the robot in order to determine the magnitude of the force that would be fed back to the operator. In terms of the sense of presence, their approach was interesting in that the degree of how strongly the robot pushed obstacles was directly given to the operator as the form of force. Nevertheless, their approach was somewhat unreasonable to be used for safe navigation since the operator could feel the force only after the robot collided with the obstacles.

A haptic teleoperation system was proposed in [20]. In their approach, when the operator determined the direction and magnitude of the desired "velocity" of the robot with the haptic device, the force, computed from the obstacle map and the displacement of the haptic device, guided the

operator to a safe trajectory. In terms of safe navigation, it was a good approach. In terms of precise control, however, it did not consider ways to turn in place. While many researchers proposed and implemented different approaches for haptic teleoperation of mobile robots, little has shown the effectiveness of the approaches in formal experiments.

3 Car-Driving Metaphor

In this paper, a car-driving metaphor for direct control of a mobile robot is used since the control of ground-vehicle type of mobile robots is considered, which is similar to driving a car. This metaphor is easily understood by users, and can be applied to most ground mobile robots that even support turning in place. A logical point (x, z) (obtained by projecting the 3D haptic probe location to the xz-ground plane) is mapped to the motion parameters of the robot, such as the speed and turn rate (See Figure 1) as follows:

$$\text{speed } v = k_1 \cdot h(-z, z_{buffer}), \quad z_{buffer} > 0 \tag{1}$$

$$\text{turn rate } \omega = \begin{cases} k_2 \cdot h(x, x_{buffer}), & \text{if } z \leq x_{buffer} \\ k_2 \cdot h(-x, x_{buffer}), & \text{if } z > x_{buffer} \end{cases}, \quad x_{buffer} > 0 \tag{2}$$

$$\text{where } h(a, b) = \begin{cases} a - b, & \text{if } a > b \\ a + b, & \text{if } a < -b \\ 0, & \text{if } |a| \leq b \end{cases}$$

Note that the speed $v = 0$ when the logical point is located in the area where $|z| \leq z_{buffer}$, and the turn rate $\omega = 0$ when the logical point resides in the area where $|x| \leq x_{buffer}$. These dead-zones defined by x_{buffer} and z_{buffer} prevent movement of the robot due to small unintended user actions and tremors. Although a linear function is used, other monotonic functions such as quadratic or cubic functions can be used. Note that the speed has positive values where $z < -z_{buffer}$ since a coordinate system is used in which the value of z is negative in the front. The values k_1 and k_2 are proportionality constants.

4 Force Rendering

Force rendering is the process of computing the force that the operator in contact with the haptic device feels. In the direct control approach of this paper, the user's action (i.e. designating the logical position of the haptic probe) is used directly to determine the speed and turn rate of the



Figure 1: Car-driving metaphor: mapping a logical point (x, z) to motion parameters (speed v, turn rate ω). Four different probe positions that translate to different motion commands are shown.



Figure 2: Force feedback from the user's action.

robot, and when the user determines the logical position of the probe, the force that the user feels is computed from the position information of the obstacles surrounding the robot. The range-finding sensors such as laser scanners and sonars attached to the robot obtain the position information of the obstacles represented as a list of distance values between the robot and the obstacles. Figure 2 shows the overall process to feed back the force from the user's action.

Two types of forces are considered: an "environmental" force and a "collision-preventing" force, and whichever is the larger (in the respective dimension) is chosen as the feedback at a given moment during control. That is, let the environmental force and the collision-preventing force be represented by $(F_{e,x}, F_{e,z})$ and $(F_{c,x}, F_{c,z})$ respectively. The final rendered force (F_x, F_z) is given by:

$$(F_x, F_z) = (\max\{F_{e,x}, F_{c,x}\}, \max\{F_{e,z}, F_{c,z}\}) \tag{3}$$



Relevant Areas	Condition
A and B	$z < 0$ (moving forward)
C and D	$z > 0$ (moving backward)
A and C	$x < 0$ (turning left)
B and D	$x > 0$ (turning right)

Figure 3: Obstacles considered according to the movement of the robot.

4.1 Environmental Force

The environmental force prevents the robot from moving and turning toward obstacles by presenting the user the distance information between the robot and the obstacles in the form of force.

This force is similar to ones in the traditional potential force field approaches used for path planning of mobile robots [21]. However, the environmental force is different from the potential force in three respects. First, there is no attraction to a goal since it is assumed that the goal position is unknown. Secondly, only obstacles in the "relevant" area (according to the logical position of the interface) are considered, i.e. the obstacles that are in the direction opposite to the movement of the robot are not relevant. Figure 3 shows areas that are considered relevant according to the position of the interface and intended direction of the robot (the area of relevancy is set arbitrarily with respect to the robot position). Finally, and most importantly, instead of the average or the sum of the forces due to obstacles, the maximum force over all obstacles is used. If the average or the sum of the forces was used, the actual range of the rendered forces would be too small for the user to notice the differences of the forces.

When the logical position of the interface is represented by (x, z), the environmental force $\mathbf{F_e} = (F_{e,x}, F_{e,z})$ is given by (See Figure 4):

$$F_{e,x} = \begin{cases} k_3 f_{-x}(D)x & \text{if } x \geq 0 \\ -k_3 f_{+x}(D)x & \text{if } x < 0 \end{cases} \tag{4}$$

$$F_{e,z} = \begin{cases} k_4 f_{-z}(D)x & \text{if } z \geq 0 \\ -k_4 f_{+z}(D)x & \text{if } z < 0 \end{cases} \tag{5}$$

where

$$f_{-x}(D) = \max_{i=1}^{n}[\phi_{-x}(d_i)\frac{d_i - r_{\text{max}}}{r_{\text{max}}}\cos\theta_i]$$

$$f_{+x}(D) = \max_{i=1}^{n}[\phi_{+x}(d_i)\frac{d_i - r_{\text{max}}}{r_{\text{max}}}\cos\theta_i]$$

$$f_{-z}(D) = \max_{i=1}^{n}[\phi_{-z}(d_i)\frac{d_i - r_{\text{max}}}{r_{\text{max}}}\sin\theta_i]$$

$$f_{+z}(D) = \max_{i=1}^{n}[\phi_{+z}(d_i)\frac{d_i - r_{\text{max}}}{r_{\text{max}}}\sin\theta_i]$$

$$\phi_{-x}(d_i) = \begin{cases} 1 & \text{if } d_i < r_{\text{max}} \text{ and } \cos\theta_i > 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\phi_{+x}(d_i) = \begin{cases} 1 & \text{if } d_i < r_{\text{max}} \text{ and } \cos\theta_i < 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\phi_{-z}(d_i) = \begin{cases} 1 & \text{if } d_i < r_{\text{max}} \text{ and } \sin\theta_i > 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\phi_{+z}(d_i) = \begin{cases} 1 & \text{if } d_i < r_{\text{max}} \text{ and } \sin\theta_i < 0 \\ 0 & \text{otherwise} \end{cases}$$

$$D = \{(d_1, \theta_1), (d_2, \theta_2), \cdots, (d_n, \theta_n)\}$$

d_i : the distance between the ith scanned obstacle point and the robot

θ_i : the angle of the ith scanned obstacle point

r_{max} : the maximum distance within which the forces emitted from obstacles affect the robot

The function f_{+z} represents the maximum value of the z components for all forces due to the obstacles in the front area of the robot, and is used when the robot advances forward. If this value exceeds 0, then the robot is prevented from moving closer to the obstacles when the user commands the robot to move forward. The functions f_{-z}, f_{+x} and f_{-x} are defined similarly, and are applied when the robot is moving backward, turning left, and turning right, respectively.

The force due to an obstacle is inversely proportional to the distance d_i between the robot and the obstacle, and does not affect the robot when the distance is equal to or greater than r_{max}. By changing r_{max}, the user can adjust the range within which the force emitted from the obstacle affects



Figure 4: An illustration of f_{+z} (The local coordinate system of the robot is used.)

the robot. Note that each scanned point obtained from the range-finding sensors is considered as an obstacle.

The values k_3 and k_4 are the constants to adjust the magnitude of the force. If these constants have large values, the robot becomes difficult to control since the rendered force is too large even though the robot is far away from the obstacles. On the other hand, if the constants are too small, the operator will not feel any force. A proper value for both of k_3 and k_4 is 0.1, which was determined empirically.

Although the environmental force prevents the robot from moving and turning toward obstacles to some degree, it does not guarantee that the robot will not collide with the obstacles. This is because the robot is modeled as a point, while, in actuality, the robot can have any shape and an obstacle is modeled as a polygon whose surface points are the scanned points sampled by the range-finding sensors. The force merely slows the robot down when obstacles are near the robot. To guarantee collision-free navigation, a collision-preventing force is introduced. A region-growing technique with higher values of k_3 and k_4 (e.g., 0.3 or more) using the radius of the robot can be considered to avoid collision. However, it is not a good solution because it can decrease the degree of freedom of control since the environmental force may prevent the user from moving the robot whenever an obstacle is near the robot (even though there is no obstacle in the direction of the movement of the robot). Note that the distances to all the obstacles in the relevant area are considered in computing the environmental force.



Figure 5: Two examples of the left and right possible-turning angles (δ_{cw} and δ_{ccw}).

4.2 Collision-Preventing Force

The collision-preventing force is computed from possible-turning angles and the distances between the robot and the obstacles in the front and rear direction of the robot. The possible-turning angles are the maximum angles by which the robot can turn without causing a collision. These angles have two types: the left (or counter-clockwise) angle (δ_{ccw}) and the right (or clockwise) angle (δ_{cw}), since the robot can turn both left and right. Figure 5 shows two examples of possible-turning angles for a rectangular-shaped robot restricted by the obstacle points scanned around the robot.

The distances between the robot and the obstacle in the front and rear direction of the robot are the maximum distances (d_{front} and d_{rear}) by which the robot can move forward and backward without any collision. Figure 6 shows an example of these distances.

When the logical position of the interface is represented by (x, z), the collision-preventing force $\mathbf{F_c} = (F_{c,x}, F_{c,z})$ is given by:

$$F_{c,x} = \begin{cases} k_5 \frac{\delta_{avg} - \delta_{ccw}}{\delta_{avg}} x & \text{if } x \geq 0 \text{ and } \delta_{avg} - \delta_{cw} > 0 \\ k_5 \frac{\delta_{avg} - \delta_{cw}}{\delta_{avg}} x & \text{if } x < 0 \text{ and } \delta_{avg} - \delta_{ccw} > 0 \end{cases} \tag{6}$$

$$F_{c,z} = \begin{cases} k_6 \frac{d_{front} - d_{max}}{d_{max}} z & \text{if } d_{front} < d_{max} \text{ and } z \leq 0 \\ -k_6 \frac{d_{rear} - d_{max}}{d_{max}} z & \text{if } d_{rear} < d_{max} \text{ and } z > 0 \\ 0 & \text{otherwise} \end{cases} \tag{7}$$

where



Figure 6: An example of d_{front} and d_{rear} (The local coordinate system of the robot is used.)

$$\delta_{avg} = \frac{\delta_{ccw} + \delta_{cw}}{2}$$

The absolute value of the z component of the collision-preventing force, $|F_{c,z}|$, is inversely proportional to d_{front} when the robot is moving forward (and to d_{rear} when the robot is moving backward). By sending this component of the force to the user when the robot is moving toward an obstacle, a collision can be prevented. The user can control the speed and turn rate of the robot without any disturbance when the robot is at a certain distance equal to or more than d_{max} from obstacles.

The x component of the force, $F_{c,x}$, is to prevent the robot from colliding with obstacles when the user intends the robot to turn left or right. Unlike $F_{c,z}$, $F_{c,x}$ is computed by using a relative difference of the left and right possible-turning angles. Consider the case shown in Figure 5(b) in which both the left and right possible-turning angles are very small since the sides of the robot are close to a wall. If absolute differences as in Equation (7) were used, it would be difficult for the user to make the robot turn in any direction because a large force would be sent to the user in order to prevent the robot from colliding with the wall. This means that the user could control only the speed of the robot, allowing the robot to only follow the wall and making it difficult for the user to change the distance between the robot and the wall. By using the relative difference, however, the user can change the heading of the robot to some degree, alleviating this problem.

The constant values k_5 and k_6 play the similar role to k_3 and k_4 in Equations (4) and (5), respectively. A proper value for both of k_5 and k_6 is 0.3, which was determined empirically. When this value is used with $x_{buffer} = z_{buffer} = 30.0$ defining the dead-zone (as described in Section 3 and Figure 1), the operator can feel the force of 9.0 N at the boundary of the dead-zone when there is an



(a) No obstacle in front of the robot.

(b) An obstacle suddenly appearing to front of the robot.

Figure 7: An example of the sudden increase in the collision-preventing force.

obstacle touching the robot.

Although the collision-preventing force guarantees that the robot will not collide with the obstacles, it is impractical to use the collision-preventing force alone. Consider the case in which a small obstacle is in the front-right side of the robot, and the robot is moving forward and turning right simultaneously at high speed (See Figure 7 (a)). At this moment, there is no obstacle in the front of the robot, so that the value of the z component of the force is zero. The moment the obstacle appears to front of the robot during the turning motion, the value of the force will abruptly change to a very high one (See Figure 7 (b)). This sudden increase in the force may cause harm to users. Thus, the collision-preventing force should be used together with the environmental force, which plays a role to buffer such increase in force feedback.

5 A Haptic Teleoperation System of a Mobile Robot

The proposed direct control system for an Activmedia Pioneer 2-DX mobile robot [22] was implemented. The robot was equipped with one SICK LMS-200 laser scanner (for forward coverage), eight ultrasonic transducer sensors (for backward coverage), and the Sony EVID-30 camera, and could move at a speed of about 1.4 m/s. The laser scanner provided a scan resolution of 10 mm with a systematic error of $\pm$15 mm, an angular resolution of 1 degree, a coverage of 180 degrees, and a distance range of about 8 m at a scan rate of about 10 Hz. The sonar array was arranged at 20-degree intervals and provided a distance range from 0.15 m to about 7 m at a multiplexed scan rate of about 25 Hz.

The resolutions and measurement accuracy of the laser scanner were reasonable to detect obstacles far from the robot, since precise distance measurement was not required to compute the environmental force, and the collision-preventing force was effective on only obstacles near the



Figure 8: The system architecture.

robot. For near obstacles, however, the laser scanner was not adequate enough as the effectiveness of the collision-preventing force was dependent on the accuracy of the measurement. It is not a serious problem if the distances to the obstacles are measured shorter than the actual. In this case, the collision-preventing force would make the robot stop moving at a distance of a few centimeters (the overall distance error due to the resolutions (or decimation) and the systematic error) from the obstacles. However, when the measured distance is larger than the actual, a collision can occur, since the collision-preventing force computed with the longer distances would be weaker than the actual force needed to avoid the collision. In this implementation, this problem was resolved by growing the size of the shape model for the robot into 8 cm more than the actual one. The grown size was 0.46×0.52 m, while the actual one was 0.38×0.44 m.

On the other hand, the sonar array was also not adequate to be used for the collision-preventing force, because it could not measure the distances of less than about 15 cm. This problem can be also resolved by growing the size of the shape model. In the implementation, however, the size-growing technique for the sonars was not considered since the sensors were used for the backward-movements only. According to the observations in the experiments described in Sections 6 and 7,

users tended to make the robot move backward only rarely and to do so at a low speed after securing a sufficient room (by making the robot move forward). This means that the collisions in the backward-movements rarely occurred even though the collision-preventing force for the backward-movements was not fed back to the users.

The SensAble PHANToM 1.5 [6, 7] was used as the force-feedback device. The device provides a workspace of 195 $\times$ 270 $\times$ 375 mm, the maximum exertable force of 6.4 N, and the nominal resolution of 0.03 mm. The resolution of the PHANToM was enough to specify the speed and turn rate of the robot, of which the values were represented with the resolutions of 0.001 m/s and 1 $^\circ$/s, respectively.

The system architecture is shown in Figure 8. The system used 2 PCs and an embedded PC in the Pioneer 2-DX. The control PC with the PHANToM was indirectly connected to the Pioneer 2-DX via the intermediate PC since, in the setup, the control PC did not support a wireless network connection. The network connections of the control PC to the intermediate PC and the intermediate PC to the Pioneer 2-DX had 100 Mbps and 1 Mbps bandwidths, respectively. The intermediate PC may be unnecessary if the control PC supports a wireless network connection. For the communication between the intermediate PC and the Pioneer 2-DX, the Player[1][23] was used.

In addition to force feedback, the system provided visual feedback of the image sequence captured by the camera attached to the Pioneer 2-DX. The image update rate on the control PC was about 8 Hz with the resolution of an image at 160 $\times$ 48 and each pixel is represented by 256 gray levels.

The input module converts the physical position of the PHANToM to a logical position (x, z), and maps the logical position to the motion parameters (speed v, turn rate ω) of the mobile robot by applying the car-driving metaphor described in Section 3. In the implementation, the logical position was the same as a physical position in the unit of mm. The system used $x_{buffer} = z_{buffer} = 30.0, k_1 = 20.0$ and $k_2 = 1.0$ in Equations (1) and (2) for the car-driving metaphor, and limited the working area of the PHANToM to 180 $\times$ 200 mm, so that the speed and the turn rate of the robot were at most 1.4 m/s and 60 $^\circ$/s, respectively.

6 Experiment I: Navigating in the Virtual Environment

Experiments in two different environments were performed to measure the effectiveness of the haptic information to operators in safely navigating a robot in the given environment. The experiment was

[1]The Player was developed jointly at the USC Robotics Research Labs and HRL Labs and is freely available under the GNU General Public License from `http://playerstage.sourceforge.net`.



Figure 9: The virtual environment used for Experiment I.

first carried out with a virtual robot in a virtual environment primarily for the ease of collecting data on the dependent variables, but later also, with a real robot in a real environment. In both of the experiments, three different methods of force rendering (independent variable) were tested and compared with one another. The three methods can be described and distinguished in terms of the values of the constants k_3, k_4, k_5 and k_6 as follows:

- NF: No force feedback ($k_3 = 0$, $k_4 = 0$, $k_5 = 0$ and $k_6 = 0$).
- EF-only: Using environmental force only ($k_3 = 0.1$, $k_4 = 0.1$, $k_5 = 0$ and $k_6 = 0$).
- EF & CF: Using both environmental and collision-preventing force ($k_3 = 0.1$, $k_4 = 0.1$, $k_5 = 0.3$ and $k_6 = 0.3$).

The method of using collision-preventing force only (CF-only) was not considered since CF-only is impractical as explained in Section 4.2. The experiment carried out in the virtual environment is first described in this section.

6.1 Virtual Test Environment

In Experiment I, a subject was required to make the virtual robot navigate a virtual environment with a size of 13.8 $\times$ 13.5 m. A perspective view of the virtual test environment used for the experiment is shown in Figure 9.

The virtual environment had two types of obstacles. One was the wall type (width = 0.2 m), and the other was the cylinder type (diameter = 0.15 m). All obstacles were 0.2 m high. The obstacles were arranged in four different ways: scattered cylinders, straight rectangular walls, (lined) cylindrical walls and curved walls. In the zone of scattered cylinders (Zone 1 in Figure 9), the



Figure 10: Two snapshots of the virtual environment shown to subjects.

distances between cylinders ranged between 0.7 m and 1.5 m. In the zones of the rectangular walls and the cylindrical walls (Zones 2 and 3 in Figure 9, respectively), the widths of wall openings were 0.5 m and the distances between the walls were 1.4 m. In the zones of the curved walls (Zone 4 in Figure 9), the widths of the road were 0.6 m.

In the virtual environment, the robot was cube-shaped with the dimension of 0.35 $\times$ 0.55 $\times$ 0.25 m. Given the position, direction, speed and turn rate of the robot at time t, as $\mathbf{P}(t) = [P_x(t)P_z(t)]^T$, $\mathbf{D}(t) = [D_x(t)D_z(t)]^T$, $v(t)$ and $\omega(t)$, respectively, the motion of the robot is modeled as follows:

$$\mathbf{P}(t) = \mathbf{P}(t - \Delta t) + v(t - \Delta t)\mathbf{D}(t - \Delta t)\Delta t$$

$$\mathbf{D}(t) = \mathbf{R}(\omega(t - \Delta t)\Delta t)\mathbf{D}(t - \Delta t)$$

$\mathbf{P}(0)$: initial position

$\mathbf{D}(0)$: initial direction

$$\mathbf{R}(\theta) = \begin{pmatrix} \cos\theta & \sin\theta \\ -\sin\theta & \cos\theta \end{pmatrix} \text{: rotation matrix}$$

Δt denotes the time interval between the previous frame and the current frame. Note that $v(t)$ and $\omega(t)$ are computed from the logical position of the interface (tip of the haptic manipulator) at time t.

The simulated robot had two virtual laser scanners to cover 360 degrees and a virtual camera positioned on its top-center, while the real robot had one laser scanner for forward coverage and eight sonars for backward coverage. The virtual laser scanner was simulated with the same specification as the actual one described in Section 5. The virtual camera had the field of view of 45 degrees and the image resolution of 640 $\times$ 480.

In addition to the scene shown through the virtual camera, the virtual environment provided visual feedback in order to let subjects know when the robot collided with obstacles, by changing the background color from blue to red. The background color returned to blue after 0.5 seconds. Figure 10 illustrates two snapshots of the virtual test environment from the subject's perspective.



Figure 11: The virtual environment used for training in Experiment I.

6.2 Experimental Design

A subject was required to make the (virtual) robot navigate the virtual environment from the start position to the goal position as *quickly and safely* as possible. Although it is assumed that there would not be a goal position in the actual use of the system, the experiment was set with a start position and a goal position in the virtual environment in order to collect experimental data.

A repeated-measure design was applied to the experiment. A subject made one trial of the task with each force rendering method in a round (with three trials total in one round) and repeated three rounds of trials, so that each subject made a total of nine trials of the task (three trials for each method). There was no break time between the trials. The methods were ordered differently for each subject in order to reduce the carry-over effect, and subjects were not notified of which method they were using. After finishing all trials, each subject filled out a questionnaire.

Each subject had a training session before the experimental session in order to learn how to use the interface and understand the task. In the training session, a subject made one trial of the task with each method. The virtual environment used for training was similar to that used for the experiment, but the training environment had a smaller number of obstacles than the actual and did not have curved walls. Figure 11 shows a perspective view of the virtual environment used for training.

Twenty subjects voluntarily participated in the experiment. The ages of the subjects were between 20 and 35, and all of the subjects except two were male.

6.3 Experimental Results

Objective Analysis

In Experiment I, the following seven dependent variables were measured.

- The number of collisions between the robot and the environment

- Navigation time from the start to the goal
- Average speed of the robot
- The average of the minimum distances between the robot and the obstacles (over all directions, front direction only (d_{front}), and rear direction only (d_{rear}))
- The average of the possible-turning angles (left angle (δ_{ccw}), and right angle (δ_{cw}))
- Speed on colliding with the obstacles (average and maximum)
- Turn rate on colliding with the obstacles (average and maximum)

The results for all of the dependent variables are shown in Figure 12 and Table 1. The within-subject ANOVA on the results for the 3rd round revealed that there were statistically significant differences among the methods on all of the dependent variables except for the navigation time.

For post hoc comparisons, the Tukey HSD tests were performed. First, EF & CF showed a significantly greater reduction in the number of collisions than either EF-only or NF alone ($p < 0.01$). As described in Section 4.1, EF-only could not guarantee that the robot would not collide with any obstacles. EF-only showed a significantly greater reduction in the number of collisions than NF ($p < 0.01$). Although the number of collisions was dramatically reduced when using EF & CF, it was not zero. In the experiment, the collision-preventing force did not completely prevent collisions. This is because the PHANToM generated forces that were too small to prevent user actions. Nevertheless, seven subjects were able to navigate the robot to avoid collisions.

As for the average speed, EF & CF compelled the robot move at a significantly lower speed than NF ($p < 0.01$), but there were no significant differences between EF & CF and EF-only ($p > 0.05$), or between EF-only and NF ($p > 0.05$). Although there was a significant difference between EF & CF and NF, the difference was not meaningful since it was important that the robot moved safely and the reduction in the average speed did not significantly affect the task completion time (the navigation time).

EF & CF made the robot navigate at a statistically significant further distance from the obstacles over all directions than did EF-only ($p < 0.05$) or NF ($p < 0.01$), and there was also a significant difference between EF-only and NF ($p < 0.05$). This means that the probability of collision was minimal when EF & CF was used.

For the average of the front and rear minimum distances between the robot and the obstacles (d_{front} and d_{rear} in Figure 6, respectively), there were significant differences found among the experimental groups (NF vs. EF-only : $p > 0.05$ and $p < 0.01$, NF vs. EF & CF : $p < 0.01$ and $p < 0.01$, and EF-only vs. EF & CF : $p > 0.05$ and $p > 0.05$ on d_{front} and d_{rear}, respectively). d_{front} and d_{rear} were the maximum distances by which the robot could move forward and backward



(a) The number of collisions.



(b) The navigation time.



(c) The average speed.



(d) The minimum distance between the robot and the obstacles over all direction.



(e) The minimum distance between the robot and the obstacles in front direction only.



(f) The minimum distance between the robot and the obstacles in rear direction only.

Figure 12: The results of Experiment I (M1: NF, M2: EF-only, and M3: EF & CF).



(g) The left possible-turning angle.



(h) The right possible-turning angle.



(i) The average speed on colliding with obstacles.



(j) The maximum speed on colliding with obstacles.



(k) The average turning rate on colliding with obstacles.



(l) The maximum turning rate on colliding with obstacles.

Figure 12: The results of Experiment I (M1: NF, M2: EF-only, and M3: EF & CF) (continued).

Table 1: Experimental results (mean and standard deviation) and the within-subject ANOVA results for the 3rd round of Experiment I.

(a) The number of collisions: $F_{2,38} = 31.39, p < 0.0001$

	1st Round	2nd Round	3rd Round
NF	23.8 (11.4)	15.8 (11.7)	13.7 (8.99)
EF-only	25.9 (22.5)	14.6 (14.1)	8.55 (4.68)
EF & CF	4.25 (5.09)	2.4 (2.66)	1.35 (1.57)

(b) The navigation time (seconds): $F_{2,38} = 3.04, p > 0.05$

	1st Round	2nd Round	3rd Round
NF	170.0 (111.5)	126.1 (89.5)	115.4 (72.2)
EF-only	214.7 (170.3)	151.4 (98.3)	130.6 (83.9)
EF & CF	193.5 (92.3)	148.8 (73.7)	140.5 (84.9)

(c) The average speed (m/s) : $F_{2,38} = 5.81, p < 0.01$

	1st Round	2nd Round	3rd Round
NF	0.26 (0.14)	0.35 (0.17)	0.39 (0.20)
EF-only	0.24 (0.14)	0.30 (0.15)	0.33 (0.15)
EF & CF	0.22 (0.13)	0.28 (0.13)	0.30 (0.13)

(d) The minimum distance between the robot and the obstacles over all directions (m): $F_{2,38} = 14.02, p < 0.0001$

	1st Round	2nd Round	3rd Round
NF	0.083 (0.026)	0.109 (0.028)	0.109 (0.032)
EF-only	0.097 (0.021)	0.112 (0.029)	0.125 (0.031)
EF & CF	0.117 (0.024)	0.129 (0.023)	0.140 (0.020)

(e) The minimum distance between the robot and the obstacles in front direction only (m): $F_{2,38} = 6.19, p < 0.005$

	1st Round	2nd Round	3rd Round
NF	0.73 (0.17)	0.80 (0.16)	0.82 (0.19)
EF-only	0.84 (0.15)	0.86 (0.13)	0.91 (0.15)
EF & CF	0.94 (0.16)	0.95 (0.11)	0.95 (0.14)

(f) The minimum distance between the robot and the obstacles in rear direction only (m): $F_{2,38} = 17.59, p < 0.0001$

	1st Round	2nd Round	3rd Round
NF	0.78 (0.14)	0.86 (0.13)	0.91 (0.13)
EF-only	0.97 (0.19)	1.03 (0.13)	1.08 (0.11)
EF & CF	1.02 (0.19)	1.13 (0.09)	1.09 (0.10)

(g) The left possible-turning angle ($^\circ$) : $F_{2,38} = 20.57, p < 0.0001$

	1st Round	2nd Round	3rd Round
NF	126.3 (26.5)	153.3 (24.6)	149.9 (30.3)
EF-only	148.8 (23.5)	155.4 (34.5)	167.8 (40.1)
EF & CF	187.7 (41.4)	186.9 (28.9)	199.5 (30.3)

(h) The right possible-turning angle ($^\circ$) : $F_{2,38} = 24.17, p < 0.0001$

	1st Round	2nd Round	3rd Round
NF	129.0 (26.5)	154.1 (25.5)	150.1 (28.9)
EF-only	152.0 (23.6)	157.9 (33.1)	168.5 (39.5)
EF & CF	193.7 (40.4)	188.2 (28.0)	201.5 (29.6)

(i) The average speed on colliding with the obstacles (m/s) : $F_{2,38} = 6.55, p < 0.005$

	1st Round	2nd Round	3rd Round
NF	0.50 (0.23)	0.56 (0.29)	0.58 (0.31)
EF-only	0.29 (0.16)	0.30 (0.18)	0.36 (0.20)
EF & CF	0.25 (0.24)	0.28 (0.20)	0.33 (0.37)

(j) The maximum speed on colliding with the obstacles (m/s) : $F_{2,38} = 20.42, p < 0.0001$

	1st Round	2nd Round	3rd Round
NF	1.14 (0.31)	1.06 (0.37)	0.98 (0.35)
EF-only	0.74 (0.33)	0.63 (0.28)	0.68 (0.30)
EF & CF	0.46 (0.39)	0.42 (0.37)	0.41 (0.43)

(k) The average turn rate on colliding with the obstacles ($^\circ$/s) : $F_{2,38} = 5.57, p < 0.01$

	1st Round	2nd Round	3rd Round
NF	21.3 (11.2)	21.5 (9.3)	18.6 (9.3)
EF-only	12.2 (7.6)	11.0 (6.7)	10.9 (8.3)
EF & CF	12.8 (8.4)	8.7 (10.9)	9.7 (13.9)

(l) The maximum turn rate on colliding with the obstacles ($^\circ$/s) : $F_{2,38} = 25.55, p < 0.0001$

	1st Round	2nd Round	3rd Round
NF	54.2 (18.4)	53.6 (18.4)	47.6 (17.5)
EF-only	37.1 (17.2)	31.1 (14.6)	26.7 (17.0)
EF & CF	24.6 (19.9)	13.9 (15.9)	14.6 (22.2)

without colliding. According to the results, compared to NF, EF & CF made the robot stop at a significantly further distance from the obstacles when the robot moved forward or backward. This means that EF & CF made the robot navigate the most safely. When a user wants to explore an environment at a close distance to objects to observe them in detail, however, it may be difficult to do so since the forces would hinder the user's actions. This can be easily resolved by adjusting the constants k_3, r_{max}, k_6 and d_{max} in Equations (4) and (7).

The multiple comparison test revealed that there were significant differences on both the averages of the left and right possible-turning angles among the methods (NF vs. EF-only : $p < 0.05$, NF vs. EF & CF : $p < 0.01$, EF-only vs. EF & CF : $p < 0.01$). The possible-turning angles are the maximum angles by which the robot can turn without any collision. The larger the average of the possible-turning angles, the less likely becomes a collision on turning. These dependent variables have a similar meaning to the average of the front and rear minimum distances, but the former is related to the turning motion of the robot while the latter is related to the translational motion of the robot.

The speed and the turn rate on colliding were also measured to see how much impact is given to the robot on colliding. Both EF & CF and EF-only showed significantly lower average speeds on colliding than NF ($p < 0.05$), but there was no significant difference between EF & CF and EF-only ($p > 0.05$). With the maximum speed, however, there were significant differences among the methods ($p < 0.05$), that is, EF & CF showed the lowest maximum speed and EF-only showed lower maximum speed than NF. There was no significant difference in average speed between EF & CF and EF-only, but there was a significant difference in the maximum speed. This is because the collision-preventing force reduced the maximum speed upon colliding. While the average speed on colliding is related to the accumulated damage to the robot, the maximum speed on colliding is related to the peak in damage to the robot. According to the results, both EF & CF and EF-only gave the same accumulated damage to the robot, but EF & CF gave less peak damage to the robot than EF-only. For the turn rate on colliding, similar results to those on the speed on colliding were obtained.

Figure 13 shows the task learning effect for each method on the number of collisions, represented by the exponential regression function. According to the learning curves, the numbers of collisions for NF, EF-only, and EF & CF are asymptotically approaching 13, 2, and 0, respectively, as the round progresses. This means that NF causes more collisions than EF-only and EF & CF even if the subjects do more trials or training. EF-only showed the more number of collisions than NF in the 1st round, but less after the 2nd round. This indicates that the users should be trained much in order to make the robot navigate safely with EF-only (at least three trials of EF for taking better effect than NF, and many more trials for taking similar effect to EF & CF). Besides, the learning curve for EF & CF shows that the number of collisions is asymptotically approaching zero as the round progresses.



Figure 13: The learning curve for each method fitted to the pairs of the number of collisions and the round in Experiment I. $\hat{Y}$ = 12.9525 + 41.3237e$^{-1.3375X}$ for NF (SSE = 1.15×10^{-18}), $\hat{Y}$ = 1.5781 + 45.4277e$^{-0.6247X}$ for EF-only (SSE = 2.84×10^{-29}), $\hat{Y}$ = $-$0.0281 + 7.5376e$^{-0.5664X}$ for EF & CF (SSE = 1.14×10^{-23}).

From this fact, it can be inferred that it is possible to make collision-free navigation with EF & CF if only the users are trained sufficiently, even though the haptic device cannot generate the appropriate force to prevent the users' actions.

Subjective Analysis

For a subjective analysis, all the subjects filled out a questionnaire after finishing all trials of the task. The questionnaire included four questions. The first asked whether the subjects could distinguish force-feedback control from no force-feedback control. The second asked how much the subjects thought the force feedback helped them to control the robot without any collisions. The subjects answered the second question on a scale from 1 to 7 (1 = never, 7 = very much) for each of force-feedback control and no force-feedback control. The third question asked whether the subjects could distinguish the differences among the three force rendering methods. The last question was similar to the second one. The subjects gave scores for each of the three methods.

For the first question, all subjects except one answered 'yes.' The subject who answered 'no' claimed that he felt force on all the methods. It is believed that this was because PHANToM gave the subject some type of a force due to its mechanics even if the control was not sending any such force. However, the basic force can be ignored since almost all subjects answered that they distinguished force-feedback control from no force-feedback control.

The subjects who answered 'yes' to the first question gave scores for the second one. The within-

subject ANOVA revealed that the subjects thought the force feedback ($M = 5.7$, $SD = 0.73$) was much more helpful than no force feedback ($M = 2.7$, $SD = 1.0$) for the collision-free control of the robot ($F_{1,18} = 88.33$, $p < 0.0001$).

For the third question, fourteen subjects answered that they could distinguish the differences among the three methods, but they said that the force made by EF & CF was merely stronger than that made by EF-only. The five subjects who answered 'no' reported that they felt the same degree of force on EF-only and EF & CF.

The subjects who answered 'yes' to the third question also gave scores. The mean scores were 2.56 for NF, 5.1 for EF-only and 6.1 for EF & CF, and their standard deviation were 1.01 for NF, 0.77 for EF-only and 0.66 for EF & CF. The within-subject ANOVA revealed that there were significant differences on the scores among the methods ($F_{2,26} = 75.87$, $p < 0.0001$). According to the results of the Tukey HSD post-hoc test, EF & CF showed the highest score ($p < 0.01$), and EF-only showed a higher score than NF ($p < 0.01$).

It is concluded from subjective analysis that the subjects thought force-feedback control (EF-only and EF & CF), especially using EF & CF, was much more helpful than no force-feedback control (NF) for collision-free navigation.

7 Experiment II: Navigating in the Real Environment

7.1 Real Test Environment

In Experiment II, a subject was required to make a real mobile robot navigate a real environment whose size was 3.65 $\times$ 6.86 m (smaller than the virtual test environment). Two snapshots of the real test environment are shown in Figure 14.

The real environment had the same types of obstacles as those of the virtual test environment described in Section 6. While the obstacles were arranged in four different ways in Experiment I, the obstacles were arranged in only two different ways in Experiment II because of the limited size of the real test environment: scattered cylinders and straight rectangular walls. In the zone of scattered cylinders, the distances between cylinders ranged between 0.7 m and 1.55 m. In the zone of the rectangular walls, the widths of wall openings were 0.65 m and the distance between the walls were 1.5 m.

Unlike the virtual test environment, the real test environment could not respond to produce the "special" feedback (e.g. color flash) to users when the robot collided with obstacles since the real robot did not have any collision/touch sensors on it. In the experiment, in order to make subjects



(a) With the robot on the start position.



(b) With the robot on the goal position.

Figure 14: Two views of the real environment used for Experiment II.

recognize collisions easily, an immediate visual feedback was given to subjects by the experimenter waving his hand in front of the camera of the robot when a collision occurred.

7.2 Experimental Design

A subject was required to make the robot navigate the real environment from a start position to a goal position as *safely* as possible. In Experiment II, the subjects were not asked to make the robot move as quickly as possible since colliding at high speed could cause serious damage to the robot. In addition, the maximum speed and turn rate of the robot was limited to 0.14 m/s (k_1 = 2.0 in Equation (1)) and 15 °/s (k_2 = 0.25 in Equation (2)), respectively, in order to reduce damage to the robot in case of a collision at the full speed on using NF, although the speed and the turn rate were 1.4 m/s and 60 °/s, respectively, in the implementation.

A repeated-measure design was applied to the experiment. A subject made one trial of the task with each force rendering method, so that each subject made a total of three trials of the task. A subject carried out only one round of trials in Experiment II, while three rounds of trials in Experiment I. There were no break time between the trials. The methods were ordered differently for each subject in order to reduce the carry-over effect, and subjects were not notified of which method they were using. After finishing a trial, each subject filled out the questionnaire shown in Table 2. The set of the presence questions in the questionnaire was a modified version of that used in [24].

Each subject had a training session before the experimental session in order to learn how to use interfaces and to understand the task. In the training session, a subject made one trial of the task with each method. A virtual environment was used for the training. The virtual training environment was designed very similarly to the real environment in order to make the subject waste less time in the

Table 2: The questionnaire used in Experiment II. The category information was not shown to the subjects.

No. (Category)	Question
1* (Force Perception)	Do you think that there is any difference between the interface used in the previous trial and that in this trial ? (Please circle the answer.) Yes / No
2** (Force Perception)	Do you think that there is any difference among the 3 interfaces ? (Please circle the answer.) Yes / No
3 (Perceived Performance)	How much do you think the interface for this trial is good in terms of achieving the required task ? (Please rate with a score, on the scale from 0 to 100, where 0 represents “Never” and 100 represents “Very much”)
4 (Presence Question 1)	When you were performing this trial, how much did you feel as if you were in the environment ? (Please rate with a score, on the scale from 0 to 100, where 0 represents “Never” and 100 represents “Completely”)
5 (Presence Question 2)	When you think back about your experience in this trial, do you think of the environment more as images that you saw, or more as somewhere that you visited ? (Please rate with a score, on the scale from 0 to 100, where 0 represents “Images that I saw” and 100 represents “Somewhere that I visited”)
6 (Presence Question 3)	During the course of the experience in this trial, which was stronger on the whole, your sense of being in the environment, or of being in the haptic laboratory ? (Please rate with a score, on the scale from 0 to 100, where 0 represents “In the haptic laboratory” and 100 represents “In the environment”)

∗ No. 1 was filled out after the 2nd and 3rd trials only. ∗∗ No. 2 was filled out after the 3rd trial only.



Figure 15: The virtual environment used for training in Experiment II.



(a) The number of collisions. (b) The navigation time.

Figure 16: The results of Experiment II.

navigation time in the actual experimental session. Figure 15 shows a view of the virtual environment used for training.

Twelve subjects participated in Experiment II. The ages of the subjects were between 23 and 37, and all of the subjects except two were male. Three subjects had participated in Experiment I.

7.3 Experimental Results

Objective Analysis

In Experiment II, the following two dependent variables were measured.

- The number of collisions between the robot and the environment
- Navigation time from the start to the goal

The dependent variables were manually measured since the robot did not have any sensor system for the precise measurement such as bumpers with touch sensors and accurate localization mechanisms. A second experimenter manually counted the number of collisions, measured the navigation time using a stop-watch, and recorded the values.

The results of the dependent variables are summarized in Figure 16 and Table 3. The within-subject ANOVA on the results revealed statistically significant differences among the methods on the number of collisions. However, there was no significant difference on the navigation time.

For post hoc comparison, the SNK (Student-Newman-Keuls) grouping test was performed for the number of collisions. Figure 16 shows the results of the test ($\alpha = 0.05$). According to the test, NF and EF-only were not significantly different from each other, but EF & CF was significantly different from NF and EF-only. EF-only showed just a marginally greater reduction in the number

Table 3: The mean and standard deviation of the results of Experiment II, and their within-subject ANOVA results.

Methods	The number of collisions $F_{2,22} = 5.49, p < 0.015$	Navigation time (seconds) $F_{2,22} = 0.02, p > 0.98$
NF	7.42 (8.53)	459 (419)
EF-only	6.33 (9.16)	461 (229)
EF & CF	0.83 (1.27)	448 (289)

Table 4: The mean and standard deviation of the results of the questionnaire in Experiment II, and their within-subject ANOVA results.

Methods	Perceived performance $F_{2,18} = 4.11$, $p < 0.034$	Presence question 1 $F_{2,18} = 4.11$, $p < 0.034$	Presence question 2 $F_{2,18} = 9.66$, $p < 0.01$	Presence question 3 $F_{2,18} = 9.40$, $p < 0.01$
NF	53.0 (22.1)	50.5 (21.8)	44.0 (26.4)	46.0 (24.2)
EF-only	69.5 (18.5)	64.0 (20.1)	58.0 (29.1)	62.0 (26.9)
EF & CF	73.5 (10.8)	68.0 (14.2)	65.0 (25.3)	68.2 (22.2)

of collisions than NF. It is because the subjects did not learn the usage of EF-only sufficiently to make the robot avoid the collisions. The results of Experiment II is similar to the 2nd round results of Experiment I (See Figures 12(a) and 13). It is believed that EF-only should show a significant greater reduction than NF if the subjects would understand the usage of EF-only better or were trained more with EF-only. The collision-preventing force did not completely prevent the collisions due to the same reason described in Section 6.3, but seven subjects were able to navigate the robot without any collision.

Subjective Analysis

The two subjects answered ‘no’ for the 1st and 2nd questions of the questionnaire. The results for the other questions are shown in Figure 17 and Table 4, which were answered by the ten subjects who marked ‘yes’ for the 1st and 2nd questions. For all of the questions, the within-subject ANOVA revealed that there were significant differences among the methods. According to the SNK grouping tests, EF-only and EF & CF were significantly different from NF, but were not significantly different from each other. This means that the subjects thought that the force feedback methods had been



(a) The perceived performance.



(b) The presence question 1.



(c) The presence question 2.



(d) The presence question 3.

Figure 17: The results of the questionnaire in Experiment II.

better than no force feedback method in terms of the task performance and presence. Particularly, it is an interesting fact that the subjects felt significantly more presence with the force feedback methods than with no force feedback method, although the force feedback methods *indirectly*[2] gave the environmental information to the subjects. While there have been reports that direct or passive haptics improved the user felt presence [25, 26], this is one of the first results of shown that the indirect haptics also enhanced presence.

8 Conclusion

In this paper, a novel and effective approach to using force feedback for mobile robot teleoperation in a shared autonomy scenario was proposed. The effectiveness was tested through an experiment in a virtual environment, then further verified through a smaller-scaled experiment in the real environment. Employing two types of forces, environmental and collision-preventing, produced a synergy effect, reducing the sometimes unintuitive nature of the control metaphor due to the conflicts between the operator intentions and the goals of the on-board controller, significantly improved the overall navigational safety and performance (along several dimensions). This was accomplished without degradation in other aspects of performance such as navigation time.

It is stipulated that the provision of forces (in one way or another) seems to promote the user's sense of presence in the remote environment and helped the user navigate more safely with better cognition of the remote environment, especially with impoverished sensory feedback in other modalities (e.g. limited field of view, low resolution of camera image, no sound). This still needs further verification by additional experiments. The future work will focus more on the issue of relating user felt presence to navigational performance. Another thread of future work includes the investigation into ways of selecting the appropriate modality or amount of sensory feedback to induce high user felt presence.

Acknowledgment

The authors would like to thank the Ministry of Education of Korea for its financial support toward the Electrical and Computer Engineering Division at POSTECH through its BK21 program. This research has been funded in part by the Integrated Media Systems Center, a National Science Foundation Engineering Research Center, Cooperative Agreement No. EEC-9529152. The authors also

[2] "indirectly" means "without a touch with the environment or the geometric models reproduced from the environment."

thank Nancy Haiyan Hu for assisting them with the experiment process.

References

[1] T. Sheridan. *Telerobotics, Automation, and Human Supervisory Control*. MIT Press, Cambridge, MA, 1992.

[2] R. Murphy and E. Rogers. Cooperative assistance for remote robot supervision. *Presence: Teleoperators and Virtual Environments*, 5(2):224–240, 1996.

[3] T. Fong, F. Conti, S. Grange, and C. Baur. Novel interfaces for remote driving: gesture, haptic and pda. In *Proc. of SPIE Telemanipulator and Telepresence VII*, Boston, MA, USA, November 2000.

[4] A. Bejczy and J. Salisbury. Kinematic coupling between operator and remote manipulator. *Advances in Computer Technology*, 1:197–211, 1980.

[5] B. Hannaford, L. Wood, D.A. McAffee, and H. Zak. Performance evaluation of a six-axis generalized force reflecting teleoperator. *IEEE Transactions on Systems, Man, and Cybernetics*, 21(3):620–633, 1991.

[6] T. H. Massie and J. K. Salisbury. The phantom haptic interface: A device for probing virtual objects. In *Proc. of the ASME Winter Annual Meeting, Symposium on Haptic Interfaces for Virtual Environment and Teleoperator Systems*, Chicago, IL, USA, November 1994.

[7] Sensable Technologies Inc. PHANToM^{TM} hardware devices. `http://www.sensable.com`.

[8] Immersion. Cybergrasp and Impulse Engine 2000. `http://www.immersion.com`.

[9] Logitech. Logitech Force^{TM} 3D. `http://www.logitech.com`.

[10] T. G. Anderson. A virtual universe utilizing haptic display. In *Proc. of the First PHANToM User's Group Workshop*, Dedham, MA, USA, September 1996.

[11] W. Aviles and J. Ranta. A brief presentation on the vrdts - virtual reality dental training system. In *Proc. of the Fourth PHANToM User's Group Workshop*, Deham, MA, USA, October 1999.

[12] I. Elhajj, N. Xi, and Y. H. Liu. Real-time control of internet based teleoperation with force reflection. In *Proc. of IEEE ICRA 2000*, San Francisco, CA, USA, April 2000.

[13] M. L. McLaughlin, G. Sukhatme, C. Shahabi, J. Hespanha, A. Ortega, and G. Medioni. The haptic museum. In *Proc. of the EVA 2000 Conference on Electronic Imaging and the Visual Arts*, Florence, Italy, 2000.

[14] M. A. Srinivasan and C. Basdogan. Haptics in virtual environments: Taxonomy, research status, and challenges. *Computers & Graphics*, 21(4):393–404, 1997.

[15] D. Xiao and R. Hubbold. Navigation guided by artificial force fields. In *Proc. of ACM CHI 98 Conference on Human Factors in Computing Systems*, Los Angeles, CA, USA, April 1998.

[16] D. Bartz and Ö. Güvit. Haptic navigation in volumetric datasets. In *Proc. of PHANToM User Research Symposium*, Zürich, Swiss, 2000.

[17] I. Elhajj, N. Xi, W. K. Fung, Y. H. Liu, W. J. Li, T. Kaga, and T. Fukuda. Haptic information in internet-based teleoperation. *IEEE/ASME Trans. on Mechatronics*, 6(3):295–304, September 2001.

[18] T. Fong, C. Thorpe, and C. Bauer. Advanced interfaces for vehicle teleoperation; collaborative control, sensor fusion displays, and remote driving tools. *Autonomous Robots*, 11:77–85, 2001.

[19] Otto J. Rösch, Klaus Schilling, and Hubert Roth. Haptic interfaces for the remote control of mobile robots. *Control Engineering Practice*, 10(11):1309–1313, November 2002.

[20] Nicola Diolaiti and Claudio Melchiorri. Haptic tele-operation of a mobile robot. In *Proc. of the 7th IFAC Symposium on Robot Control (SYROCO 2003)*, Wroclaw, Poland, September 1-3 2003.

[21] O. Khatib. Real-time obstacle avoidance for manipulators and mobile robots. *The International Journal of Robotics Research*, 5(1), 1986.

[22] ActivMedia Robotics. P2-DXE. `http://www.activmedia.com`.

[23] Brian P. Gerkey, Richard T. Vaughan, Kasper Støy, Andrew Howard, Gaurav S. Sukhatme, and Maja J Matarić. Most valuable player: A robot device server for distributed control. In *Proc. of IEEE/RSJ IROS 2001*, Wailea, Hawaii, October 29 - November 3 2001.

[24] Mel Slater, Martin Usoh, and Anthony Steed. Depth of presence in virtual environments. *Presence: Teleoperators and Virtual Environments*, 3(2):130–144, 1994.

[25] Eva-Lotta Sallnäs, Kirsten Rassmus-Gröhn, and Calle Sjöström. Supporting presence in collaborative environments by haptic force feedback. *ACM Transactions on Computer-Human Interaction*, 7(4):461–476, December 2000.

[26] Hunter G. Hoffman. Physically touching virtual objects using tactile augmentation enhances the realism of virtual environments. In *Proc. of the IEEE Virtual Reality Annual International Symposium (VRAIS 98)*, Atlanta, GA, March 14-18 1998.