

Shaping Human Behavior by Observing Mobility Gestures

David Feil-Seifer
Interaction Laboratory
Computer Science Department
University of Southern California
University Park, Los Angeles, California, USA
dfseifer@usc.edu

Maja J Matarić
Interaction Laboratory
Computer Science Department
University of Southern California
University Park, Los Angeles, California, USA
mataric@usc.edu

Categories and Subject Descriptors: I.2.9 Artificial Intelligence: Robotics

General Terms: Human Factors

1. INTRODUCTION

We present a method for testing shaping-based training of human behavior in a repetitive memory drill. Our work is focused on Socially Assistive Robotics (SAR), a field formed by the intersection of Socially Interactive Robotics (SIR, robots whose goal is to socially interact with human users) and Assistive Robotics (AR, robots whose goal is to assist those in need, typically through physical contact). SAR focuses on providing assistance through non-contact social interaction [3], with a broad spectrum of applications in education.

Our goal is to show that a robot can behave expressively in order to shape and enhance a user's learning experience. This work, as part of our general SAR research, is aimed at applications in health care and special education, where our interviews with teachers have shown a desire for robots that can engage one or a group of students in learning activities.

2. RELATED WORK

Several lines of research bear relevance to the work we are pursuing. The two most relevant are: expressibility in human-robot interaction in social robotics, and human-robot teaching and learning by demonstration.

The most related work from social robotics is that of Breazeal et al., who used the Leonardo robot platform to study robot learning through social interaction [1]. Learning was viewed as a collaborative dialog. The use of an embodied system that interacts via gestures showed that a robot learning from a human through social interaction is an attainable goal.

Our previous work has used mobility gestures for social interaction [4], and has shown that laser leg tracking was highly effective in social interaction using simple mobility

gestures. Nicolescu and Matarić demonstrated that, given a task framework, a robot can learn in relatively few iterations and with little direct reinforcement complex tasks [5]. The system learned the task by generalizing from demonstrations, and was corrected by shaping individual subtasks that were done improperly.

3. EXPERIMENT DESIGN



Figure 1: The mobile robot used in the experiments

The task we used for our experiment is a memory task similar to the game "Simon." In our version, the robot teacher presents a sequence of colored targets (e.g., RED, GREEN, YELLOW, BLUE) for the human user to traverse in the specified order. The task begins with a sequence of three colors. After the user successfully performs the three-color ordered trajectory by visiting each of the colored targets in order, the robot adds three more colors to the sequence for the user to learn and follow. The robot keeps adding items to the sequence until the user fails to remember, as determined by sustained repeated errors in the performed sequence.

The task is repeatable, since the color sequence can be randomized and the task relies on memory more than learning of a specific concept, and the time it takes to perform each individual task element, i.e., walk over to a specific color target, is about 2-3 seconds, long enough for the robot to sense and correct a user's mistake. The traversal behavior (going from one goal to another) is easily and accurately observable by the robot. Together, these constitute a task domain that is both learnable for the user (and whose difficulty can be adjusted to keep it interesting) and shapable for the robot.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

HRI'06, March 2-3, 2006, Salt Lake City, Utah, USA.

Copyright 2006 ACM 1-59593-294-1/06/0003 ...\$5.00.



Figure 2: The arena used in the experiments

3.1 Reinforcement and Shaping

The demonstration phase in our current implementation involves the robot verbally stating the color sequence for the user. The human user then attempts to execute the same sequence of targets.

During the user’s execution of the memorized path, robot-human shaping can be done by observing the behavior of the user and providing appropriate reinforcement along the way, thereby promoting fast task learning. Positive reinforcement is given when the user attains a partial goal, i.e., one of the colored targets, in the appropriate place in the sequence. At that time the robot provides verbal approval by saying “good” or “right on.” When the robot observes an incorrect action on the part of the user (i.e., having gone to the incorrect target), it indicates the error verbally, by saying statements to the effect of: “you’re wrong”, “whoops”, “try again”, and “that isn’t right.”

When the robot senses that the user is about to make a mistake, indicated by the user’s movement toward an incorrect goal, or a lack of movement, it attempts to interrupt the user and signal what the correct behavior should be. The robot uses a verbal cue, “ahem”, followed by pointing its camera and “gazing” at the correct goal, thus indicating to the user that a mistake is about to be made.

3.2 Behaviors and Observations

We determine the destination of the observed person by using a Bayesian filter. The direction the tracked person is moving is recorded in world coordinates over time, and the probability of that bearing given a particular goal is fed into the filter. When confidence of one target over the others is attained, the filter returns a target goal.

The robot sensed the intended goal of the user by observing the direction that the user was moving. The pan-tilt-zoom camera is invariably interpreted by human users as the “eyes and head” of the robot. When the camera is pointing at an object, human observers interpret it as the robot “looking” at that object. The robot can observe the intentions of the user through the person tracking discussed above, and the user can observe the intentions of the robot from observing its gaze.

We used the AT&T text-to-speech system [2] for speech expression, which creates an audio recording simulating human speech. The result was an understandable while still mechanical-sounding voice.

For this task, the robot correctly identified the current goal that the user was over 99% of the time, with only one mistake in over 200 observations. The robot was able to intervene correctly when the user was moving to the wrong goal 75% (30 of 40) of the time.

4. EXPERIMENT

This system was designed to observe if the robot’s interventions resulted in better performance in the memory task. Performance is measured by how long a string of colors the subject could remember and repeat.

We conducted a series of tests with 10 subjects. Each was tested with and without shaping. The control condition involved the subject repeating a color sequence recited by the robot, and being informed of the robot if the sequence was correct when completed, or interrupting when an incorrect color was chosen. The shaping condition involved the robot interrupting the subject if the robot observed the subject moving to an incorrect goal.

5. RESULTS

During the control case, the subject was able to remember a sequence an average of 8(SD=2.16) colors long. When repeated for the shaping exercise, the subject was able to get an average of 11.1(SD=3.18) colors long. With the robot’s assistance through shaping interventions, an improvement of 39% was achieved. These results are related to working memory experiments conducted on different types of tasks.

6. CONTINUING WORK

Our continuing work includes exploring the nature of robot shaping of human behavior by expanding to more complex tasks that include interaction with people through gestures or specific exercises, and problem solving in the real world.

We are interested in exploring the effect of perceived robot personality and form on the performance of a human learning in robot-human teaching contexts.

7. ACKNOWLEDGMENTS

This work was supported by the USC Provost’s Center for Interdisciplinary Research and the Okawa Foundation.

8. REFERENCES

- [1] C. Breazeal, G. Hoffman, and A. Lockerd. Teaching and working with robots as a collaboration. In *Proc of the Int Joint Conf on Autonomous Agents and Multiagent Systems*, volume 3, pages 1030–1037, New York, NY, July 2004.
- [2] M. Bulut, S. S. Narayanan, and A. K. Syrdal. Expressive speech synthesis using a concatenative synthesizer. In *Int. Conference on Spoken Language Processing*, pages 1265–1268, Denver, CO, September 2002.
- [3] D. Feil-Seifer and M. Matarić. Defining socially assistive robotics. In *Proc of the Int Conf on Rehabilitation Robotics*, pages 465–468, Chicago, IL, Jul 2005.
- [4] D. Feil-Seifer and M. Matarić. A multi-modal approach to selective interaction in assistive domains. In *Proc of the Int Workshop on Robot and Human Communication (RO-MAN)*, pages 416–421, Nashville, TN, Aug 2005.
- [5] M. N. Nicolescu and M. J. Matarić. Natural methods for robot task learning: Instructive demonstrations, generalization and practice. In *Proc of the Int Joint Conf on Autonomous Agents and Multi-Agent Systems*, pages 241–248, Melbourne, Australia, Jul 2003.