

# Towards Autonomous Wireless Backbone Deployment in Highly-Obstructed Environments

Marcos A. M. Vieira, Ramesh Govindan and Gaurav S. Sukhatme

**Abstract**—In a setting that lacks infrastructure *e.g.*, urban search and rescue, a team of networked mobile robots can provide a communication substrate by acting as routers in a wireless mesh network. We study the problem of determining the minimum number of robots, and how to position them, so that all clients using the resulting robotic network are connected and all network links satisfy minimum rate requirements. The key challenge we address is that in an environment with obstacles the strength of a wireless link is a non-monotonic function of the distance between the link end-points. Our approach to the problem is based on virtual potential fields. Clients and environmental obstacles are modeled as virtual charged particles exerting virtual forces on the robots. We validate our algorithm with physical robots in an indoor environment and demonstrate that we are able to get feasible solutions.

## I. INTRODUCTION

With advances in processor, sensing, actuation, and radio technology, it is possible to put together interesting systems using off-the-shelf components. A good example is a robot with navigation capabilities, and an on-board processor with wireless communication capabilities. Among its many uses, such robots can be used as *routers* in a mobile wireless mesh network. In such a network, a team of robotic routers can provide a communication substrate for a collection of clients.

Such a mobile wireless mesh network might find application in various settings which are either without infrastructure or infrastructure-impooverished *e.g.*, military operations, urban search and rescue, disaster response and fire-fighting [1].

In this paper, we consider a specific problem that arises naturally in such settings: how and where to deploy a wireless robotic-router based backbone to ensure pairwise connectivity between a given set of clients.

Our work focuses on highly-obstructed environments.

**Contributions.** To overcome this challenge, we develop an algorithm called *Potential Field-based Wireless Backbone Deployment* (or, PFWD, for short). In PFWD, a team of mother ship robots, each starting from one of the clients,

deploys into a given environment, guided by attractive and repulsive forces in a potential field, thus forming a wireless mesh network. We define an attractive force between each client and each robot, where the force is derived from an indoor radio propagation model. The attractive forces are designed to ensure that the mother ship robots converge to the point where the maximum wireless signal attenuation from each client to the mother ship robots is minimized. To our knowledge, this is a novel use of potential fields, which have previously been based on physical distance. Repulsive forces are used for obstacle avoidance and to avoid local minima. As each mother ship moves, it deploys robots along the way in order to maintain the following invariant: there must exist a connected multi-hop path from each mother ship to the client where it started from. Robot deployment uses a feature of the 802.11a/b/g/n standard, which specifies the minimum radio signal required to establish a link of a given rate. Eventually, the mother ships converge at the point of lowest potential, ensuring that each client is connected to every other client at the specified link rate.

We validate and evaluate PFWD using simulation and experimentation. We present an experimental validation of PFWD in realistic scenario and measure an important network metric: minimum TCP flow between clients.

## II. PROBLEM FORMULATION




Fig. 1. A sketch of the problem and a solution over a floorplan

We wish to deploy a team of  $N$  mobile robots to connect  $C$  clients in a given environment. We define the problem as follows:

**Input:** Given  $C$  clients, their positions, a map  $E$  of the environment, and a performance specification in the form of a minimum data link rate constraint of  $D$  Mbps.

The environment map  $E$  includes a complete floorplan, with obstacles. The obstacles specify where it is not possible to deploy robots. Some obstacles (*e.g.*, walls) might also

M. Vieira is with Universidade Federal de Minas Gerais, Belo Horizonte-MG, Brasil mmvieira@dcc.ufmg.edu

R. Govindan and G. Sukhatme are with Department of Computer Science, University of Southern California, Los Angeles, CA, USA ramesh, gaurav@usc.edu

This material is based in part upon work supported in part by the National Science Foundation under Grants No. CCF-0820230, CNS-0540420, CNS-0325875 and CCR-0120778 and a gift from the Okawa Foundation. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation. The work was also supported in part by DARPA contract N00014-08-1-0693/489.

affect radio propagation. Modern wireless standards operate at different transfer rates or speeds. For example, the popular 802.11a standard can operate at 8 different rates, ranging from 6 Mbps to 54 Mbps. The highest rate at which a wireless link between two nodes can operate depends upon their distance (among other factors): intuitively, the closer the nodes are, the higher their achievable operating rate.

**Objective:** Deploy the minimum number of mobile robots to form a (possibly) multi-hop wireless backbone that ensures connectivity between each pair of clients, while ensuring that each wireless link can operate at least  $D$  Mbps, and without violating restrictions imposed by the environment (e.g., robots cannot be placed in occupied areas).

Our problem specification requires that, in the resulting network backbone, the minimum rate at which each link in the network must operate is  $D$  Mbps.

**Output:** The position  $p_{r_i}$  for each robot  $r_i$  in the environment  $E$ . Figure 1 shows an instance of the problem, and a viable solution. The map  $E$  contains obstacles and walls. Clients are represented by laptops, and robots by an image of the iRobot Create. The position of the robots is the output of the algorithm. The black lines show the links in the network backbone. Each client can connect to at least one robot; between each pair of clients, there exists a multi-hop network path. Observe that some inter-robot links traverse walls and other obstacles: while robot placement is constrained by walls and obstacles, inter-robot communication is not. Indeed, this last point indicates why this problem is very challenging.

### III. SOLUTION OVERVIEW

In this section, we present an overview of our approach. As discussed in Section II, radio propagation in obstructed environments forms a non-metric space (e.g., the triangle equality does not hold for radio signal strength in an environment with obstacles). To understand this better, we first describe models of radio propagation both in free-space and in the presence of obstacles, and then explain how radio propagation in the presence of obstacles forms a non-metric space.

We have designed an algorithm called *Potential Field-based Wireless Backbone Deployment* (or, PFWD, for short). This algorithm uses virtual potential fields. Potential Fields provide virtual forces similar to an electric field. They provide attractive and repulsive virtual forces to cause robots to move from a high potential state to a low potential state similar to the way in which a charged particle would move in an electrostatic field.

We use potential fields in two ways. First, an attractive force determined by the radio propagation model guides robot placement to ensure connectivity. This is a departure from previous work, which has used physical distance to set the attractive force. Second, we use repulsive forces in the potential field for obstacle avoidance, a more traditional use of potential fields.

Finally, to guarantee the data rate constraint, we use a feature of the 802.11a wireless standard specification. This standard specifies the minimum signal-to-noise ratio (SNR)

required to decode transmissions, at each allowable data rate. PFWD leverages this in a novel manner as follows: It uses an indoor radio propagation model to predict SNR between robots or between a robot and a client, and guides the deployment of robots such that the SNR between backbone links is sufficient to ensure the data-rate constraint.

#### A. Radio Model

While wireless propagation is known to be hard to characterize in general, there has been a significant line of research attempting to fit models to radio propagation characteristics observed in different environments [2], [3]. The attenuation factor (AF) model [2] is a commonly-used radio propagation model for indoor environments. It is an in-building site-specific propagation model that includes the effect of building materials and building structures.

This model decomposes the path loss into three factors: attenuations from propagation through an office or hallway, propagation through a wall, and propagation through a floor. Specifically, the model is described by an equation that calculates the multiplicative factor  $PL(d)$  by which signal power is attenuated (hence the *attenuation factor* or AF model) between a transmitter and a receiver whose physical distance is  $d$ . The model is approximate, since it models only the direct (or primary) path between transmitter and receiver, and not any reflected paths. As such, it does not incorporate multi-path fading: in prior work, we have discussed techniques to improve network throughput using robotic motion to mitigate multi-path fading [4]. The AF model is reported [2] to provide loss within 4dB of the actual path loss.

According to the AF model,  $PL(d)$  is given by:

$$PL(d) = PL(d_0) + 10n \log \left( \frac{d}{d_0} \right) + WL * w + FAF(f) \quad (1)$$

where  $n$  is the *path loss exponent* and indicates the rate at which the attenuation increases with distance.  $d_0$  is a reference distance. The variable  $WL$  represents attenuation through a single wall, and the term  $WL * w$  represents the attenuation factor for communication traversing  $w$  walls. (This is a simplified model: in practice, because of material and construction differences, different walls have different attenuation factors, which we discuss later).  $FAF$  is a function that represents a floor attenuation factor for a specified number  $f$  of floors; generally,  $FAF$  is monotonically increasing.

An important component of this model is the increasing attenuation as a function of distance: in general, the wireless signal attenuates logarithmically with distance. Moreover, note that the model has several parameters, which need to be empirically measured for a given environment  $E$ : the path loss exponent  $n$ , and, the attenuation factor  $W$  (or more generally, an attenuation factor  $W_i$  for each distinct wall type  $l$ ). In lieu of measurement, one can obtain nominal values for these parameters from standard texts [2].

#### B. Attenuation in the Presence of Walls

In unobstructed environments (i.e., in the absence of walls/floors), the attenuation factor satisfies the triangle inequality (or, equivalently, defines a metric space). To see

why this is so, consider two points  $x$  and  $z$  and two rays: one directly from  $x$  to  $z$  and another reflected from a point  $y$  (Figure 2). In the absence of walls, the attenuation of the reflected ray will *always* be higher than that of the direct ray. However, if there is a wall between  $x$  and  $z$ , the direct ray may be attenuated *more* than the reflected ray, depending on the value of  $W$ , resulting in a non-metric space.




Fig. 2. Triangle inequality does not hold for path loss




Fig. 3. The space partition of wireless signals might result in disjointed cells

Previous work on robotic deployment has assumed that wireless attenuation is a metric space (*i.e.*, they have ignored walls and obstacles), and these solutions do not generalize to our setting. To understand this, consider Figure 3 which depicts two wireless transmitters and the result of applying a Voronoi space partition based on the attenuation factor. In the presence of the wall, the Voronoi cells might not be convex and might result in disjoint cells, as shown in the figure. Prior work has deployed robots at the centroid of each Voronoi cell, but, in our example, this centroid may not even fall within the cell! For this reason, PFWD uses a qualitatively different approach, based on iterative potential fields.

#### IV. THE PFWD ALGORITHM

In this section, we describe the PFWD algorithm. The algorithm takes as input  $p_{c_j}$ , the position of client  $j$  for  $1 \leq j \leq m$ , an environment map  $E$ , and a data rate constraint  $D$ . The outputs are the  $N$  robot positions  $p_{r_i}$ .

As discussed below, PFWD is an iterative potential field-based approach. In PFWD, a robotic *mother ship* is initially co-located with each client.  $m$  clients imply that our algorithm uses  $m$  mother ships. Each mother ship is then guided by the potential field towards the minimum energy position (we describe the choice of the forces, and the minimum energy position below). As each mother ship moves, it continuously evaluates whether it needs to deploy a robot<sup>1</sup>  $r_i$  (a node in the wireless backbone): if so, it marks the current position as one of the outputs  $p_{r_i}$ . Thus, PFWD has two components: the attractive and repulsive forces that define the potential fields, and the deployment algorithm that determines when robots are deployed by mother ships. We discuss each component in turn.

##### A. Potential Fields in PFWD

Potential Fields are used to represent goals and constraints. In PFWD, they provide virtual forces to guide the mother

<sup>1</sup>For the purposes of this paper, the deployed object need not be a robot, but can be a wireless router. However, we envision [4] that the deployed wireless backbone will need to be iteratively repositioned, using local motions in order to mitigate fading due to multi-path effects.

ships to move from a high potential state (near each client) to a low potential state similar to the way in which a charged particle would move in an electrostatic field. The design of these forces in order to achieve the deployment objective is a novel contribution of this paper.

In PFWD, there are two kinds of forces. The first,  $\mathbf{F}_{\text{client}}$ , is an attractive force defined between each mother ship and *every* client, and causes the mother ships to converge to a low potential state. The second,  $\mathbf{F}_{\text{obstacle}}$  causes mother ship robots to be repelled by obstacles. By using a combination of these forces each robot minimizes its energy by moving to a “rendezvous” point, trying to minimize the travelled distance while avoiding obstacles. Mathematically, the forces are expressed as follows. Consider a network of  $M$  mother ships  $\langle s_1, s_2, \dots, s_m \rangle$  and  $M$  clients  $\langle c_1, c_2, \dots, c_m \rangle$ . Let the position of the  $j$ -th client be denoted by  $p_{c_j}$  and that of the  $i$ -th mother ship, at any instant, by  $p_{s_i}$ . For position  $p_i$ , we use  $(x_i, y_i)$  to denote its coordinates on a 2-D plane.

A force has two components: an orientation and a magnitude. For a mother ship robots  $i$  and a client  $j$ , the orientation of the force is given by equation 2.

$$\theta = \text{atan2}(y_j - y_i, x_j - x_i) \quad (2)$$

The function  $\text{atan2}$  is a variant of the trigonometric arctangent function, but accounts for the quadrant in which  $\theta$  lies.

For a mother ship  $s_i$  and a client  $c_j$ , the magnitude of the force is given by:

$$F_{\text{client}} = K_{\text{client}} * (PL(d_0) + 10n \log \left( \frac{d_{i,j}}{d_0} \right) + WL * w + FAF(f)) \quad (3)$$

where  $d_{i,j}$  is the distance between  $s_i$  and  $c_j$ ,  $w$  is the number of walls and  $f$  the number of floors between  $s_i$  and  $c_j$ , and  $K_{\text{client}}$  is a force constant, and other terms are as defined in 1. Thus, *the attractive force is proportional to the signal attenuation* (even in the presence of obstacles): collectively, these attractive forces ensure that each mother ship moves to a point where the maximum path loss between a mother ship and every other client is minimized.

PFWD also defines repulsive forces between mother ship and obstacles. Obstacles represent 2 dimensional objects within which no robots can be deployed. The repulsive forces ensure obstacle avoidance. However, a repulsive force alone may result in a local minimum for concave objects [5], so we also include a tangential force that moves the mother ship along the side of the object.

Thus, between each mother ship and an obstacle  $o$ , we define a force  $\mathbf{F}(\mathbf{i}, \mathbf{o})$  that consists of two components: a repulsive force that is perpendicular to the obstacle and a tangential force to avoid local minima.

We make one subtle distinction between obstacles and walls. In our model, walls are 1D objects which merely attenuate wireless signals, but can be navigated around by a robot. Since PFWD is designed as an off-line tool to determine positions of robot deployment, we let mother ships pass through walls following radio propagation. If we were using PFWD online for deployment we would have to fix this with a navigation algorithm that causes the robot

to navigate around the wall. Finally, we note that there is no force between the mother ship robots. The second component of PFWD ensures inter-robot placement distance, as described below.

Thus, mother ship robot  $i$  will experience a net force of

$$\mathbf{F}_i = \sum_{\forall \text{ clients } j} \mathbf{F}(\mathbf{i}, \mathbf{j}) + \sum_{\forall \text{ obstacles } o} \mathbf{F}(\mathbf{i}, \mathbf{o}) \quad (4)$$

Following basic physics, the equation of motion for node  $i$  is:

$$\ddot{\mathbf{x}}_i(\mathbf{t}) = \left( \frac{\mathbf{F}_i - \nu \dot{\mathbf{x}}_i}{m} \right) \quad (5)$$

where  $\ddot{\mathbf{x}}$  denotes the acceleration of the robot,  $m$  is the virtual mass of the robot which is assumed to be 1, and  $\dot{\mathbf{x}}_i$  is the robot velocity. The second term on the right hand side of this equation has a *viscous friction* term in which  $\nu$  is the viscosity coefficient. The viscous friction is a damping factor that has the effect of removing energy from the system: the total energy decreases monotonically over time, and since the potential energy of the system is bounded, this ensures that the system will ultimately reach a state of static equilibrium (*i.e.*, a state in which all mother ship robots have stopped moving).

Equation 5 can be used to map the virtual force onto a velocity control vector. We can calculate the next position by, for every time step  $\Delta t$ , calculating:

- 1) Total Force  $\mathbf{F}_i$
- 2) Velocity as  $\dot{\mathbf{x}}_{t+1} = \dot{\mathbf{x}}_t + \frac{(\mathbf{F}_i - \nu \dot{\mathbf{x}}_t)}{m} \Delta t$
- 3) Position to  $x_{t+1} = x_t + \dot{\mathbf{x}}_{t+1} \Delta t$

Using these equations, each mother ship determines where to move, iteratively, until it converges to the minimum potential energy point.

In summary, these forces ensure that each mother ship moves to a point where the maximum path loss between a mother ship and every other client is minimized, while avoiding obstacles. However, the correctness and performance of PFWD depends upon the choices of its parameters. The algorithm is not guaranteed to converge for all choices of parameters, for a given environment  $E$ . For example, a choice of a high  $\nu$  can cause the system to run out of energy prematurely. Similarly, if the obstacle tangential force is not strong enough, a mother ship may not be able to exit a local optimum. Currently, PFWD users can overcome this by using conservative parameters (low  $\nu$  values or high tangential forces) at the expense of convergence time. But if the local optimum problem persists for a challenging environment  $E$ , one approach is to apply complimentary techniques. One such technique is the Harmonic Potential Fields [5], which uses harmonic functions to build an artificial Potential Field free of local minima. Understanding optimal parameter settings for a given environment  $E$  is left to future work.

### B. The Deployment Decision in PFWD

The second component of PFWD determines where the mother ship will deploy robots. To do this, it uses an algorithm that tests the following invariant for each mother ship  $s_i$ :  $s_i$  always has a multi-hop path from itself through

already-deployed robots (possibly deployed by other mother ships) to its “own” client  $c_i$ , and that each hop in the path can sustain a link rate of  $D$ . When  $s_i$  is at a position where this invariant is violated, it backtracks to a previous position where the invariant holds, and deploys the robot there. The movement of each mother ship is guided by the forces described above.

The pseudo-code for the algorithm is in Algorithm 1.

---

#### Algorithm 1 Deployment Algorithm

---

```

1: while (has energy to move) and (not all clients connected?) do
2:   if Is  $D$  Mbps connected with last deployed robot ? then
3:     Move using Potential Fields
4:   else
5:     Move one step back
6:     Deploy Robot
7:     update adjacency matrix of deployed robots
8:   end if
9: end while

```

---

To check whether the mother ship is connected to its client, it needs to know the positions of all robots that have been deployed until now, and each deployed robot’s neighbors. For this, the algorithm maintains an adjacency matrix. It uses a graph connectivity algorithm to determine if connectivity exists between itself and the client. (In a practical system, the mother ship can use a decentralized routing protocol [6] to determine the existence of connectivity). When all the clients converge to the minimum potential point, by construction *there will exist a multi-hop path between every pair of clients.*

Rates	6	9	12	18	24	36	48	54
SNR	6.02	7.78	9.03	10.79	17.04	18.80	24.05	24.56

TABLE I  
NECESSARY SNR (DB) FOR REQUIRED DATA RATE (MBPS)

To determine when a mother ship is “disconnected” from its client, and also to ensure the link data rate constraint  $D$ , PFWD relies on a feature of modern standard radios, which can operate on different data rates. Wireless standards, such as those for 802.11a, define the minimum SNR needed to decode a transmission at a given rate. The table I [7], [8] presents these SNR values. Given a mother ship’s location, PFWD uses 1 to determine the SNR between itself and its neighboring deployed robots. When the SNR to every neighbor is below the minimum SNR required to maintain the target rate  $D$ , the mother ship considers itself to be disconnected, backtracks and deploys a robot. Thus, at each step of PFWD, each robot is guaranteed to have at least one link capable of operating at  $D$  Mbps.

In a practical deployment system, a mother ship can directly measure the SNR and maintain the above guarantee.

Finally, our description of PFWD has implicitly assumed that each mother ship initially has an infinite number of robots. Thus, PFWD may deploy more robots than the user may have at her disposal. To obtain a deployment requiring no more than the number of available robots, the user can try lower  $D$  values: a lower value of  $D$  generally results in “longer” wireless links, and therefore fewer robots.

## V. EVALUATION

In this section, we validate and evaluate PFWD using analysis, simulation, and experimentation.

### A. Validating the PFWD Tool

We have implemented the PFWD algorithm and outputs robot positions  $p_{r_i}$ . We illustrate the outputs of PFWD for some canonical topologies (Figures 4(a)- 4(d)). In the figures, the black dots represent the clients, the green dots (lighter) the deployed robots and the red dots (gray) the mother ships. The blue lines represent the trajectory of the mother ships, and the green circles represent the communication range in free space.




Figure 4(a) shows the result for three clients. Notice how the mother ships converge on the centroid of the triangle, and the robots are deployed at regular intervals along the medians, as expected. Figure 4(b) shows the output when the configuration is the same as figure 4(a) but with the addition of a wall. Since a wall attenuates radio signals, robots are deployed more frequently on the segment crossing the wall.

Figure 4(c) depicts the simulation output for four clients, where the mother ships again converge at the centroid of the figure. In this case, too, we can show the deployment to be optimal. Finally, Figure 4(d) depicts the case where there is an obstacle in the environment. We can see impact of the force  $\mathbf{F}_{\text{obstacles}}$ : the mother ships move counter-clockwise around the periphery of the obstacle until the viscous damping causes the system to lose energy and the algorithm converges.

### B. Validating the PFWD Algorithm

To validate PFWD experimentally, we employ the following methodology:

- We take an indoor office environment  $E$  and measure the parameters for the AF model.
- We then feed  $E$  and several client configurations to the PFWD tool.
- For each output from PFWD, we deploy robots at positions corresponding to the clients, and at the backbone robot positions suggested by PFWD.
- We then measure TCP and UDP data throughput between each pair of clients.

Our platform consists of an iRobot Create. For sensing and control, we developed a Create driver for Player [9].

Figure 5(a) shows the PFWD tool output for an environment with three clients, with a data rate constraint of 54 Mbps. PFWD suggests a backbone consisting of three robots (Figure 5(b)) and we measure the traffic throughput between

the clients shown. Figure 5(c) shows the TCP and UDP throughputs obtained for the suggested configuration. In each case, notice that each flow receives non-zero throughput: this is encouraging, indicating that our radio model, together with the data rate model and the potential fields approach work well together to deliver a *feasible* network.




Fig. 6. Minimum Throughput Flow for different configurations

We have conducted a more rigorous evaluation of PFWD. For each of 3 and 4 clients, we computed the output of PFWD for 3 different client locations and two different data rate requirements (54 Mbps and 36 Mbps). In all, this resulted in 12 different instances. For each instance, we deployed the requisite number of robots at the suggested locations, then measured all possible end-to-end TCP throughput between clients. For a given instance, we calculated the minimum TCP throughput among all pairwise TCP measurements. Figure 6 shows the minimum pairwise TCP throughput between the 4 sets, sorted by instance. We can see that the minimum pairwise throughput is greater than zero in every instance. Even with paths of 5 hops, we were able to get a connected network (the 4Clients-54 set): this is significant because TCP throughput is known to degrade dramatically and often fail in multi-hop network paths.

Thus, we conclude that there is strong evidence to suggest that PFWD can yield feasible network configurations in indoor settings.

### C. Comparing Against Alternative Approaches

Algorithm				
PFWD	7	9	11	13
MST	10	12	14	14

TABLE II

COMPARISON OF NECESSARY NUMBER OF ROBOTS

To compare the number of deployed robots using an alternative plausible strategy, we calculate the Minimum Spanning Tree using the set of clients as nodes. Table II compares the necessary number of robots to provide a connected topology for clients placed at the nodes on different regular polygons. In each case, note that PFWD deploys fewer robots.

We also compare the quality of PFWD's solution against a random placement strategy. We deploy the same number of




Fig. 5. Environment with 3 clients and 3 robots

robots as PFWD suggests, but randomly within the convex hull. Figure 5(d) shows the minimum data rate link obtained from 100 random deployments for the client configuration shown in Figure 5(b). None of the 100 random deployments is able to satisfy the minimum link rate requirement of 54 Mbps, while PFWD is able to find a feasible configuration.

## VI. RELATED WORK

In [10], a similar problem is presented. Their work is designed for an unknown environment so, unfortunately, the proposed algorithm has no guarantees that the network will be connected. We, on the other hand, take advantage of a known global map to guarantee connectivity.

Our work is inspired by prior Potential Fields work on area coverage. Howard et al. [11] present a distributed and scalable approach to deploy robots. Each node is repelled by both obstacles and by other nodes, thereby forcing the network to spread itself throughout the environment. Poduri et al. [12] extended the previous work to maximize the area coverage with the additional constraint that each node has at least  $K$  neighbors. In contrast to area coverage, PFWD focuses on guaranteeing connectivity between clients.

Tekdas and Isler [13] presents a game theoretic approach: the problem is modeled as a pursuit-evasion game, with the goal of finding the shortest escape trajectory. Our problem setting is qualitatively different, that of deploying a team of robots to form a backbone for a collection of static clients.

Hsieh et al. [14] study a complementary problem to ours, that of driving a team of robots to specific locations along a parameterized curve while maintaining point-to-point communication links. Their approach receives as input specific goal positions for each robot in the team; in PFWD, the goal positions are the output of the system.

Finally, our problem bears superficial resemblance to the facility location problem in operations research. Unfortunately, this formulation does not apply to our multi-hop network, since we also need to consider the connectivity between facilities (robots in our case).

## VII. CONCLUSION

We showed that a mobile wireless network can take advantage of mobility from networked robots. We described an algorithm based on virtual potential fields to deploy a wireless backbone in a non-metric space. We verified that the radio propagation model follows the log-distance path

model in our testbed. We evaluated our system with physical robots in an indoor environment and demonstrated that we are able to get feasible solutions.

## REFERENCES

- [1] H. Liu, J. Li, Z. Xie, S. Lin, K. Whitehouse, J. A. Stankovic, and D. Siu, "Automatic and robust breadcrumb system deployment for indoor firefighter applications," in *Proceedings of the 8th international conference on Mobile systems, applications, and services*. New York, NY, USA: ACM, 2010, pp. 21–34.
- [2] T. Rappaport, *Wireless Communications: Principles and Practice*. Upper Saddle River, NJ, USA: Prentice Hall PTR, 2001.
- [3] "Propagation data and prediction models for the planning of indoor communication systems and local area networks in the frequency range 900 MHz to 100 GHz," in *International Telecommunication Union, ITU-R Recommendation*, 1997.
- [4] M. A. M. Vieira, "The Interplay between Networks and Robotics: Networked Robots and Robotic Routers," Ph.D. dissertation, University of Southern California, US, 2010.
- [5] J.-O. Kim and P. Khosla, "Real-Time Obstacle Avoidance Using Harmonic Potential Functions," *IEEE Transactions on Robotics and Automation*, June 1992.
- [6] T. Clausen and P. Jacquet, "RFC3626: Optimized Link State Routing Protocol (OLSR)," United States, 2003.
- [7] "IEEE Std. 802.11a-1999, Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications, IEEE," 1999.
- [8] J. Yee and H. Pezeshki-Esfahani, "Understanding wireless LAN performance trade-offs," *CommsDesign.com*, Nov 2002.
- [9] B. P. Gerkey, R. T. Vaughan, K. Støy, A. Howard, G. S. Sukhatme, and M. J. Mataric, "Most Valuable Player: a Robot Device Server for Distributed Control," in *Intl. Conf. On Intelligent Robots and Systems*, vol. 3, Maui, HI, USA, 2001, pp. 1226–1231.
- [10] H. C. H. Chiu, B. Ryu, H. Zhu, P. Szekeley, R. Maheswaran, C. Rogers, A. Galstyan, B. Salemi, M. Rubenstein, and W.-M. Shen, "Tentacles: self-configuring robotic radio networks in unknown environments," in *IROS'09: Proceedings of the 2009 IEEE/RSJ international conference on Intelligent robots and systems*. Piscataway, NJ, USA: IEEE Press, 2009, pp. 1383–1388.
- [11] A. Howard, M. J. Mataric, and G. S. Sukhatme, "Mobile Sensor Network Deployment using Potential Fields: A Distributed, Scalable Solution to the Area Coverage Problem," in *Proceedings of the International Symposium on Distributed Autonomous Robotic Systems*, 2002, pp. 299–308.
- [12] S. Poduri and G. S. Sukhatme, "Constrained Coverage for Mobile Sensor Networks," in *In IEEE International Conference on Robotics and Automation*, 2004, pp. 165–172.
- [13] O. Tekdas and V. Isler, "Robotic Routers," in *Proc. IEEE Int. Conf. on Robotics and Automation*, 2008.
- [14] M. A. Hsieh, A. Cowley, V. Kumar, and C. J. Taylor, "Towards the deployment of a mobile robot network with end-to-end performance guarantees," in *Proceedings of the 2006 IEEE International Conference on Robotics and Automation*, 2006, pp. 2085–2091.