

Distributed Combinatorial Rigidity Control in Multi-Agent Networks

Ryan K. Williams, Andrea Gasparri, Attilio Priolo and Gaurav S. Sukhatme

Abstract—In this paper, we propose a distributed control law to maintain the combinatorial rigidity of a multi-agent system in the plane, when interaction is proximity-limited. Motivated by the generic properties of rigidity as a function of the underlying network graph, local link addition and deletion rules are proposed that preserve combinatorial rigidity through agent mobility. Specifically, redundancy of network links over local subgraphs allows the determination of topological transitions that preserve rigidity. It is shown that local redundancy of a network link is sufficient for global redundancy, and thus applying minimal communication, and computation that scales like $O(n^2)$, the generic topological rigidity of a network can be preserved. An analysis of the properties of the local rigidity rule, rigidity maintenance guarantees, and a simple consensus-based extension are explored, while Monte Carlo simulations illustrate complexity results. Finally, a dynamic agent simulation demonstrates the distributed rigidity maintenance controller in a realistic coordination scenario.

I. INTRODUCTION

Distributed systems of intelligent coordinating agents have become the focus of significant interest, particularly in control and robotics communities, with motivation rooted in fundamental advantages of failure robustness, adaptability, scalability, and efficiency when compared to single-agent counterparts. Applications exploiting multi-agent systems are highly varied and impactful, with examples including adaptive sampling [1], [2], distributed monitoring [3], [4], and surveillance [5], [6].

The primary focus of this work lies in controlling the *rigidity* property of a mobile multi-agent network. Rigidity is an under-investigated topic in multi-agent control that has deep implications particularly in collective motion. For example, in formation control rigidity plays a vital role in guaranteeing stabilization using only relative inter-agent information [7]–[9]. In localization tasks where a global frame of reference is unavailable, rigidity is also of fundamental importance as it is necessary in allowing relative sensing agents to establish common frames [10]–[12].

The study of rigidity has a rich history in various areas of engineering, science, and mathematics [13]–[15]. In terms of rigidity control in multi-agent networks, [16] and [9] exploit combinatorial rigidity to define node-wise operations for switching between formations while preserving rigidity, however without explicit agent control. In [17] a centralized method for constructing optimal combinatorially rigid graphs based on the Henneberg construction [18] is explored, from a

static framework perspective. Finally, the most closely related work to this paper is [19], where a continuous gradient control for maintaining infinitesimal rigidity (as opposed to combinatorial rigidity) is proposed that applies the notion of a rigidity eigenvalue, although without decentralization.

In contrast to previous work, we propose a *distributed* rigidity controller that preserves the *combinatorial* rigidity of a *dynamic* network topology in the plane, through mobility control. Our motivation rests on the notion that rigidity is a *generic* property of a network topology [20], eliminating the need to examine all possible realizations. Thus we require rigidity control only during *transitions* in network topology, resulting in a solution that yields guaranteed generic rigidity (with direct applicability, as in [10]), infinitesimal rigidity in *almost all* realizations [20], and by-construction complexity and robustness advantages due to non-continuous operation. Local link addition and deletion rules are proposed that preserve combinatorial rigidity by exploiting neighbor-wise communication. The pebble game algorithm [15] for testing generic rigidity is applied to local subgraphs in the region of link propositions to determine changes in topology that preserve rigidity. It is shown that local redundancy of a link in some subgraph is sufficient for redundancy in the entire network, and thus applying minimal communication, and computation that scales like $O(n^2)$, the generic topological rigidity of a network can be preserved. The discrimination of links in the network is accomplished in a distributed manner by applying the framework proposed by Williams and Sukhatme in [21], termed *constrained spatial interaction*. An analysis of the properties of the local rigidity rule, rigidity maintenance guarantees, and a simple consensus-based extension are explored, while Monte Carlo simulations illustrate complexity results. Finally a dynamic agent simulation demonstrates the distributed rigidity maintenance controller in a realistic coordination scenario.

The outline of the paper is as follows. In Section II we provide preliminary materials including an overview of rigidity theory and constrained spatial interaction. A local rule for maintaining the graph rigidity is studied in Section III, together with a consensus-based extension. Simulation results are provided in Section IV, and concluding remarks are stated in Section V.

II. PRELIMINARIES

Consider a system of n mobile agents operating over \mathbb{R}^m each having single integrator dynamics

$$\dot{x}_i(t) = u_i(t) \quad (1)$$

where $x_i(t), u_i(t) \in \mathbb{R}^m$ are the position and the velocity control input for an agent $i \in \mathcal{I} = \{1, \dots, n\}$ at time $t \in \mathbb{R}_+$, respectively. The aggregate position of the system is then given

R. K. Williams and G. S. Sukhatme are with the Departments of Electrical Engineering and Computer Science at the University of Southern California, Los Angeles, CA 90089 USA (email: rkwillia@usc.edu; gaurav@usc.edu).

A. Gasparri and A. Priolo are with the Department of Engineering, University of Roma Tre, Via della Vasca Navale, 79, Roma, 00146, Italy (email: gasparri@dia.uniroma3.it; priolo@dia.uniroma3.it).




Fig. 1. Example graphs demonstrating several embodiments of rigidity, where dashed links indicate edges that have been added to form new networks. Notice that all links in graphs (a), (b), and (d) are independent, while edge (v_1, v_3) in (c) is redundant.

by $\mathbf{x} = [x_1, \dots, x_n]^T \in \mathbb{R}^{mn}$, the stacked vector of agent positions. We consider here the case of planar operation, $m = 2$, noting that an extension to $m > 2$ is the focus of future work. It is assumed that the agents can intercommunicate in a proximity-limited way, inducing interactions (topology) of a time varying nature. Specifically, letting $d_{ij} \triangleq \|x_{ij}\| \triangleq \|x_i - x_j\|$ denote the distance between agents i and j , and (i, j) a link between connected agents, the spatial neighborhood of each agent is partitioned by defining concentric radii $\rho_2 > \rho_1 > \rho_0$ as in Fig. 2, where we refer to ρ_2, ρ_1, ρ_0 as the *interaction*, *connection*, and *collision avoidance* radii, respectively. The radii introduce a *hysteresis* in interaction by assuming that links (i, j) are established only after $d_{ij} \leq \rho_1$, with link loss then occurring when $d_{ij} > \rho_2$, generating the annulus of $\rho_2 - \rho_1$ where *decisions* on link additions and deletions are made.

The assumed spatial interaction model is formalized by the *undirected dynamic graph*, $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, with vertices (nodes) $\mathcal{V} = \{v_1, \dots, v_n\}$ indexed by \mathcal{I} (the agents), and edges $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{V}$ such that $(i, j) \in \mathcal{E} \Leftrightarrow (\|x_{ij}\| \leq \rho_2) \wedge \sigma_{ij}(t)$, with switching signals [22]:

$$\sigma_{ij}(t^+) = \begin{cases} 0, & (i, j) \notin \mathcal{E} \wedge \|x_{ij}\| > \rho_1 \\ 1, & \text{otherwise} \end{cases} \quad (2)$$

where $(i, i) \notin \mathcal{E}$ (no self-loops) and $(i, j) \in \mathcal{E} \Leftrightarrow (j, i) \in \mathcal{E}$ (symmetry) hold for all $i, j \in \mathcal{V}$. Again, notice that the spatial interaction radii, coupled with switching action (2) induces a *lag* in transitions of \mathcal{G} , a feature that is vital in constructing mobility that respects topological constraints (Section II-B). Nodes with $(i, j) \in \mathcal{E}$ are called *neighbors* and the neighbor set for an agent i is denoted $\mathcal{N}_i = \{j \in \mathcal{V} \mid (i, j) \in \mathcal{E}\}$. Finally, the *framework*, $\mathbb{F}_{\mathbf{x}} \triangleq (\mathcal{G}, p)$, associated with the multi-agent system is the graph \mathcal{G} together with the mapping $p(i) = x_i, \forall i \in \mathcal{I}$, which assigns to each node the position of the associated agent in \mathbb{R}^m , that is a *realization* of graph \mathcal{G} .

A. Rigidity Theory

We are interested specifically in the *rigidity* properties of the framework $\mathbb{F}_{\mathbf{x}}$, that is whether or not the framework can flex while preserving edge lengths. To begin, consider an *infinitesimal motion* of the framework $\mathbb{F}_{\mathbf{x}}$, that is the assignment of velocities u_i to the vertices v_i of \mathcal{G} such that edge lengths d_{ij} are preserved. A *finite flexing* of $\mathbb{F}_{\mathbf{x}}$ is a family of realizations of \mathcal{G} , parameterized by t , such that x_i is differentiable for all

t and the edge lengths (or inter-agent distances) d_{ij} remain constant for every $(i, j) \in \mathcal{E}$. Translations and rotations of \mathbb{R}^m clearly preserve edge lengths and are referred to as *trivial* finite flexings. If the framework $\mathbb{F}_{\mathbf{x}}$ has infinitesimal motions that are only trivial flexings it is called *infinitesimally rigid*. Otherwise, the framework is *infinitesimally flexible*.

In determining and controlling the rigidity of the framework $\mathbb{F}_{\mathbf{x}}$ over time, one could continuously check infinitesimal rigidity and take suitable action towards preservation, as is explored in [19]. However, in [20] it is shown that almost all realizations of \mathcal{G} are either infinitesimally rigid or flexible, indicating that rigidity can be approached *generically*, by examining the underlying graph \mathcal{G} . Such a combinatorial characterization of graph rigidity in the plane was first described by Laman in [23], and is summarized as follows¹:

Theorem 2.1 (Graph rigidity, [23]): A graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ over realizations in \mathbb{R}^2 having $n \geq 2$ nodes is rigid if and only if there exists a subset $\bar{\mathcal{E}} \subseteq \mathcal{E}$ consisting of $|\bar{\mathcal{E}}| = 2n - 3$ edges satisfying the property that for any non-empty subset $\hat{\mathcal{E}} \subseteq \bar{\mathcal{E}}$, we have $|\hat{\mathcal{E}}| \leq 2k - 3$, where k is the number of nodes in \mathcal{V} that are endpoints of $(i, j) \in \hat{\mathcal{E}}$. We call the graph $\bar{\mathcal{G}} = (\mathcal{V}, \bar{\mathcal{E}})$ a *Laman subgraph* of \mathcal{G} .

It follows from Theorem 2.1 that any rigid graph in the plane must then have $|\mathcal{E}| \geq 2n - 3$ edges, where equality holds for *minimally rigid* graphs. Notice that Laman's theorem places restrictions on the network edges, thus we must only evaluate the Laman conditions during transitions in \mathcal{G} . When compared to continuum methods such as [19], exploiting Theorem 2.1 in rigidity control yields a fundamentally more efficient and robust solution, as continuous computation and communication resources are not required for implementation. Such insights motivate the problem investigated in this work:

Problem 1 (Graph rigidity control): Given an initial rigid² graph $\mathcal{G}(0)$ associated with agents having dynamics (1), design velocity controls $u_i(t)$ such that $\mathcal{G}(t)$ is rigid for all $t > 0$.

In solving Problem 1 we will therefore require knowledge of the impact of each edge on the rigidity of graph \mathcal{G} , which is captured in the notion of edge independence, a direct consequence

¹A full extension of Laman's conditions to higher dimensions is at present an unresolved problem in rigidity theory.

²Such a condition can be relaxed to a connectedness requirement if we assume the agents perform a rendezvous maneuver at system initialization, specifically as the fully connected network is rigid.




Fig. 2. Agent interaction model with radii determining sensing and communication $\|x_{ij}\| \leq \rho_2$, neighbor discernment relative to constraints $\rho_1 < \|x_{ij}\| \leq \rho_2$, link establishment $\|x_{ik}\| \leq \rho_1$, and collision avoidance $\|x_{ij}\| \leq \rho_0$.

of Theorem 2.1:

Definition 2.1 (Edge independence, [15]): An edge (i, j) of a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ is *independent* if and only if removing (i, j) from \mathcal{E} makes graph \mathcal{G} non-rigid. Otherwise, (i, j) is called *redundant*. In terms of the Laman conditions, we have that the edges $(i, j) \in \mathcal{E}$ are independent in \mathbb{R}^2 if and only if no subgraph $\bar{\mathcal{G}} = (\bar{\mathcal{V}}, \bar{\mathcal{E}})$ has $|\bar{\mathcal{E}}| > 2|\bar{\mathcal{V}}| - 3$.

The above conditions imply that all rigid graphs have $2n - 3$ independent edges, precisely members of a Laman subgraph (see Fig. 1 for the various embodiments of rigidity). The solution to Problem 1 is now apparent: we simply disallow transitions (switches) in \mathcal{G} that correspond to the removal of independent links, implying the preservation of graph rigidity.

B. Constrained Spatial Interaction

In order to control network links and ultimately graph rigidity, we exploit the *constrained interaction* framework proposed by Williams and Sukhatme in [21], with a brief overview given here for brevity. As opposed to switching links directly to control network topology, the constrained interaction framework acts through hysteresis (2) to regulate links *spatially* with simple application of attraction and repulsion to retain established links or reject new links with respect to topological constraints (c.f. Fig. 2). Define the *discernment region* $\|x_{ij}\| \in (\rho_1, \rho_2]$, where agent i decides relative to system constraints (rigidity) whether agent j is a *candidate* for link addition ($j \notin \mathcal{N}_i$) or deletion ($j \in \mathcal{N}_i$), or if agent j should be attracted (retain $(i, j) \in \mathcal{E}$) or repelled (deny $(i, j) \notin \mathcal{E}$). To execute such decisions with hysteresis, constraint satisfying transitions in topology are determined *preemptively*, i.e. before the change in topology occurs, allowing spatial actions to effectively regulate topology. Specifically, define *predicates* for link addition and deletion, $P_{ij}^a, P_{ij}^d : \mathcal{V} \times \mathcal{V} \rightarrow \{0, 1\}$, activated at ρ_2 and ρ_1 , respectively, that indicate constraint violations if the link (i, j) were allowed to be either created or destroyed, i.e. $\|x_{ij}\|$ transits ρ_1 or ρ_2 . The predicates designate for the i th agent the membership of nearby agents j in *discernment sets*, i.e. link addition and deletion candidate sets $\mathcal{C}_i^a, \mathcal{C}_i^d$, and attraction and




Fig. 3. Discernment set switching for constrained spatial interaction, including signals and switching states for link addition and deletion.

repulsion sets $\mathcal{D}_i^a, \mathcal{D}_i^r$. Link control is then achieved by defining switching dynamics for the discernment sets as depicted by Fig. 3, and choosing control u_i having attractive and repulsive potential fields between members of $\mathcal{D}_i^a, \mathcal{D}_i^r$, respectively. The primary result from [21] can now be stated as follows:

Theorem 2.2 (Constraint satisfaction, [21]): Consider the multi-agent system (1) starting from feasible initial condition $\mathbf{x} \in \mathbb{R}^{mn} \mid \mathbb{P} = 1$, with constraint predicate $\mathbb{P} : \mathcal{G}_n \rightarrow \{0, 1\}$ indicating constraint satisfaction over the space of undirected graphs with n nodes \mathcal{G}_n . Further, assume predicates P_{ij}^a and P_{ij}^d are constructed according to Assumption 1 below, with switching as in Fig. 3. Then the network constraints are satisfied for the trajectories of the closed-loop switching system.

The Lyapunov arguments that underlie Theorem 2.2 leverage a fundamental assumption on the construction of P_{ij}^a and P_{ij}^d , which requires first the notion of a *worst-case graph*, a requirement due to the hysteresis in agent interaction and decisioning:

Definition 2.2 (Worst-case graph): Assume we have a topological constraint \mathbb{P} , and a known space of reachable topologies $\mathcal{G}_C(t)$ in which the network graph must lie, $\mathcal{G}(t) \in \mathcal{G}_C(t) \subset \mathcal{G}_n$, for all $t \geq 0$. A *worst-case graph* relative to constraint \mathbb{P} is a graph $\mathcal{G}_w \in \mathcal{G}_C$ such that $\mathbb{P}(\mathcal{G}_w) = 1 \Rightarrow \mathbb{P}(\mathcal{G}) = 1, \forall \mathcal{G} \in \mathcal{G}_C$.

Finally, the predicates must be constructed along the following restrictions:

Assumption 1 (Preemption, [21], [24]): By construction, transitions in $\mathcal{G}(t)$ due to link addition or deletion occur over only *candidate links*, i.e. new communication links to be added to \mathcal{N}_i must first be members of \mathcal{C}_i^a and deleted links, that is those removed from \mathcal{N}_i , must first be members of \mathcal{C}_i^d as in Fig. 3. Thus, at time t , $\mathcal{C}_i^a(t), \mathcal{C}_i^d(t)$, and $\mathcal{G}(t)$ define the space of reachable network topologies, $\mathcal{G}_C(t) \subset \mathcal{G}_n$. If in \mathcal{G}_C we can identify a worst-case graph, we can choose P_{ij}^a and P_{ij}^d (and by extension, the candidates) such that $\mathbb{P}(\mathcal{G}_w) = 1$, which implies that $\mathbb{P}(\mathcal{G}) = 1, \forall \mathcal{G} \in \mathcal{G}_C$, and the network constraints are satisfied.

The above assumption dictates that predicates P_{ij}^a and P_{ij}^d preemptively determine the worst-case topology with respect to network constraints and proposed link (i, j) , only allowing transitions in \mathcal{G}_w that are constraint satisfying. We now pos-

sess the tools necessary to solve Problem 1, specifically we must equip each agent with predicates P_{ij}^a and P_{ij}^d that satisfy Assumption 1 in terms of a graph rigidity constraint, or equivalently, disallow the removal of independent edges in the graph.

III. PREDICATES FOR RIGIDITY PRESERVATION

Determining an independent edge set over \mathcal{G} is clearly a global operation, yet we aim to define a distributed method with minimal communication load. Thus, we propose here a local method for discerning links in the graph by applying redundancy in *subgraphs* containing discerned links (i, j) . Notice first that the Laman conditions, while elegant, exhibit exponential complexity when applied directly. Conveniently, many works have discovered polynomial time algorithms for combinatorial rigidity; for its simplistic appeal, we cite here the *pebble game* proposed by Jacobs and Hendrickson in [15], which can determine graph rigidity with worst case complexity $O(n^2)$, generating in the case of a rigid graph, a set of $2n - 3$ independent edges through incremental application of Definition 2.1. In determining edge independence, we will therefore assume that each agent can apply efficiently the pebble game algorithm.

Now, we need to understand how local knowledge of edge redundancy influences the rigidity of the entire network graph. The simple case of a minimally rigid graph is a direct consequence of the Laman conditions: in \mathcal{G} there exists a single Laman subgraph, \mathcal{G} itself, and thus in every subgraph $\bar{\mathcal{G}}$ we must have $|\bar{\mathcal{E}}| \leq 2|\bar{\mathcal{V}}| - 3$, requiring that every edge $(i, j) \in \bar{\mathcal{E}}$ is independent in $\bar{\mathcal{G}}$. Thus, in the context of a minimally rigid graph, a local rule exploiting edge redundancy will properly preserve rigidity. We extend such reasoning for the case of non-minimally rigid graphs where there must exist redundant edges. Specifically, we are interested in the global implications of redundant edges identified in local subgraphs:

Lemma 3.1 (Local redundancy): Assume graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ is non-minimally rigid in \mathbb{R}^2 and consider a subgraph $\bar{\mathcal{G}} = (\bar{\mathcal{V}}, \bar{\mathcal{E}}) \subseteq \mathcal{G}$ having an edge $(i, j) \in \bar{\mathcal{E}}$ that is redundant with respect to $\bar{\mathcal{G}}$. Then, there must exist a Laman subgraph $\mathcal{S} = (\mathcal{V}, \mathcal{E}_s) \subset \mathcal{G}$ such that $(i, j) \notin \mathcal{E}_s$.

Proof: This is again a consequence of Theorem 2.1, and we can provide a reasoning that relates well to our application of the pebble game in revealing independent edges. Clearly we have that the order of edge consideration for independence (i.e. applications of Definition 2.1) is irrelevant under the assumption that all edges are considered (specifically as edges in the independent edge set are mutually independent by Definition 2.1). As \mathcal{G} is rigid we know for any such ordering we must find $2n - 3$ independent edges, members of a Laman subgraph $\mathcal{S} = (\mathcal{V}, \mathcal{E}_s) \subset \mathcal{G}$. Denote by $\bar{\mathcal{S}} = (\bar{\mathcal{V}}, \bar{\mathcal{E}}_s)$ a Laman subgraph of $\bar{\mathcal{G}}$, with $(i, j) \notin \bar{\mathcal{E}}_s$ by definition. Now consider a specific independence check ordering, where we begin by considering first every $(k, l) \in \bar{\mathcal{E}}_s$, then every $(k, l) \in \bar{\mathcal{E}} \setminus \bar{\mathcal{E}}_s$, $(k, l) \neq (i, j)$, leaving then (i, j) for the final independence consideration. As we know all $(k, l) \in \bar{\mathcal{E}}_s$ are independent by definition, we have $\bar{\mathcal{E}}_s \subset \bar{\mathcal{E}}_s$ by the consideration ordering. As (i, j) is redundant against $\bar{\mathcal{E}}_s$ it

follows that $(i, j) \notin \mathcal{E}_s$ as then there would exist a subgraph in \mathcal{S} that violates Definition 2.1. Thus, we have identified a Laman subgraph of \mathcal{G} of which (i, j) is not a member, and the result follows³. ■

Equivalently Lemma 3.1 implies that edge (i, j) is redundant with respect to \mathcal{G} and thus the graph $\mathcal{G}_{-e} = (\mathcal{V}, \mathcal{E} - (i, j))$ is rigid. Such a conclusion allows us then to gain insight into the impact of arbitrary links on the rigidity of the graph by inspecting only local subgraphs of our choosing. This is powerful in the context of the constrained interaction framework (Section II-B) as we now can define predicates that preserve independent links in the network (or equivalently, allow the removal of redundant links), and guarantee dynamic rigidity maintenance. First, in order to comply with the predicate construction requirements of Assumption 1, we require a worst-case graph \mathcal{G}_w , with respect to $\mathcal{C}_i^a, \mathcal{C}_i^d$. Consider the following graph

$$\mathcal{G}_w = (\mathcal{V}, \mathcal{E}_w), \quad \mathcal{E}_w \triangleq \{(i, j) \in \mathcal{E} \mid \forall v_i \in \mathcal{V}, v_j \notin \mathcal{C}_i^d\} \quad (3)$$

corresponding to the graph \mathcal{G} with all candidates for deletion removed (as addition candidates are not yet links, such links are also not present in \mathcal{G}_w). Defining function $f_r(\mathcal{G}): \mathcal{G}_n \rightarrow \{0, 1\}$ representing the rigidity of a graph \mathcal{G} , we then have the following result:

Lemma 3.2 (Worst-case rigid graph): Consider a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ with an associated *worst-case* graph $\mathcal{G}_w = (\mathcal{V}, \mathcal{E}_w)$ defined as in (3). It follows that if $f_r(\mathcal{G}_w) = 1$, then $f_r(\mathcal{G}) = 1$ for all $\mathcal{G} \in \mathcal{G}_C$, the space of reachable topologies over $\mathcal{C}_i^a, \mathcal{C}_i^d, \forall i \in \mathcal{I}$.

Proof: Notice that as all deletion candidate links are removed from \mathcal{G}_w , there exist no further edges that can be removed from \mathcal{G} as topological transitions can only occur over candidate links (c.f. Fig. 3). Thus, from \mathcal{G}_w we can construct any $\mathcal{G} \in \mathcal{G}_C$ through link addition, that is we simply add deletion candidates or addition candidates to \mathcal{G}_w to form all possible combinations. Thus, assuming $f_r(\mathcal{G}_w) = 1$ and noting that link addition preserves graph rigidity, it follows that $f_r(\mathcal{G}) = 1, \forall \mathcal{G} \in \mathcal{G}_C$, our desired result. ■

We can now leverage Lemma 3.2 in conjunction with Lemma 3.1 to generate distributed predicates for rigidity preservation. Considering the proposition of the addition or deletion of link $(i, j) \in \mathcal{E}$, we construct a local worst-case subgraph $\mathcal{G}_{ij}^w = (\mathcal{V}_{ij}^w, \mathcal{E}_{ij}^w) \subseteq \mathcal{G}_w \subseteq \mathcal{G}$ as follows:

$$\begin{aligned} \mathcal{V}_{ij}^w &\triangleq \{v_i, v_j\} \cup \mathcal{N}_i^w \cup \{\mathcal{N}_k^w \mid v_k \in \mathcal{N}_i^w\} \\ \mathcal{E}_{ij}^w &\triangleq \{(k, l) \in \mathcal{E} \mid v_k, v_l \in \mathcal{V}_{ij}^w\} \end{aligned} \quad (4)$$

with $\mathcal{N}_k^w \triangleq \{v_l \in \mathcal{N}_k \mid (k, l) \in \mathcal{E}_w\}, \forall k \in \mathcal{I}$, where we refer to agent i as the *discerning agent*, that is the agent to whom the responsibility has been assigned to determine the independence of link (i, j) ⁴. Notice that \mathcal{G}_{ij}^w constitutes 2-hop information from the perspective of agent i , however under the assumption that all agents maintain an updated neighbor

³Notice that the key aspect in this proof is the discovery of a Laman subgraph not containing (i, j) , and thus the purpose of our specific choice of ordering; alternative orderings do not necessarily reveal such information.

⁴Such responsibility can be chosen through simple communication between agents i and j , relative to metrics such as computational capability (in heterogeneous networks), availability, etc.

set, the construction of \mathcal{G}_{ij}^w requires only local communication with $v_k \in \mathcal{N}_i^w$. It turns out that such a local graph construction is necessary to extract information that is meaningful in the global graph scope:

Lemma 3.3 (Local graph construction): For an agent i , the local graph containing neighboring nodes and incident edges possesses *only* independent edges.

Proof: If we consider only \mathcal{N}_i , we generate discernment graphs with $1 + |\mathcal{N}_i|$ nodes and $|\mathcal{N}_i|$ edges, and as rigid graphs must satisfy $|\mathcal{N}_i| > 1$, $\forall i \in \mathcal{I}$, we have $|\mathcal{N}_i| < 2(|\mathcal{N}_i| + 1) - 3$ and by Definition 2.1 all edges are independent⁵. ■

Despite the existence of redundant edges in a network, Lemma 3.3 indicates that a purely local inspection yields no insight into edge redundancy.

We are finally prepared to define our link discernment predicates for dynamic rigidity preservation in the constrained interaction framework. Denoting $f_{red}((i, j), \mathcal{G}) : \mathcal{V} \times \mathcal{V} \rightarrow \{0, 1\}$ as the function indicating the redundancy of a link (i, j) with respect to graph \mathcal{G} , we have link deletion predicate

$$P_{ij}^d \triangleq \neg f_{red}((i, j), \mathcal{G}_{ij}^w) \quad (5)$$

discerning links relative to the local worst-case graphs, and link addition predicate

$$P_{ij}^a \triangleq 0 \quad (6)$$

allowing all link additions as they preserve graph rigidity. Our primary conclusion concerning dynamic graph rigidity preservation can now be stated:

Theorem 3.1 (Rigidity preservation): Consider the multi-agent system defined by dynamics (1), with control inputs driven by the switching behavior depicted in Fig. 3, and starting from a feasible initial condition, where our assumed constraint is $\mathbb{P}(\mathcal{G}) \triangleq f_r(\mathcal{G})$, implying that the initial graph $\mathcal{G}(0)$ is rigid. Further, assume that P_{ij}^a and P_{ij}^d are defined as in (5), (6). Then for all $t > 0$, we have $\mathbb{P}(\mathcal{G}(t)) = 1$ and graph rigidity is maintained.

Proof: Assuming trivially that we have $\mathcal{C}_i^a(0) = \mathcal{C}_i^d(0) = \emptyset$, it follows that $\mathcal{G}_w(0) = \mathcal{G}(0)$ and thus $f_r(\mathcal{G}_w(0)) = 1$. Now, consider the possible transitions in \mathcal{G}_w that can occur due to switching as in Fig. 3. We have two cases to consider, either current members of $j \in \mathcal{C}_i^a, \mathcal{C}_i^d$ are lost due to $d_{ij} > \rho_2$ or $d_{ij} \leq \rho_1$, respectively, or new members $j \in \mathcal{C}_i^a, \mathcal{C}_i^d$ are gained due to $d_{ij} \leq \rho_2$, $P_{ij}^a = 0$ or $d_{ij} > \rho_1$, $P_{ij}^d = 0$, respectively. The first case is trivial as lost members $j \in \mathcal{C}_i^a$ were not members of \mathcal{G}_w and thus no transition occurs, while lost members $j \in \mathcal{C}_i^d$ represent the link (i, j) being added back to \mathcal{G}_w , preserving rigidity. Now, in the second case for new members $j \in \mathcal{C}_i^a$ the link (i, j) is not added to \mathcal{G}_w by definition, and again no transition occurs. Finally, for new members $j \in \mathcal{C}_i^d$, we have $f_{red}((i, j), \mathcal{G}_{ij}^w) = 1$, that is the link (i, j) is redundant with respect to \mathcal{G}_{ij}^w . As $\mathcal{G}_{ij}^w \subseteq \mathcal{G}_w$ it follows from Lemma 3.1 that (i, j) is also redundant with respect to \mathcal{G}_w , implying

⁵Such a conclusion does not imply rigidity maintenance cannot be achieved, instead that rigidity maintenance would degenerate into maintaining all network links.

that the removal of (i, j) from \mathcal{G}_w due to new membership $j \in \mathcal{C}_i^d$ preserves the rigidity of \mathcal{G}_w . Thus, for all possible transitions in \mathcal{G}_w rigidity is preserved and P_{ij}^a, P_{ij}^d abide by the preemptive construction required by Assumption 1. As all conditions of Theorem 2.2 have been satisfied, we can then conclude that $\mathbb{P}(\mathcal{G}(t)) \triangleq f_r(\mathcal{G}(t)) = 1$ for all $t > 0$, our desired result. ■

From the above result we thus arrive at a distributed controller for combinatorial rigidity preservation in mobile networks, when interaction is proximity-limited.

Remark 3.1 (Local rule complexity): The discernment of a link (i, j) requires a single communication message of size $O(n)$, between $O(n)$ neighbors for the discerning agent i . The application of the pebble game by agent i requires $O(n^2)$ operations in the worst-case, with average performance on the order of $O(n^{1.15})$ [15]. Most importantly, as our controller acts over network links and not agent realization, we require communication and computation *only* during proposed transitions in the network topology, *not* continuous operation.

Remark 3.2 (Local rigidity matrix): In determining link redundancy, a rigidity matrix [18] could also be applied in the context of the constrained interaction framework to control graph rigidity. However, we choose the pebble game [15] for the following advantages: improved computational complexity ($O(n^2)$ vs. $O(n^3)$), implications in reusing pebble assignments for future discernments to improve dynamic complexity, and amenability to distributed implementation⁶.

Remark 3.3 (Improved infinitesimal rigidity): Notice that in solving the problem of controlling graph rigidity, we have performed significant effort towards controlling infinitesimal rigidity, except for the guarantee of algebraic independence of the realization, a significantly easier problem (a collinearity condition) [18]. We conjecture that by decoupling topological rigidity and algebraic independence, we can vastly simplify the control of infinitesimal rigidity.

A. Local Conservatism and Extensions

To conclude, we provide a brief discussion of the trade-offs involved in applying a local rigidity control rule, and a consensus-based extension to allow the discernment of links relative to the entire network. In applying deletion predicate (5) over local subgraph \mathcal{G}_{ij}^w , notice that $f_{red}((i, j), \mathcal{G}_{ij}^w)$ is affirmative only when, according to Definition 2.1, there exists some subgraph $\bar{\mathcal{G}}_{ij}^w = (\bar{\mathcal{V}}_{ij}^w, \bar{\mathcal{E}}_{ij}^w) \subseteq \mathcal{G}_{ij}^w$ having $|\bar{\mathcal{E}}_{ij}^w| > 2|\bar{\mathcal{V}}_{ij}^w| - 3$ edges. However, for \mathcal{G}_w rigid, such a condition need not hold in every \mathcal{G}_{ij}^w , leading to scenarios such as that depicted in Fig. 4, in which the local rule can behave conservatively in link deletions⁷. In Fig. 4a we have a non-minimally rigid graph in which edge (v_4, v_5) is redundant by construction. If we then assume that agents v_4 and v_5 move apart, triggering the discernment of (v_4, v_5) for deletion, we obtain the subgraph Fig. 4b against which (v_4, v_5) is checked for redundancy. Clearly in this graph (v_4, v_5) is independent by Definition 2.1 and as we would then have predicate $P_{45}^d = 1$, edge (v_4, v_5) would

⁶We explore such a possibility in our upcoming work [25].

⁷Even in light of such behavior, network rigidity is still maintained.




Fig. 4. An illustration of conservatism in the local redundancy rule. The edge (v_4, v_5) is redundant with respect to graph (a). However, applying the local redundancy check over subgraph (b) suggests (v_4, v_5) is independent (due to non-rigidity), denying link deletion.

become a member of $\mathcal{D}_4^a, \mathcal{D}_5^a$, denying deletion, despite the redundancy of (v_4, v_5) over \mathcal{G}_w . Such conservatism clearly diminishes with increasing connectivity (a claim we bolster in Section IV), due to shrinking network diameter (making a local check effectively global) and the increase in network links and thus possibilities for subgraphs with redundancy. As discussed by Remark 3.1 such conservatism trades off with minimal local communication and computation that scales well in n . Thus in rigid networks with localized redundancy, our proposed rule will uncover edge redundancy without a full network inquiry, becoming conservative only near the boundary of minimal rigidity (confirmed in Section IV).

If there are cases where the conservatism of a local check is undesirable, we can simply expand the checked subgraphs by applying consensus to generate \mathcal{G}_w instead of \mathcal{G}_{ij}^w . For convenience, consider the *adjacency matrix* $A(t) \in \{0, 1\}^{n \times n}$ having symmetric elements $a_{ij}(t) = 1$ if $(i, j) \in \mathcal{E}(t)$ and $a_{ij}(t) = 0$ otherwise. Further, we can collect the candidacy information $j \in \mathcal{C}_i^a, \mathcal{C}_i^d, \forall i, j \in \mathcal{I}$ into matrices $W(t), Y(t) \in \{0, 1\}^{n \times n}$, having elements $w_{ij} = 1$ if $j \in \mathcal{C}_i^a$ and $y_{ij} = 1$ if $j \in \mathcal{C}_i^d$, respectively. Now, inspired by previous work [24], [26], the network can perform the following consensus iteration (per agent i):

$$A_i(t+1) = \vee_{j \in \mathcal{N}_i} (A_i(t) \vee A_j(t)) \quad (7a)$$

$$W_i(t+1) = \vee_{j \in \mathcal{N}_i} (W_i(t) \vee W_j(t)) \quad (7b)$$

$$Y_i(t+1) = \vee_{j \in \mathcal{N}_i} (Y_i(t) \vee Y_j(t)) \quad (7c)$$

where each agent i initializes $A_i(0), W_i(0), Y_i(0)$ with their local knowledge only. Assuming $\mathcal{G}(t)$ is connected⁸, iterations (7) converge in at most $n-1$ steps to $A_i = A(t), W_i = W(t)$, and $Y_i = Y(t)$, that is uniformly to the global topology and candidacy state [26]. Now we can construct \mathcal{G}_w locally for discerning agent i from the matrix $A_w = A_i \oplus Y_i$, where \oplus is the matrix-wise XOR operation, noting that adjacency A_w precisely describes the construction (3). Discernment of the redundancy of link (i, j) can then occur over the entire graph \mathcal{G}_w , eliminating the previously discussed conservative behavior. Of course instead of a single communication with

⁸A simple condition guaranteed by network rigidity.




Fig. 5. Monte Carlo simulations comparing computation and communication complexity versus network size (n) for our proposed local rule and the consensus-based extension.

$O(n)$ neighbors, iterations (7) require $O(n^2)$ communications in the worst case.

IV. SIMULATION RESULTS

In this section, we present simulation results of our proposed graph rigidity controller. First, to verify the technical contributions of Section III, we randomly generated 1000 rigid graphs with $n \in [4, 20]$ uniformly. For each graph, we then applied our local redundancy rule and the consensus-based extension to *every* edge in the graph, determining if an edge could be removed and preserve rigidity, comparing the decision to the known redundancy of each edge. To demonstrate complexity, we compared the average computation time (in milliseconds) for the local rule (5) and the consensus-based extension (7) versus network size n , as depicted in Fig. 5. We see that the local rule fares better in computation (top) as the network size increases, as local checks become less likely to be global (due to increasing network diameter). Further, the local rule vastly outperforms the consensus-based rule in communication as is clear by Fig. 5 (bottom, measured in total inter-agent messages). Overall, in our simulations the local rule and consensus extension exhibited $O(n^{1.007})$ vs. $O(n^{1.065})$ computation scaling, respectively, and $O(n^{0.7212})$ vs. $O(n^{2.022})$ communication scaling, respectively.

To demonstrate how the complexity advantages of the local rule tradeoff with conservative link deletions, we provide the results depicted in Fig. 6. Specifically, we compared the ratio of known redundant edges to those identified by our local rule (i.e. 1 implies least conservative, 0 implies most conservative), to the network *redundancy ratio*, that is $(|\mathcal{E}| - 2n + 3)/(n(n-1)/2 - 2n + 3)$, the ratio of redundant edges to total possible redundant edges (i.e. 1 implies most redundant, 0 implies minimally rigid). We see immediately that near the region of minimally rigid graphs, the local rule becomes conservative in link deletions, as locally




Fig. 6. Monte Carlo simulations demonstrating conservative behavior of the local rigidity rule for link deletions, measuring redundancy versus deleted edges.

redundant subgraphs become less likely. However, such conservatism recovers quickly as network redundancy increases, with complete ignorance to redundant links only occurring very near minimal rigidity. Thus, the local rigidity controller allows topologies with near-optimal redundancy⁹, with complexity that has demonstrated near-linear scaling.

Our final contribution is a coordination simulation that demonstrates the utility of our graph rigidity control. We assume a system of $n = 7$ agents, each applying a standard dispersive control (e.g. $\psi_{ij}^o = 1/\|d_{ij}\|^2$) to force link deletion in the network. When an equilibrium position is reached, the network graph (rigid by control) is used to define a target formation, and the objective is switched to a formation keeping controller (e.g. [27]). As rigidity is a sufficient condition for formation stability, such a composite objective can be seen as *growing* rigid formations, in a dynamic and distributed way (contrasting with the centralized and static methods of [17]). We refer the reader to http://gasparri.dia.uniroma3.it/video/rigidity_cdc_2013.mp4 for a video of the scenario in the Player/Stage environment.

V. CONCLUSIONS AND FUTURE WORK

In this paper we proposed local rules for link addition and deletion that guaranteed the preservation of rigidity of a dynamic network graph through agent mobility. It was proven that local link redundancy is sufficient for global redundancy in preserving graph rigidity, and the tradeoffs of applying a localized rule were explored, together with a simple consensus-based extension. Finally, Monte Carlo analysis and a simulated agent coordination scenario exploiting generic rigidity demonstrated and confirmed our results.

Directions for future work include extensions to global rigidity for further applications in localization, methods for control in $m = 3$ dimensions, and fusing graph rigidity with continuous control of algebraic independence to enhance the current state of infinitesimal rigidity control.

⁹In the sense that a minimally rigid graph is edge optimal.

REFERENCES

- [1] R. K. Williams and G. S. Sukhatme, "Probabilistic Spatial Mapping and Curve Tracking in Distributed Multi-Agent Systems," in *IEEE International Conference on Robotics and Automation*, 2012.
- [2] W. Wu and F. Zhang, "Robust Cooperative Exploration With a Switching Strategy," *Robotics, IEEE Transactions on*, 2012.
- [3] S. L. Smith, M. Schwager, and D. Rus, "Persistent Robotic Tasks: Monitoring and Sweeping in Changing Environments," *Robotics, IEEE Transactions on*, 2012.
- [4] M. Zhong and C. Cassandras, "Distributed Coverage Control and Data Collection With Mobile Sensor Networks," *IEEE Transactions on Automatic Control*, 2011.
- [5] A. Ghaffarkhah and Y. Mostofi, "Communication-aware surveillance in mobile sensor networks," in *American Control Conference*, 2011.
- [6] R. Olfati-Saber and P. Jalalkamali, "Collaborative target tracking using distributed Kalman filtering on mobile sensor networks," in *American Control Conference*, 2011.
- [7] R. Olfati-Saber and R. M. Murray, "Distributed cooperative control of multiple vehicle formations using structural potential functions," in *in IFAC World Congress*, 2002.
- [8] T. Eren, P. N. Belhumeur, B. D. O. Anderson, and A. Morse, "A framework for maintaining formations based on rigidity," in *15th IFAC World Congress*, 2002.
- [9] B. Anderson, C. Yu, B. Fidan, and J. Hendrickx, "Rigid graph control architectures for autonomous formations," *Control Systems, IEEE*, 2008.
- [10] I. Shames, A. N. Bishop, and B. D. O. Anderson, "Analysis of Noisy Bearing-Only Network Localization," *IEEE Transactions on Automatic Control*, 2013.
- [11] M. Franceschetti and A. Gasparri, "Decentralized centroid estimation for multi-agent systems in absence of a common reference frame: A convergence analysis," *IEEE Conference on Decision and Control*, 2012.
- [12] T. Eren, W. Whiteley, and P. N. Belhumeur, "Using Angle of Arrival (Bearing) Information in Network Localization," in *Decision and Control, 2006 45th IEEE Conference on*, 2006.
- [13] L. Asimov and B. Roth, "The rigidity of graphs, II," *Journal of Mathematical Analysis and Applications*, 1979.
- [14] L. Lovasz and Y. Yemini, "On Generic Rigidity in the Plane," *Siam Journal on Algebraic and Discrete Methods*, 1982.
- [15] D. J. Jacobs and B. Hendrickson, "An algorithm for two-dimensional rigidity percolation: the pebble game," *J. Comput. Phys.*, 1997.
- [16] R. Olfati-Saber and R. M. Murray, "Graph rigidity and distributed formation stabilization of multi-vehicle systems," in *IEEE Conference on Decision and Control*, 2002.
- [17] D. Zelazo and F. Allgower, "Growing optimally rigid formations," in *American Control Conference*, 2012.
- [18] T.-S. Tay and W. Whiteley, "Generating Isostatic Frameworks," *Structural Topology*, 1985.
- [19] D. Zelazo, A. Franchi, F. Allgower, H. H. Bulthoff, and P. R. Giordano, "Rigidity Maintenance Control for Multi-Robot Systems," in *Robotics: Science and Systems*, 2012.
- [20] H. Gluck, "Almost all simply connected closed surfaces are rigid," in *Geometric Topology*, 1975.
- [21] R. K. Williams and G. S. Sukhatme, "Constrained Interaction and Coordination in Proximity-Limited Multi-Agent Systems," *IEEE Transactions on Robotics (to appear)*, 2012.
- [22] M. Ji and M. Egerstedt, "Distributed Coordination Control of Multi-agent Systems While Preserving Connectedness," *IEEE Transactions on Robotics*, 2007.
- [23] G. Laman, "On graphs and rigidity of plane skeletal structures," *Journal of Engineering Mathematics*, 1970.
- [24] R. K. Williams and G. S. Sukhatme, "Topology-Constrained Flocking in Locally Interacting Mobile Networks," in *IEEE International Conference on Robotics and Automation (to appear)*, 2013.
- [25] R. K. Williams, A. Gasparri, A. Priolo, and G. S. Sukhatme, "Decentralized Identification of Generic Rigidity in Multi-Robot Systems," in *IEEE/RSJ International Conference on Intelligent Robots and Systems (submitted)*, 2013.
- [26] M. M. Zavlanos and G. J. Pappas, "Distributed Connectivity Control of Mobile Networks," *IEEE Transactions on Robotics*, 2008.
- [27] L. Krick, M. E. Broucke, and B. A. Francis, "Stabilization of infinitesimally rigid formations of multi-robot networks," in *IEEE Conference on Decision and Control*, 2008.