

Autonomous Control of Human-Robot Spacing: A Socially Situated Approach

Ross Mead
University of Southern California
3710 McClintock Ave., RTH 423
Los Angeles, CA 90089-0781
(213)-740-6245
rossmead@usc.edu

Maja J Matarić
University of Southern California
3650 McClintock Ave., OHE 200
Los Angeles, CA 90089-1450
(213)-740-4520
mataric@usc.edu

ABSTRACT

To enable socially situated human-robot interaction, a robot must both understand and control *proxemics*, the social use of space, to employ communication mechanisms analogous to those used by humans. In this work, we investigate speech and gesture production and recognition as a function of social agent spacing during both human-human and human-robot interactions. These models were used to implement an autonomous proxemic robot controller. The controller utilizes a sampling-based method, wherein each sample represents inter-agent pose, as well as agent speech and gesture production and recognition estimates; a particle filter uses these estimates to maximize the performance of both the robot and the human during the interaction. This functional approach yields pose, speech, and gesture estimates consistent with related literature. This work contributes to the understanding of the underlying pre-cultural processes that govern proxemic behavior, and has implications for robust proxemic controllers for robots in complex interactions and environments.

Categories and Subject Descriptors

I.2.9 [Artificial Intelligence]: Robotics – *operator interfaces*.

H.1.2 [Models and Principles]: User/Machine Systems.

General Terms

Algorithms, Design, Experimentation, Human Factors, Theory.

Keywords

Human-robot interaction, proxemics, probabilistic models.

1. INTRODUCTION

To facilitate socially situated human-robot interaction (HRI), a robot must often employ multimodal communication mechanisms analogous to those used by humans: speech production (via speakers), speech recognition (via microphones), gesture production (via physical embodiment), and gesture recognition (via cameras or motion trackers). This research focuses on answering the question: How do speech and gesture influence spatially situated communication between humans and robots in social encounters? Within that question there are several others: How does the pose between a robot and a person affect speech and gesture recognition for each of them? How can a robot adjust its communication mechanisms to maximize human perceptions of its social signals?

Copyright is held by the author/owner(s).

SUI'13, July 20–21, 2013, Los Angeles, California, USA.
ACM 978-1-4503-2141-9/13/07.

In [1], we proposed a probabilistic framework for autonomous human-robot spacing that considered the sensory experience of each agent (human or robot) in a co-present social encounter. In this work, we present the results of a preliminary data collection to formally investigate this framework and model the relationship between spatial, speech, and gesture parameters to develop a socially situated autonomous spatial controller for HRI.

2. APPROACH

We conducted a data collection to inform models of pose, speech, and gesture parameters for humans and robots in our probabilistic framework [1, 2]. This data collection was designed to expose: (1) how people place themselves with respect to each other and a robot; (2) how inter-agent spacing influences human speech and gesture production (output); and (3) how inter-agent spacing influences speech and gesture perception (input) for both humans and robots.

Models resulting from this data collection were implemented as an autonomous spacing controller for a sociable robot. The robot considers (samples) possible interagent poses, estimating how all interacting agents would likely perceive and produce social stimuli (speech and gesture) if the interaction occurred with the robot at that pose—these estimates are maintained in a “particle”. For each sampled pose, the corresponding speech and gesture input/output levels [2] are inferred based on the model as if the interaction were to occur at that pose; the pose is then assigned a weight based on the likelihood (“desirability”) of an interaction actually occurring with these parameters. The pose, speech, and gesture parameters with maximum weight are selected as the robot goal state.

Models and controllers are available in the Social Behavior Library in the USC Interaction Lab ROS repository (<https://code.google.com/p/usc-interaction-software/ros>).

3. REFERENCES

- [1] Mead, R. and Matarić, M.J. 2012. A probabilistic framework for autonomous proxemic control in situated and mobile human-robot interaction. *Proc. of the 7th ACM/IEEE Int'l. Conf. on Human-Robot Interaction*. Boston, MA, 193-194.
- [2] Mead, R. 2012. Space, speech, and gesture in human-robot interaction. *Proc. of the 14th ACM Int'l. Conf. on Multimodal Interaction*. Santa Monica, CA, 333-336.