In *IEEE International Conference on Robotics and Automation (ICRA),*
pages 721--726, Taipei, Taiwan, Sep 2003.

From Local to Global Behavior in Intelligent Self-Assembly

Chris Jones and Maja J. Matarić
Computer Science Department
University of Southern California
941 West 37th Place, Mailcode 0781
Los Angeles, CA 90089-0781
{cvjones|maja}@robotics.usc.edu

Abstract

In this paper we present a method by which to organize the interactions of autonomous assembly agents in Intelligent Self-Assembly (ISA). Each assembly agent has limited and local sensing and local rule-based control. A Transition Rule Set (TRS) Compiler is presented which takes a desired goal structure as input and gives as output a set of rules. When each assembly agent utilizes these rules, the desired goal structure is assembled. We show that the TRS Compiler is scalable, efficient, and is capable of producing rules for a large class of goal structures.

I. Introduction

Manufacturing processes traditionally assemble a desired structure out of atomic components by following a predefined optimal assembly sequence. Such techniques are the mainstay of assembly operations in mass production whereby a robot manipulator is programmed to perform a set of sequential actions, such as picking up and placing a specified atomic component in an exact location on the growing assembly. This method is suitable and proven for well-defined and predictable domains in which a single assembly agent is involved. However, such methods quickly become intractable and infeasible in unpredictable environments, on parallel assembly sequences requiring the coordination of many assembly agents, and on increasingly large and complex structures.

In contrast, self-assembly is the process by which a collection of atomic components autonomously assemble into a coherent final structure. The atomic components are autonomous, have no pre-programmed sequence of actions, can only sense their local environment, and are largely interchangeable, thus they are not pre-assigned to a specific location in the final assembly. The atomic components are selected or designed in such a way as to have unique local interactions with the environment and with other components such that the natural course of these interactions leads to the assembly of a structure. Assembling a structure through self-assembly is advantageous because with an appropriate set of atomic components and associated interactions, they will autonomously, robustly, and efficiently assemble into a desired structure.

For example, the atomic components in a self-assembly system may be a set of well-chosen molecules that, when placed in relative proximity and under the influence of natural forces such as attraction, repulsion, or various chemical properties, etc., interact in such a way that they automatically assemble into a structure. Such techniques are utilized in the assembly of synthetic nanostructures, such as nanowires, nanotubes, and nanosensors. Phenomena such as crystal formation and the morphological processes in biological organisms are further examples of self-assembly found in nature.

Intelligent Self-Assembly (ISA) is a class of self-assembly in which the atomic components, called assembly agents (AA) in ISA, can be equipped with increased computational capabilities. These increased capabilities may be utilized during the assembly process to allow for richer interaction and greater coordination among AAs, and therefore allow the assembly of more complex structures. However, each AA remains an autonomous entity, limited to local sensing, with no pre-programmed action sequence and no pre-assigned location or task in the assembly of the final structure. Depending on the domain of application, AAs may be modules in a self-reconfigurable robot, an individual autonomous construction robot in a group of such robots, or an individual in a group of mobile robots moving into a desired formation.

ISA is an insightful domain when viewed as a problem of spatio-temporal coordination in a large-scale highly distributed system operating in a nonstationary and unpredictable environment. The assembly of any interesting structure requires global coordination over the assembly process in order to successfully assemble the structure in a consistent manner. Furthermore, the assembly process in ISA is inherently sequential, requiring the placement of some components before others, yet there remains significant opportunity to exploit parallelism.

Domains that motivate and are likely to benefit from advances in ISA include distributed reconfiguration algorithms for self-reconfigurable robotics, the construction of physical artifacts by a group of mobile robots, and more generally, ISA will contribute to the understanding of spatio-temporal coordination in large-scale distributed systems.

An important issue in the design of an ISA system is understanding the translation from local interactions among many AAs to the global behavior of the system, in this case, the goal structure assembled. In this paper, we highlight some issues that must be addressed in developing ISA algorithms that can assemble a large class of structures. We present one such algorithm that requires only very simple AAs, each identical, using fully reactive rule-based control, and requiring only limited and local sensing information. The local rules provided to each AA are generated for a desired goal structure with an off-line rule compiler. The presented ISA algorithm is deterministic and allows for the prediction of global behavior (e.g., the structure assembled) from the local interactions among AAs.

The paper is organized as follows. In Section II we provide related work. In Section III we describe our model for use in the study of ISA algorithms and present our algorithm for consistent ISA through the use of a transition rule set compiler. In Section IV we describe and analyze some experimental results, discuss them in Section V, and draw conclusions in Section VI.

II. Related Work

There are a number of contributions to the theory, analysis, and experimentation in self-assembly systems. In Adleman (2000), a mathematical theory of self-assembly with step-counting is proposed, along with related measures for assembly processes in terms of computational complexity. Rothemund & Winfree (2000) and Adleman, Cheng, Goel & Huang (2001) expand this theory and apply it to the simulated assembly and analysis of self-assembled NxN squares. Rothemund (2000) details a physically implemented self-assembly system making use of plastic tiles which bind through surface tension.

Bonabeau, Théraulaz, Arpin & Sardet (1994) use a rule-based self-assembly method similar to the one presented in this paper in the construction of biologically-plausible nest structures similar to those of some wasp species. Bonabeau, Dorigo & Théraulaz (1999) investigates the use of genetic algorithms to generate the rules used in the self-assembly of biologically-plausible structures and explores the relationship between the space of rules and resulting structures.

Since ISA bears close resemblance to reconfiguration in self-reconfigurable robotics, we provide a brief review of work in this area. Kotay, Rus, Vona & McGray (1998), Murata, Kurokawa, Yoshida, Tomita & Kikaji (1998), and Castano & Will (2000) are just a few references that contain descriptions of hardware platforms for self-reconfigurable robots. Centralized reconfiguration planning methods for self-reconfigurable robots are described in Rus & Vona (1999) and Kotay & Rus (1999). Distributed reconfiguration methods are described in Yim, Zhang, Lamping & Mao (2000) and Murata et al. (1998). Støy, Shen & Will (2002) describe a distributed approach to locomotion in modular robots and Butler, Kotay, Rus & Tomita (2002) present a cellular automata inspired algorithm for reconfiguration as regards locomotion.

In the area of construction by physical robots, Wawerla, Sukhatme & Matarić (2002) presents work on the assembly of a linear 2D structure using a group of mobile robots. In Melhuish, Welsby & Edwards (1999) a group of minimalist robots construct defensive walls using biologically-inspired templates.

III. Our Approach to ISA

Our approach to the design of ISA algorithms is based on the generation of appropriate rules, which, when executed by each AA, results in the consistent assembly of a desired goal structure. The rules are generated in an off-line manner using a Transition Rule Set Compiler. Each AA is given the same set of rules returned by the compiler and executes them during the assembly process to determine when and where to connect to the growing structure.

A. A Model for Intelligent Self-Assembly

Our model for the investigation of ISA in simulation consists of a 2D square lattice world populated with a set of unit square AAs. Although the work presented in this paper is all done in a 2D lattice, the extension to a 3D lattice is straightforward and is currently being implemented. The neighbors of any given lattice square are defined as the set of the four adjacent squares to the North, South, East, and West. The growth of a desired goal structure occurs by the connecting of AAs around a single, initial AA called the Seed.

An AA is defined by a state value and a lookup table of transition rules called the Transition Rule Set (TRS). AAs may connect to neighboring AAs as dictated by the TRS. Each transition rule specifies two pieces of information: 1) a condition upon which an AA will connect to neighboring AAs based on their respective state values and 2) a state value the connecting AA will transition to if this condition is met. A transition rule whose condition is met is said to be active. The Seed and any connected AAs remain stationary and may not disconnect once connected. All other AAs randomly move about the lattice, and, when a transition rule becomes active, will connect to all neighboring AAs and change their state value to that given in the active transition rule.

Furthermore, unconnected AAs may move to any unoccupied adjacent lattice square – no more than one AA may occupy a given lattice square at a time. All AAs are oriented in the same direction with no rotation allowed, and AAs act in an asynchronous manner with no global timing signals. Because connected AAs remain stationary, in our approach sub-assemblies of multiple AAs cannot be separately assembled and later connected to the growing goal structure.

B. Transition Rule Sets

The steps by which assembly proceeds are not fully constrained. The goal structure may be assembled in any of a large set of valid assembly processes with the geometry of the goal structure defining any necessary constraints on the assembly process. The problem of designing appropriate local interactions among AAs to result in the assembly of a goal structure while adhering to all required constraints is the fundamental investigation of this paper. Using the ISA Model described in Section III-A, interactions among AAs are dictated by the TRS identical for all AAs.

A TRS that results in the successful assembly of the goal structure is said to be *consistent*. A consistent TRS must satisfy two points. First, it must not be ambiguous by having the possibility of multiple, contradictory transition rules being simultaneously active at any location on the growing structure at any time during the assembly process. Second, the TRS must enforce any required spatio-temporal constraints present in the assembly process. Figure 1b visualizes the consequences of an inconsistent TRS that does not enforce proper spatio-temporal constraints during the assembly of a 5x5 solid square goal structure as shown in Figure 1a. In this case, the TRS allows the assembly of the frame of the square before the interior is complete, thereby making the successful completion of the goal structure impossible.



Fig. 1. a) Desired 5x5 solid square structure. The Seed is labeled with an S. b) Possible situation resulting from an inconsistent TRS.

Furthermore, it is desirable for the TRS to allow for as much parallelism in the assembly process as possible, thereby making full use of the inherent parallel nature of the distributed system of AAs. It is also desirable, but not necessary in all cases, to use a minimal number of unique state values. Since observation requires the sensing of neighbor state values, an excessively large number of unique state values that must be distinguishable could, in some cases, become prohibitive to implement in a physical system relying on limited sensing capabilities. These desired features of parallelism in the assembly process and a minimal number of unique state values are motivated by the time and program complexity metrics defined in Rothemund & Winfree (2000) and Adleman et al. (2001) for measuring the complexity of a self-assembly system.

C. Transition Rule Set Compiler

In this section, we present the Transition Rule Set Compiler (TRS Compiler), which takes as input a desired goal structure and the location of the Seed in the goal structure and gives as output a consistent TRS. The TRS Compiler is capable of producing a consistent TRS for a large class of structures.



Fig. 2. Division of Sectors as relative to the Seed. The Seed is labeled with an S.

Sector	Required Neighbors	Sector	Required Neighbors
1	■ × ■	2	× ■ ■
3	■ × ■	4	■ ■ ×
5	■ ×	6	× ■
7	× ■	8	■ ×

TABLE I

NEIGHBORS REQUIRED FOR BINDING IN EACH SECTOR. "X" DENOTES THE POTENTIAL CONNECTING SITE.

The TRS Compiler is a procedure by which to generate and organize the local interactions among AAs in order to achieve the desired global behavior. It enforces spatio-temporal constraints in the assembly process by defining, for all locations in the desired goal structure, which of its neighbors must already be connected for an AA to be legally connected at that location. To determine this, the goal structure is split up into 8 sectors relative to the Seed, as shown in Figure 2. The neighbor AAs that must be present for connection in each sector are shown in Table I. A transition rule that allows an AA to connect at a structure location when all the required neighbors, as dictated by the sector, are not connected is an inconsistent transition rule. Ambiguity in the TRS is prevented by verifying that for any potential state of the assembly process there is no situation in which more than one transition rule is active at any given location.

The process by which we generate a consistent TRS proceeds as follows. Taking an assembled goal structure, we assign each AA in the structure an identical state value, say of 1. Next, a transition rule is generated for each AA and added to the TRS. This TRS, containing a transition rule for the addition of each AA, is then checked for consistency by verifying that for all locations `X` in the structure and at all stages of assembly, only a single transition rule is active. All locations `Y` on the periphery of the goal structure are also checked to verify that no transition rules are active at those locations. This check of peripheral locations assures the assembly process is terminal at the goal structure. For all locations in `X` with multiple transition rules active and locations in `Y` with any transition rules active, the state value of a neighbor AA for each of these locations is assigned a single, unique state value not previously present in the structure. Changing the neighboring AAs state value to a unique value guarantees that no other transition rule will be active at this location. This process of generating the TRS, verifying its consistency, and updating any inconsistent locations, is repeated until a consistent TRS is built.

IV. Experiments and Analysis

In this section we show the application of the TRS Compiler on a set of desired goal structures and analyze the resulting TRSs. All structures reported on are shown with a picture of the goal structure with the seed AA highlighted with an `S`, the number of AAs in the goal structure, the number of unique state values used during assembly, and the minimum number of assembly steps needed to assembly the goal structure. The number of assembly steps is computed as follows. Starting with only the seed AA, each assembly step consists of synchronously connecting an AA at all locations that activate a transition rule. This process is repeated until the goal structure is completely assembled. It should be noted that the number of assembly steps does not directly represent the actual time needed to assemble the goal structure, rather it is a useful metric to measure the efficiency of the generated assembly process.

A set of goal structures are shown in Figure 3 and their analysis is shown in Table II.



Fig. 3. a) Simple goal structure. The full TRS for this structure is shown in Table III. b) An 8x8 square goal structure. c) A large, complex goal structure containing holes.

Structure	# AAs in Structure	Unique States	Assembly Steps
a	12	5	4
b	64	26	14
c	245	165	18

TABLE II
ANALYSIS OF STRUCTURES SHOWN IN FIGURE 3.

The TRS returned by the TRS Compiler for the goal structure shown in Figure 3a is shown in Table III. This is a very simple structure and is meant to show the relationship between the TRS and the goal structure. For example, the assembly process begins with only the Seed. At this point, the transition rules 2, 6, 7, and 10 may be activated at the appropriate locations. If it happens that an AA connects to the East of the Seed with transition rule 7, and then changes its state value to 1, then the potentially active transition rules would be 2, 6, 10, and 8. This continues until the structure is complete, noting that the completed goal structure is terminal as there are no further periphery locations that will activate a transition rule. This example also illustrates how the assembly process may proceed in many different directions in parallel and may be assembled in different ways from run to run.

The scalability of the TRS Compiler is demonstrated by its capacity to handle large goal structures, for example those shown in Figure 3b and 3c. The goal structure in Figure 3c demonstrates the TRS Compiler is capable of handling structures of complex geometry.

Simulations of the assembly of the structures presented in this paper, as well as additional structures, along with the full TRSs used can be found on the Internet at `http://robotics.usc.edu/~cvjones/sa-web.html`.

TR	Condition (N, S, E, W)	Next State
1	(3, X, 3, X)	3
2	(0, X, X, X)	3
3	(1, X, X, 3)	3
4	(3, X, X, 3)	2
5	(X X, X, 2)	4
6	(X, X, 0, X)	3
7	(X, X, X, 0)	1
8	(X, X, X, 1)	3
9	(X, 3, 4, X)	3
10	(X, 0, X, X)	4
11	(X, 1, X, 4)	4

TABLE III
TRS FOR STRUCTURE SHOWN IN FIGURE 3A. A CONDITION OF "X" DENOTES THE STATE VALUE OF THE AA AT THE LOCATION IS IRRELEVANT, THE LOCATION MAY BE OCCUPIED BY ANY AA OR MAY BE EMPTY. THE SEED AA HAS A STATE VALUE OF 0

In the simulations it becomes obvious how the goal structures can be assembled in many different ways, yet the TRS guarantees the structure will be successfully assembled.

V. Discussion

The method of ISA presented in this paper is akin to the class of modular self-reconfigurable robots in which each module moves independently and connects to the main assembly at appropriate locations. There is also a close resemblance to lattice-type self-reconfigurable robots in which all modules remain connected and change shape by moving into positions on a virtual lattice. Our model for ISA and the TRS Compiler are directly applicable to lattice-type self-reconfigurable robots, the only modification being the motions of unconnected AAs need to be constrained to move only on the surface of the main assembly, therby forcing all AAs to remain in a single connected component.

The presented ISA algorithm can also be used for the construction of physical artifacts by a group of mobile robots. In Wawerla et al. (2002), a group of mobile robots constructs linear 2D structures by using colored bricks to, in effect, communicate the current state of construction. The use of colored bricks is synonymous to the use of AA state values in our ISA algorithm. This is an example application where the number of recognizable state values is limited due to the imprecision and low fidelity of the color detection capabilities of the construction robots. This warrants the use of a minimal number of unique state values. At this time, there is no formal understanding of what the minimal number of state values necessary to build an arbitrary goal structure is, although theoretical work in this direction can be found in Rothemund & Winfree (2000). In some applications, such as self-reconfigurable robots, the use of a minimal number of unique state values is not necessary because the detecting of neighbor state values is done via direct communication. In cases such as this, each AA in the goal structure can be assigned a unique state value with no impact on the ISA algorithm. Spatio-temporal control of the assembly process is inherent in the TRS and is not affected by the number of unique state values.

Although the TRS Compiler is capable of generating a consistent TRS for a large class of structures, there are some structures which it cannot handle. These structures are ones where a location in the structure does not have any neighbors in the directions, as defined by the sector, used to generate the transition rule. For example, a structure calling for an AA in sector 5 with no AA immediately to the West of its location cannot be handled by the TRS Compiler. A simple way of dealing with many problems of this class is to move the location of Seed in the structure to a location that alleviates the issue. Another weakness of the TRS Compiler is that it is not directly capable of exploiting symmetry in a goal structure to minimize the number of necessary unique state values.

We would also like to say a few words about the impact of erroneous AA behavior on the assembly of the goal structure. There are two classes of errors that may occur: 1) an AA does not connect at a location where it should have, and 2) an AA connects at an inappropriate location on the structure. The first case could occur if an AA incorrectly senses the state values of its neighbors, and, as a result, the AA does not bind at a location it should have because the appropriate transition rule was not activated. The effects of this error are normally not important as there is a high level of redundancy in the system as all AAs are identical. The second class of errors, where an AA has connected at an inappropriate location, can be more significant because it could disrupt further assembly by preventing future transition rule activations. Some application specific ways to deal with this problem include having the neighbors prevent the AA from erroneously connecting in the first place, having the neighbors eject the erroneously connected AA, or having all connected AAs periodically verify their neighbor's state values in the chance of detecting and correcting past erroneous sensor readings. We are currently investigating the impacting of this type of error on the assembly process.

VI. Conclusions

In this paper we have presented an ISA algorithm that organizes the interactions of AAs through the use of a TRS Compiler. We have shown the TRS Compiler is scalable in that it can generate TRSs for large structures, is efficient in that it can generate consistent TRSs that take advantage of the parallel nature of the distributed AAs, and is capable of producing rules for a large class of goal structures consisting of complex geometry. We have shown how the ISA algorithm can be incorporated into distributed reconfiguration algorithms for self-reconfigurable robots and how it can be used in the construction of physical artifacts by a group of mobile robots.

VII. Acknowledgments

This work is supported in part by DARPA TASK Grant F30602-00-2-0573 and in part by NSF ITR Grant EIA-0121141.

VIII. REFERENCES

Adleman, L. (2000), Toward a mathematical theory of self-assembly, Technical report, Technical Report 00-722, Department of Computer Science, University of Southern California.

Adleman, L., Cheng, Q., Goel, A. & Huang, M.-D. (2001), Running time and program size for self-assembled squares, *in* 'ACM Symposium on Theory of Computing (STOC-01)', pp. 740–748.

Bonabeau, E., Dorigo, M. & Théraulaz, G. (1999), *Swarm Intelligence: From Natural to Artificial Systems*, Oxford University Press.

Bonabeau, E., Théraulaz, G., Arpin, E. & Sardet, E. (1994), The building behavior of lattice swarms, *in* 'Fourth Intl. Conf. on Artificial Life', MIT Press, pp. 307–312.

Butler, Z., Kotay, K., Rus, D. & Tomita, K. (2002), Generic decentralized control for a class of self-reconfigurable robots, *in* 'IEEE Intl. Conf. on Robotics and Automation (ICRA-02)', Washington D.C., USA, pp. 809–816.

Castano, A. & Will, P. (2000), Mechanical design of a module for reconfigurable robots, *in* 'IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS-00)', pp. 2203–2209.

Kotay, K. & Rus, D. (1999), 'Locomotion versatility through self-reconfiguration', *Robotics and Autonomous Systems* **26**, 217–232.

Kotay, K., Rus, D., Vona, M. & McGray, C. (1998), The self-reconfiguring molecule: Design and control algorithms, *in* 'IEEE International Conference on Robotics and Automation (ICRA-98)', pp. 4324–431.

Melhuish, C., Welsby, J. & Edwards, C. (1999), Using templates for defensive wall building with autonomous mobile ant-like robots, *in* 'Towards Intelligent Mobile Robots (TIMR)', Bristol, UK.

Murata, S., Kurokawa, H., Yoshida, E., Tomita, K. & Kikaji, S. (1998), A 3-d self-reconfigurable structure, *in* 'IEEE Intl. Conf. on Robotics and Automation (ICRA-98)', pp. 432–439.

Rothemund, P. (2000), 'Using lateral capillary forces to compute by self-assembly', *Proceedings of the National Academy of Sciences (PNAS)* **97**(3), 984–989.

Rothemund, P. W. K. & Winfree, E. (2000), The program size complexity of self-assembled squares, *in* 'ACM Symposium on Theory of Computing (STOC-00)', Portland, Oregon, USA, pp. 459–468.

Rus, D. & Vona, M. (1999), Self-reconfiguration planning with compressible unit modules, *in* 'IEEE International Conference on Robotics and Automation (ICRA-02)', pp. 2513–2520.

Støy, K., Shen, W.-M. & Will, P. (2002), Global locomotion from local interaction in self-reconfigurable robots, *in* '7th Intl. Conf. on Intelligent Autonomous Systems (IAS-7)', pp. 309–316, Marina del Rey, California, USA.

Wawerla, J., Sukhatme, G. S. & Matarić, M. J. (2002), Collective construction with multiple robots, *in* 'IEEE/RSJ International Conference on Intelligent Robots and Systems, (IROS-02)', September 30 - October 4, 2002, EPFL, Lausanne, Switzerland.

Yim, M., Zhang, Y., Lamping, J. & Mao, E. (2000), 'Distributed control for 3d shape metamorphosis', *Autonomous Robots* **10**(1), 41–56.