Generating Expressive Light Signals for Appearance-Constrained Robots

Elizabeth Cha[1], Naomi T Fitter[1], Yunkyung Kim[2], Terrence Fong[2], and Maja J Matarić[1]

[1] University of Southern California, Los Angeles CA 90089, USA
[2] NASA Ames Research Center, Mountain View CA 94035, USA

Abstract. Our goal is to enable robots to communicate information about their internal state using expressive light signals. Since nonverbal cues are typically given context by a robot's other actions, we combined light signals, varying their color, pattern, and frequency, with robot base motion and investigated the effects of these nonverbal signals on human observers' attribution of certain task-related properties (e.g., urgency and safety) to the robot. The results show that variations in light signal parameters affect human attribution of common notification properties. Using these findings, we present a first step towards systematically generating new light signals that can convey different state-related properties relevant for human-robot interaction, validated in a video-based study.

1 Introduction and Background

Robots are complex machines that require a high degree of expressivity to convey the many facets of their state [3, 4]. Recent work has suggested the use of light signals as a robot communication modality because LEDs are affordable, reliable, salient, and versatile [3, 4, 14, 16]. Modulating light signal parameters, such as color, position, duration, and frequency, can be used to communicate a wide range of state information for appearance-constrained robots [10, 14].

Although light signals have been employed by many devices, there are few universal guidelines or principles to drive their design [10, 14]. As a result, many signals are simplistic and not particularly iconic, requiring humans to learn them by rote [10]. As robots take on different forms and purposes, their signaling needs will continue to grow [4]. Learning new signals will become increasingly difficult, especially as humans reach the limits of their perceptual capability and memory.

The current method of creating specialized signals for each robot requires extensive time and effort from human designers. In contrast, this work aims to enable more automatic generation of light signals by leveraging existing human perceptions that are formed from prior experiences. A greater understanding of these perceptions not only facilitates intuitive signal design but also prevents design inconsistencies in which the robot inadvertently expresses information that conflicts with its communication objectives.

The primary contribution of this work is a exploratory user study investigating the effects of manipulating light signal parameters on a robot's expressiveness. Since robots typically have primary goals involving motion, we coupled

the robot's light signals with base motion to mimic the realistic task-oriented settings that robots will operate in. The goal of this study is to support intuitive signal design and modulation of signal parameters to create a rich set of robot communication behaviors. The gained insights also facilitate the creation of common light signaling conventions across different robot platforms.

We focus primarily on perceptions of functional properties, rather than social or affective ones, as many current robots are used for task-oriented applications. These properties are general communication attributes (e.g., urgency), rather than concrete state information (e.g., low power). As prior work has shown that light signals may be too abstract to iconically represent precise information without additional training or context [10], the scope of this study was to determine the effects of light signal design characteristics on these attributes.

A secondary contribution of this work is the application of the initial study findings to several types of appearance-constrained robots and applications. We propose a model for generating robot light signals for human-robot interaction (HRI) and validated it in a video-based study with four different appearance-constrained robot platforms. As much of current HRI research still takes place in laboratory settings, it is important to understand how robot communication behaviors are affected by the context of these scenarios. This knowledge also facilitates the creation of standard nonverbal signals.

2 Technical Approach

The key insight of this work is that consideration of human users' existing perceptions or biases can be leveraged to design more intuitive light signals for robots. To better understand how the design of these signals affects humans' attribution of desired properties to a robot, we conducted an exploratory video-based user study that varied parameters of a robot's light signal and motion. The signal parameters and measured properties were derived from past works [13, 15].

Since light signaling for robot communication is a nascent area of research, formulating well-informed hypotheses is still challenging. Instead, we explored several signal parameters and measured properties with the goal of building a foundation that will allow for generating light signals more systematically and for hypothesis testing in future research.

2.1 Robot

This study employed a Parrot AR drone, equipped with an array of 80 individually programmable Adafruit Neopixel RGBW LEDs embedded in the robot's outer foam hull and surrounded by white filter sheets for light diffusion (Fig. 1).

2.2 Manipulated Variables

We manipulated the robot's *light signal parameters* (color, pattern, and pattern frequency) [2, 10] and its *base motion parameters* (path and speed) [8, 15, 18]. Fig. 2 shows a table of the resulting conditions.



Fig. 1. The light signal patterns used in the exploratory video-based user study.

Light Signal Parameters: To better understand how existing signals affect human perceptions, we chose to study three common and fundamental light signal parameters: *color*, *pattern*, and *pattern frequency* [2, 10, 15].

1. Color- Color is a common differentiator for light signals on individual devices. Consequently, standards for its usage have emerged in certain fields, especially transportation (e.g., traffic signals). We included five common colors in this study: *green*, *red*, *orange*, *blue*, and *white* [10].
2. Pattern- Past work has investigated light signal patterns on both point light sources and light arrays [2, 10]. We investigated four basic and frequently utilized patterns, as shown in Fig. 1. *Steady* is a static light signal in which all lights in the array are on. *Blink* consists of the entire array turning on and off at a constant frequency. *Beacon* consists of a set of three lights moving across the array [10, 15]. *Wipe* is visually similar to a progress bar in which subsequent lights are turned on to fill the array.
3. Pattern Frequency- Since the steady pattern is static, it does not have a pattern frequency. For the other three patterns above, we varied the frequency or the speed of the pattern repeating itself to be either *slow* or *fast* with the fast condition about four times faster than the slow condition.

Motion Parameters: We manipulated two motion parameters: *path* and *speed*. Although these parameters were inspired by work in HRI and animation, few researchers to date have explored their effects on light signal perception.

1. Motion Path- Motion path is defined as the direction of the robot's base motion and has three levels, *no path*, *approaching*, and *receding*. In the no path condition, the robot hovers at a fixed altitude.
2. Motion Speed- We varied the robot's motion speed to be either *slow* or *fast*. The robot reaches a maximum velocity of $0.5\frac{m}{sec}$ in the fast condition and a maximum velocity of $0.15\frac{m}{sec}$ in the slow condition.



Fig. 2. The variables manipulated in the study: base motion parameters (path, speed) on the left and light signal parameters (color, pattern, pattern frequency) on the top. Cell coloring indicates separate analyses.

2.3 Participant Allocation

We generated a total of 175 video conditions, shown in Fig. 2. Since a fully within-subjects design was infeasible with the high number of conditions, participants were randomly assigned 7 of the video conditions (partially within-subjects), with a total of 18 participants per video condition [18].

We recruited participants using the Amazon Mechanical Turk platform. Participants were located in the United States, were at least 18 years of age, and had an approval rating of at least 95%. A total of 450 participants (48% male and 52% female; M=39.4 years, SD=12.5 years) participated in the study.

2.4 Dependent Measures

To assess how the light and motion parameters affect human attribution of desired task-related properties, we identified 3 dependent measures: *urgency*, *error*, and *difficulty to ignore*. These attributes and their measurement scales are derived from notification systems literature [13]. We used a unipolar, 5-point Likert scale ranging from "Not at all" to "Extremely".

1. Urgency- Urgency is defined as the need for immediate attention. Notification systems and alarm literature often explore how to convey varying levels of urgency in order to elicit appropriate reactions from the user.
2. Error- Since robots are embodied agents that can physically interact with the world, it is important for human safety and task success to consider the degree at which the robot is operating or functioning correctly.
3. Difficulty to Ignore- This property measures the salience of a signal is and is shown to affect the success and speed of eliciting a human response [5].

		Light Signal			Robot Motion		Interaction Effect		
		Color	Pattern	Frequency	Path	Speed	Color, Pattern	Pattern, Frequency	Color, Pattern, Frequency
Notification Attributes	Urgency	✓	✓	✓	✓	✓	✓		
	Error	✓				✓			
	Difficulty to Ignore	✓	✓	✓	✓	✓		✓	

Fig. 3. Analysis **(1)** results: Check marks indicate a significant mean effect for the manipulated variable (column) and dependent measure (row).

3 Results

In this section, we present an overview of the statistical analyses performed on the data gathered in the initial user study. From this data and the results of our analyses, we generated a decision tree for generating robot light signals.

3.1 Analyses

First, we performed a multivariate analysis to confirm that the items used as dependent measures were not highly correlated. Due to the unbalanced nature of study, we performed multiple analyses that examined subsets of our nested data. For each subset of data, we employed a factorial repeated measures analysis of variance (ANOVA). We present highlights of the analyses, primarily analysis **(1)** (Fig. 3) and include results that showed statistical significance, were surprising, or provided other interesting insights. We will refer to each of these analyses shown by the colored boxes in Fig. 2 using the numbers in the figure key.

Urgency: In analysis **(1)**, we found a significant main effect for all of the manipulated variables: light signal color ($F(3, 2159) = 5.24, p < 0.001$), pattern ($F(2, 2159) = 18.1, p < 0.001$), and pattern frequency ($F(1, 2159) = 71.87, p < 0.001$) and motion path ($F(1, 2159) = 9.84, p = 0.002$) and speed ($F(1, 2159) = 68.87, p < 0.001$). We also found an interaction effect between the light signal pattern and its frequency ($F(2, 2159) = 6.64, p = 0.001$).

Color was expected to have a strong effect on urgency, due to its strong usage in transportation. A post hoc analysis using Tukey HSD revealed, however, that only red and green were rated significantly different, with red perceived as the most urgent and green perceived as the least. We found similar results in analyses **(2)** and **(3)**, suggesting that color alone does not convey urgency.

Past research exploring perceptions of urgency in alarm and alert signal design have primarily looked at acoustic properties [1, 9]. We found that varying similar signal characteristics (e.g., blinking vs. beeping cycle frequency) across modalities had the same effects on urgency, as shown in the post hoc analysis for **(1)**; all dynamic patterns were rated as significantly different with blink the most urgent and wipe the least.

As the robot's overall goal is ambiguous in the videos used in the study, we did not expect that its motion path would affect perceptions of urgency. However, approaching motions towards the camera were rated as significantly more urgent than receding motions. This could be due to participants framing

the term urgency relative to themselves. The effect size of the motion path was the smallest ($\eta_p^2 = 0.005$) of our manipulated variables.

For the interaction effect found between the light signal pattern and frequency in analysis **(1)**, a post hoc analysis showed that conditions with blink and beacon patterns at the faster frequency had significantly higher ratings than the other conditions. Conditions with the fast pattern frequency were rated on average higher than those with the slow frequency; within these groups, the blink pattern was rated the most urgent and wipe the least. This suggests that the pattern frequency ($\eta_p^2 = 0.018$) has a stronger effect than the pattern ($\eta_p^2 = 0.035$).

Error: As high urgency scenarios are often associated with off-nominal conditions, such as errors, we expected similar findings for error and urgency. However, we found significant effects for only a subset of the dependent measures. In analysis **(1)**, a significant main effect was found for light signal color ($F(3, 2159) = 5.85, p < 0.001$) and motion speed ($F(1, 2159) = 29.85, p < 0.001$).

We expected that participants would draw on their experiences with colors used to signify error (e.g., red stop signs, emergency stop buttons, alarm lights). A post hoc analysis showed significant differences in the conditions with red and orange lights compared to conditions with green and blue lights. Surprisingly, white light was not found to be significantly different than any other color. As white is often a default light color, these results suggest that participants may have a more neutral or diverse perception towards its usage.

We also found that in the absence of motion (analyses **(3)** and **(4)**) color has no significant effect. This was surprising as static red or orange lights, symbols, and signs are often found in everyday life. As many of these instances combine color with a symbol, sound, or text, people may expect the signal to be less ambiguous when conveying important information such as errors (e.g., stop sign).

Surprisingly, we did not find any effect for signal pattern or frequency. We expected that light patterns with some variation, such as those resembling a police beacon or blinking fire alarm, would have a significant effect. The mean results showed that beacon was the highest rated pattern for error and wipe was the lowest. The fast pattern frequency was also rated higher than the slow.

Difficulty to Ignore: We expected that signals with larger variations in their parameters over time will be more salient. This was confirmed in analysis **(1)**, as we found a significant main effect for light signal pattern ($F(2, 2159) = 9.8, p < 0.001$) and pattern frequency ($F(1, 2159) = 11.26, p = 0.001$). Color was shown only to be significant ($F(3, 2159) = 3.11, p = 0.015$) in analysis **(1)**, indicating the weakness of color without motion or a light signal pattern for salience.

The post hoc analysis revealed that red and green were rated significantly differently than the other colors. Since past work has not shown color alone to have a significant effect on salience [17], this could suggest that participants rated light colors commonly utilized by other signals (e.g., traffic lights) higher. This could be because they are better trained to notice these signals or it could be an effect of utilizing videos rather than in-person interactions.



Fig. 4. The average Likert ratings (including 95% confidence intervals) for the urgency, difficult to ignore, and error measures in analysis **(1)**.

We expected that a higher number of LEDs changing over a set period of time would cause more apparent motion and increase saliency [6]. This was confirmed by the the post hoc analysis for **(1)** which showed that the blink pattern was rated significantly higher than the beacon and wipe patterns. A significant mean effect was also found for pattern frequency, with the faster frequency rated more difficult to ignore.

Both motion parameters, path and speed, were found to have significant effects. We expected that participants would have more difficulty ignoring the approaching motion as the robot moves in the direction of the camera and ends in close proximity. This finding was confirmed, suggesting that motion biases found in prior work [7, 11] also apply to robot motion when a dynamic light signal is present, as shown in analysis **(2)**. We also found that the faster motion was rated as significantly more difficult to ignore.

3.2 Light Signal Design Decision Tree

As a first step towards a more systematic approach for signal design, we propose a decision tree for light signal generation based on common parameters found in notification systems literature [12,13] (Fig. 5). Since the focus of this work is light signal design and motion acts as an implicit cue, only light signal parameters are included in the decision tree.

We employed the ID3 decision tree algorithm for each of the three notification attributes: urgency, error, and difficulty to ignore. The robot attributes were not included in the decision tree as their results were mixed and not as readily related with the signal design parameters used to split the tree.

Signal Design Parameters The decision tree includes two signal design parameters: *information type* and *urgency*. Our study findings suggested that light signals are better suited for conveying broader categories of information. Therefore, the goal of this decision tree is to generate a set of generalizable signals well suited for many HRI scenarios.

The *signal type* is defined as a notification, warning, or error. Notification is defined as information from the robot that may be beneficial for the human. Warnings and errors indicate off-nominal states with errors preventing successful



Fig. 5. A decision tree for light signal generation using the signal parameters investigated in the exploratory user study.

operation of the robot. *Urgency* only had two levels, with the assumption that signals that are not urgent requires less attention from a human observer.

Notification Signal Design: Our study results showed two distinct color groupings: 1) red, orange and 2) green, blue, white. For notifications, we employed blue signals as green was rated more salient than blue or white, and comments from participants indicated that green might inadvertently express a positive state (e.g., operating correctly).

Since non-urgent notification signals are used for information that is not critical to the human or constrained by time, they require low levels of awareness or attention from the human interactor [12, 13]. The steady light pattern was rated the lowest in salience, urgency, and error, making it well suited for non-urgent signals.

Since the wipe pattern was rated the next lowest for salience and error, it was chosen to represent urgent notifications. Although pattern frequency was shown to provide the highest information gain for urgency, the faster frequency increased salience significantly, leading us to choose the low frequency pattern.

Warning Signal Design: Color provided the highest information gain for the error measure with red and orange indicating the highest levels of error. Since orange (or yellow) is often employed for warning signals in other applications, we employed orange signals for the warning signal type.

We also assumed that warnings require a larger level of human attention, suggesting the need for higher saliency signals. We chose the beacon and blink signal patterns, which were rated highest in saliency and error. We chose to employ only the slower pattern frequency for warning signals which are by definition less critical than error signals.

Error Signal Design: As red signals were rated significantly higher for urgency, error, and salience, red was employed for both types of error signals. Similar to the warning signal design, beacon and blink were chosen for their higher ratings of error and saliency. We assumed that all errors require higher levels of human

Fig. 6. The four appearance-constrained robots—the Astrobee, Fetch mobile base, Ohmni telepresence robot, and autonomous car—used in the validation study.

awareness, and consequently, employed only the faster pattern frequency for error signals.

4 Validation Study

We conducted a video-based study validating the decision tree across four HRI contexts. These contexts involve different appearance-constrained, non-humanoid robots (Fig. 6) performing their respective tasks (e.g., autonomous car driving) while interacting with humans. For each robot, we generated videos of three different scenarios in which the robot employs light signals for communication (Fig. 7) and had participants rate the robot and its signals using several measures.

4.1 HRI Contexts

We chose four types of appearance-constrained robots, focusing on platforms and applications already found in the real world (Fig. 6). We added LED arrays to the models of the robots that do not already possess communicative lights.

Free-Flying Robot: We used the NASA Astrobee, a free-flying robot designed to perform tasks on the International Space Station (ISS) and operate in close proximity with human astronauts at all times.

Industrial Mobile Base: We used the Fetch mobile base, a robot that is significantly shorter than adult humans (16 inches tall) and typically employed to transport loads around industrial environments, such as factories and warehouses.

Telepresence Robot: We used an OhmniLabs telepresence robot that is 48 inches tall and designed to provided human operators with the ability face-to-face communication capabilities and mobility in a remote environment for a human operator.

Autonomous Car: We used a Prius model taken from open source ROS repositories, modified with simulated sensors to mimic an autonomous vehicle capable of sensing the environment and navigating without human input.

4.2 Participant Allocation

We recruited 80 participants (67.5% male and 32.5% female, M=34.5 years; SD=11.5 years) using the Amazon Mechanical Turk platform. We used a partially-

Type	Scenario		Signal Type	Urgency
Free-Flying Robot	1	Waiting for new task	Notification (85%)	Not Urgent (90%)
	2	Issue while docking	Warning (55%)	Not Urgent (90%)
	3	Out of control motion	Error (60%)	Urgent (80%)
Industrial Mobile Base	1	Waiting for a person to pass	Notification (80%)	Urgent (10%)*
	2	Robot is physically stuck	Warning (45%)	Urgent (70%)
	3	Overheating	Error (45%)	Urgent (80%)
Telepresence Robot	1	Remote operator logging on	Notification (100%)	Urgent (0%)*
	2	Low battery	Warning (45%)	Urgent (65%)
	3	Loss of connection	Error (45%)	Not Urgent (65%)
Autonomous Car	1	Operating autonomously	Notification (65%)	Not Urgent (80%)
	2	Slowing down for pedestrian	Warning (70%)	Not Urgent (66%)
	3	Sensor damage	Error (65%)	Not Urgent (55%)

Fig. 7. Percentages of correct responses for the forced-choice measures: the asterick indicates a majority of participants chose the incorrect response.

within subjects design; each participant saw all three videos (randomized and counterbalanced) for one robot platform.

4.3 Dependent Measures

1. Description- Participants were asked to describe the light signal and what they believe it indicates. This item was used as a manipulation check for the videos and to check whether participants could infer the precise meanings behind the signals.
2. Signal Type- Participants chose the signal type—"notification," "warning," or "error"—they believed best represented the robot's light signal.
3. Urgency- Participants chose whether they believed the robot's light signal to be urgent or not.
4. Signal Usage- Participants rated on a 5-point Likert scale how helpful they found the robot's light signal in understanding the scenario they observed.

To avoid biasing participants responses, we provided only minimal information about the robot platforms, the simulated environments, and the tasks the robots were performing.

4.4 Analysis

We present the results of the validation experiment, primarily focusing on counts of the forced-choice measures describing the light signals. We refer to the scenarios representing the notification, warning, and error signals for each of the robot platforms by numbers (1-3), as shown in Fig. 7.

Signal Type- The signal type fixed-choice measure was chosen correctly for all scenarios. We found that despite participants choosing the notification signal

type correctly most often, their comments showed they were uncertain about what precise information the robot was trying to notify them of. Although the warning and error scenarios had more mixed results, participants were able to infer the precise cause of the warning and error signals more often in their descriptions of the videos.

Urgency- The urgency fixed-choice measure was chosen correctly for all scenarios, except for those with urgent, notification signals. 90% of participants chose non-urgent for the notification scenarios (1). Comments suggest that participants may never classify notifications as urgent due to their lower criticality.

Signal Usage- For all four robot types, participants rated the error signal most helpful and the notification the least helpful. Since notifications encompass a wider range of information, participants had more trouble inferring what the robot was notifying them of. We also found that participants had more difficulty understanding the scenarios with the Astrobee free-flying robot and the telepresence robot due to their lack of familiarity with these types of robot.

5 Conclusion

Our goal in this work is to enable appearance-constrained robots to communicate information about their state using expressive light signals. First, we conducted an exploratory video-based user study on Amazon Mechanical Turk to identify how variations in certain light signal parameters affect human perception of notification attributes.

The rich set of overall light parameters and the human ratings from the initial exploratory user-study gave us the information needed to generate distinct notification, warning, and error signals using a decision tree. The results of this study are a promising first step for transforming the generation of light signals from a specialized task for individual human designers to an automated and standard process across a multitude of robot platforms.

We conducted a second video-based study validating the light signal decision tree. The results demonstrated that our signal designs were reasonable and illuminated certain distinctions that are difficult for human onlookers. In the future, this work could be further validated by studies in the real world, but the presented studies and findings supply the initial step needed to automatically generate light signals that can convey state-related properties of non-humanoid robots. This work may guide roboticists who are interested in providing appearance-constrained robots the expressive abilities needed to make the world a easier and safer place for humans and robots to coexist.

References

1. G Robert Arrabito, Todd A Mondor, and Kimberley J Kent. Judging the urgency of non-verbal auditory alarms: A case study. *Ergonomics*, 47(8):821–840, 2004.
2. Kim Baraka, Ana Paiva, and Manuela Veloso. Expressive Lights for Revealing Mobile Service Robot State. In *Robot 2015: Second Iberian Robotics Conference*, pages 107–119. Springer, 2015.

3. Kim Baraka, Stephanie Rosenthal, and Manuela Veloso. Enhancing Human Understanding of a Mobile Robots State and Actions using Expressive Lights. In *IEEE International Symposium on Robot and Human Interactive Communication*, pages 652–657. IEEE, 2016.
4. Elizabeth Cha, Yunkyung Kim, Terrence Fong, and Maja J Matarić. A Survey of Nonverbal Signaling Methods for Non-Humanoid Robots. *Foundations and Trends in Robotics*, 2018.
5. Elizabeth Cha and Maja Matarić. Using Nonverbal Signals to Request Help During Human-Robot Collaboration. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5070–5076. IEEE, 2016.
6. T.E. Cohn. Method and apparatus for enhancing visual perception of display lights, warning lights and the like, and of stimuli used in testing for ocular disease, January 20 1998. US Patent 5,710,560.
7. Kerstin Dautenhahn, Michael Walters, Sarah Woods, Kheng Lee Koay, Chrystopher L Nehaniv, A Sisbot, Rachid Alami, and Thierry Siméon. How May I Serve You? A Robot Companion Approaching a Seated Person in a Helping Context. In *ACM/IEEE International Conference on Human-Robot Interaction*, pages 172–179. ACM, 2006.
8. Anca D Dragan, Kenton CT Lee, and Siddhartha S Srinivasa. Legibility and Predictability of Robot Motion. In *ACM/IEEE International Conference on Human-Robot Interaction*, pages 301–308. IEEE, 2013.
9. A Guillaume, C Drake, M Rivenez, L Pellieux, and V Chastres. Perception of urgency and alarm design. In *International Conference on Auditory Display*. Elsevier, 2002.
10. Chris Harrison, John Horstman, Gary Hsieh, and Scott Hudson. Unlocking the Expressivity of Point Lights. In *ACM Conference on Human Factors in Computing Systems*, pages 1683–1692. ACM, 2012.
11. Clifford F Lewis and Michael K McBeath. Bias to experience approaching motion in a three-dimensional virtual environment. *Perception*, 33(3):259–276, 2004.
12. D Scott McCrickard, Christa M Chewar, Jacob P Somervell, and Ali Ndiwalana. A Model for Notification Systems Evaluation-Assessing User Goals for Multitasking Activity. *ACM Transactions on Computer-Human Interaction*, 10(4):312–338, 2003.
13. Zachary Pousman and John Stasko. A Taxonomy of Ambient Information Systems: Four Patterns of Design. In *Working Conference on Advanced Visual Interfaces*, pages 67–74. ACM, 2006.
14. Sichao Song and Seiji Yamada. Effect of expressive lights on human perception and interpretation of functional robot. In *Extended Abstracts of the 2018 CHI Conference on Human Factors in Computing Systems*, page LBW629. ACM, 2018.
15. Daniel Szafir, Bilge Mutlu, and Terry Fong. Communicating Directionality in Flying Robots. In *ACM/IEEE International Conference on Human-Robot Interaction*, pages 19–26. ACM, 2015.
16. Daniel J Szafir. *Human Interaction with Assistive Free-Flying Robots*. PhD thesis, The University of Wisconsin-Madison, 2015.
17. Lauren E Wool, Stanley J Komban, Jens Kremkow, Michael Jansen, Xiaobing Li, Jose-Manuel Alonso, and Qasim Zaidi. Salience of unique hues and implications for color theory. *Journal of Vision*, 15(2):10–10, 2015.
18. Allan Zhou, Dylan Hadfield-Menell, Anusha Nagabandi, and Anca D Dragan. Expressive Robot Motion Timing. In *ACM/IEEE International Conference on Human-Robot Interaction*, pages 22–31. ACM, 2017.