

Nonverbal Signaling for Non-Humanoid Robots During Human-Robot Collaboration

Elizabeth Cha¹, Maja Matarić¹, Terrence Fong²,

¹Department of Computer Science, University of Southern California, Los Angeles, CA 90089

²Intelligent Robotics Group, NASA Ames Research Center, Mountain View, CA 94035
echa@usc.edu, terry.fong@nasa.gov, mataric@usc.edu

Abstract—Non-humanoid robots are becoming increasingly utilized for collaborative tasks across many domains, including industrial and service settings. Collaborative tasks between the human and robot rely on each collaborator’s ability to effectively convey their mental state while accurately estimating and interpreting their partner’s knowledge, intent, and actions. My research focuses on nonverbal communication signals that a non-humanoid robot can utilize during human-robot collaboration. We focus on motion, light and sound as they are commonly used communication channels across many domains and are available on most robot platforms. As a first step towards this goal, I present a completed study exploring how to use a simple multimodal light and sound signal to request help during a collaborative task. We then discuss future work to generate and utilize more complex signals to convey a variety of statuses to improve collaboration.

I. INTRODUCTION

Collaboration requires multiple entities to work together by effectively coordinating their actions to achieve a shared goal [1], [2]. Humans are able to effectively utilize both verbal and nonverbal cues to signal information, such as their knowledge, goals, and intent, to achieve a high degree of coordination [1], [2]. Replicating such signals is challenging for robots as many cues are subtle, unintentional, and utilize modalities or degrees-of-freedom that robots often do not possess (posture, gaze, facial expressions). In my research, I seek to enable non-humanoid robots to utilize commonly available communication channels, such as motion, sound, and light, to generate cues that provide information important to coordinating collaborators’ actions and goals.

Typically non-humanoid robots are goal-driven, only taking action when they have a specified task or goal. Hence, a greater degree of planning is required to not only take into account human collaborators, but to generate the cues necessary for coordination. Much of the subtlety and communicativeness of these cues are lost if the robot simply speaks or uses text to convey this information. This not only increases the cognitive load of the collaborator, it also makes the collaboration less fluid and efficient. To overcome this challenge and create signals which are both informative, intuitive, and easy to learn, we take inspiration from work in human-computer interaction, human factors, and psychophysics.

In this paper, we present two separate projects that enable a robot to convey important aspects of its mental status to better inform its human collaborators. This allows the human collaborator to not only take the best action for the collaboration, but



Fig. 1: A participant responds to the robot’s multimodal signal utilizing light and sound for requesting help during a collaborative meal order task.

also to better understand and therefore, accept the robot as a partner. In the first project, we explore how a robot can indicate to physically co-located human collaborators that it needs help. We utilize a multimodal simultaneous light and sound signal to request help and vary the frequency and intensity of the signal to indicate different levels of urgencies of the request. We evaluate these signals and their effects on a loosely-coupled collaborative task through a user study.

In the second project, which is in progress, we explore how a robot can indicate their awareness of others in the environment while operating in different modes (e.g., autonomous, telepresence). As many robots are able to operate with varying degrees of autonomy, it is important that human collaborators are able to easily determine the robot’s mode and level of awareness in order to decide their own actions as well as other critical aspects of the collaboration, such as their trust in the robot. This is especially challenging since the appearance and form of the robot does not change between modes.

II. HELP REQUESTS

Humans are experts in assessing one another’s availability and effectively utilizing subtle and non-subtle cues, such as gestures and sounds, to communicate the need for assistance [3], [4]. However, most robots lack the ability to generate the same subtle cues as humans. Consequently, robots requesting help are often distracting and obtrusive, lowering efficiency and annoying collaborators [5]. In order to be a

more effective and acceptable collaborator, the robot should attempt to balance both parties needs when requesting help.

Asking for help can be broken down into three phases: 1) get the responder's *attention*, 2) *alert* the responder that help is needed, and 3) put forth the *request* [3], [4], [6]. Since the semantics of the request are often dictated by the scenario, we focus on only the first two phases.

To generate a signal that both captures attention and indicates a need for help, we developed a set of multimodal stimuli that utilize two common communication channels—light and sound—to convey varying levels of urgency. We created these signals by testing different frequencies and intensities of sound and light. We chose to utilize only red light as red is the most commonly employed color when indicating error, help needed, or other issues. By testing these signals independently, we were able to find that a simple binary (on/off) signal of sound or light is able to convey varying levels of urgency. Moreover, we also saw that the higher urgency a signal was, the more attention-grabbing and annoying it was [7]. We then combined the independent signals (of the same frequency and intensity) to create 3 multimodal binary signals of varying levels of urgency, attention-grabbing, and annoyance.

To better understand how human collaborators respond to help requests of differing urgencies, we employed these signals during a collaborative task in a user study. The robot and human are partners in a food service scenario in which the robot drives around collecting meal orders and the human inputs the collected orders into a computer system. The robot periodically asks the participant for help using the designed signals when it has difficulty with the orders.

Our manipulation check and post-study interviews verified the effectiveness and intuitiveness of the signals. We also found that participants utilized the light and sound very differently: sound alerted the user that the robot needed help and the light indicated the level of urgency of the help request. Our results also showed that human collaborators reacted differently to the varying levels of urgencies: when the robot had a high urgency request, the participant would respond immediately and finish helping the robot more quickly. Participants ratings of the interaction and their post-study surveys showed participants not only accepted a more attention-grabbing and annoying signal when the urgency of the request was high, they actually preferred it to be “obtrusive, alarm-like, and difficult to ignore.” On the other hand, when the urgency of the request was lower, participants wanted the robot to be more human-like by taking into account the participant's level of availability, utilizing greetings, and being more polite.

III. OPERATING MODE AND AWARENESS

Most robots can operate in various modes with different degrees of autonomy and supervision [8]. However, it is often important for collaborators, especially those co-located to the robot, to be able to determine which mode the robot is operating in and whether the robot is aware of their presence. Although today's robots take on a variety of forms and functions, this is an issue that encompasses most of robotics, from

autonomous cars to socially assistive agents. Understanding who is in control and whether they are aware of you is critical for a collaborator's trust as most people are inexperienced with robots or autonomous agents. Moreover, having someone constantly monitoring the robot's sensors can cause privacy concerns if the co-located human does not realize that a person may be hearing or seeing them.

Although we have just started exploring this research area, we have already found a lack of prior work focusing on this problem. However, as the number of robots sharing spaces and collaborating with humans continues to increase, it becomes a more critical issue. One such application which has already started to explore the issues of trust and mode is autonomous cars. Driving is a coordinated process and humans have set expectations of how other drivers will behave. Autonomous cars, on the other hand, are new and unfamiliar to most people making expectations and trust of these robots vary greatly. Enabling these robots to easily indicate to other human drivers whether the car is operating as an autonomous agent or being controlled by a human driver, may ease acceptance toward the technology. Moreover, driving is a task that requires each party to communicate in a way that allows each car to coordinate their actions. When operating autonomously, we cannot assume that the robot is aware of others in the environment. Instead, we require the same types of cues humans give off such as gaze or gesture to enable coordination.

In our future work, we plan to explore this issue by identifying important aspects of operating modes and what signals humans use to acknowledge their awareness of one another.

ACKNOWLEDGMENTS

This work is supported by a NASA Science and Technology Research Fellowship (NSTRF) and NSF NRI IIS-1208500.

REFERENCES

- [1] G. Knoblich, S. Butterfill, and N. Sebanz, “Psychological research on joint action: theory and data,” *Psychology of Learning and Motivation-Advances in Research and Theory*, vol. 54, p. 59, 2011.
- [2] B. Mutlu, A. Terrell, and C.-M. Huang, “Coordination mechanisms in human-robot collaboration,” in *Proceedings of the Workshop on Collaborative Manipulation, 8th ACM/IEEE International Conference on Human-Robot Interaction*, 2013.
- [3] H. Hüttenrauch and K. S. Eklundh, “To help or not to help a service robot,” in *Proceedings of the 12th IEEE International Workshop on Robot and Human Interactive Communication ROMAN2003*, 2003.
- [4] P. Saulnier, E. Sharlin, and S. Greenberg, “Exploring minimal nonverbal interruption in hri,” in *RO-MAN, 2011 IEEE*. IEEE, 2011, pp. 79–86.
- [5] G. Hoffman and C. Breazeal, “Cost-based anticipatory action selection for human-robot fluency,” *Robotics, IEEE Transactions on*, vol. 23, no. 5, pp. 952–961, 2007.
- [6] K. Fischer, B. Soto, C. Pantofaru, and L. Takayama, “Initiating interactions in order to get help: Effects of social framing on people's responses to robots' requests for assistance,” in *Robot and Human Interactive Communication, 2014 RO-MAN: The 23rd IEEE International Symposium on*. IEEE, 2014, pp. 999–1005.
- [7] G. R. Arrabito, T. A. Mondor, and K. J. Kent, “Judging the urgency of non-verbal auditory alarms: A case study,” *Ergonomics*, vol. 47, no. 8, pp. 821–840, 2004.
- [8] J. Scholtz, “Theory and evaluation of human robot interactions,” in *System Sciences, 2003. Proceedings of the 36th Annual Hawaii International Conference on*. IEEE, 2003, pp. 10–pp.